

1 进入房间 GET /api/v1/room/member/actor/{actorId}

示例

请求url: GET http://localhost:8080/api/v1/room/member/actor/8

响应: Room

2: 获取房间成员列表: /api/v1/room/member/list/{actorId}/{role}/{state}

role: 取值:

```
public static final int ROLE_ACTOR = 2;  
public static final int ROLE_AGENT = 3;  
public static final int ROLE_AUDIENCE = 4;
```

state: 取值

```
public static final int STATE_NORMAL = 0; //正常  
public static final int STATE_QUIT = 1; //已退出, 客户端不显示  
public static final int STATE_KICK = 2; //黑名单成员  
public static final int STATE_SILENCE=3; //禁言  
public static final int STATE_ASK = 10; //连麦列表  
public static final int STATE_CHECK = 11; //主播已同意列表,
```

示例

请求url: GET http://localhost:8080/api/v1/room/member/list/8/4/0

响应: Collection<RoomMember>

3: 申请连麦

GET /api/v1/room/member/ask/{actorId}

或者 GET /api/v1/room/member/ask/{actorId}/{agoraId}

agoraId: 声网Id

示例

请求url: GET http://localhost:8080/api/v1/room/member/ask/8

请求url: GET http://localhost:8080/api/v1/room/member/ask/8/10

响应: BaseResponse

4 同意连麦: GET /api/v1/room/member/check/{actorId}

actorId: 申请连麦的人

示例

请求url: GET http://localhost:8080/api/v1/room/member/check/9

响应: BaseResponse

5 房主确认后连麦的人进入房间: GET /api/v1/room/member/join/{masterId}

示例

请求url: GET <http://localhost:8080/api/v1/room/member/join/8>

响应: BaseResponse

6 退出连麦, 任然仔房间里

GET /api/v1/room/member/actor/leave/{actorId}/{masterId}

actorId: 连麦的人

masterId: 创建房间的人

目前, 只有掉用改接口的人的ID是actorId或者masterId才能成功

示例

请求url: GET <http://localhost:8080/api/v1/room/member/actor/leave/9/8>

响应: BaseResponse

7禁言 GET /api/v1/room/member/silence/{uid}

uid: 被禁言的人

示例

请求url: GET <http://localhost:8080/api/v1/room/member/silence/9>

响应: BaseResponse

8: 踢出房间 GET /api/v1/room/member/kick/{uid}

uid: 被踢出的人

示例

请求url: GET <http://localhost:8080/api/v1/room/member/kick/9>

9: 退出房间 GET /api/v1/room/member/exit/{actorId}

示例

请求url: GET <http://121.42.181.209/api/v1/room/member/exit/9>

响应: BaseResponse

10: 设为场控: GET /api/v1/room/member/agent/add/{uid}

把uid设为当前房间的场控

示例

请求url: GET <http://localhost:8080/api/v1/room/member/agent/add/9>

响应: BaseResponse

11: 取消场控 GET /api/v1/room/member/agent/add/{uid}

取消uid的场控

示例

请求url: GET <http://localhost:8080/api/v1/room/member/agent/add/9>

响应: BaseResponse

涉及对象

```
public class RoomMember{
    private String id;
    private int uid;
    private int actorId;
    private int state;
    private int roomRole;
    private long enterTime;
    private Long exitTime;
    private int medium; //送礼的金币数量
    private User user; //用户信息
    private Integer agoraId; //声网id
}
```