

Post-quantum transition for device bounded anonymous credentials: a EUDI wallet application

Leonardo Rufini

July 2026

Abstract

In 2026, member states of the European Union are expected to have running their own EUDI wallet applications instances compliant with the ARF architecture guidelines. The goal of the ARF architecture is to provide privacy-preserving anonymous credentials to the users, but the current implementation fails. In the meantime, in 2024 the European Union has published a roadmap for the post quantum digital transition of members digital infrastructures.

No current implementation of anonymous credentials is post quantum secure at the moment, with cryptologist and mathematician in top publications claiming that is not possible to build a post quantum anonymous credential scheme with the actual technologies, given hardware constraints and advanced requirements. So we asked ourselves: is it possible to build a post quantum device bounded anonymous credential scheme with the actual technologies, giving hardware constraints and technical difficulties? The answer is **yes**, it is possible.

Moreover, in this thesis we present a post quantum anonymous credentials model that can be deployed with the actual technologies and legacy infrastructures, with NIST standardized post quantum signature schemes. We went further and implemented the full model and run it into android devices in order to benchmark the performance and the results are surprising. We also present some optimizations that could be implemented in order to further improve the performance of the scheme, and we show how to implement them with the actual technologies.

Contents

1	Introduction	2
1.1	EUDI Wallet	2
1.2	Post quantum transition	2

2	State of the art/Literture overview	3
2.1	Anonymous Credentials	3
2.2	Post quantum anonymous credentials	3
3	Implementation	3
4	Results	3
5	Future work	3
6	Conclusion	3

1 Introduction

Anonymous credentials are a powerful tool for preserving privacy in digital interactions between users and service providers. Anonymous credentials were introduced by David Chaum in 1982 [4], and later formalized by Camenisch and Lysyanskaya in 2001 [1, 2]. They allow users to prove their identity or attributes without revealing any additional information about themselves. In the first approach [5], the issuer was signing user’s credentials using a secure protocol that protects user’s attributes. Credential(s) are then showed to a verifier via zero-knowledge proof of knowledge of a credential(s) whose attributes satisfy some predicate.

Systems based on anonymous credentials have been studied and adopted over the years by big tech companies like Microsoft [6], IBM [3], and are in continuous study and development by the scientific community, facing challenges like performance improvements, revocation lists, legacy infrastructures and hardware, and more recently post quantum security.

1.1 EUDI Wallet

1.2 Post quantum transition

The european union on 11 April 2024 has published a roadmap for the post quantum digital transition of members digital infrastructures.

The roadmap is a comprehensive plan that outlines the steps that the European Union will take to transition to post-quantum cryptography. The roadmap includes a timeline for the transition, as well as a list of actions that will be taken to ensure a smooth transition.

2 State of the art/Literture overview

2.1 Anonymous Credentials

2.2 Post quantum anonymous credentials

3 Implementation

4 Results

5 Future work

6 Conclusion

References

- [1] Jan Camenisch and Anna Lysyanskaya. An efficient system for non-transferable anonymous credentials with optional anonymity revocation. Cryptology ePrint Archive, Paper 2001/019, 2001.
- [2] Jan Camenisch and Anna Lysyanskaya. Signature schemes and anonymous credentials from bilinear maps. In Matt Franklin, editor, *Advances in Cryptology – CRYPTO 2004*, pages 56–72, Berlin, Heidelberg, 2004. Springer Berlin Heidelberg.
- [3] Jan Camenisch and Els Van Herreweghen. Design and implementation of the idemix anonymous credential system. In *Proceedings of the 9th ACM Conference on Computer and Communications Security, CCS '02*, page 21–30, New York, NY, USA, 2002. Association for Computing Machinery.
- [4] David Chaum. Blind signatures for untraceable payments. In David Chaum, Ronald L. Rivest, and Alan T. Sherman, editors, *Advances in Cryptology*, pages 199–203, Boston, MA, 1983. Springer US.
- [5] Anna Lysyanskaya. *Signature schemes and applications to cryptographic protocol design*. PhD thesis, Massachusetts Institute of Technology, 2002.
- [6] Christian Paquin and Greg Zaverucha. U-prove cryptographic specification v1.1 (revision 3), December 2013. Released under the Open Specification Promise (<http://www.microsoft.com/openspecifications/en/us/programs/osp/default.aspx>).