



In Python, a list is a versatile and widely used data structure that allows you to store and manipulate a collection of items. Lists are mutable, meaning you can modify their elements by adding, removing, or updating values. Each element in a list can be of any data type, and a list can contain a mix of different data types.

Here's a basic example of a Python list:

python

Copy code

```
my_list = [1, 2, 3, 'four', 5.0]
```

In this example, `my_list` contains integers, a string, and a floating-point number.

Python provides several built-in functions for working with lists. Some commonly used list functions include:

len(): Returns the number of elements in a list.

python

Copy code

```
length = len(my_list)
```

append(): Adds an element to the end of the list.

python

Copy code

```
my_list.append(6)
```

insert(): Inserts an element at a specified position in the list.

python

Copy code

```
my_list.insert(2, 'inserted')
```

remove(): Removes the first occurrence of a specified value from the list.



python

Copy code

```
my_list.remove('four')
```

pop(): Removes and returns the element at a specified index. If no index is provided, it removes and returns the last element.

python

Copy code

```
popped_element = my_list.pop(3)
```

index(): Returns the index of the first occurrence of a specified value in the list.

python

Copy code

```
index_of_five = my_list.index(5.0)
```

count(): Returns the number of occurrences of a specified value in the list.

python

Copy code

```
number_of_twos = my_list.count(2)
```

sort(): Sorts the elements of the list in ascending order. You can use the **reverse** parameter to sort in descending order.

python

Copy code

```
my_list.sort()
```

reverse(): Reverses the order of the elements in the list.

python

Copy code

```
my_list.reverse()
```



These are just a few examples of the functions you can use with Python lists. Lists and their associated functions provide a flexible way to work with collections of data in Python.

Code:

```
product = ["Sweet", "tag", "soap", "Rin", "Namkeen"]
print(product)

#print(product [0])
numbers = [2, 7, 9, 11, 3]
#print(numbers[2])
numbers = [2, 7, 9, 11, 3]
numbers.sort()
#print(numbers)

numbers.reverse()
#print(numbers)

print(numbers[:5])
print(numbers[1:4])

print(numbers[:1])
print(numbers[:2])
print(numbers[:3])
print(numbers[:-2])

numbers.append(7)
print(numbers)

numbers.insert(2, 67)
print(numbers)

numbers.pop()
print(numbers)

numbers[1] = 98
```



```
print(numbers)

#tp[1] = 8 #this will give an error as its
immutable
tp = (1,)
print(tp)
```

Output:

```
C:\Users\test\PycharmProjects\project_1\.venv\Scripts\python.exe C:\Users\test\PycharmProjects\project_1\Project_1.py
['Sweet', 'tag', 'soap', 'Rin', 'Namkeen']
[11, 9, 7, 3, 2]
[9, 7, 3]
[11, 9, 7, 3, 2]
[11, 7, 2]
[11, 3]
[2, 7, 11]
[11, 9, 7, 3, 2, 7]
[11, 9, 67, 7, 3, 2, 7]
[11, 9, 67, 7, 3, 2]
[11, 98, 67, 7, 3, 2]
(1,)
```



Dictionary:

In Python, a dictionary is a built-in data type that allows you to store and retrieve key-value pairs. It is a flexible and powerful data structure that is commonly used for tasks like indexing, mapping, and organizing data. Here are some basic operations and functions associated with dictionaries in Python:

Creating a Dictionary:

python

Copy code

```
my_dict = {'key1': 'value1', 'key2': 'value2', 'key3': 'value3'}
```

Accessing Values:

python

Copy code

```
value_of_key1 = my_dict['key1']
```

Modifying Values:

python

Copy code

```
my_dict['key2'] = 'new_value'
```

Adding a New Key-Value Pair:


python

Copy code

```
my_dict['key4'] = 'value4'
```

Removing a Key-Value Pair:


python

 Copy code

```
del my_dict['key3']
```

Checking if a Key Exists:

python


 Copy code

```
if 'key2' in my_dict:  
    print('Key2 exists in the dictionary')
```

Dictionary Methods:

1. `keys()`: Returns a view of all keys in the dictionary.


python

 Copy code

```
keys = my_dict.keys()
```

2. `values()`: Returns a view of all values in the dictionary.


python

 Copy code

```
values = my_dict.values()
```

3. `items()`: Returns a view of all key-value pairs as tuples.


python

 Copy code

```
items = my_dict.items()
```

4. `get()`: Returns the value for a given key. If the key is not found, it can return a default value (or `None` if not specified).

python

 Copy code

```
value = my_dict.get('key1', 'default_value')
```

5. `pop()`: Removes and returns the value for a given key. If the key is not found, it can return a default value (or raise a `KeyError` if not specified).

python

Copy code

```
popped_value = my_dict.pop('key1', 'default_value')
```

6. `update()`: Updates the dictionary with key-value pairs from another dictionary or an iterable of key-value pairs.

python

Copy code

```
other_dict = {'key5': 'value5', 'key6': 'value6'}  
my_dict.update(other_dict)
```

These are some of the basic functions and methods associated with dictionaries in Python. Dictionaries are widely used in various applications due to their efficiency in mapping and retrieving data.

Code:

```
d1 = {}  
print(type(d1))  
  
d2 = {"Mohan" : "Burger",  
      "Sam" : "meal",  
      "nimish" : "coca cola",  
      }  
  
d2["Nikhil"] = "Food"  
d2[420] = "Dosa"  
print(d2)  
  
del d2[420]  
  
d3 = d2.copy()  
del d3["Mohan"]  
d2.update({"Ankur": "Toffee"})  
print(d2.keys())  
print(d2.items())
```



```
print(d2.get("Mohan"))
```

Output:

```
C:\Users\test\PycharmProjects\project_1\.venv\Scripts\python.exe C:\Users\test\PycharmProjects\project_1\dict.py
<class 'dict'>
{'Mohan': 'Burger', 'Sam': 'meal', 'nimish': 'coca cola', 'Nikhil': 'Food', 420: 'Dosa'}
dict_keys(['Mohan', 'Sam', 'nimish', 'Nikhil', 'Ankur'])
dict_items([('Mohan', 'Burger'), ('Sam', 'meal'), ('nimish', 'coca cola'), ('Nikhil', 'Food'), ('Ankur', 'Toffee')])
Burger
```