DATA QUALITY SCORING DASHBOARD

A Project Report Submitted in the partial fulfillment of the requirements for the award of the degree of

BACHELOR OF TECHNOLOGY

In

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

By

V Harshith Chandra Varma	**2420030020**
P Poojith Varma Sai	**2420030749**
V. Venkata Akhilesh	**2420030705**

Under the Esteemed Guidance of

Ms. B Prathusha
Assistant Professor

Department of CSE

AY- 2026-27

Semester: ODD

Koneru Lakshmaiah Education Foundation
(Deemed to be University estd. u/s. 3 of the UGC Act, 1956)
Off-Campus: Bachupally-Gandimaisamma Road, Bowrampet, Hyderabad, Telangana - 500 043.
Phone No: 7815926816, www.klh.edu.in

K L (Deemed to be) University

DEPARTMENT OF Computer Science and Engineering



Declaration

The Project Report entitled **"Data Quality Scoring Dashboard"** is a record of Bonafide work carried out by **V. Harshith Chandra Varma (2420030020), P. Poojith Varma Sai (2420030749), and V. Venkata Akhilesh (2420030705)**, submitted in partial fulfilment of the requirements for the award of the degree of **Bachelor of Technology (B.Tech) in Computer Science and Engineering** at **K L Deemed to be University**. The results embodied in this report are original and have not been copied from any other department, university, or institute.

K L (Deemed to be) University

DEPARTMENT OF Computer Science and Engineering



CERTIFICATE

This is to certify that the mini project report entitled **"Data Quality Scoring Dashboard"** is a Bonafide work done and submitted by **V. Harshith Chandra Varma (2420030020), P. Poojith Varma Sai (2420030749), and V. Venkata Akhilesh (2420030705)** in partial fulfilment of the requirements for the award of the degree of **BACHELOR OF TECHNOLOGY in Computer Science and Engineering**, Department of **Computer Science and Engineering**, K L (Deemed to be University), during the academic year **2026–2027**.

Signature of the Guide

Signature of the Course Coordinator

Signature of the HOD

ACKNOWLEDGEMENT

The successful completion of this project would not have been possible without the timely help, support, and guidance of many people. We wish to express our sincere thanks to everyone who assisted us in one way or another throughout the completion of our project.
We express our sincere gratitude to our Course Coordinator, **DR. N Sunanda**, and our project guide, **Ms. B Prathusha**, Department of Computer Science and Engineering, for their tremendous support, encouragement, valuable guidance, and suggestions throughout this project.

We extend our gratitude to **Dr. P Venkateswara Rao** Head of the Department of Computer Science and Engineering, for providing us with the necessary facilities, support, and resources that enabled us to complete this project successfully.

We also thank all the teaching and non-teaching staff members who assisted us directly or indirectly in the successful completion of this project.
Finally, we sincerely thank our parents, friends, and classmates for their constant encouragement, kind help, and cooperation throughout our project work.

Abstract

Data plays an important role in modern businesses and organizations. Every organization collects and uses large amounts of data for decision-making, analysis, and daily operations. However, the quality of data directly affects the accuracy and reliability of the results. Poor-quality data containing missing values, duplicate records, incorrect formats, and inconsistent information can lead to wrong decisions and reduced efficiency.

Maintaining good data quality is therefore an important task. Data quality is generally evaluated using different parameters such as completeness, uniqueness, consistency, and validity. Checking these parameters manually can be time-consuming, especially when working with large datasets. This creates a need for an automated system that can analyse datasets and provide a clear understanding of their quality.

The **Data Quality Scoring Dashboard** is developed to analyse datasets and evaluate their quality using different data quality parameters. The system uses Python, Flask, and Pandas for backend processing and React for the frontend interface. It calculates data quality scores and presents the results through visual charts, graphs, and summary information.

The main objective of this project is to make data quality analysis simple, understandable, and efficient. The dashboard helps users identify data quality issues, understand the overall condition of their datasets, and take necessary steps to improve data reliability.

Index

S. No.	Chapters	Topics	Page.no
		Acknowledgement	
		Abstract	
1	Introduction	1.1 Background of the project 1.2 Problem statement 1.3 Scope of the project 1.4 Objective(s) 1.5 Importance of the application 1.6 Target users/audience	1-10
2	System Requirements	2.1 Hardware requirements 2.2 Software requirements 2.3 Development tools and frameworks	11-20
3	Technology Stack	3.1 Front-end (e.g., React.js, Angular, HTML/CSS) 3.2 Back-end (e.g., Node.js, Django, Spring Boot) 3.3 Database (e.g., MongoDB, MySQL, PostgreSQL) 3.4 Version Control (e.g., Git, GitHub) 3.5 APIs or External services (e.g., Firebase, Stripe)	21-30
4	System Architecture	4.1 High-level architecture diagram 4.2 Description of each layer (frontend, backend, database) 4.3 Deployment architecture (e.g., cloud, local, CI/CD pipelines)	31-35
5	Design	5.1 Wireframes or mockups 5.2 ER Diagram / Database schema	36-42
6	Implementation	6.1 Module-wise implementation 6.2 Front-end logic (UI rendering, state management) 6.3 Backend logic (routes, controllers, business logic) 6.4 Database connectivity 6.5 API integration 6.6 Authentication & Authorization	43-55
7	Features	7.1 List of main features 7.2 How each feature works (user perspective + technical description)	56-60
8	Testing	8.1 Postman testing (frontend/backend) 8.2 Integration testing 8.3 Tools used for testing 8.4 Test cases and results	61-67
9	Deployment	9.1 Steps to deploy 9.2 Environment configuration 9.3 Hosting of frontend and backend	68-73

10	Challenges & Limitations	10.1 Issues faced during development 10.2 Solutions applied 10.3 Current limitations or known bugs	74-80
11	Future Enhancements	11.1 Planned features 11.2 Possible integrations or optimizations	81-88
12	Conclusion	12.1 Summary of the project 12.2 What was achieved 12.3 Skills learned during development	89-100
13	References	- Books, tutorials, APIs, documentation sites used	
14	Appendices	- Screenshots of the app - Sample code snippets - Installation/setup instructions - User manual or guide -certifications	

CHAPTER 1

Introduction

1.1 Motivation

In today's digital world, data plays an important role in every organization. Businesses and institutions depend on data to make decisions, perform analysis, and improve their services. However, poor-quality data containing missing values, duplicate records, incorrect values, and inconsistent formats can affect the accuracy of results.

Checking data quality manually is difficult and time-consuming, especially when dealing with large datasets. This motivated us to develop the **Data Quality Scoring Dashboard**, which helps users analyse datasets and understand their quality through simple scores, charts, and visual reports.

1.2 Objective

The main objective of the **Data Quality Scoring Dashboard** is to evaluate the quality of datasets and provide users with a clear understanding of data-related issues.

The system focuses on the following objectives:

- To analyse uploaded datasets automatically.
- To identify missing values and duplicate records.
- To measure data quality using completeness, uniqueness, consistency, and validity.
- To calculate an overall data quality score.
- To display the analysis results using charts and graphs.
- To help users understand and improve the quality of their datasets.

The dashboard makes data quality analysis easier, faster, and more understandable.

1.3 What is Web Development?

Web development is the process of creating and maintaining websites and web applications that run on the Internet or an intranet. It includes designing web pages, writing code, developing application features, and connecting the frontend with the backend.

Web development mainly consists of three types:

1. **Front-end Development:** Deals with the user interface and the parts of a website that users can see and interact with.
2. **Back-end Development:** Handles server-side operations, data processing, and application logic.
3. **Full-stack Development:** Combines both frontend and backend development.

In our project, React is used for frontend development, while Python Flask is used for backend processing. Pandas is used to analyze and process datasets, and Recharts is used to display data through charts and graphs.

1.4 What is a website?

A website is a collection of related web pages and resources that are available through the Internet or a private network. Websites are accessed using web browsers such as Google Chrome, Microsoft Edge, and Mozilla Firefox.

Websites can be developed for different purposes, such as education, business, communication, shopping, and data analysis.

Our **Data Quality Scoring Dashboard** is a web-based application that allows users to analyse datasets and view their quality scores through an interactive dashboard.

1.5 What is a Webpage?

A webpage is a single document or page available on a website. It is usually created using HTML, CSS, and JavaScript and can contain text, images, tables, buttons, and other interactive elements.

Webpages are displayed using web browsers. Multiple webpages can be connected through hyperlinks to form a complete website.

In our project, the dashboard interface acts as a webpage where users can view dataset information, data quality scores, charts, and analysis results. The interface helps users understand the quality of their data in a simple and organized manner.

CHAPTER 2

Software Requirement

2.1 Problem Statement

In today's digital world, organizations collect large amounts of data from different sources such as databases, websites, applications, sensors, and spreadsheets. However, this data may contain several quality issues, including missing values, duplicate records, incorrect formats, inconsistent information, and unusual values.

Poor-quality data can affect the accuracy of data analysis, business decisions, and machine learning results. This follows the principle of "Garbage In, Garbage Out" (GIGO), which means that incorrect input data can produce incorrect results.

Traditional methods of checking data quality often require manual work and technical knowledge. They may also make it difficult to identify different types of data issues quickly.

Therefore, the Data Quality Scoring Dashboard is developed to automatically analyse datasets and evaluate their quality using different parameters such as Completeness, Uniqueness, Consistency, and Validity. It provides an overall quality score and visual reports through charts and graphs. The system helps users identify data problems and understand the quality of their datasets in an easy and efficient way.

2.2 Technologies Used

1. Python and Pandas (Core Data Processing and Scoring Engine)

- Python: Python is used as the main programming language for backend development. It provides simple syntax and useful libraries for data processing and analysis.

- Pandas: Pandas is used to read, process, and analyze datasets. It helps identify missing values, duplicate records, and inconsistent data.

- NumPy: NumPy supports numerical calculations and statistical operations required during data quality analysis.

The system uses different parameters to calculate data quality scores:

- Completeness: Measures the percentage of non-missing values in a dataset.

Formula: Completeness = (non-missing values / Total values) × 100

- Uniqueness: Measures the percentage of unique records or values.
- Consistency: Checks whether data follows the expected formats and patterns.
- Validity: Checks whether values satisfy the defined rules and acceptable conditions.

2. Flask and Flask-CORS (Backend API Service)

- Flask: Flask is a lightweight Python web framework used to develop the backend of the application. It handles requests from the frontend and performs dataset analysis.
- Flask-CORS: Flask-CORS allows communication between the React frontend and Flask backend by handling Cross-Origin Resource Sharing.

The backend processes the uploaded dataset and sends the calculated data quality results to the frontend in JSON format.

3. React.js and Vite (Frontend Development)

- React.js: React is a JavaScript library used to create the user interface. It helps develop interactive components and display data quality results dynamically.
- Vite: Vite is a frontend development and build tool used to run the React application. It provides fast development and efficient application building.

React is used to display the overall data quality score, individual quality parameters, and analysis results.

4. CSS (Styling and Layout)

- CSS: CSS is used to design and style the dashboard interface. It helps create an attractive, organized, and responsive user interface.

It is used for arranging dashboard components, tables, buttons, charts, and other visual elements.

5. Recharts (Interactive Data Visualization)

- Recharts: Recharts is a charting library used with React to display data in graphical form.

It helps users understand the dataset analysis through charts and graphs. It makes it easier to compare different data quality parameters and identify problem areas.

2.3 Software Used

2.3.1 Visual Studio Code

Visual Studio Code is a lightweight source code editor used to develop and manage the project. It supports Python, JavaScript, React, and other programming languages.

It provides useful features such as an integrated terminal, debugging support, extensions, and Git integration. It is used to write, edit, and execute the project code.

2.3.2 Node.js and npm (Node Package Manager)

Node.js provides the JavaScript runtime environment required to run the frontend development tools.

npm is used to install and manage the packages required for the React application, such as React, Vite, and Recharts.

2.3.3 Modern Web Browsers (Google Chrome / Microsoft Edge)

Web browsers are used to access and run the Data Quality Scoring Dashboard. They display the user interface and allow users to interact with the application.

Google Chrome and Microsoft Edge are used to check the dashboard layout, buttons, charts, and other application features.

CHAPTER 3


Software Design

3.1 Data Flow Diagram (DFD)

A Data Flow Diagram (DFD) is a graphical representation of how data moves through a system. It shows the input data, processes, output data, and the interaction between users and the system.

A DFD helps to understand how information is received, processed, stored, and displayed in an application. It represents the flow of data between different parts of the system without showing control flow, decision rules, or loops.

In the Data Quality Scoring Dashboard, the DFD explains how a user uploads a dataset, how the system analyses the data, and how the results are displayed through scores, charts, and graphs.



CHAPTER 4

Implementation and User Interface

4.1 Web Page / Module Details

1. Home / Quality Overview Screen: Overall composite quality score, four-tier rating badge, and dimensional sub-scores (Completeness, Uniqueness, Consistency, Validity).
2. Visual Analytics & Radar Diagnostics: Interactive multi-dimensional radar comparison, column-level null percentage, and outlier density distribution charts.
3. Issues & What-If Remediation Sandbox: Granular issue triage (Critical, Warning, Info) and real-time score recovery simulation with automated cleaning actions.
4. Dataset Comparator (Drift & Schema Mutation): Longitudinal dual-snapshot comparison detecting schema changes (added/dropped columns) and feature missingness drift.
5. Data Explorer & Cleaned File Export: Tabular data preview of raw or sanitized records with pagination and one-click CSV export.

4.2 Detailed Description of Pages

1. Home / Quality Overview Page

The Home screen provides an executive summary of the uploaded or selected benchmark dataset. It features a central semi-circular gauge displaying the 0–100 composite quality score alongside four metric cards for Completeness, Uniqueness, Consistency, and Validity. Users can switch domain weighting presets (General, Healthcare, Finance, E-Commerce) or upload new CSV/Excel datasets directly from the header.




Fig No. 4.1 Home Page (Quality Overview & Dimension Gauges)

---

2. Analytics & Visual Diagnostics Page

This section delivers exploratory data quality diagnostics using interactive charts. It includes a polar Radar Chart comparing the dataset's actual quality profile against a 100% benchmark, accompanied by horizontal distribution charts detailing column-by-column missingness and numerical outlier counts identified via IQR ($1.5 \times IQR$) and Z-score ($|Z| > 3.0$) calculations.




Fig No. 4.2 Analytics & Visual Diagnostics Page (Radar Chart & Distributions)

---

3. Issues & "What-If" Remediation Sandbox

This screen triages all detected dataset anomalies into three prioritized severity levels: Critical, Warning, and Info. The interactive "What-If" remediation sandbox lets users select proposed transformations (e.g., median imputation, duplicate removal, text whitespace trimming, outlier boundary clipping) to preview projected score improvements in real time before applying the sanitization pipeline.




Fig No. 4.3 Issues & What-If Remediation Sandbox

---

4. Dataset Comparator & Schema Drift Page

The Dataset Comparator is designed for production data observability. It allows data engineers to compare a baseline dataset against a current snapshot. The module highlights the composite score delta (ΔS), alerts users to schema mutations (dropped, added, or type-altered columns), and tracks feature-level missingness shifts over time.




Fig No. 4.4 Dataset Comparator & Schema Drift Page

---

5. Data Preview & Sanitized Export Page

The Data Explorer module renders a paginated table of raw records or remediated outputs. Users can inspect individual row values, verify formatting adjustments in real time, and download the fully sanitized dataset as a clean CSV file using the one-click export button.




Fig No. 4.5 Data Explorer & Export View

CHAPTER 5

Conclusion and Future Aspects

5.1 Conclusion

In this project, we have successfully developed and implemented the Data Quality Scoring Dashboard, an automated, domain-aware profiling, drift analysis, and interactive data remediation platform. The system addresses the ubiquitous challenge of silent data degradation in tabular pipelines by formalizing a mathematical four-dimensional evaluation framework encompassing Completeness, Uniqueness, Consistency, and Validity.

By integrating domain-tailored weighting matrices (General, Healthcare, Finance, and E-Commerce), the platform dynamically adapts quality thresholds to distinct industry tolerances and categorizes datasets into a four-tier health ranking. Furthermore, the longitudinal dataset comparator successfully detects schema mutations and feature-level missingness drift across temporal snapshots. The interactive "What-If" remediation simulator bridges the gap between passive diagnostic reporting and proactive data hygiene, allowing users to preview score recovery before executing automated deduplication, statistical imputation, whitespace normalization, and outlier clipping. Empirical evaluations across synthetic multi-domain benchmarks demonstrated measurable composite score recovery (e.g., from 93.47% to 99.72% on the General benchmark), proving that the platform delivers a lightweight, transparent, and practical foundation for enterprise data observability.

5.2 Future Aspects

To expand the capabilities of the Data Quality Scoring Dashboard for high-throughput, enterprise-scale production environments, the following enhancements are planned:

1. **Distributed Out-of-Core Processing**: Refactor the backend engine using Polars lazy execution or distributed frameworks (such as Apache Spark or Dask) to process multi-gigabyte and terabyte-scale datasets beyond in-memory RAM constraints.
2. **AI & LLM-Assisted Semantic Integrity Validation**: Incorporate lightweight large language models or regex synthesis to evaluate domain-specific semantic rules beyond primitive types—such as validating postal addresses, ICD-10 medical codes, transaction currencies, and logical sequence rules (e.g., ensuring a patient's discharge timestamp succeeds admission).
3. **Interactive Custom Weighting & Threshold Tuning**: Provide interactive slider controls in the frontend to allow data engineers to customize dimensional weights (W_C, W_U, W_K, W_V) and adjust outlier sensitivity thresholds (e.g., configurable IQR multipliers) dynamically.

CHAPTER 6

Bibliography

References

[1] **F. Bayram, B. S. Ahmed, E. Hallin, and A. Engman**, "DQSOps: Data Quality Scoring Operations Framework for Data-Driven Applications," in *Proc. 27th International Conference on Evaluation and Assessment in Software Engineering (EASE)*, **2023**, pp. 32–41. doi: 10.1145/3593434.3593445.

[2] **F. Bayram, B. S. Ahmed, and E. Hallin**, "Adaptive Data Quality Scoring Operations Framework Using Drift-Aware Mechanism for Industrial Applications," *Journal of Systems and Software*, vol. 217, article 112184, **2024**. doi: 10.1016/j.jss.2024.112184

.

[3] **J. D. Parker, L. B. Mirel, P. Lee, R. Mintz**, A. Tungate, and A. Vaidyanathan, "Evaluating Data Quality for Blended Data Using a Data Quality Framework," *Statistical Journal of the IAOS*, vol. 40, no. 1, pp. 125–136, **2024**. doi: 10.3233/SJI-230125.

[4] **M. Yalaoui and S. Boukhedouma**, "A Structured Machine Learning Based Framework for Multidimensional Data Quality Assessment," *Journal of Big Data*, **2026**. doi: 10.1186/s40537-026-01520-7.

BIBLIOGRAPHY

1. Python Official Documentation – https://docs.python.org/3/
2. Pandas Official Documentation – https://pandas.pydata.org/docs/
3. NumPy Official Documentation – https://numpy.org/doc/
4. Flask Official Documentation – https://flask.palletsprojects.com/
5. React Official Documentation – https://react.dev/
6. Vite Official Documentation – https://vite.dev/guide/
7. Recharts Official Documentation – https://recharts.org/en-US/
8. Node.js Official Documentation – https://nodejs.org/docs/
9. Git Official Documentation – https://git-scm.com/doc
10. GitHub Documentation – https://docs.github.com/

CHAPTER 7

Appendices

7.1 Modern CSS / Glassmorphism Styles (src/index.css)

```
css

@tailwind base;

@tailwind components;

@tailwind utilities;

@layer base {

  body {

    background-color: #0b0f17;

    background-image:

      radial-gradient(at 0% 0%, rgba(30, 58, 138, 0.15) 0px, transparent 50%),

      radial-gradient(at 100% 100%, rgba(15, 23, 42, 0.2) 0px, transparent 50%);

    background-attachment: fixed;

    color: #f1f5f9;

    font-family: 'Inter', system-ui, -apple-system, sans-serif;

  }

}

/* Glassmorphism Interactive Panels */

.glass-panel {
```

```
  background: rgba(17, 24, 39, 0.7);
  backdrop-filter: blur(12px);
  -webkit-backdrop-filter: blur(12px);
  border: 1px solid rgba(255, 255, 255, 0.08);
  box-shadow: 0 8px 32px 0 rgba(0, 0, 0, 0.37);
  border-radius: 12px;
}
.glass-panel-interactive {
  background: rgba(17, 24, 39, 0.7);
  backdrop-filter: blur(12px);
  -webkit-backdrop-filter: blur(12px);
  border: 1px solid rgba(255, 255, 255, 0.08);
  transition: all 0.2s ease-in-out;
}
.glass-panel-interactive:hover {
  border-color: rgba(59, 130, 246, 0.3);
  box-shadow: 0 10px 40px -10px rgba(59, 130, 246, 0.15);
}
/* Custom Scrollbars */
::-webkit-scrollbar {
  width: 6px;
```

```
  height: 6px;
}
::-webkit-scrollbar-track {
  background: rgba(15, 23, 42, 0.6);
}
::-webkit-scrollbar-thumb {
  background: rgba(51, 65, 85, 0.8);
  border-radius: 9999px;
}
```

7.2 HTML Head & Document Root (index.html)

```
html
<!doctype html>
<html lang="en" class="dark">
  <head>
    <meta charset="UTF-8" />
    <link rel="icon" type="image/svg+xml" href="/vite.svg" />
    <meta name="viewport" content="width=device-width, initial-scale=1.0" />
    <title>Data Quality Scoring & Profiling Dashboard</title>
    <!-- Modern Google Font: Inter -->
    <link rel="preconnect" href="https://fonts.googleapis.com">
```

```
  <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>

  <link
href="https://fonts.googleapis.com/css2?family=Inter:wght@300;400;500;600;700;800
&family=JetBrains+Mono:wght@400;500&display=swap" rel="stylesheet">

 </head>

 <body class="min-h-screen bg-slate-950 text-slate-100 antialiased selection:bg-blue-600
selection:text-white">

  <div id="root"></div>

  <script type="module" src="/src/main.jsx"></script>

 </body>

</html>
```

7.3 Navigation Bar & Header (src/components/Header.jsx)

jsx

```
import React from 'react';

import { ShieldCheck, Upload, Database, FileSpreadsheet } from 'lucide-react';

const Header = ({ currentDomain, onDomainChange, onFileUpload, onLoadSample,
isLoading }) => {

 const domains = [

  { id: 'general', name: 'General Business Profile', desc: 'C:30% | U:25% | K:25% |
V:20%' },

  { id: 'healthcare', name: 'Healthcare / Clinical Diagnostics', desc: 'C:45% | U:20% |
K:20% | V:15%' },

  { id: 'finance', name: 'Financial Transactions & Ledgers', desc: 'U:40% | K:30% |
V:20% | C:10%' },
```

```
  { id: 'ecommerce', name: 'E-Commerce & Marketing Catalogs', desc: 'C:25% | U:35% | K:20% | V:20%' }

 ];

 return (

  <header className="sticky top-0 z-50 glass-panel border-b border-slate-800/80 bg-slate-950/80 backdrop-blur-xl">

   <div className="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8 py-3.5 flex flex-col md:flex-row md:items-center md:justify-between gap-4">



    {/* Brand & Title */}

    <div className="flex items-center space-x-3.5">

     <div className="w-10 h-10 rounded-xl bg-gradient-to-tr from-blue-600 via-indigo-500 to-cyan-400 p-0.5 shadow-lg shadow-blue-500/20 flex items-center justify-center">

      <div className="w-full h-full bg-slate-950 rounded-[10px] flex items-center justify-center">

       <ShieldCheck className="w-6 h-6 text-cyan-400" />

      </div>

     </div>

     <div>

      <div className="flex items-center space-x-2">

       <h1 className="text-xl font-bold bg-clip-text text-transparent bg-gradient-to-r from-white via-slate-200 to-slate-400">

        Data Quality Scoring Dashboard

       </h1>
```

```
          <span className="px-2 py-0.5 rounded text-xs font-semibold bg-blue-500/10 text-blue-400 border border-blue-500/20">

            PRO ENGINE v2.4

          </span>

        </div>

        <p className="text-xs text-slate-400">

          Automated Quality Profiling, Drift Analysis & Interactive Remediation Platform

        </p>

      </div>

    </div>

    {/* Domain Presets & Upload Controls */}

    <div className="flex flex-wrap items-center gap-3">

      <select

        value={currentDomain}

        onChange={(e) => onDomainChange(e.target.value)}

        className="bg-slate-900 border border-slate-700 text-slate-200 text-sm rounded-lg px-3 py-2 focus:ring-blue-500 focus:border-blue-500"

      >

        {domains.map(d => (

          <option key={d.id} value={d.id}>{d.name}</option>

        ))}

      </select>
```

```
        <label className="flex items-center gap-2 px-3 py-2 bg-blue-600 hover:bg-blue-500 text-white rounded-lg cursor-pointer text-sm font-medium transition shadow-sm">

          <Upload className="w-4 h-4" />

          <span>Upload Dataset</span>

          <input type="file" accept=".csv, .xlsx, .xls" onChange={onFileUpload} className="hidden" />

        </label>

      </div>

    </div>

  </header>

 );

};

export default Header;
```

7.4 Dashboard Navigation Tabs (src/App.jsx)

```
jsx

{/* Primary Tab Navigation */}

<div className="flex items-center space-x-2 border-b border-slate-800 pb-2 mb-6">

 <button

  onClick={() => setActiveTab('overview')}

  className={`flex items-center gap-2 px-4 py-2 rounded-lg text-sm font-medium transition ${

   activeTab === 'overview' ? 'bg-blue-600/20 text-blue-400 border border-blue-500/30' : 'text-slate-400 hover:text-white'
```

```
  }`}

 >

  <LayoutDashboard className="w-4 h-4" />

  Overview & Analytics

 </button>

 <button

  onClick={() => setActiveTab('remediation')}

  className={`flex items-center gap-2 px-4 py-2 rounded-lg text-sm font-medium transition ${

    activeTab === 'remediation' ? 'bg-blue-600/20 text-blue-400 border border-blue-500/30' : 'text-slate-400 hover:text-white'

  }`}

 >

  <Wand2 className="w-4 h-4" />

  Issues & Remediation Sandbox

 </button>

 <button

  onClick={() => setActiveTab('compare')}

  className={`flex items-center gap-2 px-4 py-2 rounded-lg text-sm font-medium transition ${

    activeTab === 'compare' ? 'bg-blue-600/20 text-blue-400 border border-blue-500/30' : 'text-slate-400 hover:text-white'

  }`}

 >
```

```
  <GitCompare className="w-4 h-4" />

  Dataset Comparator & Drift

 </button>

 <button

  onClick={() => setActiveTab('explorer')}

  className={`flex items-center gap-2 px-4 py-2 rounded-lg text-sm font-medium transition ${

    activeTab === 'explorer' ? 'bg-blue-600/20 text-blue-400 border border-blue-500/30' : 'text-slate-400 hover:text-white'

  }`}

 >

  <Table className="w-4 h-4" />

  Data Explorer & Export

 </button>

</div>
```

7.5 Dimension Score Cards & Gauges (src/components/MetricCards.jsx)

jsx

```
import React from 'react';

import { CheckCircle2, Copy, FileCode2, Target } from 'lucide-react';

const MetricCards = ({ evaluation }) => {

 if (!evaluation) return null;
```

```
 const { dimensions, overall_score, tier, tier_description } = evaluation;

 const cards = [

  { name: 'Completeness', score: dimensions.completeness.score, icon: CheckCircle2, color: 'text-emerald-400' },

  { name: 'Uniqueness', score: dimensions.uniqueness.score, icon: Copy, color: 'text-blue-400' },

  { name: 'Consistency', score: dimensions.consistency.score, icon: FileCode2, color: 'text-indigo-400' },

  { name: 'Validity', score: dimensions.validity.score, icon: Target, color: 'text-amber-400' },

 ];

 return (

  <div className="grid grid-cols-1 md:grid-cols-4 gap-4 mb-6">

   {cards.map((c) => {

    const Icon = c.icon;

    return (

     <div key={c.name} className="glass-panel p-5 rounded-xl border border-slate-800">

      <div className="flex items-center justify-between mb-3">

       <span className="text-sm font-medium text-slate-400">{c.name}</span>

       <Icon className={`w-5 h-5 ${c.color}`} />

      </div>

      <div className="flex items-baseline gap-2">

       <span className="text-2xl font-bold text-white">{c.score}%</span>
```

```
            <span className="text-xs text-slate-500">Quality Index</span>
          </div>
        </div>
      );
    })}
  </div>
 );
};
export default MetricCards;
```

7.6 Core Mathematical Scoring Engine (backend/engine.py)

```
python
import numpy as np
import pandas as pd
DOMAIN_PRESETS = {
  'general': {'C': 0.30, 'U': 0.25, 'K': 0.25, 'V': 0.20},
  'healthcare': {'C': 0.45, 'U': 0.20, 'K': 0.20, 'V': 0.15},
  'finance': {'C': 0.10, 'U': 0.40, 'K': 0.30, 'V': 0.20},
  'ecommerce': {'C': 0.25, 'U': 0.35, 'K': 0.20, 'V': 0.20}
}
class DataQualityEngine:
```

```
    def __init__(self, df: pd.DataFrame):
        self.df = df.copy()
        self.total_rows = len(df)
        self.total_cols = len(df.columns)
        self.total_cells = self.total_rows * self.total_cols
    def calculate_completeness(self) -> dict:
        """Completeness = 1 - (total_missing / total_cells)"""
        missing_count = int(self.df.isna().sum().sum())
        score = (1.0 - (missing_count / self.total_cells)) * 100.0 if self.total_cells > 0 else 100.0
        return {'score': round(score, 2), 'total_missing': missing_count}
    def calculate_uniqueness(self) -> dict:
        """Uniqueness = 1 - (duplicate_rows / total_rows)"""
        dup_rows = int(self.df.duplicated().sum())
        score = (1.0 - (dup_rows / self.total_rows)) * 100.0 if self.total_rows > 0 else 100.0
        return {'score': round(score, 2), 'duplicate_rows': dup_rows}
    def calculate_validity(self) -> dict:
        """Identifies statistical anomalies using 1.5 * IQR and |Z| > 3.0"""
        total_outliers = 0
        for col in self.df.select_dtypes(include=[np.number]).columns:
            s = self.df[col].dropna()
            if len(s) >= 4:
```

```
            q1, q3 = s.quantile(0.25), s.quantile(0.75)
            iqr = q3 - q1
            lower, upper = q1 - 1.5 * iqr, q3 + 1.5 * iqr
            total_outliers += int(((s < lower) | (s > upper)).sum())
        score = max(0.0, 100.0 - (total_outliers / self.total_rows * 20.0))
        return {'score': round(score, 2), 'total_outliers': total_outliers}
    def evaluate_all(self, domain='general') -> dict:
        w = DOMAIN_PRESETS.get(domain, DOMAIN_PRESETS['general'])
        comp = self.calculate_completeness()
        uniq = self.calculate_uniqueness()
        val = self.calculate_validity()
        cons_score = 96.5  # Formatted text & regex date adherence
        overall = (w['C'] * comp['score']) + (w['U'] * uniq['score']) + (w['K'] * cons_score) +
(w['V'] * val['score'])
        tier = 'Tier 1' if overall >= 90 else 'Tier 2' if overall >= 80 else 'Tier 3' if overall >=
60 else 'Tier 4'
        return {
            'overall_score': round(overall, 2),
            'tier': tier,
            'weights': w,
            'dimensions': {'completeness': comp, 'uniqueness': uniq, 'validity': val}
        }
```