

6.765-6.795M	Inductive loop system	42 dB μ A/m @ 10 m. No restrictions on duty cycle No channel spacing.	EN 300 330 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03
13.553-13.567M	Inductive loop system, including RFID	42 dB μ A/m @ 10 m. No restrictions on duty cycle No channel spacing.	EN 300 330 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03 ASK, FSK, & PSK
13.553-13.567M	RFID and EAS systems only	60 dB μ A/m @ 10 m.	EN 300 330 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03
26.957-27.283M	Inductive loop system	42 dB μ A/m @ 10 m. No restrictions on duty cycle No channel spacing.	EN 300 330 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03
26.957-27.283M	Non-specific SRDs	10 mW ERP No restrictions on duty cycle. No channel spacing.	EN 300 220 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03
26.995; 27.045; 27.095; 27,145; 27.195M	Surface model control	100 mW ERP No restrictions on duty cycle. 10 kHz channel spacing.	EN 300 220 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03
35.00 – 35.25M	Aircraft model control	100 mW ERP No restrictions on duty cycle. 10 kHz channel spacing.	EN 300 220 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03
36.65 – 36.75M	Wireless microphones	100 mW ERP 100% duty cycle No channel spacing.	EN 300 422 EN 301 489-9 EN 60950	CEPT/ERC/REC 70-03
40.65 – 40.70M	Wireless microphones	100 mW ERP 100% duty cycle No channel spacing.	EN 300 422 EN 301 489-9 EN 60950	CEPT/ERC/REC 70-03