

40.665M 40.675M 40.685M 40.695M	Surface model control	100mW ERP No restriction on duty cycle. 10 kHz channel spacing.	EN 300 220 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03
40.66 – 40.7M	Non-specific SRDs	10 mW ERP No duty cycle restriction. No channel spacing.	EN 300 220 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03
46.61 – 46.97M 49.67 – 49.97M	CT0 cordless phones.	10 mW e.i.r.p.	The Authority TE-013	Government Gazette 22443 of 4 July 2001
53 – 54M	Wireless microphones	50 mW ERP for class 1 equipment 100 mW ERP 100% duty cycle No channel spacing	EN 300 422 EN 301 489-1,9 EN 60950	CEPT/ERC/REC 70-03
54.4500; 54.4625; 54.4750; 54.4875; 54.500; 54.5125; 54.5250; 54.5375; 54.5500M	Model control	5W ERP 12.5 kHz channel spacing	EN 300 220 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03
141 – 142M	Remote control industrial apparatus	100 mW ERP	EN 300 220 EN 301 489-1,3 EN 60950	
148 – 152M	Wildlife telemetry tracking	25 mW ERP	EN 300 220 EN 301 489-1,3 EN 60950	The use of this band is restricted to national game parks.
169.4 – 169.475M	Meter reading	500 mW ERP 50 kHz channel spacing < 10% duty cycle	EN 300 220 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03 ECC/DEC (05)02
173.2125 – 173.2375M	Non-specific SRDs –	10 mW ERP	EN 300 220	