

	telecommand only	25 kHz channel spacing	EN 301 489-1,3 EN 60950	
173.2375 – 173.2875M	Non-specific SRDs	10 mW ERP 25 kHz channel spacing.	EN 300 220 EN 301 489-1,3 EN 60950	
173.965 – 174.015M	Wireless microphones and assistive listening devices	2 mW e.i.r.p. 100% duty cycle. No channel spacing.	EN 300 220 EN 301 489-9 EN 60950	CEPT/ERC/REC 70-03
401 – 406M	Medical implants	25 μ W ERP No duty cycle restriction for devices with LBT $\leq 1\%$ duty cycle for all other devices 25 kHz channel spacing.	EN 300 839 EN 301 489-1,3 EN 60950	ITU-R RS.1346 CEPT/ERC/DEC (01)17
402 – 406M	Doppler shift movement detectors, wireless microphones, garage door openers and motor car alarm systems	10 mW ERP No channel spacing. 100% duty cycle.	EN 300 422 EN 300 220 EN 301 489-1,3 EN 60950	
433.04 – 434.79M	Non-specific SRDs, including RFID	1 mW ERP No channel spacing. 100% duty cycle	EN 300 220 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03 ASK, FSK, PSK, & FHSS
433.04 – 434.79M	Non-specific SRDs, including RFID	10 mW ERP duty cycle < 10% No channel spacing	EN 300 220 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03 ASK, FSK, PSK, & FHSS
433.04 – 434.79M	Non-specific SRDs	10 mW ERP 100% duty cycle Up to 25 kHz channel spacing.	EN 300 220 EN 301 489-3 EN 60950	CEPT/ERC/REC 70-03