

433.04 – 434.79M	Non-specific SRDs	100 mW ERP No duty cycle restriction No channel spacing	EN 300 220 EN 301 489-3 EN 60950	CEPT/ERC/REC 70-03
446 - 446.1 M Includes the following eight channels. 446.00625M; 446.01875M; 446.03125M; 446.04375M; 446.05625M; 446.06875M; 446.08125M; 446.09375M;	Public mobile radio (PMR)	500 mW 12,5 kHz channel spacing	EN 300 296 EN 301 489-5 EN 60950	
464.5375M	Security systems	1 W 25 kHz channel spacing.	EN 300 296 EN 301 489-5 EN 60950	
464.500 – 464.5875	Non-specific SRDs	100 mW No channel spacing	EN 300 220 EN 301 489-3 EN 60950	
463.975M; 464.125M; 464.175M; 464.325M; 464.375M;	Low power radio	500 mW. 12.5 kHz channel spacing	EN 300 296 EN 301 489-5 EN 60950	
863 – 865M	Wireless audio systems	10 mW ERP 100 % duty cycle. No channel spacing.	EN 300 357 EN 301 489-9 EN 60950	CEPT/ERC/REC 70-03 CEPT/ERC/DEC (01)18
863 – 865M	Wireless microphones	10 mW ERP 100 % duty cycle. No channel spacing.	EN 300 422 EN 301 489-9 EN 60950	CEPT/ERC/REC 70-03