

865 -868 M	RFID	Channels 1, 2 and 3 100 mW ERP 200 kHz channel spacing	EN 302 208-2 EN 301 489-1,3 EN60950 ISO/IEC 18047-6	CEPT/ERC/REC 70-03 Listen Before Talk (LBT) is mandatory FHSS or other spread spectrum techniques shall not be used
865 – 868 M	RFID	Channels 4,7,10 and 13 2 W ERP 200 kHz channel spacing	EN 302 208-2 EN 301 489-1,3 EN60950 ISO/IEC 18047-6	CEPT/ERC/REC 70-03 Listen Before Talk (LBT) is mandatory FHSS or other spread spectrum techniques shall not be used
865 – 868 M	RFID	Channels 5,6,8,9,11,12,14 and 15 500 mW ERP 200 kHz channel spacing	EN 302 208-2 EN 301 489-1,3 EN60950 ISO/IEC 18047-6	CEPT/ERC/REC 70-03 Listen Before Talk (LBT) is mandatory FHSS or other spread spectrum techniques shall not be used
864.1 – 868.1M	CT2 cordless phones	10 mW e.i.r.p.	EN 301 797 EN 301 489-1,10 The Authority TE - 012	CEPT/ERC/REC 70-03
868 – 868.6M	Non-specific SRDs	25 mW ERP < 1% duty cycle or LBT.	EN 300 220 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03 CEPT/ERC/DEC (01) 04