

868.6 – 868.7M	Alarms	10 mW ERP < 1 % duty cycle. 25 kHz channel spacing.	EN 300 220 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03 CEPT/ERC/REC (01) 09
868.7 – 869.2M	Non-specific SRDs	25 mW ERP < 0.1 % duty cycle or LBT. No channel spacing.	EN 300 220 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03 CEPT/ERC/REC (01) 04
869.25 – 869.3M	Alarms	10 mW ERP < 0.1 % duty cycle. 25 kHz channel spacing.	EN 300 220 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03
869.4 – 869.65M	Non-specific SRDs, including RFID	500 mW ERP < 10% duty cycle or LBT. 25 kHz channel spacing.	EN 300 220 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03
869.65 – 869.7M	Alarms	25 mW ERP 10 % duty cycle. 25 kHz channel spacing.	EN 300 220 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03
869.7 – 870 M	Non-specific SRDs	5 mW ERP 100% duty cycle. No channel spacing.	EN 300 220 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03
915.1 -915.2 M	Real time location systems (RTLS)	25 mW ERP	EN 300 086 EN 301 489-1,3 EN 60950	
915.2 – 915.4 M	Passive tags	100 mW ERP 10 x 20 kHz wide channels		