

915.4-919 M	Modulating RFID systems (FHSS)	4 W e.i.r.p.	FCC CFR 47 Part 15.247 CISPR 16 EN 60950	200 kHz channel spacing
919 -919.2 M	Tag backscatter systems Guard band			
919.2 – 921 M	Non- modulating backscatter RFID systems	4 W e.i.r.p.; CW only @ 920 MHz ($\pm$ 1.5 kHz frequency stability)	Spectral masks as in EN 302 208 – 2 EN 301 489 -1,3 EN 60950	
1880 – 1900M	DECT cordless phones	250 mW e.i.r.p. (peak). 1.728 MHz channel spacing.	EN 300 406 EN 301 489-1,6 EN 60950 The Authority TE 001	
2400 – 2483.5M	Non-specific SRDs	10 mW e.i.r.p. No duty cycle. No channel spacing.	EN 300 440 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03
2400 - 2483.5M	Wideband wireless systems WLAN Wideband data transmission applications (WBDTS) Model control	100 mW e.i.r.p. No duty cycle. No channel spacing. For wide band modulations other than FHSS, the maximum e.i.r.p. density is limited to 10 mW/MHz. Adequate spectrum sharing mechanisms shall be implemented by the equipment (e.g. Listen-before- Talk, Detect-and- Avoid)	EN 300 328 EN 301 489 -1,3 EN 60950	CEPT/ERC/REC 70-03 For wide band modulations other than FHSS, the maximum e.i.r.p. density is limited to 10 mW/MHz