

|                |                                                                                      |                                                                                                                                                                                                                                                                   |                                                    |                                                                                                                                                                                                                                                                                                                                 |
|----------------|--------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2400 – 2483.5M | FDDA                                                                                 | 25 mW e.i.r.p.<br><br>No duty cycle.<br><br>No channel spacing.                                                                                                                                                                                                   | EN 300 440<br><br>EN 301 489-1,3<br><br>EN 60950   | CEPT/ERC/REC 70-03                                                                                                                                                                                                                                                                                                              |
| 2400 – 2483.5M | Low power video surveillance                                                         | 100 mW e.i.r.p.<br><br>No duty cycle.<br><br>No channel spacing.                                                                                                                                                                                                  | EN 300 440<br><br>EN 301 489-1,3<br><br>EN 60950   | CEPT/ERC/REC 70-03                                                                                                                                                                                                                                                                                                              |
| 2446-2454 MHz  | RFID                                                                                 | 500 mW e.i.r.p.<br><br>No duty cycle<br><br>4 W e.i.r.p. < 15% duty cycle<br><br>FHSS should be used                                                                                                                                                              | EN 300 440<br><br>EN 301 489 – 1,3<br><br>EN 60950 | CEPT/ERC/REC 70-03                                                                                                                                                                                                                                                                                                              |
| 5150 – 5350M   | Wireless access systems & radio local access networks (WAS & RLAN) – indoor use only | 200 mW e.i.r.p.<br><br>Dynamic frequency selection (DFS) & transmitter power control (TPC) obligatory.                                                                                                                                                            | EN 301 893<br><br>EN 301 489-1,17<br><br>EN 60950  | ITU-R M.1625                                                                                                                                                                                                                                                                                                                    |
| 5470 – 5725M   | Wireless access systems & radio local access networks (WAS & RLAN)                   | 1 W e.i.r.p.                                                                                                                                                                                                                                                      | EN 301 893<br><br>EN 301 489-1,17<br><br>EN 60950  | ITU-R M.1625                                                                                                                                                                                                                                                                                                                    |
| 5725 - 5875 M  | Wireless access systems and radio local access networks (WAS & RLAN)                 | <ul style="list-style-type: none"> <li>• A maximum of 4 watts e.i.r.p.</li> <li>• A maximum of 1 watt transmitter output power</li> <li>• A maximum transmitter output spectral density of 8 dBmW in any 3 kHz band</li> <li>• Digital modulation only</li> </ul> | FCC 15.247<br><br>FCC 15.249                       | <ul style="list-style-type: none"> <li>• Fixed point-to-multipoint systems and point-to-point links.<br/>In any 100 kHz outside the band, the e.i.r.p. shall be at least 30 dB below the 100 kHz within the band that contains the highest level of desired power.</li> </ul> <p><i>Note 1</i><br/>Transmission towards the</p> |