

		Nominal bandwidth of transmissions must not be less than 1 MHz		common node of a point-to-multipoint is regarded as point-to-point node
5725 – 5875 M	BFWA	- A maximum of 200 watts e.i.r.p. - A maximum of 1 watt transmitter output power - A maximum transmitter output spectral density of 8 dBmW in any 3 kHz band - Digital modulation only - Nominal bandwidth of transmissions must not be less than 1 MHz	FCC 15.247 FCC 15.249	- Fixed point-to-point links only - Point-to-multipoint systems, omnidirectional applications, and multiple co-located transmitters transmitting the same information are not permitted. (see note 1) - In any 100 kHz outside the band, the e.i.r.p. shall be at least 30 dB below the 100 kHz within the band that contains the highest level of desired power. <i>Note 1: Transmission towards the common node of a point-to-multipoint system is regarded as point-to-point mode.</i>
5795 – 5805M	RTTT data	2 W e.i.r.p. No duty cycle restriction. No channel spacing.	EN 300 674 EN 301 489-1,3 EN 60950	ITU-R M.1453 CEPT/ERC/DEC (92)02
5805 – 5815M	RTTT data	2 W e.i.r.p. No duty cycle restriction. No channel spacing.	EN 300 674 EN 301 489-1,3 EN 60950	ITU-R M.1453 CEPT/ERC/DEC (92)02 CEPT/ERC/REC 70-03
9200 – 9500M	FDDA	25 mW e.i.r.p. No duty cycle restriction. No channel spacing.	EN 300 440 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03