

9500 – 9975M	FDDA	25 mW e.i.r.p. No duty cycle restriction. No channel spacing.	EN 300 440 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03
10.025 – 10.145 G	Low power video surveillance	1W e.i.r.p. 8 MHz channel spacing, with first channel on 10.029 GHz.	ETS 300 440	
10.5 – 10.6G	FDDA	500 mW e.i.r.p. No duty cycle restriction. No channel spacing.	EN 300 440 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03
13.4 – 14G	FDDA	25 mW e.i.r.p. No duty cycle restriction. No channel spacing.	EN 300 440 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03
17.1 – 17.3G	HiperLAN	100 mW e.i.r.p.	EN 301 489-1,3 EN 60950	
24.00 – 24.25G	Non-specific SRDs	100 mW e.i.r.p. No duty cycle restriction. No channel spacing.	EN 300 440 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03
24.05 – 24.25G	FDDA	100 mW e.i.r.p. No duty cycle restriction. No channel spacing.	EN 300 440 EN 301 489-1,3 EN 60950	CEPT/ERC/REC 70-03
57 – 64G	Point-to-point links	55 dBm e.i.r.p.	EN 305 550	The maximum transmitter output power is 10 dBm. The minimum antenna gain is 30 dBi