MCH3474

Power MOSFET
30V, 50mΩ, 4A, Single N-Channel

ON Semiconductor®

www.onsemi.com

This Power MOSFET is produced using ON Semiconductor's trench technology, which is specifically designed to minimize gate charge and low on resistance. This device is suitable for applications with low gate charge driving or low on resistance requirements.

Features

- Low On-Resistance
- High Speed Switching
- 1.8V drive
- ESD Diode-Protected Gate
- Pb-Free, Halogen Free and RoHS compliance

Typical Applications

- DC/DC Converter

V_{DSS}	R_{DS}(on) Max	I_D Max
30V	50mΩ@ 4.5V	4A
	72mΩ@ 2.5V	
	130mΩ@ 1.8V	

ELECTRICAL CONNECTION
N-Channel



PACKING TYPE : TL



MARKING



ORDERING INFORMATION
See detailed ordering and shipping information on page 5 of this data sheet.

SPECIFICATIONS

ABSOLUTE MAXIMUM RATING at Ta = 25°C (Note 1)

Parameter	Symbol	Value	Unit
Drain to Source Voltage	V_{DSS}	30	V
Gate to Source Voltage	V_{GSS}	±12	V
Drain Current (DC)	I_D	4	A
Drain Current (Pulse) PW ≤ 10μs, duty cycle ≤ 1%	I_{DP}	16	A
Power Dissipation When mounted on ceramic substrate (900mm^2 × 0.8mm)	P_D	1	W
Junction Temperature	Tj	150	°C
Storage Temperature	Tstg	−55 to +150	°C

Note 1 : Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Value	Unit
Junction to Ambient When mounted on ceramic substrate (900mm^2 × 0.8mm)	$R_{\theta JA}$	125	°C/W

ELECTRICAL CHARACTERISTICS at Ta = 25°C (Note 2)

Parameter	Symbol	Conditions	Value			Unit
			min	typ	max	
Drain to Source Breakdown Voltage	$V_{(BR)DSS}$	I_D=1mA, V_{GS}=0V	30			V
Zero-Gate Voltage Drain Current	I_{DSS}	V_{DS}=30V, V_{GS}=0V			1	μA
Gate to Source Leakage Current	I_{GSS}	V_{GS}=±8V, V_{DS}=0V			±10	μA
Gate Threshold Voltage	$V_{GS}(th)$	V_{DS}=10V, I_D=1mA	0.4		1.3	V
Forward Transconductance	g_{FS}	V_{DS}=10V, I_D=2A	2.0	3.4		S
Static Drain to Source On-State Resistance	$R_{DS}(on)1$	I_D=2A, V_{GS}=4.5V		38	50	mΩ
	$R_{DS}(on)2$	I_D=1A, V_{GS}=2.5V		51	72	mΩ
	$R_{DS}(on)3$	I_D=0.5A, V_{GS}=1.8V		80	130	mΩ
Input Capacitance	Ciss	V_{DS}=10V, f=1MHz		430		pF
Output Capacitance	Coss			59		pF
Reverse Transfer Capacitance	Crss			38		pF
Turn-ON Delay Time	$t_d(on)$	See specified Test Circuit		10		ns
Rise Time	t_r			41		ns
Turn-OFF Delay Time	$t_d(off)$			36		ns
Fall Time	t_f			37		ns
Total Gate Charge	Qg	V_{DS}=15V, V_{GS}=4.5V, I_D=4A		4.7		nC
Gate to Source Charge	Qgs			0.8		nC
Gate to Drain “Miller” Charge	Qgd			1.1		nC
Forward Diode Voltage	V_{SD}	I_S=4A, V_{GS}=0V		0.82	1.2	V

Note 2 : Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

Switching Time Test Circuit




ID – VDS
Ta=25°C
7.0V
4.5V
3.5V
2.5V
1.8V
1.5V
VGS=1.2V
Drain Current, ID – A
Drain to Source Voltage, VDS – V
IT14344


ID – VGS
VDS=10V
Ta=75°C
25°C
–25°C
Drain Current, ID – A
Gate to Source Voltage, VGS – V
IT14345


RDS(on) – VGS
Ta=25°C
ID=1A
0.5A
2A
Static Drain to Source On-State Resistance, RDS(on) – mΩ
Gate to Source Voltage, VGS – V
IT14346


RDS(on) – Ta
VGS=1.8V, ID=0.5A
VGS=2.5V, ID=1.0A
VGS=4.5V, ID=2.0A
Static Drain to Source On-State Resistance, RDS(on) – mΩ
Ambient Temperature, Ta – °C
IT14347


gFS – ID
VDS=10V
Ta= –25°C
75°C
25°C
Forward Transconductance, gFS – S
Drain Current, ID – A
IT14348


IS – VSD
VGS=0V
Ta=75°C
25°C
–25°C
Source Current, IS – A
Forward Diode Voltage, VSD – V
IT14349


SW Time – ID
VDD=15V
VGS=4.5V
td(off)
tf
td(on)
tr
Switching Time, SW Time – ns
Drain Current, ID – A
IT14350


Ciss, Coss, Crss – VDS
f=1MHz
Ciss
Coss
Crss
Ciss, Coss, Crss – pF
Drain to Source Voltage, VDS – V
IT14351


VGS – Qg
VDS=15V
ID=4A
Gate to Source Voltage, VGS – V
Total Gate Charge, Qg – nC
IT14352


S O A
IDP=16A (PW≤10μs)
ID=4A
100μs
1ms
10ms
100ms
DC operation(Ta=25°C)
Operation in this area
is limited by RDS(on).
Ta=25°C
Single pulse
When mounted on ceramic substrate
(900mm2×0.8mm)
Drain Current, ID – A
Drain to Source Voltage, VDS – V
IT17925


PD – Ta
When mounted on ceramic substrate
(900mm2×0.8mm)
Power Dissipation, PD – W
Ambient Temperature, Ta – °C
IT14354


RθJA – Pulse Time
Duty Cycle=0.5
0.2
0.1
0.05
0.02
0.01
Single Pulse
When mounted on ceramic substrate
(900mm2×0.8mm)
Thermal Resistance, RθJA – °C/W
Pulse Time, PT – s
IT17926

PACKAGE DIMENSIONS

unit : mm

SC-70FL / MCPH3
CASE 419AQ
ISSUE O



1 : Gate
2 : Source
3 : Drain

Recommended Soldering Footprint



ORDERING INFORMATION

Device	Marking	Package	Shipping (Qty / Packing)
MCH3474-TL-H	FF	SC-70FL / MCPH3 (Pb-Free / Halogen Free)	3,000 / Tape & Reel
MCH3474-TL-W			

† For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D. http://www.onsemi.com/pub_link/Collateral/BRD8011-D.PDF

Note on usage : Since the MCH3474 is a MOSFET product, please avoid using this device in the vicinity of highly charged objects.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ON Semiconductor:

MCH3474-TL-H MCH3474-TL-W MCH3474-TL-E