# Programming Thinking Session 13

Pepe García jgarciah@faculty.ie.edu

# Plan for today

Handling files in Python

# Plan for today

- Handling files in Python
- CSV files

# the **open** function

We can use **open()** to open a file in Python, we only need to pass the path of the file we want to open. Let's say there's a file named hello.txt in my desktop that I want to open and read from Python, I can do it as follows:

# the **open** function

We can use **open()** to open a file in Python, we only need to pass the path of the file we want to open. Let's say there's a file named hello.txt in my desktop that I want to open and read from Python, I can do it as follows:

```
file = open("/Users/pepe/Desktop/hello.txt")
```

# closing files

Something very important we must do if we're going to deal with files is to close them. Once we've opened them, we can directly call **close()** on them at any point to close them.

# closing files

Something very important we must do if we're going to deal with files is to close them. Once we've opened them, we can directly call **close()** on them at any point to close them.

```
file = open("/Users/pepe/Desktop/hello.txt")
# deal with the file
file.close()
```

# Reading the contents of a file

Now that we know how to open and close files, we can read the contents of a file. Let's do that line by line.

# Reading the contents of a file

Now that we know how to open and close files, we can read the contents of a file. Let's do that line by line.

```
file = open("/Users/pepe/Desktop/hello.txt")

for line in file:
    print(line)

file.close()
```

# Reading the contents of a file

Now that we know how to open and close files, we can read the contents of a file. Let's do that line by line.

```
file = open("/Users/pepe/Desktop/hello.txt")

for line in file:
    print(line)

file.close()
```

As you can see, we're treating file as a list of lines.

#### Be careful with closed files

If you try to operate with a file that has already been closed, you'll see an error.

```
file = open("/Users/pepe/Desktop/hello.txt")

# In this line we're closing the file
file.close()

# trying to do this will cause an error
for line in file:
    print(line)
```

#### Be careful with closed files

If you try to operate with a file that has already been closed, you'll see an error.

```
file = open("/Users/pepe/Desktop/hello.txt")

# In this line we're closing the file
file.close()

# trying to do this will cause an error
for line in file:
    print(line)
```

ValueError: I/O operation on closed file.

### Interlude, with

there is a useful Python keyword that one can use to make sure that the file will always be closed, **with**:

### Interlude, with

there is a useful Python keyword that one can use to make sure that the file will always be closed, **with**:

```
with open("file_path") as file:
    for line in file:
      #do something with line
      print(line)
```

# Handling files. modes

When opening a file, we can choose in which **mode** we open it depending on how we're going to use it.

| I/O Mode          | Syntax | Behavior   |
|-------------------|--------|--|
| Read              | ʻr'    | Opens the contents of a file for reading into the file interface, allowing for lines to be read-in successively.   |
| Write             | 'w'    | Creates a file with the specified name and allows for text to be written to the file; note that specifying a pre-existing filename will overwrite the existing file. |
| Append            | 'a'    | Opens an existing file and allows for text to be written to it, starting at the conclusion of the original file contents.  |
| Read and<br>Write | 'r+'   | Opens a file such that its contents can be both read-in and written-to, thus offering great versatility.   |

Python's available file-access modes are summarized here.

doi:10.1371/journal.pcbi.1004867.t004

Figure 1: file modes

# Writing files

We can write into files in a way similar to the one used for reading them.

# Writing files

We can write into files in a way similar to the one used for reading them.

```
with open('/Users/pepe/Desktop/goodbye.txt', 'w') as f
   file.write("goodbye y'all!")
```

# Checkpoint

#### Checkpoint

Is everything clear so far? do you have any question?

Python comes with a **CSV** library that we can use out of the box. We use it by **importing** it. **Imports** are commonly added at the top of the file.

import csv

The **csv** library is based on the idea of readers and writers. One can read all lines in a file like so:

```
with open("file.csv") as f:
    reader = csv.reader(f)
    for line in reader:
        print(line) #line will be a list here
```

The **csv** library is based on the idea of readers and writers. One can read all lines in a file like so:

```
with open("file.csv") as f:
    reader = csv.reader(f)
    for line in reader:
        print(line) #line will be a list here
```

first we open the file normally

The **csv** library is based on the idea of readers and writers. One can read all lines in a file like so:

```
with open("file.csv") as f:
    reader = csv.reader(f)
    for line in reader:
        print(line) #line will be a list here
```

first we open the file normally

Then we create a reader using csv.reader()

The **csv** library is based on the idea of readers and writers. One can read all lines in a file like so:

```
with open("file.csv") as f:
    reader = csv.reader(f)
    for line in reader:
        print(line) #line will be a list here
```

first we open the file normally

Then we create a reader using csv.reader()

Finally, we operate with the reader

writing is not very different from reading:

```
lines = [
    ["asdf", "qwer"],
    ["hello", "world"]
]

with open("file.csv", "a") as f:
    writer = csv.writer(f)
    for line in lines:
        writer.writerow(line)
```

writing is not very different from reading:

```
lines = [
    ["asdf", "qwer"],
    ["hello", "world"]
]

with open("file.csv", "a") as f:
    writer = csv.writer(f)
    for line in lines:
        writer.writerow(line)
```

First we need some data to put in the csv file

writing is not very different from reading:

```
lines = [
    ["asdf", "qwer"],
    ["hello", "world"]
]

with open("file.csv", "a") as f:
    writer = csv.writer(f)
    for line in lines:
        writer.writerow(line)
```

First we need some data to put in the csv file

Then we open the file with the append mode

. . . Later, we create a csv.writer

writing is not very different from reading:

```
lines = [
    ["asdf", "qwer"],
    ["hello", "world"]
]

with open("file.csv", "a") as f:
    writer = csv.writer(f)
    for line in lines:
        writer.writerow(line)
```

First we need some data to put in the csv file

Then we open the file with the append mode

. . . Later, we create a csv.writer