

Programming Thinking

Session 6

Pepe García jgarciah@faculty.ie.edu



SCHOOL OF
SCIENCE &
TECHNOLOGY

You have been invited to **Codecademy**. Please follow the link in your email and create an account. There will be some sessions in which you'll be required to get something done in Codecademy, but for now, explore and see if there's any course that catches your eye.



Plan for today

- review last day exercises



Plan for today

- review last day exercises
- mutability



Plan for today

- review last day exercises
- mutability
- lists



Plan for today

- review last day exercises
- mutability
- lists
- iteration



Last session exercises

- 1 Create a function `weekly_commute_time` that asks the user their daily commute time and returns their weekly time spent commuting.
- 2 What do the following expressions return?
 - `True or 11 > 34`
 - `False and (1 == 1)`
 - `(77 // 11) > 6 and False`
- 3 Create a function `im_in_love` that takes a weekday number (from monday to friday), and returns how that weekday is (according to The Cure!):

```
I don't care if Monday's blue  
Tuesday's grey and Wednesday too  
Thursday I don't care about you  
It's Friday, I'm in love
```

Mutability

Mutability is a feature of variables in most programming languages. It means that variables can be updated to newer values.

```
x = 1
x = x * 3

print(x)
```



Mutability

Mutability is a feature of variables in most programming languages. It means that variables can be updated to newer values.

```
x = 1
x = x * 3

print(x)
```

Demo

Let's refresh how we can change the value of a variable in Spyder.

Iteration

Iteration is the act of repeating a process. In Python we express iteration with the **while** statement

Iteration

Iteration is the act of repeating a process. In Python we express iteration with the **while** statement

```
while <condition>:  
    <body>
```

While

```
while <condition>:  
    <body>
```

How does it work?



While

```
while <condition>:  
    <body>
```

How does it work?

- 1 Evaluate the condition



While

```
while <condition>:  
    <body>
```

How does it work?

- 1 Evaluate the condition
- 2 If the condition is False, exit while and go to next statement



While

```
while <condition>:  
    <body>
```

How does it work?

- 1 Evaluate the condition
- 2 If the condition is False, exit while and go to next statement
- 3 If condition is true, execute body. Then go to step 1.



While

```
while <condition>:  
    <body>
```

How does it work?

- 1 Evaluate the condition
- 2 If the condition is False, exit while and go to next statement
- 3 If condition is true, execute body. Then go to step 1.

Demo

Let's see how does the **while** loop work. Let's create a function that prints the numbers 1 to 50 (using iteration)



exercise

Create a function `pyramid` that receives an integer `n` as parameter and prints `n` lines of the following pattern:

```
*  
**  
***  
****  
*****
```



Lists

Lists are sequences of values

Constructing Lists

We construct lists with the brackets `[]` syntax. We surround everything that we want to include in the list with **square brackets** and separate elements with **commas**:

```
[1, 2, 3, 4, 5]
```

```
["hello", "dolly"]
```

```
[]
```

```
[1, "hello", 2, "dolly", 3]
```



Constructing Lists

We construct lists with the brackets `[]` syntax. We surround everything that we want to include in the list with **square brackets** and separate elements with **commas**:

```
[1, 2, 3, 4, 5]
```

```
["hello", "dolly"]
```

```
[]
```

```
[1, "hello", 2, "dolly", 3]
```

Demo

Let's create some lists and see the type of those values.



List length

We can get the length of a list using the **len** function:

```
names = ["Pepe", "Antonio"]  
print(len(names)) # will print 2
```



Accessing list elements

We use **square brackets** to access elements by their **index**.

Indices

indices in lists start by **0**, not 1.

```
words = ["hello", "dolly"]  
words[0]  
# "hello"  
words[1]  
# "dolly"
```



Accessing list elements

We use **square brackets** to access elements by their **index**.

Indices

indices in lists start by **0**, not 1.

```
words = ["hello", "dolly"]  
words[0]  
# "hello"  
words[1]  
# "dolly"
```

Demo



Exercise

Create a function that receives a list as a parameter and prints each element of the list individually.

Operators on lists

As with strings, `+` and `*` operators work with lists too!



Operators on lists

As with strings, `+` and `*` operators work with lists too!

Demo



Mutating lists

Lists are mutable values, and they provide functionality to add, delete, and update elements



Updating elements in the list

To update an element inside the list, we use a syntax similar to the one for declaring variables, but using the brackets and the index we refer to.

```
numbers = [1,2,4]
numbers[2] = 3
print(numbers) # prints [1,2,3]
```



Updating elements in the list

To update an element inside the list, we use a syntax similar to the one for declaring variables, but using the brackets and the index we refer to.

```
numbers = [1,2,4]
numbers[2] = 3
print(numbers) # prints [1,2,3]
```

Demo

Appending elements to the list

To add a new element to the end of the list we use the `append()` method on it.

```
numbers = [1,2,3]
numbers.append(4)
print(numbers) # prints [1,2,3,4]
```

Appending elements to the list

To add a new element to the end of the list we use the `append()` method on it.

```
numbers = [1,2,3]
numbers.append(4)
print(numbers) # prints [1,2,3,4]
```

Demo

Inserting elements in the list

There's an alternative way of adding new elements to the list, and it's using the `insert()` method on it:

```
words = ["hello", "my", "friends"]  
words.insert(2, "dear")  
print(words) # prints ["hello", "my", "dear", "friends"]
```

The difference between this and `append` is that with `insert` we can choose where to put it by using the target index

Inserting elements in the list

There's an alternative way of adding new elements to the list, and it's using the `insert()` method on it:

```
words = ["hello", "my", "friends"]  
words.insert(2, "dear")  
print(words) # prints ["hello", "my", "dear", "friends"]
```

The difference between this and `append` is that with `insert` we can choose where to put it by using the target index

Demo

Removing elements from the list

In order to remove an element from a list, we should use the `.pop()` method, and pass the index of the element we want to remove

```
words = ["hello", "my", "friend"]  
words.pop(1)  
print(words)
```

Removing elements from the list

In order to remove an element from a list, we should use the `.pop()` method, and pass the index of the element we want to remove

```
words = ["hello", "my", "friend"]  
words.pop(1)  
print(words)
```

Demo



For loops

For loops are simpler than while loops. They iterate over elements in a list. They loop once for every element in the list.

For loops

For loops are simpler than while loops. They iterate over elements in a list. They loop once for every element in the list.

```
for <iteration_variable> in <list>:  
    <body>
```

In each iteration, we will have a new value for the `iteration_variable`.



For loops

For loops are simpler than while loops. They iterate over elements in a list. They loop once for every element in the list.

```
for <iteration_variable> in <list>:  
    <body>
```

In each iteration, we will have a new value for the `iteration_variable`.

Demo



Exercise

create a function named **to_string** that receives a list and returns a string with all elements of the list concatenated. Don't use the `join` function.

Recap



SCHOOL OF
SCIENCE &
TECHNOLOGY

Recap

We will use **while** loops for iterating given a boolean condition.

Recap

We will use **while** loops for iterating given a boolean condition.

Use **lists** to store collections of values

Recap

We will use **while** loops for iterating given a boolean condition.

Use **lists** to store collections of values

Use mutation operations on list to append, remove, or update elements in the list



Recap

We will use **while** loops for iterating given a boolean condition.

Use **lists** to store collections of values

Use mutation operations on list to append, remove, or update elements in the list

Use for loops to iterate over elements in the list



Exercises

- Create a function that returns a list of numbers from 0 to 500
- Create a function that takes a list of numbers (you can use the one you created in the previous exercise) and returns the sum of all of them
- Investigate the `range()` function. After you've used it, create a function that receives a number as parameter and prints all numbers from it to zero (using a for loop).
- Create a function that takes a list of numbers and returns the maximum value among them
- Create a function that takes a list of numbers and returns the minimum value among them

(cont)



SCHOOL OF
SCIENCE &
TECHNOLOGY

Exercises (Cont)

- Create a function that prints the numbers 1 to 50 (using iteration)
- Create a program that prints multiplication tables from 1 to 10
- Create a function `inverted_pyramid` that writes the pyramid of stars in an inverted fashion.

**

*

(cont)



Exercises (Cont)

- Create a function `multiply` that takes two integers (`a` and `b`, for example) and returns `a` times `b`. Do not use the `*` operator.
- Create a function `exponentiate` that takes two arguments `base` and `exponent` and raises `base` to the `exponent` power. Do not use the `**` operator.



Recommended literature

<https://www.py4e.com/html3/05-iterations>

<https://www.py4e.com/lessons/lists>



SCHOOL OF
SCIENCE &
TECHNOLOGY