


Funciones y paquetes

Pepi Amodeo

Instituto Argentino de Oceanografía

CONICET-UNS

CCT Bahía Blanca



Funciones

$f(x)$

Funciones

$f(\text{argumento1} = \dots, \text{argumento 2} = \dots)$


Funciones

```
log(2)  
log10(2)
```

```
log(x=2)  
log10(x=2)
```

Los argumentos se pueden explicitar siempre
Pero para agilizar se pueden indicar directamente (sin =)... ojo! R asume...

Funciones



Paquetes



Agregan funciones al R base

Paquetes



1997: 12 paquetes

2022: 18728 paquetes

Paquetes

- Open-source. Los generan los mismos usuarios (libre)
- Incorporan nuevas funcionalidades al R base
- Hay redundancias
- CRAN unifica y organiza los paquetes oficiales
- Existen paquetes en desarrollo o desarrollos “no oficiales” (github, dropbox, de mano en mano)

usuario/a



desarrollador/a

CRAN



CRAN

[Mirrors](#)

[What's new?](#)

[Search](#)

About R

[R Homepage](#)

[The R Journal](#)

Software

[R Sources](#)

[R Binaries](#)

[Packages](#)

[Task Views](#)

[Other](#)

Documentation

[Manuals](#)

[FAQs](#)

[Contributed](#)

Available CRAN Packages By Date of Publication

Date	Package	Title
2022-08-09	abcrf	Approximate Bayesian Computation via Random Forests
2022-08-09	apollo	Tools for Choice Model Estimation and Application
2022-08-09	BeeGUTS	General Unified Threshold Model of Survival for Bees using Bayesian Inference
2022-08-09	BioRssay	Analyze Bioassays and Probit Graphs
2022-08-09	BMS	Bayesian Model Averaging Library
2022-08-09	BSBT	The Bayesian Spatial Bradley–Terry Model
2022-08-09	calibrationband	Calibration Bands
2022-08-09	caret	Classification and Regression Training
2022-08-09	cassowaryr	Compute Scagnostics on Pairs of Numeric Variables in a Data Set
2022-08-09	censusapi	Retrieve Data from the Census APIs
2022-08-09	climate	Interface to Download Meteorological (and Hydrological) Datasets

Repositorio donde se alojan todos los desarrollos "oficiales" relacionados con el proyecto R

Instalación paquetes

The screenshot displays the RStudio environment with the following components:

- Source Editor:** Contains an R script with the following code:

```
1 rm(list = ls())
2 N <- 1000
3 u <- rnorm(N)
4 x1 <- -2 + rnorm(N)
5 x2 <- 1 + x1 + rnorm(N)
6 y <- 1 + x1 + x2 + u
7 r1 <- lm(y ~ x1 + x2)
8
9
10 |
```
- Console:** Shows the execution of the script with the following output:

```
> rm(list = ls())
> N <- 1000
> u <- rnorm(N)
> x1 <- -2 + rnorm(N)
> x2 <- 1 + x1 + rnorm(N)
> y <- 1 + x1 + x2 + u
> r1 <- lm(y ~ x1 + x2)
>
```
- Workspace:** Displays the objects created in the environment:

Object	Value
N	1000
r1	lm[12]
u	numeric[1000]
x1	numeric[1000]
x2	numeric[1000]
y	numeric[1000]
- Help Pane:** Shows the documentation for the `lm` function, titled "Fitting Linear Models". It includes a description of the function's purpose, its usage, and its arguments.

Instalación vs Activación

- `install.packages("ggplot2")`
 - Instalado en la pc
 - Queda disponible pero inactivo
 - Única vez
- `library("ggplot2")`
 - En cada sesión
 - Tiene que estar instalado previamente
 - Cada vez que lo quiero usar

Instalación paquetes

- Forma reproducible (en el script)

```
install.packages("ggplot2")
```



- Forma NO reproducible (en el panel)


```
Panel / packages / install
```

- A mano (zip)

Alternativa cuando falla CRAN



Ayuda



The screenshot shows the RStudio environment with the following components:

- Source Editor:** Contains R code for generating data and fitting a linear model.
- Console:** Shows the execution of the code, with prompts for help and the results of the operations.
- Workspace:** Displays the objects created in the environment, including N, u, x1, x2, y, and r1.
- Help Panel:** Shows the documentation for the `lm` function, including a description, usage, and arguments.

```
1 rm(list = ls())
2 N <- 1000
3 u <- rnorm(N)
4 x1 <- -2 + rnorm(N)
5 x2 <- 1 + x1 + rnorm(N)
6 y <- 1 + x1 + x2 + u
7 r1 <- lm(y ~ x1 + x2)
8
9
10
```

Console output:

```
Tapez <Entrée> pour voir le graphique suivant :
Tapez <Entrée> pour voir le graphique suivant :
Tapez <Entrée> pour voir le graphique suivant :
>
> ?lm
> rm(list = ls())
> N <- 1000
> u <- rnorm(N)
> x1 <- -2 + rnorm(N)
> x2 <- 1 + x1 + rnorm(N)
> y <- 1 + x1 + x2 + u
> r1 <- lm(y ~ x1 + x2)
>
```

Workspace Values:

Object	Value
N	1000
r1	lm[12]
u	numeric[1000]
x1	numeric[1000]
x2	numeric[1000]
y	numeric[1000]

Help Panel: R: Fitting Linear Models

Description

`lm` is used to fit linear models. It can be used to carry out regression, single stratum analysis of variance and analysis of covariance (although `av` may provide a more convenient interface for these).

Usage

```
lm(formula, data, subset, weights,
    method = "qr", model = TRUE, x =
    singular.ok = TRUE, contrasts =
```

Arguments

- `?mifuncion()`
- `help()`
- En el Panel / Help / Buscar

ó F1



```
help("+")
```

Arithmetic Operators

Description

These unary and binary operators perform arithmetic on numeric or complex vectors (or objects which can be coerced to them).

Usage

```
+ x
- x
x + y
x - y
x * y
x / y
x ^ y
x %% y
x %/% y
```

Arguments

x, *y* numeric or complex vectors or objects which can be coerced to such, or other objects for which methods have been written.

Details

The unary and binary arithmetic operators are generic functions: methods can be written for them individually or via the [Ops](#) group generic function. (See [Ops](#) for how dispatch is computed.)

If applied to arrays the result will be an array if this is sensible (for example it will not if the recycling rule has been invoked).

Logical vectors will be coerced to integer or numeric vectors, `FALSE` having value zero and `TRUE` having value one.

$1 \wedge y$ and $y \wedge 0$ are 1, *always*. $x \wedge y$ should also give the proper limit result when either (numeric) argument is [infinite](#) (one of `Inf` or `-Inf`).

Objects such as arrays or time-series can be operated on this way provided they are conformable.

For double arguments, `%%` can be subject to catastrophic loss of accuracy if *x* is much larger than *y*, and a warning is given if this is detected.

`%%` and `x %/% y` can be used for non-integer *y*, e.g. `1 %/% 0.2`, but the results are subject to representation error and so may be platform-dependent. Because the IEC 60559 representation of 0.2 is a binary fraction slightly larger than 0.2, the answer to `1 %/% 0.2` should be 4 but most platforms give 5.

Users are sometimes surprised by the value returned, for example why `(-8)^(1/3)` is `NaN`. For [double](#) inputs, R makes use of IEC 60559 arithmetic on all platforms, together with the C system function `pow` for the `^` operator. The relevant standards define the result in many corner cases. In particular, the result in the example above is mandated by the C99 standard. On many Unix-alike systems the command `man pow` gives details of the values in a large number of corner cases.

Arithmetic on type [double](#) in R is supposed to be done in 'round to nearest, ties to even' mode, but this does depend on the compiler and FPU being set up correctly.

Value

Unary `+` and unary `-` return a numeric or complex vector. All attributes (including class) are preserved if there is no coercion: logical *x* is coerced to integer and names, dims and dimnames are preserved.

S4 methods

These operators are members of the S4 [Arith](#) group generic, and so methods can be written for them individually as well as for the group generic (or the `Ops` group generic), with arguments `c(e1, e2)` (with `e2` missing for a unary operator).

Implementation limits

R is dependent on OS services (and they on FPUs) for floating-point arithmetic. On all current R platforms IEC 60559 (also known as IEEE 754) arithmetic is used, but some things in those standards are optional. In particular, the support for *denormal* aka *subnormal* numbers (those outside the range given by [.Machine](#)) may differ between platforms and even between calculations on a single platform.

Another potential issue is signed zeroes: on IEC 60559 platforms there are two zeroes with internal representations differing by sign. Where possible R treats them as the same, but for example direct output from C code often does not do so and may output `-0.0` (and on Windows whether it does so or not depends on the version of Windows). One place in R where the difference might be seen is in division by zero: `1/x` is `Inf` or `-Inf` depending on the sign of zero `x`. Another place is [identical](#)(0, -0, num.eq = FALSE).

Note

All logical operations involving a zero-length vector have a zero-length result.

The binary operators are sometimes called as functions as e.g. ``&`(x, y)`: see the description of how argument-matching is done in [Ops](#).

`**` is translated in the parser to `^`, but this was undocumented for many years. It appears as an index entry in Becker *et al* (1988), pointing to the help for `Deprecated` but is not actually mentioned on that page. Even though it had been deprecated in S for 20 years, it was still accepted in R in 2008.

References

Becker, R. A., Chambers, J. M. and Wilks, A. R. (1988) *The New S Language*. Wadsworth & Brooks/Cole.

D. Goldberg (1991). What Every Computer Scientist Should Know about Floating-Point Arithmetic. *ACM Computing Surveys*, **23**(1), 5–48. doi: [10.1145/103162.103163](https://doi.org/10.1145/103162.103163).

Also available at https://docs.oracle.com/cd/E19957-01/806-3568/ncg_goldberg.html.

For the IEC 60559 (aka IEEE 754) standard: <https://www.iso.org/standard/57469.html> and https://en.wikipedia.org/wiki/IEEE_754.

See Also

[sqrt](#) for miscellaneous and [Special](#) for special mathematical functions.

[Syntax](#) for operator precedence.

[%*%](#) for matrix multiplication.

Examples

```
x <- -1:12
x + 1
2 * x + 3
x %% 2 #-- is periodic
x %/% 5
x %% Inf # now is defined by limit (gave NaN in earlier versions of R)
```


Operadores básicos

Operadores aritméticos

Arithmetic {base}

R Documentation

Arithmetic Operators

Description

These unary and binary operators perform arithmetic on numeric or complex vectors (or objects which can be coerced to them).

Usage

```
+ x  
- x  
x + y  
x - y  
x * y  
x / y  
x ^ y  
x %% y  
x %/% y
```

`help("+")`

Panel/Help: Arithmetic operators

Operadores básicos

Funciones matemáticas

```
sin(1) # trigonometry functions
```

```
[1] 0.841471
```

```
log(1) # natural logarithm
```

```
[1] 0
```

```
log10(10) # base-10 logarithm
```

```
[1] 1
```

```
exp(0.5) #  $e^{(1/2)}$ 
```

```
[1] 1.648721
```

Salida de web blog

Operadores básicos

Operadores relacionales

```
1 == 1 # equality (note two equals signs, read as "is equal to")
```

```
[1] TRUE
```

```
1 != 2 # inequality (read as "is not equal to")
```

```
[1] TRUE
```

```
1 < 2 # less than
```

```
[1] TRUE
```

```
1 <= 1 # less than or equal to
```

```
[1] TRUE
```

```
1 > 0 # greater than
```

```
[1] TRUE
```

Evalúa una condición y devuelve TRUE/FALSE

Consola

The image shows the RStudio environment. The top menu bar includes File, Edit, Code, View, Plots, Session, Project, Build, Tools, and Help. The main editor window contains an R script with the following code:

```
1  
2 rm(list = ls())  
3 N <- 1000  
4 u <- rnorm(N)  
5 x1 <- -2 + rnorm(N)  
6 x2 <- 1 + x1 + rnorm(N)  
7 y <- 1 + x1 + x2 + u  
8 r1 <- lm(y ~ x1 + x2)  
9  
10 |
```

The console window at the bottom shows the execution of the script, with prompts in Spanish: "Tapez <Entrée> pour voir le graphique suivant :". The help pane on the right displays the documentation for the `lm` function, titled "Fitting Linear Models".

Workspace

Values	
N	1000
r1	lm[12]
u	numeric[1000]
x1	numeric[1000]
x2	numeric[1000]
y	numeric[1000]

Files **Plots** **Packages** **Help**

R: Fitting Linear Models

lm (stats) [R Documentation](#)

Fitting Linear Models

Description

lm is used to fit linear models. It can be used to carry out regression, single stratum analysis of variance and analysis of covariance (although [aov](#) may provide a more convenient interface for these).

Usage

```
lm(formula, data, subset, weights,  
   method = "qr", model = TRUE, x =  
   singular.ok = TRUE, contrasts =
```


Arguments

A través de ella se da la interacción con "el autómatas".
Mandamos órdenes, vuelven mensajes y salidas

Consola

- Símbolo STOP
- Mensajes

Consola



The image shows a screenshot of an R console window. The window has a title bar with tabs for 'Console', 'Terminal', and 'Jobs'. The address bar shows the path '~/Documents/MarPackProjTest/'. The console output includes instructions on using R, such as 'Natural language support but running in an English locale', 'R is a collaborative project with many contributors.', and 'Type 'demo()' for some demos, 'help()' for on-line help, or 'help.start()' for an HTML browser interface to help. Type 'q()' to quit R.'. The user has entered the command '> plumber::plumb(file='MarNewPlumbAPIfile/plumber.R')\$run()', and the output shows 'Starting server to listen on port 8095' and 'Running the swagger UI at http://127.0.0.1:8095/__swagger__/'. A red 'STOP' button is visible in the top right corner of the console window, with a black arrow pointing to it. To the right of the console window is a cartoon illustration of a red squirrel standing on a log, with its arms raised in a 'stop' gesture.

```
Console Terminal x Jobs x
~/Documents/MarPackProjTest/

Natural language support but running in an English locale

R is a collaborative project with many contributors.
Type 'contributors()' for more information and
'citation()' on how to cite R or R packages in publications.

Type 'demo()' for some demos, 'help()' for on-line help, or
'help.start()' for an HTML browser interface to help.
Type 'q()' to quit R.

> plumber::plumb(file='MarNewPlumbAPIfile/plumber.R')$run()
Starting server to listen on port 8095
Running the swagger UI at http://127.0.0.1:8095/__swagger__/

|
```

El STOP indica que está procesando.

Pulsar para interrumpir el proceso... a veces es mejor tener paciencia...

Consola

- Message

Tranqui... no es un error...
es solo un autómatata
tratando de expresarse

```
> message("esto es un mensaje")  
esto es un mensaje
```

- Warning

Tranqui... no es un error...
nos avisa algo por las
dudas

```
> library(cowsay)  
Warning message:  
package 'cowsay' was built under R version 4.1.3
```

- Error

Ahora sí se pudo todo!



```
> say()  
Error in say() : could not find function "say"
```

```
Error in say() : could not find function "say"  
> mean(c(uno,2,3))  
Error in mean(c(uno, 2, 3)) : object 'uno' not found
```

Editor de Scripts

The screenshot displays the RStudio environment. The main script editor contains the following R code:

```
1  
2 rm(list = ls())  
3 N <- 1000  
4 u <- rnorm(N)  
5 x1 <- -2 + rnorm(N)  
6 x2 <- 1 + x1 + rnorm(N)  
7 y <- 1 + x1 + x2 + u  
8 r1 <- lm(y ~ x1 + x2)  
9  
10 |
```

The console at the bottom shows the execution of these commands:

```
Tapez <Entrée> pour voir le graphique suivant :  
Tapez <Entrée> pour voir le graphique suivant :  
Tapez <Entrée> pour voir le graphique suivant :  
>  
> ?lm  
> rm(list = ls())  
> N <- 1000  
> u <- rnorm(N)  
> x1 <- -2 + rnorm(N)  
> x2 <- 1 + x1 + rnorm(N)  
> y <- 1 + x1 + x2 + u  
> r1 <- lm(y ~ x1 + x2)  
>
```

The right-hand pane is divided into two sections. The top section, 'Values', lists the objects in the workspace:

Object	Value
N	1000
r1	lm[12]
u	numeric[1000]
x1	numeric[1000]
x2	numeric[1000]
y	numeric[1000]

The bottom section, 'R: Fitting Linear Models', displays the documentation for the `lm` function:

Fitting Linear Models

Description

`lm` is used to fit linear models. It can be used to carry out regression, single stratum analysis of variance and analysis of covariance (although `aov` may provide a more convenient interface for these).

Usage

```
lm(formula, data, subset, weights,  
    method = "qr", model = TRUE, x =  
    singular.ok = TRUE, contrasts =
```


Arguments



Es donde genero el documento (LO MÁS IMPORTANTE)

Interactúa con la consola enviando línea por línea (CTRL+ENTER)

Con # hago comentarios (lineas que no se ejecutan)

Editor de Scripts



 TP1_ejercicio.R
 TP2_ejercicio.R

Archivo .R (texto plano)
¡¡¡LO MÁS IMPORTANTE!!!