

# Home Challenge #1: Sniffing

Prof. Matteo Cesana - Year 2020/2021

*Gabba Rohit [codice persona: 10706944]*

*Tortorelli Giuseppe [codice persona: 10582962]*

## Contents

1	What's the difference between the message with MID: 3978 and the one with MID: 22636?	2
2	Does the client receive the response of message No. 6949?	2
3	How many replies of type confirmable and result code "Content" are received by the server "localhost"?	2
4	How many messages containing the topic "factory/department*/+" are published by a client with user name: "jane"? Where * replaces the dep. number, e.g. factory/department1/+, factory/department2/+ and so on?	2
5	How many clients connected to the broker "hivemq" have specified a will message?	2
6	How many publishes with QoS 1 don't receive thr ACK?	2
7	How many last will messages with QoS set to 0 are actually delivered?	3
8	Are all the messages with QoS 0 published by the client "4m3DWYzWr40pce6OaBQAfk" correctly delivered to the subscribers?	3
9	What is the average message length of a connect msg using mqttv5 protocol? Why messages have different size?	3
10	Why there aren't any REQ/RESP pings in the pcap?	4

## 1 What's the difference between the message with MID: 3978 and the one with MID: 22636?

Using Wireshark filter:

$$coap.mid == 3978 \&\& coap.mid == 22636$$

we have isolated the two packets. After that we noticed that they have a different token and also that the first is of type *CON* and the second of type *NON*. Therefore the first one requires an *ACK* message and the second one does not.

## 2 Does the client receive the response of message No. 6949?

First of all using Wireshark *No.* column we found the message number 6949 and we read its *MID*. After this using filter:

$$coap.mid == 28357$$

we discovered that there was an *ACK* referred to the previous one, that contains error message *4.05*. That means the method is not allowed, so the client did not received the response.

## 3 How many replies of type confirmable and result code "Content" are received by the server "localhost"?

Using filter:

$$coap.type == 0 \&\& ip.dst == 127.0.0.1 \&\& coap.code == 69$$

we found out that there was 8 lines

## 4 How many messages containing the topic "factory/department\*/+" are published by a client with user name: "jane"? Where \* replaces the dep. number, e.g. factory/department1/+, factory/department2/+ and so on?

## 5 How many clients connected to the broker "hivemq" have specified a will message?

First of all we found "hivemq" ip addresses (18.185.199.22, 3.120.68.56). Using filter:

$$mqtt.willmsg \&\& mqtt.clientid\_len > 0$$

we have selected all connection messages with *will flag* setted and send by not null *ClientID*. Browsing all the entries we counted 3 different clients.

## 6 How many publishes with QoS 1 don't receive thr ACK?

Using filter:

$$mqtt.msgtype == 3 \&\& mqtt.qos == 1$$

we got all published messages with QoS equals to 1 (124).

Using filter:

$$mqtt.msgtype == 4$$

we got all *ACK* messages for the published one (74).

By computing the difference

$$124 - 74 = 50$$

we obtained the number of messages that did not receive an *ACK*

**7 How many last will messages with QoS set to 0 are actually delivered?**

**8 Are all the messages with QoS 0 published by the client “4m3DWYzWr40pce6OaBQAfk” correctly delivered to the subscribers?**

Using filter:

*mqtt.clientid == "4m3DWYzWr40pce6OaBQAfk"*

we found sender ip address (10.0.2.15), source port (58313), destination ip (5.196.95.208).

Using filter:

*ip.src == 10.0.2.15 && tcp.srcport == 58313 && mqtt.qos > 0 && mqtt.msgtype == 3*

we found that the client sent one pub message with *QoS* set to 2.

Using filter:

*ip.src == 5.196.95.208 && tcp.dstport == 58313 && ip.dst == 10.0.2.15 && mqtt.msgtype == 5*

we got the *PUBREC* message sent from the broker to the client.

Not having found any *PUBREL* message, it means that the broker successfully received the message but did not send it to any other client. So no messages published by “4m3DWYzWr40pce6OaBQAfk” is correctly delivered

**9 What is the average message length of a connect msg using mqttv5 protocol? Why messages have different size?**

Using filter:

*mqtt.ver == 5*

we got all connection messages that use mqtt version 5.

Analyzing them we obtained:

- 35 messages of length 13
- 1 message of length 29
- 4 messages of length 69
- 4 messages of length 65
- 1 message of length 20
- 4 messages of length 77
- 2 messages of length 32
- 5 messages of length 25
- 1 message of length 27
- 1 message of length 86
- 1 message of length 33
- 2 messages of length 30
- 1 message of length 78
- 1 message of length 83

Calculating the average, we obtained an average length of 30.22 bytes.

The length changes from message to message because the connection message may or may not contain additional information such as the last will message.

10 Why there aren't any REQ/RESP pings in the pcap?