Agent session evidence

Session pocketos-replay · exported 2026-11-04T08:19:10Z · perathos

VERIFIED

Recorded	2026-11-04T08:19:04.700884Z to 2026-11-04T08:19:08.217162Z (local clock)
Tool calls	4
Blocked by guard	2
Sealed	through receipt 8 by 2 signed checkpoint(s)
Independent timestamps	2 token(s), through receipt 8 at 2026-11-04T08:19:09Z
Signer key	d53f11ff38959d472a2e619b346340b44a79866fb8650d96f22ada467f524707
Model (self-reported)	unknown

Destructive actions

- **Blocked** receipt 3 · 2026-11-04T08:19:05.192047Z · Bash · rule `paas.railway`
- **Blocked** receipt 4 · 2026-11-04T08:19:05.431384Z · Bash · rule `guard.self-authorize`
- **Allowed under safety check** receipt 6 · 2026-11-04T08:19:07.697718Z · rule `paas.railway` check: `python check_backup.py offsite/prod-backup.db` · scope `pg-data` · signed 2026-11-04T08:19:07Z

What this evidence does not show

- Shows which key sealed the record, not which model ran (the model name is self-reported).
- Event times come from the local clock; only anchored checkpoints have an independent time.
- Tool arguments and outputs are not included, only their SHA-256 hashes.
- A gap in recording (hooks switched off) is not visible in the log.
- The guard matches command patterns; it is a safeguard against accidents, not a sandbox.

Every file in this pack is listed with its SHA-256 in MANIFEST.json, which is signed. Re-check it yourself: `pip install 'perathos[anchor]'` then `perathos evidence verify <pack>`.