

# R Reference Card

by Tom Short, EPRI PEAC, tshort@epri-peac.com 2004-11-07

Granted to the public domain. See www.Rpad.org for the source and latest version. Includes material from *R for Beginners* by Emmanuel Paradis (with permission).

## Getting help

Most R functions have online documentation.

**help(topic)** documentation on topic

**?topic** id.

**help.search("topic")** search the help system

**apropos("topic")** the names of all objects in the search list matching the regular expression "topic"

**help.start()** start the HTML version of help

**str(a)** display the internal \*str\*ucture of an R object

**summary(a)** gives a "summary" of a, usually a statistical summary but it is *generic* meaning it has different operations for different classes of a

**ls()** show objects in the search path; specify pat="pat" to search on a pattern

**ls.str()** str() for each variable in the search path

**dir()** show files in the current directory

**methods(a)** shows S3 methods of a

**methods(class=class(a))** lists all the methods to handle objects of class a

## Input and output

**load()** load the datasets written with **save**

**data(x)** loads specified data sets

**library(x)** load add-on packages

**read.table(file)** reads a file in table format and creates a data frame from it; the default separator sep=" " is any whitespace; use header=TRUE to read the first line as a header of column names; use as.is=TRUE to prevent character vectors from being converted to factors; use comment.char=" " to prevent "#" from being interpreted as a comment; use skip=n to skip n lines before reading data; see the help for options on row naming, NA treatment, and others

**read.csv("filename", header=TRUE)** id. but with defaults set for reading comma-delimited files

**read.delim("filename", header=TRUE)** id. but with defaults set for reading tab-delimited files

**read.fwf(file, widths, header=FALSE, sep=" ", as.is=FALSE)** read a table of fixed width formatted data into a 'data.frame'; widths is an integer vector, giving the widths of the fixed-width fields

**save(file,...)** saves the specified objects (...) in the XDR platform-independent binary format

**save.image(file)** saves all objects

**cat(..., file="", sep=" ")** prints the arguments after coercing to character; sep is the character separator between arguments

**print(a, ...)** prints its arguments; generic, meaning it can have different methods for different objects

**format(x,...)** format an R object for pretty printing

**write.table(x, file="", row.names=TRUE, col.names=TRUE, sep=" ")** prints x after converting to a data frame; if quote is TRUE,

character or factor columns are **surrounded by quotes ("**); sep is the field separator; eol is the end-of-line separator; na is the string for missing values; use col.names=NA to add a blank column header to get the column headers aligned correctly for spreadsheet input

**sink(file)** output to file, until sink()

Most of the I/O functions have a file argument. This can often be a character string naming a file or a connection. file="" means the standard input or output. Connections can include files, pipes, zipped files, and R variables.

On windows, the file connection can also be used with description = "clipboard". To read a table copied from Excel, use

x <- read.delim("clipboard")

To write a table to the clipboard for Excel, use

write.table(x, "clipboard", sep="\t", col.names=NA)

For database interaction, see packages RODBC, DBI, RMySQL, RPgSQL, and ROracle. See packages XML, hdf5, netCDF for reading other file formats.

## Data creation

**c(...)** generic function to combine arguments with the default forming a vector; with recursive=TRUE descends through lists combining all elements into one vector

**from:** to generates a sequence; ":" has operator priority; 1:4 + 1 is "2,3,4,5"

**seq(from,to)** generates a sequence by= specifies increment; length= specifies desired length

**seq(along=x)** generates 1, 2, ..., length(along); useful for for loops

**rep(x,times)** replicate x times; use each= to repeat "each" element of x each times; rep(c(1,2,3),2) is 1 2 3 1 2 3; rep(c(1,2,3),each=2) is 1 1 2 2 3 3

**data.frame(...)** create a data frame of the named or unnamed arguments; data.frame(v=1:4, ch=c("a", "B", "c", "d"), n=10); shorter vectors are recycled to the length of the longest

**list(...)** create a list of the named or unnamed arguments; list(a=c(1,2), b="hi", c=3i);

**array(x,dim=)** array with data x; specify dimensions like dim=c(3,4,2); elements of x recycle if x is not long enough

**matrix(x,nrow=,ncol=)** matrix; elements of x recycle

**factor(x,levels=)** encodes a vector x as a factor

**gl(n,k,length=n\*k,labels=1:n)** generate levels (factors) by specifying the pattern of their levels; k is the number of levels, and n is the number of replications

**expand.grid()** a data frame from all combinations of the supplied vectors or factors

**rbind(...)** combine arguments by rows for matrices, data frames, and others

**cbind(...)** id. by columns

## Slicing and extracting data

Indexing vectors

x[n]	n <sup>th</sup> element
x[-n]	all <i>but</i> the n <sup>th</sup> element
x[1:n]	first n elements
x[-(1:n)]	elements from n+1 to the end
x[c(1,4,2)]	specific elements
x["name"]	element named "name"
x[x > 3]	all elements greater than 3
x[x > 3 & x < 5]	all elements between 3 and 5
x[x %in% c("a", "and", "the")]	elements in the given set

Indexing lists

x[n]	list with elements n
x[[n]]	n <sup>th</sup> element of the list
x[["name"]]	element of the list named "name"
x\$name	id.

Indexing matrices

x[i, j]	element at row i, column j
x[i,]	row i
x[, j]	column j
x[, c(1,3)]	columns 1 and 3

x["name",] row named "name"

Indexing data frames (matrix indexing plus the following)

x[["name"]]	column named "name"
x\$name	id.

## Variable conversion

**as.array(x), as.data.frame(x), as.numeric(x), as.logical(x), as.complex(x), as.character(x), ...** convert type; for a complete list, use methods(as)

## Variable information

**is.na(x), is.null(x), is.array(x), is.data.frame(x), is.numeric(x), is.complex(x), is.character(x), ...** test for type; for a complete list, use methods(is)

**length(x)** number of elements in x

**dim(x)** Retrieve or set the dimension of an object; dim(x) <- c(3,2)

**dimnames(x)** Retrieve or set the dimension names of an object

**nrow(x)** number of rows; NROW(x) is the same but treats a vector as a one-row matrix

**ncol(x)** and **NCOL(x)** id. for columns

**class(x)** get or set the class of x; class(x) <- "myclass"

**unclass(x)** remove the class attribute of x

**attr(x,which)** get or set the attribute which of x

**attributes(obj)** get or set the list of attributes of obj

## Data selection and manipulation

**which.max(x)** returns the index of the greatest element of x

**which.min(x)** returns the index of the smallest element of x

**rev(x)** reverses the elements of x

**sort(x)** sorts the elements of x in increasing order; to sort in decreasing order: rev(sort(x))

**cut(x,breaks)** divides x into intervals (factors); breaks is the number of cut intervals or a vector of cut points

**match(x, y)** returns a vector of the same length than x with the elements of x which are in y (NA otherwise)

**which(x == a)** returns a vector of the indices of x if the comparison operation is true (TRUE), in this example the values of i for which x[i] == a (the argument of this function must be a variable of mode logical)

**choose(n, k)** computes the combinations of k events among n repetitions = n!/[(n-k)!k!]

**na.omit(x)** suppresses the observations with missing data (NA) (suppresses the corresponding line if x is a matrix or a data frame)

**na.fail(x)** returns an error message if x contains at least one NA

**unique(x)** if x is a vector or a data frame, returns a similar object but with the duplicate elements suppressed

**table(x)** returns a table with the numbers of the differents values of x (typically for integers or factors)

**subset(x, ...)** returns a selection of x with respect to criteria (...), typically comparisons: `x$V1 < 10`; if x is a data frame, the option `select` gives the variables to be kept or dropped using a minus sign

**sample(x, size)** resample randomly and without replacement `size` elements in the vector x, the option `replace = TRUE` allows to resample with replacement

**prop.table(x,margin=)** table entries as fraction of marginal table

Math

**sin, cos, tan, asin, acos, atan, atan2, log, log10, exp**

**max(x)** maximum of the elements of x

**min(x)** minimum of the elements of x

**range(x)** id. then `c(min(x), max(x))`

**sum(x)** sum of the elements of x

**diff(x)** lagged and iterated differences of vector x

**prod(x)** product of the elements of x

**mean(x)** mean of the elements of x

**median(x)** median of the elements of x

**quantile(x, probs=)** sample quantiles corresponding to the given probabilities (defaults to 0,25,5,75,1)

**weighted.mean(x, w)** mean of x with weights w

**rank(x)** ranks of the elements of x

**var(x)** or `cov(x)` variance of the elements of x (calculated on  $n - 1$ ); if x is a matrix or a data frame, the variance-covariance matrix is calculated

**sd(x)** standard deviation of x

**cor(x)** correlation matrix of x if it is a matrix or a data frame (1 if x is a vector)

**var(x, y)** or `cov(x, y)` covariance between x and y, or between the columns of x and those of y if they are matrices or data frames

**cor(x, y)** linear correlation between x and y, or correlation matrix if they are matrices or data frames

**round(x, n)** rounds the elements of x to n decimals

**log(x, base)** computes the logarithm of x with base base

**scale(x)** if x is a matrix, centers and reduces the data; to center only use the option `center=FALSE`, to reduce only `scale=FALSE` (by default `center=TRUE`, `scale=TRUE`)

**pmin(x,y,...)** a vector which *i*th element is the minimum of `x[i]`, `y[i]`,...

**pmax(x,y,...)** id. for the maximum

**cumsum(x)** a vector which *i*th element is the sum from `x[1]` to `x[i]`

**cumprod(x)** id. for the product

**cummin(x)** id. for the minimum

**cummax(x)** id. for the maximum

**union(x,y), intersect(x,y), setdiff(x,y), setequal(x,y), is.element(e1,set)** “set” functions

**Re(x)** real part of a complex number

**Im(x)** imaginary part

**Mod(x)** modulus; `abs(x)` is the same

**Arg(x)** angle in radians of the complex number

**Conj(x)** complex conjugate

**convolve(x,y)** compute the several kinds of convolutions of two sequences

**fft(x)** Fast Fourier Transform of an array

**mvfft(x)** FFT of each column of a matrix

**filter(x,filter)** applies linear filtering to a univariate time series or to each series separately of a multivariate time series

Many math functions have a logical parameter `na.rm=FALSE` to specify missing data (NA) removal.

Matrices

**t(x)** transpose

**diag(x)** diagonal

**%%** matrix multiplication

**solve(a,b)** solves `a %% x = b` for x

**solve(a)** matrix inverse of a

**rowsum(x)** sum of rows for a matrix-like object; **rowSums(x)** is a faster version

**colsum(x), colSums(x)** id. for columns

**rowMeans(x)** fast version of row means

**colMeans(x)** id. for columns

Advanced data processing

**apply(X, INDEX, FUN=)** a vector or array or list of values obtained by applying a function FUN to margins (INDEX) of X

**lapply(X, FUN)** apply FUN to each element of the list X

**tapply(X, INDEX, FUN=)** apply FUN to each cell of a ragged array given by X with indexes INDEX

**by(data, INDEX, FUN)** apply FUN to data frame data subsetted by INDEX

**merge(a,b)** merge two data frames by common columns or row names

**xtabs(a b, data=x)** a contingency table from cross-classifying factors

**aggregate(x,by,FUN)** splits the data frame x into subsets, computes summary statistics for each, and returns the result in a convenient form; by is a list of grouping elements, each as long as the variables in x

**stack(x, ...)** transform data available as separate columns in a data frame or list into a single column

**unstack(x, ...)** inverse of `stack()`

**reshape(x, ...)** reshapes a data frame between ‘wide’ format with repeated measurements in separate columns of the same record and ‘long’ format with the repeated measurements in separate records; use (direction=“wide”) or (direction=“long”)

Strings

**paste(...)** concatenate vectors after converting to character; `sep=` is the string to separate terms (a single space is the default); `collapse=` is an optional string to separate “collapsed” results

**substr(x,start,stop)** substrings in a character vector; can also assign, as `substr(x, start, stop) <- value`

**strsplit(x,split)** split x according to the substring split

**grep(pattern,x)** searches for matches to pattern within x; see `?regex`

**gsub(pattern,replacement,x)** replacement of matches determined by regular expression matching `sub()` is the same but only replaces the first occurrence.

**tolower(x)** convert to lowercase

**toupper(x)** convert to uppercase

**match(x,table)** a vector of the positions of first matches for the elements of x among table

**x %in% table** id. but returns a logical vector

**pmatch(x,table)** partial matches for the elements of x among table

**nchar(x)** number of characters

Dates and Times

The class `Date` has dates without times. `POSIXct` has dates and times, including time zones. Comparisons (e.g. `>`), `seq()`, and `difftime()` are useful. `Date` also allows `+` and `-`. `?DateTimeClasses` gives more information. See also package `chron`.

**as.Date(s)** and **as.POSIXct(s)** convert to the respective class; `format(dt)` converts to a string representation. The default string format is “2001-02-21”. These accept a second argument to specify a format for conversion. Some common formats are:

- %a, %A Abbreviated and full weekday name.
- %b, %B Abbreviated and full month name.
- %d Day of the month (01–31).
- %H Hours (00–23).
- %I Hours (01–12).
- %j Day of year (001–366).
- %m Month (01–12).
- %M Minute (00–59).
- %p AM/PM indicator.
- %S Second as decimal number (00–61).
- %U Week (00–53); the first Sunday as day 1 of week 1.
- %w Weekday (0–6, Sunday is 0).
- %W Week (00–53); the first Monday as day 1 of week 1.
- %y Year without century (00–99). Don’t use.
- %Y Year with century.
- %z (output only.) Offset from Greenwich; -0800 is 8 hours west of.
- %Z (output only.) Time zone as a character string (empty if not available).

Where leading zeros are shown they will be used on output but are optional on input. See `?strftime`.

Plotting

**plot(x)** plot of the values of x (on the y-axis) ordered on the x-axis

**plot(x, y)** bivariate plot of x (on the x-axis) and y (on the y-axis)

**hist(x)** histogram of the frequencies of x

**barplot(x)** histogram of the values of x; use `horiz=FALSE` for horizontal bars

**dotchart(x)** if x is a data frame, plots a Cleveland dot plot (stacked plots line-by-line and column-by-column)

**pie(x)** circular pie-chart

**boxplot(x)** “box-and-whiskers” plot

**sunflowerplot(x, y)** id. than `plot()` but the points with similar coordinates are drawn as flowers which petal number represents the number of points

**stripplot(x)** plot of the values of x on a line (an alternative to `boxplot()` for small sample sizes)

**coplot(x~y | z)** bivariate plot of x and y for each value or interval of values of z

**interaction.plot(f1, f2, y)** if f1 and f2 are factors, plots the means of y (on the y-axis) with respect to the values of f1 (on the x-axis) and of f2 (different curves); the option `fun` allows to choose the summary statistic of y (by default `fun=mean`)

**matplot(x,y)** bivariate plot of the first column of x vs. the first one of y, the second one of x vs. the second one of y, etc.

**fourfoldplot(x)** visualizes, with quarters of circles, the association between two dichotomous variables for different populations (x must be an array with dim=c(2, 2, k), or a matrix with dim=c(2, 2) if k = 1)

**assocplot(x)** Cohen–Friendly graph showing the deviations from independence of rows and columns in a two dimensional contingency table

**mosaicplot(x)** ‘mosaic’ graph of the residuals from a log-linear regression of a contingency table

**pairs(x)** if x is a matrix or a data frame, draws all possible bivariate plots between the columns of x

**plot.ts(x)** if x is an object of class "ts", plot of x with respect to time, x may be multivariate but the series must have the same frequency and dates

**ts.plot(x)** id. but if x is multivariate the series may have different dates and must have the same frequency

**qqnorm(x)** quantiles of x with respect to the values expected under a normal law

**qqplot(x, y)** quantiles of y with respect to the quantiles of x

**contour(x, y, z)** contour plot (data are interpolated to draw the curves), x and y must be vectors and z must be a matrix so that dim(z)=c(length(x), length(y)) (x and y may be omitted)

**filled.contour(x, y, z)** id. but the areas between the contours are coloured, and a legend of the colours is drawn as well

**image(x, y, z)** id. but with colours (actual data are plotted)

**persp(x, y, z)** id. but in perspective (actual data are plotted)

**stars(x)** if x is a matrix or a data frame, draws a graph with segments or a star where each row of x is represented by a star and the columns are the lengths of the segments

**symbols(x, y, ...)** draws, at the coordinates given by x and y, symbols (circles, squares, rectangles, stars, thermometres or “boxplots”) which sizes, colours ... are specified by supplementary arguments

**termpplot(mod.obj)** plot of the (partial) effects of a regression model (mod.obj)

The following parameters are common to many plotting functions:

**add=FALSE** if TRUE superposes the plot on the previous one (if it exists)

**axes=TRUE** if FALSE does not draw the axes and the box

**type="p"** specifies the type of plot, "p": points, "l": lines, "b": points connected by lines, "o": id. but the lines are over the points, "h": vertical lines, "s": steps, the data are represented by the top of the vertical lines, "S": id. but the data are represented by the bottom of the vertical lines

**xlim=, ylim=** specifies the lower and upper limits of the axes, for example plot(xlim=c(1, 10) or xlim=range(x))

**xlab=, ylab=** annotates the axes, must be variables of mode character

**main=** main title, must be a variable of mode character

**sub=** sub-title (written in a smaller font)

## Low-level plotting commands

**points(x, y)** adds points (the option type= can be used)

**lines(x, y)** id. but with lines

**text(x, y, labels, ...)** adds text given by labels at coordinates (x,y); a typical use is: plot(x, y, type="n"); text(x, y, names)

**mtext(text, side=3, line=0, ...)** adds text given by text in the margin specified by side (see axis() below); line specifies the line from the plotting area

**segments(x0, y0, x1, y1)** draws lines from points (x0,y0) to points (x1,y1)

**arrows(x0, y0, x1, y1, angle= 30, code=2)** id. with arrows at points (x0,y0) if code=2, at points (x1,y1) if code=1, or both if code=3; angle controls the angle from the shaft of the arrow to the edge of the arrow head

**abline(a,b)** draws a line of slope b and intercept a

**abline(h=y)** draws a horizontal line at ordinate y

**abline(v=x)** draws a vertical line at abscissa x

**abline(lm.obj)** draws the regression line given by lm.obj

**rect(x1, y1, x2, y2)** draws a rectangle which left, right, bottom, and top limits are x1, x2, y1, and y2, respectively

**polygon(x, y)** draws a polygon linking the points with coordinates given by x and y

**legend(x, y, legend)** adds the legend at the point (x,y) with the symbols given by legend

**title()** adds a title and optionally a sub-title

**axis(side, vect)** adds an axis at the bottom (side=1), on the left (2), at the top (3), or on the right (4); vect (optional) gives the abscissa (or ordinates) where tick-marks are drawn

**rug(x)** draws the data x on the x-axis as small vertical lines

**locator(n, type="n", ...)** returns the coordinates (x,y) after the user has clicked n times on the plot with the mouse; also draws symbols (type="p") or lines (type="l") with respect to optional graphic parameters (...); by default nothing is drawn (type="n")

## Graphical parameters

These can be set globally with **par(...)**; many can be passed as parameters to plotting commands.

**adj** controls text justification (0 left-justified, 0.5 centred, 1 right-justified)

**bg** specifies the colour of the background (ex. : bg="red", bg="blue", ... the list of the 657 available colours is displayed with colors())

**bty** controls the type of box drawn around the plot, allowed values are: "o", "l", "7", "c", "u" ou "j" (the box looks like the corresponding character); if bty="n" the box is not drawn

**cex** a value controlling the size of texts and symbols with respect to the default; the following parameters have the same control for numbers on the axes, cex.axis, the axis labels, cex.lab, the title, cex.main, and the sub-title, cex.sub

**col** controls the color of symbols and lines; use color names: "red", "blue" see colors() or as "#RRGGBB"; see rgb(), hsv(), gray(), and rainbow(); as for cex there are: col.axis, col.lab, col.main, col.sub

**font** an integer which controls the style of text (1: normal, 2: italics, 3: bold, 4: bold italics); as for cex there are: font.axis, font.lab, font.main, font.sub

**las** an integer which controls the orientation of the axis labels (0: parallel to the axes, 1: horizontal, 2: perpendicular to the axes, 3: vertical)

**lty** controls the type of lines, can be an integer or string (1: "solid", 2: "dashed", 3: "dotted", 4: "dotdash", 5: "longdash", 6: "twodash", or a string of up to eight characters (between "0" and "9") which specifies alternatively the length, in points or pixels, of the drawn elements and the blanks, for example lty="44" will have the same effect than lty=2

**lwd** a numeric which controls the width of lines, default 1

**mar** a vector of 4 numeric values which control the space between the axes and the border of the graph of the form c(bottom, left, top, right), the default values are c(5.1, 4.1, 4.1, 2.1)

**mfcol** a vector of the form c(nr,nc) which partitions the graphic window as a matrix of nr lines and nc columns, the plots are then drawn in columns

**mfrow** id. but the plots are drawn by row

**pch** controls the type of symbol, either an integer between 1 and 25, or any single character within ""

1 ○ 2 △ 3 + 4 × 5 ◇ 6 ▽ 7 ⊗ 8 ✱ 9 ⊕ 10 ⊕ 11 ✎ 12 ⊞ 13 ⊞ 14 ⊞ 15 ■  
16 ● 17 ▲ 18 ◆ 19 ● 20 ● 21 ○ 22 □ 23 ◇ 24 △ 25 ▽ \* · . · X X a a ? ?

**ps** an integer which controls the size in points of texts and symbols

**pty** a character which specifies the type of the plotting region, "s": square, "m": maximal

**tick** a value which specifies the length of tick-marks on the axes as a fraction of the smallest of the width or height of the plot; if tick=1 a grid is drawn

**tc1** a value which specifies the length of tick-marks on the axes as a fraction of the height of a line of text (by default tc1=-0.5)

**xaxt** if xaxt="n" the x-axis is set but not drawn (useful in conjunction with axis(side=1, ...))

**yaxt** if yaxt="n" the y-axis is set but not drawn (useful in conjunction with axis(side=2, ...))

## Lattice (Trellis) graphics

**xyplot(y~x)** bivariate plots (with many functionalities)

**barchart(y~x)** histogram of the values of y with respect to those of x

**dotplot(y~x)** Cleveland dot plot (stacked plots line-by-line and column-by-column)

**densityplot(~x)** density functions plot

**histogram(~x)** histogram of the frequencies of x

**bwplot(y~x)** “box-and-whiskers” plot

**qqmath(~x)** quantiles of x with respect to the values expected under a theoretical distribution

**stripplot(y~x)** single dimension plot, x must be numeric, y may be a factor

**qq(y~x)** quantiles to compare two distributions, x must be numeric, y may be numeric, character, or factor but must have two ‘levels’

**splo(m~x)** matrix of bivariate plots

**parallel(~x)** parallel coordinates plot

**levelplot(z~x\*y|g1\*g2)** coloured plot of the values of z at the coordinates given by x and y (x, y and z are all of the same length)

**wireframe(z~x\*y|g1\*g2)** 3d surface plot

**cloud(z~x\*y|g1\*g2)** 3d scatter plot

In the normal Lattice formula,  $y \sim x|g1 \sim g2$  has combinations of optional conditioning variables  $g1$  and  $g2$  plotted on separate panels. Lattice functions take many of the same arguments as base graphics plus also `data=` the data frame for the formula variables and `subset=` for subsetting. Use `panel=` to define a custom panel function (see `apropos("panel")` and `?llines`). Lattice functions return an object of class `trellis` and have to be printed to produce the graph. Use `print(xyplot(...))` inside functions where automatic printing doesn't work. Use `lattice.theme` and `lset` to change Lattice defaults.

## Optimization and model fitting

**optim(par, fn, method = c("Nelder-Mead", "BFGS", "CG", "L-BFGS-B", "SANN"))** general-purpose optimization; `par` is initial values, `fn` is function to optimize (normally minimize)  
**nlm(f, p)** minimize function `f` using a Newton-type algorithm with starting values `p`

**lm(formula)** fit linear models; formula is typically of the form `response termA + termB + ...`; use `I(x*y)` + `I(x^2)` for terms made of nonlinear components

**glm(formula, family=)** fit generalized linear models, specified by giving a symbolic description of the linear predictor and a description of the error distribution; `family` is a description of the error distribution and link function to be used in the model; see `?family`

**nls(formula)** nonlinear least-squares estimates of the nonlinear model parameters

**approx(x, y=)** linearly interpolate given data points; `x` can be an `xy` plotting structure

**spline(x, y=)** cubic spline interpolation

**loess(formula)** fit a polynomial surface using local fitting

Many of the formula-based modeling functions have several common arguments: `data=` the data frame for the formula variables, `subset=` a subset of variables used in the fit, `na.action=` action for missing values: `"na.fail"`, `"na.omit"`, or a function. The following generics often apply to model fitting functions:

**predict(fit, ...)** predictions from `fit` based on input data

**df.residual(fit)** returns the number of residual degrees of freedom

**coef(fit)** returns the estimated coefficients (sometimes with their standard-errors)

**residuals(fit)** returns the residuals

**deviance(fit)** returns the deviance

**fitted(fit)** returns the fitted values

**logLik(fit)** computes the logarithm of the likelihood and the number of parameters

**AIC(fit)** computes the Akaike information criterion or AIC

## Statistics

**aov(formula)** analysis of variance model

**anova(fit, ...)** analysis of variance (or deviance) tables for one or more fitted model objects

**density(x)** kernel density estimates of `x`

**binom.test()**, **pairwise.t.test()**, **power.t.test()**, **prop.test()**, **t.test()**, ... use `help.search("test")`

## Distributions

**rnorm(n, mean=0, sd=1)** Gaussian (normal)

**rexp(n, rate=1)** exponential

**rgamma(n, shape, scale=1)** gamma

**rpois(n, lambda)** Poisson

**rweibull(n, shape, scale=1)** Weibull

**rcauchy(n, location=0, scale=1)** Cauchy

**rbeta(n, shape1, shape2)** beta

**rt(n, df)** 'Student' ( $t$ )

**rf(n, df1, df2)** Fisher-Snedecor ( $F$ ) ( $\chi^2$ )

**rchisq(n, df)** Pearson

**rbinom(n, size, prob)** binomial

**rgeom(n, prob)** geometric

**rhyper(nn, m, n, k)** hypergeometric

**rlogis(n, location=0, scale=1)** logistic

**rlnorm(n, meanlog=0, sdlog=1)** lognormal

**rnbinom(n, size, prob)** negative binomial

**runif(n, min=0, max=1)** uniform

**rwilcox(nn, m, n), rsignrank(nn, n)** Wilcoxon's statistics

All these functions can be used by replacing the letter `r` with `d`, `p` or `q` to get, respectively, the probability density (`dfunc(x, ...)`), the cumulative probability density (`pfunc(x, ...)`), and the value of quantile (`qfunc(p, ...)`), with  $0 < p < 1$ .

## Programming

**function( arglist ) expr** function definition

**return(value)**

**if(cond) expr**

**if(cond) cons.expr else alt.expr**

**for(var in seq) expr**

**while(cond) expr**

**repeat expr**

**break**

**next**

Use braces `{}` around statements

**ifelse(test, yes, no)** a value with the same shape as `test` filled with elements from either `yes` or `no`

**do.call(funname, args)** executes a function call from the name of the function and a list of arguments to be passed to it