


Аппаратный генератор углов v0.01.  
Техническое справочное руководство.

**Suppression Filter Compare Register (HWASFCR)**

Offset = 00h



LEGEND: R/W = Read/Write; -n = value after reset

Bit	Field	Value	Description
15-0	SFCR		Counter Compare Value

Global Configuration Set Register 0 (HWAGCSR0)

Offset = 80h

Global Configuration Set Register 0 (HWAGCSR0)



LEGEND: R/W = Read/Write; -n = value after reset

Bit	Field	Value	Description
2	SFLTE	0	Suppression Filter Enable. Read: Suppression Filter is disabled. Write: Writes have no effect.
		1	Read: Suppression Filter is enabled. Write: Suppression Filter is enabled.
1	EDGES	0	Edge Select. Read: Rise edge selected. Write: Writes have no effect.
		1	Read: Fall edge selected. Write: Fall edge selected.
0	CAPE	0	Capture Enable. Read: Capture disabled. Write: Writes have no effect.
		1	Read: Capture enabled. Write: Capture enabled.

**Global Configuration Clear Register 0 (HWAGCCR0)**

Offset = 82h

**Global Configuration Clear Register 0 (HWAGCCR0)**

--	--	--	--	--	--	--	--

7	6	5	4	3	2	1	0
					SFLTE	EDGES	CAPE
R/W-0	R/W-0	R/W-0	R/W-0	R/W-0	R/W-0	R/W-0	R/W-0


LEGEND: R/W = Read/Write; -n = value after reset

Bit	Field	Value	Description
2	SFLTE	0 1	Suppression Filter Enable. Read: Suppression Filter is disabled. Write: Writes have no effect. Read: Suppression Filter is enabled. Write: Suppression Filter is disabled.
1	EDGES	0 1	Edge Select. Read: Rise edge selected. Write: Writes have no effect. Read: Fall edge selected. Write: Rise edge selected.
0	CAPE	0 1	Capture Enable. Read: Capture disabled. Write: Writes have no effect. Read: Capture enabled. Write: Capture disabled.

Interrupt Enable Set Register (HWAIESR)

Offset = 84h

Interrupt Enable Set Register (HWAIESR)




LEGEND: R/W = Read/Write; -n = value after reset

Bit	Field	Value	Description
2		0 1	Read: Write: Writes have no effect. Read: Write:
1		0 1	Read: Write: Writes have no effect. Read: Write:
0	CAPIE	0 1	Capture Interrupt Enable. Read: Capture Interrupt disabled. Write: Writes have no effect. Read: Capture Interrupt enabled. Write: Capture Interrupt enabled.

Interrupt Enable Clear Register (HWAIECR)

Offset = 86h

Interrupt Enable Clear Register (HWAIECR)




LEGEND: R/W = Read/Write; -n = value after reset

Bit	Field	Value	Description
2		0 1	Read: Write: Writes have no effect. Read: Write:
1		0 1	Read: Write: Writes have no effect. Read: Write:
0	CAPIE	0 1	Capture Interrupt Enable. Read: Capture Interrupt disabled. Write: Writes have no effect. Read: Capture Interrupt enabled. Write: Capture Interrupt disabled.

Interrupt Flag Register (HWAIFR)

Offset = 88h

Interrupt Flag Register (HWAIFR)



LEGEND: R/W = Read/Write; -n = value after reset

Bit	Field	Value	Description
2		0 1	Read: Write: Writes have no effect. Read: Write:
1		0 1	Read: Write: Writes have no effect. Read: Write:
0	CAPIF	0 1	Capture Interrupt Flag. Read: No interrupt is pending. Write: Writes have no effect. Read: Capture Interrupt is pending. Write: Clear capture interrupt flag.