Perforce P4Prometheus - Installation Guide

Perforce Professional Services

Version v2026.1, 2026-09-15

Table of Contents

Preface . . . 1
1. Deployment Roles . . . 2
1.1. Expected systemd Services by Role . . . 2
1.2. Combined-Role Hosts . . . 2
2. Automated Installation . . . 4
2.1. Updating config files for new installation . . . 4
2.2. Script Reference . . . 5
2.2.1. install_prom_graf.sh . . . 5
2.2.2. update_prom_graf.sh . . . 6
2.2.3. install_p4prom.sh . . . 6
2.2.4. update_p4prom.sh . . . 7
2.2.5. install_node.sh . . . 8
2.2.6. install_lslocks.sh . . . 9
2.2.7. migrate_prom_graf_data.sh . . . 10
2.3. Upgrades . . . 10
3. Enterprise Options . . . 11
3.1. Dedicated Data Volume . . . 11
3.1.1. What `-d` does and does not relocate . . . 11
3.2. Retention, Binaries, and Targets . . . 12
3.3. Air-Gapped Installation . . . 12
3.4. Install State and Fleet Configuration . . . 12
4. Verify Installation . . . 13
4.1. Troubleshooting . . . 13
4.1.1. On monitoring server . . . 13
4.1.1.1. prometheus . . . 13
4.1.1.2. Victoria Metrics . . . 14
4.1.1.3. Grafana . . . 14
4.1.2. On p4d servers . . . 14
4.1.2.1. p4prometheus . . . 14
4.1.2.2. p4metrics . . . 15
4.1.2.3. node exporter . . . 15
5. Manual Installation . . . 16
5.1. Install Prometheus . . . 16
5.1.1. Prometheus config . . . 17
5.2. Install victoria metrics (optional but recommended) . . . 18
5.3. Package Installation of Grafana . . . 20
5.3.1. Create your first Data Source . . . 20
5.3.2. Setup of Grafana dashboards . . . 20

5.3.3. Script to create Grafana dashboard . . . 21
5.3.4. Substituting Victoria Metrics for Prometheus in Grafana . . . 22
5.3.5. Importing Prometheus data into Victoria Metrics . . . 22
5.4. Install node exporter . . . 22
5.5. Install p4prometheus - details . . . 24
5.6. Install p4metrics and monitor_locks systemd timer services . . . 27
5.6.1. Checking for blocked commands . . . 27
5.6.2. Start and enable service . . . 28
5.7. Alerting . . . 28
5.7.1. Alertmanager config . . . 30
5.7.2. Alerting rules . . . 30
5.7.2.1. Split-file alerting rules (recommended) . . . 30
Template-based custom rules . . . 31
5.7.3. Prometheus config to reference alertmanager rules . . . 32
5.8. Advanced config options . . . 32
5.9. Windows Installation . . . 33
5.9.1. Windows Exporter . . . 33
5.9.2. P4prometheus on Windows . . . 33
5.9.3. Running p4metrics . . . 34
5.9.4. Installing Programs as Services . . . 34

Preface

P4Prometheus installation is automated (on Linux) by the scripts in scripts/. Manual component installation is retained in Chapter 5, *Manual Installation* for environments where automation cannot be used (including Windows).

© 2021 Perforce Software, Inc.

Chapter 1. Deployment Roles

Install the following components for each role:

Role	Installer and components
Monitoring server	install_prom_graf.sh: Grafana, Prometheus, VictoriaMetrics, node_exporter, Alertmanager, and optional Pushgateway and Pint.
Helix Core server	install_p4prom.sh: node_exporter, p4prometheus, p4metrics, and lock-monitoring scripts.
Other monitored server	install_node.sh: node_exporter only, for example on Swarm, Hansoft, or Helix TeamHub hosts.

1.1. Expected systemd Services by Role

Use this table to confirm which services should be running (`systemctl status <service>`) on a given machine after installation:

Role	systemd services (installed/enabled by the installer)
Monitoring server	`node_exporter`, `prometheus`, `victoria-metrics`, `alertmanager`, `grafana-server` (package-managed), and optionally `pushgateway` (`-push`) and `pint` (`-pint`)
Helix Core server	`node_exporter`, `p4prometheus`, `p4metrics`, `p4monitor_locks.timer` (which runs `p4monitor_locks.service`), and optionally `vmagent` (with `-push`)
Other monitored server (Swarm, Hansoft, HTH, etc.)	`node_exporter` only



Only `node_exporter` runs on "other monitored server" hosts; there is no p4prometheus, p4metrics, or monitoring-stack component to install there.

1.2. Combined-Role Hosts

Some hosts serve more than one role, e.g. a Helix Core replica that also runs Swarm. Do **not** run `install_node.sh` on a host where `install_p4prom.sh` has already been (or will be) run: both scripts install and manage `node_exporter`. `install_node.sh` replaces `/etc/systemd/system/node_exporter.service` with its own definition (binary in `/usr/local/bin`, textfile directory `/var/metrics`). The `p4_*` metrics written by p4prometheus and p4metrics then silently stop being exported the next time `node_exporter` restarts, with no error. If this happens, re-run `install_p4prom.sh` (or `update_p4prom.sh`), then run `systemctl daemon-reload && systemctl restart node_exporter`.

For a combined Helix Core + Swarm (or other monitored application) host:

- Run only `install_p4prom.sh` (it already installs `node_exporter`).

© 2021 Perforce Software, Inc.

- Ensure the `node_exporter --collector.textfile.directories` value covers metrics written by any other locally-run application (this project only writes p4prometheus/p4metrics `.prom` files, so metrics from Swarm, etc. would require their own textfile-collector export mechanism configured separately).
- Run `update_p4prom.sh` for upgrades on this host; do not additionally run `update_node.sh`.

© 2021 Perforce Software, Inc.

Chapter 2. Automated Installation

Run the relevant installer as `root`. Download the script from a checkout, or download its raw GitHub URL, make it executable, and review the available options before installing.

`p4prom_common.sh` is a shared library required by all four install/update scripts (`install_prom_graf.sh`, `update_prom_graf.sh`, `install_p4prom.sh`, `update_p4prom.sh`). If missing, each script attempts to auto-download it from `master` on GitHub — but this will fail on a host with no internet access. Always download `p4prom_common.sh` into the same directory as whichever script you are running, especially for air-gapped installs (see Section 3.3, “Air-Gapped Installation”).

For the monitoring server:

```
wget
https://raw.githubusercontent.com/perforce/p4prometheus/master/scripts/install_prom_gr
af.sh
wget
https://raw.githubusercontent.com/perforce/p4prometheus/master/scripts/p4prom_common.s
h
chmod +x install_prom_graf.sh
./install_prom_graf.sh -h
```

For a Helix Core server, download `install_p4prom.sh` together with `p4prom_common.sh` into the same directory:

```
wget
https://raw.githubusercontent.com/perforce/p4prometheus/master/scripts/install_p4prom.
sh
wget
https://raw.githubusercontent.com/perforce/p4prometheus/master/scripts/p4prom_common.s
h
chmod +x install_p4prom.sh
./install_p4prom.sh -h

# SDP instance 1
./install_p4prom.sh 1
```

For a non-SDP server, use `./install_p4prom.sh -nosdp -h` to review the required connection and path options before installing.

2.1. Updating config files for new installation

The following files will typically need to be updated for your environment:

see docs on examples with links to configuration files

© 2021 Perforce Software, Inc.

2.2. Script Reference

2.2.1. install_prom_graf.sh

This section provides a reference for the `install_prom_graf.sh` script, including usage and available options.

Usage

```
   echo "USAGE for install_prom_graf.sh:

    install_prom_graf.sh [-d <data_root>] [-b <bin_dir>] [-r <months>]
                         [-target <host:port>] [-grafana-setup]
                         [--local-tarballs-dir <path>]
                         [-push] [-pint]

or

    install_prom_graf.sh -h

    -d <data_root>          Base directory for all runtime data.
                            Default: /var/lib
                            Example: -d /data  (puts all data under /data/)
    -b <bin_dir>            Directory for installed binaries.
                            Default: /usr/local/bin
    -r <months>             Metrics retention period in months (for use with
VictoriaMetrics).
                            Not used by Prometheus itself, which has a short retention
setting.
                            Default: 6
    -target <host:port>     Prometheus scrape target. Repeatable.
                            Example: -target myserver:9100 -target otherserver:9100
                            If not specified, a placeholder is written to
prometheus.yml.
    -grafana-setup          Create Grafana datasource for Victoria Metrics and
                            import recommended dashboards from INSTALL.md.
    --local-tarballs-dir <p>  Directory containing pre-staged release tarballs.
                            Skips all downloads - for air-gapped environments.
                            Files must match GitHub release asset names exactly.
    -push                   Install Pushgateway (not installed by default).
                            This is generally deprecated in favor of using VMAgent
remotely.
    -pint                   Install Pint linter and create pint.service
                            for continuous validation of
/etc/prometheus/perforce_rules.yml.

Example:

    sudo ./install_prom_graf.sh -d /data -b /opt/bin -r 12 -target myserver:9100
-grafana-setup
```

© 2021 Perforce Software, Inc.

```
    sudo ./install_prom_graf.sh -grafana-setup
    sudo ./install_prom_graf.sh -d /data -target myp4:9100 -target myreplica:9100
-grafana-setup
    sudo ./install_prom_graf.sh -pint
"
```

2.2.2. update_prom_graf.sh

Updates the monitoring server while preserving paths and options stored by `install_prom_graf.sh`.

Usage

```
   echo "USAGE for update_prom_graf.sh:

    update_prom_graf.sh [-d <data_root>] [-b <bin_dir>] [-r <months>]
                        [--local-tarballs-dir <path>] [-push]

or

    update_prom_graf.sh -h

    -d <data_root>          Base directory for runtime data (prometheus, alertmanager,
etc.)
                            Loaded automatically from state file if not specified.
    -b <bin_dir>            Binary installation directory.
                            Loaded automatically from state file if not specified.
    -r <months>             Metrics retention period in months for
VictoriaMetrics/Prometheus.
                            Loaded automatically from state file if not specified.
    --local-tarballs-dir <p> Directory of pre-staged release tarballs (air-gap
installs).
                            Skips all downloads; file names must match GitHub release
assets.
    -push                   Update Pushgateway if installed (not updated by default).

Note: If /etc/p4prometheus-monitoring/install.env exists from a prior
  install_prom_graf.sh run, all paths and settings are loaded from it automatically.

"
```

2.2.3. install_p4prom.sh

Installs node_exporter, p4prometheus, p4metrics, and lock monitoring on a Helix Core server.

Usage

```
    echo "USAGE for install_p4prom.sh:

install_p4prom.sh [<instance> | -nosdp] [-m <metrics_root>] [-osuser <osuser>]
        [-p <P4PORT>] [-u <p4user>] [-c <p4prom_config_dir>]
```


© 2021 Perforce Software, Inc.

```
        [-b <bin_dir>] [--local-tarballs-dir <path>] [-push]

   or

install_p4prom.sh -h

    <metrics_root>        Directory where metrics will be written - default:
$metrics_root
    <osuser>              OS user running p4d; used for file ownership and crontab
    <P4PORT>              P4PORT to use within installed scripts
    <P4USER>              P4USER to use within installed scripts
    <p4prom_config_dir>   Directory for p4prometheus config files (non-SDP installs)
                          Default: /etc/p4prometheus
    -b <bin_dir>          Directory for installed binaries - default: $local_bin_dir
    --local-tarballs-dir  Directory of pre-staged release tarballs (air-gap installs).
                          Skips all downloads; file names must match GitHub release
assets.
    -push                 Install vmagent service/configuration in /var/vmagent.
                          Not relevant for most installations.

IMPORTANT: Specify either the installed SDP instance (e.g. 1), or -nosdp and other
parameters

WARNING: If using -nosdp, ensure P4PORT and P4USER are provided or set in environment,
    and that you can connect (e.g. 'p4 trust' done, already logged in)

Examples:

./install_p4prom.sh 1
./install_p4prom.sh hw
./install_p4prom.sh -nosdp -m /p4metrics -u perforce -p 1666 -u p4admin -c
/p4/p4prometheus

"
```

2.2.4. update_p4prom.sh

Updates the monitoring components installed on a Helix Core server.

Usage

```
    echo "USAGE for update_p4prom.sh:

update_p4prom.sh [<instance> | -nosdp] [-m <metrics_root>] [-l <metrics_link>]
                 [-u <osuser>] [-c <p4prom_config_dir>] [-b <bin_dir>]
                 [--local-tarballs-dir <path>]

   or

update_p4prom.sh -h
```

```
    <metrics_root>        Directory where metrics are written - default: $metrics_root
    <metrics_link>        Symlink to metrics_root (SDP installs only) - default:
$metrics_link
    <osuser>              OS user running p4d (e.g. perforce)
    <p4prom_config_dir>   Config file directory (non-SDP installs) - default:
/etc/p4prometheus
    -b <bin_dir>          Binary installation directory - default: $local_bin_dir
    --local-tarballs-dir  Directory of pre-staged release tarballs (air-gap installs).
                          Skips all downloads; file names must match GitHub release
assets.
    -vmagent              Install vmagent to replace legacy push_metrics cron jobs.
                          Intended for P4RA only. Migrates a valid .push_metrics.cfg,
                          preserves a complete existing configuration, or creates
                          placeholder files for review before starting vmagent.

Specify either the SDP instance (e.g. 1), or -nosdp

WARNING: If using -nosdp, ensure P4PORT and P4USER are set and you can connect
    (e.g. 'p4 trust' done, already logged in)

Note: If a p4prom_install.env state file exists from a prior install_p4prom.sh
    run, paths are loaded from it automatically. CLI flags always override.

Examples:

./update_p4prom.sh 1
./update_p4prom.sh -nosdp -m /p4metrics -u perforce -c /etc/p4prometheus

"
```

2.2.5. install_node.sh

Installs node_exporter on another monitored host, such as a Swarm, Hansoft, or Helix TeamHub server.

Usage

```
    echo "USAGE for install_node.sh:

install_node.sh [-m <metrics_root>] [-push]

   or

install_node.sh -h

    <metrics_root>  is the directory where metrics will be written - default:
$metrics_root
    -push           Means install pushgateway cronjob and config file.
```


© 2021 Perforce Software, Inc.

```
This expects to be run as root/sudo. If -push is specified then a crontab entry will
be written.

Examples:

./install_node.sh
./install_node.sh -m /p4metrics
./install_node.sh -m /p4metrics -push

"
```

2.2.6. install_lslocks.sh

Installs lock monitoring only, without the full Helix Core monitoring stack.

Usage

```
    echo "USAGE for install_lslocks.sh:

install_lslocks.sh [<instance> | -nosdp] [-m <metrics_root>] [-osuser <osuser>]
        [-p <P4PORT>] [-u <p4user>]

   or

install_lslocks.sh -h

    <metrics_root>  is the directory where metrics will be written - default:
$metrics_root
    <osuser>        Operating system user, e.g. perforce, under which p4d process is
running and to install crontab
    <P4PORT>        P4PORT to use within any installed scripts
    <P4USER>        P4USER to use within any installed scripts

IMPORTANT: Specify either the SDP instance (e.g. 1), or -nosdp and other parameters

WARNING: If using -nosdp, then please ensure P4PORT and P4USER are provided or are
appropriately set and that you can connect
    to your server (e.g. you have done a 'p4 trust' if required, and logged in
already)

Examples:

./install_lslocks.sh 1
./install_lslocks.sh -nosdp -osuser perforce -m /p4metrics -p 1666 -u p4admin

"
```

2.2.7. migrate_prom_graf_data.sh

Moves existing monitoring-server data to a different base directory without a full reinstall.

Usage

```
# Usage:
#   migrate_prom_graf_data.sh -d <new_data_root> [--dry-run] [--cleanup-old]
#
# Flags:
#   -d <new_data_root>   REQUIRED. New base directory (e.g. /data or /hxdata)
#   --dry-run            Show what would be done; make no changes
#   --cleanup-old        After successful migration, remove old data directories
#                        (default: leave originals; safe to re-run)
#   -h, --help           Show this usage text
#
# Preflight checks performed:
#   - New data root is on a writable filesystem
#   - Sufficient free space at destination (current usage + 10% headroom)
#   - All affected services are present (will be stopped/started)
#   - No source/dest overlap
#
# Services stopped for migration (then restarted):
#   prometheus, alertmanager, victoria-metrics, grafana-server, pushgateway
#
# After migration:
#   - /etc/grafana/grafana.ini [paths.data] is updated
#   - Systemd service files are regenerated with new paths
#   - State file is updated with new DATA_ROOT
#   - Old directories are left intact (renamed with .migrated-YYYYMMDD suffix)
#     unless --cleanup-old is passed
#
# Recovery:
#   If this script is interrupted, old data is still in place.  Simply run
#   migrate_prom_graf_data.sh again; it will skip components whose data has
#   already been moved.
```

2.3. Upgrades

In an SDP environment, run the update checker as the `perforce` user:

```
cd /p4/common/site/bin
./check_for_updates.sh
sudo ./update_p4prom.sh 1
```

For very old installations where `update_p4prom.sh` was not downloaded, remove `.update_config` and rerun `check_for_updates.sh`. Alternatively, download update_p4prom.sh directly, review `-h`, and run it as `root`.

© 2021 Perforce Software, Inc.

Chapter 3. Enterprise Options

All install and update scripts support a common set of options. Run the appropriate script with `-h` for the complete list.

3.1. Dedicated Data Volume

Use `-d` to keep monitoring data on a dedicated volume:

```
sudo ./install_prom_graf.sh -d /data
sudo ./update_prom_graf.sh
```



The `-d` (and `-b`) path must already exist (e.g. a volume you have deliberately created or mounted) before running the installer. The scripts will fail with an error rather than create missing top-level paths automatically — this avoids silently writing data to the root filesystem if an intended dedicated volume failed to mount.

The selected path is retained in `/etc/p4prometheus-monitoring/install.env`. To move an existing installation, use:

```
sudo ./migrate_prom_graf_data.sh -d /data --dry-run
sudo ./migrate_prom_graf_data.sh -d /data
sudo ./migrate_prom_graf_data.sh -d /data --cleanup-old
```

3.1.1. What `-d` does and does not relocate

`-d` relocates the runtime **data** directories only (Prometheus TSDB, VictoriaMetrics storage, Alertmanager state, Grafana's data directory, Pushgateway persistence file). It does **not** move package/config files, which always remain under `/etc/ and /usr/share/` regardless of `-d`:

Path	Contents (never relocated by `-d`)
`/etc/grafana/grafana.ini`	Grafana's own config file (it is edited in place to **point at** the relocated data dir, but the file itself stays here)
`/etc/prometheus/prometheus.yml`, `/etc/prometheus/perforce_rules*.yml`	Prometheus configuration and alerting rules
`/etc/alertmanager/alertmanager.yml`	Alertmanager configuration
`/usr/share/grafana/`	Grafana application files (package-managed)
`/etc/p4prometheus-monitoring/install.env`	Installer state file read by `update_prom_graf.sh` (records the `-d`/`-b` choices)
`/etc/systemd/system/*.service`	systemd unit files (fixed location by systemd convention)

© 2021 Perforce Software, Inc.

3.2. Retention, Binaries, and Targets

```
# Retain metrics for 12 months and use a custom binary directory.
sudo ./install_prom_graf.sh -d /data -r 12 -b /opt/monitoring/bin

# Add scrape targets during installation.
sudo ./install_prom_graf.sh -target myp4server:9100 -target replica1:9100
```

3.3. Air-Gapped Installation

Download the required GitHub release assets on a connected machine, transfer them to the target, then pass their directory with `--local-tarballs-dir`:

```
sudo ./install_prom_graf.sh -d /data --local-tarballs-dir /opt/installers
sudo ./install_p4prom.sh --local-tarballs-dir /opt/installers
```

`p4prom_common.sh` must be pre-staged alongside whichever script you are running on an air-gapped host — this applies to all four scripts (`install_prom_graf.sh`, `update_prom_graf.sh`, `install_p4prom.sh`, `update_p4prom.sh`), not just the Helix Core server ones. Each script attempts to auto-download it from GitHub if missing, which will fail with no network access.

3.4. Install State and Fleet Configuration

Monitoring-server scripts save state in `/etc/p4prometheus-monitoring/install.env`. Helix Core server scripts use `/p4/common/site/config/p4prom_install.env` with SDP, or `/etc/p4prometheus/p4prom_install.env` without it.

For HMS fleets sharing `/p4/common`, create a hostname-specific configuration when required:

```
cp /p4/common/site/config/p4prometheus.yml \
   /p4/common/site/config/p4prometheus.$(hostname -s).yml
systemctl restart p4prometheus
```

The generated wrappers choose the hostname-specific file before the shared default.

© 2021 Perforce Software, Inc.

Chapter 4. Verify Installation

```
systemctl status p4prometheus p4metrics node_exporter
curl http://localhost:9100/metrics | grep p4_
```

On the monitoring server, verify Prometheus targets and dashboards after running the relevant installer. See Troubleshooting section next for component-specific checks.

4.1. Troubleshooting

Make sure all *firewalls* are appropriately configured and the various components on each machine can see each other!

Port defaults are:

- Monitoring server (the following should be accessible to users)
  - Grafana: 3000
  - Prometheus: 9090
  - Victoria Metrics: 8428
  - Node_exporter: 9100
  - Alertmanager: 9093
- P4d server(s) - the following should be accessible to the monitoring server to scrape metrics from.
  - Node_exporter: 9100

Use curl on the monitoring server to ensure that you can pull metrics from the other servers (from the target Node Exporter ports) - see below.

4.1.1. On monitoring server

4.1.1.1. prometheus

Access page http://localhost:9090 (or http://<monitoring_server_ip_or_hostname>:9090) in your browser and search for some metrics.

Check the prometheus config file to ensure that it is correctly pointing to the appropriate targets and scrape intervals. The default location is usually `/etc/prometheus/prometheus.yml`.

Use `curl` to check targets are accessible, e.g. if yaml contains:

```
    - targets:
        - p4hms:9100
        - p4main:9100
        - p4_ha:9100
```

© 2021 Perforce Software, Inc.

Then:

```
curl p4hms:9100/metrics | grep p4_
curl p4main:9100/metrics | grep p4_
curl p4_ha:9100/metrics | grep p4_
```

Problems are most likely due to incorrect target addresses (DNS?), network issues including firewalls, or the node exporter not running on the specified hosts.

4.1.1.2. Victoria Metrics

Access page http://localhost:8428 (or http://<monitoring_server_ip_or_hostname>:8428) in your browser and search for some metrics.

Check the Victoria Metrics config file and the status of the service.

4.1.1.3. Grafana

Check that a suitable data source is setup (i.e. Victoria Metrics or Prometheus) - Section 5.3.1, “Create your first Data Source”

Use the `Explore` option to look for some basic metrics, e.g. just start typing `p4_` and it should autocomplete if it has found `p4_` metrics being collected. Alternatively try `node_time_seconds`

4.1.2. On p4d servers

4.1.2.1. p4prometheus

Make sure the service `p4prometheus` is running:

```
sudo systemctl status p4prometheus
sudo journalctl -u p4prometheus --no-pager | tail -20
```

If this is running correctly, it should write into the designated log file, e.g. `/hxlogs/metrics/p4_cmds.prom`

You can just grep for the most basic metric a couple of times (make sure it is increasing every minute or so):

```
$ grep lines /p4/metrics/p4_cmds.prom

# HELP p4_prom_log_lines_read A count of log lines read
# TYPE p4_prom_log_lines_read counter
p4_prom_log_lines_read{serverid="master.1",sdpinst="1"} 7143
```

 © 2021 Perforce Software, Inc.

4.1.2.2. p4metrics

Make sure the service `p4metrics` is running:

```
sudo systemctl status p4metrics
sudo journalctl -u p4metrics --no-pager | less
```

You can test it via:

```
p4metrics --config p4metrics.yaml --debug --dry.run
```

Check that appropriate files are listed in your metrics dir (and are being updated every minute), e.g.

```
ls -ltr /hxlogs/metrics/
```

4.1.2.3. node exporter

Make sure node_exporter is working (it is easy for there to be permissions access problems to the metrics dir).

Assuming you have installed the `/etc/systemd/system/node_exporter.service` then find the ExecStart line and run it manually and check for errors (optionally appending "--log.level=debug").

Check that you can see values:

```
curl localhost:9100/metrics | grep p4_
```

If the above is empty, then double check the permissions on `/hxlogs/metrics' or the directory you have configured. Look for errors in:

```
sudo journalctl -u node_exporter --no-pager | less
```

© 2021 Perforce Software, Inc.

Chapter 5. Manual Installation

The following component-by-component procedures are retained for sites that cannot use the scripts. They are not the recommended default installation path.

5.1. Install Prometheus

This must be done on the monitoring server only. If not using automated scripts then follow these instructions.



Once you have installed prometheus you will need to adjust its configuration file!

Run the following as root:

```
sudo useradd --no-create-home --shell /bin/false prometheus
sudo mkdir /etc/prometheus
sudo mkdir /var/lib/prometheus
sudo chown prometheus:prometheus /etc/prometheus
sudo chown prometheus:prometheus /var/lib/prometheus

export PVER="2.33.5"
wget https://github.com/prometheus/prometheus/releases/download/v$PVER/prometheus-
$PVER.linux-amd64.tar.gz

tar xvf prometheus-$PVER.linux-amd64.tar.gz
mv prometheus-$PVER.linux-amd64 prometheus-files

sudo cp prometheus-files/prometheus /usr/local/bin/
sudo cp prometheus-files/promtool /usr/local/bin/
sudo chown prometheus:prometheus /usr/local/bin/prometheus
sudo chown prometheus:prometheus /usr/local/bin/promtool
sudo chmod 755 /usr/local/bin/prometheus
sudo chmod 755 /usr/local/bin/promtool

sudo cp -r prometheus-files/consoles /etc/prometheus
sudo cp -r prometheus-files/console_libraries /etc/prometheus
sudo chown -R prometheus:prometheus /etc/prometheus/consoles
sudo chown -R prometheus:prometheus /etc/prometheus/console_libraries
```

Create service file:

```
cat << EOF > /etc/systemd/system/prometheus.service
[Unit]
Description=Prometheus
Wants=network-online.target
After=network-online.target
```


© 2021 Perforce Software, Inc.

```
[Service]
User=prometheus
Group=prometheus
Type=simple
ExecStart=/usr/local/bin/prometheus \
    --config.file /etc/prometheus/prometheus.yml \
    --storage.tsdb.path /var/lib/prometheus/ \
    --web.console.templates=/etc/prometheus/consoles \
    --web.console.libraries=/etc/prometheus/console_libraries

[Install]
WantedBy=multi-user.target
EOF
```

5.1.1. Prometheus config

It is important you edit and adjust the `targets` value appropriately below (see `#####` section) to scrape from your commit/edge/replica servers (and localhost).

See later section on enabling Alertmanager if required.

```
cat << EOF > /etc/prometheus/prometheus.yml
global:
  scrape_interval:     15s # Set the scrape interval to every 15 seconds. Default is
every 1 minute.
  evaluation_interval: 15s # Evaluate rules every 15 seconds. The default is every 1
minute.
  # scrape_timeout is set to the global default (10s).

# Alertmanager configuration - optional - uncomment if using
# alerting:
#   alertmanagers:
#   - static_configs:
#     - targets:
#         - localhost:9093

# Load rules once and periodically evaluate them according to the global
'evaluation_interval'.
# Uncomment if using alertmanager
# rule_files:
  # - "perforce_rules.yml"

# A scrape configuration containing exactly one endpoint to scrape:
# Here it's Prometheus itself.
scrape_configs:
  - job_name: 'prometheus'
    static_configs:
    - targets: ['localhost:9090']

  - job_name: 'node_exporter'
```

```
    static_configs:
    ##############################################################
    # CONFIGURE THESE VALUES AS APPROPRIATE FOR YOUR SERVERS!!!!
    # Note that the names here will appear as labels in your metrics.
    # Recommend not using IP address as not user friendly!
    # The port is going to be 9100 by default for node_exporter unless using Windows
Exporter targets
    ##############################################################
    - targets:
        - p4hms:9100
        - p4main:9100
        - p4_ha:9100

EOF
```

Make sure user has access:

```
sudo chown prometheus:prometheus /etc/prometheus/prometheus.yml
```

5.2. Install victoria metrics (optional but recommended)

This is a high performing component (up to 20x faster) and good for long term storage (data compression is up to 70x) so that much more data can be stored in the same space. If not using automated scripts then follow these instructions.

It is API compatible and thus a drop in for querying. It is configured as a Prometheus writer so is continually kept up-to-date.

Run the following as root:

```
export PVER="1.87.5"    # Adjust to suitable recent value!
wget
https://github.com/VictoriaMetrics/VictoriaMetrics/releases/download/v$PVER/victoria-
metrics-v$PVER.tar.gz
wget
https://github.com/VictoriaMetrics/VictoriaMetrics/releases/download/v$PVER/vmutils-
v$PVER.tar.gz

tar zxvf victoria-metrics-v$PVER.tar.gz
tar zxvf vmutils-v$PVER.tar.gz

mv victoria-metrics-prod /usr/local/bin/
mv vmagent-prod /usr/local/bin/
mv vmalert-prod /usr/local/bin/
mv vmauth-prod /usr/local/bin/
mv vmbackup-prod /usr/local/bin/
```


© 2021 Perforce Software, Inc.

```
mv vmrestore-prod /usr/local/bin/
```

Create service file (**adjust retentionPeriod as desired**):

```
cat << EOF > /etc/systemd/system/victoria-metrics.service
[Unit]
Description=Victoria Metrics
Wants=network-online.target
After=network-online.target

[Service]
User=prometheus
Group=prometheus
Type=simple
ExecStart=/usr/local/bin/victoria-metrics-prod \
    -storageDataPath /var/lib/victoria-metrics/ \
    -retentionPeriod=6

[Install]
WantedBy=multi-user.target
EOF
```

Consider adjusting the `retentionPeriod` vale in the config file.

Ensure data directory exists and is properly owned:

```
sudo mkdir /var/lib/victoria-metrics
sudo chown -R prometheus:prometheus /var/lib/victoria-metrics
```

Start and enable service:

```
sudo systemctl daemon-reload
sudo systemctl enable victoria-metrics
sudo systemctl start victoria-metrics
sudo systemctl status victoria-metrics
```

Check logs for service in case of errors:

```
journalctl -u victoria-metrics --no-pager | tail
```

Update the Prometheus config file `/etc/prometheus/prometheus.yml`, by adding the following section to the end of the file (it starts in the first column):

```
remote_write:
```

© 2021 Perforce Software, Inc.

```
  - url: http://localhost:8428/api/v1/write
```

Note in the above it is possible to customize the port - but usually not required.

Either start or restart Prometheus:

```
sudo systemctl restart prometheus
make restart # Convenience command
```

5.3. Package Installation of Grafana

This should be done on the monitoring server only. If not using Chapter 2, *Automated Installation* scripts, then follow these instructions.

Use the appropriate link below depending if you using `apt` or `yum`:

- https://grafana.com/docs/grafana/latest/installation/debian/
- https://grafana.com/docs/grafana/latest/installation/rpm/

5.3.1. Create your first Data Source

Assuming you are using Victoria Metrics (VM):

- Data source > new
  - Type is Prometheus (VM is API compatible)
  - Name is `Victoria Metrics`
  - Target/port: `http://localhost:8428`
- Click `Save and test`

5.3.2. Setup of Grafana dashboards

Once Grafana is installed (and Prometheus/Victoria Metrics) the following dashboards are recommended to be imported as starting points for further customisation:

- https://grafana.com/grafana/dashboards/12278 - P4 Stats
- https://grafana.com/grafana/dashboards/15509 - P4 Stats (non-SDP)
- https://grafana.com/grafana/dashboards/405 - Node Exporter Server Info
- https://grafana.com/grafana/dashboards/1860 - Node Exporter Full
- https://grafana.com/grafana/dashboards?search=node%20exporter

They can be imported from Grafana dashboard management page.

- Dashboard > New > Import

Alternatively see below for experimental script to create dashboards which is easier to customize.

© 2021 Perforce Software, Inc.

See an example of interpreting Linux prometheus performance metrics

For Windows see Windows Installation since Windows Exporter is used instead of Node Exporter.

If first time with Grafana, the default user/pwd: `admin`/`admin`. It will prompt you to create a proper password!

5.3.3. Script to create Grafana dashboard

Download the following files:

- create_dashboard.py or for use with wget, download raw file: *right click this link > copy link address*
- dashboard.yaml or for use with wget, download raw file: *right click this link > copy link address*

Create a Grafana service account token (or legacy API key token) for your Grafana installation.

Version notes (dashboard generation/upload):

- Tested with Grafana 9.x, 10.x, 11.x, and 12.x using the classic dashboard API endpoint `/api/dashboards/db`.
- Recommended Python package versions: `grafanalib>=0.7,<1.0` and `requests>=2.28`.
- The script accepts both modern service account tokens (`GRAFANA_API_TOKEN`) and legacy API keys (`GRAFANA_API_KEY`).

Install Python dependencies (recommended: uv):

```
curl -LsSf https://astral.sh/uv/install.sh | sh
uv venv .venv
source .venv/bin/activate
uv pip install "grafanalib>=0.7,<1.0" "requests>=2.28"
```

Fallback (pip):

```
pip3 install grafanalib requests
```

Optional: verify installed package versions

```
python3 -c "import grafanalib, requests; print('grafanalib', getattr(grafanalib,
'__version__', 'unknown')); print('requests', requests.__version__)"
```

Set environment variables:

```
export GRAFANA_SERVER=https://p4monitor:3000
export GRAFANA_API_TOKEN="<service account token created above>"
```

© 2021 Perforce Software, Inc.

or legacy variable name:

```
export GRAFANA_API_KEY="<API key created above>"
```

Review the `dashboard.yaml` file and adjust to your local site names where appropriate.

```
vi dashboard.yaml
```

Create and upload the dashboard:

```
./create_dashboard.py --title "P4Prometheus" --url $GRAFANA_SERVER --api-key
$GRAFANA_API_KEY
```

You can re-upload the dashboard with the same title (it will create a new version).

5.3.4. Substituting Victoria Metrics for Prometheus in Grafana

If using Victoria Metrics, then you should:

- Create a suitable data source in Grafana (e.g. use the Prometheus type since VM is API compatible, but specify target as `http://localhost:8428`)
- Click the `Test and Save` button
- Change existing dashboards to use it instead of Prometheus (it is API compatible)

5.3.5. Importing Prometheus data into Victoria Metrics

This can be fairly easily done, and will allow you to save the space used by Prometheus.

See taking a snapshot via web api

Then import it using vmctl

5.4. Install node exporter

This must be done on the Perforce (Helix Core) server machine (ditto for any other servers such as replicas which are being monitored).

Run the following as root:

```
useradd --no-create-home --shell /bin/false node_exporter

export PVER="1.12.1"
wget
https://github.com/prometheus/node_exporter/releases/download/v$PVER/node_exporter-
$PVER.linux-amd64.tar.gz
```


© 2021 Perforce Software, Inc.

```
tar xvf node_exporter-$PVER.linux-amd64.tar.gz
mv node_exporter-$PVER.linux-amd64/node_exporter /usr/local/bin/
```

If you are installing on a Helix Core commit or replica server, then create a metrics directory, give ownership to account writing metrics, and make sure it has global read access (so `node_exporter` account can read entries)

```
mkdir /hxlogs/metrics
chown perforce:perforce /hxlogs/metrics
ls -al /hxlogs/metrics
```

Ensure the above has global read access (e.g. user `perforce` will write files, user `node_exporter` will read them).

If using SDP, then suggest this:

```
ln -s /hxlogs/metrics /p4/
chown -h perforce:perforce /p4/metrics
```

Create service file (note value for directory - may need to be adjusted).

Note that when installing on the monitoring machine, you do not need the /hxlogs/metrics directory, and you don't need the `collector.textfile.directory` parameter in the service file shown below.

```
cat << EOF > /etc/systemd/system/node_exporter.service
[Unit]
Description=Node Exporter
Wants=network-online.target
After=network-online.target

[Service]
User=node_exporter
Group=node_exporter
Type=simple
ExecStart=/usr/local/bin/node_exporter --collector.textfile.directory=/hxlogs/metrics

[Install]
WantedBy=multi-user.target
EOF
```

If using Alertmanager and wanting to check on the status of systemd services, the `ExecStart` line above should be:

```
ExecStart=/usr/local/bin/node_exporter --collector.systemd \
```

```
        --collector.systemd.unit-include=(p4.*|node_exporter)\.service \
        --collector.textfile.directory=/hxlogs/metrics
```

Check the `node_exporter` help, but the above will collect info on the specified services only.

Start and enable service:

```
sudo systemctl daemon-reload
sudo systemctl enable node_exporter
sudo systemctl start node_exporter
sudo systemctl status node_exporter
```

Check logs for service in case of errors:

```
journalctl -u node_exporter --no-pager | tail
```

Check that metrics are being exposed:

```
curl http://localhost:9100/metrics | less
```

5.5. Install p4prometheus - details

This must be done on the Perforce (Helix Core) server machine (and any replica machines).

This assumes SDP structure is in use on the server, and thus that user `perforce` exists.

Get latest release download link: https://github.com/perforce/p4prometheus/releases

Run the following as `root` (using link copied from above page):

```
export PVER=0.11.3  # Adjust this to latest release!
wget
https://github.com/perforce/p4prometheus/releases/download/v$PVER/p4prometheus.linux-
amd64.gz
gunzip p4prometheus.linux-amd64.gz
chmod +rx p4prometheus.linux-amd64
mv p4prometheus.linux-amd64 /usr/local/bin/p4prometheus
```

As user `perforce` run as below.

Important to check configuration values, e.g. `log_path`, `metrics_output` etc.

```
cat << EOF > /p4/common/config/p4prometheus.yaml
# ----------------------
# sdp_instance: SDP instance - typically integer, but can be
```


© 2021 Perforce Software, Inc.

```
# See: https://swarm.workshop.perforce.com/projects/perforce-software-sdp for more
# If this value is blank then it is assumed to be a non-SDP instance.
sdp_instance:   1

# ----------------------
# log_path: Path to p4d server log - REQUIRED!
#   Recommended to set an absolute path, e.g. /p4/1/logs/log
log_path:       /p4/1/logs/log

# ----------------------
# metrics_output: Name of output file to write for processing by node_exporter.
# Ensure that node_exporter user has read access to this folder.
metrics_output: /hxlogs/metrics/p4_cmds.prom

# ----------------------
# server_id: Optional - serverid for metrics.
# If SDP install then it will read /p4/<sdp_instance>/root/server.id for
# If non-SDP install, set this field or set server_id_path (this field has
preference!)
server_id:

# ----------------------
# server_id_path: Optional - path to server.id file for metrics - only used if non-SDP
install.
# If non-SDP install, set either this field, or server_id instead.
# e.g. server_id_path: /opt/perforce/server/root/server.id
server_id_path:

# ----------------------
# output_cmds_by_user: true/false - Whether to output metrics
p4_cmd_user_counter/p4_cmd_user_cumulative_seconds
# Normally this should be set to true as the metrics are useful.
# If you have a p4d instance with thousands of users you may find the number
# of metrics labels is too great (one per distinct user), so set this to false.
output_cmds_by_user: true

# ----------------------
# case_sensitive_server: true/false - if output_cmds_by_user=true then if this value
is set to false
# all userids will be written in lowercase - otherwise as they occur in the log file
# If not present, this value will default to true on Windows and false otherwise.
case_sensitive_server: true

# ----------------------
# output_cmds_by_ip: true/false - Whether to output metrics
p4_cmd_ip_counter/p4_cmd_ip_cumulative_seconds
# Like output_cmds_by_user this can be an issue for larger sites so defaults to false.
output_cmds_by_ip: true

# ----------------------
# output_cmds_by_user_regex: Specifies a Go regex for users for whom to output
```

```
# metrics p4_cmd_user_detail_counter (tracks cmd counts per user/per cmd) and
# p4_cmd_user_detail_cumulative_seconds
#
# This can be set to values such as: "" (no users), ".*" (all users), or
"swarm|jenkins"
# for just those 2 users. The latter is likely to be appropriate in many sites (keep
an eye
# on automation users only, without generating thousands of labels for all users)
output_cmds_by_user_regex: ""

EOF
```

chown perforce:perforce /p4/common/config/p4prometheus.yaml

As user `root`:

Create service file as below - parameters you may need to customise:

- `User`
- `Group`
- `ExecStart`

```
cat << EOF > /etc/systemd/system/p4prometheus.service
[Unit]
Description=P4prometheus
Wants=network-online.target
After=network-online.target

[Service]
User=perforce
Group=perforce
Type=simple
ExecStart=/usr/local/bin/p4prometheus --config=/p4/common/config/p4prometheus.yaml

[Install]
WantedBy=multi-user.target
EOF
```

Start and enable service:

```
sudo systemctl daemon-reload
sudo systemctl enable p4prometheus
sudo systemctl start p4prometheus
sudo systemctl status p4prometheus
```

Check logs for service in case of errors:

© 2021 Perforce Software, Inc.

```
journalctl -u p4prometheus --no-pager | tail
```

Check that metrics are being written:

```
grep lines /hxlogs/metrics/p4_cmds.prom
```

5.6. Install p4metrics and monitor_locks systemd timer services

Use Automated Script Installation!!

Check out: install_p4metrics function in installer script for details

Note that `p4metrics` has now replaced `monitor_metrics.sh` - the latter is retained as an example, but should not be installed!

Please note that `monitor_metrics.py` (which is called by `monitor_wrapper.sh`) runs `lslocks` and cross references locks found with `p4 monitor show` output. This is incredibly useful for determining processes which are blocked by other processes. It is hard to discover this information if you are not collecting the data at the time!

Warning: make sure that `lslocks` is installed on your Linux distribution!

The `monitor_metrics.py` (which is called by `monitor_wrapper.sh`) were previously installed in `crontab`. They are now installed as a systemd timer service.

If not using SDP then please ensure that an appropriate LONG TERM TICKET is setup in the environment that this script is running in.

5.6.1. Checking for blocked commands

Look in the log file `/p4/1/logs/monitor_metrics.log` (or wherever you have configured it to go) for output.

e.g. the following will find all info messages

```
grep "blocked by pid" /p4/1/logs/p4monitor_locks.log | less
```

Other options to remove client locks (which are output with paths like `⋯ /server.locks/clients/90,d/<client name>`):

```
grep "blocked by pid" /p4/1/logs/p4monitor_locks.log | grep -v /clients | less
```

Output might contain lines like:

```
2021-06-08 10:42:01 pid 4203, user bldagent, cmd client, table
/hxmetadata/p4/1/db1/db.have, blocked by pid 3877, user jim, cmd sync, args
c:\Users\jim\p4servers\...#have
```

It may also be worth checking for commands which are "blocking" others, e.g.

```
grep blocking /p4/1/logs/p4monitor_locks.log

2024-04-04 00:29:02: blocking cmd: elapsed 02:09:23, pid 284460, user perforce, cmd
sync, blocking 2, indirectly 203
2024-04-04 00:29:02: blocking cmd: elapsed 00:59:35, pid 374896, user fred, cmd dm-
CommitSubmit, blocking 203, indirectly 0
2024-04-04 00:29:02: blocking cmd: elapsed 00:30:45, pid 396091, user fred, cmd
shelve, blocking 3, indirectly 0
```

Please note that metrics (counts of processes locked) are written to `/p4/metrics/locks.prom` (or your metrics dir) and will be available to Prometheus/Grafana. See P4Prometheus Metrics (look for p4_lock*).

5.6.2. Start and enable service

```
sudo systemctl daemon-reload
sudo systemctl start prometheus
sudo systemctl status prometheus
sudo systemctl enable prometheus
```

Check logs for service in case of errors:

```
journalctl -u prometheus --no-pager | tail
```

Check that prometheus web interface is running:

```
curl http://localhost:9090/
```

Or open URL in a browser.

5.7. Alerting

Done via `alertmanager`. Optional component.

Please see also the examples of Runbook Alert Handling doc which can be customised for your specific site/organisation.

Setup is very similar to the above.

© 2021 Perforce Software, Inc.

```
sudo useradd --no-create-home --shell /bin/false alertmanager
sudo mkdir /etc/alertmanager
sudo mkdir /var/lib/alertmanager
sudo chown alertmanager:alertmanager /etc/alertmanager
sudo chown alertmanager:alertmanager /var/lib/alertmanager

export PVER="0.23.0"
wget https://github.com/prometheus/alertmanager/releases/download/v$PVER/alertmanager-
$PVER.linux-amd64.tar.gz

tar xvf alertmanager-$PVER.linux-amd64.tar.gz
mv alertmanager-$PVER.linux-amd64 alertmanager-files

sudo cp alertmanager-files/alertmanager /usr/local/bin/
sudo cp alertmanager-files/amtool /usr/local/bin/
sudo chown alertmanager:alertmanager /usr/local/bin/alertmanager
sudo chown alertmanager:alertmanager /usr/local/bin/amtool
sudo chmod 755 /usr/local/bin/alertmanager
sudo chmod 755 /usr/local/bin/amtool
```

```
cat << EOF > /etc/systemd/system/alertmanager.service
[Unit]
Description=Alertmanager
Wants=network-online.target
After=network-online.target

[Service]
User=alertmanager
Group=alertmanager
Type=simple
ExecStart=/usr/local/bin/alertmanager --config.file=/etc/alertmanager/alertmanager.yml
\
    --storage.path=/var/lib/alertmanager --log.level=debug

[Install]
WantedBy=multi-user.target
EOF
```

Start and enable service:

```
sudo systemctl daemon-reload
sudo systemctl enable alertmanager
sudo systemctl start alertmanager
sudo systemctl status alertmanager
```

Check logs for service in case of errors:

© 2021 Perforce Software, Inc.

```
journalctl -u alertmanager --no-pager | tail
```

5.7.1. Alertmanager config

See sample config file here:

- EXAMPLES.md

Strongly recommend: set up a simple `Makefile` in `/etc/alertmanager` which validates config file:

Note that Makefile format requires a `<tab>` char (not spaces) at the start of 'action' lines.

```
# Makefile for alertmanager
validate:
        amtool check-config alertmanager.yml

restart: validate
        sudo systemctl restart alertmanager
        sudo systemctl restart prometheus
```

Then you can validate your config:

```
# make validate
amtool check-config alertmanager.yml
Checking 'alertmanager.yml'  SUCCESS
Found:
 - global config
 - route
 - 0 inhibit rules
 - 1 receivers
 - 0 templates
```

5.7.2. Alerting rules

This is an example, assuming simple email and local postfix or equivalent have been setup.

See the version in: EXAMPLES.md

It would be setup as `/etc/prometheus/perforce_rules.yml`

5.7.2.1. Split-file alerting rules (recommended)

`update_prom_graf.sh` manages two separate rules files to avoid overwriting your customizations on each update:

© 2021 Perforce Software, Inc.

File	Managed by	Description
`/etc/prometheus/perforce_rules.yml`	Script (auto-updated)	Upstream rules from this project. Overwritten when upstream changes.
`/etc/prometheus/perforce_rules_local.yml`	You	Your site-specific rules. Never touched by the script. Created with helpful comments on first run.

On each `update_prom_graf.sh` run:

- If the upstream `perforce_rules.yml` has changed and you have not modified it locally, it is silently overwritten.
- If both the upstream has changed **and** you have local edits, the script backs up your version as `perforce_rules.yml.YYYYMMDD` before installing the new upstream, then prints a warning reminding you to review and merge any new upstream rules into your `perforce_rules_local.yml`.

To activate both files, reference them in `prometheus.yml`:

```
rule_files:
  - "perforce_rules.yml"
  - "perforce_rules_local.yml"
```

Template-based custom rules

The custom rule template and custom values provide two examples of site-specific rules. The values file is rendered after the default values, so it can override only the thresholds or selectors that differ at your site while inheriting the remaining defaults.

Copy these files to a working directory and adjust `custom-values.yml` as required. Render the rules with `ytt`, then install the result as the local rules file:

```
cd /path/to/p4prometheus/examples/prometheus
make custom_perforce_rules.yml
sudo install -m 0644 custom_perforce_rules.yml
/etc/prometheus/perforce_rules_local.yml
```

Custom rules must use alert names that do not duplicate alerts in `perforce_rules.yml`.

Then uncomment the relevant section in `prometheus.yml`:

```
# Alertmanager configuration - optional
alerting:
  alertmanagers:
  - static_configs:
```

```
    - targets:
        - localhost:9093

# Load rules once and periodically evaluate them according to the global
'evaluation_interval'.
rule_files:
  - "perforce_rules.yml"
```

5.7.3. Prometheus config to reference alertmanager rules

Strongly recommend: set up a simple `Makefile` in `/etc/prometheus` which validates config and rules file:

Note that Makefile format requires a `<tab>` char (not spaces) at the start of 'action' lines.

```
# Makefile for prometheus - convenience for validating and restarting the service
validate:
        promtool check config prometheus.yml

# Always validates first before restarting
restart: validate
        systemctl restart prometheus
```

Then you can validate your config:

```
# make validate
promtool check config prometheus.yml
Checking prometheus.yml
  SUCCESS: 1 rule files found

Checking perforce_rules.yml
  SUCCESS: 8 rules found
```

For an example of a good starter alertmanager rules file see: example prometheus_rules.yml file

See also the example pint configuration - this is a very valuable linter/validator for alerting rules!

5.8. Advanced config options

For improved security:

- consider LDAP integration for Grafana
- implement appropriate authentication for the various end-points such as Prometheus and node_exporter

© 2021 Perforce Software, Inc.

5.9. Windows Installation

The above instructions are all for Linux. However, all the components have Windows binaries, with the exception of the systemd timer service for `lslocks` monitoring (`monitor_wrapper.sh` and `monitor_metrics.py`). Note that `p4metrics` now has a Windows executable version (it wraps the `p4.exe` CLI)

Details:

- Grafana has a Windows Installer: Grafana Installer
- Prometheus has a Windows executable: Prometheus Executable
- Instead of Node Exporter use: Windows Exporter
- P4Prometheus has a Windows executable: P4prometheus Executable
- P4Metrics has a Windows executable: P4metrics Executable

For testing it is recommended just to run the various executables from command line first and test with Prometheus and Grafana. This allows you to test with firewalls/ports/access rights etc. When it is all working, you can wrap up and install each binary as a Service as noted below.

5.9.1. Windows Exporter

This used to be called "WMI Exporter".

You can download a release, e.g. https://github.com/prometheus-community/windows_exporter/releases

Note that when you run the .MSI file it may appear that it has done nothing - there are no dialogs etc! In fact it will have installed a service called `windows_exporter`. Look for it with `RegEdit.exe` under the key `HKLM\SYSTEM\CurrentControlSet\Services`.

Edit the executable and add the similar parameter to node_exporter: `--collector.textfile.directories` which must be correctly set and agree with the value used by P4prometheus.

Note that the default port is 9182.

You can test in a similar way to on Linux:

```
curl http://localhost:9182/metrics
```

and see what the output is.

5.9.2. P4prometheus on Windows

The executable takes the `--config` parameter and the yaml file is same format as for Linux version. You can specify paths with forward slashes if desired, e.g. `c:/p4/metrics`

© 2021 Perforce Software, Inc.

5.9.3. Running p4metrics

Starting with the version draft version of p4metrics create locally and adjust path settings, e.g. `c:/p4/metrics`

Test the tool with your installation (analyse it's settings). First make sure your admin user is logged in.

```
p4metrics.exe --config p4metrics.yaml --debug --dry.run
```

It is important that the user account used has a long login ticket specified.

5.9.4. Installing Programs as Services

To install as a service using for example NSSM - Non Sucking Service Manager! to wrap the Prometheus/Windows Exporter/P4Prometheus binaries downloaded above.

Note that `Windows Exporter` has an MSI installer which will install it as a service automatically (if run with Windows Admin privileges). See the Installation section for more details and options.

You may wish to use `regedit.exe` to find the installed service (it just "does it") and tweak any parameters you want to add.

Note recommendation above regarding getting things working on command line first (e.g. with debug options).

© 2021 Perforce Software, Inc.