

# Hardware Migration From CC26x0 to CC26x2R

Fredrik Kervel

## ABSTRACT

This application report describes the required hardware changes when moving from the CC26x0 to the CC2642R or CC2652R SimpleLink™ wireless MCUs.

## Contents

1	Changes Between CC26x0 and CC26x2R .....	1
2	Crystal .....	1
3	DCDC Regulator Components .....	2
4	Decoupling .....	2
5	Similarities Between the CC26x2R and the CC26xx .....	2
6	Summary .....	2
7	References .....	2

## Trademarks

SimpleLink is a trademark of Texas Instruments.  
Bluetooth is a registered trademark of Bluetooth SIG, Inc .  
All other trademarks are the property of their respective owners.

## 1 Changes Between CC26x0 and CC26x2R

CC26x2R is the latest generation of ultra-low power wireless MCUs for 2.4 GHz operation from Texas Instruments. The CC2642R supports *Bluetooth®* low energy as well as proprietary RF while the CC2652R additionally supports 802.15.4 based protocols. Compared to the CC26x0 devices, the CC26x2R have more memory, 80 kB of RAM and 352 kB of flash; more capable processors, ARM Cortex M4F as well as updated Sensor Controller Engine, and updated peripherals.

From an external point of view, the CC26x2R is very similar to the CC26x0. In the 7x7 QFN package (RGZ), which is the only option for the CC26x2R, the devices are pin compatible and a PCB design made for the CC26x0 can be reused for the CC26x2R.

There are a few considerations that has to be made regarding external circuitry, these are discussed in the following sections. The CC26x2R LaunchPad design files should also be reviewed.

## 2 Crystal

The CC26x2R devices require a 48 MHz crystal, whereas, the CC26x0 requires a 24 MHz crystal. This change makes it easier to source physically small crystals with specifications within the CC26xx requirements. 48 MHz crystals are available in all the most commonly used crystal packages, and while the CC26x2R reference designs are using 2016 size, 2520 and 3225 sizes are available from all the major crystal manufacturers.

As with the CC26x0, the load capacitance is handled internally on the IC with a user-adjustable load capacitance array, which ranges from 2 pF to 10 pF. No external capacitors are required.

When selecting a crystal for the CC26x2R, it is important to refer to the crystal requirements outlined in the *CC26x2R Data Manual* (SWRS207) and making sure the crystal fulfills these.

### 3 DCDC Regulator Components

The DCDC regulator components, the output inductor and capacitor values used with the CC26x2R are updated to 6.8  $\mu$ H and 22  $\mu$ F, respectively. This is done to reduce the current consumption even further. It is highly recommended to use the same components as in the CC26x2R reference designs, or components with similar parameters. This is to ensure optimum efficiency and low energy consumption.

### 4 Decoupling

The bulk decoupling capacitor on the CC26x2R is changed from 10  $\mu$ F to 22  $\mu$ F. This change is done due to the output capacitor of the DCDC regulator being increased.

### 5 Similarities Between the CC26x2R and the CC26xx

While the CC26x2R is very similar to CC26x0 from an RF perspective, there are several updates to the device (for example, clock frequencies), which typically triggers the need for new regulatory compliance certification.

RF certification of the customer's application and end equipment is the customer's responsibility. The customer is solely responsible for the design, validation, and testing of its applications as well as for compliance with all legal and regulatory requirements concerning its applications. Industry best practices generally require that the customer conducts qualification tests on actual applications taking into account possible environmental and other conditions that the customer's application may encounter. TI recommends consulting with a test house if in doubt on regulatory matters.

### 6 Summary

A PCB designed for the CC26x0 can be reused for the CC26x2R as the devices (in the 7x7 QFN package) are pin to pin compatible. Updates have been done on the CC26x2R, which require external components to be changed: the high frequency crystal, the DCDC regulator output inductor and capacitor and the bulk decoupling capacitor.

### 7 References

- [CC2642R Data Sheet](#)
- [CC2652R Data Manual](#)
- [CC26x2R LaunchPad Design Files](#)

## IMPORTANT NOTICE FOR TI DESIGN INFORMATION AND RESOURCES

Texas Instruments Incorporated ("TI") technical, application or other design advice, services or information, including, but not limited to, reference designs and materials relating to evaluation modules, (collectively, "TI Resources") are intended to assist designers who are developing applications that incorporate TI products; by downloading, accessing or using any particular TI Resource in any way, you (individually or, if you are acting on behalf of a company, your company) agree to use it solely for this purpose and subject to the terms of this Notice.

TI's provision of TI Resources does not expand or otherwise alter TI's applicable published warranties or warranty disclaimers for TI products, and no additional obligations or liabilities arise from TI providing such TI Resources. TI reserves the right to make corrections, enhancements, improvements and other changes to its TI Resources.

You understand and agree that you remain responsible for using your independent analysis, evaluation and judgment in designing your applications and that you have full and exclusive responsibility to assure the safety of your applications and compliance of your applications (and of all TI products used in or for your applications) with all applicable regulations, laws and other applicable requirements. You represent that, with respect to your applications, you have all the necessary expertise to create and implement safeguards that (1) anticipate dangerous consequences of failures, (2) monitor failures and their consequences, and (3) lessen the likelihood of failures that might cause harm and take appropriate actions. You agree that prior to using or distributing any applications that include TI products, you will thoroughly test such applications and the functionality of such TI products as used in such applications. TI has not conducted any testing other than that specifically described in the published documentation for a particular TI Resource.

You are authorized to use, copy and modify any individual TI Resource only in connection with the development of applications that include the TI product(s) identified in such TI Resource. NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER TI INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT OF TI OR ANY THIRD PARTY IS GRANTED HEREIN, including but not limited to any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information regarding or referencing third-party products or services does not constitute a license to use such products or services, or a warranty or endorsement thereof. Use of TI Resources may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

TI RESOURCES ARE PROVIDED "AS IS" AND WITH ALL FAULTS. TI DISCLAIMS ALL OTHER WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, REGARDING TI RESOURCES OR USE THEREOF, INCLUDING BUT NOT LIMITED TO ACCURACY OR COMPLETENESS, TITLE, ANY EPIDEMIC FAILURE WARRANTY AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

TI SHALL NOT BE LIABLE FOR AND SHALL NOT DEFEND OR INDEMNIFY YOU AGAINST ANY CLAIM, INCLUDING BUT NOT LIMITED TO ANY INFRINGEMENT CLAIM THAT RELATES TO OR IS BASED ON ANY COMBINATION OF PRODUCTS EVEN IF DESCRIBED IN TI RESOURCES OR OTHERWISE. IN NO EVENT SHALL TI BE LIABLE FOR ANY ACTUAL, DIRECT, SPECIAL, COLLATERAL, INDIRECT, PUNITIVE, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES IN CONNECTION WITH OR ARISING OUT OF TI RESOURCES OR USE THEREOF, AND REGARDLESS OF WHETHER TI HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

You agree to fully indemnify TI and its representatives against any damages, costs, losses, and/or liabilities arising out of your non-compliance with the terms and provisions of this Notice.

This Notice applies to TI Resources. Additional terms apply to the use and purchase of certain types of materials, TI products and services. These include; without limitation, TI's standard terms for semiconductor products (<http://www.ti.com/sc/docs/stdterms.htm>), [evaluation modules](#), and [samples](http://www.ti.com/sc/docs/sampterm.htm) (<http://www.ti.com/sc/docs/sampterm.htm>).

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2018, Texas Instruments Incorporated