

# Path-Coloring Algorithms for Plane Graphs

Aven Bross

Department of Computer Science

University of Alaska

Fairbanks, AK 99775-6670

dabross@alaska.edu

Glenn G. Chappell

Department of Computer Science

University of Alaska

Fairbanks, AK 99775-6670

chappellg@member.ams.org

Chris Hartman

Department of Computer Science

University of Alaska

Fairbanks, AK 99775-6670

cmhartman@alaska.edu

May 30, 2017

*2010 Mathematics Subject Classification.* Primary 05C38; Secondary 05C10, 05C15.

*Key words and phrases.* Path coloring, list coloring, algorithm.

## Abstract

A path coloring of a graph  $G$  is a vertex coloring of  $G$  such that each color class induces a disjoint union of paths. We present two efficient algorithms to construct a path coloring of a plane graph.

The first algorithm, based on a proof of Poh [7], is given a plane graph; it produces a path coloring of the given graph using three colors.

The second algorithm, based on similar proofs by Hartman [6] and Škrekovski [8], performs a list-coloring generalization of the above. The algorithm is given a plane graph and an assignment of lists of three colors to each vertex; it produces a path coloring of the given graph in which each vertex receives a color from its list.

Implementations of both algorithms are available.

## 1 Introduction

All graphs will be finite, simple, and undirected.

A *path coloring* of a graph  $G$  is a vertex coloring (not necessarily proper) of  $G$  such that each color class induces a disjoint union of paths. A graph  $G$  is *path  $k$ -colorable* if  $G$  admits a path coloring using  $k$  colors.

Broere & Mynhardt conjectured [1, Conj. 16] that every planar graph is path 3-colorable. This was proven independently by Poh [7, Thm. 2] and by Goddard [5, Thm. 1].

**Theorem 1.1** (Poh 1990, Goddard 1991). *Let  $G$  be a planar graph. Then  $G$  is path 3-colorable.*  $\square$

It is easily shown that the “3” in Theorem 1.1 is best possible. In particular, Chartrand & Kronk [4] gave an example of a planar graph whose vertex set cannot be partitioned into two subsets, each inducing a forest.

[Check Chartrand-Kronk reference.]

Hartman [6, Thm. 4.1] (see also Chappell & Hartman [3, Thm. 2.1]) proved a list-coloring generalization of Theorem 1.1. A graph  $G$  is *path  $k$ -choosable* if, whenever each vertex of  $G$  is assigned a list of  $k$  colors, there exists a path coloring of  $G$  in which each vertex receives a color from its list.

**Theorem 1.2** (Hartman 1997). *Let  $G$  be a planar graph. Then  $G$  is path 3-choosable.*  $\square$

Essentially the same technique was used by Škrekovski [8, Thm. 2.2b] to prove a result slightly weaker than Theorem 1.2.

We discuss two efficient path-coloring algorithms based on proofs of the above theorems. We distinguish between a *planar* graph—one that can be drawn in the plane without crossing edges—and a *plane* graph—a graph with a given embedding in the plane.

In Section 2 we outline our graph representations and the basis for our computations of time complexity.

Section 3 covers an algorithm based on Poh’s proof of Theorem 1.1. The algorithm is given a plane graph; it produces a path coloring of the given graph using three colors.

Section 4 covers an algorithm based Hartman’s proof of Theorem 1.2, along with the proof of Škrekovski mentioned above. The algorithm is given a plane graph and an assignment of a list of three colors to each vertex; it produces a path coloring of the given graph in which each vertex receives a color from its list.

Implementations of both algorithms are available; see Bross [2].

## 2 Graph Representatons and Time Complexity

We will represent a graph via *adjacency lists*: a list, for each vertex  $v$ , of the neighbors of  $v$ . A vertex can be represented by an integer  $0 \dots n - 1$ , where  $n$  is the order of the graph.

A plane graph will be specified via a *rotation scheme*: a circular ordering, for each vertex  $v$ , of the edges incident with  $v$ , in the order they appear around  $v$  in the plane embedding; this completely specifies the combinatorial embedding of the graph. Rotation schemes are convenient when we represent a graph using adjacency lists; we simply order the adjacency list for each vertex  $v$  in clockwise order around  $v$ ; no additional data structures are required.

ZZZ Time Complexity ZZZ

ZZZ Augmented Adjacency Lists ZZZ

### 3 Path Coloring: the Poh Algorithm

ZZZ

### 4 Path List Coloring: the Hartman-Škrekovski Algorithm

ZZZ

## References

- [1] I. Broere and C. M. Mynhardt, Generalized colorings of outerplanar and planar graphs, *Graph theory with applications to algorithms and computer science* (Kalamazoo, Mich., 1984), 151–161, Wiley-Intersci. Publ., Wiley, New York, 1985.
- [2] A. Bross, *Implementing path coloring algorithms on planar graphs*, Masters Project, University of Alaska, 2017, available from [http://github.com/permutationlock/path\\_coloring\\_bgl](http://github.com/permutationlock/path_coloring_bgl).
- [3] G. G. Chappell and C. Hartman, Path choosability of planar graphs, in preparation.
- [4] G. Chartrand and H. V. Kronk, The point-arboricity of planar graphs, *J. London. Math. Soc.* **44** (1969), 612–616.
- [5] W. Goddard, Acyclic colorings of planar graphs, *Discrete Math.* **91** (1991), no. 1, 91–94.
- [6] C. M. Hartman, *Extremal Problems in Graph Theory*, Ph.D. Thesis, University of Illinois, 1997.
- [7] K. S. Poh, On the linear vertex-arboricity of a planar graph, *J. Graph Theory* **14** (1990), no. 1, 73–75.
- [8] R. Škrekovski, List improper colourings of planar graphs, *Combin. Probab. Comput.* **8** (1999), no. 3, 293–299.