

# ORACLE

#### Safe Harbor Statement

The following is intended to outline our general product direction. It is intended for information purposes only, and may not be incorporated into any contract. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, and timing of any features or functionality described for Oracle's products remains at the sole discretion of Oracle.



# Agenda

- Our Philosophy on Defaults
- 8.0 Server areas of focus
- 8.0 Replication areas of focus
- How you can help



# Defaults are Important



- We want the best out of box experience
  - Ease of use
  - Performance
- Safe & Secure
  - Don't lose data
  - Don't expose data
- Must also preserve upgrade story...



### The Pursuit of the unattainable

- Never have to change any setting
- Everything works perfectly!

ALEST: 10.17 UPDATE

CHANGES IN VERSION 10.17: THE CPU NO LONGER OVERHEATS WHEN YOU HOLD DOWN SPACEBAR.

COMMENTS:

#### LONGTIME USER4 WRITES:

THIS UPDATE BROKE MY WORKFLOW!
MY CONTROL KEY IS HARD TO REACH,
SO I HOUD SPACEBAR INSTEAD, AND I
CONFIGURED EMACS TO INTERPRET A
RAPID TEMPERATURE RISE AS CONTROL.

**ADMIN** WRITES: THAT'S HORRIFYING.

LOOK, MY SETUP WORKS FOR ME.
JUST ADD AN OPTION TO REENABLE
SPACEBAR HEATING.

EVERY CHANGE BREAKS SOMEONE'S WORKFLOW.

https://xkcd.com/1172/



### Our Criteria



Must work on virtual machines and cloud instances out of the box.

No change for the sake of change.

Follow the principle of least surprise.

The test-suite should pass.



#### What does that mean?



- Some good ideas do not meet threshold for no change for the sake of change:
  - e.g. isolation level.
- We also evaluate performance impact on the test suite must pass.
- Some changes have significant impact to edge cases:
  - e.g. character set.



# Partially Related Goal: Fewer Settings!

- Primary target is good defaults.
- We will remove variables where changing is illogical.
  - This helps manual readability, and improves user experience.
  - Not easy: often edge cases and usability in regression testing.



#### Server 8.0

- Started asking for feedback
   12 months ago
- Seeded discussion with some of the areas we are most interested in.



#### Planning the defaults for MySQL 5.8

In the MySQL team we pay close attention to the default configuration of MySQL, and aim for users to have the best out of the box experience possible.

Following on from a series of blog posts for MySQL 5.7, we are now planning the defaults for MySQL 5.8. We are looking for feed back from you, our users, to share insights on what can be improved.

#### An Introduction

Being the *default* means that these settings should appeal to the largest group of users possible. This creates a constraint where values are often the lowest common denominator. The general guidelines for new defaults is as follows:

- Must work on virtual machines and cloud instances out of the box. Currently this stands at 64-bit Linux with 512M memory and swap disabled.
- Follow the principle of least surprise. This means that if a new option is introduced to potentially lose data (at increased performance) it should be off by default.
- No change for the sake of change. That is to say that some changes may not be suitable if the upgrade effort is disproportionate to the value brought.
- The test-suite should pass. For some changes, this can result in significant work behind the scenes.



### Character Set and Collation

- UTF8MB4 as the default character set
  - Project started in MySQL 5.7
  - Many improvements to reduce performance impact
- New! Support for the latest Unicode 9.0
- We are working on per-country collation rules
  - Accent Sensitive
  - Case Sensitive



#### **Event Scheduler**

- Proposal is to turn on by default.
- See opportunities for SYS and third party applications.



#### Misc Session Buffers

- See opportunity to increase default max\_allowed\_packet
- Increasing Group Concat has sparked further discussion on improving behaviour.
  - Respect strict mode
- Other settings very workload dependent.

- group\_concat\_max\_len (currently 1K)
- join\_buffer\_size (currently 256K)
- read\_buffer\_size (currently 128K)
- read\_rnd\_buffer\_size (currently 256K)
- sort\_buffer\_size (currently 256K)
- max\_allowed\_packet (currently 4M)



# Security

- Goal starting from 5.7 is secure by default.
- Need to harden behaviour around symbolic links.

- symbolic\_links (currently de facto disabled)
- local\_infile (currently on)
- default\_authentication\_plugin (currently mysql\_native\_password)



# Slow query log

- Proposal imported from 5.7-plan
- We know that "2 seconds" is more ideal range
- Would like to offer more comprehensive filtering options
  - Not 8.0 timeframe at this point

- long\_query\_time (currently 10)
- log\_slow\_admin\_statements / log\_slow\_slave\_statements (currently off)

#### InnoDB

- Changing Sample Pages to 100 has very low overhead.
- Log file resize is not dynamic, but buffer pool is
  - Would be great to over provision slightly.

- innodb\_autoinc\_lock\_mode (currently 1)
- innodb\_log\_file\_size (currently 48M)
- innodb\_print\_all\_deadlocks (currently OFF)
- innodb\_sort\_buffer\_size (currently 1M)
- innodb\_stats\_persistent\_sample\_pages (currently 20)



# InnoDB (IO Configuration)

- Would like to switch the default to be "SSDs first".
- Users with hard drives are the minority.

- innodb\_flush\_method (currently uses buffered IO)
- innodb\_flush\_neighbors (currently ON)
- innodb\_page\_cleaners (currently 1)

#### **Timeouts**

- Do not yet have a clear proposal
- Would like to shorten timeouts, but can not "change for the sake of change"
- Need clear use case showing improvement

- innodb\_lock\_wait\_timeout (currently 50 seconds)
- interactive\_timeout (currently 8 hours)
- lock\_wait\_timeout (currently 1 year)
- wait\_timeout (currently 8 hours)

#### Misc


- SQL Standard has different behaviour w.r.t. lctn. Need to consider alternative implementation.
- No clear proposal on digest length
  - Long term may need to investigate alternatives (smart truncate, dynamic)

- lower\_case\_table\_names (currently 0)
- max\_connect\_errors (currently 100)
- max\_digest\_length (currently 1024)
- thread\_cache\_size (autosized)



### Replication 8.0

- Similar blog post to the server
   12 months ago now
- Curated by my colleague
   Matt Lord





# Binary Log

- Turn on binary log by default
- Limit retention to 30 days
- GTIDs enabled by default, with consistency enforced

- log-bin (currently OFF)
- expire-log-days (currently unlimited)
- gtid-mode (currently OFF)
- enforce-gtid-consistency (currently OFF)



# Transactional Replication

- Change repositories to TABLE
- Allows for transactional replication, and an easy switch to multi-source.

 master-info-repository and relay-loginfo-repository (currently FILE)



# **Slave Options**

- Proposal is to enable intra-schema parallel replication by default (4 threads)
  - Commit order preserved
- Add HASH\_SCAN to the list of search algorithms

- log-slave-updates (currently OFF)
- slave-parallel-type (currently DATABASE)
- slave-parallel-workers (currently 0)
- slave-preserve-commit-order (currently OFF)
- slave-rows-search-algorithms (currently TABLE\_SCAN,INDEX\_SCAN)



# **Group Replication**

- Enable the group replication plugin by default with XXHASH64 write set extraction
- Simplifies configuration steps

- transaction-write-set-extraction (currently OFF)
- plugin-load (currently GR not loaded)

## How can you help?

- Many of our best changes come from the Community
- Please send feedback via email, comment on blog posts, etc.
- We value your operational expertise



# Integrated Cloud

Applications & Platform Services



# ORACLE