

MySQL 8.0 Error Message Reference

Abstract

This is the MySQL 8.0 Error Message Reference. It lists all error messages produced by server and client programs in MySQL 8.0. This document accompanies [Error Messages and Common Problems](#), in [MySQL 8.0 Reference Manual](#).

For help with using MySQL, please visit the [MySQL Forums](#), where you can discuss your issues with other MySQL users.

Document generated on: 2021-05-06 (revision: 69662)

Table of Contents

Preface and Legal Notices	v
1 MySQL Error Reference	1
2 Server Error Message Reference	3
3 Client Error Message Reference	527
4 Global Error Message Reference	533
Index	541

Preface and Legal Notices

This is the MySQL 8.0 Error Message Reference. It lists all error messages produced by server and client programs in MySQL 8.0.

Legal Notices

Copyright © 1997, 2021, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

This documentation is NOT distributed under a GPL license. Use of this documentation is subject to the following terms:

You may create a printed copy of this documentation solely for your own personal use. Conversion to other formats is allowed as long as the actual content is not altered or edited in any way. You shall not publish or distribute this documentation in any form or on any media, except if you distribute the documentation in a manner similar to how Oracle disseminates it (that is, electronically for download on a Web site with the software) or on a CD-ROM or similar medium, provided however that the documentation is disseminated together with the software on the same medium. Any other use, such as any dissemination of printed copies or use of this documentation, in whole or in part, in another publication, requires the prior written consent from an authorized representative of Oracle. Oracle and/or its affiliates reserve any and all rights to this documentation not expressly granted above.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at

<https://www.oracle.com/corporate/accessibility/>.

Access to Oracle Support for Accessibility

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit

<https://www.oracle.com/corporate/accessibility/learning-support.html#support-tab>.

Chapter 1 MySQL Error Reference

This document provides a reference for the various types of error messages in MySQL:

- Error messages produced only by the server: [Chapter 2, Server Error Message Reference](#)

On the server side, error messages may occur during the startup and shutdown processes, as a result of issues that occur during SQL statement execution, and so forth.

- The MySQL server writes some error messages to its error log. These indicate issues of interest to database administrators or that require DBA action.
- The server sends other error messages to client programs. These indicate issues pertaining only to a particular client. The MySQL client library takes errors received from the server and makes them available to the host client program.
- Error messages that originate only from within the MySQL client library: [Chapter 3, Client Error Message Reference](#)

Client-side error messages are generated from within the MySQL client library, usually involving problems communicating with the server.

- Error messages that are shared between the server and the client library: [Chapter 4, Global Error Message Reference](#)

Some “global” error messages are shared in the sense that they can be produced by the MySQL server or by MySQL client programs.

For a description of the types of error information MySQL provides and how to obtain information about them, see [Error Messages and Common Problems](#), in [MySQL 8.0 Reference Manual](#).

Chapter 2 Server Error Message Reference

The MySQL server writes some error messages to its error log, and sends others to client programs.

Example server-side error messages written to the error log:

```
2018-10-28T13:01:32.735983Z 0 [Note] [MY-010303] [Server] Skipping generation of SSL certificates as options related to SSL are specified.
```

```
2018-10-02T03:20:39.410387Z 768 [ERROR] [MY-010045] [Server] Event Scheduler: [evtuser@localhost][myschema.e_daily] Unknown database 'mydb'
```

Example server-side error message sent to client programs, as displayed by the `mysql` client:

```
mysql> SELECT * FROM no_such_table;
ERROR 1146 (42S02): Table 'test.no_such_table' doesn't exist
```

Each server error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#).

In addition to the errors in the following list, the server can also produce error messages that have error codes in the range from 1 to 999. See [Chapter 4, Global Error Message Reference](#)

- Error number: [1002](#); Symbol: `ER_NO`; SQLSTATE: `HY000`

Message: NO

Used in the construction of other messages.

- Error number: [1003](#); Symbol: `ER_YES`; SQLSTATE: `HY000`

Message: YES

Used in the construction of other messages.

Extended `EXPLAIN` format generates Note messages. `ER_YES` is used in the `Code` column for these messages in subsequent `SHOW WARNINGS` output.

- Error number: [1004](#); Symbol: `ER_CANT_CREATE_FILE`; SQLSTATE: `HY000`

Message: Can't create file '%s' (errno: %d - %s)

Occurs for failure to create or copy a file needed for some operation.

Possible causes: Permissions problem for source file; destination file already exists but is not writeable.

- Error number: [1005](#); Symbol: `ER_CANT_CREATE_TABLE`; SQLSTATE: `HY000`

Message: Can't create table '%s' (errno: %d - %s)

`InnoDB` reports this error when a table cannot be created. If the error message refers to error 150, table creation failed because a [foreign key constraint](#) was not correctly formed. If the error message refers to error -1, table creation probably failed because the table includes a column name that matched the name of an internal `InnoDB` table.

- Error number: [1006](#); Symbol: `ER_CANT_CREATE_DB`; SQLSTATE: `HY000`

Message: Can't create database '%s' (errno: %d - %s)

- Error number: [1007](#); Symbol: `ER_DB_CREATE_EXISTS`; SQLSTATE: `HY000`

Message: Can't create database '%s'; database exists

An attempt to create a database failed because the database already exists.

Drop the database first if you really want to replace an existing database, or add an `IF NOT EXISTS` clause to the `CREATE DATABASE` statement if to retain an existing database without having the statement produce an error.

- Error number: `1008`; Symbol: `ER_DB_DROP_EXISTS`; SQLSTATE: `HY000`
Message: Can't drop database '%s'; database doesn't exist
- Error number: `1010`; Symbol: `ER_DB_DROP_RMDIR`; SQLSTATE: `HY000`
Message: Error dropping database (can't rmdir '%s', errno: %d - %s)
- Error number: `1012`; Symbol: `ER_CANT_FIND_SYSTEM_REC`; SQLSTATE: `HY000`
Message: Can't read record in system table

Returned by `InnoDB` for attempts to access `InnoDB INFORMATION_SCHEMA` tables when `InnoDB` is unavailable.

- Error number: `1013`; Symbol: `ER_CANT_GET_STAT`; SQLSTATE: `HY000`
Message: Can't get status of '%s' (errno: %d - %s)
- Error number: `1015`; Symbol: `ER_CANT_LOCK`; SQLSTATE: `HY000`
Message: Can't lock file (errno: %d - %s)
- Error number: `1016`; Symbol: `ER_CANT_OPEN_FILE`; SQLSTATE: `HY000`
Message: Can't open file: '%s' (errno: %d - %s)

`InnoDB` reports this error when the table from the `InnoDB` data files cannot be found.

- Error number: `1017`; Symbol: `ER_FILE_NOT_FOUND`; SQLSTATE: `HY000`
Message: Can't find file: '%s' (errno: %d - %s)
- Error number: `1018`; Symbol: `ER_CANT_READ_DIR`; SQLSTATE: `HY000`
Message: Can't read dir of '%s' (errno: %d - %s)
- Error number: `1020`; Symbol: `ER_CHECKREAD`; SQLSTATE: `HY000`
Message: Record has changed since last read in table '%s'
- Error number: `1022`; Symbol: `ER_DUP_KEY`; SQLSTATE: `23000`
Message: Can't write; duplicate key in table '%s'
- Error number: `1024`; Symbol: `ER_ERROR_ON_READ`; SQLSTATE: `HY000`
Message: Error reading file '%s' (errno: %d - %s)
- Error number: `1025`; Symbol: `ER_ERROR_ON_RENAME`; SQLSTATE: `HY000`
Message: Error on rename of '%s' to '%s' (errno: %d - %s)
- Error number: `1026`; Symbol: `ER_ERROR_ON_WRITE`; SQLSTATE: `HY000`
Message: Error writing file '%s' (errno: %d - %s)
- Error number: `1027`; Symbol: `ER_FILE_USED`; SQLSTATE: `HY000`

Message: '%s' is locked against change

- Error number: [1028](#); Symbol: [ER_FILSORT_ABORT](#); SQLSTATE: [HY000](#)

Message: Sort aborted

[ER_FILSORT_ABORT](#) was removed after 8.0.18.

- Error number: [1030](#); Symbol: [ER_GET_ERRNO](#); SQLSTATE: [HY000](#)

Message: Got error %d - '%s' from storage engine

Check the `%d` value to see what the OS error means. For example, 28 indicates that you have run out of disk space.

- Error number: [1031](#); Symbol: [ER_ILLEGAL_HA](#); SQLSTATE: [HY000](#)

Message: Table storage engine for '%s' doesn't have this option

- Error number: [1032](#); Symbol: [ER_KEY_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Can't find record in '%s'

- Error number: [1033](#); Symbol: [ER_NOT_FORM_FILE](#); SQLSTATE: [HY000](#)

Message: Incorrect information in file: '%s'

- Error number: [1034](#); Symbol: [ER_NOT_KEYFILE](#); SQLSTATE: [HY000](#)

Message: Incorrect key file for table '%s'; try to repair it

- Error number: [1035](#); Symbol: [ER_OLD_KEYFILE](#); SQLSTATE: [HY000](#)

Message: Old key file for table '%s'; repair it!

- Error number: [1036](#); Symbol: [ER_OPEN_AS_READONLY](#); SQLSTATE: [HY000](#)

Message: Table '%s' is read only

- Error number: [1037](#); Symbol: [ER_OUTOFMEMORY](#); SQLSTATE: [HY001](#)

Message: Out of memory; restart server and try again (needed %d bytes)

- Error number: [1038](#); Symbol: [ER_OUT_OF_SORTMEMORY](#); SQLSTATE: [HY001](#)

Message: Out of sort memory, consider increasing server sort buffer size

- Error number: [1040](#); Symbol: [ER_CON_COUNT_ERROR](#); SQLSTATE: [08004](#)

Message: Too many connections

- Error number: [1041](#); Symbol: [ER_OUT_OF_RESOURCES](#); SQLSTATE: [HY000](#)

Message: Out of memory; check if mysqld or some other process uses all available memory; if not, you may have to use 'ulimit' to allow mysqld to use more memory or you can add more swap space

- Error number: [1042](#); Symbol: [ER_BAD_HOST_ERROR](#); SQLSTATE: [08S01](#)

Message: Can't get hostname for your address

- Error number: [1043](#); Symbol: [ER_HANDSHAKE_ERROR](#); SQLSTATE: [08S01](#)

Message: Bad handshake

- Error number: 1044; Symbol: ER_DBACCESS_DENIED_ERROR; SQLSTATE: 42000
Message: Access denied for user '%s'@'%s' to database '%s'
- Error number: 1045; Symbol: ER_ACCESS_DENIED_ERROR; SQLSTATE: 28000
Message: Access denied for user '%s'@'%s' (using password: %s)
- Error number: 1046; Symbol: ER_NO_DB_ERROR; SQLSTATE: 3D000
Message: No database selected
- Error number: 1047; Symbol: ER_UNKNOWN_COM_ERROR; SQLSTATE: 08S01
Message: Unknown command
- Error number: 1048; Symbol: ER_BAD_NULL_ERROR; SQLSTATE: 23000
Message: Column '%s' cannot be null
- Error number: 1049; Symbol: ER_BAD_DB_ERROR; SQLSTATE: 42000
Message: Unknown database '%s'
- Error number: 1050; Symbol: ER_TABLE_EXISTS_ERROR; SQLSTATE: 42S01
Message: Table '%s' already exists
- Error number: 1051; Symbol: ER_BAD_TABLE_ERROR; SQLSTATE: 42S02
Message: Unknown table '%s'
- Error number: 1052; Symbol: ER_NON_UNIQ_ERROR; SQLSTATE: 23000
Message: Column '%s' in %s is ambiguous

```
%s = column name
%s = location of column (for example, "field list")
```

Likely cause: A column appears in a query without appropriate qualification, such as in a select list or ON clause.

Examples:

```
mysql> SELECT i FROM t INNER JOIN t AS t2;
ERROR 1052 (23000): Column 'i' in field list is ambiguous

mysql> SELECT * FROM t LEFT JOIN t AS t2 ON i = i;
ERROR 1052 (23000): Column 'i' in on clause is ambiguous
```

Resolution:

- Qualify the column with the appropriate table name:

```
mysql> SELECT t2.i FROM t INNER JOIN t AS t2;
```

- Modify the query to avoid the need for qualification:

```
mysql> SELECT * FROM t LEFT JOIN t AS t2 USING (i);
```

- Error number: 1053; Symbol: ER_SERVER_SHUTDOWN; SQLSTATE: 08S01

Message: Server shutdown in progress

- Error number: 1054; Symbol: ER_BAD_FIELD_ERROR; SQLSTATE: 42S22

Message: Unknown column '%s' in '%s'

- Error number: [1055](#); Symbol: [ER_WRONG_FIELD_WITH_GROUP](#); SQLSTATE: [42000](#)

Message: '%s' isn't in GROUP BY

- Error number: [1056](#); Symbol: [ER_WRONG_GROUP_FIELD](#); SQLSTATE: [42000](#)

Message: Can't group on '%s'

- Error number: [1057](#); Symbol: [ER_WRONG_SUM_SELECT](#); SQLSTATE: [42000](#)

Message: Statement has sum functions and columns in same statement

- Error number: [1058](#); Symbol: [ER_WRONG_VALUE_COUNT](#); SQLSTATE: [21S01](#)

Message: Column count doesn't match value count

- Error number: [1059](#); Symbol: [ER_TOO_LONG_IDENT](#); SQLSTATE: [42000](#)

Message: Identifier name '%s' is too long

- Error number: [1060](#); Symbol: [ER_DUP_FIELDNAME](#); SQLSTATE: [42S21](#)

Message: Duplicate column name '%s'

- Error number: [1061](#); Symbol: [ER_DUP_KEYNAME](#); SQLSTATE: [42000](#)

Message: Duplicate key name '%s'

- Error number: [1062](#); Symbol: [ER_DUP_ENTRY](#); SQLSTATE: [23000](#)

Message: Duplicate entry '%s' for key %d

The message returned with this error uses the format string for [ER_DUP_ENTRY_WITH_KEY_NAME](#).

- Error number: [1063](#); Symbol: [ER_WRONG_FIELD_SPEC](#); SQLSTATE: [42000](#)

Message: Incorrect column specifier for column '%s'

- Error number: [1064](#); Symbol: [ER_PARSE_ERROR](#); SQLSTATE: [42000](#)

Message: %s near '%s' at line %d

- Error number: [1065](#); Symbol: [ER_EMPTY_QUERY](#); SQLSTATE: [42000](#)

Message: Query was empty

- Error number: [1066](#); Symbol: [ER_NONUNIQ_TABLE](#); SQLSTATE: [42000](#)

Message: Not unique table/alias: '%s'

- Error number: [1067](#); Symbol: [ER_INVALID_DEFAULT](#); SQLSTATE: [42000](#)

Message: Invalid default value for '%s'

- Error number: [1068](#); Symbol: [ER_MULTIPLE_PRI_KEY](#); SQLSTATE: [42000](#)

Message: Multiple primary key defined

- Error number: [1069](#); Symbol: [ER_TOO_MANY_KEYS](#); SQLSTATE: [42000](#)

Message: Too many keys specified; max %d keys allowed

- Error number: [1070](#); Symbol: [ER_TOO_MANY_KEY_PARTS](#); SQLSTATE: [42000](#)

Message: Too many key parts specified; max %d parts allowed
- Error number: [1071](#); Symbol: [ER_TOO_LONG_KEY](#); SQLSTATE: [42000](#)

Message: Specified key was too long; max key length is %d bytes
- Error number: [1072](#); Symbol: [ER_KEY_COLUMN_DOES_NOT_EXISTS](#); SQLSTATE: [42000](#)

Message: Key column '%s' doesn't exist in table
- Error number: [1073](#); Symbol: [ER_BLOB_USED_AS_KEY](#); SQLSTATE: [42000](#)

Message: BLOB column '%s' can't be used in key specification with the used table type
- Error number: [1074](#); Symbol: [ER_TOO_BIG_FIELDLENGTH](#); SQLSTATE: [42000](#)

Message: Column length too big for column '%s' (max = %lu); use BLOB or TEXT instead
- Error number: [1075](#); Symbol: [ER_WRONG_AUTO_KEY](#); SQLSTATE: [42000](#)

Message: Incorrect table definition; there can be only one auto column and it must be defined as a key
- Error number: [1076](#); Symbol: [ER_READY](#); SQLSTATE: [HY000](#)

Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d
- Error number: [1077](#); Symbol: [ER_NORMAL_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: %s: Normal shutdown
[ER_NORMAL_SHUTDOWN](#) was removed after 8.0.4.
- Error number: [1079](#); Symbol: [ER_SHUTDOWN_COMPLETE](#); SQLSTATE: [HY000](#)

Message: %s: Shutdown complete
- Error number: [1080](#); Symbol: [ER_FORCING_CLOSE](#); SQLSTATE: [08S01](#)

Message: %s: Forcing close of thread %ld user: '%s'
- Error number: [1081](#); Symbol: [ER_IPSOCK_ERROR](#); SQLSTATE: [08S01](#)

Message: Can't create IP socket
- Error number: [1082](#); Symbol: [ER_NO_SUCH_INDEX](#); SQLSTATE: [42S12](#)

Message: Table '%s' has no index like the one used in CREATE INDEX; recreate the table
- Error number: [1083](#); Symbol: [ER_WRONG_FIELD_TERMINATORS](#); SQLSTATE: [42000](#)

Message: Field separator argument is not what is expected; check the manual
- Error number: [1084](#); Symbol: [ER_BLOBS_AND_NO_TERMINATED](#); SQLSTATE: [42000](#)

Message: You can't use fixed rowlength with BLOBS; please use 'fields terminated by'
- Error number: [1085](#); Symbol: [ER_TEXTFILE_NOT_READABLE](#); SQLSTATE: [HY000](#)

Message: The file '%s' must be in the database directory or be readable by all
- Error number: [1086](#); Symbol: [ER_FILE_EXISTS_ERROR](#); SQLSTATE: [HY000](#)

Message: File '%s' already exists

- Error number: [1087](#); Symbol: [ER_LOAD_INFO](#); SQLSTATE: [HY000](#)

Message: Records: %ld Deleted: %ld Skipped: %ld Warnings: %ld

- Error number: [1088](#); Symbol: [ER_ALTER_INFO](#); SQLSTATE: [HY000](#)

Message: Records: %ld Duplicates: %ld

- Error number: [1089](#); Symbol: [ER_WRONG_SUB_KEY](#); SQLSTATE: [HY000](#)

Message: Incorrect prefix key; the used key part isn't a string, the used length is longer than the key part, or the storage engine doesn't support unique prefix keys

- Error number: [1090](#); Symbol: [ER_CANT_REMOVE_ALL_FIELDS](#); SQLSTATE: [42000](#)

Message: You can't delete all columns with ALTER TABLE; use DROP TABLE instead

- Error number: [1091](#); Symbol: [ER_CANT_DROP_FIELD_OR_KEY](#); SQLSTATE: [42000](#)

Message: Can't DROP '%s'; check that column/key exists

- Error number: [1092](#); Symbol: [ER_INSERT_INFO](#); SQLSTATE: [HY000](#)

Message: Records: %ld Duplicates: %ld Warnings: %ld

- Error number: [1093](#); Symbol: [ER_UPDATE_TABLE_USED](#); SQLSTATE: [HY000](#)

Message: You can't specify target table '%s' for update in FROM clause

This error occurs for attempts to select from and modify the same table within a single statement. If the select attempt occurs within a derived table, you can avoid this error by setting the `derived_merge` flag of the `optimizer_switch` system variable to force the subquery to be materialized into a temporary table, which effectively causes it to be a different table from the one modified. See [Optimizing Derived Tables, View References, and Common Table Expressions with Merging or Materialization](#).

- Error number: [1094](#); Symbol: [ER_NO_SUCH_THREAD](#); SQLSTATE: [HY000](#)

Message: Unknown thread id: %lu

- Error number: [1095](#); Symbol: [ER_KILL_DENIED_ERROR](#); SQLSTATE: [HY000](#)

Message: You are not owner of thread %lu

- Error number: [1096](#); Symbol: [ER_NO_TABLES_USED](#); SQLSTATE: [HY000](#)

Message: No tables used

- Error number: [1097](#); Symbol: [ER_TOO_BIG_SET](#); SQLSTATE: [HY000](#)

Message: Too many strings for column %s and SET

- Error number: [1098](#); Symbol: [ER_NO_UNIQUE_LOGFILE](#); SQLSTATE: [HY000](#)

Message: Can't generate a unique log-filename %s.(1-999)

- Error number: [1099](#); Symbol: [ER_TABLE_NOT_LOCKED_FOR_WRITE](#); SQLSTATE: [HY000](#)

Message: Table '%s' was locked with a READ lock and can't be updated

- Error number: [1100](#); Symbol: [ER_TABLE_NOT_LOCKED](#); SQLSTATE: [HY000](#)

Message: Table '%s' was not locked with LOCK TABLES

- Error number: [1101](#); Symbol: [ER_BLOB_CANT_HAVE_DEFAULT](#); SQLSTATE: [42000](#)

Message: BLOB, TEXT, GEOMETRY or JSON column '%s' can't have a default value

- Error number: [1102](#); Symbol: [ER_WRONG_DB_NAME](#); SQLSTATE: [42000](#)

Message: Incorrect database name '%s'

- Error number: [1103](#); Symbol: [ER_WRONG_TABLE_NAME](#); SQLSTATE: [42000](#)

Message: Incorrect table name '%s'

- Error number: [1104](#); Symbol: [ER_TOO_BIG_SELECT](#); SQLSTATE: [42000](#)

Message: The SELECT would examine more than MAX_JOIN_SIZE rows; check your WHERE and use SET SQL_BIG_SELECTS=1 or SET MAX_JOIN_SIZE=# if the SELECT is okay

- Error number: [1105](#); Symbol: [ER_UNKNOWN_ERROR](#); SQLSTATE: [HY000](#)

Message: Unknown error

- Error number: [1106](#); Symbol: [ER_UNKNOWN_PROCEDURE](#); SQLSTATE: [42000](#)

Message: Unknown procedure '%s'

- Error number: [1107](#); Symbol: [ER_WRONG_PARAMCOUNT_TO_PROCEDURE](#); SQLSTATE: [42000](#)

Message: Incorrect parameter count to procedure '%s'

- Error number: [1108](#); Symbol: [ER_WRONG_PARAMETERS_TO_PROCEDURE](#); SQLSTATE: [HY000](#)

Message: Incorrect parameters to procedure '%s'

- Error number: [1109](#); Symbol: [ER_UNKNOWN_TABLE](#); SQLSTATE: [42S02](#)

Message: Unknown table '%s' in %s

- Error number: [1110](#); Symbol: [ER_FIELD_SPECIFIED_TWICE](#); SQLSTATE: [42000](#)

Message: Column '%s' specified twice

- Error number: [1111](#); Symbol: [ER_INVALID_GROUP_FUNC_USE](#); SQLSTATE: [HY000](#)

Message: Invalid use of group function

- Error number: [1112](#); Symbol: [ER_UNSUPPORTED_EXTENSION](#); SQLSTATE: [42000](#)

Message: Table '%s' uses an extension that doesn't exist in this MySQL version

- Error number: [1113](#); Symbol: [ER_TABLE_MUST_HAVE_COLUMNS](#); SQLSTATE: [42000](#)

Message: A table must have at least 1 column

- Error number: [1114](#); Symbol: [ER_RECORD_FILE_FULL](#); SQLSTATE: [HY000](#)

Message: The table '%s' is full

[InnoDB](#) reports this error when the system tablespace runs out of free space. Reconfigure the system tablespace to add a new data file.

- Error number: [1115](#); Symbol: [ER_UNKNOWN_CHARACTER_SET](#); SQLSTATE: [42000](#)

Message: Unknown character set: '%s'

- Error number: [1116](#); Symbol: [ER_TOO_MANY_TABLES](#); SQLSTATE: [HY000](#)

Message: Too many tables; MySQL can only use %d tables in a join

- Error number: [1117](#); Symbol: [ER_TOO_MANY_FIELDS](#); SQLSTATE: [HY000](#)

Message: Too many columns

- Error number: [1118](#); Symbol: [ER_TOO_BIG_ROWSIZE](#); SQLSTATE: [42000](#)

Message: Row size too large. The maximum row size for the used table type, not counting BLOBS, is %ld. This includes storage overhead, check the manual. You have to change some columns to TEXT or BLOBS

- Error number: [1119](#); Symbol: [ER_STACK_OVERRUN](#); SQLSTATE: [HY000](#)

Message: Thread stack overrun: Used: %ld of a %ld stack. Use 'mysqld --thread_stack=#' to specify a bigger stack if needed

- Error number: [1120](#); Symbol: [ER_WRONG_OUTER_JOIN](#); SQLSTATE: [42000](#)

Message: Cross dependency found in OUTER JOIN; examine your ON conditions

[ER_WRONG_OUTER_JOIN](#) was removed after 8.0.0.

- Error number: [1120](#); Symbol: [ER_WRONG_OUTER_JOIN_UNUSED](#); SQLSTATE: [42000](#)

Message: Cross dependency found in OUTER JOIN; examine your ON conditions

[ER_WRONG_OUTER_JOIN_UNUSED](#) was added in 8.0.1.

- Error number: [1121](#); Symbol: [ER_NULL_COLUMN_IN_INDEX](#); SQLSTATE: [42000](#)

Message: Table handler doesn't support NULL in given index. Please change column '%s' to be NOT NULL or use another handler

- Error number: [1122](#); Symbol: [ER_CANT_FIND_UDF](#); SQLSTATE: [HY000](#)

Message: Can't load function '%s'

- Error number: [1123](#); Symbol: [ER_CANT_INITIALIZE_UDF](#); SQLSTATE: [HY000](#)

Message: Can't initialize function '%s'; %s

- Error number: [1124](#); Symbol: [ER_UDF_NO_PATHS](#); SQLSTATE: [HY000](#)

Message: No paths allowed for shared library

- Error number: [1125](#); Symbol: [ER_UDF_EXISTS](#); SQLSTATE: [HY000](#)

Message: Function '%s' already exists

- Error number: [1126](#); Symbol: [ER_CANT_OPEN_LIBRARY](#); SQLSTATE: [HY000](#)

Message: Can't open shared library '%s' (errno: %d %s)

- Error number: [1127](#); Symbol: [ER_CANT_FIND_DL_ENTRY](#); SQLSTATE: [HY000](#)

Message: Can't find symbol '%s' in library

- Error number: [1128](#); Symbol: [ER_FUNCTION_NOT_DEFINED](#); SQLSTATE: [HY000](#)

Message: Function '%s' is not defined

- Error number: [1129](#); Symbol: [ER_HOST_IS_BLOCKED](#); SQLSTATE: [HY000](#)

Message: Host '%s' is blocked because of many connection errors; unblock with 'mysqladmin flush-hosts'

- Error number: [1130](#); Symbol: [ER_HOST_NOT_PRIVILEGED](#); SQLSTATE: [HY000](#)

Message: Host '%s' is not allowed to connect to this MySQL server

- Error number: [1131](#); Symbol: [ER_PASSWORD_ANONYMOUS_USER](#); SQLSTATE: [42000](#)

Message: You are using MySQL as an anonymous user and anonymous users are not allowed to change passwords

- Error number: [1132](#); Symbol: [ER_PASSWORD_NOT_ALLOWED](#); SQLSTATE: [42000](#)

Message: You must have privileges to update tables in the mysql database to be able to change passwords for others

- Error number: [1133](#); Symbol: [ER_PASSWORD_NO_MATCH](#); SQLSTATE: [42000](#)

Message: Can't find any matching row in the user table

- Error number: [1134](#); Symbol: [ER_UPDATE_INFO](#); SQLSTATE: [HY000](#)

Message: Rows matched: %ld Changed: %ld Warnings: %ld

- Error number: [1135](#); Symbol: [ER_CANT_CREATE_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create a new thread (errno %d); if you are not out of available memory, you can consult the manual for a possible OS-dependent bug

- Error number: [1136](#); Symbol: [ER_WRONG_VALUE_COUNT_ON_ROW](#); SQLSTATE: [21S01](#)

Message: Column count doesn't match value count at row %ld

- Error number: [1137](#); Symbol: [ER_CANT_REOPEN_TABLE](#); SQLSTATE: [HY000](#)

Message: Can't reopen table: '%s'

- Error number: [1138](#); Symbol: [ER_INVALID_USE_OF_NULL](#); SQLSTATE: [22004](#)

Message: Invalid use of NULL value

- Error number: [1139](#); Symbol: [ER_REGEXP_ERROR](#); SQLSTATE: [42000](#)

Message: Got error '%s' from regexp

- Error number: [1140](#); Symbol: [ER_MIX_OF_GROUP_FUNC_AND_FIELDS](#); SQLSTATE: [42000](#)

Message: Mixing of GROUP columns (MIN(),MAX(),COUNT(),...) with no GROUP columns is illegal if there is no GROUP BY clause

- Error number: [1141](#); Symbol: [ER_NONEXISTING_GRANT](#); SQLSTATE: [42000](#)

Message: There is no such grant defined for user '%s' on host '%s'

- Error number: [1142](#); Symbol: [ER_TABLEACCESS_DENIED_ERROR](#); SQLSTATE: [42000](#)

Message: %s command denied to user '%s'@'%s' for table '%s'

-
- Error number: [1143](#); Symbol: [ER_COLUMNACCESS_DENIED_ERROR](#); SQLSTATE: [42000](#)
Message: %s command denied to user '%s'@'%s' for column '%s' in table '%s'
 - Error number: [1144](#); Symbol: [ER_ILLEGAL_GRANT_FOR_TABLE](#); SQLSTATE: [42000](#)
Message: Illegal GRANT/REVOKE command; please consult the manual to see which privileges can be used
 - Error number: [1145](#); Symbol: [ER_GRANT_WRONG_HOST_OR_USER](#); SQLSTATE: [42000](#)
Message: The host or user argument to GRANT is too long
 - Error number: [1146](#); Symbol: [ER_NO SUCH_TABLE](#); SQLSTATE: [42S02](#)
Message: Table '%s.%s' doesn't exist
 - Error number: [1147](#); Symbol: [ER_NONEXISTING_TABLE_GRANT](#); SQLSTATE: [42000](#)
Message: There is no such grant defined for user '%s' on host '%s' on table '%s'
 - Error number: [1148](#); Symbol: [ER_NOT_ALLOWED_COMMAND](#); SQLSTATE: [42000](#)
Message: The used command is not allowed with this MySQL version
 - Error number: [1149](#); Symbol: [ER_SYNTAX_ERROR](#); SQLSTATE: [42000](#)
Message: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use
 - Error number: [1152](#); Symbol: [ER_ABORTING_CONNECTION](#); SQLSTATE: [08S01](#)
Message: Aborted connection %d to db: '%s' user: '%s' (%s)
 - Error number: [1153](#); Symbol: [ER_NET_PACKET_TOO_LARGE](#); SQLSTATE: [08S01](#)
Message: Got a packet bigger than 'max_allowed_packet' bytes
 - Error number: [1154](#); Symbol: [ER_NET_READ_ERROR_FROM_PIPE](#); SQLSTATE: [08S01](#)
Message: Got a read error from the connection pipe
 - Error number: [1155](#); Symbol: [ER_NET_FCNTL_ERROR](#); SQLSTATE: [08S01](#)
Message: Got an error from fcntl()
 - Error number: [1156](#); Symbol: [ER_NET_PACKETS_OUT_OF_ORDER](#); SQLSTATE: [08S01](#)
Message: Got packets out of order
 - Error number: [1157](#); Symbol: [ER_NET_UNCOMPRESS_ERROR](#); SQLSTATE: [08S01](#)
Message: Couldn't uncompress communication packet
 - Error number: [1158](#); Symbol: [ER_NET_READ_ERROR](#); SQLSTATE: [08S01](#)
Message: Got an error reading communication packets
 - Error number: [1159](#); Symbol: [ER_NET_READ_INTERRUPTED](#); SQLSTATE: [08S01](#)
Message: Got timeout reading communication packets
 - Error number: [1160](#); Symbol: [ER_NET_ERROR_ON_WRITE](#); SQLSTATE: [08S01](#)
Message: Got an error writing communication packets

- Error number: [1161](#); Symbol: [ER_NET_WRITE_INTERRUPTED](#); SQLSTATE: [08S01](#)
Message: Got timeout writing communication packets
- Error number: [1162](#); Symbol: [ER_TOO_LONG_STRING](#); SQLSTATE: [42000](#)
Message: Result string is longer than 'max_allowed_packet' bytes
- Error number: [1163](#); Symbol: [ER_TABLE_CANT_HANDLE_BLOB](#); SQLSTATE: [42000](#)
Message: The used table type doesn't support BLOB/TEXT columns
- Error number: [1164](#); Symbol: [ER_TABLE_CANT_HANDLE_AUTO_INCREMENT](#); SQLSTATE: [42000](#)
Message: The used table type doesn't support AUTO_INCREMENT columns
- Error number: [1166](#); Symbol: [ER_WRONG_COLUMN_NAME](#); SQLSTATE: [42000](#)
Message: Incorrect column name '%s'
- Error number: [1167](#); Symbol: [ER_WRONG_KEY_COLUMN](#); SQLSTATE: [42000](#)
Message: The used storage engine can't index column '%s'
- Error number: [1168](#); Symbol: [ER_WRONG_MRG_TABLE](#); SQLSTATE: [HY000](#)
Message: Unable to open underlying table which is differently defined or of non-MyISAM type or doesn't exist
- Error number: [1169](#); Symbol: [ER_DUP_UNIQUE](#); SQLSTATE: [23000](#)
Message: Can't write, because of unique constraint, to table '%s'
- Error number: [1170](#); Symbol: [ER_BLOB_KEY_WITHOUT_LENGTH](#); SQLSTATE: [42000](#)
Message: BLOB/TEXT column '%s' used in key specification without a key length
- Error number: [1171](#); Symbol: [ER_PRIMARY_CANT_HAVE_NULL](#); SQLSTATE: [42000](#)
Message: All parts of a PRIMARY KEY must be NOT NULL; if you need NULL in a key, use UNIQUE instead
- Error number: [1172](#); Symbol: [ER_TOO_MANY_ROWS](#); SQLSTATE: [42000](#)
Message: Result consisted of more than one row
- Error number: [1173](#); Symbol: [ER_REQUIRES_PRIMARY_KEY](#); SQLSTATE: [42000](#)
Message: This table type requires a primary key
- Error number: [1175](#); Symbol: [ER_UPDATE_WITHOUT_KEY_IN_SAFE_MODE](#); SQLSTATE: [HY000](#)
Message: You are using safe update mode and you tried to update a table without a WHERE that uses a KEY column. %s
- Error number: [1176](#); Symbol: [ER_KEY_DOES_NOT_EXISTS](#); SQLSTATE: [42000](#)
Message: Key '%s' doesn't exist in table '%s'
- Error number: [1177](#); Symbol: [ER_CHECK_NO SUCH_TABLE](#); SQLSTATE: [42000](#)
Message: Can't open table
- Error number: [1178](#); Symbol: [ER_CHECK_NOT_IMPLEMENTED](#); SQLSTATE: [42000](#)

Message: The storage engine for the table doesn't support %s

- Error number: 1179; Symbol: ER_CANT_DO_THIS_DURING_AN_TRANSACTION; SQLSTATE: 25000

Message: You are not allowed to execute this command in a transaction

- Error number: 1180; Symbol: ER_ERROR_DURING_COMMIT; SQLSTATE: HY000

Message: Got error %d - '%s' during COMMIT

- Error number: 1181; Symbol: ER_ERROR_DURING_ROLLBACK; SQLSTATE: HY000

Message: Got error %d - '%s' during ROLLBACK

- Error number: 1182; Symbol: ER_ERROR_DURING_FLUSH_LOGS; SQLSTATE: HY000

Message: Got error %d during FLUSH_LOGS

- Error number: 1184; Symbol: ER_NEW_ABORTING_CONNECTION; SQLSTATE: 08S01

Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s)

- Error number: 1188; Symbol: ER_MASTER; SQLSTATE: HY000

Message: Error from master: '%s'

- Error number: 1189; Symbol: ER_MASTER_NET_READ; SQLSTATE: 08S01

Message: Net error reading from master

- Error number: 1190; Symbol: ER_MASTER_NET_WRITE; SQLSTATE: 08S01

Message: Net error writing to master

- Error number: 1191; Symbol: ER_FT_MATCHING_KEY_NOT_FOUND; SQLSTATE: HY000

Message: Can't find FULLTEXT index matching the column list

- Error number: 1192; Symbol: ER_LOCK_OR_ACTIVE_TRANSACTION; SQLSTATE: HY000

Message: Can't execute the given command because you have active locked tables or an active transaction

- Error number: 1193; Symbol: ER_UNKNOWN_SYSTEM_VARIABLE; SQLSTATE: HY000

Message: Unknown system variable '%s'

- Error number: 1194; Symbol: ER_CRASHED_ON_USAGE; SQLSTATE: HY000

Message: Table '%s' is marked as crashed and should be repaired

- Error number: 1195; Symbol: ER_CRASHED_ON_REPAIR; SQLSTATE: HY000

Message: Table '%s' is marked as crashed and last (automatic?) repair failed

- Error number: 1196; Symbol: ER_WARNING_NOT_COMPLETE_ROLLBACK; SQLSTATE: HY000

Message: Some non-transactional changed tables couldn't be rolled back

- Error number: 1197; Symbol: ER_TRANS_CACHE_FULL; SQLSTATE: HY000

Message: Multi-statement transaction required more than 'max_binlog_cache_size' bytes of storage; increase this mysqld variable and try again

- Error number: [1199](#); Symbol: [ER_SLAVE_NOT_RUNNING](#); SQLSTATE: [HY000](#)

Message: This operation requires a running slave; configure slave and do START SLAVE
- Error number: [1200](#); Symbol: [ER_BAD_SLAVE](#); SQLSTATE: [HY000](#)

Message: The server is not configured as slave; fix in config file or with CHANGE MASTER TO
- Error number: [1201](#); Symbol: [ER_MASTER_INFO](#); SQLSTATE: [HY000](#)

Message: Could not initialize master info structure; more error messages can be found in the MySQL error log
- Error number: [1202](#); Symbol: [ER_SLAVE_THREAD](#); SQLSTATE: [HY000](#)

Message: Could not create slave thread; check system resources
- Error number: [1203](#); Symbol: [ER_TOO_MANY_USER_CONNECTIONS](#); SQLSTATE: [42000](#)

Message: User %s already has more than 'max_user_connections' active connections
- Error number: [1204](#); Symbol: [ER_SET_CONSTANTS_ONLY](#); SQLSTATE: [HY000](#)

Message: You may only use constant expressions with SET
- Error number: [1205](#); Symbol: [ER_LOCK_WAIT_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: Lock wait timeout exceeded; try restarting transaction

[InnoDB](#) reports this error when lock wait timeout expires. The statement that waited too long was [rolled back](#) (not the entire [transaction](#)). You can increase the value of the [innodb_lock_wait_timeout](#) configuration option if SQL statements should wait longer for other transactions to complete, or decrease it if too many long-running transactions are causing [locking](#) problems and reducing [concurrency](#) on a busy system.
- Error number: [1206](#); Symbol: [ER_LOCK_TABLE_FULL](#); SQLSTATE: [HY000](#)

Message: The total number of locks exceeds the lock table size

[InnoDB](#) reports this error when the total number of locks exceeds the amount of memory devoted to managing locks. To avoid this error, increase the value of [innodb_buffer_pool_size](#). Within an individual application, a workaround may be to break a large operation into smaller pieces. For example, if the error occurs for a large [INSERT](#), perform several smaller [INSERT](#) operations.
- Error number: [1207](#); Symbol: [ER_READ_ONLY_TRANSACTION](#); SQLSTATE: [25000](#)

Message: Update locks cannot be acquired during a READ UNCOMMITTED transaction
- Error number: [1210](#); Symbol: [ER_WRONG_ARGUMENTS](#); SQLSTATE: [HY000](#)

Message: Incorrect arguments to %s
- Error number: [1211](#); Symbol: [ER_NO_PERMISSION_TO_CREATE_USER](#); SQLSTATE: [42000](#)

Message: '%s'@'%s' is not allowed to create new users
- Error number: [1213](#); Symbol: [ER_LOCK_DEADLOCK](#); SQLSTATE: [40001](#)

Message: Deadlock found when trying to get lock; try restarting transaction

[InnoDB](#) reports this error when a [transaction](#) encounters a [deadlock](#) and is automatically [rolled back](#) so that your application can take corrective action. To recover from this error, run all the operations in this transaction again. A deadlock occurs when requests for locks arrive in inconsistent order

between transactions. The transaction that was rolled back released all its locks, and the other transaction can now get all the locks it requested. Thus, when you re-run the transaction that was rolled back, it might have to wait for other transactions to complete, but typically the deadlock does not recur. If you encounter frequent deadlocks, make the sequence of locking operations ([LOCK TABLES](#), [SELECT ... FOR UPDATE](#), and so on) consistent between the different transactions or applications that experience the issue. See [Deadlocks in InnoDB](#) for details.

- Error number: [1214](#); Symbol: [ER_TABLE_CANT_HANDLE_FT](#); SQLSTATE: [HY000](#)
Message: The used table type doesn't support FULLTEXT indexes
- Error number: [1215](#); Symbol: [ER_CANNOT_ADD_FOREIGN](#); SQLSTATE: [HY000](#)
Message: Cannot add foreign key constraint
- Error number: [1216](#); Symbol: [ER_NO_REFERENCED_ROW](#); SQLSTATE: [23000](#)
Message: Cannot add or update a child row: a foreign key constraint fails
[InnoDB](#) reports this error when you try to add a row but there is no parent row, and a [foreign key constraint](#) fails. Add the parent row first.
- Error number: [1217](#); Symbol: [ER_ROW_IS_REFERENCED](#); SQLSTATE: [23000](#)
Message: Cannot delete or update a parent row: a foreign key constraint fails
[InnoDB](#) reports this error when you try to delete a parent row that has children, and a [foreign key constraint](#) fails. Delete the children first.
- Error number: [1218](#); Symbol: [ER_CONNECT_TO_MASTER](#); SQLSTATE: [08S01](#)
Message: Error connecting to master: %s
- Error number: [1220](#); Symbol: [ER_ERROR_WHEN_EXECUTING_COMMAND](#); SQLSTATE: [HY000](#)
Message: Error when executing command %s: %s
- Error number: [1221](#); Symbol: [ER_WRONG_USAGE](#); SQLSTATE: [HY000](#)
Message: Incorrect usage of %s and %s
- Error number: [1222](#); Symbol: [ER_WRONG_NUMBER_OF_COLUMNS_IN_SELECT](#); SQLSTATE: [21000](#)
Message: The used SELECT statements have a different number of columns
- Error number: [1223](#); Symbol: [ER_CANT_UPDATE_WITH_READLOCK](#); SQLSTATE: [HY000](#)
Message: Can't execute the query because you have a conflicting read lock
- Error number: [1224](#); Symbol: [ER_MIXING_NOT_ALLOWED](#); SQLSTATE: [HY000](#)
Message: Mixing of transactional and non-transactional tables is disabled
- Error number: [1225](#); Symbol: [ER_DUP_ARGUMENT](#); SQLSTATE: [HY000](#)
Message: Option '%s' used twice in statement
- Error number: [1226](#); Symbol: [ER_USER_LIMIT_REACHED](#); SQLSTATE: [42000](#)
Message: User '%s' has exceeded the '%s' resource (current value: %ld)
- Error number: [1227](#); Symbol: [ER_SPECIFIC_ACCESS_DENIED_ERROR](#); SQLSTATE: [42000](#)
Message: Access denied; you need (at least one of) the %s privilege(s) for this operation

- Error number: [1228](#); Symbol: [ER_LOCAL_VARIABLE](#); SQLSTATE: [HY000](#)
Message: Variable '%s' is a SESSION variable and can't be used with SET GLOBAL
- Error number: [1229](#); Symbol: [ER_GLOBAL_VARIABLE](#); SQLSTATE: [HY000](#)
Message: Variable '%s' is a GLOBAL variable and should be set with SET GLOBAL
- Error number: [1230](#); Symbol: [ER_NO_DEFAULT](#); SQLSTATE: [42000](#)
Message: Variable '%s' doesn't have a default value
- Error number: [1231](#); Symbol: [ER_WRONG_VALUE_FOR_VAR](#); SQLSTATE: [42000](#)
Message: Variable '%s' can't be set to the value of '%s'
- Error number: [1232](#); Symbol: [ER_WRONG_TYPE_FOR_VAR](#); SQLSTATE: [42000](#)
Message: Incorrect argument type to variable '%s'
- Error number: [1233](#); Symbol: [ER_VAR_CANT_BE_READ](#); SQLSTATE: [HY000](#)
Message: Variable '%s' can only be set, not read
- Error number: [1234](#); Symbol: [ER_CANT_USE_OPTION_HERE](#); SQLSTATE: [42000](#)
Message: Incorrect usage/placement of '%s'
- Error number: [1235](#); Symbol: [ER_NOT_SUPPORTED_YET](#); SQLSTATE: [42000](#)
Message: This version of MySQL doesn't yet support '%s'
- Error number: [1236](#); Symbol: [ER_MASTER_FATAL_ERROR_READING_BINLOG](#); SQLSTATE: [HY000](#)
Message: Got fatal error %d from master when reading data from binary log: '%s'
- Error number: [1237](#); Symbol: [ER_SLAVE_IGNORED_TABLE](#); SQLSTATE: [HY000](#)
Message: Slave SQL thread ignored the query because of replicate-*-table rules
- Error number: [1238](#); Symbol: [ER_INCORRECT_GLOBAL_LOCAL_VAR](#); SQLSTATE: [HY000](#)
Message: Variable '%s' is a %s variable
- Error number: [1239](#); Symbol: [ER_WRONG_FK_DEF](#); SQLSTATE: [42000](#)
Message: Incorrect foreign key definition for '%s': %s
- Error number: [1240](#); Symbol: [ER_KEY_REF_DO_NOT_MATCH_TABLE_REF](#); SQLSTATE: [HY000](#)
Message: Key reference and table reference don't match
- Error number: [1241](#); Symbol: [ER_OPERAND_COLUMNS](#); SQLSTATE: [21000](#)
Message: Operand should contain %d column(s)
- Error number: [1242](#); Symbol: [ER_SUBQUERY_NO_1_ROW](#); SQLSTATE: [21000](#)
Message: Subquery returns more than 1 row
- Error number: [1243](#); Symbol: [ER_UNKNOWN_STMT_HANDLER](#); SQLSTATE: [HY000](#)
Message: Unknown prepared statement handler (%.*s) given to %s
- Error number: [1244](#); Symbol: [ER_CORRUPT_HELP_DB](#); SQLSTATE: [HY000](#)

Message: Help database is corrupt or does not exist

- Error number: 1246; Symbol: ER_AUTO_CONVERT; SQLSTATE: HY000

Message: Converting column '%s' from %s to %s

- Error number: 1247; Symbol: ER_ILLEGAL_REFERENCE; SQLSTATE: 42S22

Message: Reference '%s' not supported (%s)

- Error number: 1248; Symbol: ER_DERIVED_MUST_HAVE_ALIAS; SQLSTATE: 42000

Message: Every derived table must have its own alias

- Error number: 1249; Symbol: ER_SELECT_REDUCED; SQLSTATE: 01000

Message: Select %u was reduced during optimization

- Error number: 1250; Symbol: ER_TABLENAME_NOT_ALLOWED_HERE; SQLSTATE: 42000

Message: Table '%s' from one of the SELECTs cannot be used in %s

- Error number: 1251; Symbol: ER_NOT_SUPPORTED_AUTH_MODE; SQLSTATE: 08004

Message: Client does not support authentication protocol requested by server; consider upgrading MySQL client

- Error number: 1252; Symbol: ER_SPATIAL_CANT_HAVE_NULL; SQLSTATE: 42000

Message: All parts of a SPATIAL index must be NOT NULL

- Error number: 1253; Symbol: ER_COLLATION_CHARSET_MISMATCH; SQLSTATE: 42000

Message: COLLATION '%s' is not valid for CHARACTER SET '%s'

- Error number: 1256; Symbol: ER_TOO_BIG_FOR_UNCOMPRESS; SQLSTATE: HY000

Message: Uncompressed data size too large; the maximum size is %d (probably, length of uncompressed data was corrupted)

- Error number: 1257; Symbol: ER_ZLIB_Z_MEM_ERROR; SQLSTATE: HY000

Message: ZLIB: Not enough memory

- Error number: 1258; Symbol: ER_ZLIB_Z_BUF_ERROR; SQLSTATE: HY000

Message: ZLIB: Not enough room in the output buffer (probably, length of uncompressed data was corrupted)

- Error number: 1259; Symbol: ER_ZLIB_Z_DATA_ERROR; SQLSTATE: HY000

Message: ZLIB: Input data corrupted

- Error number: 1260; Symbol: ER_CUT_VALUE_GROUP_CONCAT; SQLSTATE: HY000

Message: Row %u was cut by GROUP_CONCAT()

- Error number: 1261; Symbol: ER_WARN_TOO_FEW_RECORDS; SQLSTATE: 01000

Message: Row %ld doesn't contain data for all columns

- Error number: 1262; Symbol: ER_WARN_TOO_MANY_RECORDS; SQLSTATE: 01000

Message: Row %ld was truncated; it contained more data than there were input columns

- Error number: [1263](#); Symbol: [ER_WARN_NULL_TO_NOTNULL](#); SQLSTATE: [22004](#)
Message: Column set to default value; NULL supplied to NOT NULL column '%s' at row %ld
- Error number: [1264](#); Symbol: [ER_WARN_DATA_OUT_OF_RANGE](#); SQLSTATE: [22003](#)
Message: Out of range value for column '%s' at row %ld
- Error number: [1265](#); Symbol: [WARN_DATA_TRUNCATED](#); SQLSTATE: [01000](#)
Message: Data truncated for column '%s' at row %ld
- Error number: [1266](#); Symbol: [ER_WARN_USING_OTHER_HANDLER](#); SQLSTATE: [HY000](#)
Message: Using storage engine %s for table '%s'
- Error number: [1267](#); Symbol: [ER_CANT_AGGREGATE_2COLLATIONS](#); SQLSTATE: [HY000](#)
Message: Illegal mix of collations (%s,%s) and (%s,%s) for operation '%s'
- Error number: [1269](#); Symbol: [ER_REVOKE_GRANTS](#); SQLSTATE: [HY000](#)
Message: Can't revoke all privileges for one or more of the requested users
- Error number: [1270](#); Symbol: [ER_CANT_AGGREGATE_3COLLATIONS](#); SQLSTATE: [HY000](#)
Message: Illegal mix of collations (%s,%s), (%s,%s), (%s,%s) for operation '%s'
- Error number: [1271](#); Symbol: [ER_CANT_AGGREGATE_NCOLLATIONS](#); SQLSTATE: [HY000](#)
Message: Illegal mix of collations for operation '%s'
- Error number: [1272](#); Symbol: [ER_VARIABLE_IS_NOT_STRUCT](#); SQLSTATE: [HY000](#)
Message: Variable '%s' is not a variable component (can't be used as XXXX.variable_name)
- Error number: [1273](#); Symbol: [ER_UNKNOWN_COLLATION](#); SQLSTATE: [HY000](#)
Message: Unknown collation: '%s'
- Error number: [1274](#); Symbol: [ER_SLAVE_IGNORED_SSL_PARAMS](#); SQLSTATE: [HY000](#)
Message: SSL parameters in CHANGE MASTER are ignored because this MySQL slave was compiled without SSL support; they can be used later if MySQL slave with SSL is started
- Error number: [1275](#); Symbol: [ER_SERVER_IS_IN_SECURE_AUTH_MODE](#); SQLSTATE: [HY000](#)
Message: Server is running in --secure-auth mode, but '%s'@'%s' has a password in the old format; please change the password to the new format

[ER_SERVER_IS_IN_SECURE_AUTH_MODE](#) was removed after 8.0.15.
- Error number: [1276](#); Symbol: [ER_WARN_FIELD_RESOLVED](#); SQLSTATE: [HY000](#)
Message: Field or reference '%s%s%s%s%s' of SELECT #%%d was resolved in SELECT #%%d
- Error number: [1277](#); Symbol: [ER_BAD_SLAVE_UNTIL_COND](#); SQLSTATE: [HY000](#)
Message: Incorrect parameter or combination of parameters for START SLAVE UNTIL
- Error number: [1278](#); Symbol: [ER_MISSING_SKIP_SLAVE](#); SQLSTATE: [HY000](#)
Message: It is recommended to use --skip-replica-start when doing step-by-step replication with START SLAVE UNTIL; otherwise, you will get problems if you get an unexpected slave's mysqld restart

-
- Error number: 1279; Symbol: `ER_UNTIL_COND_IGNORED`; SQLSTATE: HY000
Message: SQL thread is not to be started so UNTIL options are ignored
 - Error number: 1280; Symbol: `ER_WRONG_NAME_FOR_INDEX`; SQLSTATE: 42000
Message: Incorrect index name '%s'
 - Error number: 1281; Symbol: `ER_WRONG_NAME_FOR_CATALOG`; SQLSTATE: 42000
Message: Incorrect catalog name '%s'
 - Error number: 1282; Symbol: `ER_WARN_QC_RESIZE`; SQLSTATE: HY000
Message: Query cache failed to set size %lu; new query cache size is %lu
`ER_WARN_QC_RESIZE` was removed after 8.0.2.
 - Error number: 1283; Symbol: `ER_BAD_FT_COLUMN`; SQLSTATE: HY000
Message: Column '%s' cannot be part of FULLTEXT index
 - Error number: 1284; Symbol: `ER_UNKNOWN_KEY_CACHE`; SQLSTATE: HY000
Message: Unknown key cache '%s'
 - Error number: 1285; Symbol: `ER_WARN_HOSTNAME_WONT_WORK`; SQLSTATE: HY000
Message: MySQL is started in --skip-name-resolve mode; you must restart it without this switch for this grant to work
 - Error number: 1286; Symbol: `ER_UNKNOWN_STORAGE_ENGINE`; SQLSTATE: 42000
Message: Unknown storage engine '%s'
 - Error number: 1287; Symbol: `ER_WARN_DEPRECATED_SYNTAX`; SQLSTATE: HY000
Message: '%s' is deprecated and will be removed in a future release. Please use %s instead
 - Error number: 1288; Symbol: `ER_NON_UPDATABLE_TABLE`; SQLSTATE: HY000
Message: The target table %s of the %s is not updatable
 - Error number: 1289; Symbol: `ER_FEATURE_DISABLED`; SQLSTATE: HY000
Message: The '%s' feature is disabled; you need MySQL built with '%s' to have it working
 - Error number: 1290; Symbol: `ER_OPTION_PREVENTS_STATEMENT`; SQLSTATE: HY000
Message: The MySQL server is running with the %s option so it cannot execute this statement
 - Error number: 1291; Symbol: `ER_DUPLICATED_VALUE_IN_TYPE`; SQLSTATE: HY000
Message: Column '%s' has duplicated value '%s' in %s
 - Error number: 1292; Symbol: `ER_TRUNCATED_WRONG_VALUE`; SQLSTATE: 22007
Message: Truncated incorrect %s value: '%s'
 - Error number: 1294; Symbol: `ER_INVALID_ON_UPDATE`; SQLSTATE: HY000
Message: Invalid ON UPDATE clause for '%s' column
 - Error number: 1295; Symbol: `ER_UNSUPPORTED_PS`; SQLSTATE: HY000

Message: This command is not supported in the prepared statement protocol yet

- Error number: [1296](#); Symbol: [ER_GET_ERRMSG](#); SQLSTATE: [HY000](#)

Message: Got error %d '%s' from %s

- Error number: [1297](#); Symbol: [ER_GET_TEMPORARY_ERRMSG](#); SQLSTATE: [HY000](#)

Message: Got temporary error %d '%s' from %s

- Error number: [1298](#); Symbol: [ER_UNKNOWN_TIME_ZONE](#); SQLSTATE: [HY000](#)

Message: Unknown or incorrect time zone: '%s'

- Error number: [1299](#); Symbol: [ER_WARN_INVALID_TIMESTAMP](#); SQLSTATE: [HY000](#)

Message: Invalid TIMESTAMP value in column '%s' at row %ld

- Error number: [1300](#); Symbol: [ER_INVALID_CHARACTER_STRING](#); SQLSTATE: [HY000](#)

Message: Invalid %s character string: '%s'

- Error number: [1301](#); Symbol: [ER_WARN_ALLOWED_PACKET_OVERFLOWED](#); SQLSTATE: [HY000](#)

Message: Result of %s() was larger than max_allowed_packet (%ld) - truncated

- Error number: [1302](#); Symbol: [ER_CONFLICTING_DECLARATIONS](#); SQLSTATE: [HY000](#)

Message: Conflicting declarations: '%s%s' and '%s%s'

- Error number: [1303](#); Symbol: [ER_SP_NO_RECURSIVE_CREATE](#); SQLSTATE: [2F003](#)

Message: Can't create a %s from within another stored routine

- Error number: [1304](#); Symbol: [ER_SP_ALREADY_EXISTS](#); SQLSTATE: [42000](#)

Message: %s %s already exists

- Error number: [1305](#); Symbol: [ER_SP_DOES_NOT_EXIST](#); SQLSTATE: [42000](#)

Message: %s %s does not exist

- Error number: [1306](#); Symbol: [ER_SP_DROP_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to DROP %s %s

- Error number: [1307](#); Symbol: [ER_SP_STORE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to CREATE %s %s

- Error number: [1308](#); Symbol: [ER_SP_LILABEL_MISMATCH](#); SQLSTATE: [42000](#)

Message: %s with no matching label: %s

- Error number: [1309](#); Symbol: [ER_SP_LABEL_REDEFINE](#); SQLSTATE: [42000](#)

Message: Redefining label %s

- Error number: [1310](#); Symbol: [ER_SP_LABEL_MISMATCH](#); SQLSTATE: [42000](#)

Message: End-label %s without match

- Error number: [1311](#); Symbol: [ER_SP_UNINIT_VAR](#); SQLSTATE: [01000](#)

Message: Referring to uninitialized variable %s

- Error number: 1312; Symbol: [ER_SP_BADSELECT](#); SQLSTATE: 0A000

Message: PROCEDURE %s can't return a result set in the given context

- Error number: 1313; Symbol: [ER_SP_BADRETURN](#); SQLSTATE: 42000

Message: RETURN is only allowed in a FUNCTION

- Error number: 1314; Symbol: [ER_SP_BADSTATEMENT](#); SQLSTATE: 0A000

Message: %s is not allowed in stored procedures

- Error number: 1315; Symbol: [ER_UPDATE_LOG_DEPRECATED_IGNORED](#); SQLSTATE: 42000

Message: The update log is deprecated and replaced by the binary log; SET SQL_LOG_UPDATE has been ignored.

- Error number: 1316; Symbol: [ER_UPDATE_LOG_DEPRECATED_TRANSLATED](#); SQLSTATE: 42000

Message: The update log is deprecated and replaced by the binary log; SET SQL_LOG_UPDATE has been translated to SET SQL_LOG_BIN.

- Error number: 1317; Symbol: [ER_QUERY_INTERRUPTED](#); SQLSTATE: 70100

Message: Query execution was interrupted

- Error number: 1318; Symbol: [ER_SP_WRONG_NO_OF_ARGS](#); SQLSTATE: 42000

Message: Incorrect number of arguments for %s %s; expected %u, got %u

- Error number: 1319; Symbol: [ER_SP_COND_MISMATCH](#); SQLSTATE: 42000

Message: Undefined CONDITION: %s

- Error number: 1320; Symbol: [ER_SP_NORETURN](#); SQLSTATE: 42000

Message: No RETURN found in FUNCTION %s

- Error number: 1321; Symbol: [ER_SP_NORETURNEND](#); SQLSTATE: 2F005

Message: FUNCTION %s ended without RETURN

- Error number: 1322; Symbol: [ER_SP_BAD_CURSOR_QUERY](#); SQLSTATE: 42000

Message: Cursor statement must be a SELECT

- Error number: 1323; Symbol: [ER_SP_BAD_CURSOR_SELECT](#); SQLSTATE: 42000

Message: Cursor SELECT must not have INTO

- Error number: 1324; Symbol: [ER_SP_CURSOR_MISMATCH](#); SQLSTATE: 42000

Message: Undefined CURSOR: %s

- Error number: 1325; Symbol: [ER_SP_CURSOR_ALREADY_OPEN](#); SQLSTATE: 24000

Message: Cursor is already open

- Error number: 1326; Symbol: [ER_SP_CURSOR_NOT_OPEN](#); SQLSTATE: 24000

Message: Cursor is not open

-
- Error number: [1327](#); Symbol: [ER_SP_UNDECLARED_VAR](#); SQLSTATE: [42000](#)
Message: Undeclared variable: %s
 - Error number: [1328](#); Symbol: [ER_SP_WRONG_NO_OF_FETCH_ARGS](#); SQLSTATE: [HY000](#)
Message: Incorrect number of FETCH variables
 - Error number: [1329](#); Symbol: [ER_SP_FETCH_NO_DATA](#); SQLSTATE: [02000](#)
Message: No data - zero rows fetched, selected, or processed
 - Error number: [1330](#); Symbol: [ER_SP_DUP_PARAM](#); SQLSTATE: [42000](#)
Message: Duplicate parameter: %s
 - Error number: [1331](#); Symbol: [ER_SP_DUP_VAR](#); SQLSTATE: [42000](#)
Message: Duplicate variable: %s
 - Error number: [1332](#); Symbol: [ER_SP_DUP_COND](#); SQLSTATE: [42000](#)
Message: Duplicate condition: %s
 - Error number: [1333](#); Symbol: [ER_SP_DUP_CURS](#); SQLSTATE: [42000](#)
Message: Duplicate cursor: %s
 - Error number: [1334](#); Symbol: [ER_SP_CANT.Alter](#); SQLSTATE: [HY000](#)
Message: Failed to ALTER %s %s
 - Error number: [1335](#); Symbol: [ER_SP_SUBSELECT_NYI](#); SQLSTATE: [0A000](#)
Message: Subquery value not supported
 - Error number: [1336](#); Symbol: [ER_STMT_NOT_ALLOWED_IN_SF_OR_TRG](#); SQLSTATE: [0A000](#)
Message: %s is not allowed in stored function or trigger
 - Error number: [1337](#); Symbol: [ER_SP_VARCOND_AFTER_CURSHNDLR](#); SQLSTATE: [42000](#)
Message: Variable or condition declaration after cursor or handler declaration
 - Error number: [1338](#); Symbol: [ER_SP_CURSOR_AFTER_HANDLER](#); SQLSTATE: [42000](#)
Message: Cursor declaration after handler declaration
 - Error number: [1339](#); Symbol: [ER_SP_CASE_NOT_FOUND](#); SQLSTATE: [20000](#)
Message: Case not found for CASE statement
 - Error number: [1340](#); Symbol: [ER_FPARSER_TOO_BIG_FILE](#); SQLSTATE: [HY000](#)
Message: Configuration file '%s' is too big
 - Error number: [1341](#); Symbol: [ER_FPARSER_BAD_HEADER](#); SQLSTATE: [HY000](#)
Message: Malformed file type header in file '%s'
 - Error number: [1342](#); Symbol: [ER_FPARSER_EOF_IN_COMMENT](#); SQLSTATE: [HY000](#)
Message: Unexpected end of file while parsing comment '%s'
 - Error number: [1343](#); Symbol: [ER_FPARSER_ERROR_IN_PARAMETER](#); SQLSTATE: [HY000](#)

Message: Error while parsing parameter '%s' (line: '%s')

- Error number: [1344](#); Symbol: [ER_FPARSER_EOF_IN_UNKNOWN_PARAMETER](#); SQLSTATE: [HY000](#)

Message: Unexpected end of file while skipping unknown parameter '%s'

- Error number: [1345](#); Symbol: [ER_VIEW_NO_EXPLAIN](#); SQLSTATE: [HY000](#)

Message: EXPLAIN/SHOW can not be issued; lacking privileges for underlying table

- Error number: [1347](#); Symbol: [ER_WRONG_OBJECT](#); SQLSTATE: [HY000](#)

Message: '%s.%s' is not %s

The named object is incorrect for the type of operation attempted on it. It must be an object of the named type. Example: [HANDLER OPEN](#) requires a base table, not a view. It fails if attempted on an [INFORMATION_SCHEMA](#) table that is implemented as a view on data dictionary tables.

- Error number: [1348](#); Symbol: [ER_NONUPDATEABLE_COLUMN](#); SQLSTATE: [HY000](#)

Message: Column '%s' is not updatable

- Error number: [1350](#); Symbol: [ER_VIEW_SELECT_CLAUSE](#); SQLSTATE: [HY000](#)

Message: View's SELECT contains a '%s' clause

- Error number: [1351](#); Symbol: [ER_VIEW_SELECT_VARIABLE](#); SQLSTATE: [HY000](#)

Message: View's SELECT contains a variable or parameter

- Error number: [1352](#); Symbol: [ER_VIEW_SELECT_TMPTABLE](#); SQLSTATE: [HY000](#)

Message: View's SELECT refers to a temporary table '%s'

- Error number: [1353](#); Symbol: [ER_VIEW_WRONG_LIST](#); SQLSTATE: [HY000](#)

Message: In definition of view, derived table or common table expression, SELECT list and column names list have different column counts

- Error number: [1354](#); Symbol: [ER_WARN_VIEW_MERGE](#); SQLSTATE: [HY000](#)

Message: View merge algorithm can't be used here for now (assumed undefined algorithm)

- Error number: [1355](#); Symbol: [ER_WARN_VIEW_WITHOUT_KEY](#); SQLSTATE: [HY000](#)

Message: View being updated does not have complete key of underlying table in it

- Error number: [1356](#); Symbol: [ER_VIEW_INVALID](#); SQLSTATE: [HY000](#)

Message: View '%s.%s' references invalid table(s) or column(s) or function(s) or definer/invoker of view lack rights to use them

- Error number: [1357](#); Symbol: [ER_SP_NO_DROP_SP](#); SQLSTATE: [HY000](#)

Message: Can't drop or alter a %s from within another stored routine

- Error number: [1359](#); Symbol: [ER_TRG_ALREADY_EXISTS](#); SQLSTATE: [HY000](#)

Message: Trigger already exists

- Error number: [1360](#); Symbol: [ER_TRG_DOES_NOT_EXIST](#); SQLSTATE: [HY000](#)

Message: Trigger does not exist

- Error number: [1361](#); Symbol: [ER_TRG_ON_VIEW_OR_TEMP_TABLE](#); SQLSTATE: [HY000](#)
Message: Trigger's '%s' is view or temporary table
- Error number: [1362](#); Symbol: [ER_TRG_CANT_CHANGE_ROW](#); SQLSTATE: [HY000](#)
Message: Updating of %s row is not allowed in %trigger
- Error number: [1363](#); Symbol: [ER_TRG_NO SUCH_ROW_IN_TRG](#); SQLSTATE: [HY000](#)
Message: There is no %s row in %s trigger
- Error number: [1364](#); Symbol: [ER_NO_DEFAULT_FOR_FIELD](#); SQLSTATE: [HY000](#)
Message: Field '%s' doesn't have a default value
- Error number: [1365](#); Symbol: [ER_DIVISION_BY_ZERO](#); SQLSTATE: [22012](#)
Message: Division by 0
- Error number: [1366](#); Symbol: [ER_TRUNCATED_WRONG_VALUE_FOR_FIELD](#); SQLSTATE: [HY000](#)
Message: Incorrect %s value: '%s' for column '%s' at row %d
- Error number: [1367](#); Symbol: [ER_ILLEGAL_VALUE_FOR_TYPE](#); SQLSTATE: [22007](#)
Message: Illegal %s '%s' value found during parsing
- Error number: [1368](#); Symbol: [ER_VIEW_NONUPD_CHECK](#); SQLSTATE: [HY000](#)
Message: CHECK OPTION on non-updatable view '%s.%s'
- Error number: [1369](#); Symbol: [ER_VIEW_CHECK_FAILED](#); SQLSTATE: [HY000](#)
Message: CHECK OPTION failed '%s.%s'
- Error number: [1370](#); Symbol: [ER_PROCACCESS_DENIED_ERROR](#); SQLSTATE: [42000](#)
Message: %s command denied to user '%s'@'%s' for routine '%s'
- Error number: [1371](#); Symbol: [ER_RELAY_LOG_FAIL](#); SQLSTATE: [HY000](#)
Message: Failed purging old relay logs: %s
- Error number: [1373](#); Symbol: [ER_UNKNOWN_TARGET_BINLOG](#); SQLSTATE: [HY000](#)
Message: Target log not found in binlog index
- Error number: [1374](#); Symbol: [ER_IO_ERR_LOG_INDEX_READ](#); SQLSTATE: [HY000](#)
Message: I/O error reading log index file
- Error number: [1375](#); Symbol: [ER_BINLOG_PURGE_PROHIBITED](#); SQLSTATE: [HY000](#)
Message: Server configuration does not permit binlog purge
- Error number: [1376](#); Symbol: [ER_FSEEK_FAIL](#); SQLSTATE: [HY000](#)
Message: Failed on fseek()
- Error number: [1377](#); Symbol: [ER_BINLOG_PURGE_FATAL_ERR](#); SQLSTATE: [HY000](#)
Message: Fatal error during log purge
- Error number: [1378](#); Symbol: [ER_LOG_IN_USE](#); SQLSTATE: [HY000](#)

Message: A purgeable log is in use, will not purge

- Error number: [1379](#); Symbol: [ER_LOG_PURGE_UNKNOWN_ERR](#); SQLSTATE: [HY000](#)

Message: Unknown error during log purge

- Error number: [1380](#); Symbol: [ER_RELAY_LOG_INIT](#); SQLSTATE: [HY000](#)

Message: Failed initializing relay log position: %s

- Error number: [1381](#); Symbol: [ER_NO_BINARY_LOGGING](#); SQLSTATE: [HY000](#)

Message: You are not using binary logging

- Error number: [1382](#); Symbol: [ER_RESERVED_SYNTAX](#); SQLSTATE: [HY000](#)

Message: The '%s' syntax is reserved for purposes internal to the MySQL server

- Error number: [1390](#); Symbol: [ER_PS_MANY_PARAM](#); SQLSTATE: [HY000](#)

Message: Prepared statement contains too many placeholders

- Error number: [1391](#); Symbol: [ER_KEY_PART_0](#); SQLSTATE: [HY000](#)

Message: Key part '%s' length cannot be 0

- Error number: [1392](#); Symbol: [ER_VIEW_CHECKSUM](#); SQLSTATE: [HY000](#)

Message: View text checksum failed

- Error number: [1393](#); Symbol: [ER_VIEW_MULTIUPDATE](#); SQLSTATE: [HY000](#)

Message: Can not modify more than one base table through a join view '%s.%s'

- Error number: [1394](#); Symbol: [ER_VIEW_NO_INSERT_FIELD_LIST](#); SQLSTATE: [HY000](#)

Message: Can not insert into join view '%s.%s' without fields list

- Error number: [1395](#); Symbol: [ER_VIEW_DELETE_MERGE_VIEW](#); SQLSTATE: [HY000](#)

Message: Can not delete from join view '%s.%s'

- Error number: [1396](#); Symbol: [ER_CANNOT_USER](#); SQLSTATE: [HY000](#)

Message: Operation %s failed for %s

- Error number: [1397](#); Symbol: [ER_XAER_NOTA](#); SQLSTATE: [XAE04](#)

Message: XAER_NOTA: Unknown XID

- Error number: [1398](#); Symbol: [ER_XAER_INVAL](#); SQLSTATE: [XAE05](#)

Message: XAER_INVAL: Invalid arguments (or unsupported command)

- Error number: [1399](#); Symbol: [ER_XAER_RMFAIL](#); SQLSTATE: [XAE07](#)

Message: XAER_RMFAIL: The command cannot be executed when global transaction is in the %s state

- Error number: [1400](#); Symbol: [ER_XAER_OUTSIDE](#); SQLSTATE: [XAE09](#)

Message: XAER_OUTSIDE: Some work is done outside global transaction

- Error number: [1401](#); Symbol: [ER_XAER_RMERR](#); SQLSTATE: [XAE03](#)

Message: XAER_RMERR: Fatal error occurred in the transaction branch - check your data for consistency

- Error number: 1402; Symbol: ER_XA_RBROLLBACK; SQLSTATE: XA100

Message: XA_RBROLLBACK: Transaction branch was rolled back

- Error number: 1403; Symbol: ER_NONEXISTING_PROC_GRANT; SQLSTATE: 42000

Message: There is no such grant defined for user '%s' on host '%s' on routine '%s'

- Error number: 1404; Symbol: ER_PROC_AUTO_GRANT_FAIL; SQLSTATE: HY000

Message: Failed to grant EXECUTE and ALTER ROUTINE privileges

- Error number: 1405; Symbol: ER_PROC_AUTO_REVOKED_FAIL; SQLSTATE: HY000

Message: Failed to revoke all privileges to dropped routine

- Error number: 1406; Symbol: ER_DATA_TOO_LONG; SQLSTATE: 22001

Message: Data too long for column '%s' at row %ld

- Error number: 1407; Symbol: ER_SP_BAD_SQLSTATE; SQLSTATE: 42000

Message: Bad SQLSTATE: '%s'

- Error number: 1408; Symbol: ER_STARTUP; SQLSTATE: HY000

Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d %s

- Error number: 1409; Symbol: ER_LOAD_FROM_FIXED_SIZE_ROWS_TO_VAR; SQLSTATE: HY000

Message: Can't load value from file with fixed size rows to variable

- Error number: 1410; Symbol: ER_CANT_CREATE_USER_WITH_GRANT; SQLSTATE: 42000

Message: You are not allowed to create a user with GRANT

- Error number: 1411; Symbol: ER_WRONG_VALUE_FOR_TYPE; SQLSTATE: HY000

Message: Incorrect %s value: '%s' for function %s

- Error number: 1412; Symbol: ER_TABLE_DEF_CHANGED; SQLSTATE: HY000

Message: Table definition has changed, please retry transaction

- Error number: 1413; Symbol: ER_SP_DUP_HANDLER; SQLSTATE: 42000

Message: Duplicate handler declared in the same block

- Error number: 1414; Symbol: ER_SP_NOT_VAR_ARG; SQLSTATE: 42000

Message: OUT or INOUT argument %d for routine %s is not a variable or NEW pseudo-variable in BEFORE trigger

- Error number: 1415; Symbol: ER_SP_NO_RETSET; SQLSTATE: 0A000

Message: Not allowed to return a result set from a %s

- Error number: 1416; Symbol: ER_CANT_CREATE_GEOMETRY_OBJECT; SQLSTATE: 22003

Message: Cannot get geometry object from data you send to the GEOMETRY field

- Error number: [1418](#); Symbol: [ER_BINLOG_UNSAFE_ROUTINE](#); SQLSTATE: [HY000](#)

Message: This function has none of DETERMINISTIC, NO SQL, or READS SQL DATA in its declaration and binary logging is enabled (you *might* want to use the less safe log_bin_trust_function_creators variable)
- Error number: [1419](#); Symbol: [ER_BINLOG_CREATE_ROUTINE_NEED_SUPER](#); SQLSTATE: [HY000](#)

Message: You do not have the SUPER privilege and binary logging is enabled (you *might* want to use the less safe log_bin_trust_function_creators variable)
- Error number: [1421](#); Symbol: [ER_STMT_HAS_NO_OPEN_CURSOR](#); SQLSTATE: [HY000](#)

Message: The statement (%lu) has no open cursor.
- Error number: [1422](#); Symbol: [ER_COMMIT_NOT_ALLOWED_IN_SF_OR_TRG](#); SQLSTATE: [HY000](#)

Message: Explicit or implicit commit is not allowed in stored function or trigger.
- Error number: [1423](#); Symbol: [ER_NO_DEFAULT_FOR_VIEW_FIELD](#); SQLSTATE: [HY000](#)

Message: Field of view '%s.%s' underlying table doesn't have a default value
- Error number: [1424](#); Symbol: [ER_SP_NO_RECURSION](#); SQLSTATE: [HY000](#)

Message: Recursive stored functions and triggers are not allowed.
- Error number: [1425](#); Symbol: [ER_TOO_BIG_SCALE](#); SQLSTATE: [42000](#)

Message: Too big scale %d specified for column '%s'. Maximum is %lu.
- Error number: [1426](#); Symbol: [ER_TOO_BIG_PRECISION](#); SQLSTATE: [42000](#)

Message: Too-big precision %d specified for '%s'. Maximum is %lu.
- Error number: [1427](#); Symbol: [ER_M_BIGGER_THAN_D](#); SQLSTATE: [42000](#)

Message: For float(M,D), double(M,D) or decimal(M,D), M must be >= D (column '%s').
- Error number: [1428](#); Symbol: [ER_WRONG_LOCK_OF_SYSTEM_TABLE](#); SQLSTATE: [HY000](#)

Message: You can't combine write-locking of system tables with other tables or lock types
- Error number: [1429](#); Symbol: [ER_CONNECT_TO_FOREIGN_DATA_SOURCE](#); SQLSTATE: [HY000](#)

Message: Unable to connect to foreign data source: %s
- Error number: [1430](#); Symbol: [ER_QUERY_ON_FOREIGN_DATA_SOURCE](#); SQLSTATE: [HY000](#)

Message: There was a problem processing the query on the foreign data source. Data source error: %s
- Error number: [1431](#); Symbol: [ER_FOREIGN_DATA_SOURCE_DOESNT_EXIST](#); SQLSTATE: [HY000](#)

Message: The foreign data source you are trying to reference does not exist. Data source error: %s
- Error number: [1432](#); Symbol: [ER_FOREIGN_DATA_STRING_INVALID_CANT_CREATE](#); SQLSTATE: [HY000](#)

Message: Can't create federated table. The data source connection string '%s' is not in the correct format
- Error number: [1433](#); Symbol: [ER_FOREIGN_DATA_STRING_INVALID](#); SQLSTATE: [HY000](#)

Message: The data source connection string '%s' is not in the correct format

- Error number: [1435](#); Symbol: [ER_TRG_IN_WRONG_SCHEMA](#); SQLSTATE: [HY000](#)

Message: Trigger in wrong schema

- Error number: [1436](#); Symbol: [ER_STACK_OVERRUN_NEED_MORE](#); SQLSTATE: [HY000](#)

Message: Thread stack overrun: %ld bytes used of a %ld byte stack, and %ld bytes needed. Use 'mysqld --thread_stack=#' to specify a bigger stack.

- Error number: [1437](#); Symbol: [ER_TOO_LONG_BODY](#); SQLSTATE: [42000](#)

Message: Routine body for '%s' is too long

- Error number: [1438](#); Symbol: [ER_WARN_CANT_DROP_DEFAULT_KEYCACHE](#); SQLSTATE: [HY000](#)

Message: Cannot drop default keycache

- Error number: [1439](#); Symbol: [ER_TOO_BIG_DISPLAYWIDTH](#); SQLSTATE: [42000](#)

Message: Display width out of range for column '%s' (max = %lu)

- Error number: [1440](#); Symbol: [ER_XAER_DUPID](#); SQLSTATE: [XAE08](#)

Message: XAER_DUPID: The XID already exists

- Error number: [1441](#); Symbol: [ER_DATETIME_FUNCTION_OVERFLOW](#); SQLSTATE: [22008](#)

Message: Datetime function: %s field overflow

- Error number: [1442](#); Symbol: [ER_CANT_UPDATE_USED_TABLE_IN_SF_OR_TRG](#); SQLSTATE: [HY000](#)

Message: Can't update table '%s' in stored function/trigger because it is already used by statement which invoked this stored function/trigger.

- Error number: [1443](#); Symbol: [ER_VIEW_PREVENT_UPDATE](#); SQLSTATE: [HY000](#)

Message: The definition of table '%s' prevents operation %s on table '%s'.

- Error number: [1444](#); Symbol: [ER_PS_NO_RECURSION](#); SQLSTATE: [HY000](#)

Message: The prepared statement contains a stored routine call that refers to that same statement. It's not allowed to execute a prepared statement in such a recursive manner

- Error number: [1445](#); Symbol: [ER_SP_CANT_SET_AUTOCOMMIT](#); SQLSTATE: [HY000](#)

Message: Not allowed to set autocommit from a stored function or trigger

- Error number: [1447](#); Symbol: [ER_VIEW_FRM_NO_USER](#); SQLSTATE: [HY000](#)

Message: View '%s'.'%s' has no definer information (old table format). Current user is used as definer. Please recreate the view!

- Error number: [1448](#); Symbol: [ER_VIEW_OTHER_USER](#); SQLSTATE: [HY000](#)

Message: You need the SUPER privilege for creation view with '%s'@'%s' definer

- Error number: [1449](#); Symbol: [ER_NO_SUCH_USER](#); SQLSTATE: [HY000](#)

Message: The user specified as a definer ('%s'@'%s') does not exist

-
- Error number: [1450](#); Symbol: [ER_FORBID_SCHEMA_CHANGE](#); SQLSTATE: [HY000](#)
Message: Changing schema from '%s' to '%s' is not allowed.
 - Error number: [1451](#); Symbol: [ER_ROW_IS_REFERENCED_2](#); SQLSTATE: [23000](#)
Message: Cannot delete or update a parent row: a foreign key constraint fails (%s)
[InnoDB](#) reports this error when you try to delete a parent row that has children, and a [foreign key constraint](#) fails. Delete the children first.
 - Error number: [1452](#); Symbol: [ER_NO_REFERENCED_ROW_2](#); SQLSTATE: [23000](#)
Message: Cannot add or update a child row: a foreign key constraint fails (%s)
[InnoDB](#) reports this error when you try to add a row but there is no parent row, and a [foreign key constraint](#) fails. Add the parent row first.
 - Error number: [1453](#); Symbol: [ER_SP_BAD_VAR_SHADOW](#); SQLSTATE: [42000](#)
Message: Variable '%s' must be quoted with `...', or renamed
 - Error number: [1454](#); Symbol: [ER_TRG_NO_DEFINER](#); SQLSTATE: [HY000](#)
Message: No definer attribute for trigger '%s'.'%s'. It's disallowed to create trigger without definer.
 - Error number: [1455](#); Symbol: [ER_OLD_FILE_FORMAT](#); SQLSTATE: [HY000](#)
Message: '%s' has an old format, you should re-create the '%s' object(s)
 - Error number: [1456](#); Symbol: [ER_SP_RECUSION_LIMIT](#); SQLSTATE: [HY000](#)
Message: Recursive limit %d (as set by the max_sp_recursion_depth variable) was exceeded for routine %s
 - Error number: [1458](#); Symbol: [ER_SP_WRONG_NAME](#); SQLSTATE: [42000](#)
Message: Incorrect routine name '%s'
 - Error number: [1459](#); Symbol: [ER_TABLE_NEEDS_UPGRADE](#); SQLSTATE: [HY000](#)
Message: Table upgrade required. Please do "REPAIR TABLE `%%s`" or dump/reload to fix it!
 - Error number: [1460](#); Symbol: [ER_SP_NO_AGGREGATE](#); SQLSTATE: [42000](#)
Message: AGGREGATE is not supported for stored functions
 - Error number: [1461](#); Symbol: [ER_MAX_PREPARED_STMT_COUNT_REACHED](#); SQLSTATE: [42000](#)
Message: Can't create more than max_prepared_stmt_count statements (current value: %lu)
 - Error number: [1462](#); Symbol: [ER_VIEW_RECURSIVE](#); SQLSTATE: [HY000](#)
Message: `%%s`.`%%s` contains view recursion
 - Error number: [1463](#); Symbol: [ER_NON_GROUPING_FIELD_USED](#); SQLSTATE: [42000](#)
Message: Non-grouping field '%s' is used in %s clause
 - Error number: [1464](#); Symbol: [ER_TABLE_CANT_HANDLE_SPKEYS](#); SQLSTATE: [HY000](#)
Message: The used table type doesn't support SPATIAL indexes
 - Error number: [1465](#); Symbol: [ER_NO_TRIGGER_ON_SYSTEM_SCHEMA](#); SQLSTATE: [HY000](#)

Message: Triggers can not be created on system tables

- Error number: [1466](#); Symbol: [ER_REMOVED_SPACES](#); SQLSTATE: [HY000](#)

Message: Leading spaces are removed from name '%s'

- Error number: [1467](#); Symbol: [ER_AUTOINC_READ_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to read auto-increment value from storage engine

- Error number: [1468](#); Symbol: [ER_USERNAME](#); SQLSTATE: [HY000](#)

Message: user name

- Error number: [1469](#); Symbol: [ER_HOSTNAME](#); SQLSTATE: [HY000](#)

Message: host name

- Error number: [1470](#); Symbol: [ER_WRONG_STRING_LENGTH](#); SQLSTATE: [HY000](#)

Message: String '%s' is too long for %s (should be no longer than %d)

- Error number: [1471](#); Symbol: [ER_NON_INSERTABLE_TABLE](#); SQLSTATE: [HY000](#)

Message: The target table %s of the %s is not insertable-into

- Error number: [1472](#); Symbol: [ER_ADMIN_WRONG_MRG_TABLE](#); SQLSTATE: [HY000](#)

Message: Table '%s' is differently defined or of non-MyISAM type or doesn't exist

- Error number: [1473](#); Symbol: [ER_TOO_HIGH_LEVEL_OF_NESTING_FOR_SELECT](#); SQLSTATE: [HY000](#)

Message: Too high level of nesting for select

- Error number: [1474](#); Symbol: [ER_NAME_BECOMES_EMPTY](#); SQLSTATE: [HY000](#)

Message: Name '%s' has become "

- Error number: [1475](#); Symbol: [ER_AMBIGUOUS_FIELD_TERM](#); SQLSTATE: [HY000](#)

Message: First character of the FIELDS TERMINATED string is ambiguous; please use non-optional and non-empty FIELDS ENCLOSED BY

- Error number: [1476](#); Symbol: [ER_FOREIGN_SERVER_EXISTS](#); SQLSTATE: [HY000](#)

Message: The foreign server, %s, you are trying to create already exists.

- Error number: [1477](#); Symbol: [ER_FOREIGN_SERVER_DOESNT_EXIST](#); SQLSTATE: [HY000](#)

Message: The foreign server name you are trying to reference does not exist. Data source error: %s

- Error number: [1478](#); Symbol: [ER_ILLEGAL_HA_CREATE_OPTION](#); SQLSTATE: [HY000](#)

Message: Table storage engine '%s' does not support the create option '%s'

- Error number: [1479](#); Symbol: [ER_PARTITIONQUIRES_VALUES_ERROR](#); SQLSTATE: [HY000](#)

Message: Syntax error: %s PARTITIONING requires definition of VALUES %s for each partition

- Error number: [1480](#); Symbol: [ER_PARTITION_WRONG_VALUES_ERROR](#); SQLSTATE: [HY000](#)

Message: Only %s PARTITIONING can use VALUES %s in partition definition

-
- Error number: [1481](#); Symbol: [ER_PARTITION_MAXVALUE_ERROR](#); SQLSTATE: [HY000](#)
Message: MAXVALUE can only be used in last partition definition
 - Error number: [1484](#); Symbol: [ER_PARTITION_WRONG_NO_PART_ERROR](#); SQLSTATE: [HY000](#)
Message: Wrong number of partitions defined, mismatch with previous setting
 - Error number: [1485](#); Symbol: [ER_PARTITION_WRONG_NO_SUBPART_ERROR](#); SQLSTATE: [HY000](#)
Message: Wrong number of subpartitions defined, mismatch with previous setting
 - Error number: [1486](#); Symbol: [ER_WRONG_EXPR_IN_PARTITION_FUNC_ERROR](#); SQLSTATE: [HY000](#)
Message: Constant, random or timezone-dependent expressions in (sub)partitioning function are not allowed
 - Error number: [1488](#); Symbol: [ER_FIELD_NOT_FOUND_PART_ERROR](#); SQLSTATE: [HY000](#)
Message: Field in list of fields for partition function not found in table
 - Error number: [1490](#); Symbol: [ER_INCONSISTENT_PARTITION_INFO_ERROR](#); SQLSTATE: [HY000](#)
Message: The partition info in the frm file is not consistent with what can be written into the frm file
 - Error number: [1491](#); Symbol: [ER_PARTITION_FUNC_NOT_ALLOWED_ERROR](#); SQLSTATE: [HY000](#)
Message: The %s function returns the wrong type
 - Error number: [1492](#); Symbol: [ER_PARTITIONS_MUST_BE_DEFINED_ERROR](#); SQLSTATE: [HY000](#)
Message: For %s partitions each partition must be defined
 - Error number: [1493](#); Symbol: [ER_RANGE_NOT_INCREASING_ERROR](#); SQLSTATE: [HY000](#)
Message: VALUES LESS THAN value must be strictly increasing for each partition
 - Error number: [1494](#); Symbol: [ER_INCONSISTENT_TYPE_OF_FUNCTIONS_ERROR](#); SQLSTATE: [HY000](#)
Message: VALUES value must be of same type as partition function
 - Error number: [1495](#); Symbol: [ER_MULTIPLE_DEF_CONST_IN_LIST_PART_ERROR](#); SQLSTATE: [HY000](#)
Message: Multiple definition of same constant in list partitioning
 - Error number: [1496](#); Symbol: [ER_PARTITION_ENTRY_ERROR](#); SQLSTATE: [HY000](#)
Message: Partitioning can not be used stand-alone in query
 - Error number: [1497](#); Symbol: [ER_MIX_HANDLER_ERROR](#); SQLSTATE: [HY000](#)
Message: The mix of handlers in the partitions is not allowed in this version of MySQL
 - Error number: [1498](#); Symbol: [ER_PARTITION_NOT_DEFINED_ERROR](#); SQLSTATE: [HY000](#)
Message: For the partitioned engine it is necessary to define all %s
 - Error number: [1499](#); Symbol: [ER_TOO_MANY_PARTITIONS_ERROR](#); SQLSTATE: [HY000](#)
Message: Too many partitions (including subpartitions) were defined

- Error number: [1500](#); Symbol: [ER_SUBPARTITION_ERROR](#); SQLSTATE: [HY000](#)

Message: It is only possible to mix RANGE/LIST partitioning with HASH/KEY partitioning for subpartitioning
- Error number: [1501](#); Symbol: [ER_CANT_CREATE_HANDLER_FILE](#); SQLSTATE: [HY000](#)

Message: Failed to create specific handler file
- Error number: [1502](#); Symbol: [ER_BLOB_FIELD_IN_PART_FUNC_ERROR](#); SQLSTATE: [HY000](#)

Message: A BLOB field is not allowed in partition function
- Error number: [1503](#); Symbol: [ER_UNIQUE_KEY_NEED_ALL_FIELDS_IN_PF](#); SQLSTATE: [HY000](#)

Message: A %s must include all columns in the table's partitioning function (prefixed columns are not considered).
- Error number: [1504](#); Symbol: [ER_NO_PARTS_ERROR](#); SQLSTATE: [HY000](#)

Message: Number of %s = 0 is not an allowed value
- Error number: [1505](#); Symbol: [ER_PARTITION_MGMT_ON_NONPARTITIONED](#); SQLSTATE: [HY000](#)

Message: Partition management on a not partitioned table is not possible
- Error number: [1506](#); Symbol: [ER_FOREIGN_KEY_ON_PARTITIONED](#); SQLSTATE: [HY000](#)

Message: Foreign keys are not yet supported in conjunction with partitioning
- Error number: [1507](#); Symbol: [ER_DROP_PARTITION_NON_EXISTENT](#); SQLSTATE: [HY000](#)

Message: Error in list of partitions to %s
- Error number: [1508](#); Symbol: [ER_DROP_LAST_PARTITION](#); SQLSTATE: [HY000](#)

Message: Cannot remove all partitions, use DROP TABLE instead
- Error number: [1509](#); Symbol: [ER_COALESCE_ONLY_ON_HASH_PARTITION](#); SQLSTATE: [HY000](#)

Message: COALESCE PARTITION can only be used on HASH/KEY partitions
- Error number: [1510](#); Symbol: [ER_REORG_HASH_ONLY_ON_SAME_NO](#); SQLSTATE: [HY000](#)

Message: REORGANIZE PARTITION can only be used to reorganize partitions not to change their numbers
- Error number: [1511](#); Symbol: [ER_REORG_NO_PARAM_ERROR](#); SQLSTATE: [HY000](#)

Message: REORGANIZE PARTITION without parameters can only be used on auto-partitioned tables using HASH PARTITIONS
- Error number: [1512](#); Symbol: [ER_ONLY_ON_RANGE_LIST_PARTITION](#); SQLSTATE: [HY000](#)

Message: %s PARTITION can only be used on RANGE/LIST partitions
- Error number: [1513](#); Symbol: [ER_ADD_PARTITION_SUBPART_ERROR](#); SQLSTATE: [HY000](#)

Message: Trying to Add partition(s) with wrong number of subpartitions
- Error number: [1514](#); Symbol: [ER_ADD_PARTITION_NO_NEW_PARTITION](#); SQLSTATE: [HY000](#)

Message: At least one partition must be added
- Error number: [1515](#); Symbol: [ER_COALESCE_PARTITION_NO_PARTITION](#); SQLSTATE: [HY000](#)

Message: At least one partition must be coalesced

- Error number: [1516](#); Symbol: [ER_REORG_PARTITION_NOT_EXIST](#); SQLSTATE: [HY000](#)

Message: More partitions to reorganize than there are partitions

- Error number: [1517](#); Symbol: [ER_SAME_NAME_PARTITION](#); SQLSTATE: [HY000](#)

Message: Duplicate partition name %s

- Error number: [1518](#); Symbol: [ER_NO_BINLOG_ERROR](#); SQLSTATE: [HY000](#)

Message: It is not allowed to shut off binlog on this command

- Error number: [1519](#); Symbol: [ER_CONSECUTIVE_REORG_PARTITIONS](#); SQLSTATE: [HY000](#)

Message: When reorganizing a set of partitions they must be in consecutive order

- Error number: [1520](#); Symbol: [ER_REORG_OUTSIDE_RANGE](#); SQLSTATE: [HY000](#)

Message: Reorganize of range partitions cannot change total ranges except for last partition where it can extend the range

- Error number: [1521](#); Symbol: [ER_PARTITION_FUNCTION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Partition function not supported in this version for this handler

- Error number: [1523](#); Symbol: [ER_LIMITED_PART_RANGE](#); SQLSTATE: [HY000](#)

Message: The %s handler only supports 32 bit integers in VALUES

- Error number: [1524](#); Symbol: [ER_PLUGIN_IS_NOT_LOADED](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' is not loaded

- Error number: [1525](#); Symbol: [ER_WRONG_VALUE](#); SQLSTATE: [HY000](#)

Message: Incorrect %s value: '%s'

- Error number: [1526](#); Symbol: [ER_NO_PARTITION_FOR_GIVEN_VALUE](#); SQLSTATE: [HY000](#)

Message: Table has no partition for value %s

- Error number: [1527](#); Symbol: [ER_FILEGROUP_OPTION_ONLY_ONCE](#); SQLSTATE: [HY000](#)

Message: It is not allowed to specify %s more than once

- Error number: [1528](#); Symbol: [ER_CREATE_FILEGROUP_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to create %s

- Error number: [1529](#); Symbol: [ER_DROP_FILEGROUP_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to drop %s

- Error number: [1530](#); Symbol: [ER_TABLESPACE_AUTO_EXTEND_ERROR](#); SQLSTATE: [HY000](#)

Message: The handler doesn't support autoextend of tablespaces

- Error number: [1531](#); Symbol: [ER_WRONG_SIZE_NUMBER](#); SQLSTATE: [HY000](#)

Message: A size parameter was incorrectly specified, either number or on the form 10M

- Error number: [1532](#); Symbol: [ER_SIZE_OVERFLOW_ERROR](#); SQLSTATE: [HY000](#)

Message: The size number was correct but we don't allow the digit part to be more than 2 billion

- Error number: 1533; Symbol: ER_ALTER_FILEGROUP_FAILED; SQLSTATE: HY000

Message: Failed to alter: %s

- Error number: 1534; Symbol: ER_BINLOG_ROW_LOGGING_FAILED; SQLSTATE: HY000

Message: Writing one row to the row-based binary log failed

- Error number: 1537; Symbol: ER_EVENT_ALREADY_EXISTS; SQLSTATE: HY000

Message: Event '%s' already exists

- Error number: 1539; Symbol: ER_EVENT_DOES_NOT_EXIST; SQLSTATE: HY000

Message: Unknown event '%s'

- Error number: 1542; Symbol: ER_EVENT_INTERVAL_NOT_POSITIVE_OR_TOO_BIG; SQLSTATE: HY000

Message: INTERVAL is either not positive or too big

- Error number: 1543; Symbol: ER_EVENT_ENDS_BEFORE_STARTS; SQLSTATE: HY000

Message: ENDS is either invalid or before STARTS

- Error number: 1544; Symbol: ER_EVENT_EXEC_TIME_IN_THE_PAST; SQLSTATE: HY000

Message: Event execution time is in the past. Event has been disabled

- Error number: 1551; Symbol: ER_EVENT_SAME_NAME; SQLSTATE: HY000

Message: Same old and new event name

- Error number: 1553; Symbol: ER_DROP_INDEX_FK; SQLSTATE: HY000

Message: Cannot drop index '%s': needed in a foreign key constraint

InnoDB reports this error when you attempt to drop the last index that can enforce a particular referential constraint.

For optimal performance with DML statements, InnoDB requires an index to exist on [foreign key](#) columns, so that [UPDATE](#) and [DELETE](#) operations on a [parent table](#) can easily check whether corresponding rows exist in the [child table](#). MySQL creates or drops such indexes automatically when needed, as a side-effect of [CREATE TABLE](#), [CREATE INDEX](#), and [ALTER TABLE](#) statements.

When you drop an index, InnoDB checks if the index is used for checking a foreign key constraint. It is still OK to drop the index if there is another index that can be used to enforce the same constraint. InnoDB prevents you from dropping the last index that can enforce a particular referential constraint.

- Error number: 1554; Symbol: ER_WARN_DEPRECATED_SYNTAX_WITH_VER; SQLSTATE: HY000

Message: The syntax '%s' is deprecated and will be removed in MySQL %s. Please use %s instead

- Error number: 1556; Symbol: ER_CANT_LOCK_LOG_TABLE; SQLSTATE: HY000

Message: You can't use locks with log tables.

- Error number: 1557; Symbol: ER_FOREIGN_DUPLICATE_KEY_OLD_UNUSED; SQLSTATE: 23000

Message: Upholding foreign key constraints for table '%s', entry '%s', key %d would lead to a duplicate entry

-
- Error number: 1558; Symbol: `ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE`; SQLSTATE: `HY000`

Message: The column count of mysql.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please perform the MySQL upgrade procedure.
 - Error number: 1559; Symbol: `ER_TEMP_TABLE_PREVENTS_SWITCH_OUT_OF_RBR`; SQLSTATE: `HY000`

Message: Cannot switch out of the row-based binary log format when the session has open temporary tables

`ER_TEMP_TABLE_PREVENTS_SWITCH_OUT_OF_RBR` was removed after 8.0.12.
 - Error number: 1560; Symbol: `ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_FORMAT`; SQLSTATE: `HY000`

Message: Cannot change the binary logging format inside a stored function or trigger
 - Error number: 1562; Symbol: `ER_PARTITION_NO_TEMPORARY`; SQLSTATE: `HY000`

Message: Cannot create temporary table with partitions
 - Error number: 1563; Symbol: `ER_PARTITION_CONST_DOMAIN_ERROR`; SQLSTATE: `HY000`

Message: Partition constant is out of partition function domain
 - Error number: 1564; Symbol: `ER_PARTITION_FUNCTION_IS_NOT_ALLOWED`; SQLSTATE: `HY000`

Message: This partition function is not allowed
 - Error number: 1565; Symbol: `ER_DDL_LOG_ERROR`; SQLSTATE: `HY000`

Message: Error in DDL log

`ER_DDL_LOG_ERROR` was removed after 8.0.1.
 - Error number: 1566; Symbol: `ER_NULL_IN_VALUES_LESS_THAN`; SQLSTATE: `HY000`

Message: Not allowed to use NULL value in VALUES LESS THAN
 - Error number: 1567; Symbol: `ER_WRONG_PARTITION_NAME`; SQLSTATE: `HY000`

Message: Incorrect partition name
 - Error number: 1568; Symbol: `ER_CANT_CHANGE_TX_CHARACTERISTICS`; SQLSTATE: `25001`

Message: Transaction characteristics can't be changed while a transaction is in progress
 - Error number: 1569; Symbol: `ER_DUP_ENTRY_AUTOINCREMENT_CASE`; SQLSTATE: `HY000`

Message: ALTER TABLE causes auto_increment resequencing, resulting in duplicate entry '%s' for key '%s'
 - Error number: 1571; Symbol: `ER_EVENT_SET_VAR_ERROR`; SQLSTATE: `HY000`

Message: Error during starting/stopping of the scheduler. Error code %u
 - Error number: 1572; Symbol: `ER_PARTITION_MERGE_ERROR`; SQLSTATE: `HY000`

Message: Engine cannot be used in partitioned tables
 - Error number: 1575; Symbol: `ER_BASE64_DECODE_ERROR`; SQLSTATE: `HY000`

Message: Decoding of base64 string failed

- Error number: 1576; Symbol: [ER_EVENT_RECUSION_FORBIDDEN](#); SQLSTATE: HY000

Message: Recursion of EVENT DDL statements is forbidden when body is present

- Error number: 1578; Symbol: [ER_ONLY_INTEGERS_ALLOWED](#); SQLSTATE: HY000

Message: Only integers allowed as number here

- Error number: 1579; Symbol: [ER_UNSUPORTED_LOG_ENGINE](#); SQLSTATE: HY000

Message: This storage engine cannot be used for log tables

- Error number: 1580; Symbol: [ER_BAD_LOG_STATEMENT](#); SQLSTATE: HY000

Message: You cannot '%s' a log table if logging is enabled

- Error number: 1581; Symbol: [ER_CANT_RENAME_LOG_TABLE](#); SQLSTATE: HY000

Message: Cannot rename '%s'. When logging enabled, rename to/from log table must rename two tables: the log table to an archive table and another table back to '%s'

- Error number: 1582; Symbol: [ER_WRONG_PARAMCOUNT_TO_NATIVE_FCT](#); SQLSTATE: 42000

Message: Incorrect parameter count in the call to native function '%s'

- Error number: 1583; Symbol: [ER_WRONG_PARAMETERS_TO_NATIVE_FCT](#); SQLSTATE: 42000

Message: Incorrect parameters in the call to native function '%s'

- Error number: 1584; Symbol: [ER_WRONG_PARAMETERS_TO_STORED_FCT](#); SQLSTATE: 42000

Message: Incorrect parameters in the call to stored function %s

- Error number: 1585; Symbol: [ER_NATIVE_FCT_NAME_COLLISION](#); SQLSTATE: HY000

Message: This function '%s' has the same name as a native function

- Error number: 1586; Symbol: [ER_DUP_ENTRY_WITH_KEY_NAME](#); SQLSTATE: 23000

Message: Duplicate entry '%s' for key '%s'

The format string for this error is also used with [ER_DUP_ENTRY](#).

- Error number: 1587; Symbol: [ER_BINLOG_PURGE_EMFILE](#); SQLSTATE: HY000

Message: Too many files opened, please execute the command again

- Error number: 1588; Symbol: [ER_EVENT_CANNOT_CREATE_IN_THE_PAST](#); SQLSTATE: HY000

Message: Event execution time is in the past and ON COMPLETION NOT PRESERVE is set. The event was dropped immediately after creation.

- Error number: 1589; Symbol: [ER_EVENT_CANNOT_ALTER_IN_THE_PAST](#); SQLSTATE: HY000

Message: Event execution time is in the past and ON COMPLETION NOT PRESERVE is set. The event was not changed. Specify a time in the future.

- Error number: 1591; Symbol: [ER_NO_PARTITION_FOR_GIVEN_VALUE_SILENT](#); SQLSTATE: HY000

Message: Table has no partition for some existing values

-
- Error number: [1592](#); Symbol: [ER_BINLOG_UNSAFE_STATEMENT](#); SQLSTATE: [HY000](#)

Message: Unsafe statement written to the binary log using statement format since BINLOG_FORMAT = STATEMENT. %s
 - Error number: [1593](#); Symbol: [ER_BINLOG_FATAL_ERROR](#); SQLSTATE: [HY000](#)

Message: Fatal error: %s
[ER_BINLOG_FATAL_ERROR](#) was added in 8.0.11.
 - Error number: [1598](#); Symbol: [ER_BINLOG_LOGGING_IMPOSSIBLE](#); SQLSTATE: [HY000](#)

Message: Binary logging not possible. Message: %s
 - Error number: [1599](#); Symbol: [ER_VIEW_NO_CREATION_CTX](#); SQLSTATE: [HY000](#)

Message: View `'%s`.`%s` has no creation context
 - Error number: [1600](#); Symbol: [ER_VIEW_INVALID_CREATION_CTX](#); SQLSTATE: [HY000](#)

Message: Creation context of view `'%s`.`%s' is invalid
 - Error number: [1602](#); Symbol: [ER_TRG_CORRUPTED_FILE](#); SQLSTATE: [HY000](#)

Message: Corrupted TRG file for table `'%s`.`%s`
 - Error number: [1603](#); Symbol: [ER_TRG_NO_CREATION_CTX](#); SQLSTATE: [HY000](#)

Message: Triggers for table `'%s`.`%s` have no creation context
 - Error number: [1604](#); Symbol: [ER_TRG_INVALID_CREATION_CTX](#); SQLSTATE: [HY000](#)

Message: Trigger creation context of table `'%s`.`%s` is invalid
 - Error number: [1605](#); Symbol: [ER_EVENT_INVALID_CREATION_CTX](#); SQLSTATE: [HY000](#)

Message: Creation context of event `'%s`.`%s` is invalid
 - Error number: [1606](#); Symbol: [ER_TRG_CANT_OPEN_TABLE](#); SQLSTATE: [HY000](#)

Message: Cannot open table for trigger `'%s`.`%s`
 - Error number: [1609](#); Symbol: [ER_NO_FORMAT_DESCRIPTION_EVENT_BEFORE_BINLOG_STATEMENT](#); SQLSTATE: [HY000](#)

Message: The BINLOG statement of type `'%s` was not preceded by a format description BINLOG statement.
 - Error number: [1610](#); Symbol: [ER_SLAVE_CORRUPT_EVENT](#); SQLSTATE: [HY000](#)

Message: Corrupted replication event was detected
 - Error number: [1612](#); Symbol: [ER_LOG_PURGE_NO_FILE](#); SQLSTATE: [HY000](#)

Message: Being purged log %s was not found
 - Error number: [1613](#); Symbol: [ER_XA_RBTIMEOUT](#); SQLSTATE: [XA106](#)

Message: XA_RBTIMEOUT: Transaction branch was rolled back: took too long
 - Error number: [1614](#); Symbol: [ER_XA_RBDEADLOCK](#); SQLSTATE: [XA102](#)

Message: XA_RBDEADLOCK: Transaction branch was rolled back: deadlock was detected

- Error number: [1615](#); Symbol: [ER_NEED_REPREPARE](#); SQLSTATE: [HY000](#)
Message: Prepared statement needs to be re-prepared
- Error number: [1617](#); Symbol: [WARN_NO_MASTER_INFO](#); SQLSTATE: [HY000](#)
Message: The master info structure does not exist
- Error number: [1618](#); Symbol: [WARN_OPTION_IGNORED](#); SQLSTATE: [HY000](#)
Message: <%s> option ignored
- Error number: [1619](#); Symbol: [ER_PLUGIN_DELETE_BUILTIN](#); SQLSTATE: [HY000](#)
Message: Built-in plugins cannot be deleted
- Error number: [1620](#); Symbol: [WARN_PLUGIN_BUSY](#); SQLSTATE: [HY000](#)
Message: Plugin is busy and will be uninstalled on shutdown
- Error number: [1621](#); Symbol: [ER_VARIABLE_IS_READONLY](#); SQLSTATE: [HY000](#)
Message: %s variable '%s' is read-only. Use SET %s to assign the value
- Error number: [1622](#); Symbol: [ER_WARN_ENGINE_TRANSACTION_ROLLBACK](#); SQLSTATE: [HY000](#)
Message: Storage engine %s does not support rollback for this statement. Transaction rolled back and must be restarted
- Error number: [1624](#); Symbol: [ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE](#); SQLSTATE: [HY000](#)
Message: The requested value for the heartbeat period is either negative or exceeds the maximum allowed (%s seconds).
- Error number: [1625](#); Symbol: [ER_NDB_REPLICATION_SCHEMA_ERROR](#); SQLSTATE: [HY000](#)
Message: Bad schema for mysql.ndb_replication table. Message: %s
- Error number: [1626](#); Symbol: [ER_CONFLICT_FN_PARSE_ERROR](#); SQLSTATE: [HY000](#)
Message: Error in parsing conflict function. Message: %s
- Error number: [1627](#); Symbol: [ER_EXCEPTIONS_WRITE_ERROR](#); SQLSTATE: [HY000](#)
Message: Write to exceptions table failed. Message: %s
- Error number: [1628](#); Symbol: [ER_TOO_LONG_TABLE_COMMENT](#); SQLSTATE: [HY000](#)
Message: Comment for table '%s' is too long (max = %lu)
- Error number: [1629](#); Symbol: [ER_TOO_LONG_FIELD_COMMENT](#); SQLSTATE: [HY000](#)
Message: Comment for field '%s' is too long (max = %lu)
- Error number: [1630](#); Symbol: [ER_FUNC_INEXISTENT_NAME_COLLISION](#); SQLSTATE: [42000](#)
Message: FUNCTION %s does not exist. Check the 'Function Name Parsing and Resolution' section in the Reference Manual
- Error number: [1631](#); Symbol: [ER_DATABASE_NAME](#); SQLSTATE: [HY000](#)
Message: Database
- Error number: [1632](#); Symbol: [ER_TABLE_NAME](#); SQLSTATE: [HY000](#)

Message: Table

- Error number: 1633; Symbol: `ER_PARTITION_NAME`; SQLSTATE: `HY000`

Message: Partition

- Error number: 1634; Symbol: `ER_SUBPARTITION_NAME`; SQLSTATE: `HY000`

Message: Subpartition

- Error number: 1635; Symbol: `ER_TEMPORARY_NAME`; SQLSTATE: `HY000`

Message: Temporary

- Error number: 1636; Symbol: `ER_RENAMED_NAME`; SQLSTATE: `HY000`

Message: Renamed

- Error number: 1637; Symbol: `ER_TOO_MANY_CONCURRENT_TRXS`; SQLSTATE: `HY000`

Message: Too many active concurrent transactions

- Error number: 1638; Symbol: `WARN_NON_ASCII_SEPARATOR_NOT_IMPLEMENTED`; SQLSTATE: `HY000`

Message: Non-ASCII separator arguments are not fully supported

- Error number: 1639; Symbol: `ER_DEBUG_SYNC_TIMEOUT`; SQLSTATE: `HY000`

Message: debug sync point wait timed out

- Error number: 1640; Symbol: `ER_DEBUG_SYNC_HIT_LIMIT`; SQLSTATE: `HY000`

Message: debug sync point hit limit reached

- Error number: 1641; Symbol: `ER_DUP_SIGNAL_SET`; SQLSTATE: `42000`

Message: Duplicate condition information item '%s'

- Error number: 1642; Symbol: `ER_SIGNAL_WARN`; SQLSTATE: `01000`

Message: Unhandled user-defined warning condition

- Error number: 1643; Symbol: `ER_SIGNAL_NOT_FOUND`; SQLSTATE: `02000`

Message: Unhandled user-defined not found condition

- Error number: 1644; Symbol: `ER_SIGNAL_EXCEPTION`; SQLSTATE: `HY000`

Message: Unhandled user-defined exception condition

- Error number: 1645; Symbol: `ER_RESIGNAL_WITHOUT_ACTIVE_HANDLER`; SQLSTATE: `0K000`

Message: RESIGNAL when handler not active

- Error number: 1646; Symbol: `ER_SIGNAL_BAD_CONDITION_TYPE`; SQLSTATE: `HY000`

Message: SIGNAL/RESIGNAL can only use a CONDITION defined with SQLSTATE

- Error number: 1647; Symbol: `WARN_COND_ITEM_TRUNCATED`; SQLSTATE: `HY000`

Message: Data truncated for condition item '%s'

- Error number: 1648; Symbol: `ER_COND_ITEM_TOO_LONG`; SQLSTATE: `HY000`

Message: Data too long for condition item '%s'

- Error number: [1649](#); Symbol: [ER_UNKNOWN_LOCALE](#); SQLSTATE: [HY000](#)

Message: Unknown locale: '%s'

- Error number: [1650](#); Symbol: [ER_SLAVE_IGNORE_SERVER_IDS](#); SQLSTATE: [HY000](#)

Message: The requested server id %d clashes with the slave startup option --replicate-same-server-id

- Error number: [1651](#); Symbol: [ER_QUERY_CACHE_DISABLED](#); SQLSTATE: [HY000](#)

Message: Query cache is disabled; restart the server with query_cache_type=1 to enable it
[ER_QUERY_CACHE_DISABLED](#) was removed after 8.0.2.

- Error number: [1652](#); Symbol: [ER_SAME_NAME_PARTITION_FIELD](#); SQLSTATE: [HY000](#)

Message: Duplicate partition field name '%s'

- Error number: [1653](#); Symbol: [ER_PARTITION_COLUMN_LIST_ERROR](#); SQLSTATE: [HY000](#)

Message: Inconsistency in usage of column lists for partitioning

- Error number: [1654](#); Symbol: [ER_WRONG_TYPE_COLUMN_VALUE_ERROR](#); SQLSTATE: [HY000](#)

Message: Partition column values of incorrect type

- Error number: [1655](#); Symbol: [ER_TOO_MANY_PARTITION_FUNC_FIELDS_ERROR](#); SQLSTATE: [HY000](#)

Message: Too many fields in '%s'

- Error number: [1656](#); Symbol: [ER_MAXVALUE_IN_VALUES_IN](#); SQLSTATE: [HY000](#)

Message: Cannot use MAXVALUE as value in VALUES IN

- Error number: [1657](#); Symbol: [ER_TOO_MANY_VALUES_ERROR](#); SQLSTATE: [HY000](#)

Message: Cannot have more than one value for this type of %s partitioning

- Error number: [1658](#); Symbol: [ER_ROW_SINGLE_PARTITION_FIELD_ERROR](#); SQLSTATE: [HY000](#)

Message: Row expressions in VALUES IN only allowed for multi-field column partitioning

- Error number: [1659](#); Symbol: [ER_FIELD_TYPE_NOT_ALLOWED_AS_PARTITION_FIELD](#); SQLSTATE: [HY000](#)

Message: Field '%s' is of a not allowed type for this type of partitioning

- Error number: [1660](#); Symbol: [ER_PARTITION_FIELDS_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: The total length of the partitioning fields is too large

- Error number: [1661](#); Symbol: [ER_BINLOG_ROW_ENGINE_AND_STMT_ENGINE](#); SQLSTATE: [HY000](#)

Message: Cannot execute statement: impossible to write to binary log since both row-incapable engines and statement-incapable engines are involved.

- Error number: [1662](#); Symbol: [ER_BINLOG_ROW_MODE_AND_STMT_ENGINE](#); SQLSTATE: [HY000](#)

Message: Cannot execute statement: impossible to write to binary log since BINLOG_FORMAT = ROW and at least one table uses a storage engine limited to statement-based logging.

- Error number: [1663](#); Symbol: [ER_BINLOG_UNSAFE_AND_STMT_ENGINE](#); SQLSTATE: [HY000](#)

Message: Cannot execute statement: impossible to write to binary log since statement is unsafe, storage engine is limited to statement-based logging, and BINLOG_FORMAT = MIXED. %s
- Error number: [1664](#); Symbol: [ER_BINLOG_ROW_INJECTION_AND_STMT_ENGINE](#); SQLSTATE: [HY000](#)

Message: Cannot execute statement: impossible to write to binary log since statement is in row format and at least one table uses a storage engine limited to statement-based logging.
- Error number: [1665](#); Symbol: [ER_BINLOG_STMT_MODE_AND_ROW_ENGINE](#); SQLSTATE: [HY000](#)

Message: Cannot execute statement: impossible to write to binary log since BINLOG_FORMAT = STATEMENT and at least one table uses a storage engine limited to row-based logging.%s
- Error number: [1666](#); Symbol: [ER_BINLOG_ROW_INJECTION_AND_STMT_MODE](#); SQLSTATE: [HY000](#)

Message: Cannot execute statement: impossible to write to binary log since statement is in row format and BINLOG_FORMAT = STATEMENT.
- Error number: [1667](#); Symbol: [ER_BINLOG_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE](#); SQLSTATE: [HY000](#)

Message: Cannot execute statement: impossible to write to binary log since more than one engine is involved and at least one engine is self-logging.
- Error number: [1668](#); Symbol: [ER_BINLOG_UNSAFE_LIMIT](#); SQLSTATE: [HY000](#)

Message: The statement is unsafe because it uses a LIMIT clause. This is unsafe because the set of rows included cannot be predicted.
- Error number: [1670](#); Symbol: [ER_BINLOG_UNSAFE_SYSTEM_TABLE](#); SQLSTATE: [HY000](#)

Message: The statement is unsafe because it uses the general log, slow query log, or performance_schema table(s). This is unsafe because system tables may differ on slaves.
- Error number: [1671](#); Symbol: [ER_BINLOG_UNSAFE_AUTOINC_COLUMNS](#); SQLSTATE: [HY000](#)

Message: Statement is unsafe because it invokes a trigger or a stored function that inserts into an AUTO_INCREMENT column. Inserted values cannot be logged correctly.
- Error number: [1672](#); Symbol: [ER_BINLOG_UNSAFE_UDF](#); SQLSTATE: [HY000](#)

Message: Statement is unsafe because it uses a UDF which may not return the same value on the slave.
- Error number: [1673](#); Symbol: [ER_BINLOG_UNSAFE_SYSTEM_VARIABLE](#); SQLSTATE: [HY000](#)

Message: Statement is unsafe because it uses a system variable that may have a different value on the slave.
- Error number: [1674](#); Symbol: [ER_BINLOG_UNSAFE_SYSTEM_FUNCTION](#); SQLSTATE: [HY000](#)

Message: Statement is unsafe because it uses a system function that may return a different value on the slave.
- Error number: [1675](#); Symbol: [ER_BINLOG_UNSAFE_NONTRANS_AFTER_TRANS](#); SQLSTATE: [HY000](#)

Message: Statement is unsafe because it accesses a non-transactional table after accessing a transactional table within the same transaction.

- Error number: [1676](#); Symbol: [ER_MESSAGE_AND_STATEMENT](#); SQLSTATE: [HY000](#)

Message: %s Statement: %s
- Error number: [1677](#); Symbol: [ER_SLAVE_CONVERSION_FAILED](#); SQLSTATE: [HY000](#)

Message: Column %d of table '%s.%s' cannot be converted from type '%s' to type '%s'
[ER_SLAVE_CONVERSION_FAILED](#) was removed after 8.0.4.
- Error number: [1678](#); Symbol: [ER_SLAVE_CANT_CREATE_CONVERSION](#); SQLSTATE: [HY000](#)

Message: Can't create conversion table for table '%s.%s'
- Error number: [1679](#); Symbol: [ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_FORMAT](#); SQLSTATE: [HY000](#)

Message: Cannot modify @@session.binlog_format inside a transaction
- Error number: [1680](#); Symbol: [ER_PATH_LENGTH](#); SQLSTATE: [HY000](#)

Message: The path specified for %s is too long.
- Error number: [1681](#); Symbol: [ER_WARN_DEPRECATED_SYNTAX_NO_REPLACEMENT](#); SQLSTATE: [HY000](#)

Message: '%s' is deprecated and will be removed in a future release.
- Error number: [1682](#); Symbol: [ER_WRONG_NATIVE_TABLE_STRUCTURE](#); SQLSTATE: [HY000](#)

Message: Native table '%s'.'%s' has the wrong structure
- Error number: [1683](#); Symbol: [ER_WRONG_PERFSCHEMA_USAGE](#); SQLSTATE: [HY000](#)

Message: Invalid performance_schema usage.
- Error number: [1684](#); Symbol: [ER_WARN_I_S_SKIPPED_TABLE](#); SQLSTATE: [HY000](#)

Message: Table '%s'.'%s' was skipped since its definition is being modified by concurrent DDL statement
- Error number: [1685](#); Symbol: [ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_DIRECT](#); SQLSTATE: [HY000](#)

Message: Cannot modify @@session.binlog_direct_non_transactional_updates inside a transaction
- Error number: [1686](#); Symbol: [ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_DIRECT](#); SQLSTATE: [HY000](#)

Message: Cannot change the binlog direct flag inside a stored function or trigger
- Error number: [1687](#); Symbol: [ER_SPATIAL_MUST_HAVE_GEOCOL](#); SQLSTATE: [42000](#)

Message: A SPATIAL index may only contain a geometrical type column
- Error number: [1688](#); Symbol: [ER_TOO_LONG_INDEX_COMMENT](#); SQLSTATE: [HY000](#)

Message: Comment for index '%s' is too long (max = %lu)
- Error number: [1689](#); Symbol: [ER_LOCK_ABORTED](#); SQLSTATE: [HY000](#)

Message: Wait on a lock was aborted due to a pending exclusive lock
- Error number: [1690](#); Symbol: [ER_DATA_OUT_OF_RANGE](#); SQLSTATE: [22003](#)

Message: %s value is out of range in '%s'

- Error number: [1691](#); Symbol: [ER_WRONG_SPVAR_TYPE_IN_LIMIT](#); SQLSTATE: [HY000](#)

Message: A variable of a non-integer based type in LIMIT clause

[ER_WRONG_SPVAR_TYPE_IN_LIMIT](#) was removed after 8.0.21.

- Error number: [1692](#); Symbol:

[ER_BINLOG_UNSAFE_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE](#); SQLSTATE: [HY000](#)

Message: Mixing self-logging and non-self-logging engines in a statement is unsafe.

- Error number: [1693](#); Symbol: [ER_BINLOG_UNSAFE_MIXED_STATEMENT](#); SQLSTATE: [HY000](#)

Message: Statement accesses nontransactional table as well as transactional or temporary table, and writes to any of them.

- Error number: [1694](#); Symbol: [ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_SQL_LOG_BIN](#); SQLSTATE: [HY000](#)

Message: Cannot modify @@session.sql_log_bin inside a transaction

- Error number: [1695](#); Symbol: [ER_STORED_FUNCTION_PREVENTS_SWITCH_SQL_LOG_BIN](#); SQLSTATE: [HY000](#)

Message: Cannot change the sql_log_bin inside a stored function or trigger

- Error number: [1696](#); Symbol: [ER_FAILED_READ_FROM_PAR_FILE](#); SQLSTATE: [HY000](#)

Message: Failed to read from the .par file

- Error number: [1697](#); Symbol: [ER_VALUES_IS_NOT_INT_TYPE_ERROR](#); SQLSTATE: [HY000](#)

Message: VALUES value for partition '%s' must have type INT

- Error number: [1698](#); Symbol: [ER_ACCESS_DENIED_NO_PASSWORD_ERROR](#); SQLSTATE: [28000](#)

Message: Access denied for user '%s'@'%s'

- Error number: [1699](#); Symbol: [ER_SET_PASSWORD_AUTH_PLUGIN](#); SQLSTATE: [HY000](#)

Message: SET PASSWORD has no significance for users authenticating via plugins

- Error number: [1701](#); Symbol: [ER_TRUNCATE_ILLEGAL_FK](#); SQLSTATE: [42000](#)

Message: Cannot truncate a table referenced in a foreign key constraint (%s)

- Error number: [1702](#); Symbol: [ER_PLUGIN_IS_PERMANENT](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' is force_plus_permanent and can not be unloaded

- Error number: [1703](#); Symbol: [ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN](#); SQLSTATE: [HY000](#)

Message: The requested value for the heartbeat period is less than 1 millisecond. The value is reset to 0, meaning that heartbeating will effectively be disabled.

- Error number: [1704](#); Symbol: [ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX](#); SQLSTATE: [HY000](#)

Message: The requested value for the heartbeat period exceeds the value of `replica_net_timeout` seconds. A sensible value for the period should be less than the timeout.

- Error number: [1705](#); Symbol: [ER_STMT_CACHE_FULL](#); SQLSTATE: [HY000](#)

Message: Multi-row statements required more than 'max_binlog_stmt_cache_size' bytes of storage; increase this mysqld variable and try again
- Error number: [1706](#); Symbol: [ER_MULTI_UPDATE_KEY_CONFLICT](#); SQLSTATE: [HY000](#)

Message: Primary key/partition key update is not allowed since the table is updated both as '%s' and '%s'.
- Error number: [1707](#); Symbol: [ER_TABLE_NEEDS_REBUILD](#); SQLSTATE: [HY000](#)

Message: Table rebuild required. Please do "ALTER TABLE `%%` FORCE" or dump/reload to fix it!
- Error number: [1708](#); Symbol: [WARN_OPTION_BELOW_LIMIT](#); SQLSTATE: [HY000](#)

Message: The value of '%s' should be no less than the value of '%s'
- Error number: [1709](#); Symbol: [ER_INDEX_COLUMN_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: Index column size too large. The maximum column size is %lu bytes.
- Error number: [1710](#); Symbol: [ER_ERROR_IN_TRIGGER_BODY](#); SQLSTATE: [HY000](#)

Message: Trigger '%s' has an error in its body: '%s'
- Error number: [1711](#); Symbol: [ER_ERROR_IN_UNKNOWN_TRIGGER_BODY](#); SQLSTATE: [HY000](#)

Message: Unknown trigger has an error in its body: '%s'
- Error number: [1712](#); Symbol: [ER_INDEX_CORRUPT](#); SQLSTATE: [HY000](#)

Message: Index %s is corrupted
- Error number: [1713](#); Symbol: [ER_UNDO_RECORD_TOO_BIG](#); SQLSTATE: [HY000](#)

Message: Undo log record is too big.
- Error number: [1714](#); Symbol: [ER_BINLOG_UNSAFE_INSERT_IGNORE_SELECT](#); SQLSTATE: [HY000](#)

Message: INSERT IGNORE... SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are ignored. This order cannot be predicted and may differ on master and the slave.
- Error number: [1715](#); Symbol: [ER_BINLOG_UNSAFE_INSERT_SELECT_UPDATE](#); SQLSTATE: [HY000](#)

Message: INSERT... SELECT... ON DUPLICATE KEY UPDATE is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are updated. This order cannot be predicted and may differ on master and the slave.
- Error number: [1716](#); Symbol: [ER_BINLOG_UNSAFE_REPLACE_SELECT](#); SQLSTATE: [HY000](#)

Message: REPLACE... SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are replaced. This order cannot be predicted and may differ on master and the slave.
- Error number: [1717](#); Symbol: [ER_BINLOG_UNSAFE_CREATE_IGNORE_SELECT](#); SQLSTATE: [HY000](#)

Message: CREATE... IGNORE SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are ignored. This order cannot be predicted and may differ on master and the slave.

- Error number: 1718; Symbol: [ER_BINLOG_UNSAFE_CREATE_REPLACE_SELECT](#); SQLSTATE: HY000

Message: CREATE... REPLACE SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are replaced. This order cannot be predicted and may differ on master and the slave.
- Error number: 1719; Symbol: [ER_BINLOG_UNSAFE_UPDATE_IGNORE](#); SQLSTATE: HY000

Message: UPDATE IGNORE is unsafe because the order in which rows are updated determines which (if any) rows are ignored. This order cannot be predicted and may differ on master and the slave.
- Error number: 1720; Symbol: [ER_PLUGIN_NO_UNINSTALL](#); SQLSTATE: HY000

Message: Plugin '%s' is marked as not dynamically uninstallable. You have to stop the server to uninstall it.
- Error number: 1721; Symbol: [ER_PLUGIN_NO_INSTALL](#); SQLSTATE: HY000

Message: Plugin '%s' is marked as not dynamically installable. You have to stop the server to install it.
- Error number: 1722; Symbol: [ER_BINLOG_UNSAFE_WRITE_AUTOINC_SELECT](#); SQLSTATE: HY000

Message: Statements writing to a table with an auto-increment column after selecting from another table are unsafe because the order in which rows are retrieved determines what (if any) rows will be written. This order cannot be predicted and may differ on master and the slave.
- Error number: 1723; Symbol: [ER_BINLOG_UNSAFE_CREATE_SELECT_AUTOINC](#); SQLSTATE: HY000

Message: CREATE TABLE... SELECT... on a table with an auto-increment column is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are inserted. This order cannot be predicted and may differ on master and the slave.
- Error number: 1724; Symbol: [ER_BINLOG_UNSAFE_INSERT_TWO_KEYS](#); SQLSTATE: HY000

Message: INSERT... ON DUPLICATE KEY UPDATE on a table with more than one UNIQUE KEY is unsafe
- Error number: 1725; Symbol: [ER_TABLE_IN_FK_CHECK](#); SQLSTATE: HY000

Message: Table is being used in foreign key check.
- Error number: 1726; Symbol: [ER_UNSUPPORTED_ENGINE](#); SQLSTATE: HY000

Message: Storage engine '%s' does not support system tables. [%s.%s]
- Error number: 1727; Symbol: [ER_BINLOG_UNSAFE_AUTOINC_NOT_FIRST](#); SQLSTATE: HY000

Message: INSERT into autoincrement field which is not the first part in the composed primary key is unsafe.
- Error number: 1728; Symbol: [ER_CANNOT_LOAD_FROM_TABLE_V2](#); SQLSTATE: HY000

Message: Cannot load from %s.%s. The table is probably corrupted
- Error number: 1729; Symbol: [ER_MASTER_DELAY_VALUE_OUT_OF_RANGE](#); SQLSTATE: HY000

Message: The requested value %s for the master delay exceeds the maximum %u

- Error number: 1730; Symbol: `ER_ONLY_FD_AND_RBR_EVENTS_ALLOWED_IN_BINLOG_STATEMENT`; SQLSTATE: HY000
Message: Only Format_description_log_event and row events are allowed in BINLOG statements (but %s was provided)
- Error number: 1731; Symbol: `ER_PARTITION_EXCHANGE_DIFFERENT_OPTION`; SQLSTATE: HY000
Message: Non matching attribute '%s' between partition and table
- Error number: 1732; Symbol: `ER_PARTITION_EXCHANGE_PART_TABLE`; SQLSTATE: HY000
Message: Table to exchange with partition is partitioned: '%s'
- Error number: 1733; Symbol: `ER_PARTITION_EXCHANGE_TEMP_TABLE`; SQLSTATE: HY000
Message: Table to exchange with partition is temporary: '%s'
- Error number: 1734; Symbol: `ER_PARTITION_INSTEAD_OF_SUBPARTITION`; SQLSTATE: HY000
Message: Subpartitioned table, use subpartition instead of partition
- Error number: 1735; Symbol: `ER_UNKNOWN_PARTITION`; SQLSTATE: HY000
Message: Unknown partition '%s' in table '%s'
- Error number: 1736; Symbol: `ER_TABLES_DIFFERENT_METADATA`; SQLSTATE: HY000
Message: Tables have different definitions
- Error number: 1737; Symbol: `ER_ROW_DOES_NOT_MATCH_PARTITION`; SQLSTATE: HY000
Message: Found a row that does not match the partition
- Error number: 1738; Symbol: `ER_BINLOG_CACHE_SIZE_GREATER_THAN_MAX`; SQLSTATE: HY000
Message: Option binlog_cache_size (%lu) is greater than max_binlog_cache_size (%lu); setting binlog_cache_size equal to max_binlog_cache_size.
- Error number: 1739; Symbol: `ER_WARN_INDEX_NOT_APPLICABLE`; SQLSTATE: HY000
Message: Cannot use %s access on index '%s' due to type or collation conversion on field '%s'
- Error number: 1740; Symbol: `ER_PARTITION_EXCHANGE_FOREIGN_KEY`; SQLSTATE: HY000
Message: Table to exchange with partition has foreign key references: '%s'
- Error number: 1742; Symbol: `ER_RPL_INFO_DATA_TOO_LONG`; SQLSTATE: HY000
Message: Data for column '%s' too long
- Error number: 1745; Symbol: `ER_BINLOG_STMT_CACHE_SIZE_GREATER_THAN_MAX`; SQLSTATE: HY000
Message: Option binlog_stmt_cache_size (%lu) is greater than max_binlog_stmt_cache_size (%lu); setting binlog_stmt_cache_size equal to max_binlog_stmt_cache_size.
- Error number: 1746; Symbol: `ER_CANT_UPDATE_TABLE_IN_CREATE_TABLE_SELECT`; SQLSTATE: HY000
Message: Can't update table '%s' while '%s' is being created.

- Error number: 1747; Symbol: `ER_PARTITION_CLAUSE_ON_NONPARTITIONED`; SQLSTATE: `HY000`

Message: PARTITION () clause on non partitioned table
- Error number: 1748; Symbol: `ER_ROW_DOES_NOT_MATCH_GIVEN_PARTITION_SET`; SQLSTATE: `HY000`

Message: Found a row not matching the given partition set
- Error number: 1750; Symbol: `ER_CHANGE_RPL_INFO_REPOSITORY_FAILURE`; SQLSTATE: `HY000`

Message: Failure while changing the type of replication repository: %s.
- Error number: 1751; Symbol: `ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_CREATED_TEMP_TABLE`; SQLSTATE: `HY000`

Message: The creation of some temporary tables could not be rolled back.
- Error number: 1752; Symbol: `ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_DROPPED_TEMP_TABLE`; SQLSTATE: `HY000`

Message: Some temporary tables were dropped, but these operations could not be rolled back.
- Error number: 1753; Symbol: `ER_MTS_FEATURE_IS_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: %s is not supported in multi-threaded slave mode. %s
- Error number: 1754; Symbol: `ER_MTS_UPDATED_DBs_GREATER_MAX`; SQLSTATE: `HY000`

Message: The number of modified databases exceeds the maximum %d; the database names will not be included in the replication event metadata.
- Error number: 1755; Symbol: `ER_MTS_CANT_PARALLEL`; SQLSTATE: `HY000`

Message: Cannot execute the current event group in the parallel mode. Encountered event %s, relay-log name %s, position %s which prevents execution of this event group in parallel mode. Reason: %s.
- Error number: 1756; Symbol: `ER_MTS_INCONSISTENT_DATA`; SQLSTATE: `HY000`

Message: %s
- Error number: 1757; Symbol: `ER_FULLTEXT_NOT_SUPPORTED_WITH_PARTITIONING`; SQLSTATE: `HY000`

Message: FULLTEXT index is not supported for partitioned tables.
- Error number: 1758; Symbol: `ER_DA_INVALID_CONDITION_NUMBER`; SQLSTATE: `35000`

Message: Invalid condition number
- Error number: 1759; Symbol: `ER_INSECURE_PLAIN_TEXT`; SQLSTATE: `HY000`

Message: Sending passwords in plain text without SSL/TLS is extremely insecure.
- Error number: 1760; Symbol: `ER_INSECURE_CHANGE_MASTER`; SQLSTATE: `HY000`

Message: Storing MySQL user name or password information in the master info repository is not secure and is therefore not recommended. Please consider using the USER and PASSWORD connection options for START SLAVE; see the 'START SLAVE Syntax' in the MySQL Manual for more information.

- Error number: [1761](#); Symbol: [ER_FOREIGN_DUPLICATE_KEY_WITH_CHILD_INFO](#); SQLSTATE: [23000](#)

Message: Foreign key constraint for table '%s', record '%s' would lead to a duplicate entry in table '%s', key '%s'
- Error number: [1762](#); Symbol: [ER_FOREIGN_DUPLICATE_KEY_WITHOUT_CHILD_INFO](#); SQLSTATE: [23000](#)

Message: Foreign key constraint for table '%s', record '%s' would lead to a duplicate entry in a child table
- Error number: [1763](#); Symbol: [ER_SQLTHREAD_WITH_SECURE_SLAVE](#); SQLSTATE: [HY000](#)

Message: Setting authentication options is not possible when only the Slave SQL Thread is being started.
- Error number: [1764](#); Symbol: [ER_TABLE_HAS_NO_FT](#); SQLSTATE: [HY000](#)

Message: The table does not have FULLTEXT index to support this query
- Error number: [1765](#); Symbol: [ER_VARIABLE_NOT_SETTABLE_IN_SF_OR_TRIGGER](#); SQLSTATE: [HY000](#)

Message: The system variable %s cannot be set in stored functions or triggers.
- Error number: [1766](#); Symbol: [ER_VARIABLE_NOT_SETTABLE_IN_TRANSACTION](#); SQLSTATE: [HY000](#)

Message: The system variable %s cannot be set when there is an ongoing transaction.
- Error number: [1769](#); Symbol: [ER_SET_STATEMENT_CANNOT_INVOKE_FUNCTION](#); SQLSTATE: [HY000](#)

Message: The statement 'SET %s' cannot invoke a stored function.
- Error number: [1770](#); Symbol: [ER_GTID_NEXT_CANT_BE_AUTOMATIC_IF_GTID_NEXT_LIST_IS_NON_NULL](#); SQLSTATE: [HY000](#)

Message: The system variable @@SESSION.GTID_NEXT cannot be 'AUTOMATIC' when @@SESSION.GTID_NEXT_LIST is non-NULL.
- Error number: [1772](#); Symbol: [ER_MALFORMED_GTID_SET_SPECIFICATION](#); SQLSTATE: [HY000](#)

Message: Malformed GTID set specification '%s'.
- Error number: [1773](#); Symbol: [ER_MALFORMED_GTID_SET_ENCODING](#); SQLSTATE: [HY000](#)

Message: Malformed GTID set encoding.
- Error number: [1774](#); Symbol: [ER_MALFORMED_GTID_SPECIFICATION](#); SQLSTATE: [HY000](#)

Message: Malformed GTID specification '%s'.
- Error number: [1775](#); Symbol: [ER_GNO_EXHAUSTED](#); SQLSTATE: [HY000](#)

Message: Impossible to generate GTID: the integer component reached the maximum value. Restart the server with a new server_uuid.
- Error number: [1776](#); Symbol: [ER_BAD_SLAVE_AUTO_POSITION](#); SQLSTATE: [HY000](#)

Message: Parameters MASTER_LOG_FILE, MASTER_LOG_POS, RELAY_LOG_FILE and RELAY_LOG_POS cannot be set when MASTER_AUTO_POSITION is active.

- Error number: [1777](#); Symbol: `ER_AUTO_POSITION_REQUIRES_GTID_MODE_NOT_OFF`; SQLSTATE: `HY000`

Message: CHANGE MASTER TO MASTER_AUTO_POSITION = 1 cannot be executed because @@GLOBAL.GTID_MODE = OFF.
- Error number: [1778](#); Symbol: `ER_CANT_DO_IMPLICIT_COMMIT_IN_TRX_WHEN_GTID_NEXT_IS_SET`; SQLSTATE: `HY000`

Message: Cannot execute statements with implicit commit inside a transaction when @@SESSION.GTID_NEXT == 'UUID:NUMBER'.
- Error number: [1779](#); Symbol: `ER_GTID_MODE_ON_REQUIRES_ENFORCE_GTID_CONSISTENCY_ON`; SQLSTATE: `HY000`

Message: GTID_MODE = ON requires ENFORCE_GTID_CONSISTENCY = ON.
- Error number: [1781](#); Symbol: `ER_CANT_SET_GTID_NEXT_TO_GTID_WHEN_GTID_MODE_IS_OFF`; SQLSTATE: `HY000`

Message: @@SESSION.GTID_NEXT cannot be set to UUID:NUMBER when @@GLOBAL.GTID_MODE = OFF.
- Error number: [1782](#); Symbol: `ER_CANT_SET_GTID_NEXT_TO_ANONYMOUS_WHEN_GTID_MODE_IS_ON`; SQLSTATE: `HY000`

Message: @@SESSION.GTID_NEXT cannot be set to ANONYMOUS when @@GLOBAL.GTID_MODE = ON.
- Error number: [1783](#); Symbol: `ER_CANT_SET_GTID_NEXT_LIST_TO_NON_NULL_WHEN_GTID_MODE_IS_OFF`; SQLSTATE: `HY000`

Message: @@SESSION.GTID_NEXT_LIST cannot be set to a non-NULL value when @@GLOBAL.GTID_MODE = OFF.
- Error number: [1785](#); Symbol: `ER_GTID_UNSAFE_NON_TRANSACTIONAL_TABLE`; SQLSTATE: `HY000`

Message: Statement violates GTID consistency: Updates to non-transactional tables can only be done in either autocommitted statements or single-statement transactions, and never in the same statement as updates to transactional tables.
- Error number: [1786](#); Symbol: `ER_GTID_UNSAFE_CREATE_SELECT`; SQLSTATE: `HY000`

Message: Statement violates GTID consistency: CREATE TABLE ... SELECT.
- Error number: [1787](#); Symbol: `ER_GTID_UNSAFE_CREATE_DROP_TEMPORARY_TABLE_IN_TRANSACTION`; SQLSTATE: `HY000`

Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE can only be executed outside transactional context. These statements are also not allowed in a function or trigger because functions and triggers are also considered to be multi-statement transactions.

`ER_GTID_UNSAFE_CREATE_DROP_TEMPORARY_TABLE_IN_TRANSACTION` was removed after 8.0.12.

- Error number: [1788](#); Symbol: [ER_GTID_MODE_CAN_ONLY_CHANGE_ONE_STEP_AT_A_TIME](#); SQLSTATE: [HY000](#)

Message: The value of @@GLOBAL.GTID_MODE can only be changed one step at a time: OFF <-> OFF_PERMISSIVE <-> ON_PERMISSIVE <-> ON. Also note that this value must be stepped up or down simultaneously on all servers. See the Manual for instructions.
- Error number: [1789](#); Symbol: [ER_MASTER_HAS_PURGED_REQUIRED_GTIDS](#); SQLSTATE: [HY000](#)

Message: Cannot replicate because the master purged required binary logs. Replicate the missing transactions from elsewhere, or provision a new slave from backup. Consider increasing the master's binary log expiration period. %s
- Error number: [1790](#); Symbol: [ER_CANT_SET_GTID_NEXT_WHEN_OWNING_GTID](#); SQLSTATE: [HY000](#)

Message: @@SESSION.GTID_NEXT cannot be changed by a client that owns a GTID. The client owns %s. Ownership is released on COMMIT or ROLLBACK.
- Error number: [1791](#); Symbol: [ER_UNKNOWN_EXPLAIN_FORMAT](#); SQLSTATE: [HY000](#)

Message: Unknown EXPLAIN format name: '%s'
- Error number: [1792](#); Symbol: [ER_CANT_EXECUTE_IN_READ_ONLY_TRANSACTION](#); SQLSTATE: [25006](#)

Message: Cannot execute statement in a READ ONLY transaction.
- Error number: [1793](#); Symbol: [ER_TOO_LONG_TABLE_PARTITION_COMMENT](#); SQLSTATE: [HY000](#)

Message: Comment for table partition '%s' is too long (max = %lu)
- Error number: [1794](#); Symbol: [ER_SLAVE_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Slave is not configured or failed to initialize properly. You must at least set --server-id to enable either a master or a slave. Additional error messages can be found in the MySQL error log.
- Error number: [1795](#); Symbol: [ER_INNODB_FT_LIMIT](#); SQLSTATE: [HY000](#)

Message: InnoDB presently supports one FULLTEXT index creation at a time
- Error number: [1796](#); Symbol: [ER_INNODB_NO_FT_TEMP_TABLE](#); SQLSTATE: [HY000](#)

Message: Cannot create FULLTEXT index on temporary InnoDB table
- Error number: [1797](#); Symbol: [ER_INNODB_FT_WRONG_DOCID_COLUMN](#); SQLSTATE: [HY000](#)

Message: Column '%s' is of wrong type for an InnoDB FULLTEXT index
- Error number: [1798](#); Symbol: [ER_INNODB_FT_WRONG_DOCID_INDEX](#); SQLSTATE: [HY000](#)

Message: Index '%s' is of wrong type for an InnoDB FULLTEXT index
- Error number: [1799](#); Symbol: [ER_INNODB_ONLINE_LOG_TOO_BIG](#); SQLSTATE: [HY000](#)

Message: Creating index '%s' required more than 'innodb_online_alter_log_max_size' bytes of modification log. Please try again.
- Error number: [1800](#); Symbol: [ER_UNKNOWN_ALTER_ALGORITHM](#); SQLSTATE: [HY000](#)

Message: Unknown ALGORITHM '%s'
- Error number: [1801](#); Symbol: [ER_UNKNOWN_ALTER_LOCK](#); SQLSTATE: [HY000](#)

Message: Unknown LOCK type '%s'

- Error number: [1802](#); Symbol: [ER_MTS_CHANGE_MASTER_CANT_RUN_WITH_GAPS](#); SQLSTATE: [HY000](#)

Message: CHANGE MASTER cannot be executed when the slave was stopped with an error or killed in MTS mode. Consider using RESET SLAVE or START SLAVE UNTIL.

- Error number: [1803](#); Symbol: [ER_MTS_RECOVERY_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot recover after SLAVE errored out in parallel execution mode. Additional error messages can be found in the MySQL error log.

- Error number: [1804](#); Symbol: [ER_MTS_RESET_WORKERS](#); SQLSTATE: [HY000](#)

Message: Cannot clean up worker info tables. Additional error messages can be found in the MySQL error log.

- Error number: [1805](#); Symbol: [ER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2](#); SQLSTATE: [HY000](#)

Message: Column count of %s.%s is wrong. Expected %d, found %d. The table is probably corrupted

- Error number: [1806](#); Symbol: [ER_SLAVE_SILENT_RETRY_TRANSACTION](#); SQLSTATE: [HY000](#)

Message: Slave must silently retry current transaction

- Error number: [1807](#); Symbol: [ER_DISCARD_FK_CHECKS_RUNNING](#); SQLSTATE: [HY000](#)

Message: There is a foreign key check running on table '%s'. Cannot discard the table.

- Error number: [1808](#); Symbol: [ER_TABLE_SCHEMA_MISMATCH](#); SQLSTATE: [HY000](#)

Message: Schema mismatch (%s)

- Error number: [1809](#); Symbol: [ER_TABLE_IN_SYSTEM_TABLESPACE](#); SQLSTATE: [HY000](#)

Message: Table '%s' in system tablespace

- Error number: [1810](#); Symbol: [ER_IO_READ_ERROR](#); SQLSTATE: [HY000](#)

Message: IO Read error: (%lu, %s) %s

- Error number: [1811](#); Symbol: [ER_IO_WRITE_ERROR](#); SQLSTATE: [HY000](#)

Message: IO Write error: (%lu, %s) %s

- Error number: [1812](#); Symbol: [ER_TABLESPACE_MISSING](#); SQLSTATE: [HY000](#)

Message: Tablespace is missing for table %s.

- Error number: [1813](#); Symbol: [ER_TABLESPACE_EXISTS](#); SQLSTATE: [HY000](#)

Message: Tablespace '%s' exists.

- Error number: [1814](#); Symbol: [ER_TABLESPACE_DISCARDED](#); SQLSTATE: [HY000](#)

Message: Tablespace has been discarded for table '%s'

- Error number: [1815](#); Symbol: [ER_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)

Message: Internal error: %s

- Error number: [1816](#); Symbol: [ER_INNODB_IMPORT_ERROR](#); SQLSTATE: [HY000](#)

Message: ALTER TABLE %s IMPORT TABLESPACE failed with error %lu : '%s'
- Error number: [1817](#); Symbol: [ER_INNODB_INDEX_CORRUPT](#); SQLSTATE: [HY000](#)

Message: Index corrupt: %s
- Error number: [1818](#); Symbol: [ER_INVALID_YEAR_COLUMN_LENGTH](#); SQLSTATE: [HY000](#)

Message: Invalid display width. Use YEAR instead.
- Error number: [1819](#); Symbol: [ER_NOT_VALID_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Your password does not satisfy the current policy requirements
- Error number: [1820](#); Symbol: [ER_MUST_CHANGE_PASSWORD](#); SQLSTATE: [HY000](#)

Message: You must reset your password using ALTER USER statement before executing this statement.
- Error number: [1821](#); Symbol: [ER_FK_NO_INDEX_CHILD](#); SQLSTATE: [HY000](#)

Message: Failed to add the foreign key constraint. Missing index for constraint '%s' in the foreign table '%s'
- Error number: [1822](#); Symbol: [ER_FK_NO_INDEX_PARENT](#); SQLSTATE: [HY000](#)

Message: Failed to add the foreign key constraint. Missing index for constraint '%s' in the referenced table '%s'
- Error number: [1823](#); Symbol: [ER_FK_FAIL_ADD_SYSTEM](#); SQLSTATE: [HY000](#)

Message: Failed to add the foreign key constraint '%s' to system tables
- Error number: [1824](#); Symbol: [ER_FK_CANNOT_OPEN_PARENT](#); SQLSTATE: [HY000](#)

Message: Failed to open the referenced table '%s'
- Error number: [1825](#); Symbol: [ER_FK_INCORRECT_OPTION](#); SQLSTATE: [HY000](#)

Message: Failed to add the foreign key constraint on table '%s'. Incorrect options in FOREIGN KEY constraint '%s'
- Error number: [1826](#); Symbol: [ER_FK_DUP_NAME](#); SQLSTATE: [HY000](#)

Message: Duplicate foreign key constraint name '%s'
- Error number: [1827](#); Symbol: [ER_PASSWORD_FORMAT](#); SQLSTATE: [HY000](#)

Message: The password hash doesn't have the expected format.
- Error number: [1828](#); Symbol: [ER_FK_COLUMN_CANNOT_DROP](#); SQLSTATE: [HY000](#)

Message: Cannot drop column '%s': needed in a foreign key constraint '%s'
- Error number: [1829](#); Symbol: [ER_FK_COLUMN_CANNOT_DROP_CHILD](#); SQLSTATE: [HY000](#)

Message: Cannot drop column '%s': needed in a foreign key constraint '%s' of table '%s'
- Error number: [1830](#); Symbol: [ER_FK_COLUMN_NOT_NULL](#); SQLSTATE: [HY000](#)

Message: Column '%s' cannot be NOT NULL: needed in a foreign key constraint '%s' SET NULL

-
- Error number: [1831](#); Symbol: [ER_DUP_INDEX](#); SQLSTATE: HY000
Message: Duplicate index '%s' defined on the table '%s.%s'. This is deprecated and will be disallowed in a future release.
 - Error number: [1832](#); Symbol: [ER_FK_COLUMN_CANNOT_CHANGE](#); SQLSTATE: HY000
Message: Cannot change column '%s': used in a foreign key constraint '%s'
 - Error number: [1833](#); Symbol: [ER_FK_COLUMN_CANNOT_CHANGE_CHILD](#); SQLSTATE: HY000
Message: Cannot change column '%s': used in a foreign key constraint '%s' of table '%s'
 - Error number: [1835](#); Symbol: [ER_MALFORMED_PACKET](#); SQLSTATE: HY000
Message: Malformed communication packet.
 - Error number: [1836](#); Symbol: [ER_READ_ONLY_MODE](#); SQLSTATE: HY000
Message: Running in read-only mode
 - Error number: [1837](#); Symbol: [ER_GTID_NEXT_TYPE_UNDEFINED_GROUP](#); SQLSTATE: HY000
Message: When @@SESSION.GTID_NEXT is set to a GTID, you must explicitly set it to a different value after a COMMIT or ROLLBACK. Please check GTID_NEXT variable manual page for detailed explanation. Current @@SESSION.GTID_NEXT is '%s'.
[ER_GTID_NEXT_TYPE_UNDEFINED_GROUP](#) was removed after 8.0.4.
 - Error number: [1837](#); Symbol: [ER_GTID_NEXT_TYPE_UNDEFINED_GTID](#); SQLSTATE: HY000
Message: When @@SESSION.GTID_NEXT is set to a GTID, you must explicitly set it to a different value after a COMMIT or ROLLBACK. Please check GTID_NEXT variable manual page for detailed explanation. Current @@SESSION.GTID_NEXT is '%s'.
[ER_GTID_NEXT_TYPE_UNDEFINED_GTID](#) was added in 8.0.11.
 - Error number: [1838](#); Symbol: [ER_VARIABLE_NOT_SETTABLE_IN_SP](#); SQLSTATE: HY000
Message: The system variable %s cannot be set in stored procedures.
 - Error number: [1840](#); Symbol: [ER_CANT_SET_GTID_PURGED_WHEN_GTID_EXECUTED_IS_NOT_EMPTY](#); SQLSTATE: HY000
Message: @@GLOBAL.GTID_PURGED can only be set when @@GLOBAL.GTID_EXECUTED is empty.
 - Error number: [1841](#); Symbol: [ER_CANT_SET_GTID_PURGED_WHEN_OWNED_GTIDS_IS_NOT_EMPTY](#); SQLSTATE: HY000
Message: @@GLOBAL.GTID_PURGED can only be set when there are no ongoing transactions (not even in other clients).
 - Error number: [1842](#); Symbol: [ER_GTID_PURGED_WAS_CHANGED](#); SQLSTATE: HY000
Message: @@GLOBAL.GTID_PURGED was changed from '%s' to '%s'.
 - Error number: [1843](#); Symbol: [ER_GTID_EXECUTED_WAS_CHANGED](#); SQLSTATE: HY000
Message: @@GLOBAL.GTID_EXECUTED was changed from '%s' to '%s'.
 - Error number: [1844](#); Symbol: [ER_BINLOG_STMT_MODE_AND_NO_REPL_TABLES](#); SQLSTATE: HY000

Message: Cannot execute statement: impossible to write to binary log since BINLOG_FORMAT = STATEMENT, and both replicated and non replicated tables are written to.

- Error number: [1845](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED](#); SQLSTATE: [0A000](#)

Message: %s is not supported for this operation. Try %s.

- Error number: [1846](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON](#); SQLSTATE: [0A000](#)

Message: %s is not supported. Reason: %s. Try %s.

- Error number: [1847](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COPY](#); SQLSTATE: [HY000](#)

Message: COPY algorithm requires a lock

- Error number: [1848](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_PARTITION](#); SQLSTATE: [HY000](#)

Message: Partition specific operations do not yet support LOCK/ALGORITHM

- Error number: [1849](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FK_RENAME](#); SQLSTATE: [HY000](#)

Message: Columns participating in a foreign key are renamed

- Error number: [1850](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COLUMN_TYPE](#); SQLSTATE: [HY000](#)

Message: Cannot change column type INPLACE

- Error number: [1851](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FK_CHECK](#); SQLSTATE: [HY000](#)

Message: Adding foreign keys needs foreign_key_checks=OFF

- Error number: [1853](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NOPK](#); SQLSTATE: [HY000](#)

Message: Dropping a primary key is not allowed without also adding a new primary key

- Error number: [1854](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_AUTOINC](#); SQLSTATE: [HY000](#)

Message: Adding an auto-increment column requires a lock

- Error number: [1855](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_HIDDEN_FTS](#); SQLSTATE: [HY000](#)

Message: Cannot replace hidden FTS_DOC_ID with a user-visible one

- Error number: [1856](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_CHANGE_FTS](#); SQLSTATE: [HY000](#)

Message: Cannot drop or rename FTS_DOC_ID

- Error number: [1857](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FTS](#); SQLSTATE: [HY000](#)

Message: Fulltext index creation requires a lock

-
- Error number: [1858](#); Symbol: [ER_SQL_SLAVE_SKIP_COUNTER_NOT_SETTABLE_IN_GTID_MODE](#); SQLSTATE: [HY000](#)

Message: sql_slave_skip_counter can not be set when the server is running with @@GLOBAL.GTID_MODE = ON. Instead, for each transaction that you want to skip, generate an empty transaction with the same GTID as the transaction

[ER_SQL_SLAVE_SKIP_COUNTER_NOT_SETTABLE_IN_GTID_MODE](#) was removed after 8.0.22.

- Error number: [1859](#); Symbol: [ER_DUP_UNKNOWN_IN_INDEX](#); SQLSTATE: [23000](#)

Message: Duplicate entry for key '%s'

- Error number: [1860](#); Symbol: [ER_IDENT_CAUSES_TOO_LONG_PATH](#); SQLSTATE: [HY000](#)

Message: Long database name and identifier for object resulted in path length exceeding %d characters. Path: '%s'.

- Error number: [1861](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NOT_NULL](#); SQLSTATE: [HY000](#)

Message: cannot silently convert NULL values, as required in this SQL_MODE

- Error number: [1862](#); Symbol: [ER_MUST_CHANGE_PASSWORD_LOGIN](#); SQLSTATE: [HY000](#)

Message: Your password has expired. To log in you must change it using a client that supports expired passwords.

- Error number: [1863](#); Symbol: [ER_ROW_IN_WRONG_PARTITION](#); SQLSTATE: [HY000](#)

Message: Found a row in wrong partition %s

- Error number: [1864](#); Symbol: [ER_MTS_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX](#); SQLSTATE: [HY000](#)

Message: Cannot schedule event %s, relay-log name %s, position %s to Worker thread because its size %lu exceeds %lu of replica_pending_jobs_size_max.

- Error number: [1866](#); Symbol: [ER_BINLOG_LOGICAL_CORRUPTION](#); SQLSTATE: [HY000](#)

Message: The binary log file '%s' is logically corrupted: %s

- Error number: [1867](#); Symbol: [ER_WARN_PURGE_LOG_IN_USE](#); SQLSTATE: [HY000](#)

Message: file %s was not purged because it was being read by %d thread(s), purged only %d out of %d files.

- Error number: [1868](#); Symbol: [ER_WARN_PURGE_LOG_IS_ACTIVE](#); SQLSTATE: [HY000](#)

Message: file %s was not purged because it is the active log file.

- Error number: [1869](#); Symbol: [ER_AUTO_INCREMENT_CONFLICT](#); SQLSTATE: [HY000](#)

Message: Auto-increment value in UPDATE conflicts with internally generated values

- Error number: [1870](#); Symbol: [WARN_ON_BLOCKHOLE_IN_RBR](#); SQLSTATE: [HY000](#)

Message: Row events are not logged for %s statements that modify BLACKHOLE tables in row format. Table(s): '%s'

- Error number: [1871](#); Symbol: [ER_SLAVE_MI_INIT_REPOSITORY](#); SQLSTATE: [HY000](#)

Message: Slave failed to initialize master info structure from the repository

- Error number: [1872](#); Symbol: [ER_SLAVE_RLI_INIT_REPOSITORY](#); SQLSTATE: [HY000](#)

Message: Slave failed to initialize relay log info structure from the repository
- Error number: [1873](#); Symbol: [ER_ACCESS_DENIED_CHANGE_USER_ERROR](#); SQLSTATE: [28000](#)

Message: Access denied trying to change to user '%s'@'%s' (using password: %s). Disconnecting.
- Error number: [1874](#); Symbol: [ER_INNODB_READ_ONLY](#); SQLSTATE: [HY000](#)

Message: InnoDB is in read only mode.
- Error number: [1875](#); Symbol: [ER_STOP_SLAVE_SQL_THREAD_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: STOP SLAVE command execution is incomplete: Slave SQL thread got the stop signal, thread is busy, SQL thread will stop once the current task is complete.
- Error number: [1876](#); Symbol: [ER_STOP_SLAVE_IO_THREAD_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: STOP SLAVE command execution is incomplete: Slave IO thread got the stop signal, thread is busy, IO thread will stop once the current task is complete.
- Error number: [1877](#); Symbol: [ER_TABLE_CORRUPT](#); SQLSTATE: [HY000](#)

Message: Operation cannot be performed. The table '%s.%s' is missing, corrupt or contains bad data.
- Error number: [1878](#); Symbol: [ER_TEMP_FILE_WRITE_FAILURE](#); SQLSTATE: [HY000](#)

Message: Temporary file write failure.
- Error number: [1879](#); Symbol: [ER_INNODB_FT_AUX_NOT_HEX_ID](#); SQLSTATE: [HY000](#)

Message: Upgrade index name failed, please use create index(alter table) algorithm copy to rebuild index.
- Error number: [1880](#); Symbol: [ER_OLD_TEMPORALS_UPGRADED](#); SQLSTATE: [HY000](#)

Message: TIME/TIMESTAMP/DATETIME columns of old format have been upgraded to the new format.
- Error number: [1881](#); Symbol: [ER_INNODB_FORCED_RECOVERY](#); SQLSTATE: [HY000](#)

Message: Operation not allowed when innodb_force_recovery > 0.
- Error number: [1882](#); Symbol: [ER_AES_INVALID_IV](#); SQLSTATE: [HY000](#)

Message: The initialization vector supplied to %s is too short. Must be at least %d bytes long
- Error number: [1883](#); Symbol: [ER_PLUGIN_CANNOT_BE_UNINSTALLED](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' cannot be uninstalled now. %s
- Error number: [1884](#); Symbol: [ER_GTIID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_GTID_GROUP](#); SQLSTATE: [HY000](#)

Message: Cannot execute statement because it needs to be written to the binary log as multiple statements, and this is not allowed when @@SESSION.GTID_NEXT == 'UUID:NUMBER'.
[ER_GTIID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_GTID_GROUP](#) was removed after 8.0.4.

- Error number: [1884](#); Symbol: [ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_ASSIGNED_GTID](#); SQLSTATE: [HY000](#)

Message: Cannot execute statement because it needs to be written to the binary log as multiple statements, and this is not allowed when @@SESSION.GTID_NEXT == 'UUID:NUMBER'.
[ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_ASSIGNED_GTID](#) was added in 8.0.11.
- Error number: [1885](#); Symbol: [ER_SLAVE_HAS_MORE_GTIDS_THAN_MASTER](#); SQLSTATE: [HY000](#)

Message: Slave has more GTIDs than the master has, using the master's SERVER_UUID. This may indicate that the end of the binary log was truncated or that the last binary log file was lost, e.g., after a power or disk failure when sync_binlog != 1. The master may or may not have rolled back transactions that were already replicated to the slave. Suggest to replicate any transactions that master has rolled back from slave to master, and/or commit empty transactions on master to account for transactions that have been committed on master but are not included in GTID_EXECUTED.
- Error number: [1886](#); Symbol: [ER_MISSING_KEY](#); SQLSTATE: [HY000](#)

Message: The table '%s.%s' does not have the necessary key(s) defined on it. Please check the table definition and create index(s) accordingly.
[ER_MISSING_KEY](#) was added in 8.0.4.
- Error number: [1887](#); Symbol: [WARN_NAMED_PIPE_ACCESS_EVERYONE](#); SQLSTATE: [HY000](#)

Message: Setting named_pipe_full_access_group='%s' is insecure. Consider using a Windows group with fewer members.
[WARN_NAMED_PIPE_ACCESS_EVERYONE](#) was added in 8.0.17.
- Error number: [3000](#); Symbol: [ER_FILE_CORRUPT](#); SQLSTATE: [HY000](#)

Message: File %s is corrupted
- Error number: [3001](#); Symbol: [ER_ERROR_ON_MASTER](#); SQLSTATE: [HY000](#)

Message: Query partially completed on the master (error on master: %d) and was aborted. There is a chance that your master is inconsistent at this point. If you are sure that your master is ok, run this query manually on the slave and then restart the slave with SET GLOBAL SQL_REPLICA_SKIP_COUNTER=1; START SLAVE;. Query:'%s'
- Error number: [3003](#); Symbol: [ER_STORAGE_ENGINE_NOT_LOADED](#); SQLSTATE: [HY000](#)

Message: Storage engine for table '%s'.'%s' is not loaded.
- Error number: [3004](#); Symbol: [ER_GET_STACKED_DA_WITHOUT_ACTIVE_HANDLER](#); SQLSTATE: [0Z002](#)

Message: GET STACKED DIAGNOSTICS when handler not active
- Error number: [3005](#); Symbol: [ER_WARN_LEGACY_SYNTAX_CONVERTED](#); SQLSTATE: [HY000](#)

Message: %s is no longer supported. The statement was converted to %s.
- Error number: [3006](#); Symbol: [ER_BINLOG_UNSAFE_FULLTEXT_PLUGIN](#); SQLSTATE: [HY000](#)

Message: Statement is unsafe because it uses a fulltext parser plugin which may not return the same value on the slave.
- Error number: [3007](#); Symbol: [ER_CANNOT_DISCARD_TEMPORARY_TABLE](#); SQLSTATE: [HY000](#)

Message: Cannot DISCARD/IMPORT tablespace associated with temporary table

- Error number: 3008; Symbol: [ER_FK_DEPTH_EXCEEDED](#); SQLSTATE: HY000

Message: Foreign key cascade delete/update exceeds max depth of %d.

- Error number: 3009; Symbol: [ER_COL_COUNT_DOESNT_MATCH PLEASE_UPDATE_V2](#); SQLSTATE: HY000

Message: The column count of %s.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please perform the MySQL upgrade procedure.

- Error number: 3010; Symbol: [ER_WARN_TRIGGER_DOESNT_HAVE_CREATED](#); SQLSTATE: HY000

Message: Trigger %s.%s.%s does not have CREATED attribute.

- Error number: 3011; Symbol: [ER_REFERENCED_TRG_DOES_NOT_EXIST](#); SQLSTATE: HY000

Message: Referenced trigger '%s' for the given action time and event type does not exist.

- Error number: 3012; Symbol: [ER_EXPLAIN_NOT_SUPPORTED](#); SQLSTATE: HY000

Message: EXPLAIN FOR CONNECTION command is supported only for SELECT/UPDATE/INSERT/DELETE/REPLACE

- Error number: 3013; Symbol: [ER_INVALID_FIELD_SIZE](#); SQLSTATE: HY000

Message: Invalid size for column '%s'.

- Error number: 3014; Symbol: [ER_MISSING_HA_CREATE_OPTION](#); SQLSTATE: HY000

Message: Table storage engine '%s' found required create option missing

- Error number: 3015; Symbol: [ER_ENGINE_OUT_OF_MEMORY](#); SQLSTATE: HY000

Message: Out of memory in storage engine '%s'.

- Error number: 3016; Symbol: [ER_PASSWORD_EXPIRE_ANONYMOUS_USER](#); SQLSTATE: HY000

Message: The password for anonymous user cannot be expired.

- Error number: 3017; Symbol: [ER_SLAVE_SQL_THREAD_MUST_STOP](#); SQLSTATE: HY000

Message: This operation cannot be performed with a running slave sql thread; run STOP SLAVE SQL_THREAD first

- Error number: 3018; Symbol: [ER_NO_FT_MATERIALIZED_SUBQUERY](#); SQLSTATE: HY000

Message: Cannot create FULLTEXT index on materialized subquery

- Error number: 3019; Symbol: [ER_INNODB_UNDO_LOG_FULL](#); SQLSTATE: HY000

Message: Undo Log error: %s

- Error number: 3020; Symbol: [ER_INVALID_ARGUMENT_FOR_LOGARITHM](#); SQLSTATE: 2201E

Message: Invalid argument for logarithm

- Error number: 3021; Symbol: [ER_SLAVE_CHANNEL_IO_THREAD_MUST_STOP](#); SQLSTATE: HY000

Message: This operation cannot be performed with a running slave io thread; run STOP SLAVE IO_THREAD FOR CHANNEL '%s' first.

- Error number: 3022; Symbol: `ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO`; SQLSTATE: `HY000`

Message: This operation may not be safe when the slave has temporary tables. The tables will be kept open until the server restarts or until the tables are deleted by any replicated DROP statement. Suggest to wait until `replica_open_temp_tables = 0`.
- Error number: 3023; Symbol: `ER_WARN_ONLY_MASTER_LOG_FILE_NO_POS`; SQLSTATE: `HY000`

Message: CHANGE MASTER TO with a `MASTER_LOG_FILE` clause but no `MASTER_LOG_POS` clause may not be safe. The old position value may not be valid for the new binary log file.
- Error number: 3024; Symbol: `ER_QUERY_TIMEOUT`; SQLSTATE: `HY000`

Message: Query execution was interrupted, maximum statement execution time exceeded
- Error number: 3025; Symbol: `ER_NON_RO_SELECT_DISABLE_TIMER`; SQLSTATE: `HY000`

Message: Select is not a read only statement, disabling timer
- Error number: 3026; Symbol: `ER_DUP_LIST_ENTRY`; SQLSTATE: `HY000`

Message: Duplicate entry '%s'.
- Error number: 3028; Symbol: `ER_AGGREGATE_ORDER_FOR_UNION`; SQLSTATE: `HY000`

Message: Expression #%u of ORDER BY contains aggregate function and applies to a UNION
- Error number: 3029; Symbol: `ER_AGGREGATE_ORDER_NON_AGG_QUERY`; SQLSTATE: `HY000`

Message: Expression #%u of ORDER BY contains aggregate function and applies to the result of a non-aggregated query
- Error number: 3030; Symbol: `ER_SLAVE_WORKER_STOPPED_PREVIOUS_THD_ERROR`; SQLSTATE: `HY000`

Message: Slave worker has stopped after at least one previous worker encountered an error when replica-preserve-commit-order was enabled. To preserve commit order, the last transaction executed by this thread has not been committed. When restarting the slave after fixing any failed threads, you should fix this worker as well.
- Error number: 3031; Symbol: `ER_DONT_SUPPORT_SLAVE_PRESERVE_COMMIT_ORDER`; SQLSTATE: `HY000`

Message: `slave_preserve_commit_order` is not supported %s.
`ER_DONT_SUPPORT_SLAVE_PRESERVE_COMMIT_ORDER` was removed after 8.0.25.
- Error number: 3031; Symbol: `ER_DONT_SUPPORT_REPLICA_PRESERVE_COMMIT_ORDER`; SQLSTATE: `HY000`

Message: `replica_preserve_commit_order` is not supported %s.
`ER_DONT_SUPPORT_REPLICA_PRESERVE_COMMIT_ORDER` was added in 8.0.26.
- Error number: 3032; Symbol: `ER_SERVER_OFFLINE_MODE`; SQLSTATE: `HY000`

Message: The server is currently in offline mode
- Error number: 3033; Symbol: `ER_GIS_DIFFERENT_SRIDS`; SQLSTATE: `HY000`

Message: Binary geometry function %s given two geometries of different srids: %u and %u, which should have been identical.

Geometry values passed as arguments to spatial functions must have the same SRID value.

- Error number: 3034; Symbol: [ER_GIS_UNSUPPORTED_ARGUMENT](#); SQLSTATE: [HY000](#)

Message: Calling geometry function %s with unsupported types of arguments.

A spatial function was called with a combination of argument types that the function does not support.

- Error number: 3035; Symbol: [ER_GIS_UNKNOWN_ERROR](#); SQLSTATE: [HY000](#)

Message: Unknown GIS error occurred in function %s.

- Error number: 3036; Symbol: [ER_GIS_UNKNOWN_EXCEPTION](#); SQLSTATE: [HY000](#)

Message: Unknown exception caught in GIS function %s.

- Error number: 3037; Symbol: [ER_GIS_INVALID_DATA](#); SQLSTATE: [22023](#)

Message: Invalid GIS data provided to function %s.

A spatial function was called with an argument not recognized as a valid geometry value.

- Error number: 3038; Symbol: [ER_BOOST_GEOMETRY_EMPTY_INPUT_EXCEPTION](#); SQLSTATE: [HY000](#)

Message: The geometry has no data in function %s.

- Error number: 3039; Symbol: [ER_BOOST_GEOMETRY_CENTROID_EXCEPTION](#); SQLSTATE: [HY000](#)

Message: Unable to calculate centroid because geometry is empty in function %s.

- Error number: 3040; Symbol: [ER_BOOST_GEOMETRY_OVERLAY_INVALID_INPUT_EXCEPTION](#); SQLSTATE: [HY000](#)

Message: Geometry overlay calculation error: geometry data is invalid in function %s.

- Error number: 3041; Symbol: [ER_BOOST_GEOMETRY_TURN_INFO_EXCEPTION](#); SQLSTATE: [HY000](#)

Message: Geometry turn info calculation error: geometry data is invalid in function %s.

- Error number: 3042; Symbol: [ER_BOOST_GEOMETRY_SELF_INTERSECTION_POINT_EXCEPTION](#); SQLSTATE: [HY000](#)

Message: Analysis procedures of intersection points interrupted unexpectedly in function %s.

- Error number: 3043; Symbol: [ER_BOOST_GEOMETRY_UNKNOWN_EXCEPTION](#); SQLSTATE: [HY000](#)

Message: Unknown exception thrown in function %s.

- Error number: 3044; Symbol: [ER_STD_BAD_ALLOC_ERROR](#); SQLSTATE: [HY000](#)

Message: Memory allocation error: %s in function %s.

- Error number: 3045; Symbol: [ER_STD_DOMAIN_ERROR](#); SQLSTATE: [HY000](#)

Message: Domain error: %s in function %s.

- Error number: 3046; Symbol: [ER_STD_LENGTH_ERROR](#); SQLSTATE: [HY000](#)

Message: Length error: %s in function %s.

-
- Error number: [3047](#); Symbol: [ER_STD_INVALID_ARGUMENT](#); SQLSTATE: [HY000](#)
Message: Invalid argument error: %s in function %s.
 - Error number: [3048](#); Symbol: [ER_STD_OUT_OF_RANGE_ERROR](#); SQLSTATE: [HY000](#)
Message: Out of range error: %s in function %s.
 - Error number: [3049](#); Symbol: [ER_STD_OVERFLOW_ERROR](#); SQLSTATE: [HY000](#)
Message: Overflow error: %s in function %s.
 - Error number: [3050](#); Symbol: [ER_STD_RANGE_ERROR](#); SQLSTATE: [HY000](#)
Message: Range error: %s in function %s.
 - Error number: [3051](#); Symbol: [ER_STD_UNDERFLOW_ERROR](#); SQLSTATE: [HY000](#)
Message: Underflow error: %s in function %s.
 - Error number: [3052](#); Symbol: [ER_STD_LOGIC_ERROR](#); SQLSTATE: [HY000](#)
Message: Logic error: %s in function %s.
 - Error number: [3053](#); Symbol: [ER_STD_RUNTIME_ERROR](#); SQLSTATE: [HY000](#)
Message: Runtime error: %s in function %s.
 - Error number: [3054](#); Symbol: [ER_STD_UNKNOWN_EXCEPTION](#); SQLSTATE: [HY000](#)
Message: Unknown exception: %s in function %s.
 - Error number: [3055](#); Symbol: [ER_GIS_DATA_WRONG_ENDIANESS](#); SQLSTATE: [HY000](#)
Message: Geometry byte string must be little endian.
 - Error number: [3056](#); Symbol: [ER_CHANGE_MASTER_PASSWORD_LENGTH](#); SQLSTATE: [HY000](#)
Message: The password provided for the replication user exceeds the maximum length of 32 characters
 - Error number: [3057](#); Symbol: [ER_USER_LOCK_WRONG_NAME](#); SQLSTATE: [42000](#)
Message: Incorrect user-level lock name '%s'.
 - Error number: [3058](#); Symbol: [ER_USER_LOCK_DEADLOCK](#); SQLSTATE: [HY000](#)
Message: Deadlock found when trying to get user-level lock; try rolling back transaction/releasing locks and restarting lock acquisition.
This error is returned when the metadata locking subsystem detects a deadlock for an attempt to acquire a named lock with [GET_LOCK](#).
 - Error number: [3059](#); Symbol: [ER_REPLACE_INACCESSIBLE_ROWS](#); SQLSTATE: [HY000](#)
Message: REPLACE cannot be executed as it requires deleting rows that are not in the view
 - Error number: [3060](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_GIS](#); SQLSTATE: [HY000](#)
Message: Do not support online operation on table with GIS index
 - Error number: [3061](#); Symbol: [ER_ILLEGAL_USER_VAR](#); SQLSTATE: [42000](#)
Message: User variable name '%s' is illegal

- Error number: [3062](#); Symbol: [ER_GTID_MODE_OFF](#); SQLSTATE: [HY000](#)

Message: Cannot %s when GTID_MODE = OFF.
- Error number: [3064](#); Symbol: [ER_INCORRECT_TYPE](#); SQLSTATE: [HY000](#)

Message: Incorrect type for argument %s in function %s.
- Error number: [3065](#); Symbol: [ER_FIELD_IN_ORDER_NOT_SELECT](#); SQLSTATE: [HY000](#)

Message: Expression #%u of ORDER BY clause is not in SELECT list, references column '%s' which is not in SELECT list; this is incompatible with %s
- Error number: [3066](#); Symbol: [ER_AGGREGATE_IN_ORDER_NOT_SELECT](#); SQLSTATE: [HY000](#)

Message: Expression #%u of ORDER BY clause is not in SELECT list, contains aggregate function; this is incompatible with %s
- Error number: [3067](#); Symbol: [ER_INVALID_RPL_WILD_TABLE_FILTER_PATTERN](#); SQLSTATE: [HY000](#)

Message: Supplied filter list contains a value which is not in the required format 'db_pattern.table_pattern'
- Error number: [3068](#); Symbol: [ER_NET_OK_PACKET_TOO_LARGE](#); SQLSTATE: [08S01](#)

Message: OK packet too large
- Error number: [3069](#); Symbol: [ER_INVALID_JSON_DATA](#); SQLSTATE: [HY000](#)

Message: Invalid JSON data provided to function %s: %s
- Error number: [3070](#); Symbol: [ER_INVALID_GEOJSON_MISSING_MEMBER](#); SQLSTATE: [HY000](#)

Message: Invalid GeoJSON data provided to function %s: Missing required member '%s'
- Error number: [3071](#); Symbol: [ER_INVALID_GEOJSON_WRONG_TYPE](#); SQLSTATE: [HY000](#)

Message: Invalid GeoJSON data provided to function %s: Member '%s' must be of type '%s'
- Error number: [3072](#); Symbol: [ER_INVALID_GEOJSON_UNSPECIFIED](#); SQLSTATE: [HY000](#)

Message: Invalid GeoJSON data provided to function %s
- Error number: [3073](#); Symbol: [ER_DIMENSION_UNSUPPORTED](#); SQLSTATE: [HY000](#)

Message: Unsupported number of coordinate dimensions in function %s: Found %u, expected %u
- Error number: [3074](#); Symbol: [ER_SLAVE_CHANNEL_DOES_NOT_EXIST](#); SQLSTATE: [HY000](#)

Message: Slave channel '%s' does not exist.
- Error number: [3076](#); Symbol: [ER_SLAVE_CHANNEL_NAME_INVALID_OR_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: Couldn't create channel: Channel name is either invalid or too long.
- Error number: [3077](#); Symbol: [ER_SLAVE_NEW_CHANNEL_WRONG_REPOSITORY](#); SQLSTATE: [HY000](#)

Message: To have multiple channels, repository cannot be of type FILE; Please check the repository configuration and convert them to TABLE.
- Error number: [3079](#); Symbol: [ER_SLAVE_MULTIPLE_CHANNELS_CMD](#); SQLSTATE: [HY000](#)

Message: Multiple channels exist on the slave. Please provide channel name as an argument.

- Error number: [3080](#); Symbol: [ER_SLAVE_MAX_CHANNELS_EXCEEDED](#); SQLSTATE: [HY000](#)

Message: Maximum number of replication channels allowed exceeded.

- Error number: [3081](#); Symbol: [ER_SLAVE_CHANNEL_MUST_STOP](#); SQLSTATE: [HY000](#)

Message: This operation cannot be performed with running replication threads; run STOP SLAVE FOR CHANNEL '%s' first

- Error number: [3082](#); Symbol: [ER_SLAVE_CHANNEL_NOT_RUNNING](#); SQLSTATE: [HY000](#)

Message: This operation requires running replication threads; configure slave and run START SLAVE FOR CHANNEL '%s'

- Error number: [3083](#); Symbol: [ER_SLAVE_CHANNEL_WAS_RUNNING](#); SQLSTATE: [HY000](#)

Message: Replication thread(s) for channel '%s' are already running.

- Error number: [3084](#); Symbol: [ER_SLAVE_CHANNEL_WAS_NOT_RUNNING](#); SQLSTATE: [HY000](#)

Message: Replication thread(s) for channel '%s' are already stopped.

- Error number: [3085](#); Symbol: [ER_SLAVE_CHANNEL_SQL_THREAD_MUST_STOP](#); SQLSTATE: [HY000](#)

Message: This operation cannot be performed with a running slave sql thread; run STOP SLAVE SQL_THREAD FOR CHANNEL '%s' first.

- Error number: [3086](#); Symbol: [ER_SLAVE_CHANNEL_SQL_SKIP_COUNTER](#); SQLSTATE: [HY000](#)

Message: When `sql_replica_skip_counter > 0`, it is not allowed to start more than one SQL thread by using 'START SLAVE [SQL_THREAD]'. Value of `sql_replica_skip_counter` can only be used by one SQL thread at a time. Please use 'START SLAVE [SQL_THREAD] FOR CHANNEL' to start the SQL thread which will use the value of `sql_replica_skip_counter`.

- Error number: [3087](#); Symbol: [ER_WRONG_FIELD_WITH_GROUP_V2](#); SQLSTATE: [HY000](#)

Message: Expression #`%u` of %s is not in GROUP BY clause and contains nonaggregated column '%s' which is not functionally dependent on columns in GROUP BY clause; this is incompatible with `sql_mode=only_full_group_by`

- Error number: [3088](#); Symbol: [ER_MIX_OF_GROUP_FUNC_AND_FIELDS_V2](#); SQLSTATE: [HY000](#)

Message: In aggregated query without GROUP BY, expression #`%u` of %s contains nonaggregated column '%s'; this is incompatible with `sql_mode=only_full_group_by`

- Error number: [3089](#); Symbol: [ER_WARN_DEPRECATED_SYSVAR_UPDATE](#); SQLSTATE: [HY000](#)

Message: Updating '%s' is deprecated. It will be made read-only in a future release.

- Error number: [3090](#); Symbol: [ER_WARN_DEPRECATED_SQLMODE](#); SQLSTATE: [HY000](#)

Message: Changing sql mode '%s' is deprecated. It will be removed in a future release.

- Error number: [3091](#); Symbol: [ER_CANNOT_LOG_PARTIAL_DROP_DATABASE_WITH_GTID](#); SQLSTATE: [HY000](#)

Message: DROP DATABASE failed; some tables may have been dropped but the database directory remains. The GTID has not been added to GTID_EXECUTED and the statement was not written to the binary log. Fix this as follows: (1) remove all files from the database directory %s; (2) SET GTID_NEXT='%;' (3) DROP DATABASE `%;`.

- Error number: [3092](#); Symbol: [ER_GROUP_REPLICATION_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: The server is not configured properly to be an active member of the group. Please see more details on error log.
- Error number: [3093](#); Symbol: [ER_GROUP_REPLICATION_RUNNING](#); SQLSTATE: [HY000](#)

Message: The START GROUP_REPLICATION command failed since the group is already running.
- Error number: [3094](#); Symbol: [ER_GROUP_REPLICATION_APPLIER_INIT_ERROR](#); SQLSTATE: [HY000](#)

Message: The START GROUP_REPLICATION command failed as the applier module failed to start.
- Error number: [3095](#); Symbol: [ER_GROUP_REPLICATION_STOP_APPLIER_THREAD_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: The STOP GROUP_REPLICATION command execution is incomplete: The applier thread got the stop signal while it was busy. The applier thread will stop once the current task is complete.
- Error number: [3096](#); Symbol: [ER_GROUP_REPLICATION_COMMUNICATION_LAYER_SESSION_ERROR](#); SQLSTATE: [HY000](#)

Message: The START GROUP_REPLICATION command failed as there was an error when initializing the group communication layer.
- Error number: [3097](#); Symbol: [ER_GROUP_REPLICATION_COMMUNICATION_LAYER_JOIN_ERROR](#); SQLSTATE: [HY000](#)

Message: The START GROUP_REPLICATION command failed as there was an error when joining the communication group.
- Error number: [3098](#); Symbol: [ER_BEFORE_DML_VALIDATION_ERROR](#); SQLSTATE: [HY000](#)

Message: The table does not comply with the requirements by an external plugin.
- Error number: [3099](#); Symbol: [ER_PREVENTS_VARIABLE_WITHOUT_RBR](#); SQLSTATE: [HY000](#)

Message: Cannot change the value of variable %s without binary log format as ROW.
`transaction_write_set_extraction` option value is set and `binlog_format` is not `ROW`.
- Error number: [3100](#); Symbol: [ER_RUN_HOOK_ERROR](#); SQLSTATE: [HY000](#)

Message: Error on observer while running replication hook '%s'.
- Error number: [3101](#); Symbol: [ER_TRANSACTION_ROLLBACK_DURING_COMMIT](#); SQLSTATE: [40000](#)

Message: Plugin instructed the server to rollback the current transaction.

When using Group Replication, this means that a transaction failed the group certification process, due to one or more members detecting a potential conflict, and was thus rolled back. See [Group Replication](#).
- Error number: [3102](#); Symbol: [ER_GENERATED_COLUMN_FUNCTION_IS_NOT_ALLOWED](#); SQLSTATE: [HY000](#)

Message: Expression of generated column '%s' contains a disallowed function.

-
- Error number: [3103](#); Symbol: [ER_UNSUPPORTED_ALTER_INPLACE_ON_VIRTUAL_COLUMN](#); SQLSTATE: [HY000](#)

Message: INPLACE ADD or DROP of virtual columns cannot be combined with other ALTER TABLE actions
 - Error number: [3104](#); Symbol: [ER_WRONG_FK_OPTION_FOR_GENERATED_COLUMN](#); SQLSTATE: [HY000](#)

Message: Cannot define foreign key with %s clause on a generated column.
 - Error number: [3105](#); Symbol: [ER_NON_DEFAULT_VALUE_FOR_GENERATED_COLUMN](#); SQLSTATE: [HY000](#)

Message: The value specified for generated column '%s' in table '%s' is not allowed.
 - Error number: [3106](#); Symbol: [ER_UNSUPPORTED_ACTION_ON_GENERATED_COLUMN](#); SQLSTATE: [HY000](#)

Message: '%s' is not supported for generated columns.
 - Error number: [3107](#); Symbol: [ER_GENERATED_COLUMN_NON_PRIOR](#); SQLSTATE: [HY000](#)

Message: Generated column can refer only to generated columns defined prior to it.
To address this issue, change the table definition to define each generated column later than any generated columns to which it refers.
 - Error number: [3108](#); Symbol: [ER_DEPENDENT_BY_GENERATED_COLUMN](#); SQLSTATE: [HY000](#)

Message: Column '%s' has a generated column dependency.
You cannot drop or rename a generated column if another column refers to it. You must either drop those columns as well, or redefine them not to refer to the generated column.
 - Error number: [3109](#); Symbol: [ER_GENERATED_COLUMN_REF_AUTO_INC](#); SQLSTATE: [HY000](#)

Message: Generated column '%s' cannot refer to auto-increment column.
 - Error number: [3110](#); Symbol: [ER_FEATURE_NOT_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: The '%s' feature is not available; you need to remove '%s' or use MySQL built with '%s'
 - Error number: [3111](#); Symbol: [ER_CANT_SET_GTID_MODE](#); SQLSTATE: [HY000](#)

Message: SET @@GLOBAL.GTID_MODE = %s is not allowed because %s.
 - Error number: [3112](#); Symbol: [ER_CANT_USE_AUTO_POSITION_WITH_GTID_MODE_OFF](#); SQLSTATE: [HY000](#)

Message: The replication receiver thread%s cannot start in AUTO_POSITION mode: this server uses @@GLOBAL.GTID_MODE = OFF.
 - Error number: [3116](#); Symbol:
[ER_CANT_ENFORCE_GTID_CONSISTENCY_WITH_ONGOING_GTID_VIOLATING_TX](#); SQLSTATE: [HY000](#)

Message: Cannot set ENFORCE_GTID_CONSISTENCY = ON because there are ongoing transactions that violate GTID consistency.
[ER_CANT_SET_ENFORCE_GTID_CONSISTENCY_ON_WITH_ONGOING_GTID_VIOLATING_TRANSACTIONS](#) was renamed to
[ER_CANT_ENFORCE_GTID_CONSISTENCY_WITH_ONGOING_GTID_VIOLATING_TX](#).

- Error number: [3117](#); Symbol: [ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_TX](#); SQLSTATE: [HY000](#)

Message: There are ongoing transactions that violate GTID consistency.
[ER_SET_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_TRANSACTIONS](#) was renamed to [ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_TX](#).
- Error number: [3118](#); Symbol: [ER_ACCOUNT_HAS_BEEN_LOCKED](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s'. Account is locked.
The account was locked with [CREATE USER ... ACCOUNT LOCK](#) or [ALTER USER ... ACCOUNT LOCK](#). An administrator can unlock it with [ALTER USER ... ACCOUNT UNLOCK](#).
- Error number: [3119](#); Symbol: [ER_WRONG_TABLESPACE_NAME](#); SQLSTATE: [42000](#)

Message: Incorrect tablespace name `'%s'
- Error number: [3120](#); Symbol: [ER_TABLESPACE_IS_NOT_EMPTY](#); SQLSTATE: [HY000](#)

Message: Tablespace `'%s` is not empty.
- Error number: [3121](#); Symbol: [ER_WRONG_FILE_NAME](#); SQLSTATE: [HY000](#)

Message: Incorrect File Name '%s'.
- Error number: [3122](#); Symbol: [ER_BOOST_GEOMETRY_INCONSISTENT_TURNS_EXCEPTION](#); SQLSTATE: [HY000](#)

Message: Inconsistent intersection points.
- Error number: [3123](#); Symbol: [ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR](#); SQLSTATE: [HY000](#)

Message: Optimizer hint syntax error
- Error number: [3124](#); Symbol: [ER_WARN_BAD_MAX_EXECUTION_TIME](#); SQLSTATE: [HY000](#)

Message: Unsupported MAX_EXECUTION_TIME
- Error number: [3125](#); Symbol: [ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME](#); SQLSTATE: [HY000](#)

Message: MAX_EXECUTION_TIME hint is supported by top-level standalone SELECT statements only
The [MAX_EXECUTION_TIME](#) optimizer hint is supported only for [SELECT](#) statements.
- Error number: [3126](#); Symbol: [ER_WARN_CONFLICTING_HINT](#); SQLSTATE: [HY000](#)

Message: Hint %s is ignored as conflicting/duplicated
- Error number: [3127](#); Symbol: [ER_WARN_UNKNOWN_QB_NAME](#); SQLSTATE: [HY000](#)

Message: Query block name %s is not found for %s hint
- Error number: [3128](#); Symbol: [ER_UNRESOLVED_HINT_NAME](#); SQLSTATE: [HY000](#)

Message: Unresolved name %s for %s hint
- Error number: [3129](#); Symbol: [ER_WARN_ON MODIFYING_GTID_EXECUTED_TABLE](#); SQLSTATE: [HY000](#)

Message: Please do not modify the %s table. This is a mysql internal system table to store GTIDs for committed transactions. Modifying it can lead to an inconsistent GTID state.

- Error number: [3130](#); Symbol: [ER_PLUGGABLE_PROTOCOL_COMMAND_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Command not supported by pluggable protocols

- Error number: [3131](#); Symbol: [ER_LOCKING_SERVICE_WRONG_NAME](#); SQLSTATE: [42000](#)

Message: Incorrect locking service lock name '%s'.

A locking service name was specified as [NULL](#), the empty string, or a string longer than 64 characters. Namespace and lock names must be non-[NULL](#), nonempty, and no more than 64 characters long.

- Error number: [3132](#); Symbol: [ER_LOCKING_SERVICE_DEADLOCK](#); SQLSTATE: [HY000](#)

Message: Deadlock found when trying to get locking service lock; try releasing locks and restarting lock acquisition.

- Error number: [3133](#); Symbol: [ER_LOCKING_SERVICE_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: Service lock wait timeout exceeded.

- Error number: [3134](#); Symbol: [ER_GIS_MAX_POINTS_IN_GEOMETRY_OVERFLOWED](#); SQLSTATE: [HY000](#)

Message: Parameter %s exceeds the maximum number of points in a geometry (%lu) in function %s.

- Error number: [3135](#); Symbol: [ER_SQL_MODE_MERGED](#); SQLSTATE: [HY000](#)

Message: 'NO_ZERO_DATE', 'NO_ZERO_IN_DATE' and 'ERROR_FOR_DIVISION_BY_ZERO' sql modes should be used with strict mode. They will be merged with strict mode in a future release.

- Error number: [3136](#); Symbol: [ER_VTOKEN_PLUGIN_TOKEN_MISMATCH](#); SQLSTATE: [HY000](#)

Message: Version token mismatch for %.*.s. Correct value %.*.s

The client has set its [version_tokens_session](#) system variable to the list of tokens it requires the server to match, but the server token list has at least one matching token name that has a value different from what the client requires. See [Version Tokens](#).

- Error number: [3137](#); Symbol: [ER_VTOKEN_PLUGIN_TOKEN_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Version token %.*.s not found.

The client has set its [version_tokens_session](#) system variable to the list of tokens it requires the server to match, but the server token list is missing at least one of those tokens. See [Version Tokens](#).

- Error number: [3138](#); Symbol: [ER_CANT_SET_VARIABLE_WHEN_OWNING_GTID](#); SQLSTATE: [HY000](#)

Message: Variable %s cannot be changed by a client that owns a GTID. The client owns %.s. Ownership is released on COMMIT or ROLLBACK.

- Error number: [3139](#); Symbol: [ER_SLAVE_CHANNEL_OPERATION_NOT_ALLOWED](#); SQLSTATE: [HY000](#)

Message: %s cannot be performed on channel '%s'.

- Error number: [3140](#); Symbol: [ER_INVALID_JSON_TEXT](#); SQLSTATE: [22032](#)

Message: Invalid JSON text: "%s" at position %u in value for column '%s'.

- Error number: [3141](#); Symbol: [ER_INVALID_JSON_TEXT_IN_PARAM](#); SQLSTATE: [22032](#)

Message: Invalid JSON text in argument %u to function %s: "%s" at position %u.%s

- Error number: [3142](#); Symbol: [ER_INVALID_JSON_BINARY_DATA](#); SQLSTATE: [HY000](#)

Message: The JSON binary value contains invalid data.

- Error number: [3143](#); Symbol: [ER_INVALID_JSON_PATH](#); SQLSTATE: [42000](#)

Message: Invalid JSON path expression. The error is around character position %u.%s

- Error number: [3144](#); Symbol: [ER_INVALID_JSON_CHARSET](#); SQLSTATE: [22032](#)

Message: Cannot create a JSON value from a string with CHARACTER SET '%s'.

- Error number: [3145](#); Symbol: [ER_INVALID_JSON_CHARSET_IN_FUNCTION](#); SQLSTATE: [22032](#)

Message: Invalid JSON character data provided to function %s: '%s'; utf8 is required.

- Error number: [3146](#); Symbol: [ER_INVALID_TYPE_FOR_JSON](#); SQLSTATE: [22032](#)

Message: Invalid data type for JSON data in argument %u to function %s; a JSON string or JSON type is required.

- Error number: [3147](#); Symbol: [ER_INVALID_CAST_TO_JSON](#); SQLSTATE: [22032](#)

Message: Cannot CAST value to JSON.

- Error number: [3148](#); Symbol: [ER_INVALID_JSON_PATH_CHARSET](#); SQLSTATE: [42000](#)

Message: A path expression must be encoded in the utf8 character set. The path expression '%s' is encoded in character set '%s'.

- Error number: [3149](#); Symbol: [ER_INVALID_JSON_PATH_WILDCARD](#); SQLSTATE: [42000](#)

Message: In this situation, path expressions may not contain the * and ** tokens or an array range.

- Error number: [3150](#); Symbol: [ER_JSON_VALUE_TOO_BIG](#); SQLSTATE: [22032](#)

Message: The JSON value is too big to be stored in a JSON column.

- Error number: [3151](#); Symbol: [ER_JSON_KEY_TOO_BIG](#); SQLSTATE: [22032](#)

Message: The JSON object contains a key name that is too long.

- Error number: [3152](#); Symbol: [ER_JSON_USED_AS_KEY](#); SQLSTATE: [42000](#)

Message: JSON column '%s' supports indexing only via generated columns on a specified JSON path.

- Error number: [3153](#); Symbol: [ER_JSON_VACUOUS_PATH](#); SQLSTATE: [42000](#)

Message: The path expression '\$' is not allowed in this context.

- Error number: [3154](#); Symbol: [ER_JSON_BAD_ONE_OR_ALL_ARG](#); SQLSTATE: [42000](#)

Message: The oneOrAll argument to %s may take these values: 'one' or 'all'.

- Error number: [3155](#); Symbol: [ER_NUMERIC_JSON_VALUE_OUT_OF_RANGE](#); SQLSTATE: [22003](#)

Message: Out of range JSON value for CAST to %s% from column %s at row %ld

-
- Error number: [3156](#); Symbol: [ER_INVALID_JSON_VALUE_FOR_CAST](#); SQLSTATE: [22018](#)

Message: Invalid JSON value for CAST to %s%s from column %s at row %ld
 - Error number: [3157](#); Symbol: [ER_JSON_DOCUMENT_TOO_DEEP](#); SQLSTATE: [22032](#)

Message: The JSON document exceeds the maximum depth.
 - Error number: [3158](#); Symbol: [ER_JSON_DOCUMENT_NULL_KEY](#); SQLSTATE: [22032](#)

Message: JSON documents may not contain NULL member names.
 - Error number: [3159](#); Symbol: [ER_SECURE_TRANSPORT_REQUIRED](#); SQLSTATE: [HY000](#)

Message: Connections using insecure transport are prohibited while --require_secure_transport=ON.
With the `require_secure_transport` system variable, clients can connect only using secure transports. Qualifying connections are those using SSL, a Unix socket file, or shared memory.
 - Error number: [3160](#); Symbol: [ER_NO_SECURE_TRANSPORTS_CONFIGURED](#); SQLSTATE: [HY000](#)

Message: No secure transports (SSL or Shared Memory) are configured, unable to set --require_secure_transport=ON.
The `require_secure_transport` system variable cannot be enabled if the server does not support at least one secure transport. Configure the server with the required SSL keys/certificates to enable SSL connections, or enable the `shared_memory` system variable to enable shared-memory connections.
 - Error number: [3161](#); Symbol: [ER_DISABLED_STORAGE_ENGINE](#); SQLSTATE: [HY000](#)

Message: Storage engine %s is disabled (Table creation is disallowed).
An attempt was made to create a table or tablespace using a storage engine listed in the value of the `disabled_storage_engines` system variable, or to change an existing table or tablespace to such an engine. Choose a different storage engine.
 - Error number: [3162](#); Symbol: [ER_USER_DOES_NOT_EXIST](#); SQLSTATE: [HY000](#)

Message: Authorization ID %s does not exist.
 - Error number: [3163](#); Symbol: [ER_USER_ALREADY_EXISTS](#); SQLSTATE: [HY000](#)

Message: Authorization ID %s already exists.
 - Error number: [3164](#); Symbol: [ER_AUDIT_API_ABORT](#); SQLSTATE: [HY000](#)

Message: Aborted by Audit API ('%s';%d).
This error indicates that an audit plugin terminated execution of an event. The message typically indicates the event subclass name and a numeric status value.
 - Error number: [3165](#); Symbol: [ER_INVALID_JSON_PATH_ARRAY_CELL](#); SQLSTATE: [42000](#)

Message: A path expression is not a path to a cell in an array.
 - Error number: [3166](#); Symbol: [ER_BUFPOOL_RESIZE_INPROGRESS](#); SQLSTATE: [HY000](#)

Message: Another buffer pool resize is already in progress.
 - Error number: [3167](#); Symbol: [ER_FEATURE_DISABLED_SEE_DOC](#); SQLSTATE: [HY000](#)

Message: The '%s' feature is disabled; see the documentation for '%s'

- Error number: 3168; Symbol: `ER_SERVER_ISNT_AVAILABLE`; SQLSTATE: `HY000`

Message: Server isn't available
- Error number: 3169; Symbol: `ER_SESSION_WAS_KILLED`; SQLSTATE: `HY000`

Message: Session was killed
- Error number: 3170; Symbol: `ER_CAPACITY_EXCEEDED`; SQLSTATE: `HY000`

Message: Memory capacity of %lu bytes for '%s' exceeded. %s
- Error number: 3171; Symbol: `ER_CAPACITY_EXCEEDED_IN_RANGE_OPTIMIZER`; SQLSTATE: `HY000`

Message: Range optimization was not done for this query.
- Error number: 3173; Symbol: `ER_CANT_WAIT_FOR_EXECUTED_GTID_SET_WHILE_OWNING_A_GTID`; SQLSTATE: `HY000`

Message: The client holds ownership of the GTID %.s. Therefore, WAIT_FOR_EXECUTED_GTID_SET cannot wait for this GTID.
- Error number: 3174; Symbol: `ER_CANNOT_ADD_FOREIGN_BASE_COL_VIRTUAL`; SQLSTATE: `HY000`

Message: Cannot add foreign key on the base column of indexed virtual column.
- Error number: 3175; Symbol: `ER_CANNOT_CREATE_VIRTUAL_INDEX_CONSTRAINT`; SQLSTATE: `HY000`

Message: Cannot create index on virtual column whose base column has foreign constraint.
- Error number: 3176; Symbol: `ER_ERROR_ON MODIFYING_GTID_EXECUTED_TABLE`; SQLSTATE: `HY000`

Message: Please do not modify the %.s table with an XA transaction. This is an internal system table used to store GTIDs for committed transactions. Although modifying it can lead to an inconsistent GTID state, if necessary you can modify it with a non-XA transaction.
- Error number: 3177; Symbol: `ER_LOCK_REFUSED_BY_ENGINE`; SQLSTATE: `HY000`

Message: Lock acquisition refused by storage engine.
- Error number: 3178; Symbol: `ER_UNSUPPORTED_ALTER_ONLINE_ON_VIRTUAL_COLUMN`; SQLSTATE: `HY000`

Message: ADD COLUMN col...VIRTUAL, ADD INDEX(col)
- Error number: 3179; Symbol: `ER_MASTER_KEY_ROTATION_NOT_SUPPORTED_BY_SE`; SQLSTATE: `HY000`

Message: Master key rotation is not supported by storage engine.
- Error number: 3181; Symbol: `ER_MASTER_KEY_ROTATION_BINLOG_FAILED`; SQLSTATE: `HY000`

Message: Write to binlog failed. However, master key rotation has been completed successfully.
- Error number: 3182; Symbol: `ER_MASTER_KEY_ROTATION_SE_UNAVAILABLE`; SQLSTATE: `HY000`

Message: Storage engine is not available.
- Error number: 3183; Symbol: `ER_TABLESPACE_CANNOT_ENCRYPT`; SQLSTATE: `HY000`

Message: This tablespace can't be encrypted.

- Error number: [3184](#); Symbol: [ER_INVALID_ENCRYPTION_OPTION](#); SQLSTATE: [HY000](#)

Message: Invalid encryption option.

- Error number: [3185](#); Symbol: [ER_CANNOT_FIND_KEY_IN_KEYRING](#); SQLSTATE: [HY000](#)

Message: Can't find master key from keyring, please check in the server log if a keyring is loaded and initialized successfully.

- Error number: [3186](#); Symbol: [ER_CAPACITY_EXCEEDED_IN_PARSER](#); SQLSTATE: [HY000](#)

Message: Parser bailed out for this query.

- Error number: [3187](#); Symbol: [ER_UNSUPPORTED_ALTER_ENCRYPTION_INPLACE](#); SQLSTATE: [HY000](#)

Message: Cannot alter encryption attribute by inplace algorithm.

- Error number: [3188](#); Symbol: [ER_KEYRING_UDF_KEYRING_SERVICE_ERROR](#); SQLSTATE: [HY000](#)

Message: Function '%s' failed because underlying keyring service returned an error. Please check if a keyring is installed and that provided arguments are valid for the keyring you are using.

- Error number: [3189](#); Symbol: [ER_USER_COLUMN_OLD_LENGTH](#); SQLSTATE: [HY000](#)

Message: It seems that your db schema is old. The %s column is 77 characters long and should be 93 characters long. Please perform the MySQL upgrade procedure.

- Error number: [3190](#); Symbol: [ER_CANT_RESET_MASTER](#); SQLSTATE: [HY000](#)

Message: RESET MASTER is not allowed because %s.

- Error number: [3191](#); Symbol: [ER_GROUP_REPLICATION_MAX_GROUP_SIZE](#); SQLSTATE: [HY000](#)

Message: The START GROUP_REPLICATION command failed since the group already has 9 members.

- Error number: [3192](#); Symbol: [ER_CANNOT_ADD_FOREIGN_BASE_COL_STORED](#); SQLSTATE: [HY000](#)

Message: Cannot add foreign key on the base column of stored column.

- Error number: [3193](#); Symbol: [ER_TABLE_REFERENCED](#); SQLSTATE: [HY000](#)

Message: Cannot complete the operation because table is referenced by another connection.

- Error number: [3197](#); Symbol: [ER_XA_RETRY](#); SQLSTATE: [HY000](#)

Message: The resource manager is not able to commit the transaction branch at this time. Please retry later.

[ER_XA_RETRY](#) was added in 8.0.2.

- Error number: [3198](#); Symbol: [ER_KEYRING_AWS_UDF_AWS_KMS_ERROR](#); SQLSTATE: [HY000](#)

Message: Function %s failed due to: %s.

[ER_KEYRING_AWS_UDF_AWS_KMS_ERROR](#) was added in 8.0.2.

- Error number: [3199](#); Symbol: [ER_BINLOG_UNSAFE_XA](#); SQLSTATE: [HY000](#)

Message: Statement is unsafe because it is being used inside a XA transaction. Concurrent XA transactions may deadlock on slaves when replicated using statements.

`ER_BINLOG_UNSAFE_XA` was added in 8.0.2.

- Error number: `3200`; Symbol: `ER_UDF_ERROR`; SQLSTATE: `HY000`

Message: %s UDF failed; %s

`ER_UDF_ERROR` was added in 8.0.4.

- Error number: `3201`; Symbol: `ER_KEYRING_MIGRATION_FAILURE`; SQLSTATE: `HY000`

Message: Can not perform keyring migration : %s

`ER_KEYRING_MIGRATION_FAILURE` was added in 8.0.4.

- Error number: `3202`; Symbol: `ER_KEYRING_ACCESS_DENIED_ERROR`; SQLSTATE: `42000`

Message: Access denied; you need %s privileges for this operation

`ER_KEYRING_ACCESS_DENIED_ERROR` was added in 8.0.4.

- Error number: `3203`; Symbol: `ER_KEYRING_MIGRATION_STATUS`; SQLSTATE: `HY000`

Message: Keyring migration %s.

`ER_KEYRING_MIGRATION_STATUS` was added in 8.0.4.

- Error number: `3218`; Symbol:

`ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH_ARG_VALUE`; SQLSTATE: `HY000`

Message: Invalid "max_array_length" argument value.

`ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH_ARG_VALUE` was added in 8.0.11.

- Error number: `3231`; Symbol: `ER_WRITE_SET_EXCEEDS_LIMIT`; SQLSTATE: `HY000`

Message: The size of writeset data for the current transaction exceeds a limit imposed by an external component. If using Group Replication check 'group_replication_transaction_size_limit'.

`ER_WRITE_SET_EXCEEDS_LIMIT` was added in 8.0.23.

- Error number: `3500`; Symbol: `ER_UNSUPPORTED_COMPRESSED_TEMPORARY_TABLE`; SQLSTATE: `HY000`

Message: CREATE TEMPORARY TABLE is not allowed with ROW_FORMAT=COMPRESSED or KEY_BLOCK_SIZE.

- Error number: `3501`; Symbol: `ER_ACL_OPERATION_FAILED`; SQLSTATE: `HY000`

Message: The ACL operation failed due to the following error from SE: errcode %d - %s

- Error number: `3502`; Symbol: `ER_UNSUPPORTED_INDEX_ALGORITHM`; SQLSTATE: `HY000`

Message: This storage engine does not support the %s index algorithm, storage engine default was used instead.

- Error number: `3503`; Symbol: `ER_NO_SUCH_DB`; SQLSTATE: `42Y07`

Message: Database '%s' doesn't exist

- Error number: `3504`; Symbol: `ER_TOO_BIG_ENUM`; SQLSTATE: `HY000`

Message: Too many enumeration values for column %s.

- Error number: 3505; Symbol: `ER_TOO_LONG_SET_ENUM_VALUE`; SQLSTATE: `HY000`

Message: Too long enumeration/set value for column %s.

- Error number: 3506; Symbol: `ER_INVALID_DD_OBJECT`; SQLSTATE: `HY000`

Message: %s dictionary object is invalid. (%s)

- Error number: 3507; Symbol: `ER_UPDATING_DD_TABLE`; SQLSTATE: `HY000`

Message: Failed to update %s dictionary object.

- Error number: 3508; Symbol: `ER_INVALID_DD_OBJECT_ID`; SQLSTATE: `HY000`

Message: Dictionary object id (%lu) does not exist.

- Error number: 3509; Symbol: `ER_INVALID_DD_OBJECT_NAME`; SQLSTATE: `HY000`

Message: Dictionary object name '%s' is invalid. (%s)

- Error number: 3510; Symbol: `ER_TABLESPACE_MISSING_WITH_NAME`; SQLSTATE: `HY000`

Message: Tablespace %s doesn't exist.

- Error number: 3511; Symbol: `ER_TOO_LONG_ROUTINE_COMMENT`; SQLSTATE: `HY000`

Message: Comment for routine '%s' is too long (max = %lu)

- Error number: 3512; Symbol: `ER_SP_LOAD_FAILED`; SQLSTATE: `HY000`

Message: Failed to load routine '%s'.

- Error number: 3513; Symbol: `ER_INVALID_BITWISE_OPERANDS_SIZE`; SQLSTATE: `HY000`

Message: Binary operands of bitwise operators must be of equal length

- Error number: 3514; Symbol: `ER_INVALID_BITWISE_AGGREGATE_OPERANDS_SIZE`; SQLSTATE: `HY000`

Message: Aggregate bitwise functions cannot accept arguments longer than 511 bytes; consider using the SUBSTRING() function

- Error number: 3515; Symbol: `ER_WARN_UNSUPPORTED_HINT`; SQLSTATE: `HY000`

Message: Hints aren't supported in %s

- Error number: 3516; Symbol: `ER_UNEXPECTED_GEOMETRY_TYPE`; SQLSTATE: `22S01`

Message: %s value is a geometry of unexpected type %s in %s.

- Error number: 3517; Symbol: `ER_SRS_PARSE_ERROR`; SQLSTATE: `SR002`

Message: Can't parse the spatial reference system definition of SRID %u.

- Error number: 3518; Symbol: `ER_SRS_PROJ_PARAMETER_MISSING`; SQLSTATE: `SR003`

Message: The spatial reference system definition for SRID %u does not specify the mandatory %s (EPSG %u) projection parameter.

- Error number: 3519; Symbol: `ER_WARN_SRS_NOT_FOUND`; SQLSTATE: `01000`

Message: There's no spatial reference system with SRID %u.

- Error number: 3520; Symbol: [ER_SRS_NOT_CARTESIAN](#); SQLSTATE: 22S00
Message: Function %s is only defined for Cartesian spatial reference systems, but one of its arguments is in SRID %u, which is not Cartesian.
- Error number: 3521; Symbol: [ER_SRS_NOT_CARTESIAN_UNDEFINED](#); SQLSTATE: SR001
Message: Function %s is only defined for Cartesian spatial reference systems, but one of its arguments is in SRID %u, which has not been defined.
- Error number: 3522; Symbol: [ER_PK_INDEX_CANT_BE_INVISIBLE](#); SQLSTATE: HY000
Message: A primary key index cannot be invisible
- Error number: 3523; Symbol: [ER_UNKNOWN_AUTHID](#); SQLSTATE: HY000
Message: Unknown authorization ID `'%s` @`%s`
- Error number: 3524; Symbol: [ER_FAILED_ROLE_GRANT](#); SQLSTATE: HY000
Message: Failed to grant %s` to %s
- Error number: 3525; Symbol: [ER_OPEN_ROLE_TABLES](#); SQLSTATE: HY000
Message: Failed to open the security system tables
- Error number: 3526; Symbol: [ER_FAILED_DEFAULT_ROLES](#); SQLSTATE: HY000
Message: Failed to set default roles
- Error number: 3527; Symbol: [ER_COMPONENTS_NO_SCHEME](#); SQLSTATE: HY000
Message: Cannot find schema in specified URN: '%s'.
- Error number: 3528; Symbol: [ER_COMPONENTS_NO_SCHEME_SERVICE](#); SQLSTATE: HY000
Message: Cannot acquire scheme load service implementation for schema '%s' in specified URN: '%s'.
- Error number: 3529; Symbol: [ER_COMPONENTS_CANT_LOAD](#); SQLSTATE: HY000
Message: Cannot load component from specified URN: '%s'.
- Error number: 3530; Symbol: [ER_ROLE_NOT_GRANTED](#); SQLSTATE: HY000
Message: `'%s` @`%s` is not granted to `'%s` @`%s`
- Error number: 3531; Symbol: [ER_FAILED_REVOKE_ROLE](#); SQLSTATE: HY000
Message: Could not revoke role from `'%s` @`%s`
- Error number: 3532; Symbol: [ER_RENAME_ROLE](#); SQLSTATE: HY000
Message: Renaming of a role identifier is forbidden
- Error number: 3533; Symbol: [ER_COMPONENTS_CANT_ACQUIRE_SERVICE_IMPLEMENTATION](#); SQLSTATE: HY000
Message: Cannot acquire specified service implementation: '%s'.
- Error number: 3534; Symbol: [ER_COMPONENTS_CANT_SATISFY_DEPENDENCY](#); SQLSTATE: HY000
Message: Cannot satisfy dependency for service '%s' required by component '%s'.

-
- Error number: [3535](#); Symbol: [ER_COMPONENTS_LOAD_CANT_REGISTER_SERVICE_IMPLEMENTATION](#); SQLSTATE: HY000
Message: Cannot register service implementation '%s' provided by component '%s'.
 - Error number: [3536](#); Symbol: [ER_COMPONENTS_LOAD_CANT_INITIALIZE](#); SQLSTATE: HY000
Message: Initialization method provided by component '%s' failed.
 - Error number: [3537](#); Symbol: [ER_COMPONENTS_UNLOAD_NOT_LOADED](#); SQLSTATE: HY000
Message: Component specified by URN '%s' to unload has not been loaded before.
 - Error number: [3538](#); Symbol: [ER_COMPONENTS_UNLOAD_CANT_DEINITIALIZE](#); SQLSTATE: HY000
Message: De-initialization method provided by component '%s' failed.
 - Error number: [3539](#); Symbol: [ER_COMPONENTS_CANT_RELEASE_SERVICE](#); SQLSTATE: HY000
Message: Release of previously acquired service implementation failed.
 - Error number: [3540](#); Symbol: [ER_COMPONENTS_UNLOAD_CANT_UNREGISTER_SERVICE](#); SQLSTATE: HY000
Message: Unregistration of service implementation '%s' provided by component '%s' failed during unloading of the component.
 - Error number: [3541](#); Symbol: [ER_COMPONENTS_CANT_UNLOAD](#); SQLSTATE: HY000
Message: Cannot unload component from specified URN: '%s'.
 - Error number: [3542](#); Symbol: [ER_WARN_UNLOAD_THE_NOT_PERSISTED](#); SQLSTATE: HY000
Message: The Persistent Dynamic Loader was used to unload a component '%s', but it was not used to load that component before.
 - Error number: [3543](#); Symbol: [ER_COMPONENT_TABLE_INCORRECT](#); SQLSTATE: HY000
Message: The mysql.component table is missing or has an incorrect definition.
 - Error number: [3544](#); Symbol: [ER_COMPONENT_MANIPULATE_ROW_FAILED](#); SQLSTATE: HY000
Message: Failed to manipulate component '%s' persistence data. Error code %d from storage engine.
 - Error number: [3545](#); Symbol: [ER_COMPONENTS_UNLOAD_DUPLICATE_IN_GROUP](#); SQLSTATE: HY000
Message: The component with specified URN: '%s' was specified in group more than once.
 - Error number: [3546](#); Symbol: [ER_CANT_SET_GTID_PURGED_DUE_SETS_CONSTRAINTS](#); SQLSTATE: HY000
Message: @@GLOBAL.GTID_PURGED cannot be changed: %s
 - Error number: [3547](#); Symbol: [ER_CANNOT_LOCK_USER_MANAGEMENT_CACHES](#); SQLSTATE: HY000
Message: Can not lock user management caches for processing.
 - Error number: [3548](#); Symbol: [ER_SRS_NOT_FOUND](#); SQLSTATE: SR001
Message: There's no spatial reference system with SRID %u.

- Error number: 3549; Symbol: `ER_VARIABLE_NOT_PERSISTED`; SQLSTATE: `HY000`

Message: Variables cannot be persisted. Please retry.
- Error number: 3550; Symbol: `ER_IS_QUERY_INVALID_CLAUSE`; SQLSTATE: `HY000`

Message: Information schema queries do not support the '%s' clause.
- Error number: 3551; Symbol: `ER_UNABLE_TO_STORE_STATISTICS`; SQLSTATE: `HY000`

Message: Unable to store dynamic %s statistics into data dictionary.
- Error number: 3552; Symbol: `ER_NO_SYSTEM_SCHEMA_ACCESS`; SQLSTATE: `HY000`

Message: Access to system schema '%s' is rejected.
- Error number: 3553; Symbol: `ER_NO_SYSTEM_TABLESPACE_ACCESS`; SQLSTATE: `HY000`

Message: Access to system tablespace '%s' is rejected.
- Error number: 3554; Symbol: `ER_NO_SYSTEM_TABLE_ACCESS`; SQLSTATE: `HY000`

Message: Access to %s '%s.%s' is rejected.
- Error number: 3555; Symbol: `ER_NO_SYSTEM_TABLE_ACCESS_FOR_DICTIONARY_TABLE`; SQLSTATE: `HY000`

Message: data dictionary table
`ER_NO_SYSTEM_TABLE_ACCESS_FOR_DICTIONARY_TABLE` was added in 8.0.1.
- Error number: 3556; Symbol: `ER_NO_SYSTEM_TABLE_ACCESS_FOR_SYSTEM_TABLE`; SQLSTATE: `HY000`

Message: system table
`ER_NO_SYSTEM_TABLE_ACCESS_FOR_SYSTEM_TABLE` was added in 8.0.1.
- Error number: 3557; Symbol: `ER_NO_SYSTEM_TABLE_ACCESS_FOR_TABLE`; SQLSTATE: `HY000`

Message: table
`ER_NO_SYSTEM_TABLE_ACCESS_FOR_TABLE` was added in 8.0.1.
- Error number: 3558; Symbol: `ER_INVALID_OPTION_KEY`; SQLSTATE: `22023`

Message: Invalid option key '%s' in function %s.
`ER_INVALID_OPTION_KEY` was added in 8.0.1.
- Error number: 3559; Symbol: `ER_INVALID_OPTION_VALUE`; SQLSTATE: `22023`

Message: Invalid value '%s' for option '%s' in function '%s'.
`ER_INVALID_OPTION_VALUE` was added in 8.0.1.
- Error number: 3560; Symbol: `ER_INVALID_OPTION_KEY_VALUE_PAIR`; SQLSTATE: `22023`

Message: The string '%s' is not a valid key %c value pair in function %s.
`ER_INVALID_OPTION_KEY_VALUE_PAIR` was added in 8.0.1.
- Error number: 3561; Symbol: `ER_INVALID_OPTION_START_CHARACTER`; SQLSTATE: `22023`

Message: The options argument in function %s starts with the invalid character '%c'.

`ER_INVALID_OPTION_START_CHARACTER` was added in 8.0.1.

- Error number: 3562; Symbol: `ER_INVALID_OPTION_END_CHARACTER`; SQLSTATE: 22023

Message: The options argument in function %s ends with the invalid character '%c'.

`ER_INVALID_OPTION_END_CHARACTER` was added in 8.0.1.

- Error number: 3563; Symbol: `ER_INVALID_OPTION_CHARACTERS`; SQLSTATE: 22023

Message: The options argument in function %s contains the invalid character sequence '%s'.

`ER_INVALID_OPTION_CHARACTERS` was added in 8.0.1.

- Error number: 3564; Symbol: `ER_DUPLICATE_OPTION_KEY`; SQLSTATE: 22023

Message: Duplicate option key '%s' in function '%s'.

`ER_DUPLICATE_OPTION_KEY` was added in 8.0.1.

- Error number: 3565; Symbol: `ER_WARN_SRS_NOT_FOUND_AXIS_ORDER`; SQLSTATE: 01000

Message: There's no spatial reference system with SRID %u. The axis order is unknown.

`ER_WARN_SRS_NOT_FOUND_AXIS_ORDER` was added in 8.0.1.

- Error number: 3566; Symbol: `ER_NO_ACCESS_TO_NATIVE_FCT`; SQLSTATE: HY000

Message: Access to native function '%s' is rejected.

`ER_NO_ACCESS_TO_NATIVE_FCT` was added in 8.0.1.

- Error number: 3567; Symbol: `ER_RESET_MASTER_TO_VALUE_OUT_OF_RANGE`; SQLSTATE: HY000

Message: The requested value '%llu' for the next binary log index is out of range. Please use a value between '1' and '%lu'.

`ER_RESET_MASTER_TO_VALUE_OUT_OF_RANGE` was added in 8.0.1.

- Error number: 3568; Symbol: `ER_UNRESOLVED_TABLE_LOCK`; SQLSTATE: HY000

Message: Unresolved table name %s in locking clause.

`ER_UNRESOLVED_TABLE_LOCK` was added in 8.0.1.

- Error number: 3569; Symbol: `ER_DUPLICATE_TABLE_LOCK`; SQLSTATE: HY000

Message: Table %s appears in multiple locking clauses.

`ER_DUPLICATE_TABLE_LOCK` was added in 8.0.1.

- Error number: 3570; Symbol: `ER_BINLOG_UNSAFE_SKIP_LOCKED`; SQLSTATE: HY000

Message: Statement is unsafe because it uses SKIP LOCKED. The set of inserted values is non-deterministic.

`ER_BINLOG_UNSAFE_SKIP_LOCKED` was added in 8.0.1.

- Error number: 3571; Symbol: `ER_BINLOG_UNSAFE_NOWAIT`; SQLSTATE: HY000

Message: Statement is unsafe because it uses NOWAIT. Whether the command will succeed or fail is not deterministic.

`ER_BINLOG_UNSAFE_NOWAIT` was added in 8.0.1.

- Error number: 3572; Symbol: `ER_LOCK_NOWAIT`; SQLSTATE: `HY000`

Message: Statement aborted because lock(s) could not be acquired immediately and NOWAIT is set.

`ER_LOCK_NOWAIT` was added in 8.0.1.

- Error number: 3573; Symbol: `ER_CTE_RECURSIVE_REQUIRE_UNION`; SQLSTATE: `HY000`

Message: Recursive Common Table Expression '%s' should contain a UNION

`ER_CTE_RECURSIVE_REQUIRE_UNION` was added in 8.0.1.

- Error number: 3574; Symbol: `ER_CTE_RECURSIVE_REQUIRE_NONRECURSIVE_FIRST`; SQLSTATE: `HY000`

Message: Recursive Common Table Expression '%s' should have one or more non-recursive query blocks followed by one or more recursive ones

`ER_CTE_RECURSIVE_REQUIRE_NONRECURSIVE_FIRST` was added in 8.0.1.

- Error number: 3575; Symbol: `ER_CTE_RECURSIVE_FORBIDS_AGGREGATION`; SQLSTATE: `HY000`

Message: Recursive Common Table Expression '%s' can contain neither aggregation nor window functions in recursive query block

`ER_CTE_RECURSIVE_FORBIDS_AGGREGATION` was added in 8.0.1.

- Error number: 3576; Symbol: `ER_CTE_RECURSIVE_FORBIDDEN_JOIN_ORDER`; SQLSTATE: `HY000`

Message: In recursive query block of Recursive Common Table Expression '%s', the recursive table must neither be in the right argument of a LEFT JOIN, nor be forced to be non-first with join order hints

`ER_CTE_RECURSIVE_FORBIDDEN_JOIN_ORDER` was added in 8.0.1.

- Error number: 3577; Symbol: `ER_CTE_RECURSIVE_REQUIRE_SINGLE_REFERENCE`; SQLSTATE: `HY000`

Message: In recursive query block of Recursive Common Table Expression '%s', the recursive table must be referenced only once, and not in any subquery

`ER_CTE_RECURSIVE_REQUIRE_SINGLE_REFERENCE` was added in 8.0.1.

- Error number: 3578; Symbol: `ER_SWITCH_TMP_ENGINE`; SQLSTATE: `HY000`

Message: '%s' requires @@internal_tmp_disk_storage_engine=InnoDB

`ER_SWITCH_TMP_ENGINE` was added in 8.0.1.

- Error number: 3579; Symbol: `ER_WINDOW_NO SUCH WINDOW`; SQLSTATE: `HY000`

Message: Window name '%s' is not defined.

`ER_WINDOW_NO SUCH WINDOW` was added in 8.0.2.

- Error number: 3580; Symbol: `ER_WINDOW_CIRCULARITY_IN_WINDOW_GRAPH`; SQLSTATE: `HY000`

Message: There is a circularity in the window dependency graph.

`ER_WINDOW_CIRCULARITY_IN_WINDOW_GRAPH` was added in 8.0.2.

- Error number: 3581; Symbol: `ER_WINDOW_NO_CHILD_PARTITIONING`; SQLSTATE: `HY000`

Message: A window which depends on another cannot define partitioning.

`ER_WINDOW_NO_CHILD_PARTITIONING` was added in 8.0.2.

- Error number: 3582; Symbol: `ER_WINDOW_NO_INHERIT_FRAME`; SQLSTATE: `HY000`

Message: Window '%s' has a frame definition, so cannot be referenced by another window.

`ER_WINDOW_NO_INHERIT_FRAME` was added in 8.0.2.

- Error number: 3583; Symbol: `ER_WINDOW_NO_REDEFINE_ORDER_BY`; SQLSTATE: `HY000`

Message: Window '%s' cannot inherit '%s' since both contain an ORDER BY clause.

`ER_WINDOW_NO_REDEFINE_ORDER_BY` was added in 8.0.2.

- Error number: 3584; Symbol: `ER_WINDOW_FRAME_START_ILLEGAL`; SQLSTATE: `HY000`

Message: Window '%s': frame start cannot be UNBOUNDED FOLLOWING.

`ER_WINDOW_FRAME_START_ILLEGAL` was added in 8.0.2.

- Error number: 3585; Symbol: `ER_WINDOW_FRAME_END_ILLEGAL`; SQLSTATE: `HY000`

Message: Window '%s': frame end cannot be UNBOUNDED PRECEDING.

`ER_WINDOW_FRAME_END_ILLEGAL` was added in 8.0.2.

- Error number: 3586; Symbol: `ER_WINDOW_FRAME_ILLEGAL`; SQLSTATE: `HY000`

Message: Window '%s': frame start or end is negative, NULL or of non-integral type

`ER_WINDOW_FRAME_ILLEGAL` was added in 8.0.2.

- Error number: 3587; Symbol: `ER_WINDOW_RANGE_FRAME_ORDER_TYPE`; SQLSTATE: `HY000`

Message: Window '%s' with RANGE N PRECEDING/FOLLOWING frame requires exactly one ORDER BY expression, of numeric or temporal type

`ER_WINDOW_RANGE_FRAME_ORDER_TYPE` was added in 8.0.2.

- Error number: 3588; Symbol: `ER_WINDOW_RANGE_FRAME_TEMPORAL_TYPE`; SQLSTATE: `HY000`

Message: Window '%s' with RANGE frame has ORDER BY expression of datetime type. Only INTERVAL bound value allowed.

`ER_WINDOW_RANGE_FRAME_TEMPORAL_TYPE` was added in 8.0.2.

- Error number: 3589; Symbol: `ER_WINDOW_RANGE_FRAME_NUMERIC_TYPE`; SQLSTATE: `HY000`

Message: Window '%s' with RANGE frame has ORDER BY expression of numeric type, INTERVAL bound value not allowed.

`ER_WINDOW_RANGE_FRAME_NUMERIC_TYPE` was added in 8.0.2.

- Error number: 3590; Symbol: `ER_WINDOW_RANGE_BOUND_NOT_CONSTANT`; SQLSTATE: `HY000`

Message: Window '%s' has a non-constant frame bound.
`ER_WINDOW_RANGE_BOUND_NOT_CONSTANT` was added in 8.0.2.
- Error number: 3591; Symbol: `ER_WINDOW_DUPLICATE_NAME`; SQLSTATE: `HY000`

Message: Window '%s' is defined twice.
`ER_WINDOW_DUPLICATE_NAME` was added in 8.0.2.
- Error number: 3592; Symbol: `ER_WINDOW_ILLEGAL_ORDER_BY`; SQLSTATE: `HY000`

Message: Window '%s': ORDER BY or PARTITION BY uses legacy position indication which is not supported, use expression.
`ER_WINDOW_ILLEGAL_ORDER_BY` was added in 8.0.2.
- Error number: 3593; Symbol: `ER_WINDOW_INVALID_WINDOW_FUNC_USE`; SQLSTATE: `HY000`

Message: You cannot use the window function '%s' in this context.
`ER_WINDOW_INVALID_WINDOW_FUNC_USE` was added in 8.0.2.
- Error number: 3594; Symbol: `ER_WINDOW_INVALID_WINDOW_FUNC_ALIAS_USE`; SQLSTATE: `HY000`

Message: You cannot use the alias '%s' of an expression containing a window function in this context.
`ER_WINDOW_INVALID_WINDOW_FUNC_ALIAS_USE` was added in 8.0.2.
- Error number: 3595; Symbol: `ER_WINDOW_NESTED_WINDOW_FUNC_USE_IN_WINDOW_SPEC`; SQLSTATE: `HY000`

Message: You cannot nest a window function in the specification of window '%s'.
`ER_WINDOW_NESTED_WINDOW_FUNC_USE_IN_WINDOW_SPEC` was added in 8.0.2.
- Error number: 3596; Symbol: `ER_WINDOW_ROWS_INTERVAL_USE`; SQLSTATE: `HY000`

Message: Window '%s': INTERVAL can only be used with RANGE frames.
`ER_WINDOW_ROWS_INTERVAL_USE` was added in 8.0.2.
- Error number: 3597; Symbol: `ER_WINDOW_NO_GROUP_ORDER`; SQLSTATE: `HY000`

Message: ASC or DESC with GROUP BY isn't allowed with window functions; put ASC or DESC in ORDER BY
`ER_WINDOW_NO_GROUP_ORDER` was added in 8.0.2, removed after 8.0.12.
- Error number: 3597; Symbol: `ER_WINDOW_NO_GROUP_ORDER_UNUSED`; SQLSTATE: `HY000`

Message: ASC or DESC with GROUP BY isn't allowed with window functions; put ASC or DESC in ORDER BY
`ER_WINDOW_NO_GROUP_ORDER_UNUSED` was added in 8.0.13.
- Error number: 3598; Symbol: `ER_WINDOW_EXPLAIN_JSON`; SQLSTATE: `HY000`

Message: To get information about window functions use EXPLAIN FORMAT=JSON

`ER_WINDOW_EXPLAIN_JSON` was added in 8.0.2.

- Error number: `3599`; Symbol: `ER_WINDOW_FUNCTION_IGNORES_FRAME`; SQLSTATE: `HY000`

Message: Window function '%s' ignores the frame clause of window '%s' and aggregates over the whole partition

`ER_WINDOW_FUNCTION_IGNORES_FRAME` was added in 8.0.2.

- Error number: `3600`; Symbol: `ER_WINDOW_SE_NOT_ACCEPTABLE`; SQLSTATE: `HY000`

Message: Windowing requires @@internal_tmp_mem_storage_engine=TempTable.

`ER_WINDOW_SE_NOT_ACCEPTABLE` was added in 8.0.2, removed after 8.0.3.

- Error number: `3600`; Symbol: `ER_WL9236_NOW_UNUSED`; SQLSTATE: `HY000`

Message: Windowing requires @@internal_tmp_mem_storage_engine=TempTable.

`ER_WL9236_NOW_UNUSED` was added in 8.0.4.

- Error number: `3601`; Symbol: `ER_INVALID_NO_OF_ARGS`; SQLSTATE: `HY000`

Message: Too many arguments for function %s: %lu; maximum allowed is %s.

`ER_INVALID_NO_OF_ARGS` was added in 8.0.1.

- Error number: `3602`; Symbol: `ER_FIELD_IN_GROUPING_NOT_GROUP_BY`; SQLSTATE: `HY000`

Message: Argument #%u of GROUPING function is not in GROUP BY

`ER_FIELD_IN_GROUPING_NOT_GROUP_BY` was added in 8.0.1.

- Error number: `3603`; Symbol: `ER_TOO_LONG_TABLESPACE_COMMENT`; SQLSTATE: `HY000`

Message: Comment for tablespace '%s' is too long (max = %lu)

`ER_TOO_LONG_TABLESPACE_COMMENT` was added in 8.0.1.

- Error number: `3604`; Symbol: `ER_ENGINE_CANT_DROP_TABLE`; SQLSTATE: `HY000`

Message: Storage engine can't drop table '%s'

`ER_ENGINE_CANT_DROP_TABLE` was added in 8.0.1.

- Error number: `3605`; Symbol: `ER_ENGINE_CANT_DROP_MISSING_TABLE`; SQLSTATE: `HY000`

Message: Storage engine can't drop table '%s' because it is missing. Use DROP TABLE IF EXISTS to remove it from data-dictionary.

`ER_ENGINE_CANT_DROP_MISSING_TABLE` was added in 8.0.1.

- Error number: `3606`; Symbol: `ER_TABLESPACE_DUP_FILENAME`; SQLSTATE: `HY000`

Message: Duplicate file name for tablespace '%s'

`ER_TABLESPACE_DUP_FILENAME` was added in 8.0.1.

- Error number: 3607; Symbol: `ER_DB_DROP_RMDIR2`; SQLSTATE: HY000

Message: Problem while dropping database. Can't remove database directory (%s). Please remove it manually.

`ER_DB_DROP_RMDIR2` was added in 8.0.1.
- Error number: 3608; Symbol: `ER_IMP_NO_FILES_MATCHED`; SQLSTATE: HY000

Message: No SDI files matched the pattern '%s'

`ER_IMP_NO_FILES_MATCHED` was added in 8.0.1.
- Error number: 3609; Symbol: `ER_IMP_SCHEMA_DOES_NOT_EXIST`; SQLSTATE: HY000

Message: Schema '%s', referenced in SDI, does not exist.

`ER_IMP_SCHEMA_DOES_NOT_EXIST` was added in 8.0.1.
- Error number: 3610; Symbol: `ER_IMP_TABLE_ALREADY_EXISTS`; SQLSTATE: HY000

Message: Table '%s.%s', referenced in SDI, already exists.

`ER_IMP_TABLE_ALREADY_EXISTS` was added in 8.0.1.
- Error number: 3611; Symbol: `ER_IMP_INCOMPATIBLE_MYSQLD_VERSION`; SQLSTATE: HY000

Message: Imported mysqld_version (%llu) is not compatible with current (%llu)

`ER_IMP_INCOMPATIBLE_MYSQLD_VERSION` was added in 8.0.1.
- Error number: 3612; Symbol: `ER_IMP_INCOMPATIBLE_DD_VERSION`; SQLSTATE: HY000

Message: Imported dd version (%u) is not compatible with current (%u)

`ER_IMP_INCOMPATIBLE_DD_VERSION` was added in 8.0.1.
- Error number: 3613; Symbol: `ER_IMP_INCOMPATIBLE_SDI_VERSION`; SQLSTATE: HY000

Message: Imported sdi version (%llu) is not compatible with current (%llu)

`ER_IMP_INCOMPATIBLE_SDI_VERSION` was added in 8.0.1.
- Error number: 3614; Symbol: `ER_WARN_INVALID_HINT`; SQLSTATE: HY000

Message: Invalid number of arguments for hint %s

`ER_WARN_INVALID_HINT` was added in 8.0.1.
- Error number: 3615; Symbol: `ER_VAR_DOES_NOT_EXIST`; SQLSTATE: HY000

Message: Variable %s does not exist in persisted config file

`ER_VAR_DOES_NOT_EXIST` was added in 8.0.1.
- Error number: 3616; Symbol: `ER_LONGITUDE_OUT_OF_RANGE`; SQLSTATE: 22S02

Message: Longitude %f is out of range in function %s. It must be within (%f, %f].

`ER_LONGITUDE_OUT_OF_RANGE` was added in 8.0.1.
- Error number: 3617; Symbol: `ER_LATITUDE_OUT_OF_RANGE`; SQLSTATE: 22S03

Message: Latitude %f is out of range in function %s. It must be within [%f, %f].

`ER_LATITUDE_OUT_OF_RANGE` was added in 8.0.1.

- Error number: `3618`; Symbol: `ER_NOT_IMPLEMENTED_FOR_GEOGRAPHIC_SRS`; SQLSTATE: `22S00`

Message: %s(%s) has not been implemented for geographic spatial reference systems.

`ER_NOT_IMPLEMENTED_FOR_GEOGRAPHIC_SRS` was added in 8.0.1.

- Error number: `3619`; Symbol: `ER_ILLEGAL_PRIVILEGE_LEVEL`; SQLSTATE: `HY000`

Message: Illegal privilege level specified for %s

`ER_ILLEGAL_PRIVILEGE_LEVEL` was added in 8.0.1.

- Error number: `3620`; Symbol: `ER_NO_SYSTEM_VIEW_ACCESS`; SQLSTATE: `HY000`

Message: Access to system view INFORMATION_SCHEMA.%s' is rejected.

`ER_NO_SYSTEM_VIEW_ACCESS` was added in 8.0.2.

- Error number: `3621`; Symbol: `ER_COMPONENT_FILTER_FLABBERGASTED`; SQLSTATE: `HY000`

Message: The log-filter component "%s" got confused at "%s" ...

`ER_COMPONENT_FILTER_FLABBERGASTED` was added in 8.0.2.

- Error number: `3622`; Symbol: `ER_PART_EXPR_TOO_LONG`; SQLSTATE: `HY000`

Message: Partitioning expression is too long.

`ER_PART_EXPR_TOO_LONG` was added in 8.0.2.

- Error number: `3623`; Symbol: `ER_UDF_DROP_DYNAMICALLY_REGISTERED`; SQLSTATE: `HY000`

Message: DROP FUNCTION can't drop a dynamically registered user defined function

`ER_UDF_DROP_DYNAMICALLY_REGISTERED` was added in 8.0.2.

- Error number: `3624`; Symbol: `ER_UNABLE_TO_STORE_COLUMN_STATISTICS`; SQLSTATE: `HY000`

Message: Unable to store column statistics for column '%s' in table '%s'.'%s'

`ER_UNABLE_TO_STORE_COLUMN_STATISTICS` was added in 8.0.2.

- Error number: `3625`; Symbol: `ER_UNABLE_TO_UPDATE_COLUMN_STATISTICS`; SQLSTATE: `HY000`

Message: Unable to update column statistics for column '%s' in table '%s'.'%s'

`ER_UNABLE_TO_UPDATE_COLUMN_STATISTICS` was added in 8.0.2.

- Error number: `3626`; Symbol: `ER_UNABLE_TO_DROP_COLUMN_STATISTICS`; SQLSTATE: `HY000`

Message: Unable to remove column statistics for column '%s' in table '%s'.'%s'

`ER_UNABLE_TO_DROP_COLUMN_STATISTICS` was added in 8.0.2.

- Error number: `3627`; Symbol: `ER_UNABLE_TO_BUILD_HISTOGRAM`; SQLSTATE: `HY000`

Message: Unable to build histogram statistics for column '%s' in table '%s'.'%s'

`ER_UNABLE_TO_BUILD_HISTOGRAM` was added in 8.0.2.

-
- Error number: 3628; Symbol: `ER_MANDATORY_ROLE`; SQLSTATE: `HY000`

Message: The role %s is a mandatory role and can't be revoked or dropped. The restriction can be lifted by excluding the role identifier from the global variable `mandatory_roles`.

`ER_MANDATORY_ROLE` was added in 8.0.2.

- Error number: 3629; Symbol: `ER_MISSING_TABLESPACE_FILE`; SQLSTATE: `HY000`

Message: Tablespace '%s' does not have a file named '%s'

`ER_MISSING_TABLESPACE_FILE` was added in 8.0.3.

- Error number: 3630; Symbol: `ER_PERSIST_ONLY_ACCESS_DENIED_ERROR`; SQLSTATE: `42000`

Message: Access denied; you need %s privileges for this operation

`ER_PERSIST_ONLY_ACCESS_DENIED_ERROR` was added in 8.0.3.

- Error number: 3631; Symbol: `ER_CMD_NEED_SUPER`; SQLSTATE: `HY000`

Message: You need the SUPER privilege for command '%s'

`ER_CMD_NEED_SUPER` was added in 8.0.3.

- Error number: 3632; Symbol: `ER_PATH_IN_DATADIR`; SQLSTATE: `HY000`

Message: Path is within the current data directory '%s'

`ER_PATH_IN_DATADIR` was added in 8.0.3.

- Error number: 3633; Symbol: `ER_DDL_IN_PROGRESS`; SQLSTATE: `HY000`

Message: Concurrent DDL is performed during the operation. Please try again.

`ER_DDL_IN_PROGRESS` was added in 8.0.3, removed after 8.0.16.

- Error number: 3633; Symbol: `ER_CLONE_DDL_IN_PROGRESS`; SQLSTATE: `HY000`

Message: Concurrent DDL is performed during clone operation. Please try again.

`ER_CLONE_DDL_IN_PROGRESS` was added in 8.0.17.

- Error number: 3634; Symbol: `ER_TOO_MANY_CONCURRENT_CLONES`; SQLSTATE: `HY000`

Message: Too many concurrent clone operations. Maximum allowed - %d.

`ER_TOO_MANY_CONCURRENT_CLONES` was added in 8.0.3, removed after 8.0.16.

- Error number: 3634; Symbol: `ER_CLONE_TOO_MANY_CONCURRENT_CLONES`; SQLSTATE: `HY000`

Message: Too many concurrent clone operations. Maximum allowed - %d.

`ER_CLONE_TOO_MANY_CONCURRENT_CLONES` was added in 8.0.17.

- Error number: 3635; Symbol: `ER_APPLIER_LOG_EVENT_VALIDATION_ERROR`; SQLSTATE: `HY000`

Message: The table in transaction %s does not comply with the requirements by an external plugin.

`ER_APPLIER_LOG_EVENT_VALIDATION_ERROR` was added in 8.0.3.

- Error number: 3636; Symbol: `ER_CTE_MAX_RECURSION_DEPTH`; SQLSTATE: HY000
Message: Recursive query aborted after %u iterations. Try increasing @@cte_max_recursion_depth to a larger value.
`ER_CTE_MAX_RECURSION_DEPTH` was added in 8.0.3.
- Error number: 3637; Symbol: `ER_NOT_HINT_UPDATABLE_VARIABLE`; SQLSTATE: HY000
Message: Variable %s cannot be set using SET_VAR hint.
`ER_NOT_HINT_UPDATABLE_VARIABLE` was added in 8.0.3.
- Error number: 3638; Symbol: `ER_CREDENTIALS_CONTRADICT_TO_HISTORY`; SQLSTATE: HY000
Message: Cannot use these credentials for '%.*s@%.*s' because they contradict the password history policy
`ER_CREDENTIALS_CONTRADICT_TO_HISTORY` was added in 8.0.3.
- Error number: 3639; Symbol: `ER_WARNING_PASSWORD_HISTORY_CLAUSES_VOID`; SQLSTATE: HY000
Message: Non-zero password history clauses ignored for user '%s'@'%s' as its authentication plugin %s does not support password history
`ER_WARNING_PASSWORD_HISTORY_CLAUSES_VOID` was added in 8.0.3.
- Error number: 3640; Symbol: `ER_CLIENT_DOES_NOT_SUPPORT`; SQLSTATE: HY000
Message: The client doesn't support %s
`ER_CLIENT_DOES_NOT_SUPPORT` was added in 8.0.3.
- Error number: 3641; Symbol: `ER_I_S_SKIPPED_TABLESPACE`; SQLSTATE: HY000
Message: Tablespace '%s' was skipped since its definition is being modified by concurrent DDL statement
`ER_I_S_SKIPPED_TABLESPACE` was added in 8.0.3.
- Error number: 3642; Symbol: `ER_TABLESPACE_ENGINE_MISMATCH`; SQLSTATE: HY000
Message: Engine '%s' does not match stored engine '%s' for tablespace '%s'
`ER_TABLESPACE_ENGINE_MISMATCH` was added in 8.0.3.
- Error number: 3643; Symbol: `ER_WRONG_SRID_FOR_COLUMN`; SQLSTATE: HY000
Message: The SRID of the geometry does not match the SRID of the column '%s'. The SRID of the geometry is %lu, but the SRID of the column is %lu. Consider changing the SRID of the geometry or the SRID property of the column.
`ER_WRONG_SRID_FOR_COLUMN` was added in 8.0.3.
- Error number: 3644; Symbol: `ER_CANNOT_ALTER_SRID_DUE_TO_INDEX`; SQLSTATE: HY000
Message: The SRID specification on the column '%s' cannot be changed because there is a spatial index on the column. Please remove the spatial index before altering the SRID specification.
`ER_CANNOT_ALTER_SRID_DUE_TO_INDEX` was added in 8.0.3.
- Error number: 3645; Symbol: `ER_WARN_BINLOG_PARTIAL_UPDATES_DISABLED`; SQLSTATE: HY000

Message: When %s, the option binlog_row_value_options=%s will be ignored and updates will be written in full format to binary log.

`ER_WARN_BINLOG_PARTIAL_UPDATES_DISABLED` was added in 8.0.3.

- Error number: 3646; Symbol: `ER_WARN_BINLOG_V1_ROW_EVENTS_DISABLED`; SQLSTATE: HY000

Message: When %s, the option log_bin_use_v1_row_events=1 will be ignored and row events will be written in new format to binary log.

`ER_WARN_BINLOG_V1_ROW_EVENTS_DISABLED` was added in 8.0.3.

- Error number: 3647; Symbol: `ER_WARN_BINLOG_PARTIAL_UPDATES_SUGGESTS_PARTIAL_IMAGES`; SQLSTATE: HY000

Message: When %s, the option binlog_row_value_options=%s will be used only for the after-image. Full values will be written in the before-image, so the saving in disk space due to binlog_row_value_options is limited to less than 50%.

`ER_WARN_BINLOG_PARTIAL_UPDATES_SUGGESTS_PARTIAL_IMAGES` was added in 8.0.3.

- Error number: 3648; Symbol: `ER_COULD_NOT_APPLY_JSON_DIFF`; SQLSTATE: HY000

Message: Could not apply JSON diff in table %.*s, column %s.

`ER_COULD_NOT_APPLY_JSON_DIFF` was added in 8.0.3.

- Error number: 3649; Symbol: `ER_CORRUPTED_JSON_DIFF`; SQLSTATE: HY000

Message: Corrupted JSON diff for table %.*s, column %s.

`ER_CORRUPTED_JSON_DIFF` was added in 8.0.3.

- Error number: 3650; Symbol: `ER_RESOURCE_GROUP_EXISTS`; SQLSTATE: HY000

Message: Resource Group '%s' exists

`ER_RESOURCE_GROUP_EXISTS` was added in 8.0.3.

- Error number: 3651; Symbol: `ER_RESOURCE_GROUP_NOT_EXISTS`; SQLSTATE: HY000

Message: Resource Group '%s' does not exist.

`ER_RESOURCE_GROUP_NOT_EXISTS` was added in 8.0.3.

- Error number: 3652; Symbol: `ER_INVALID_VCPU_ID`; SQLSTATE: HY000

Message: Invalid cpu id %u

`ER_INVALID_VCPU_ID` was added in 8.0.3.

- Error number: 3653; Symbol: `ER_INVALID_VCPU_RANGE`; SQLSTATE: HY000

Message: Invalid VCPU range %u-%u

`ER_INVALID_VCPU_RANGE` was added in 8.0.3.

- Error number: 3654; Symbol: `ER_INVALID_THREAD_PRIORITY`; SQLSTATE: HY000

Message: Invalid thread priority value %d for %s resource group %s. Allowed range is [%d, %d].

`ER_INVALID_THREAD_PRIORITY` was added in 8.0.3.

-
- Error number: 3655; Symbol: `ER_DISALLOWED_OPERATION`; SQLSTATE: `HY000`

Message: %s operation is disallowed on %s
`ER_DISALLOWED_OPERATION` was added in 8.0.3.
 - Error number: 3656; Symbol: `ER_RESOURCE_GROUP_BUSY`; SQLSTATE: `HY000`

Message: Resource group %s is busy.
`ER_RESOURCE_GROUP_BUSY` was added in 8.0.3.
 - Error number: 3657; Symbol: `ER_RESOURCE_GROUP_DISABLED`; SQLSTATE: `HY000`

Message: Resource group %s is disabled.
`ER_RESOURCE_GROUP_DISABLED` was added in 8.0.3.
 - Error number: 3658; Symbol: `ER_FEATURE_UNSUPPORTED`; SQLSTATE: `HY000`

Message: Feature %s is unsupported (%s).
`ER_FEATURE_UNSUPPORTED` was added in 8.0.3.
 - Error number: 3659; Symbol: `ER_ATTRIBUTE_IGNORED`; SQLSTATE: `HY000`

Message: Attribute %s is ignored (%s).
`ER_ATTRIBUTE_IGNORED` was added in 8.0.3.
 - Error number: 3660; Symbol: `ER_INVALID_THREAD_ID`; SQLSTATE: `HY000`

Message: Invalid thread id (%llu).
`ER_INVALID_THREAD_ID` was added in 8.0.3.
 - Error number: 3661; Symbol: `ER_RESOURCE_GROUP_BIND_FAILED`; SQLSTATE: `HY000`

Message: Unable to bind resource group %s with thread id (%llu).(%s).
`ER_RESOURCE_GROUP_BIND_FAILED` was added in 8.0.3.
 - Error number: 3662; Symbol: `ER_INVALID_USE_OF_FORCE_OPTION`; SQLSTATE: `HY000`

Message: Option FORCE invalid as DISABLE option is not specified.
`ER_INVALID_USE_OF_FORCE_OPTION` was added in 8.0.3.
 - Error number: 3663; Symbol: `ER_GROUP_REPLICATION_COMMAND_FAILURE`; SQLSTATE: `HY000`

Message: The %s command encountered a failure. %s
`ER_GROUP_REPLICATION_COMMAND_FAILURE` was added in 8.0.4.
 - Error number: 3664; Symbol: `ER_SDI_OPERATION_FAILED`; SQLSTATE: `HY000`

Message: Failed to %s SDI '%s.%s' in tablespace '%s'.
`ER_SDI_OPERATION_FAILED` was added in 8.0.3.
 - Error number: 3665; Symbol: `ER_MISSING_JSON_TABLE_VALUE`; SQLSTATE: `22035`

Message: Missing value for JSON_TABLE column '%s'
`ER_MISSING_JSON_TABLE_VALUE` was added in 8.0.4.

- Error number: 3666; Symbol: `ER_WRONG_JSON_TABLE_VALUE`; SQLSTATE: `2203F`

Message: Can't store an array or an object in the scalar JSON_TABLE column '%s'
`ER_WRONG_JSON_TABLE_VALUE` was added in 8.0.4.
- Error number: 3667; Symbol: `ER_TF_MUST_HAVE_ALIAS`; SQLSTATE: `42000`

Message: Every table function must have an alias
`ER_TF_MUST_HAVE_ALIAS` was added in 8.0.4.
- Error number: 3668; Symbol: `ER_TF_FORBIDDEN_JOIN_TYPE`; SQLSTATE: `HY000`

Message: INNER or LEFT JOIN must be used for LATERAL references made by '%s'
`ER_TF_FORBIDDEN_JOIN_TYPE` was added in 8.0.4.
- Error number: 3669; Symbol: `ER_JT_VALUE_OUT_OF_RANGE`; SQLSTATE: `22003`

Message: Value is out of range for JSON_TABLE's column '%s'
`ER_JT_VALUE_OUT_OF_RANGE` was added in 8.0.4.
- Error number: 3670; Symbol: `ER_JT_MAX_NESTED_PATH`; SQLSTATE: `42000`

Message: More than supported %u NESTED PATHs were found in JSON_TABLE '%s'
`ER_JT_MAX_NESTED_PATH` was added in 8.0.4.
- Error number: 3671; Symbol: `ER_PASSWORD_EXPIRATION_NOT_SUPPORTED_BY_AUTH_METHOD`; SQLSTATE: `HY000`

Message: The selected authentication method %.*s does not support password expiration
`ER_PASSWORD_EXPIRATION_NOT_SUPPORTED_BY_AUTH_METHOD` was added in 8.0.4.
- Error number: 3672; Symbol: `ER_INVALID_GEOJSON_CRS_NOT_TOP_LEVEL`; SQLSTATE: `HY000`

Message: Invalid GeoJSON data provided to function %s: Member 'crs' must be specified in the top level object.
`ER_INVALID_GEOJSON_CRS_NOT_TOP_LEVEL` was added in 8.0.4.
- Error number: 3673; Symbol: `ER_BAD_NULL_ERROR_NOT_IGNORED`; SQLSTATE: `23000`

Message: Column '%s' cannot be null
`ER_BAD_NULL_ERROR_NOT_IGNORED` was added in 8.0.4.
- Error number: 3674; Symbol: `WARN_USELESS_SPATIAL_INDEX`; SQLSTATE: `HY000`

Message: The spatial index on column '%s' will not be used by the query optimizer since the column does not have an SRID attribute. Consider adding an SRID attribute to the column.
`WARN_USELESS_SPATIAL_INDEX` was added in 8.0.4.
- Error number: 3675; Symbol: `ER_DISK_FULL_NOWAIT`; SQLSTATE: `HY000`

Message: Create table/tablespace '%s' failed, as disk is full
`ER_DISK_FULL_NOWAIT` was added in 8.0.4.
- Error number: 3676; Symbol: `ER_PARSE_ERROR_IN_DIGEST_FN`; SQLSTATE: `HY000`

Message: Could not parse argument to digest function: "%s".

`ER_PARSE_ERROR_IN_DIGEST_FN` was added in 8.0.4.

- Error number: 3677; Symbol: `ER_UNDISCLOSED_PARSE_ERROR_IN_DIGEST_FN`; SQLSTATE: `HY000`

Message: Could not parse argument to digest function.

`ER_UNDISCLOSED_PARSE_ERROR_IN_DIGEST_FN` was added in 8.0.4.

- Error number: 3678; Symbol: `ER_SCHEMA_DIR_EXISTS`; SQLSTATE: `HY000`

Message: Schema directory '%s' already exists. This must be resolved manually (e.g. by moving the schema directory to another location).

`ER_SCHEMA_DIR_EXISTS` was added in 8.0.4.

- Error number: 3679; Symbol: `ER_SCHEMA_DIR_MISSING`; SQLSTATE: `HY000`

Message: Schema directory '%s' does not exist

`ER_SCHEMA_DIR_MISSING` was added in 8.0.4.

- Error number: 3680; Symbol: `ER_SCHEMA_DIR_CREATE_FAILED`; SQLSTATE: `HY000`

Message: Failed to create schema directory '%s' (errno: %d - %s)

`ER_SCHEMA_DIR_CREATE_FAILED` was added in 8.0.4.

- Error number: 3681; Symbol: `ER_SCHEMA_DIR_UNKNOWN`; SQLSTATE: `HY000`

Message: Schema '%s' does not exist, but schema directory '%s' was found. This must be resolved manually (e.g. by moving the schema directory to another location).

`ER_SCHEMA_DIR_UNKNOWN` was added in 8.0.4.

- Error number: 3682; Symbol: `ER_ONLY_IMPLEMENTED_FOR_SRID_0_AND_4326`; SQLSTATE: `22S00`

Message: Function %s is only defined for SRID 0 and SRID 4326.

`ER_ONLY_IMPLEMENTED_FOR_SRID_0_AND_4326` was added in 8.0.4.

- Error number: 3683; Symbol: `ER_BINLOG_EXPIRE_LOG_DAYS_AND_SECS_USED_TOGETHER`; SQLSTATE: `HY000`

Message: The option expire_logs_days and binlog_expire_logs_seconds cannot be used together. Please use binlog_expire_logs_seconds to set the expire time (expire_logs_days is deprecated)

`ER_BINLOG_EXPIRE_LOG_DAYS_AND_SECS_USED_TOGETHER` was added in 8.0.11.

- Error number: 3684; Symbol: `ER_REGEXP_STRING_NOT_TERMINATED`; SQLSTATE: `HY000`

Message: An output string could not be zero-terminated because the length exceeds the buffer capacity.

`ER_REGEXP_STRING_NOT_TERMINATED` was added in 8.0.4, removed after 8.0.4.

- Error number: 3684; Symbol: `ER_REGEXP_BUFFER_OVERFLOW`; SQLSTATE: `HY000`

Message: The result string is larger than the result buffer.

`ER_REGEXP_BUFFER_OVERFLOW` was added in 8.0.4.

- Error number: 3685; Symbol: `ER_REGEXP_ILLEGAL_ARGUMENT`; SQLSTATE: `HY000`

Message: Illegal argument to a regular expression.
`ER_REGEXP_ILLEGAL_ARGUMENT` was added in 8.0.4.
- Error number: 3686; Symbol: `ER_REGEXP_INDEX_OUTOFGBOUNDS_ERROR`; SQLSTATE: `HY000`

Message: Index out of bounds in regular expression search.
`ER_REGEXP_INDEX_OUTOFGBOUNDS_ERROR` was added in 8.0.4.
- Error number: 3687; Symbol: `ER_REGEXP_INTERNAL_ERROR`; SQLSTATE: `HY000`

Message: Internal error in the regular expression library.
`ER_REGEXP_INTERNAL_ERROR` was added in 8.0.4.
- Error number: 3688; Symbol: `ER_REGEXP_RULE_SYNTAX`; SQLSTATE: `HY000`

Message: Syntax error in regular expression on line %u, character %u.
`ER_REGEXP_RULE_SYNTAX` was added in 8.0.4.
- Error number: 3689; Symbol: `ER_REGEXP_BAD_ESCAPE_SEQUENCE`; SQLSTATE: `HY000`

Message: Unrecognized escape sequence in regular expression.
`ER_REGEXP_BAD_ESCAPE_SEQUENCE` was added in 8.0.4.
- Error number: 3690; Symbol: `ER_REGEXP_UNIMPLEMENTED`; SQLSTATE: `HY000`

Message: The regular expression contains a feature that is not implemented in this library version.
`ER_REGEXP_UNIMPLEMENTED` was added in 8.0.4.
- Error number: 3691; Symbol: `ER_REGEXP_MISMATCHED_PAREN`; SQLSTATE: `HY000`

Message: Mismatched parenthesis in regular expression.
`ER_REGEXP_MISMATCHED_PAREN` was added in 8.0.4.
- Error number: 3692; Symbol: `ER_REGEXP_BAD_INTERVAL`; SQLSTATE: `HY000`

Message: Incorrect description of a {min,max} interval.
`ER_REGEXP_BAD_INTERVAL` was added in 8.0.4.
- Error number: 3693; Symbol: `ER_REGEXP_MAX_LT_MIN`; SQLSTATE: `HY000`

Message: The maximum is less than the minimum in a {min,max} interval.
`ER_REGEXP_MAX_LT_MIN` was added in 8.0.4.
- Error number: 3694; Symbol: `ER_REGEXP_INVALID_BACK_REF`; SQLSTATE: `HY000`

Message: Invalid back-reference in regular expression.
`ER_REGEXP_INVALID_BACK_REF` was added in 8.0.4.
- Error number: 3695; Symbol: `ER_REGEXP_LOOK_BEHIND_LIMIT`; SQLSTATE: `HY000`

Message: The look-behind assertion exceeds the limit in regular expression.

`ER_REGEXP_LOOK_BEHIND_LIMIT` was added in 8.0.4.

- Error number: [3696](#); Symbol: `ER_REGEXP_MISSING_CLOSE_BRACKET`; SQLSTATE: `HY000`

Message: The regular expression contains an unclosed bracket expression.

`ER_REGEXP_MISSING_CLOSE_BRACKET` was added in 8.0.4.

- Error number: [3697](#); Symbol: `ER_REGEXP_INVALID_RANGE`; SQLSTATE: `HY000`

Message: The regular expression contains an [x-y] character range where x comes after y.

`ER_REGEXP_INVALID_RANGE` was added in 8.0.4.

- Error number: [3698](#); Symbol: `ER_REGEXP_STACK_OVERFLOW`; SQLSTATE: `HY000`

Message: Overflow in the regular expression backtrack stack.

`ER_REGEXP_STACK_OVERFLOW` was added in 8.0.4.

- Error number: [3699](#); Symbol: `ER_REGEXP_TIME_OUT`; SQLSTATE: `HY000`

Message: Timeout exceeded in regular expression match.

`ER_REGEXP_TIME_OUT` was added in 8.0.4.

- Error number: [3700](#); Symbol: `ER_REGEXP_PATTERN_TOO_BIG`; SQLSTATE: `HY000`

Message: The regular expression pattern exceeds limits on size or complexity.

`ER_REGEXP_PATTERN_TOO_BIG` was added in 8.0.4.

- Error number: [3701](#); Symbol: `ER_CANT_SET_ERROR_LOG_SERVICE`; SQLSTATE: `HY000`

Message: Value for %s got confusing at or around "%s". Syntax may be wrong, component may not be INSTALLED, or a component that does not support instances may be listed more than once.

`ER_CANT_SET_ERROR_LOG_SERVICE` was added in 8.0.4.

- Error number: [3702](#); Symbol: `ER_EMPTY_PIPELINE_FOR_ERROR_LOG_SERVICE`; SQLSTATE: `HY000`

Message: Setting an empty %s pipeline disables error logging!

`ER_EMPTY_PIPELINE_FOR_ERROR_LOG_SERVICE` was added in 8.0.4.

- Error number: [3703](#); Symbol: `ER_COMPONENT_FILTER_DIAGNOSTICS`; SQLSTATE: `HY000`

Message: filter %s: %s

`ER_COMPONENT_FILTER_DIAGNOSTICS` was added in 8.0.4.

- Error number: [3704](#); Symbol: `ER_INNODB_CANNOT_BE_IGNORED`; SQLSTATE: `HY000`

Message: ignore-built-innodb is ignored and will be removed in future releases.

`ER_INNODB_CANNOT_BE_IGNORED` was added in 8.0.2, removed after 8.0.2.

- Error number: [3704](#); Symbol: `ER_NOT_IMPLEMENTED_FOR_CARTESIAN_SRS`; SQLSTATE: `22S00`

Message: %s(%s) has not been implemented for Cartesian spatial reference systems.

`ER_NOT_IMPLEMENTED_FOR_CARTESIAN_SRS` was added in 8.0.4.

- Error number: `3705`; Symbol: `ER_NOT_IMPLEMENTED_FOR_PROJECTED_SRS`; SQLSTATE: `22S00`

Message: %s(%s) has not been implemented for projected spatial reference systems.

`ER_NOT_IMPLEMENTED_FOR_PROJECTED_SRS` was added in 8.0.4.

- Error number: `3706`; Symbol: `ER_NONPOSITIVE_RADIUS`; SQLSTATE: `22003`

Message: Invalid radius provided to function %s: Radius must be greater than zero.

`ER_NONPOSITIVE_RADIUS` was added in 8.0.4.

- Error number: `3707`; Symbol: `ER_RESTART_SERVER_FAILED`; SQLSTATE: `HY000`

Message: Restart server failed (%s).

`ER_RESTART_SERVER_FAILED` was added in 8.0.4.

- Error number: `3708`; Symbol: `ER_SRS_MISSING_MANDATORY_ATTRIBUTE`; SQLSTATE: `SR006`

Message: Missing mandatory attribute %s.

`ER_SRS_MISSING_MANDATORY_ATTRIBUTE` was added in 8.0.4.

- Error number: `3709`; Symbol: `ER_SRS_MULTIPLE_ATTRIBUTE_DEFINITIONS`; SQLSTATE: `SR006`

Message: Multiple definitions of attribute %s.

`ER_SRS_MULTIPLE_ATTRIBUTE_DEFINITIONS` was added in 8.0.4.

- Error number: `3710`; Symbol: `ER_SRS_NAME_CANT_BE_EMPTY_OR_WHITESPACE`; SQLSTATE: `SR006`

Message: The spatial reference system name can't be an empty string or start or end with whitespace.

`ER_SRS_NAME_CANT_BE_EMPTY_OR_WHITESPACE` was added in 8.0.4.

- Error number: `3711`; Symbol: `ER_SRS_ORGANIZATION_CANT_BE_EMPTY_OR_WHITESPACE`; SQLSTATE: `SR006`

Message: The organization name can't be an empty string or start or end with whitespace.

`ER_SRS_ORGANIZATION_CANT_BE_EMPTY_OR_WHITESPACE` was added in 8.0.4.

- Error number: `3712`; Symbol: `ER_SRS_ID_ALREADY_EXISTS`; SQLSTATE: `SR004`

Message: There is already a spatial reference system with SRID %u.

`ER_SRS_ID_ALREADY_EXISTS` was added in 8.0.4.

- Error number: `3713`; Symbol: `ER_WARN_SRS_ID_ALREADY_EXISTS`; SQLSTATE: `01S00`

Message: There is already a spatial reference system with SRID %u.

`ER_WARN_SRS_ID_ALREADY_EXISTS` was added in 8.0.4.

- Error number: `3714`; Symbol: `ER_CANT_MODIFY_SRID_0`; SQLSTATE: `SR000`

Message: SRID 0 is not modifiable.

`ER_CANT MODIFY_SRID_0` was added in 8.0.4.

- Error number: `3715`; Symbol: `ER_WARN_RESERVED_SRID_RANGE`; SQLSTATE: `01S01`

Message: The SRID range [%u, %u] has been reserved for system use. SRSs in this range may be added, modified or removed without warning during upgrade.

`ER_WARN_RESERVED_SRID_RANGE` was added in 8.0.4.

- Error number: `3716`; Symbol: `ER_CANT MODIFY_SRS_USED_BY_COLUMN`; SQLSTATE: `SR005`

Message: Can't modify SRID %u. There is at least one column depending on it.

`ER_CANT MODIFY_SRS_USED_BY_COLUMN` was added in 8.0.4.

- Error number: `3717`; Symbol: `ER_SRS_INVALID_CHARACTER_IN_ATTRIBUTE`; SQLSTATE: `SR006`

Message: Invalid character in attribute %s.

`ER_SRS_INVALID_CHARACTER_IN_ATTRIBUTE` was added in 8.0.4.

- Error number: `3718`; Symbol: `ER_SRS_ATTRIBUTE_STRING_TOO_LONG`; SQLSTATE: `SR006`

Message: Attribute %s is too long. The maximum length is %u characters.

`ER_SRS_ATTRIBUTE_STRING_TOO_LONG` was added in 8.0.4.

- Error number: `3719`; Symbol: `ER_DEPRECATED_UTF8_ALIAS`; SQLSTATE: `HY000`

Message: 'utf8' is currently an alias for the character set UTF8MB3, but will be an alias for UTF8MB4 in a future release. Please consider using UTF8MB4 in order to be unambiguous.

`ER_DEPRECATED_UTF8_ALIAS` was added in 8.0.11.

- Error number: `3720`; Symbol: `ER_DEPRECATED_NATIONAL`; SQLSTATE: `HY000`

Message: NATIONAL/NCHAR/NVARCHAR implies the character set UTF8MB3, which will be replaced by UTF8MB4 in a future release. Please consider using CHAR(x) CHARACTER SET UTF8MB4 in order to be unambiguous.

`ER_DEPRECATED_NATIONAL` was added in 8.0.11.

- Error number: `3721`; Symbol: `ER_INVALID_DEFAULT_UTF8MB4_COLLATION`; SQLSTATE: `HY000`

Message: Invalid default collation %s: utf8mb4_0900_ai_ci or utf8mb4_general_ci expected

`ER_INVALID_DEFAULT_UTF8MB4_COLLATION` was added in 8.0.11.

- Error number: `3722`; Symbol: `ER_UNABLE_TO_COLLECT_LOG_STATUS`; SQLSTATE: `HY000`

Message: Unable to collect information for column '%s': %s.

`ER_UNABLE_TO_COLLECT_LOG_STATUS` was added in 8.0.11.

- Error number: `3723`; Symbol: `ER_RESERVED_TABLESPACE_NAME`; SQLSTATE: `HY000`

Message: The table '%s' may not be created in the reserved tablespace '%s'.

`ER_RESERVED_TABLESPACE_NAME` was added in 8.0.11.

- Error number: `3724`; Symbol: `ER_UNABLE_TO_SET_OPTION`; SQLSTATE: `HY000`

Message: This option cannot be set %s.

`ER_UNABLE_TO_SET_OPTION` was added in 8.0.11.

- Error number: 3725; Symbol: `ER_SLAVE_POSSIBLY_DIVERGED_AFTER_DDL`; SQLSTATE: HY000

Message: A commit for an atomic DDL statement was unsuccessful on the master and the slave. The slave supports atomic DDL statements but the master does not, so the action taken by the slave and master might differ. Check that their states have not diverged before proceeding.

`ER_SLAVE_POSSIBLY_DIVERGED_AFTER_DDL` was added in 8.0.11.

- Error number: 3726; Symbol: `ER_SRS_NOT_GEOGRAPHIC`; SQLSTATE: 22S00

Message: Function %s is only defined for geographic spatial reference systems, but one of its arguments is in SRID %u, which is not geographic.

`ER_SRS_NOT_GEOGRAPHIC` was added in 8.0.12.

- Error number: 3727; Symbol: `ER_POLYGON_TOO_LARGE`; SQLSTATE: 22023

Message: Function %s encountered a polygon that was too large. Polygons must cover less than half the planet.

`ER_POLYGON_TOO_LARGE` was added in 8.0.12.

- Error number: 3728; Symbol: `ER_SPATIAL_UNIQUE_INDEX`; SQLSTATE: HY000

Message: Spatial indexes can't be primary or unique indexes.

`ER_SPATIAL_UNIQUE_INDEX` was added in 8.0.12.

- Error number: 3729; Symbol: `ER_INDEX_TYPE_NOT_SUPPORTED_FOR_SPATIAL_INDEX`; SQLSTATE: HY000

Message: The index type %s is not supported for spatial indexes.

`ER_INDEX_TYPE_NOT_SUPPORTED_FOR_SPATIAL_INDEX` was added in 8.0.12.

- Error number: 3730; Symbol: `ER_FK_CANNOT_DROP_PARENT`; SQLSTATE: HY000

Message: Cannot drop table '%s' referenced by a foreign key constraint '%s' on table '%s'.

`ER_FK_CANNOT_DROP_PARENT` was added in 8.0.12.

- Error number: 3731; Symbol: `ER_GEOMETRY_PARAM_LONGITUDE_OUT_OF_RANGE`; SQLSTATE: 22S02

Message: A parameter of function %s contains a geometry with longitude %f, which is out of range. It must be within (%f, %f].

`ER_GEOMETRY_PARAM_LONGITUDE_OUT_OF_RANGE` was added in 8.0.12.

- Error number: 3732; Symbol: `ER_GEOMETRY_PARAM_LATITUDE_OUT_OF_RANGE`; SQLSTATE: 22S03

Message: A parameter of function %s contains a geometry with latitude %f, which is out of range. It must be within [%f, %f].

`ER_GEOMETRY_PARAM_LATITUDE_OUT_OF_RANGE` was added in 8.0.12.

- Error number: 3733; Symbol: `ER_FK_CANNOT_USE_VIRTUAL_COLUMN`; SQLSTATE: HY000

Message: Foreign key '%s' uses virtual column '%s' which is not supported.

`ER_FK_CANNOT_USE_VIRTUAL_COLUMN` was added in 8.0.12.

- Error number: 3734; Symbol: `ER_FK_NO_COLUMN_PARENT`; SQLSTATE: HY000

Message: Failed to add the foreign key constraint. Missing column '%s' for constraint '%s' in the referenced table '%s'

`ER_FK_NO_COLUMN_PARENT` was added in 8.0.12.

- Error number: 3735; Symbol: `ER_CANT_SET_ERROR_SUPPRESSION_LIST`; SQLSTATE: HY000

Message: %s: Could not add suppression rule for code "%s". Rule-set may be full, or code may not correspond to an error-log message.

`ER_CANT_SET_ERROR_SUPPRESSION_LIST` was added in 8.0.13.

- Error number: 3736; Symbol: `ER_SRS_GEOGCS_INVALID_AXES`; SQLSTATE: SR002

Message: The spatial reference system definition for SRID %u specifies invalid geographic axes '%s' and '%s'. One axis must be NORTH or SOUTH and the other must be EAST or WEST.

`ER_SRS_GEOGCS_INVALID_AXES` was added in 8.0.13.

- Error number: 3737; Symbol: `ER_SRS_INVALID_SEMI_MAJOR_AXIS`; SQLSTATE: SR002

Message: The length of the semi-major axis must be a positive number.

`ER_SRS_INVALID_SEMI_MAJOR_AXIS` was added in 8.0.13.

- Error number: 3738; Symbol: `ER_SRS_INVALID_INVERSE_FLATTENING`; SQLSTATE: SR002

Message: The inverse flattening must be larger than 1.0, or 0.0 if the ellipsoid is a sphere.

`ER_SRS_INVALID_INVERSE_FLATTENING` was added in 8.0.13.

- Error number: 3739; Symbol: `ER_SRS_INVALID_ANGULAR_UNIT`; SQLSTATE: SR002

Message: The angular unit conversion factor must be a positive number.

`ER_SRS_INVALID_ANGULAR_UNIT` was added in 8.0.13.

- Error number: 3740; Symbol: `ER_SRS_INVALID_PRIME_MERIDIAN`; SQLSTATE: SR002

Message: The prime meridian must be within (-180, 180] degrees, specified in the SRS angular unit.

`ER_SRS_INVALID_PRIME_MERIDIAN` was added in 8.0.13.

- Error number: 3741; Symbol: `ER_TRANSFORM_SOURCE_SRS_NOT_SUPPORTED`; SQLSTATE: 22S00

Message: Transformation from SRID %u is not supported.

`ER_TRANSFORM_SOURCE_SRS_NOT_SUPPORTED` was added in 8.0.13.

- Error number: 3742; Symbol: `ER_TRANSFORM_TARGET_SRS_NOT_SUPPORTED`; SQLSTATE: 22S00

Message: Transformation to SRID %u is not supported.

`ER_TRANSFORM_TARGET_SRS_NOT_SUPPORTED` was added in 8.0.13.

- Error number: [3743](#); Symbol: [ER_TRANSFORM_SOURCE_SRS_MISSING_TOWGS84](#); SQLSTATE: [22S00](#)

Message: Transformation from SRID %u is not supported. The spatial reference system has no TOWGS84 clause.

[ER_TRANSFORM_SOURCE_SRS_MISSING_TOWGS84](#) was added in 8.0.13.

- Error number: [3744](#); Symbol: [ER_TRANSFORM_TARGET_SRS_MISSING_TOWGS84](#); SQLSTATE: [22S00](#)

Message: Transformation to SRID %u is not supported. The spatial reference system has no TOWGS84 clause.

[ER_TRANSFORM_TARGET_SRS_MISSING_TOWGS84](#) was added in 8.0.13.

- Error number: [3745](#); Symbol: [ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG_FORMAT](#); SQLSTATE: [HY000](#)

Message: Changing @@session.binlog_format is disallowed when the session has open temporary table(s). You could wait until these temporary table(s) are dropped and try again.

[ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG_FORMAT](#) was added in 8.0.13.

- Error number: [3746](#); Symbol: [ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT](#); SQLSTATE: [HY000](#)

Message: Changing @@global.binlog_format or @@persist.binlog_format is disallowed when any replication channel has open temporary table(s). You could wait until Replica_open_temp_tables = 0 and try again

[ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT](#) was added in 8.0.13.

- Error number: [3747](#); Symbol: [ER_RUNNING_APPLIER_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT](#); SQLSTATE: [HY000](#)

Message: Changing @@global.binlog_format or @@persist.binlog_format is disallowed when any replication channel applier thread is running. You could execute STOP SLAVE SQL_THREAD and try again.

[ER_RUNNING_APPLIER_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT](#) was added in 8.0.13.

- Error number: [3748](#); Symbol: [ER_CLIENT_GTIID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_TRX_IN_SBR](#); SQLSTATE: [HY000](#)

Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE are not allowed inside a transaction or inside a procedure in a transactional context when @@session.binlog_format=STATEMENT.

[ER_CLIENT_GTIID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_TRX_IN_SBR](#) was added in 8.0.13.

- Error number: [3750](#); Symbol: [ER_TABLE_WITHOUT_PK](#); SQLSTATE: [HY000](#)

Message: Unable to create or change a table without a primary key, when the system variable 'sql_require_primary_key' is set. Add a primary key to the table or unset this variable to avoid this message. Note that tables without a primary key can cause performance problems in row-based replication, so please consult your DBA before changing this setting.

[ER_TABLE_WITHOUT_PK](#) was added in 8.0.13.

-
- Error number: 3751; Symbol: `WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX`; SQLSTATE: `01000`

Message: Data truncated for functional index '%s' at row %ld
`WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX` was added in 8.0.13, removed after 8.0.16.
 - Error number: 3751; Symbol: `ER_WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX`; SQLSTATE: `01000`

Message: Data truncated for functional index '%s' at row %ld
`ER_WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX` was added in 8.0.17.
 - Error number: 3752; Symbol: `ER_WARN_DATA_OUT_OF_RANGE_FUNCTIONAL_INDEX`; SQLSTATE: `22003`

Message: Value is out of range for functional index '%s' at row %ld
`ER_WARN_DATA_OUT_OF_RANGE_FUNCTIONAL_INDEX` was added in 8.0.13.
 - Error number: 3753; Symbol: `ER_FUNCTIONAL_INDEX_ON_JSON_OR_GEOMETRY_FUNCTION`; SQLSTATE: `42000`

Message: Cannot create a functional index on a function that returns a JSON or GEOMETRY value.
`ER_FUNCTIONAL_INDEX_ON_JSON_OR_GEOMETRY_FUNCTION` was added in 8.0.13.
 - Error number: 3754; Symbol: `ER_FUNCTIONAL_INDEX_REF_AUTO_INCREMENT`; SQLSTATE: `HY000`

Message: Functional index '%s' cannot refer to an auto-increment column.
`ER_FUNCTIONAL_INDEX_REF_AUTO_INCREMENT` was added in 8.0.13.
 - Error number: 3755; Symbol: `ER_CANNOT_DROP_COLUMN_FUNCTIONAL_INDEX`; SQLSTATE: `HY000`

Message: Cannot drop column '%s' because it is used by a functional index. In order to drop the column, you must remove the functional index.
`ER_CANNOT_DROP_COLUMN_FUNCTIONAL_INDEX` was added in 8.0.13.
 - Error number: 3756; Symbol: `ER_FUNCTIONAL_INDEX_PRIMARY_KEY`; SQLSTATE: `HY000`

Message: The primary key cannot be a functional index
`ER_FUNCTIONAL_INDEX_PRIMARY_KEY` was added in 8.0.13.
 - Error number: 3757; Symbol: `ER_FUNCTIONAL_INDEX_ON_LOB`; SQLSTATE: `HY000`

Message: Cannot create a functional index on an expression that returns a BLOB or TEXT. Please consider using CAST.
`ER_FUNCTIONAL_INDEX_ON_LOB` was added in 8.0.13.
 - Error number: 3758; Symbol: `ER_FUNCTIONAL_INDEX_FUNCTION_IS_NOT_ALLOWED`; SQLSTATE: `HY000`

Message: Expression of functional index '%s' contains a disallowed function.
`ER_FUNCTIONAL_INDEX_FUNCTION_IS_NOT_ALLOWED` was added in 8.0.13.
 - Error number: 3759; Symbol: `ER_FULLTEXT_FUNCTIONAL_INDEX`; SQLSTATE: `HY000`

Message: Fulltext functional index is not supported.

`ER_FULLTEXT_FUNCTIONAL_INDEX` was added in 8.0.13.

- Error number: `3760`; Symbol: `ER_SPATIAL_FUNCTIONAL_INDEX`; SQLSTATE: `HY000`

Message: Spatial functional index is not supported.

`ER_SPATIAL_FUNCTIONAL_INDEX` was added in 8.0.13.

- Error number: `3761`; Symbol: `ER_WRONG_KEY_COLUMN_FUNCTIONAL_INDEX`; SQLSTATE: `HY000`

Message: The used storage engine cannot index the expression '%s'.

`ER_WRONG_KEY_COLUMN_FUNCTIONAL_INDEX` was added in 8.0.13.

- Error number: `3762`; Symbol: `ER_FUNCTIONAL_INDEX_ON_FIELD`; SQLSTATE: `HY000`

Message: Functional index on a column is not supported. Consider using a regular index instead.

`ER_FUNCTIONAL_INDEX_ON_FIELD` was added in 8.0.13.

- Error number: `3763`; Symbol: `ER_GENERATED_COLUMN_NAMED_FUNCTION_IS_NOT_ALLOWED`; SQLSTATE: `HY000`

Message: Expression of generated column '%s' contains a disallowed function: %s.

`ER_GENERATED_COLUMN_NAMED_FUNCTION_IS_NOT_ALLOWED` was added in 8.0.13.

- Error number: `3764`; Symbol: `ER_GENERATED_COLUMN_ROW_VALUE`; SQLSTATE: `HY000`

Message: Expression of generated column '%s' cannot refer to a row value.

`ER_GENERATED_COLUMN_ROW_VALUE` was added in 8.0.13.

- Error number: `3765`; Symbol: `ER_GENERATED_COLUMN_VARIABLES`; SQLSTATE: `HY000`

Message: Expression of generated column '%s' cannot refer user or system variables.

`ER_GENERATED_COLUMN_VARIABLES` was added in 8.0.13.

- Error number: `3766`; Symbol: `ER_DEPENDENT_BY_DEFAULT_GENERATED_VALUE`; SQLSTATE: `HY000`

Message: Column '%s' of table '%s' has a default value expression dependency and cannot be dropped or renamed.

`ER_DEPENDENT_BY_DEFAULT_GENERATED_VALUE` was added in 8.0.13.

- Error number: `3767`; Symbol: `ER_DEFAULT_VAL_GENERATED_NON_PRIOR`; SQLSTATE: `HY000`

Message: Default value expression of column '%s' cannot refer to a column defined after it if that column is a generated column or has an expression as default value.

`ER_DEFAULT_VAL_GENERATED_NON_PRIOR` was added in 8.0.13.

- Error number: `3768`; Symbol: `ER_DEFAULT_VAL_GENERATED_REF_AUTO_INC`; SQLSTATE: `HY000`

Message: Default value expression of column '%s' cannot refer to an auto-increment column.

`ER_DEFAULT_VAL_GENERATED_REF_AUTO_INC` was added in 8.0.13.

- Error number: [3769](#); Symbol: `ER_DEFAULT_VAL_GENERATED_FUNCTION_IS_NOT_ALLOWED`; SQLSTATE: `HY000`

Message: Default value expression of column '%s' contains a disallowed function.
`ER_DEFAULT_VAL_GENERATED_FUNCTION_IS_NOT_ALLOWED` was added in 8.0.13.
- Error number: [3770](#); Symbol: `ER_DEFAULT_VAL_GENERATED_NAMED_FUNCTION_IS_NOT_ALLOWED`; SQLSTATE: `HY000`

Message: Default value expression of column '%s' contains a disallowed function: %s.
`ER_DEFAULT_VAL_GENERATED_NAMED_FUNCTION_IS_NOT_ALLOWED` was added in 8.0.13.
- Error number: [3771](#); Symbol: `ER_DEFAULT_VAL_GENERATED_ROW_VALUE`; SQLSTATE: `HY000`

Message: Default value expression of column '%s' cannot refer to a row value.
`ER_DEFAULT_VAL_GENERATED_ROW_VALUE` was added in 8.0.13.
- Error number: [3772](#); Symbol: `ER_DEFAULT_VAL_GENERATED_VARIABLES`; SQLSTATE: `HY000`

Message: Default value expression of column '%s' cannot refer user or system variables.
`ER_DEFAULT_VAL_GENERATED_VARIABLES` was added in 8.0.13.
- Error number: [3773](#); Symbol: `ER_DEFAULT_AS_VAL_GENERATED`; SQLSTATE: `HY000`

Message: DEFAULT function cannot be used with default value expressions
`ER_DEFAULT_AS_VAL_GENERATED` was added in 8.0.13.
- Error number: [3774](#); Symbol: `ER_UNSUPPORTED_ACTION_ON_DEFAULT_VAL_GENERATED`; SQLSTATE: `HY000`

Message: '%s' is not supported for default value expressions.
`ER_UNSUPPORTED_ACTION_ON_DEFAULT_VAL_GENERATED` was added in 8.0.13.
- Error number: [3775](#); Symbol: `ER_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION`; SQLSTATE: `HY000`

Message: Statement violates GTID consistency: ALTER TABLE ... ADD COLUMN .. with expression as DEFAULT.
`ER_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION` was added in 8.0.13.
- Error number: [3776](#); Symbol: `ER_FK_CANNOT_CHANGE_ENGINE`; SQLSTATE: `HY000`

Message: Cannot change table's storage engine because the table participates in a foreign key constraint.
`ER_FK_CANNOT_CHANGE_ENGINE` was added in 8.0.13.
- Error number: [3777](#); Symbol: `ER_WARN_DEPRECATED_USER_SET_EXPR`; SQLSTATE: `HY000`

Message: Setting user variables within expressions is deprecated and will be removed in a future release. Consider alternatives: 'SET variable=expression, ...', or 'SELECT expression(s) INTO variables(s)'.
`ER_WARN_DEPRECATED_USER_SET_EXPR` was added in 8.0.13.
- Error number: [3778](#); Symbol: `ER_WARN_DEPRECATED_UTF8MB3_COLLATION`; SQLSTATE: `HY000`

Message: '%s' is a collation of the deprecated character set UTF8MB3. Please consider using UTF8MB4 with an appropriate collation instead.

[ER_WARN_DEPRECATED_UTF8MB3_COLLATION](#) was added in 8.0.13.

- Error number: [3779](#); Symbol: [ER_WARN_DEPRECATED_NESTED_COMMENT_SYNTAX](#); SQLSTATE: [HY000](#)

Message: Nested comment syntax is deprecated and will be removed in a future release.

[ER_WARN_DEPRECATED_NESTED_COMMENT_SYNTAX](#) was added in 8.0.13.

- Error number: [3780](#); Symbol: [ER_FK_INCOMPATIBLE_COLUMNS](#); SQLSTATE: [HY000](#)

Message: Referencing column '%s' and referenced column '%s' in foreign key constraint '%s' are incompatible.

[ER_FK_INCOMPATIBLE_COLUMNS](#) was added in 8.0.14.

- Error number: [3781](#); Symbol: [ER_GR_HOLD_WAIT_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: Timeout exceeded for held statement while new Group Replication primary member is applying backlog.

[ER_GR_HOLD_WAIT_TIMEOUT](#) was added in 8.0.14.

- Error number: [3782](#); Symbol: [ER_GR_HOLD_KILLED](#); SQLSTATE: [HY000](#)

Message: Held statement aborted because Group Replication plugin got shut down or thread was killed while new primary member was applying backlog.

[ER_GR_HOLD_KILLED](#) was added in 8.0.14.

- Error number: [3783](#); Symbol: [ER_GR_HOLD_MEMBER_STATUS_ERROR](#); SQLSTATE: [HY000](#)

Message: Held statement was aborted due to member being in error state, while backlog is being applied during Group Replication primary election.

[ER_GR_HOLD_MEMBER_STATUS_ERROR](#) was added in 8.0.14.

- Error number: [3784](#); Symbol: [ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY](#); SQLSTATE: [HY000](#)

Message: Failed to fetch key from keyring, please check if keyring is loaded.

[ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY](#) was added in 8.0.14.

- Error number: [3785](#); Symbol: [ER_RPL_ENCRYPTION_KEY_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Can't find key from keyring, please check in the server log if a keyring is loaded and initialized successfully.

[ER_RPL_ENCRYPTION_KEY_NOT_FOUND](#) was added in 8.0.14.

- Error number: [3786](#); Symbol: [ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY](#); SQLSTATE: [HY000](#)

Message: Fetched an invalid key from keyring.

[ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY](#) was added in 8.0.14.

- Error number: [3787](#); Symbol: [ER_RPL_ENCRYPTION_HEADER_ERROR](#); SQLSTATE: [HY000](#)

Message: Error reading a replication log encryption header: %s.

`ER_RPL_ENCRYPTION_HEADER_ERROR` was added in 8.0.14.

- Error number: 3788; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS`; SQLSTATE: HY000

Message: Failed to rotate some logs after changing binlog encryption settings. Please fix the problem and rotate the logs manually.

`ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS` was added in 8.0.14.

- Error number: 3789; Symbol: `ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED`; SQLSTATE: HY000

Message: Key %s exists unexpected.

`ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED` was added in 8.0.14.

- Error number: 3790; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY`; SQLSTATE: HY000

Message: Failed to generate key, please check if keyring is loaded.

`ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY` was added in 8.0.14.

- Error number: 3791; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY`; SQLSTATE: HY000

Message: Failed to store key, please check if keyring is loaded.

`ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY` was added in 8.0.14.

- Error number: 3792; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY`; SQLSTATE: HY000

Message: Failed to remove key, please check if keyring is loaded.

`ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY` was added in 8.0.14.

- Error number: 3793; Symbol: `ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTION`; SQLSTATE: HY000

Message: Failed to change binlog_encryption value. %s.

`ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTION` was added in 8.0.14.

- Error number: 3794; Symbol: `ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED`; SQLSTATE: HY000

Message: Unable to recover binlog encryption master key, please check if keyring is loaded.

`ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED` was added in 8.0.14.

- Error number: 3795; Symbol: `ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGING_TO_FILE`; SQLSTATE: HY000

Message: slow query log file format changed as requested, but setting will have no effect when not actually logging to a file.

`ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGING_TO_FILE` was added in 8.0.14.

- Error number: 3796; Symbol: `ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED`; SQLSTATE: HY000

Message: The option group_replication_consistency cannot be used on the current member state.

`ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED` was added in 8.0.14.

- Error number: 3797; Symbol: `ER_GRP_TRX_CONSISTENCY_BEFORE`; SQLSTATE: HY000

Message: Error while waiting for group transactions commit on group_replication_consistency= 'BEFORE'.

`ER_GRP_TRX_CONSISTENCY_BEFORE` was added in 8.0.14.

- Error number: 3798; Symbol: `ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN`; SQLSTATE: HY000

Message: Error while waiting for transactions with group_replication_consistency= 'AFTER' to commit.

`ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN` was added in 8.0.14.

- Error number: 3799; Symbol: `ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED`; SQLSTATE: HY000

Message: The Group Replication plugin is stopping, therefore new transactions are not allowed to start.

`ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED` was added in 8.0.14.

- Error number: 3800; Symbol: `ER_FUNCTIONAL_INDEX_ROW_VALUE_IS_NOT_ALLOWED`; SQLSTATE: HY000

Message: Expression of functional index '%s' cannot refer to a row value.

`ER_FUNCTIONAL_INDEX_ROW_VALUE_IS_NOT_ALLOWED` was added in 8.0.14.

- Error number: 3801; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT`; SQLSTATE: HY000

Message: Failed to encrypt content to write into binlog file: %s.

`ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT` was added in 8.0.14.

- Error number: 3802; Symbol: `ER_PAGE_TRACKING_NOT_STARTED`; SQLSTATE: HY000

Message: Page Tracking is not started yet.

`ER_PAGE_TRACKING_NOT_STARTED` was added in 8.0.16.

- Error number: 3803; Symbol: `ER_PAGE_TRACKING_RANGE_NOT_TRACKED`; SQLSTATE: HY000

Message: Tracking was not enabled for the LSN range specified

`ER_PAGE_TRACKING_RANGE_NOT_TRACKED` was added in 8.0.16.

- Error number: 3804; Symbol: `ER_PAGE_TRACKING_CANNOT_PURGE`; SQLSTATE: HY000

Message: Cannot purge data when concurrent clone is in progress. Try later.

`ER_PAGE_TRACKING_CANNOT_PURGE` was added in 8.0.16.

- Error number: 3805; Symbol: `ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MASTER_KEY`; SQLSTATE: HY000

Message: Cannot rotate binary log master key when 'binlog-encryption' is off.

`ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MASTER_KEY` was added in 8.0.16.

- Error number: `3806`; Symbol: `ER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION`; SQLSTATE: `HY000`

Message: Unable to recover binary log master key, the combination of `new_master_key_seqno=%u`, `master_key_seqno=%u` and `old_master_key_seqno=%u` are wrong.

`ER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION` was added in 8.0.16.

- Error number: `3807`; Symbol: `ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_OPERATE_KEY`; SQLSTATE: `HY000`

Message: Failed to operate binary log master key on keyring, please check if keyring is loaded. The statement had no effect: the old binary log master key is still in use, the keyring, binary and relay log files are unchanged, and the server could not start using a new binary log master key for encrypting new binary and relay log files.

`ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_OPERATE_KEY` was added in 8.0.16.

- Error number: `3808`; Symbol: `ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_ROTATE_LOGS`; SQLSTATE: `HY000`

Message: Failed to rotate one or more binary or relay log files. A new binary log master key was generated and will be used to encrypt new binary and relay log files. There may still exist binary or relay log files using the previous binary log master key.

`ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_ROTATE_LOGS` was added in 8.0.16.

- Error number: `3809`; Symbol: `ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_REENCRYPT_LOG`; SQLSTATE: `HY000`

Message: %s. A new binary log master key was generated and will be used to encrypt new binary and relay log files. There may still exist binary or relay log files using the previous binary log master key.

`ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_REENCRYPT_LOG` was added in 8.0.16.

- Error number: `3810`; Symbol: `ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_UNUSED_KEYS`; SQLSTATE: `HY000`

Message: Failed to remove unused binary log encryption keys from the keyring, please check if keyring is loaded. The unused binary log encryption keys may still exist in the keyring, and they will be removed upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.

`ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_UNUSED_KEYS` was added in 8.0.16.

- Error number: `3811`; Symbol: `ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_AUX_KEY`; SQLSTATE: `HY000`

Message: Failed to remove auxiliary binary log encryption key from keyring, please check if keyring is loaded. The cleanup of the binary log master key rotation process did not finish as expected and the cleanup will take place upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.

`ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_AUX_KEY` was added in 8.0.16.

- Error number: 3812; Symbol: `ER_NON_BOOLEAN_EXPR_FOR_CHECK_CONSTRAINT`; SQLSTATE: `HY000`

Message: An expression of non-boolean type specified to a check constraint '%s'.

`ER_NON_BOOLEAN_EXPR_FOR_CHECK_CONSTRAINT` was added in 8.0.16.

- Error number: 3813; Symbol: `ER_COLUMN_CHECK_CONSTRAINT_REFERENCES_OTHER_COLUMN`; SQLSTATE: `HY000`

Message: Column check constraint '%s' references other column.

`ER_COLUMN_CHECK_CONSTRAINT_REFERENCES_OTHER_COLUMN` was added in 8.0.16.

- Error number: 3814; Symbol: `ER_CHECK_CONSTRAINT_NAMED_FUNCTION_IS_NOT_ALLOWED`; SQLSTATE: `HY000`

Message: An expression of a check constraint '%s' contains disallowed function: %s.

`ER_CHECK_CONSTRAINT_NAMED_FUNCTION_IS_NOT_ALLOWED` was added in 8.0.16.

- Error number: 3815; Symbol: `ER_CHECK_CONSTRAINT_FUNCTION_IS_NOT_ALLOWED`; SQLSTATE: `HY000`

Message: An expression of a check constraint '%s' contains disallowed function.

`ER_CHECK_CONSTRAINT_FUNCTION_IS_NOT_ALLOWED` was added in 8.0.16.

- Error number: 3816; Symbol: `ER_CHECK_CONSTRAINT_VARIABLES`; SQLSTATE: `HY000`

Message: An expression of a check constraint '%s' cannot refer to a user or system variable.

`ER_CHECK_CONSTRAINT_VARIABLES` was added in 8.0.16.

- Error number: 3817; Symbol: `ER_CHECK_CONSTRAINT_ROW_VALUE`; SQLSTATE: `HY000`

Message: Check constraint '%s' cannot refer to a row value.

`ER_CHECK_CONSTRAINT_ROW_VALUE` was added in 8.0.16.

- Error number: 3818; Symbol: `ER_CHECK_CONSTRAINT_REFERS_AUTO_INCREMENT_COLUMN`; SQLSTATE: `HY000`

Message: Check constraint '%s' cannot refer to an auto-increment column.

`ER_CHECK_CONSTRAINT_REFERS_AUTO_INCREMENT_COLUMN` was added in 8.0.16.

- Error number: 3819; Symbol: `ER_CHECK_CONSTRAINT_VIOLATED`; SQLSTATE: `HY000`

Message: Check constraint '%s' is violated.

`ER_CHECK_CONSTRAINT_VIOLATED` was added in 8.0.16.

- Error number: 3820; Symbol: `ER_CHECK_CONSTRAINT_REFERS_UNKNOWN_COLUMN`; SQLSTATE: `HY000`

Message: Check constraint '%s' refers to non-existing column '%s'.

`ER_CHECK_CONSTRAINT_REFERS_UNKNOWN_COLUMN` was added in 8.0.16.

- Error number: 3821; Symbol: `ER_CHECK_CONSTRAINT_NOT_FOUND`; SQLSTATE: `HY000`

Message: Check constraint '%s' is not found in the table.

`ER_CHECK_CONSTRAINT_NOT_FOUND` was added in 8.0.16.

- Error number: `3822`; Symbol: `ER_CHECK_CONSTRAINT_DUP_NAME`; SQLSTATE: `HY000`

Message: Duplicate check constraint name '%s'.

`ER_CHECK_CONSTRAINT_DUP_NAME` was added in 8.0.16.

- Error number: `3823`; Symbol:

`ER_CHECK_CONSTRAINT_CLAUSE_USING_FK_REFER_ACTION_COLUMN`; SQLSTATE: `HY000`

Message: Column '%s' cannot be used in a check constraint '%s': needed in a foreign key constraint '%s' referential action.

`ER_CHECK_CONSTRAINT_CLAUSE_USING_FK_REFER_ACTION_COLUMN` was added in 8.0.16.

- Error number: `3824`; Symbol: `WARN_UNENCRYPTED_TABLE_IN_ENCRYPTED_DB`; SQLSTATE: `HY000`

Message: Creating an unencrypted table in a database with default encryption enabled.

`WARN_UNENCRYPTED_TABLE_IN_ENCRYPTED_DB` was added in 8.0.16.

- Error number: `3825`; Symbol: `ER_INVALID_ENCRYPTION_REQUEST`; SQLSTATE: `HY000`

Message: Request to create %s table while using an %s tablespace.

`ER_INVALID_ENCRYPTION_REQUEST` was added in 8.0.16.

- Error number: `3826`; Symbol: `ER_CANNOT_SET_TABLE_ENCRYPTION`; SQLSTATE: `HY000`

Message: Table encryption differ from its database default encryption, and user doesn't have enough privilege.

`ER_CANNOT_SET_TABLE_ENCRYPTION` was added in 8.0.16.

- Error number: `3827`; Symbol: `ER_CANNOT_SET_DATABASE_ENCRYPTION`; SQLSTATE: `HY000`

Message: Database default encryption differ from 'default_table_encryption' setting, and user doesn't have enough privilege.

`ER_CANNOT_SET_DATABASE_ENCRYPTION` was added in 8.0.16.

- Error number: `3828`; Symbol: `ER_CANNOT_SET_TABLESPACE_ENCRYPTION`; SQLSTATE: `HY000`

Message: Tablespace encryption differ from 'default_table_encryption' setting, and user doesn't have enough privilege.

`ER_CANNOT_SET_TABLESPACE_ENCRYPTION` was added in 8.0.16.

- Error number: `3829`; Symbol: `ER_TABLESPACE_CANNOT_BE_ENCRYPTED`; SQLSTATE: `HY000`

Message: This tablespace can't be encrypted, because one of table's schema has default encryption OFF and user doesn't have enough privilege.

`ER_TABLESPACE_CANNOT_BE_ENCRYPTED` was added in 8.0.16.

- Error number: `3830`; Symbol: `ER_TABLESPACE_CANNOT_BE_DECRYPTED`; SQLSTATE: `HY000`

Message: This tablespace can't be decrypted, because one of table's schema has default encryption ON and user doesn't have enough privilege.

`ER_TABLESPACE_CANNOT_BE_DECRYPTED` was added in 8.0.16.

- Error number: 3831; Symbol: `ER_TABLESPACE_TYPE_UNKNOWN`; SQLSTATE: `HY000`

Message: Cannot determine the type of the tablespace named '%s'.
`ER_TABLESPACE_TYPE_UNKNOWN` was added in 8.0.16.
- Error number: 3832; Symbol: `ER_TARGET_TABLESPACE_UNENCRYPTED`; SQLSTATE: `HY000`

Message: Source tablespace is encrypted but target tablespace is not.
`ER_TARGET_TABLESPACE_UNENCRYPTED` was added in 8.0.16.
- Error number: 3833; Symbol: `ER_CANNOT_USE_ENCRYPTION_CLAUSE`; SQLSTATE: `HY000`

Message: ENCRYPTION clause is not valid for %s tablespace.
`ER_CANNOT_USE_ENCRYPTION_CLAUSE` was added in 8.0.16.
- Error number: 3834; Symbol: `ER_INVALID_MULTIPLE_CLAUSES`; SQLSTATE: `HY000`

Message: Multiple %s clauses
`ER_INVALID_MULTIPLE_CLAUSES` was added in 8.0.16.
- Error number: 3835; Symbol: `ER_UNSUPPORTED_USE_OF_GRANT_AS`; SQLSTATE: `HY000`

Message: GRANT ... AS is currently supported only for global privileges.
`ER_UNSUPPORTED_USE_OF_GRANT_AS` was added in 8.0.16.
- Error number: 3836; Symbol: `ER_UNKNOWN_AUTH_ID_OR_ACCESS_DENIED_FOR_GRANT_AS`; SQLSTATE: `HY000`

Message: Either some of the authorization IDs in the AS clause are invalid or the current user lacks privileges to execute the statement.
`ER_UNKNOWN_AUTH_ID_OR_ACCESS_DENIED_FOR_GRANT_AS` was added in 8.0.16.
- Error number: 3837; Symbol: `ER_DEPENDENT_BY_FUNCTIONAL_INDEX`; SQLSTATE: `HY000`

Message: Column '%s' has a functional index dependency and cannot be dropped or renamed.
`ER_DEPENDENT_BY_FUNCTIONAL_INDEX` was added in 8.0.17.
- Error number: 3838; Symbol: `ER_PLUGIN_NOT_EARLY`; SQLSTATE: `HY000`

Message: Plugin '%s' is not to be used as an "early" plugin. Don't add it to --early-plugin-load, keyring migration etc.
`ER_PLUGIN_NOT_EARLY` was added in 8.0.17.
- Error number: 3839; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_START_SUBDIR_PATH`; SQLSTATE: `HY000`

Message: Redo log archiving start prohibits path name in 'subdir' argument
`ER_INNODB_REDO_LOG_ARCHIVE_START_SUBDIR_PATH` was added in 8.0.17.
- Error number: 3840; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_START_TIMEOUT`; SQLSTATE: `HY000`

Message: Redo log archiving start timed out
`ER_INNODB_REDO_LOG_ARCHIVE_START_TIMEOUT` was added in 8.0.17.

- Error number: 3841; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_DIRS_INVALID`; SQLSTATE: `HY000`

Message: Server variable 'innodb_redo_log_archive_dirs' is NULL or empty
`ER_INNODB_REDO_LOG_ARCHIVE_DIRS_INVALID` was added in 8.0.17.
- Error number: 3842; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_LABEL_NOT_FOUND`; SQLSTATE: `HY000`

Message: Label '%s' not found in server variable 'innodb_redo_log_archive_dirs'
`ER_INNODB_REDO_LOG_ARCHIVE_LABEL_NOT_FOUND` was added in 8.0.17.
- Error number: 3843; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_DIR_EMPTY`; SQLSTATE: `HY000`

Message: Directory is empty after label '%s' in server variable 'innodb_redo_log_archive_dirs'
`ER_INNODB_REDO_LOG_ARCHIVE_DIR_EMPTY` was added in 8.0.17.
- Error number: 3844; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_NO SUCH_DIR`; SQLSTATE: `HY000`

Message: Redo log archive directory '%s' does not exist or is not a directory
`ER_INNODB_REDO_LOG_ARCHIVE_NO SUCH_DIR` was added in 8.0.17.
- Error number: 3845; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_DIR_CLASH`; SQLSTATE: `HY000`

Message: Redo log archive directory '%s' is in, under, or over server directory '%s' - '%s'
`ER_INNODB_REDO_LOG_ARCHIVE_DIR_CLASH` was added in 8.0.17.
- Error number: 3846; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_DIR_PERMISSIONS`; SQLSTATE: `HY000`

Message: Redo log archive directory '%s' is accessible to all OS users
`ER_INNODB_REDO_LOG_ARCHIVE_DIR_PERMISSIONS` was added in 8.0.17.
- Error number: 3847; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_FILE_CREATE`; SQLSTATE: `HY000`

Message: Cannot create redo log archive file '%s' (OS errno: %d - %s)
`ER_INNODB_REDO_LOG_ARCHIVE_FILE_CREATE` was added in 8.0.17.
- Error number: 3848; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_ACTIVE`; SQLSTATE: `HY000`

Message: Redo log archiving has been started on '%s' - Call innodb_redo_log_archive_stop() first
`ER_INNODB_REDO_LOG_ARCHIVE_ACTIVE` was added in 8.0.17.
- Error number: 3849; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_INACTIVE`; SQLSTATE: `HY000`

Message: Redo log archiving is not active
`ER_INNODB_REDO_LOG_ARCHIVE_INACTIVE` was added in 8.0.17.
- Error number: 3850; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_FAILED`; SQLSTATE: `HY000`

Message: Redo log archiving failed: %s
`ER_INNODB_REDO_LOG_ARCHIVE_FAILED` was added in 8.0.17.

- Error number: 3851; Symbol: [ER_INNODB_REDO_LOG_ARCHIVE_SESSION](#); SQLSTATE: HY000
Message: Redo log archiving has not been started by this session
[ER_INNODB_REDO_LOG_ARCHIVE_SESSION](#) was added in 8.0.17.
- Error number: 3852; Symbol: [ER_STD_REGEX_ERROR](#); SQLSTATE: HY000
Message: Regex error: %s in function %.
[ER_STD_REGEX_ERROR](#) was added in 8.0.17.
- Error number: 3853; Symbol: [ER_INVALID_JSON_TYPE](#); SQLSTATE: 22032
Message: Invalid JSON type in argument %u to function %.; an %s is required.
[ER_INVALID_JSON_TYPE](#) was added in 8.0.17.
- Error number: 3854; Symbol: [ER_CANNOT_CONVERT_STRING](#); SQLSTATE: HY000
Message: Cannot convert string '%s' from %s to %.
[ER_CANNOT_CONVERT_STRING](#) was added in 8.0.17.
- Error number: 3855; Symbol: [ER_DEPENDENT_BY_PARTITION_FUNC](#); SQLSTATE: HY000
Message: Column '%s' has a partitioning function dependency and cannot be dropped or renamed.
[ER_DEPENDENT_BY_PARTITION_FUNC](#) was added in 8.0.17.
- Error number: 3856; Symbol: [ER_WARN_DEPRECATED_FLOAT_AUTO_INCREMENT](#); SQLSTATE: HY000
Message: AUTO_INCREMENT support for FLOAT/DOUBLE columns is deprecated and will be removed in a future release. Consider removing AUTO_INCREMENT from column '%s'.
[ER_WARN_DEPRECATED_FLOAT_AUTO_INCREMENT](#) was added in 8.0.17.
- Error number: 3857; Symbol: [ER_RPL_CANT_STOP_SLAVE_WHILE_LOCKED_BACKUP](#); SQLSTATE: HY000
Message: Cannot stop the slave SQL thread while the instance is locked for backup. Try running `UNLOCK INSTANCE` first.
[ER_RPL_CANT_STOP_SLAVE_WHILE_LOCKED_BACKUP](#) was added in 8.0.17.
- Error number: 3858; Symbol: [ER_WARN_DEPRECATED_FLOAT_DIGITS](#); SQLSTATE: HY000
Message: Specifying number of digits for floating point data types is deprecated and will be removed in a future release.
[ER_WARN_DEPRECATED_FLOAT_DIGITS](#) was added in 8.0.17.
- Error number: 3859; Symbol: [ER_WARN_DEPRECATED_FLOAT_UNSIGNED](#); SQLSTATE: HY000
Message: UNSIGNED for decimal and floating point data types is deprecated and support for it will be removed in a future release.
[ER_WARN_DEPRECATED_FLOAT_UNSIGNED](#) was added in 8.0.17.
- Error number: 3860; Symbol: [ER_WARN_DEPRECATED_INTEGER_DISPLAY_WIDTH](#); SQLSTATE: HY000
Message: Integer display width is deprecated and will be removed in a future release.

`ER_WARN_DEPRECATED_INTEGER_DISPLAY_WIDTH` was added in 8.0.17.

- Error number: `3861`; Symbol: `ER_WARN_DEPRECATED_ZEROFILL`; SQLSTATE: `HY000`

Message: The ZEROFILL attribute is deprecated and will be removed in a future release. Use the LPAD function to zero-pad numbers, or store the formatted numbers in a CHAR column.

`ER_WARN_DEPRECATED_ZEROFILL` was added in 8.0.17.

- Error number: `3862`; Symbol: `ER_CLONE_DONOR`; SQLSTATE: `HY000`

Message: Clone Donor Error: %s.

`ER_CLONE_DONOR` was added in 8.0.17.

- Error number: `3863`; Symbol: `ER_CLONE_PROTOCOL`; SQLSTATE: `HY000`

Message: Clone received unexpected response from Donor : %s.

`ER_CLONE_PROTOCOL` was added in 8.0.17.

- Error number: `3864`; Symbol: `ER_CLONE_DONOR_VERSION`; SQLSTATE: `HY000`

Message: Clone Donor MySQL version: %s is different from Recipient MySQL version %s.

`ER_CLONE_DONOR_VERSION` was added in 8.0.17.

- Error number: `3865`; Symbol: `ER_CLONE_OS`; SQLSTATE: `HY000`

Message: Clone Donor OS: %s is different from Recipient OS: %s.

`ER_CLONE_OS` was added in 8.0.17.

- Error number: `3866`; Symbol: `ER_CLONE_PLATFORM`; SQLSTATE: `HY000`

Message: Clone Donor platform: %s is different from Recipient platform: %s.

`ER_CLONE_PLATFORM` was added in 8.0.17.

- Error number: `3867`; Symbol: `ER_CLONE_CHARSET`; SQLSTATE: `HY000`

Message: Clone Donor collation: %s is unavailable in Recipient.

`ER_CLONE_CHARSET` was added in 8.0.17.

- Error number: `3868`; Symbol: `ER_CLONE_CONFIG`; SQLSTATE: `HY000`

Message: Clone Configuration %s: Donor value: %s is different from Recipient value: %s.

`ER_CLONE_CONFIG` was added in 8.0.17.

- Error number: `3869`; Symbol: `ER_CLONE_SYS_CONFIG`; SQLSTATE: `HY000`

Message: Clone system configuration: %s

`ER_CLONE_SYS_CONFIG` was added in 8.0.17.

- Error number: `3870`; Symbol: `ER_CLONE_PLUGIN_MATCH`; SQLSTATE: `HY000`

Message: Clone Donor plugin %s is not active in Recipient.

`ER_CLONE_PLUGIN_MATCH` was added in 8.0.17.

- Error number: `3871`; Symbol: `ER_CLONE_LOOPBACK`; SQLSTATE: `HY000`

Message: Clone cannot use loop back connection while cloning into current data directory.

`ER_CLONE_LOOPBACK` was added in 8.0.17.

- Error number: 3872; Symbol: `ER_CLONE_ENCRYPTION`; SQLSTATE: `HY000`

Message: Clone needs SSL connection for encrypted table.

`ER_CLONE_ENCRYPTION` was added in 8.0.17.

- Error number: 3873; Symbol: `ER_CLONE_DISK_SPACE`; SQLSTATE: `HY000`

Message: Clone estimated database size is %s. Available space %s is not enough.

`ER_CLONE_DISK_SPACE` was added in 8.0.17.

- Error number: 3874; Symbol: `ER_CLONE_IN_PROGRESS`; SQLSTATE: `HY000`

Message: Concurrent clone in progress. Please try after clone is complete.

`ER_CLONE_IN_PROGRESS` was added in 8.0.17.

- Error number: 3875; Symbol: `ER_CLONE_DISALLOWED`; SQLSTATE: `HY000`

Message: The clone operation cannot be executed when %s.

`ER_CLONE_DISALLOWED` was added in 8.0.17.

- Error number: 3876; Symbol: `ER_CANNOT_GRANT_ROLES_TO_ANONYMOUS_USER`; SQLSTATE: `HY000`

Message: Cannot grant roles to an anonymous user.

`ER_CANNOT_GRANT_ROLES_TO_ANONYMOUS_USER` was added in 8.0.16.

- Error number: 3877; Symbol: `ER_SECONDARY_ENGINE_PLUGIN`; SQLSTATE: `HY000`

Message: %s

`ER_SECONDARY_ENGINE_PLUGIN` was added in 8.0.14.

- Error number: 3878; Symbol: `ER_SECOND_PASSWORD_CANNOT_BE_EMPTY`; SQLSTATE: `HY000`

Message: Empty password can not be retained as second password for user '%s'@'%s'.

`ER_SECOND_PASSWORD_CANNOT_BE_EMPTY` was added in 8.0.14.

- Error number: 3879; Symbol: `ER_DB_ACCESS_DENIED`; SQLSTATE: `HY000`

Message: Access denied for AuthId `'%s`@`'%s` to database '%s'.

`ER_DB_ACCESS_DENIED` was added in 8.0.16.

- Error number: 3880; Symbol:

`ER_DA_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES`; SQLSTATE: `HY000`

Message: Cannot set mandatory_roles: AuthId `'%s`@`'%s` has '%s' privilege.

`ER_DA_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES` was added in 8.0.17.

- Error number: 3881; Symbol: `ER_DA_RPL_GTID_TABLE_CANNOT_OPEN`; SQLSTATE: `HY000`

Message: Gtid table is not ready to be used. Table '%s.%s' cannot be opened.

`ER_DA_RPL_GTID_TABLE_CANNOT_OPEN` was added in 8.0.17.

- Error number: 3882; Symbol: `ER_GEOMETRY_IN_UNKNOWN_LENGTH_UNIT`; SQLSTATE: `SU001`

Message: The geometry passed to function '%s' is in SRID 0, which doesn't specify a length unit. Can't convert to '%s'.

`ER_GEOMETRY_IN_UNKNOWN_LENGTH_UNIT` was added in 8.0.14.

- Error number: 3883; Symbol: `ER_DA_PLUGIN_INSTALL_ERROR`; SQLSTATE: `HY000`

Message: Error installing plugin '%s': %s

`ER_DA_PLUGIN_INSTALL_ERROR` was added in 8.0.17.

- Error number: 3884; Symbol: `ER_NO_SESSION_TEMP`; SQLSTATE: `HY000`

Message: Storage engine could not allocate temporary tablespace for this session.

`ER_NO_SESSION_TEMP` was added in 8.0.13.

- Error number: 3885; Symbol: `ER_DA_UNKNOWN_ERROR_NUMBER`; SQLSTATE: `HY000`

Message: Got unknown error: %d

`ER_DA_UNKNOWN_ERROR_NUMBER` was added in 8.0.17.

- Error number: 3886; Symbol: `ER_COLUMN_CHANGE_SIZE`; SQLSTATE: `HY000`

Message: Could not change column '%s' of table '%s'. The resulting size of index '%s' would exceed the max key length of %d bytes.

`ER_COLUMN_CHANGE_SIZE` was added in 8.0.14.

- Error number: 3887; Symbol: `ER_REGEXP_INVALID_CAPTURE_GROUP_NAME`; SQLSTATE: `HY000`

Message: A capture group has an invalid name.

`ER_REGEXP_INVALID_CAPTURE_GROUP_NAME` was added in 8.0.11.

- Error number: 3888; Symbol: `ER_DA_SSL_LIBRARY_ERROR`; SQLSTATE: `HY000`

Message: Failed to set up SSL because of the following SSL library error: %s

`ER_DA_SSL_LIBRARY_ERROR` was added in 8.0.17.

- Error number: 3889; Symbol: `ER_SECONDARY_ENGINE`; SQLSTATE: `HY000`

Message: Secondary engine operation failed. %s.

`ER_SECONDARY_ENGINE` was added in 8.0.13.

- Error number: 3890; Symbol: `ER_SECONDARY_ENGINE_DDL`; SQLSTATE: `HY000`

Message: DDLs on a table with a secondary engine defined are not allowed.

`ER_SECONDARY_ENGINE_DDL` was added in 8.0.13.

- Error number: 3891; Symbol: `ER_INCORRECT_CURRENT_PASSWORD`; SQLSTATE: `HY000`

Message: Incorrect current password. Specify the correct password which has to be replaced.

`ER_INCORRECT_CURRENT_PASSWORD` was added in 8.0.13.

- Error number: 3892; Symbol: `ER_MISSING_CURRENT_PASSWORD`; SQLSTATE: `HY000`

Message: Current password needs to be specified in the REPLACE clause in order to change it.
`ER_MISSING_CURRENT_PASSWORD` was added in 8.0.13.
- Error number: 3893; Symbol: `ER_CURRENT_PASSWORD_NOT_REQUIRED`; SQLSTATE: `HY000`

Message: Do not specify the current password while changing it for other users.
`ER_CURRENT_PASSWORD_NOT_REQUIRED` was added in 8.0.13.
- Error number: 3894; Symbol: `ER_PASSWORD_CANNOT_BE_RETAINED_ON_PLUGIN_CHANGE`; SQLSTATE: `HY000`

Message: Current password can not be retained for user '%s'@'%s' because authentication plugin is being changed.
`ER_PASSWORD_CANNOT_BE_RETAINED_ON_PLUGIN_CHANGE` was added in 8.0.14.
- Error number: 3895; Symbol: `ER_CURRENT_PASSWORD_CANNOT_BE_RETAINED`; SQLSTATE: `HY000`

Message: Current password can not be retained for user '%s'@'%s' because new password is empty.
`ER_CURRENT_PASSWORD_CANNOT_BE_RETAINED` was added in 8.0.14.
- Error number: 3896; Symbol: `ER_PARTIAL_REVOKES_EXIST`; SQLSTATE: `HY000`

Message: At least one partial revoke exists on a database. The system variable '@@partial_revokes' must be set to ON.
`ER_PARTIAL_REVOKES_EXIST` was added in 8.0.16.
- Error number: 3897; Symbol: `ER_CANNOT_GRANT_SYSTEM_PRIV_TO_MANDATORY_ROLE`; SQLSTATE: `HY000`

Message: AuthId `'%s` @ `'%s` is set as mandatory_roles. Cannot grant the '%s' privilege.
`ER_CANNOT_GRANT_SYSTEM_PRIV_TO_MANDATORY_ROLE` was added in 8.0.16.
- Error number: 3898; Symbol: `ER_XA_REPLICATION_FILTERS`; SQLSTATE: `HY000`

Message: The use of replication filters with XA transactions is not supported, and can lead to an undefined state in the replication slave.
`ER_XA_REPLICATION_FILTERS` was added in 8.0.12.
- Error number: 3899; Symbol: `ER_UNSUPPORTED_SQL_MODE`; SQLSTATE: `HY000`

Message: sql_mode=0x%08x is not supported.
`ER_UNSUPPORTED_SQL_MODE` was added in 8.0.11.
- Error number: 3900; Symbol: `ER_REGEXP_INVALID_FLAG`; SQLSTATE: `HY000`

Message: Invalid match mode flag in regular expression.
`ER_REGEXP_INVALID_FLAG` was added in 8.0.12.
- Error number: 3901; Symbol: `ER_PARTIAL_REVOCES_EXIST`; SQLSTATE: `HY000`

Message: '%s' privilege for database '%s' exists both as partial revoke and mysql.db simultaneously.
It could mean that the 'mysql' schema is corrupted.

[ER_PARTIAL_REVOKES_AND_DB_GRANT_BOTH_EXISTS](#) was added in 8.0.16.

- Error number: [3902](#); Symbol: [ER_UNIT_NOT_FOUND](#); SQLSTATE: [SU001](#)

Message: There's no unit of measure named '%s'.

[ER_UNIT_NOT_FOUND](#) was added in 8.0.14.

- Error number: [3903](#); Symbol: [ER_INVALID_JSON_VALUE_FOR_FUNC_INDEX](#); SQLSTATE: [22018](#)

Message: Invalid JSON value for CAST for functional index '%s'.

[ER_INVALID_JSON_VALUE_FOR_FUNC_INDEX](#) was added in 8.0.16.

- Error number: [3904](#); Symbol: [ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX](#); SQLSTATE: [22003](#)

Message: Out of range JSON value for CAST for functional index '%s'.

[ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX](#) was added in 8.0.16.

- Error number: [3905](#); Symbol: [ER_EXCEEDED_MV_KEYS_NUM](#); SQLSTATE: [HY000](#)

Message: Exceeded max number of values per record for multi-valued index '%s' by %u value(s).

[ER_EXCEEDED_MV_KEYS_NUM](#) was added in 8.0.16.

- Error number: [3906](#); Symbol: [ER_EXCEEDED_MV_KEYS_SPACE](#); SQLSTATE: [HY000](#)

Message: Exceeded max total length of values per record for multi-valued index '%s' by %u bytes.

[ER_EXCEEDED_MV_KEYS_SPACE](#) was added in 8.0.16.

- Error number: [3907](#); Symbol: [ER_FUNCTIONAL_INDEX_DATA_IS_TOO_LONG](#); SQLSTATE: [22001](#)

Message: Data too long for functional index '%s'.

[ER_FUNCTIONAL_INDEX_DATA_IS_TOO_LONG](#) was added in 8.0.16.

- Error number: [3908](#); Symbol: [ER_WRONG_MVI_VALUE](#); SQLSTATE: [HY000](#)

Message: Cannot store an array or an object in a scalar key part of the index '%s'.

[ER_WRONG_MVI_VALUE](#) was added in 8.0.16.

- Error number: [3909](#); Symbol: [ER_WARN_FUNC_INDEX_NOT_APPLICABLE](#); SQLSTATE: [HY000](#)

Message: Cannot use functional index '%s' due to type or collation conversion.

[ER_WARN_FUNC_INDEX_NOT_APPLICABLE](#) was added in 8.0.16.

- Error number: [3910](#); Symbol: [ER_GRP_RPL_UDF_ERROR](#); SQLSTATE: [HY000](#)

Message: The function '%s' failed. %s

[ER_GRP_RPL_UDF_ERROR](#) was added in 8.0.13.

- Error number: [3911](#); Symbol: [ER_UPDATE_GTID_PURGED_WITH_GR](#); SQLSTATE: [HY000](#)

Message: Cannot update GTID_PURGED with the Group Replication plugin running

`ER_UPDATE_GTID_PURGED_WITH_GR` was added in 8.0.12.

- Error number: 3912; Symbol: `ER_GROUPING_ON_TIMESTAMP_IN_DST`; SQLSTATE: `HY000`

Message: Grouping on temporal is non-deterministic for timezones having DST. Please consider switching to UTC for this query.

`ER_GROUPING_ON_TIMESTAMP_IN_DST` was added in 8.0.17.

- Error number: 3913; Symbol: `ER_TABLE_NAME_CAUSES_TOO_LONG_PATH`; SQLSTATE: `HY000`

Message: Long database name and identifier for object resulted in a path length too long for table '%s'. Please check the path limit for your OS.

`ER_TABLE_NAME_CAUSES_TOO_LONG_PATH` was added in 8.0.4.

- Error number: 3914; Symbol: `ER_AUDIT_LOG_INSUFFICIENT_PRIVILEGE`; SQLSTATE: `HY000`

Message: Request ignored for '%s'@'%s'. Role needed to perform operation: '%s'

`ER_AUDIT_LOG_INSUFFICIENT_PRIVILEGE` was added in 8.0.16.

- Error number: 3916; Symbol: `ER_DA_GRP_RPL_STARTED_AUTO_REJOIN`; SQLSTATE: `HY000`

Message: Started auto-rejoin procedure attempt %lu of %lu

`ER_DA_GRP_RPL_STARTED_AUTO_REJOIN` was added in 8.0.17.

- Error number: 3917; Symbol: `ER_SYSVAR_CHANGE_DURING_QUERY`; SQLSTATE: `HY000`

Message: A plugin was loaded or unloaded during a query, a system variable table was changed.

`ER_SYSVAR_CHANGE_DURING_QUERY` was added in 8.0.18.

- Error number: 3918; Symbol: `ER_GLOBSTAT_CHANGE_DURING_QUERY`; SQLSTATE: `HY000`

Message: A plugin was loaded or unloaded during a query, a global status variable was changed.

`ER_GLOBSTAT_CHANGE_DURING_QUERY` was added in 8.0.18.

- Error number: 3919; Symbol: `ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE`; SQLSTATE: `HY000`

Message: The START GROUP_REPLICATION command failed to start its message service.

`ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE` was added in 8.0.18.

- Error number: 3920; Symbol: `ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_CLIENT`; SQLSTATE: `HY000`

Message: Invalid MASTER_COMPRESSION_ALGORITHMS '%s' for channel '%s'.

`ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_CLIENT` was added in 8.0.18.

- Error number: 3921; Symbol: `ER_CHANGE_MASTER_WRONG_COMPRESSION_LEVEL_CLIENT`; SQLSTATE: `HY000`

Message: Invalid MASTER_ZSTD_COMPRESSION_LEVEL %u for channel '%s'.

`ER_CHANGE_MASTER_WRONG_COMPRESSION_LEVEL_CLIENT` was added in 8.0.18.

- Error number: 3922; Symbol: `ER_WRONG_COMPRESSION_ALGORITHM_CLIENT`; SQLSTATE: `HY000`

Message: Invalid compression algorithm '%s'.

`ER_WRONG_COMPRESSION_ALGORITHM_CLIENT` was added in 8.0.18.

- Error number: `3923`; Symbol: `ER_WRONG_COMPRESSION_LEVEL_CLIENT`; SQLSTATE: `HY000`

Message: Invalid zstd compression level for algorithm '%s'.

`ER_WRONG_COMPRESSION_LEVEL_CLIENT` was added in 8.0.18.

- Error number: `3924`; Symbol: `ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_LIST_CLIENT`; SQLSTATE: `HY000`

Message: Specified compression algorithm list '%s' exceeds total count of 3 for channel '%s'.

`ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_LIST_CLIENT` was added in 8.0.18.

- Error number: `3925`; Symbol: `ER_CLIENT_PRIVILEGE_CHECKS_USER_CANNOT_BE_ANONYMOUS`; SQLSTATE: `HY000`

Message: PRIVILEGE_CHECKS_USER for replication channel '%s' was set to ``@`%s`, but anonymous users are disallowed for PRIVILEGE_CHECKS_USER.

`ER_CLIENT_PRIVILEGE_CHECKS_USER_CANNOT_BE_ANONYMOUS` was added in 8.0.18.

- Error number: `3926`; Symbol: `ER_CLIENT_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST`; SQLSTATE: `HY000`

Message: PRIVILEGE_CHECKS_USER for replication channel '%s' was set to `%s`@`%s`, but this is not an existing user.

`ER_CLIENT_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST` was added in 8.0.18.

- Error number: `3927`; Symbol: `ER_CLIENT_PRIVILEGE_CHECKS_USER_CORRUPT`; SQLSTATE: `HY000`

Message: Invalid, corrupted PRIVILEGE_CHECKS_USER was found in the replication configuration repository for channel '%s'. Use CHANGE MASTER TO PRIVILEGE_CHECKS_USER to correct the configuration.

`ER_CLIENT_PRIVILEGE_CHECKS_USER_CORRUPT` was added in 8.0.18.

- Error number: `3928`; Symbol: `ER_CLIENT_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPLIER_PRIV`; SQLSTATE: `HY000`

Message: PRIVILEGE_CHECKS_USER for replication channel '%s' was set to `%s`@`%s`, but this user does not have REPLICATION_APPLIER privilege.

`ER_CLIENT_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPLIER_PRIV` was added in 8.0.18.

- Error number: `3929`; Symbol: `ER_WARN_DA_PRIVILEGE_NOT_REGISTERED`; SQLSTATE: `HY000`

Message: Dynamic privilege '%s' is not registered with the server.

`ER_WARN_DA_PRIVILEGE_NOT_REGISTERED` was added in 8.0.18.

- Error number: `3930`; Symbol: `ER_CLIENT_KEYRING_UDF_KEY_INVALID`; SQLSTATE: `HY000`

Message: Function '%s' failed because key is invalid.

`ER_CLIENT_KEYRING_UDF_KEY_INVALID` was added in 8.0.19.

- Error number: 3931; Symbol: `ER_CLIENT_KEYRING_UDF_KEY_TYPE_INVALID`; SQLSTATE: HY000

Message: Function '%s' failed because key type is invalid.

`ER_CLIENT_KEYRING_UDF_KEY_TYPE_INVALID` was added in 8.0.19.

- Error number: 3932; Symbol: `ER_CLIENT_KEYRING_UDF_KEY_TOO_LONG`; SQLSTATE: HY000

Message: Function '%s' failed because key length is too long.

`ER_CLIENT_KEYRING_UDF_KEY_TOO_LONG` was added in 8.0.19.

- Error number: 3933; Symbol: `ER_CLIENT_KEYRING_UDF_KEY_TYPE_TOO_LONG`; SQLSTATE: HY000

Message: Function '%s' failed because key type is too long.

`ER_CLIENT_KEYRING_UDF_KEY_TYPE_TOO_LONG` was added in 8.0.19.

- Error number: 3934; Symbol:

`ER_JSON_SCHEMA_VALIDATION_ERROR_WITH_DETAILED_REPORT`; SQLSTATE: HY000

Message: %s.

`ER_JSON_SCHEMA_VALIDATION_ERROR_WITH_DETAILED_REPORT` was added in 8.0.19.

- Error number: 3935; Symbol: `ER_DA_UDF_INVALID_CHARSET_SPECIFIED`; SQLSTATE: HY000

Message: Invalid character set '%s' was specified. It must be either character set name or collation name as supported by server.

`ER_DA_UDF_INVALID_CHARSET_SPECIFIED` was added in 8.0.19.

- Error number: 3936; Symbol: `ER_DA_UDF_INVALID_CHARSET`; SQLSTATE: HY000

Message: Invalid character set '%s' was specified. It must be a character set name as supported by server.

`ER_DA_UDF_INVALID_CHARSET` was added in 8.0.19.

- Error number: 3937; Symbol: `ER_DA_UDF_INVALID_COLLATION`; SQLSTATE: HY000

Message: Invalid collation '%s' was specified. It must be a collation name as supported by server.

`ER_DA_UDF_INVALID_COLLATION` was added in 8.0.19.

- Error number: 3938; Symbol: `ER_DA_UDF_INVALID_EXTENSION_ARGUMENT_TYPE`; SQLSTATE: HY000

Message: Invalid extension argument type '%s' was specified. Refer the MySQL manual for the valid UDF extension arguments type.

`ER_DA_UDF_INVALID_EXTENSION_ARGUMENT_TYPE` was added in 8.0.19.

- Error number: 3939; Symbol: `ER_MULTIPLE_CONSTRAINTS_WITH_SAME_NAME`; SQLSTATE: HY000

Message: Table has multiple constraints with the name '%s'. Please use constraint specific '%s' clause.

`ER_MULTIPLE_CONSTRAINTS_WITH_SAME_NAME` was added in 8.0.19.

- Error number: 3940; Symbol: `ER_CONSTRAINT_NOT_FOUND`; SQLSTATE: HY000

Message: Constraint '%s' does not exist.

`ER_CONSTRAINT_NOT_FOUND` was added in 8.0.19.

- Error number: 3941; Symbol: `ER.Alter.Constraint.Enforcement.NotSupported`; SQLSTATE: `HY000`

Message: Altering constraint enforcement is not supported for the constraint '%s'. Enforcement state alter is not supported for the PRIMARY, UNIQUE and FOREIGN KEY type constraints.

`ER.Alter.Constraint.Enforcement.NotSupported` was added in 8.0.19.

- Error number: 3942; Symbol: `ER.Table.Value.Constructor.MustHaveColumns`; SQLSTATE: `HY000`

Message: Each row of a VALUES clause must have at least one column, unless when used as source in an INSERT statement.

`ER.Table.Value.Constructor.MustHaveColumns` was added in 8.0.19.

- Error number: 3943; Symbol: `ER.Table.Value.Constructor.CannotHaveDefault`; SQLSTATE: `HY000`

Message: A VALUES clause cannot use DEFAULT values, unless used as a source in an INSERT statement.

`ER.Table.Value.Constructor.CannotHaveDefault` was added in 8.0.19.

- Error number: 3944; Symbol: `ER.Client.Query.Failure.InvalidNonRowFormat`; SQLSTATE: `HY000`

Message: The query does not comply with variable require_row_format restrictions.

`ER.Client.Query.Failure.InvalidNonRowFormat` was added in 8.0.19.

- Error number: 3945; Symbol: `ER.Require.RowFormat.InvalidValue`; SQLSTATE: `HY000`

Message: The requested value %s is invalid for REQUIRE_ROW_FORMAT, must be either 0 or 1.

`ER.Require.RowFormat.InvalidValue` was added in 8.0.19.

- Error number: 3946; Symbol: `ER.Failed.To.Determine.If.Role.Is.Mandatory`; SQLSTATE: `HY000`

Message: Failed to acquire lock on user management service, unable to determine if role `%'@`%s` is mandatory

`ER.Failed.To.Determine.If.Role.Is.Mandatory` was added in 8.0.19.

- Error number: 3947; Symbol: `ER.Failed.To.Fetch.Mandatory.Role.List`; SQLSTATE: `HY000`

Message: Failed to acquire lock on user management service, unable to fetch mandatory role list

`ER.Failed.To.Fetch.Mandatory.Role.List` was added in 8.0.19.

- Error number: 3948; Symbol: `ER.Client.Local.Files.Disabled`; SQLSTATE: `42000`

Message: Loading local data is disabled; this must be enabled on both the client and server sides

`ER.Client.Local.Files.Disabled` was added in 8.0.19.

- Error number: 3949; Symbol: `ER.Imp.Incompatible.Cfg.Version`; SQLSTATE: `HY000`

Message: Failed to import %s because the CFG file version (%u) is not compatible with the current version (%u)

`ER_IMP_INCOMPATIBLE_CFG_VERSION` was added in 8.0.19.

- Error number: 3950; Symbol: `ER_DA_OOM`; SQLSTATE: `HY000`

Message: Out of memory

`ER_DA_OOM` was added in 8.0.19.

- Error number: 3951; Symbol: `ER_DA_UDF_INVALID_ARGUMENT_TO_SET_CHARSET`; SQLSTATE: `HY000`

Message: Character set can be set only for the UDF argument type STRING.

`ER_DA_UDF_INVALID_ARGUMENT_TO_SET_CHARSET` was added in 8.0.19.

- Error number: 3952; Symbol: `ER_DA_UDF_INVALID_RETURN_TYPE_TO_SET_CHARSET`; SQLSTATE: `HY000`

Message: Character set can be set only for the UDF RETURN type STRING.

`ER_DA_UDF_INVALID_RETURN_TYPE_TO_SET_CHARSET` was added in 8.0.19.

- Error number: 3953; Symbol: `ER_MULTIPLE_INTO_CLAUSES`; SQLSTATE: `HY000`

Message: Multiple INTO clauses in one query block.

`ER_MULTIPLE_INTO_CLAUSES` was added in 8.0.19.

- Error number: 3954; Symbol: `ER_MISPLACED_INTO`; SQLSTATE: `HY000`

Message: Misplaced INTO clause, INTO is not allowed inside subqueries, and must be placed at end of UNION clauses.

`ER_MISPLACED_INTO` was added in 8.0.19.

- Error number: 3955; Symbol:

`ER_USER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY_PASSWORD_LOCK`; SQLSTATE: `HY000`

Message: Access denied for user '%s'@'%s'. Account is blocked for %s day(s) (%s day(s) remaining) due to %u consecutive failed logins.

`ER_USER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY_PASSWORD_LOCK` was added in 8.0.19.

- Error number: 3956; Symbol: `ER_WARN_DEPRECATED_YEAR_UNSIGNED`; SQLSTATE: `HY000`

Message: UNSIGNED for the YEAR data type is deprecated and support for it will be removed in a future release.

`ER_WARN_DEPRECATED_YEAR_UNSIGNED` was added in 8.0.19.

- Error number: 3957; Symbol: `ER_CLONE_NETWORK_PACKET`; SQLSTATE: `HY000`

Message: Clone needs max_allowed_packet value to be %u or more. Current value is %u

`ER_CLONE_NETWORK_PACKET` was added in 8.0.19.

- Error number: 3958; Symbol: `ER_SDI_OPERATION_FAILED_MISSING_RECORD`; SQLSTATE: `HY000`

Message: Failed to %s sdi for %s.%s in %s due to missing record.

[ER_SDI_OPERATION_FAILED_MISSING_RECORD](#) was added in 8.0.19.

- Error number: [3959](#); Symbol: [ER_DEPENDENT_BY_CHECK_CONSTRAINT](#); SQLSTATE: [HY000](#)

Message: Check constraint '%s' uses column '%s', hence column cannot be dropped or renamed.

[ER_DEPENDENT_BY_CHECK_CONSTRAINT](#) was added in 8.0.19.

- Error number: [3960](#); Symbol: [ER_GRP_OPERATION_NOT_ALLOWED_GR_MUST_STOP](#); SQLSTATE: [HY000](#)

Message: This operation cannot be performed while Group Replication is running; run STOP GROUP_REPLICATION first

[ER_GRP_OPERATION_NOT_ALLOWED_GR_MUST_STOP](#) was added in 8.0.20.

- Error number: [3961](#); Symbol: [ER_WARN_DEPRECATED_JSON_TABLE_ON_ERROR_ON_EMPTY](#); SQLSTATE: [HY000](#)

Message: Specifying an ON EMPTY clause after the ON ERROR clause in a JSON_TABLE column definition is deprecated syntax and will be removed in a future release. Specify ON EMPTY before ON ERROR instead.

[ER_WARN_DEPRECATED_JSON_TABLE_ON_ERROR_ON_EMPTY](#) was added in 8.0.20.

- Error number: [3962](#); Symbol: [ER_WARN_DEPRECATED_INNER_INTO](#); SQLSTATE: [HY000](#)

Message: The INTO clause is deprecated inside query blocks of query expressions and will be removed in a future release. Please move the INTO clause to the end of statement instead.

[ER_WARN_DEPRECATED_INNER_INTO](#) was added in 8.0.20.

- Error number: [3963](#); Symbol: [ER_WARN_DEPRECATED_VALUES_FUNCTION_ALWAYS_NULL](#); SQLSTATE: [HY000](#)

Message: The VALUES function is deprecated and will be removed in a future release. It always returns NULL in this context. If you meant to access a value from the VALUES clause of the INSERT statement, consider using an alias (INSERT INTO ... VALUES (...) AS alias) and reference alias.col instead of VALUES(col) in the ON DUPLICATE KEY UPDATE clause.

[ER_WARN_DEPRECATED_VALUES_FUNCTION_ALWAYS_NULL](#) was added in 8.0.20.

- Error number: [3964](#); Symbol: [ER_WARN_DEPRECATED_SQL_CALC_FOUND_ROWS](#); SQLSTATE: [HY000](#)

Message: SQL_CALC_FOUND_ROWS is deprecated and will be removed in a future release. Consider using two separate queries instead.

[ER_WARN_DEPRECATED_SQL_CALC_FOUND_ROWS](#) was added in 8.0.16.

- Error number: [3965](#); Symbol: [ER_WARN_DEPRECATED_FOUND_ROWS](#); SQLSTATE: [HY000](#)

Message: FOUND_ROWS() is deprecated and will be removed in a future release. Consider using COUNT(*) instead.

[ER_WARN_DEPRECATED_FOUND_ROWS](#) was added in 8.0.16.

- Error number: [3966](#); Symbol: [ER_MISSING_JSON_VALUE](#); SQLSTATE: [22035](#)

Message: No value was found by '%s' on the specified path.

`ER_MISSING_JSON_VALUE` was added in 8.0.21.

- Error number: [3967](#); Symbol: `ER_MULTIPLE_JSON_VALUES`; SQLSTATE: [22034](#)

Message: More than one value was found by '%s' on the specified path.

`ER_MULTIPLE_JSON_VALUES` was added in 8.0.21.

- Error number: [3968](#); Symbol: `ER_HOSTNAME_TOO_LONG`; SQLSTATE: [HY000](#)

Message: Hostname cannot be longer than %d characters.

`ER_HOSTNAME_TOO_LONG` was added in 8.0.21.

- Error number: [3969](#); Symbol: `ER_WARN_CLIENT_DEPRECATED_PARTITION_PREFIX_KEY`; SQLSTATE: [HY000](#)

Message: Column '%s.%s.%s' having prefix key part '%s(%u)' is ignored by the partitioning function. Use of prefixed columns in the PARTITION BY KEY() clause is deprecated and will be removed in a future release.

`ER_WARN_CLIENT_DEPRECATED_PARTITION_PREFIX_KEY` was added in 8.0.21.

- Error number: [3970](#); Symbol: `ER_GROUP_REPLICATION_USER_EMPTY_MSG`; SQLSTATE: [HY000](#)

Message: The START GROUP_REPLICATION command failed since the username provided for recovery channel is empty.

`ER_GROUP_REPLICATION_USER_EMPTY_MSG` was added in 8.0.21.

- Error number: [3971](#); Symbol: `ER_GROUP_REPLICATION_USER_MANDATORY_MSG`; SQLSTATE: [HY000](#)

Message: The START GROUP_REPLICATION command failed since the USER option was not provided with PASSWORD for recovery channel.

`ER_GROUP_REPLICATION_USER_MANDATORY_MSG` was added in 8.0.21.

- Error number: [3972](#); Symbol: `ER_GROUP_REPLICATION_PASSWORD_LENGTH`; SQLSTATE: [HY000](#)

Message: The START GROUP_REPLICATION command failed since the password provided for the recovery channel exceeds the maximum length of 32 characters.

`ER_GROUP_REPLICATION_PASSWORD_LENGTH` was added in 8.0.21.

- Error number: [3973](#); Symbol: `ER_SUBQUERY_TRANSFORM_REJECTED`; SQLSTATE: [HY000](#)

Message: Statement requires a transform of a subquery to a non-SET operation (like IN2EXISTS, or subquery-to-LATERAL-derived-table). This is not allowed with optimizer switch 'subquery_to_derived' on

`ER_SUBQUERY_TRANSFORM_REJECTED` was added in 8.0.21.

- Error number: [3974](#); Symbol: `ER_DA_GRP_RPL_RECOVERY_ENDPOINT_FORMAT`; SQLSTATE: [HY000](#)

Message: Invalid input value for recovery socket endpoints '%s'. Please, provide a valid, comma separated, list of endpoints (IP:port)

`ER_DA_GRP_RPL_RECOVERY_ENDPOINT_FORMAT` was added in 8.0.21.

-
- Error number: 3975; Symbol: `ER_DA_GRP_RPL_RECOVERY_ENDPOINT_INVALID`; SQLSTATE: `HY000`

Message: The server is not listening on endpoint '%s'. Only endpoints that the server is listening on are valid recovery endpoints.

`ER_DA_GRP_RPL_RECOVERY_ENDPOINT_INVALID` was added in 8.0.21.

- Error number: 3976; Symbol: `ER_WRONG_VALUE_FOR_VAR_PLUS_ACTIONABLE_PART`; SQLSTATE: `HY000`

Message: Variable '%s' cannot be set to the value of '%s'. %s

`ER_WRONG_VALUE_FOR_VAR_PLUS_ACTIONABLE_PART` was added in 8.0.21.

- Error number: 3977; Symbol: `ER_STATEMENT_NOT_ALLOWED_AFTER_START_TRANSACTION`; SQLSTATE: `HY000`

Message: Only BINLOG INSERT, COMMIT and ROLLBACK statements are allowed after CREATE TABLE with START TRANSACTION statement.

`ER_STATEMENT_NOT_ALLOWED_AFTER_START_TRANSACTION` was added in 8.0.21.

- Error number: 3978; Symbol: `ER_FOREIGN_KEY_WITH_ATOMIC_CREATE_SELECT`; SQLSTATE: `HY000`

Message: Foreign key creation is not allowed with CREATE TABLE as SELECT and CREATE TABLE with START TRANSACTION statement.

`ER_FOREIGN_KEY_WITH_ATOMIC_CREATE_SELECT` was added in 8.0.21.

- Error number: 3979; Symbol: `ER_NOT_ALLOWED_WITH_START_TRANSACTION`; SQLSTATE: `HY000`

Message: START TRANSACTION clause cannot be used %s

`ER_NOT_ALLOWED_WITH_START_TRANSACTION` was added in 8.0.21.

- Error number: 3980; Symbol: `ER_INVALID_JSON_ATTRIBUTE`; SQLSTATE: `HY000`

Message: Invalid json attribute, error: "%s" at pos %u: '%s'

`ER_INVALID_JSON_ATTRIBUTE` was added in 8.0.21.

- Error number: 3981; Symbol: `ER_ENGINE_ATTRIBUTE_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Storage engine '%s' does not support ENGINE_ATTRIBUTE.

`ER_ENGINE_ATTRIBUTE_NOT_SUPPORTED` was added in 8.0.21.

- Error number: 3982; Symbol: `ER_INVALID_USER_ATTRIBUTE_JSON`; SQLSTATE: `HY000`

Message: The user attribute must be a valid JSON object

`ER_INVALID_USER_ATTRIBUTE_JSON` was added in 8.0.21.

- Error number: 3983; Symbol: `ER_INNODB_REDO_DISABLED`; SQLSTATE: `HY000`

Message: Cannot perform operation as InnoDB redo logging is disabled. Please retry after enabling redo log with ALTER INSTANCE

`ER_INNODB_REDO_DISABLED` was added in 8.0.21.

- Error number: 3984; Symbol: `ER_INNODB_REDO_ARCHIVING_ENABLED`; SQLSTATE: `HY000`

Message: Cannot perform operation as InnoDB is archiving redo log. Please retry after stopping redo archive by invoking innodb_redo_log_archive_stop()

`ER_INNODB_REDO_ARCHIVING_ENABLED` was added in 8.0.21.

- Error number: 3985; Symbol: `ER_MDL_OUT_OF_RESOURCES`; SQLSTATE: `HY000`

Message: Not enough resources to complete lock request.

`ER_MDL_OUT_OF_RESOURCES` was added in 8.0.21.

- Error number: 3986; Symbol: `ER_IMPLICIT_COMPARISON_FOR_JSON`; SQLSTATE: `HY000`

Message: Evaluating a JSON value in SQL boolean context does an implicit comparison against JSON integer 0; if this is not what you want, consider converting JSON to a SQL numeric type with `JSON_VALUE RETURNING`

`ER_IMPLICIT_COMPARISON_FOR_JSON` was added in 8.0.21.

- Error number: 3987; Symbol: `ER_FUNCTION_DOES_NOT_SUPPORT_CHARACTER_SET`; SQLSTATE: `HY000`

Message: The function '%s' does not support the character set '%s'.

`ER_FUNCTION_DOES_NOT_SUPPORT_CHARACTER_SET` was added in 8.0.21.

- Error number: 3988; Symbol: `ER_IMPOSSIBLE_STRING_CONVERSION`; SQLSTATE: `HY000`

Message: Conversion from collation %s into %s impossible for %s

`ER_IMPOSSIBLE_STRING_CONVERSION` was added in 8.0.22.

- Error number: 3989; Symbol: `ER_SCHEMA_READ_ONLY`; SQLSTATE: `HY000`

Message: Schema '%s' is in read only mode.

`ER_SCHEMA_READ_ONLY` was added in 8.0.22.

- Error number: 3990; Symbol: `ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF`; SQLSTATE: `HY000`

Message: Failed to enable Asynchronous Replication Connection Failover feature. The `CHANGE MASTER TO SOURCE_CONNECTION_AUTO_FAILOVER = 1` can only be set when `@@GLOBAL.GTID_MODE = ON`.

`ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF` was added in 8.0.22.

- Error number: 3991; Symbol: `ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFF`; SQLSTATE: `HY000`

Message: Failed to enable Asynchronous Replication Connection Failover feature. The `CHANGE MASTER TO SOURCE_CONNECTION_AUTO_FAILOVER = 1` can only be set when `MASTER_AUTO_POSITION` option of `CHANGE MASTER TO` is enabled.

`ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFF` was added in 8.0.22.

-
- Error number: [3992](#); Symbol: [ER_DISABLE_GTID_MODE_REQUIRES_ASYNC_RECONNECT_OFF](#); SQLSTATE: [HY000](#)

Message: The @@GLOBAL.GTID_MODE = %s cannot be executed because Asynchronous Replication Connection Failover is enabled i.e. CHANGE MASTER TO SOURCE_CONNECTION_AUTO_FAILOVER = 1.

[ER_DISABLE_GTID_MODE_REQUIRES_ASYNC_RECONNECT_OFF](#) was added in 8.0.22.

- Error number: [3993](#); Symbol: [ER_DISABLE_AUTO_POSITION_REQUIRES_ASYNC_RECONNECT_OFF](#); SQLSTATE: [HY000](#)

Message: CHANGE MASTER TO MASTER_AUTO_POSITION = 0 cannot be executed because Asynchronous Replication Connection Failover is enabled i.e. CHANGE MASTER TO SOURCE_CONNECTION_AUTO_FAILOVER = 1.

[ER_DISABLE_AUTO_POSITION_REQUIRES_ASYNC_RECONNECT_OFF](#) was added in 8.0.22.

- Error number: [3994](#); Symbol: [ER_INVALID_PARAMETER_USE](#); SQLSTATE: [HY000](#)

Message: Invalid use of parameters in '%s'

[ER_INVALID_PARAMETER_USE](#) was added in 8.0.22.

- Error number: [3995](#); Symbol: [ER_CHARACTER_SET_MISMATCH](#); SQLSTATE: [HY000](#)

Message: Character set '%s' cannot be used in conjunction with '%s' in call to %s.

[ER_CHARACTER_SET_MISMATCH](#) was added in 8.0.22.

- Error number: [3996](#); Symbol: [ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Changing %s not supported on this platform. Falling back to the default.

[ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED](#) was added in 8.0.22.

- Error number: [3997](#); Symbol: [ER_INVALID_TIME_ZONE_INTERVAL](#); SQLSTATE: [HY000](#)

Message: Invalid time zone interval: '%s'

[ER_INVALID_TIME_ZONE_INTERVAL](#) was added in 8.0.22.

- Error number: [3998](#); Symbol: [ER_INVALID_CAST](#); SQLSTATE: [HY000](#)

Message: Cannot cast value to %s.

[ER_INVALID_CAST](#) was added in 8.0.22.

- Error number: [3999](#); Symbol: [ER_HYPERGRAPH_NOT_SUPPORTED_YET](#); SQLSTATE: [42000](#)

Message: The hypergraph optimizer does not yet support '%s'

[ER_HYPERGRAPH_NOT_SUPPORTED_YET](#) was added in 8.0.22.

- Error number: [4000](#); Symbol: [ER_WARN_HYPERGRAPH_EXPERIMENTAL](#); SQLSTATE: [HY000](#)

Message: The hypergraph optimizer is highly experimental and is meant for testing only. Do not enable it unless you are a MySQL developer.

[ER_WARN_HYPERGRAPH_EXPERIMENTAL](#) was added in 8.0.22.

- Error number: [4001](#); Symbol: [ER_DA_NO_ERROR_LOG_PARSER_CONFIGURED](#); SQLSTATE: [HY000](#)

Message: None of the log-sinks selected with --log-error-services=... provides a log-parser. The server will not be able to make the previous runs' error-logs available in performance_schema.error_log.

[ER_DA_NO_ERROR_LOG_PARSER_CONFIGURED](#) was added in 8.0.22.

- Error number: [4002](#); Symbol: [ER_DA_ERROR_LOG_TABLE_DISABLED](#); SQLSTATE: [HY000](#)

Message: None of the log-sinks selected in @@global.log_error_services supports writing to the performance schema. The server will not be able to make the current runs' error events available in performance_schema.error_log. To change this, add a log-sink that supports the performance schema to @@global.log_error_services.

[ER_DA_ERROR_LOG_TABLE_DISABLED](#) was added in 8.0.22.

- Error number: [4003](#); Symbol: [ER_DA_ERROR_LOG_MULTIPLE_FILTERS](#); SQLSTATE: [HY000](#)

Message: @@global.log_error_services lists more than one log-filter service. This is discouraged as it will make it hard to understand which rule in which filter affected a log-event.

[ER_DA_ERROR_LOG_MULTIPLE_FILTERS](#) was added in 8.0.22.

- Error number: [4004](#); Symbol: [ER_DA_CANT_OPEN_ERROR_LOG](#); SQLSTATE: [HY000](#)

Message: Could not open file '%s' for error logging%
%

[ER_DA_CANT_OPEN_ERROR_LOG](#) was added in 8.0.22.

- Error number: [4005](#); Symbol: [ER_USER_REFERENCED_AS_DEFINER](#); SQLSTATE: [HY000](#)

Message: User %s is referenced as a definer account in %s.

[ER_USER_REFERENCED_AS_DEFINER](#) was added in 8.0.22.

- Error number: [4006](#); Symbol: [ER_CANNOT_USER_REFERENCED_AS_DEFINER](#); SQLSTATE: [HY000](#)

Message: Operation %s failed for %s as it is referenced as a definer account in %s.

[ER_CANNOT_USER_REFERENCED_AS_DEFINER](#) was added in 8.0.22.

- Error number: [4007](#); Symbol: [ER_REGEX_NUMBER_TOO_BIG](#); SQLSTATE: [HY000](#)

Message: Decimal number in regular expression is too large.

[ER_REGEX_NUMBER_TOO_BIG](#) was added in 8.0.22.

- Error number: [4008](#); Symbol: [ER_SPVAR_NONINTEGER_TYPE](#); SQLSTATE: [HY000](#)

Message: The variable "%s" has a non-integer based type

[ER_SPVAR_NONINTEGER_TYPE](#) was added in 8.0.22.

- Error number: [4009](#); Symbol: [WARN_UNSUPPORTED_ACL_TABLES_READ](#); SQLSTATE: [HY000](#)

Message: Reads with serializable isolation/SELECT FOR SHARE are not supported for ACL tables.

[WARN_UNSUPPORTED_ACL_TABLES_READ](#) was added in 8.0.22.

-
- Error number: [4010](#); Symbol: [ER_BINLOG_UNSAFE_ACL_TABLE_READ_IN_DML_DDL](#); SQLSTATE: [HY000](#)

Message: The statement is unsafe because it updates a table depending on ACL table read operation. As storage engine row locks are skipped for ACL table, it may not have same effect on master and slave.

[ER_BINLOG_UNSAFE_ACL_TABLE_READ_IN_DML_DDL](#) was added in 8.0.22.

- Error number: [4011](#); Symbol: [ER_STOP_REPLICA_MONITOR_IO_THREAD_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: STOP REPLICA command execution is incomplete: Replica Monitor thread got the stop signal, thread is busy, Monitor thread will stop once the current task is complete.

[ER_STOP_REPLICA_MONITOR_IO_THREAD_TIMEOUT](#) was added in 8.0.23.

- Error number: [4012](#); Symbol: [ER_STARTING_REPLICA_MONITOR_IO_THREAD](#); SQLSTATE: [HY000](#)

Message: The Replica Monitor thread failed to start.

[ER_STARTING_REPLICA_MONITOR_IO_THREAD](#) was added in 8.0.23.

- Error number: [4013](#); Symbol: [ER_CANT_USE_ANONYMOUS_TO_GTID_WITH_GTID_MODE_NOT_ON](#); SQLSTATE: [HY000](#)

Message: Replication cannot start%[s](#) with [ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>](#) as this server uses [@@GLOBAL.GTID_MODE <> ON](#).

[ER_CANT_USE_ANONYMOUS_TO_GTID_WITH_GTID_MODE_NOT_ON](#) was added in 8.0.23.

- Error number: [4014](#); Symbol: [ER_CANT_COMBINE_ANONYMOUS_TO_GTID_AND_AUTOPOSITION](#); SQLSTATE: [HY000](#)

Message: The options [ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>](#) and [MASTER_AUTO_POSITION = 1](#) cannot be used together.

[ER_CANT_COMBINE_ANONYMOUS_TO_GTID_AND_AUTOPOSITION](#) was added in 8.0.23.

- Error number: [4015](#); Symbol: [ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONSQUIRES_GTID_MODE_ON](#); SQLSTATE: [HY000](#)

Message: [CHANGE MASTER TO ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>](#) cannot be executed because [@@GLOBAL.GTID_MODE <> ON](#).

[ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONSQUIRES_GTID_MODE_ON](#) was added in 8.0.23.

- Error number: [4016](#); Symbol: [ER_SQL_SLAVE_SKIP_COUNTER_USED_WITH_GTID_MODE_ON](#); SQLSTATE: [HY000](#)

Message: The value of [sql_slave_skip_counter](#) will only take effect for channels running with [ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS <> OFF](#).

[ER_SQL_SLAVE_SKIP_COUNTER_USED_WITH_GTID_MODE_ON](#) was added in 8.0.23, removed after 8.0.25.

- Error number: [4016](#); Symbol: `ER_SQL_REPLICA_SKIP_COUNTER_USED_WITH_GTID_MODE_ON`; SQLSTATE: `HY000`

Message: The value of `sql_replica_skip_counter` will only take effect for channels running with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS <> OFF`.

`ER_SQL_REPLICA_SKIP_COUNTER_USED_WITH_GTID_MODE_ON` was added in 8.0.26.

- Error number: [4017](#); Symbol: `ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_AS_LOCAL_OR_UUID`; SQLSTATE: `HY000`

Message: Using `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS` creates limitations on the replication topology - you cannot fail over between downstream and upstream servers. Only use this option if it is not possible to enable GTIDs on the source, for instance, because of lack of permissions. If possible, use the procedure for enabling GTID transactions online instead, as described in the documentation.

`ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_AS_LOCAL_OR_UUID` was added in 8.0.23.

- Error number: [4018](#); Symbol: `ER_CANT_SET_ANONYMOUS_TO_GTID_AND_WAIT_UNTIL_SQL_THD_AFTER_GTIDS`; SQLSTATE: `HY000`

Message: `WAIT_UNTIL_SQL_THREAD_AFTER_GTIDS` cannot be used on a channel configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>`

`ER_CANT_SET_ANONYMOUS_TO_GTID_AND_WAIT_UNTIL_SQL_THD_AFTER_GTIDS` was added in 8.0.23.

- Error number: [4019](#); Symbol: `ER_CANT_SET_SQL_AFTER_OR_BEFORE_GTIDS_WITH_ANONYMOUS_TO_GTID`; SQLSTATE: `HY000`

Message: The `SQL_AFTER_GTIDS` or `SQL_BEFORE_GTIDS` clauses for `START REPLICA` cannot be used when the replication channel is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>`.

`ER_CANT_SET_SQL_AFTER_OR_BEFORE_GTIDS_WITH_ANONYMOUS_TO_GTID` was added in 8.0.23.

- Error number: [4020](#); Symbol: `ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME`; SQLSTATE: `HY000`

Message: Replication '`%s`' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = <UUID>` where the UUID value is equal to the `group_replication_group_name`

`ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME` was added in 8.0.23.

- Error number: [4021](#); Symbol: `ER_CANT_USE_SAME_UUID_AS_GROUP_NAME`; SQLSTATE: `HY000`

Message: `CHANGE MASTER TO ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = <UUID>` cannot be executed because the UUID value is equal to the `group_replication_group_name`.

`ER_CANT_USE_SAME_UUID_AS_GROUP_NAME` was added in 8.0.23.

-
- Error number: [4022](#); Symbol: [ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING](#); SQLSTATE: [HY000](#)

Message: The group_replication_recovery channel is still running, most likely it is waiting for a database/table lock, which is preventing the channel from stopping. Please check database/table locks, including the ones created by backup tools.

[ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING](#) was added in 8.0.23.

- Error number: [4023](#); Symbol: [ER_INNODB_INVALID_AUTOEXTEND_SIZE_VALUE](#); SQLSTATE: [HY000](#)

Message: AUTOEXTEND_SIZE should be a multiple of %uM

[ER_INNODB_INVALID_AUTOEXTEND_SIZE_VALUE](#) was added in 8.0.23.

- Error number: [4024](#); Symbol: [ER_INNODB_INCOMPATIBLE_WITH_TABLESPACE](#); SQLSTATE: [HY000](#)

Message: InnoDB: "%s" not allowed with general tablespaces

[ER_INNODB_INCOMPATIBLE_WITH_TABLESPACE](#) was added in 8.0.23.

- Error number: [4025](#); Symbol: [ER_INNODB_AUTOEXTEND_SIZE_OUT_OF_RANGE](#); SQLSTATE: [HY000](#)

Message: AUTOEXTEND_SIZE value should be between %uM and %uM

[ER_INNODB_AUTOEXTEND_SIZE_OUT_OF_RANGE](#) was added in 8.0.23.

- Error number: [4026](#); Symbol: [ER_CANNOT_USE_AUTOEXTEND_SIZE_CLAUSE](#); SQLSTATE: [HY000](#)

Message: AUTOEXTEND_SIZE clause is not valid for %s tablespace.

[ER_CANNOT_USE_AUTOEXTEND_SIZE_CLAUSE](#) was added in 8.0.23.

- Error number: [4027](#); Symbol: [ER_ROLE_GRANTED_TO_ITSELF](#); SQLSTATE: [HY000](#)

Message: User account %s is directly or indirectly granted to the role %s. The GRANT would create a loop

[ER_ROLE_GRANTED_TO_ITSELF](#) was added in 8.0.23.

- Error number: [4028](#); Symbol: [ER_TABLE_MUST_HAVE_A_VISIBLE_COLUMN](#); SQLSTATE: [HY000](#)

Message: A table must have at least one visible column.

[ER_TABLE_MUST_HAVE_A_VISIBLE_COLUMN](#) was added in 8.0.23.

- Error number: [4029](#); Symbol: [ER_INNODB_COMPRESSION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Compression failed with the following error : %s

[ER_INNODB_COMPRESSION_FAILURE](#) was added in 8.0.23.

- Error number: [4030](#); Symbol: [ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAMESPACE](#); SQLSTATE: [HY000](#)

Message: The parameter network_namespace is reserved for future use. Please use the CHANGE REPLICATION SOURCE command to set channel network_namespace parameter.

[ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAMESPACE](#) was added in 8.0.23.

- Error number: [4031](#); Symbol: [ER_CLIENT_INTERACTION_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: The client was disconnected by the server because of inactivity. See wait_timeout and interactive_timeout for configuring this behavior.

`ER_CLIENT_INTERACTION_TIMEOUT` was added in 8.0.24.

- Error number: `4032`; Symbol: `ER_INVALID_CAST_TO_GEOMETRY`; SQLSTATE: `22S01`

Message: Invalid cast from %s to %s.

`ER_INVALID_CAST_TO_GEOMETRY` was added in 8.0.24.

- Error number: `4033`; Symbol: `ER_INVALID_CAST_POLYGON_RING_DIRECTION`; SQLSTATE: `22S04`

Message: Invalid cast from %s to %s. A polygon ring is in the wrong direction.

`ER_INVALID_CAST_POLYGON_RING_DIRECTION` was added in 8.0.24.

- Error number: `4034`; Symbol: `ER_GIS_DIFFERENT_SRIDS_AGGREGATION`; SQLSTATE: `22S05`

Message: Arguments to function %s contains geometries with different SRIDs: %u and %u. All geometries must have the same SRID.

`ER_GIS_DIFFERENT_SRIDS_AGGREGATION` was added in 8.0.24.

- Error number: `4035`; Symbol: `ER_RELOAD_KEYRING_FAILURE`; SQLSTATE: `HY000`

Message: Keyring reload failed. Please check error log for more details.

`ER_RELOAD_KEYRING_FAILURE` was added in 8.0.24.

- Error number: `4036`; Symbol: `ER_SDI_GET_KEYS_INVALID_TABLESPACE`; SQLSTATE: `HY000`

Message: Tablespace '%s' is invalid for SDI operations.

`ER_SDI_GET_KEYS_INVALID_TABLESPACE` was added in 8.0.24.

- Error number: `4037`; Symbol: `ER_CHANGE_RPL_SRC_WRONG_COMPRESSION_ALGORITHM_SIZE`; SQLSTATE: `HY000`

Message: Value too long setting SOURCE_COMPRESSION_ALGORITHMS option to a %d chars long string for channel '%s'.

`ER_CHANGE_RPL_SRC_WRONG_COMPRESSION_ALGORITHM_SIZE` was added in 8.0.24.

- Error number: `4038`; Symbol: `ER_WARN_DEPRECATED_TLS_VERSION_FOR_CHANNEL_CLI`; SQLSTATE: `HY000`

Message: A deprecated TLS version %s is enabled for channel %s. Please use TLSv1.2 or higher.

`ER_WARN_DEPRECATED_TLS_VERSION_FOR_CHANNEL_CLI` was added in 8.0.26.

- Error number: `4039`; Symbol: `ER_CANT_USE_SAME_UUID_AS_VIEW_CHANGE_UUID`; SQLSTATE: `HY000`

Message: CHANGE REPLICATION SOURCE TO
ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = <UUID> cannot be executed because the
UUID value is equal to the group_replication_view_change_uuid.

`ER_CANT_USE_SAME_UUID_AS_VIEW_CHANGE_UUID` was added in 8.0.26.

- Error number: `4040`; Symbol: `ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW_CHANGE_UUID`; SQLSTATE: `HY000`

Message: Replication '%s' is configured with ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = <UUID> where the UUID value is equal to the group_replication_view_change_uuid

[ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW_CHANGE_UUID](#) was added in 8.0.26.

- Error number: 4041; Symbol: [ER_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE](#); SQLSTATE: HY000

Message: Unable to retrieve group_replication_view_change_uuid variable during server checks on replication operations.

[ER_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE](#) was added in 8.0.26.

- Error number: 4042; Symbol: [ER_WARN_AUDIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS](#); SQLSTATE: HY000

Message: Both audit_log_max_size and audit_log_prune_seconds are set to non-zero.
audit_log_max_size takes precedence and audit_log_prune_seconds is ignored

[ER_WARN_AUDIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS](#) was added in 8.0.26.

- Error number: 4043; Symbol: [ER_WARN_AUDIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE_ON_SIZE](#); SQLSTATE: HY000

Message: audit_log_rotate_on_size is not granular enough for the value of audit_log_max_size supplied. Should be at least %d times smaller.

[ER_WARN_AUDIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE_ON_SIZE](#) was added in 8.0.26.

- Error number: 4044; Symbol: [ER_KERBEROS_CREATE_USER](#); SQLSTATE: HY000

Message: Create/Alter user has failed, Configured user realm as authentication string is empty, Please make sure to configure authentication string as user realm.

[ER_KERBEROS_CREATE_USER](#) was added in 8.0.26.

- Error number: 4045; Symbol: [ER_INSTALL_PLUGIN_CONFLICT_CLIENT](#); SQLSTATE: HY000

Message: Cannot install the %s plugin when the %s plugin is installed.

[ER_INSTALL_PLUGIN_CONFLICT_CLIENT](#) was added in 8.0.26.

- Error number: 4046; Symbol: [ER_DA_ERROR_LOG_COMPONENT_FLUSH_FAILED](#); SQLSTATE: HY000

Message: %d error logging component(s) failed to flush. For file-based logs this can happen when the path or permissions of the log-file have changed. Failure to flush file-based logs may affect log-rotation.

[ER_DA_ERROR_LOG_COMPONENT_FLUSH_FAILED](#) was added in 8.0.26.

- Error number: 4047; Symbol: [ER_WARN_SQL_AFTER_MTS_GAPS_GAP_NOT_CALCULATED](#); SQLSTATE: HY000

Message: The until clause SQL_AFTER_MTS_GAPS is being used for channel '%s' when GTID_MODE = ON and SOURCE_AUTO_POSITION=1 meaning the server did not compute internally what gaps may exist in the relay log transaction execution. To close any execution gaps use either the SQL_BEFORE_GTIDS or SQL_AFTER_GTIDS until clause.

[ER_WARN_SQL_AFTER_MTS_GAPS_GAP_NOT_CALCULATED](#) was added in 8.0.26.

- Error number: MY-010000; Symbol: [ER_PARSER_TRACE](#); SQLSTATE: XX999

Message: Parser saw: %s

`ER_PARSER_TRACE` was added in 8.0.2.

- Error number: `MY-010001`; Symbol: `ER_BOOTSTRAP_CANT_THREAD`; SQLSTATE: `HY000`

Message: Can't create thread to handle bootstrap (errno: %d)

`ER_BOOTSTRAP_CANT_THREAD` was added in 8.0.2.

- Error number: `MY-010002`; Symbol: `ER_TRIGGER_INVALID_VALUE`; SQLSTATE: `HY000`

Message: Trigger for table '%s'.'%s': invalid %s value (%s).

`ER_TRIGGER_INVALID_VALUE` was added in 8.0.2.

- Error number: `MY-010003`; Symbol: `ER_OPT_WRONG_TREE`; SQLSTATE: `HY000`

Message: Wrong tree: %s

`ER_OPT_WRONG_TREE` was added in 8.0.2.

- Error number: `MY-010004`; Symbol: `ER_DD_FAILSAFE`; SQLSTATE: `HY000`

Message: Error: Invalid %s

`ER_DD_FAILSAFE` was added in 8.0.2.

- Error number: `MY-010005`; Symbol: `ER_DD_NO_WRITES_NO_REPOPULATION`; SQLSTATE: `HY000`

Message: Skip re-populating collations and character sets tables in %s%sread-only mode.

`ER_DD_NO_WRITES_NO_REPOPULATION` was added in 8.0.2.

- Error number: `MY-010006`; Symbol: `ER_DD_VERSION_FOUND`; SQLSTATE: `HY000`

Message: Using data dictionary with version '%d'.

`ER_DD_VERSION_FOUND` was added in 8.0.2.

- Error number: `MY-010007`; Symbol: `ER_DD_VERSION_INSTALLED`; SQLSTATE: `HY000`

Message: Installed data dictionary with version %d

`ER_DD_VERSION_INSTALLED` was added in 8.0.2.

- Error number: `MY-010008`; Symbol: `ER_DD_VERSION_UNSUPPORTED`; SQLSTATE: `HY000`

Message: Data Dictionary version '%d' not supported.

`ER_DD_VERSION_UNSUPPORTED` was added in 8.0.2.

- Error number: `MY-010009`; Symbol: `ER_LOG_SYSLOG_FACILITY_FAIL`; SQLSTATE: `HY000`

Message: Failed to set syslog facility to "%s", setting to "%s" (%d) instead.

`ER_LOG_SYSLOG_FACILITY_FAIL` was added in 8.0.2, removed after 8.0.12.

- Error number: `MY-010010`; Symbol: `ER_LOG_SYSLOG_CANNOT_OPEN`; SQLSTATE: `HY000`

Message: Cannot open %s; check privileges, or remove syseventlog from --log-error-services!

`ER_LOG_SYSLOG_CANNOT_OPEN` was added in 8.0.2.

-
- Error number: `MY-010011`; Symbol: `ER_LOG_SLOW_CANNOT_OPEN`; SQLSTATE: `HY000`
Message: either restart the query logging by using "SET GLOBAL SLOW_QUERY_LOG=ON" or
`ER_LOG_SLOW_CANNOT_OPEN` was added in 8.0.2.
 - Error number: `MY-010012`; Symbol: `ER_LOG_GENERAL_CANNOT_OPEN`; SQLSTATE: `HY000`
Message: either restart the query logging by using "SET GLOBAL GENERAL_LOG=ON" or
`ER_LOG_GENERAL_CANNOT_OPEN` was added in 8.0.2.
 - Error number: `MY-010013`; Symbol: `ER_LOG_CANNOT_WRITE`; SQLSTATE: `HY000`
Message: Failed to write to %s: %s
`ER_LOG_CANNOT_WRITE` was added in 8.0.2.
 - Error number: `MY-010014`; Symbol: `ER_RPL_ZOMBIE_ENCOUNTERED`; SQLSTATE: `HY000`
Message: While initializing dump thread for slave with %s <%s>, found a zombie dump thread with
the same %s. Master is killing the zombie dump thread(%u).
`ER_RPL_ZOMBIE_ENCOUNTERED` was added in 8.0.2.
 - Error number: `MY-010015`; Symbol: `ER_RPL_GTID_TABLE_CANNOT_OPEN`; SQLSTATE: `HY000`
Message: Gtid table is not ready to be used. Table '%s.%s' cannot be opened.
`ER_RPL_GTID_TABLE_CANNOT_OPEN` was added in 8.0.2.
 - Error number: `MY-010016`; Symbol: `ER_SYSTEM_SCHEMA_NOT_FOUND`; SQLSTATE: `HY000`
Message: System schema directory does not exist.
`ER_SYSTEM_SCHEMA_NOT_FOUND` was added in 8.0.2.
 - Error number: `MY-010017`; Symbol: `ER_DD_INIT_UPGRADE_FAILED`; SQLSTATE: `HY000`
Message: Error in initializing dictionary, upgrade will do a cleanup and exit
`ER_DD_INIT_UPGRADE_FAILED` was added in 8.0.2.
 - Error number: `MY-010018`; Symbol: `ER_VIEW_UNKNOWN_CHARSET_OR_COLLATION`; SQLSTATE: `HY000`
Message: View '%s'.'%s': unknown charset name and/or collation name (client: '%s'; connection:
'%s').
`ER_VIEW_UNKNOWN_CHARSET_OR_COLLATION` was added in 8.0.2.
 - Error number: `MY-010019`; Symbol: `ER_DD_VIEW_CANT_ALLOC_CHARSET`; SQLSTATE: `HY000`
Message: Error in allocating memory for character set name for view %s.%s.
`ER_DD_VIEW_CANT_ALLOC_CHARSET` was added in 8.0.2.
 - Error number: `MY-010020`; Symbol: `ER_DD_INIT_FAILED`; SQLSTATE: `HY000`
Message: Data Dictionary initialization failed.
`ER_DD_INIT_FAILED` was added in 8.0.2.
 - Error number: `MY-010021`; Symbol: `ER_DD_UPDATING_PLUGIN_MD_FAILED`; SQLSTATE: `HY000`

Message: Failed to update plugin metadata in dictionary tables.

`ER_DD_UPDATING_PLUGIN_MD_FAILED` was added in 8.0.2.

- Error number: `MY-010022`; Symbol: `ER_DD_POPULATING_TABLES_FAILED`; SQLSTATE: `HY000`

Message: Failed to Populate DD tables.

`ER_DD_POPULATING_TABLES_FAILED` was added in 8.0.2.

- Error number: `MY-010023`; Symbol: `ER_DD_VIEW_CANT_CREATE`; SQLSTATE: `HY000`

Message: Error in Creating View %s.%s

`ER_DD_VIEW_CANT_CREATE` was added in 8.0.2.

- Error number: `MY-010024`; Symbol: `ER_DD_METADATA_NOT_FOUND`; SQLSTATE: `HY000`

Message: Unable to start server. Cannot find the meta data for data dictionary table '%s'.

`ER_DD_METADATA_NOT_FOUND` was added in 8.0.2.

- Error number: `MY-010025`; Symbol: `ER_DD_CACHE_NOT_EMPTY_AT_SHUTDOWN`; SQLSTATE: `HY000`

Message: Dictionary cache not empty at shutdown.

`ER_DD_CACHE_NOT_EMPTY_AT_SHUTDOWN` was added in 8.0.2.

- Error number: `MY-010026`; Symbol: `ER_DD_OBJECT_REMAINS`; SQLSTATE: `HY000`

Message: Dictionary objects used but not released.

`ER_DD_OBJECT_REMAINS` was added in 8.0.2.

- Error number: `MY-010027`; Symbol: `ER_DD_OBJECT_REMAINS_IN_RELEASEER`; SQLSTATE: `HY000`

Message: Dictionary objects left in default releaser.

`ER_DD_OBJECT_REMAINS_IN_RELEASEER` was added in 8.0.2.

- Error number: `MY-010028`; Symbol: `ER_DD_OBJECT_RELEASEER_REMAINS`; SQLSTATE: `HY000`

Message: Dictionary object auto releaser not deleted

`ER_DD_OBJECT_RELEASEER_REMAINS` was added in 8.0.2.

- Error number: `MY-010029`; Symbol: `ER_DD_CANT_GET_OBJECT_KEY`; SQLSTATE: `HY000`

Message: Error: Unable to create primary object key

`ER_DD_CANT_GET_OBJECT_KEY` was added in 8.0.2.

- Error number: `MY-010030`; Symbol: `ER_DD_CANT_CREATE_OBJECT_KEY`; SQLSTATE: `HY000`

Message: Error: Unable to create object key

`ER_DD_CANT_CREATE_OBJECT_KEY` was added in 8.0.2.

-
- Error number: [MY-010031](#); Symbol: [ER_CANT_CREATE_HANDLE_MGR_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create handle_manager thread (errno= %d)
[ER_CANT_CREATE_HANDLE_MGR_THREAD](#) was added in 8.0.2.
 - Error number: [MY-010032](#); Symbol: [ER_RPL_REPO_HAS_GAPS](#); SQLSTATE: [HY000](#)

Message: It is not possible to change the type of the relay log's repository because there are workers' repositories with gaps. Please, fix the gaps first before doing such change.
[ER_RPL_REPO_HAS_GAPS](#) was added in 8.0.2.
 - Error number: [MY-010033](#); Symbol: [ER_INVALID_VALUE_FOR_ENFORCE_GTID_CONSISTENCY](#); SQLSTATE: [HY000](#)

Message: option 'enforce-gtid-consistency': value '%s' was not recognized. Setting enforce-gtid-consistency to OFF.
[ER_INVALID_VALUE_FOR_ENFORCE_GTID_CONSISTENCY](#) was added in 8.0.2.
 - Error number: [MY-010034](#); Symbol: [ER_CHANGED_ENFORCE_GTID_CONSISTENCY](#); SQLSTATE: [HY000](#)

Message: Changed ENFORCE_GTID_CONSISTENCY from %s to %s.
[ER_CHANGED_ENFORCE_GTID_CONSISTENCY](#) was added in 8.0.2.
 - Error number: [MY-010035](#); Symbol: [ER_CHANGED_GTID_MODE](#); SQLSTATE: [HY000](#)

Message: Changed GTID_MODE from %s to %s.
[ER_CHANGED_GTID_MODE](#) was added in 8.0.2.
 - Error number: [MY-010036](#); Symbol: [ER_DISABLED_STORAGE_ENGINE_AS_DEFAULT](#); SQLSTATE: [HY000](#)

Message: %s is set to a disabled storage engine %s.
[ER_DISABLED_STORAGE_ENGINE_AS_DEFAULT](#) was added in 8.0.2.
 - Error number: [MY-010037](#); Symbol: [ER_DEBUG_SYNC_HIT](#); SQLSTATE: [HY000](#)

Message: Debug sync points hit: %s
[ER_DEBUG_SYNC_HIT](#) was added in 8.0.2.
 - Error number: [MY-010038](#); Symbol: [ER_DEBUG_SYNC_EXECUTED](#); SQLSTATE: [HY000](#)

Message: Debug sync points executed: %s
[ER_DEBUG_SYNC_EXECUTED](#) was added in 8.0.2.
 - Error number: [MY-010039](#); Symbol: [ER_DEBUG_SYNC_THREAD_MAX](#); SQLSTATE: [HY000](#)

Message: Debug sync points max active per thread: %s
[ER_DEBUG_SYNC_THREAD_MAX](#) was added in 8.0.2.
 - Error number: [MY-010040](#); Symbol: [ER_DEBUG_SYNC_OOM](#); SQLSTATE: [HY000](#)

Message: Debug Sync Facility disabled due to lack of memory.

`ER_DEBUG_SYNC_OOM` was added in 8.0.2.

- Error number: `MY-010041`; Symbol: `ER_CANT_INIT_TC_LOG`; SQLSTATE: `HY000`

Message: Can't init tc log

`ER_CANT_INIT_TC_LOG` was added in 8.0.2.

- Error number: `MY-010042`; Symbol: `ER_EVENT_CANT_INIT_QUEUE`; SQLSTATE: `HY000`

Message: Event Scheduler: Can't initialize the execution queue

`ER_EVENT_CANT_INIT_QUEUE` was added in 8.0.2.

- Error number: `MY-010043`; Symbol: `ER_EVENT_PURGING_QUEUE`; SQLSTATE: `HY000`

Message: Event Scheduler: Purging the queue. %u events

`ER_EVENT_PURGING_QUEUE` was added in 8.0.2.

- Error number: `MY-010044`; Symbol: `ER_EVENT_LAST_EXECUTION`; SQLSTATE: `HY000`

Message: Event Scheduler: Last execution of %s.%s. %s

`ER_EVENT_LAST_EXECUTION` was added in 8.0.2.

- Error number: `MY-010045`; Symbol: `ER_EVENT_MESSAGE_STACK`; SQLSTATE: `HY000`

Message: %*s

`ER_EVENT_MESSAGE_STACK` was added in 8.0.2.

- Error number: `MY-010046`; Symbol: `ER_EVENT_EXECUTION_FAILED`; SQLSTATE: `HY000`

Message: Event Scheduler: [%s].[%s.%s] event execution failed.

`ER_EVENT_EXECUTION_FAILED` was added in 8.0.2.

- Error number: `MY-010047`; Symbol: `ER_CANT_INIT_SCHEDULER_THREAD`; SQLSTATE: `HY000`

Message: Event Scheduler: Cannot initialize the scheduler thread

`ER_CANT_INIT_SCHEDULER_THREAD` was added in 8.0.2.

- Error number: `MY-010048`; Symbol: `ER_SCHEDULER_STOPPED`; SQLSTATE: `HY000`

Message: Event Scheduler: Stopped

`ER_SCHEDULER_STOPPED` was added in 8.0.2.

- Error number: `MY-010049`; Symbol: `ER_CANT_CREATE_SCHEDULER_THREAD`; SQLSTATE: `HY000`

Message: Event scheduler: Failed to start scheduler, Can not create thread for event scheduler
(errno=%d)

`ER_CANT_CREATE_SCHEDULER_THREAD` was added in 8.0.2.

- Error number: `MY-010050`; Symbol: `ER_SCHEDULER_WAITING`; SQLSTATE: `HY000`

Message: Event Scheduler: Waiting for the scheduler thread to reply

`ER_SCHEDULER_WAITING` was added in 8.0.2.

- Error number: `MY-010051`; Symbol: `ER_SCHEDULER_STARTED`; SQLSTATE: `HY000`

Message: Event Scheduler: scheduler thread started with id %u

`ER_SCHEDULER_STARTED` was added in 8.0.2.

- Error number: `MY-010052`; Symbol: `ER_SCHEDULER_STOPPING_FAILED_TO_GET_EVENT`; SQLSTATE: `HY000`

Message: Event Scheduler: Serious error during getting next event to execute. Stopping

`ER_SCHEDULER_STOPPING_FAILED_TO_GET_EVENT` was added in 8.0.2.

- Error number: `MY-010053`; Symbol: `ER_SCHEDULER_STOPPING_FAILED_TO_CREATE_WORKER`; SQLSTATE: `HY000`

Message: Event_scheduler::execute_top: Can not create event worker thread (errno=%d). Stopping event scheduler

`ER_SCHEDULER_STOPPING_FAILED_TO_CREATE_WORKER` was added in 8.0.2.

- Error number: `MY-010054`; Symbol: `ER_SCHEDULER_KILLING`; SQLSTATE: `HY000`

Message: Event Scheduler: Killing the scheduler thread, thread id %u

`ER_SCHEDULER_KILLING` was added in 8.0.2.

- Error number: `MY-010055`; Symbol: `ER_UNABLE_TO_RESOLVE_IP`; SQLSTATE: `HY000`

Message: IP address '%s' could not be resolved: %s

`ER_UNABLE_TO_RESOLVE_IP` was added in 8.0.2.

- Error number: `MY-010056`; Symbol: `ER_UNABLE_TO_RESOLVE_HOSTNAME`; SQLSTATE: `HY000`

Message: Host name '%s' could not be resolved: %s

`ER_UNABLE_TO_RESOLVE_HOSTNAME` was added in 8.0.2.

- Error number: `MY-010057`; Symbol: `ER_HOSTNAME_RESEMBLES_IPV4`; SQLSTATE: `HY000`

Message: IP address '%s' has been resolved to the host name '%s', which resembles IPv4-address itself.

`ER_HOSTNAME_RESEMBLES_IPV4` was added in 8.0.2.

- Error number: `MY-010058`; Symbol: `ER_HOSTNAME_DOESNT_RESOLVE_TO`; SQLSTATE: `HY000`

Message: Hostname '%s' does not resolve to '%s'.

`ER_HOSTNAME_DOESNT_RESOLVE_TO` was added in 8.0.2.

- Error number: `MY-010059`; Symbol: `ER_ADDRESSES_FOR_HOSTNAME_HEADER`; SQLSTATE: `HY000`

Message: Hostname '%s' has the following IP addresses:

`ER_ADDRESSES_FOR_HOSTNAME_HEADER` was added in 8.0.2.

- Error number: `MY-010060`; Symbol: `ER_ADDRESSES_FOR_HOSTNAME_LIST_ITEM`; SQLSTATE: `HY000`

Message: - %s

`ER_ADDRESSES_FOR_HOSTNAME_LIST_ITEM` was added in 8.0.2.

- Error number: [MY-010061](#); Symbol: [ER_TRG_WITHOUT_DEFINER](#); SQLSTATE: [HY000](#)

Message: Definer clause is missing in Trigger of Table %s. Rebuild Trigger to fix definer.
[ER_TRG_WITHOUT_DEFINER](#) was added in 8.0.2.
- Error number: [MY-010062](#); Symbol: [ER_TRG_NO_CLIENT_CHARSET](#); SQLSTATE: [HY000](#)

Message: Client character set is missing for trigger of table %s. Using default character set.
[ER_TRG_NO_CLIENT_CHARSET](#) was added in 8.0.2.
- Error number: [MY-010063](#); Symbol: [ER_PARSING_VIEW](#); SQLSTATE: [HY000](#)

Message: Error in parsing view %s.%s
[ER_PARSING_VIEW](#) was added in 8.0.2.
- Error number: [MY-010064](#); Symbol: [ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP](#); SQLSTATE: [HY000](#)

Message: Failed to bootstrap components infrastructure.
[ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP](#) was added in 8.0.2.
- Error number: [MY-010065](#); Symbol: [ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: Failed to shutdown components infrastructure.
[ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN](#) was added in 8.0.2.
- Error number: [MY-010066](#); Symbol: [ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP](#); SQLSTATE: [HY000](#)

Message: Failed to bootstrap persistent components loader.
[ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP](#) was added in 8.0.2.
- Error number: [MY-010067](#); Symbol: [ER_DEPART_WITH_GRACE](#); SQLSTATE: [HY000](#)

Message: Giving %d client threads a chance to die gracefully
[ER_DEPART_WITH_GRACE](#) was added in 8.0.2.
- Error number: [MY-010068](#); Symbol: [ER_CA_SELF_SIGNED](#); SQLSTATE: [HY000](#)

Message: CA certificate %s is self signed.
[ER_CA_SELF_SIGNED](#) was added in 8.0.2.
- Error number: [MY-010069](#); Symbol: [ER_SSL_LIBRARY_ERROR](#); SQLSTATE: [HY000](#)

Message: Failed to set up SSL because of the following SSL library error: %s
[ER_SSL_LIBRARY_ERROR](#) was added in 8.0.2.
- Error number: [MY-010070](#); Symbol: [ER_NO_THD_NO_UUID](#); SQLSTATE: [HY000](#)

Message: Failed to generate a server UUID because it is failed to allocate the THD.
[ER_NO_THD_NO_UUID](#) was added in 8.0.2.
- Error number: [MY-010071](#); Symbol: [ER_UUID_SALT](#); SQLSTATE: [HY000](#)

Message: Salting uuid generator variables, current_pid: %lu, server_start_time: %lu, bytes_sent: %llu,

`ER_UUID_SALT` was added in 8.0.2.

- Error number: `MY-010072`; Symbol: `ER_UUID_IS`; SQLSTATE: `HY000`

Message: Generated uuid: '%s', server_start_time: %lu, bytes_sent: %llu

`ER_UUID_IS` was added in 8.0.2.

- Error number: `MY-010073`; Symbol: `ER_UUID_INVALID`; SQLSTATE: `HY000`

Message: The server_uuid stored in auto.cnf file is not a valid UUID.

`ER_UUID_INVALID` was added in 8.0.2.

- Error number: `MY-010074`; Symbol: `ER_UUID_SCRUB`; SQLSTATE: `HY000`

Message: Garbage characters found at the end of the server_uuid value in auto.cnf file. It should be of length '%d' (UUID_LENGTH). Clear it and restart the server.

`ER_UUID_SCRUB` was added in 8.0.2.

- Error number: `MY-010075`; Symbol: `ER_CREATING_NEW_UUID`; SQLSTATE: `HY000`

Message: No existing UUID has been found, so we assume that this is the first time that this server has been started. Generating a new UUID: %s.

`ER_CREATING_NEW_UUID` was added in 8.0.2.

- Error number: `MY-010076`; Symbol: `ER_CANT_CREATE_UUID`; SQLSTATE: `HY000`

Message: Initialization of the server's UUID failed because it could not be read from the auto.cnf file. If this is a new server, the initialization failed because it was not possible to generate a new UUID.

`ER_CANT_CREATE_UUID` was added in 8.0.2.

- Error number: `MY-010077`; Symbol: `ER_UNKNOWN_UNSUPPORTED_STORAGE_ENGINE`; SQLSTATE: `HY000`

Message: Unknown/unsupported storage engine: %s

`ER_UNKNOWN_UNSUPPORTED_STORAGE_ENGINE` was added in 8.0.2.

- Error number: `MY-010078`; Symbol: `ER_SECURE_AUTH_VALUE_UNSUPPORTED`; SQLSTATE: `HY000`

Message: Unsupported value 0 for secure-auth

`ER_SECURE_AUTH_VALUE_UNSUPPORTED` was added in 8.0.2.

- Error number: `MY-010079`; Symbol: `ER_INVALID_INSTRUMENT`; SQLSTATE: `HY000`

Message: Invalid instrument name or value for performance_schema_instrument '%s'

`ER_INVALID_INSTRUMENT` was added in 8.0.2.

- Error number: `MY-010080`; Symbol: `ER_INNODB_MANDATORY`; SQLSTATE: `HY000`

Message: The use of InnoDB is mandatory since MySQL 5.7. The former options like '--innodb=0/1/OFF/ON' or '--skip-innodb' are ignored.

`ER_INNODB_MANDATORY` was added in 8.0.2.

- Error number: [MY-010082](#); Symbol: `ER_OLD_PASSWORDS_NO_MIDDLE_GROUND`; SQLSTATE: `HY000`

Message: Invalid old_passwords mode: 1. Valid values are 2 and 0

`ER_OLD_PASSWORDS_NO_MIDDLE_GROUND` was added in 8.0.2, removed after 8.0.15.

- Error number: [MY-010083](#); Symbol: `ER_VERBOSE_REQUIRES_HELP`; SQLSTATE: `HY000`

Message: --verbose is for use with --help; did you mean --log-error-verbosity?

`ER_VERBOSE_REQUIRES_HELP` was added in 8.0.2.

- Error number: [MY-010084](#); Symbol: `ER_POINTLESS_WITHOUT_SLOWLOG`; SQLSTATE: `HY000`

Message: options --log-slow-admin-statements, --log-queries-not-using-indexes and --log-slow-replica-statements have no effect if --slow-query-log is not set

`ER_POINTLESS_WITHOUT_SLOWLOG` was added in 8.0.2.

- Error number: [MY-010085](#); Symbol: `ER_WASTEFUL_NET_BUFFER_SIZE`; SQLSTATE: `HY000`

Message: net_buffer_length (%lu) is set to be larger than max_allowed_packet (%lu). Please rectify.

`ER_WASTEFUL_NET_BUFFER_SIZE` was added in 8.0.2.

- Error number: [MY-010086](#); Symbol: `ER_DEPRECATED_TIMESTAMP_IMPLICIT_DEFAULTS`; SQLSTATE: `HY000`

Message: TIMESTAMP with implicit DEFAULT value is deprecated. Please use --explicit_defaults_for_timestamp server option (see documentation for more details).

`ER_DEPRECATED_TIMESTAMP_IMPLICIT_DEFAULTS` was added in 8.0.2.

- Error number: [MY-010087](#); Symbol: `ER_FT_BOOL_SYNTAX_INVALID`; SQLSTATE: `HY000`

Message: Invalid ft-boolean-syntax string: %s

`ER_FT_BOOL_SYNTAX_INVALID` was added in 8.0.2.

- Error number: [MY-010088](#); Symbol: `ER_CREDENTIALLESS_AUTO_USER_BAD`; SQLSTATE: `HY000`

Message: 'NO_AUTO_CREATE_USER' sql mode was not set.

`ER_CREDENTIALLESS_AUTO_USER_BAD` was added in 8.0.2.

- Error number: [MY-010089](#); Symbol: `ER_CONNECTION_HANDLING_OOM`; SQLSTATE: `HY000`

Message: Could not allocate memory for connection handling

`ER_CONNECTION_HANDLING_OOM` was added in 8.0.2.

- Error number: [MY-010090](#); Symbol: `ER_THREAD_HANDLING_OOM`; SQLSTATE: `HY000`

Message: Could not allocate memory for thread handling

`ER_THREAD_HANDLING_OOM` was added in 8.0.2.

- Error number: [MY-010091](#); Symbol: `ER_CANT_CREATE_TEST_FILE`; SQLSTATE: `HY000`

Message: Can't create test file %s

`ER_CANT_CREATE_TEST_FILE` was added in 8.0.2.

- Error number: `MY-010092`; Symbol: `ER_CANT_CREATE_PID_FILE`; SQLSTATE: `HY000`

Message: Can't start server: can't create PID file: %s

`ER_CANT_CREATE_PID_FILE` was added in 8.0.2.

- Error number: `MY-010093`; Symbol: `ER_CANT_REMOVE_PID_FILE`; SQLSTATE: `HY000`

Message: Unable to delete pid file: %s

`ER_CANT_REMOVE_PID_FILE` was added in 8.0.2.

- Error number: `MY-010094`; Symbol: `ER_CANT_CREATE_SHUTDOWN_THREAD`; SQLSTATE: `HY000`

Message: Can't create thread to handle shutdown requests (errno= %d)

`ER_CANT_CREATE_SHUTDOWN_THREAD` was added in 8.0.2.

- Error number: `MY-010095`; Symbol: `ER_SEC_FILE_PRIV_CANT_ACCESS_DIR`; SQLSTATE: `HY000`

Message: Failed to access directory for --secure-file-priv. Please make sure that directory exists and is accessible by MySQL Server. Supplied value : %s

`ER_SEC_FILE_PRIV_CANT_ACCESS_DIR` was added in 8.0.2.

- Error number: `MY-010096`; Symbol: `ER_SEC_FILE_PRIV_IGNORED`; SQLSTATE: `HY000`

Message: Ignoring --secure-file-priv value as server is running with --initialize(-insecure).

`ER_SEC_FILE_PRIV_IGNORED` was added in 8.0.2.

- Error number: `MY-010097`; Symbol: `ER_SEC_FILE_PRIV_EMPTY`; SQLSTATE: `HY000`

Message: Insecure configuration for --secure-file-priv: Current value does not restrict location of generated files. Consider setting it to a valid, non-empty path.

`ER_SEC_FILE_PRIV_EMPTY` was added in 8.0.2.

- Error number: `MY-010098`; Symbol: `ER_SEC_FILE_PRIV_NULL`; SQLSTATE: `HY000`

Message: --secure-file-priv is set to NULL. Operations related to importing and exporting data are disabled

`ER_SEC_FILE_PRIV_NULL` was added in 8.0.2.

- Error number: `MY-010099`; Symbol: `ER_SEC_FILE_PRIV_DIRECTORY_INSECURE`; SQLSTATE: `HY000`

Message: Insecure configuration for --secure-file-priv: %s is accessible through --secure-file-priv. Consider choosing a different directory.

`ER_SEC_FILE_PRIV_DIRECTORY_INSECURE` was added in 8.0.2.

- Error number: `MY-010100`; Symbol: `ER_SEC_FILE_PRIV_CANT_STAT`; SQLSTATE: `HY000`

Message: Failed to get stat for directory pointed out by --secure-file-priv

`ER_SEC_FILE_PRIV_CANT_STAT` was added in 8.0.2.

- Error number: [MY-010101](#); Symbol: [ER_SEC_FILE_PRIV_DIRECTORY_PERMISSIONS](#); SQLSTATE: [HY000](#)

Message: Insecure configuration for --secure-file-priv: Location is accessible to all OS users. Consider choosing a different directory.
[ER_SEC_FILE_PRIV_DIRECTORY_PERMISSIONS](#) was added in 8.0.2.
- Error number: [MY-010102](#); Symbol: [ER_SEC_FILE_PRIV_ARGUMENT_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: Value for --secure-file-priv is longer than maximum limit of %d
[ER_SEC_FILE_PRIV_ARGUMENT_TOO_LONG](#) was added in 8.0.2.
- Error number: [MY-010103](#); Symbol: [ER_CANT_CREATE_NAMED_PIPES_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create thread to handle named pipes (errno= %d)
[ER_CANT_CREATE_NAMED_PIPES_THREAD](#) was added in 8.0.2.
- Error number: [MY-010104](#); Symbol: [ER_CANT_CREATE_TCPIP_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create thread to handle TCP/IP (errno= %d)
[ER_CANT_CREATE_TCPIP_THREAD](#) was added in 8.0.2.
- Error number: [MY-010105](#); Symbol: [ER_CANT_CREATE_SHM_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create thread to handle shared memory (errno= %d)
[ER_CANT_CREATE_SHM_THREAD](#) was added in 8.0.2.
- Error number: [MY-010106](#); Symbol: [ER_CANT_CREATE_INTERRUPT_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create interrupt-thread (error %d, errno: %d)
[ER_CANT_CREATE_INTERRUPT_THREAD](#) was added in 8.0.2.
- Error number: [MY-010107](#); Symbol: [ER_WRITABLE_CONFIG_REMOVED](#); SQLSTATE: [HY000](#)

Message: World-writable config file '%s' has been removed.
[ER_WRITABLE_CONFIG_REMOVED](#) was added in 8.0.2.
- Error number: [MY-010108](#); Symbol: [ER_CORE_VALUES](#); SQLSTATE: [HY000](#)

Message: setrlimit could not change the size of core files to 'infinity'; We may not be able to generate a core file on signals
[ER_CORE_VALUES](#) was added in 8.0.2.
- Error number: [MY-010109](#); Symbol: [ER_WRONG_DATETIME_SPEC](#); SQLSTATE: [HY000](#)

Message: Wrong date/time format specifier: %s
[ER_WRONG_DATETIME_SPEC](#) was added in 8.0.2.
- Error number: [MY-010110](#); Symbol: [ER_RPL_BINLOG_FILTERS_OOM](#); SQLSTATE: [HY000](#)

Message: Could not allocate replication and binlog filters: %s
[ER_RPL_BINLOG_FILTERS_OOM](#) was added in 8.0.2.

-
- Error number: [MY-010111](#); Symbol: [ER_KEYCACHE_OOM](#); SQLSTATE: [HY000](#)

Message: Cannot allocate the keycache
[ER_KEYCACHE_OOM](#) was added in 8.0.2.
 - Error number: [MY-010112](#); Symbol: [ER_CONFIRMING_THE_FUTURE](#); SQLSTATE: [HY000](#)

Message: Current time has got past year 2038. Validating current time with %d iterations before initiating the normal server shutdown process.
[ER_CONFIRMING_THE_FUTURE](#) was added in 8.0.2.
 - Error number: [MY-010113](#); Symbol: [ER_BACK_IN_TIME](#); SQLSTATE: [HY000](#)

Message: Iteration %d: Obtained valid current time from system
[ER_BACK_IN_TIME](#) was added in 8.0.2.
 - Error number: [MY-010114](#); Symbol: [ER_FUTURE_DATE](#); SQLSTATE: [HY000](#)

Message: Iteration %d: Current time obtained from system is greater than 2038
[ER_FUTURE_DATE](#) was added in 8.0.2.
 - Error number: [MY-010115](#); Symbol: [ER_UNSUPPORTED_DATE](#); SQLSTATE: [HY000](#)

Message: This MySQL server doesn't support dates later than 2038
[ER_UNSUPPORTED_DATE](#) was added in 8.0.2.
 - Error number: [MY-010116](#); Symbol: [ER_STARTING_AS](#); SQLSTATE: [HY000](#)

Message: %s (mysqld %s) starting as process %lu
[ER_STARTING_AS](#) was added in 8.0.2.
 - Error number: [MY-010117](#); Symbol: [ER_SHUTTING_DOWN_SLAVE_THREADS](#); SQLSTATE: [HY000](#)

Message: Shutting down slave threads
[ER_SHUTTING_DOWN_SLAVE_THREADS](#) was added in 8.0.2.
 - Error number: [MY-010118](#); Symbol: [ER_DISCONNECTING_REMAINING_CLIENTS](#); SQLSTATE: [HY000](#)

Message: Forcefully disconnecting %d remaining clients
[ER_DISCONNECTING_REMAINING_CLIENTS](#) was added in 8.0.2.
 - Error number: [MY-010119](#); Symbol: [ER_ABORTING](#); SQLSTATE: [HY000](#)

Message: Aborting
[ER_ABORTING](#) was added in 8.0.2.
 - Error number: [MY-010120](#); Symbol: [ER_BINLOG_END](#); SQLSTATE: [HY000](#)

Message: Binlog end
[ER_BINLOG_END](#) was added in 8.0.2.

- Error number: MY-010121; Symbol: `ER_CALL_ME_LOCALHOST`; SQLSTATE: HY000

Message: gethostname failed, using '%s' as hostname
`ER_CALL_ME_LOCALHOST` was added in 8.0.2.
- Error number: MY-010122; Symbol: `ER_USER_REQUIRES_ROOT`; SQLSTATE: HY000

Message: One can only use the --user switch if running as root
`ER_USER_REQUIRES_ROOT` was added in 8.0.2.
- Error number: MY-010123; Symbol: `ER_REALLY_RUN_AS_ROOT`; SQLSTATE: HY000

Message: Fatal error: Please read "Security" section of the manual to find out how to run mysqld as root!
`ER_REALLY_RUN_AS_ROOT` was added in 8.0.2.
- Error number: MY-010124; Symbol: `ER_USER_WHAT_USER`; SQLSTATE: HY000

Message: Fatal error: Can't change to run as user '%s' ; Please check that the user exists!
`ER_USER_WHAT_USER` was added in 8.0.2.
- Error number: MY-010125; Symbol: `ER_TRANSPORTS_WHAT_TRANSPORTS`; SQLSTATE: HY000

Message: Server is started with --require-secure-transport=ON but no secure transports (SSL or Shared Memory) are configured.
`ER_TRANSPORTS_WHAT_TRANSPORTS` was added in 8.0.2.
- Error number: MY-010126; Symbol: `ER_FAIL_SETGID`; SQLSTATE: HY000

Message: setgid: %s
`ER_FAIL_SETGID` was added in 8.0.2.
- Error number: MY-010127; Symbol: `ER_FAIL_SETUID`; SQLSTATE: HY000

Message: setuid: %s
`ER_FAIL_SETUID` was added in 8.0.2.
- Error number: MY-010128; Symbol: `ER_FAIL_SETREGID`; SQLSTATE: HY000

Message: setregid: %s
`ER_FAIL_SETREGID` was added in 8.0.2.
- Error number: MY-010129; Symbol: `ER_FAIL_SETREUID`; SQLSTATE: HY000

Message: setreuid: %s
`ER_FAIL_SETREUID` was added in 8.0.2.
- Error number: MY-010130; Symbol: `ER_FAIL_CHROOT`; SQLSTATE: HY000

Message: chroot: %s
`ER_FAIL_CHROOT` was added in 8.0.2.

-
- Error number: [MY-010131](#); Symbol: [ER_WIN_LISTEN_BUT_HOW](#); SQLSTATE: [HY000](#)
Message: TCP/IP, --shared-memory, or --named-pipe should be configured on NT OS
[ER_WIN_LISTEN_BUT_HOW](#) was added in 8.0.2.
 - Error number: [MY-010132](#); Symbol: [ER_NOT_RIGHT_NOW](#); SQLSTATE: [HY000](#)
Message: CTRL-C ignored during startup
[ER_NOT_RIGHT_NOW](#) was added in 8.0.2.
 - Error number: [MY-010133](#); Symbol: [ER_FIXING_CLIENT_CHARSET](#); SQLSTATE: [HY000](#)
Message: '%s' can not be used as client character set. '%s' will be used as default client character set.
[ER_FIXING_CLIENT_CHARSET](#) was added in 8.0.2.
 - Error number: [MY-010134](#); Symbol: [ER_OOM](#); SQLSTATE: [HY000](#)
Message: Out of memory
[ER_OOM](#) was added in 8.0.2.
 - Error number: [MY-010135](#); Symbol: [ER_FAILED_TO_LOCK_MEM](#); SQLSTATE: [HY000](#)
Message: Failed to lock memory. Errno: %d
[ER_FAILED_TO_LOCK_MEM](#) was added in 8.0.2.
 - Error number: [MY-010136](#); Symbol: [ER_MYINIT_FAILED](#); SQLSTATE: [HY000](#)
Message: my_init() failed.
[ER_MYINIT_FAILED](#) was added in 8.0.2.
 - Error number: [MY-010137](#); Symbol: [ER_BEG_INITFILE](#); SQLSTATE: [HY000](#)
Message: Execution of init_file '\%s' started.
[ER_BEG_INITFILE](#) was added in 8.0.2.
 - Error number: [MY-010138](#); Symbol: [ER_END_INITFILE](#); SQLSTATE: [HY000](#)
Message: Execution of init_file '\%s' ended.
[ER_END_INITFILE](#) was added in 8.0.2.
 - Error number: [MY-010139](#); Symbol: [ER_CHANGED_MAX_OPEN_FILES](#); SQLSTATE: [HY000](#)
Message: Changed limits: max_open_files: %lu (requested %lu)
[ER_CHANGED_MAX_OPEN_FILES](#) was added in 8.0.2.
 - Error number: [MY-010140](#); Symbol: [ER_CANT_INCREASE_MAX_OPEN_FILES](#); SQLSTATE: [HY000](#)
Message: Could not increase number of max_open_files to more than %lu (request: %lu)
[ER_CANT_INCREASE_MAX_OPEN_FILES](#) was added in 8.0.2.
 - Error number: [MY-010141](#); Symbol: [ER_CHANGED_MAX_CONNECTIONS](#); SQLSTATE: [HY000](#)
Message: Changed limits: max_connections: %lu (requested %lu)

`ER_CHANGED_MAX_CONNECTIONS` was added in 8.0.2.

- Error number: `MY-010142`; Symbol: `ER_CHANGED_TABLE_OPEN_CACHE`; SQLSTATE: `HY000`

Message: Changed limits: table_open_cache: %lu (requested %lu)

`ER_CHANGED_TABLE_OPEN_CACHE` was added in 8.0.2.

- Error number: `MY-010143`; Symbol: `ER_THE_USER_ABIDES`; SQLSTATE: `HY000`

Message: Ignoring user change to '%s' because the user was set to '%s' earlier on the command line

`ER_THE_USER_ABIDES` was added in 8.0.2.

- Error number: `MY-010144`; Symbol: `ER_RPL_CANT_ADD_DO_TABLE`; SQLSTATE: `HY000`

Message: Could not add do table rule '%s'!

`ER_RPL_CANT_ADD_DO_TABLE` was added in 8.0.2.

- Error number: `MY-010145`; Symbol: `ER_RPL_CANT_ADD_IGNORE_TABLE`; SQLSTATE: `HY000`

Message: Could not add ignore table rule '%s'!

`ER_RPL_CANT_ADD_IGNORE_TABLE` was added in 8.0.2.

- Error number: `MY-010146`; Symbol: `ER_TRACK_VARIABLES_BOGUS`; SQLSTATE: `HY000`

Message: The variable session_track_system_variables either has duplicate values or invalid values.

`ER_TRACK_VARIABLES_BOGUS` was added in 8.0.2.

- Error number: `MY-010147`; Symbol: `ER_EXCESS_ARGUMENTS`; SQLSTATE: `HY000`

Message: Too many arguments (first extra is '%s').

`ER_EXCESS_ARGUMENTS` was added in 8.0.2.

- Error number: `MY-010148`; Symbol: `ER_VERBOSE_HINT`; SQLSTATE: `HY000`

Message: Use --verbose --help to get a list of available options!

`ER_VERBOSE_HINT` was added in 8.0.2.

- Error number: `MY-010149`; Symbol: `ER_CANT_READ_ERRMSGS`; SQLSTATE: `HY000`

Message: Unable to read errmsg.sys file

`ER_CANT_READ_ERRMSGS` was added in 8.0.2.

- Error number: `MY-010150`; Symbol: `ER_CANT_INIT_DBs`; SQLSTATE: `HY000`

Message: Can't init databases

`ER_CANT_INIT_DBs` was added in 8.0.2.

- Error number: `MY-010151`; Symbol: `ER_LOG_OUTPUT CONTRADICTORY`; SQLSTATE: `HY000`

Message: There were other values specified to log-output besides NONE. Disabling slow and general logs anyway.

`ER_LOG_OUTPUT CONTRADICTORY` was added in 8.0.2.

- Error number: `MY-010152`; Symbol: `ER_NO_CSV_NO_LOG_TABLES`; SQLSTATE: `HY000`

Message: CSV engine is not present, falling back to the log files

`ER_NO_CSV_NO_LOG_TABLES` was added in 8.0.2.

- Error number: `MY-010153`; Symbol: `ER_RPL_REWRITEDB_MISSING_ARROW`; SQLSTATE: `HY000`

Message: Bad syntax in replicate-rewrite-db - missing '->!

`ER_RPL_REWRITEDB_MISSING_ARROW` was added in 8.0.2.

- Error number: `MY-010154`; Symbol: `ER_RPL_REWRITEDB_EMPTY_FROM`; SQLSTATE: `HY000`

Message: Bad syntax in replicate-rewrite-db - empty FROM db!

`ER_RPL_REWRITEDB_EMPTY_FROM` was added in 8.0.2.

- Error number: `MY-010155`; Symbol: `ER_RPL_REWRITEDB_EMPTY_TO`; SQLSTATE: `HY000`

Message: Bad syntax in replicate-rewrite-db - empty TO db!

`ER_RPL_REWRITEDB_EMPTY_TO` was added in 8.0.2.

- Error number: `MY-010156`; Symbol: `ER_LOG_FILES_GIVEN_LOG_OUTPUT_IS_TABLE`; SQLSTATE: `HY000`

Message: Although a path was specified for the %s, log tables are used. To enable logging to files use the --log-output=file option.

`ER_LOG_FILES_GIVEN_LOG_OUTPUT_IS_TABLE` was added in 8.0.2.

- Error number: `MY-010157`; Symbol: `ER_LOG_FILE_INVALID`; SQLSTATE: `HY000`

Message: Invalid value for %s: %s

`ER_LOG_FILE_INVALID` was added in 8.0.2.

- Error number: `MY-010158`; Symbol: `ER_LOWER_CASE_TABLE_NAMES_CS_DD_ON_CI_FS_UNSUPPORTED`; SQLSTATE: `HY000`

Message: The server option 'lower_case_table_names' is configured to use case sensitive table names but the data directory is on a case-insensitive file system which is an unsupported combination. Please consider either using a case sensitive file system for your data directory or switching to a case-insensitive table name mode.

`ER_LOWER_CASE_TABLE_NAMES_CS_DD_ON_CI_FS_UNSUPPORTED` was added in 8.0.2.

- Error number: `MY-010159`; Symbol: `ER_LOWER_CASE_TABLE_NAMES_USING_2`; SQLSTATE: `HY000`

Message: Setting lower_case_table_names=2 because file system for %s is case insensitive

`ER_LOWER_CASE_TABLE_NAMES_USING_2` was added in 8.0.2.

- Error number: `MY-010160`; Symbol: `ER_LOWER_CASE_TABLE_NAMES_USING_0`; SQLSTATE: `HY000`

Message: lower_case_table_names was set to 2, even though your the file system '%s' is case sensitive. Now setting lower_case_table_names to 0 to avoid future problems.

`ER_LOWER_CASE_TABLE_NAMES_USING_0` was added in 8.0.2.

- Error number: `MY-010161`; Symbol: `ER_NEED_LOG_BIN`; SQLSTATE: `HY000`

Message: You need to use --log-bin to make %s work.

`ER_NEED_LOG_BIN` was added in 8.0.2.

- Error number: `MY-010162`; Symbol: `ER_NEED_FILE_INSTEAD_OF_DIR`; SQLSTATE: `HY000`

Message: Path '%s' is a directory name, please specify a file name for %s option

`ER_NEED_FILE_INSTEAD_OF_DIR` was added in 8.0.2.

- Error number: `MY-010163`; Symbol: `ER_LOG_BIN_BETTER_WITH_NAME`; SQLSTATE: `HY000`

Message: No argument was provided to --log-bin, and --log-bin-index was not used; so replication may break when this MySQL server acts as a master and has his hostname changed!! Please use '--log-bin=%s' to avoid this problem.

`ER_LOG_BIN_BETTER_WITH_NAME` was added in 8.0.2.

- Error number: `MY-010164`; Symbol: `ER_BINLOG_NEEDS_SERVERID`; SQLSTATE: `HY000`

Message: You have enabled the binary log, but you haven't provided the mandatory server-id. Please refer to the proper server start-up parameters documentation

`ER_BINLOG_NEEDS_SERVERID` was added in 8.0.2.

- Error number: `MY-010165`; Symbol: `ER_RPL_CANT_MAKE_PATHS`; SQLSTATE: `HY000`

Message: Unable to create replication path names: out of memory or path names too long (path name exceeds %d or file name exceeds %d).

`ER_RPL_CANT_MAKE_PATHS` was added in 8.0.2.

- Error number: `MY-010166`; Symbol: `ER_CANT_INITIALIZE_GTID`; SQLSTATE: `HY000`

Message: Failed to initialize GTID structures.

`ER_CANT_INITIALIZE_GTID` was added in 8.0.2.

- Error number: `MY-010167`; Symbol: `ER_CANT_INITIALIZE_EARLY_PLUGINS`; SQLSTATE: `HY000`

Message: Failed to initialize early plugins.

`ER_CANT_INITIALIZE_EARLY_PLUGINS` was added in 8.0.2.

- Error number: `MY-010168`; Symbol: `ER_CANT_INITIALIZE_BUILTIN_PLUGINS`; SQLSTATE: `HY000`

Message: Failed to initialize builtin plugins.

`ER_CANT_INITIALIZE_BUILTIN_PLUGINS` was added in 8.0.2.

- Error number: `MY-010169`; Symbol: `ER_CANT_INITIALIZE_DYNAMIC_PLUGINS`; SQLSTATE: `HY000`

Message: Failed to initialize dynamic plugins.

`ER_CANT_INITIALIZE_DYNAMIC_PLUGINS` was added in 8.0.2.

- Error number: `MY-010170`; Symbol: `ER_PERFSHEMA_INIT_FAILED`; SQLSTATE: `HY000`

Message: Performance schema disabled (reason: init failed).

`ER_PERFSHEMA_INIT_FAILED` was added in 8.0.2.

- Error number: `MY-010171`; Symbol: `ER_STACKSIZE_UNEXPECTED`; SQLSTATE: `HY000`

Message: Asked for %lu thread stack, but got %ld
`ER_STACKSIZE_UNEXPECTED` was added in 8.0.2.
- Error number: `MY-010172`; Symbol: `ER_CANT_SET_DATADIR`; SQLSTATE: `HY000`

Message: failed to set datadir to %s
`ER_CANT_SET_DATADIR` was added in 8.0.2, removed after 8.0.13.
- Error number: `MY-010173`; Symbol: `ER_CANT_STAT_DATADIR`; SQLSTATE: `HY000`

Message: Can't read data directory's stats (%d): %s. Assuming that it's not owned by the same user/group
`ER_CANT_STAT_DATADIR` was added in 8.0.2.
- Error number: `MY-010174`; Symbol: `ER_CANT_CHOWN_DATADIR`; SQLSTATE: `HY000`

Message: Can't change data directory owner to %s
`ER_CANT_CHOWN_DATADIR` was added in 8.0.2.
- Error number: `MY-010175`; Symbol: `ER_CANT_SET_UP_PERSISTED_VALUES`; SQLSTATE: `HY000`

Message: Setting persistent options failed.
`ER_CANT_SET_UP_PERSISTED_VALUES` was added in 8.0.2.
- Error number: `MY-010176`; Symbol: `ER_CANT_SAVE_GTIDS`; SQLSTATE: `HY000`

Message: Failed to save the set of Global Transaction Identifiers of the last binary log into the mysql.gtid_executed table while the server was shutting down. The next server restart will make another attempt to save Global Transaction Identifiers into the table.
`ER_CANT_SAVE_GTIDS` was added in 8.0.2.
- Error number: `MY-010177`; Symbol: `ER_AUTH_CANT_SET_DEFAULT_PLUGIN`; SQLSTATE: `HY000`

Message: Can't start server: Invalid value for --default-authentication-plugin
`ER_AUTH_CANT_SET_DEFAULT_PLUGIN` was added in 8.0.2.
- Error number: `MY-010178`; Symbol: `ER_CANT_JOIN_SHUTDOWN_THREAD`; SQLSTATE: `HY000`

Message: Could not join %sthread. error:%d
`ER_CANT_JOIN_SHUTDOWN_THREAD` was added in 8.0.2.
- Error number: `MY-010179`; Symbol: `ER_CANT_HASH_DO_AND_IGNORE_RULES`; SQLSTATE: `HY000`

Message: An error occurred while building do_table and ignore_table rules to hashes for global replication filter.
`ER_CANT_HASH_DO_AND_IGNORE_RULES` was added in 8.0.2.
- Error number: `MY-010180`; Symbol: `ER_CANT_OPEN_CA`; SQLSTATE: `HY000`

Message: Error opening CA certificate file

`ER_CANT_OPEN_CA` was added in 8.0.2.

- Error number: `MY-010181`; Symbol: `ER_CANT_ACCESS_CAPATH`; SQLSTATE: `HY000`

Message: Error accessing directory pointed by --ssl-capath

`ER_CANT_ACCESS_CAPATH` was added in 8.0.2.

- Error number: `MY-010182`; Symbol: `ER_SSL_TRYING_DATADIR_DEFAULTS`; SQLSTATE: `HY000`

Message: Found %s, %s and %s in data directory. Trying to enable SSL support using them.

`ER_SSL_TRYING_DATADIR_DEFAULTS` was added in 8.0.2.

- Error number: `MY-010183`; Symbol: `ER_AUTO_OPTIONS_FAILED`; SQLSTATE: `HY000`

Message: Failed to create %s(file: '%s', errno %d)

`ER_AUTO_OPTIONS_FAILED` was added in 8.0.2.

- Error number: `MY-010184`; Symbol: `ER_CANT_INIT_TIMER`; SQLSTATE: `HY000`

Message: Failed to initialize timer component (errno %d).

`ER_CANT_INIT_TIMER` was added in 8.0.2.

- Error number: `MY-010185`; Symbol: `ER_SERVERID_TOO_LARGE`; SQLSTATE: `HY000`

Message: server-id configured is too large to represent with server-id-bits configured.

`ER_SERVERID_TOO_LARGE` was added in 8.0.2.

- Error number: `MY-010186`; Symbol: `ER_DEFAULT_SE_UNAVAILABLE`; SQLSTATE: `HY000`

Message: Default%s storage engine (%s) is not available

`ER_DEFAULT_SE_UNAVAILABLE` was added in 8.0.2.

- Error number: `MY-010187`; Symbol: `ER_CANT_OPEN_ERROR_LOG`; SQLSTATE: `HY000`

Message: Could not open file '%s' for error logging%s%s

`ER_CANT_OPEN_ERROR_LOG` was added in 8.0.2.

- Error number: `MY-010188`; Symbol: `ER_INVALID_ERROR_LOG_NAME`; SQLSTATE: `HY000`

Message: Invalid log file name after expanding symlinks: '%s'

`ER_INVALID_ERROR_LOG_NAME` was added in 8.0.2.

- Error number: `MY-010189`; Symbol: `ER_RPL_INFINITY_DENIED`; SQLSTATE: `HY000`

Message: using --replicate-same-server-id in conjunction with --log-replica-updates is impossible, it would lead to infinite loops in this server.

`ER_RPL_INFINITY_DENIED` was added in 8.0.2.

-
- Error number: [MY-010190](#); Symbol: [ER_RPL_INFINITY_IGNORED](#); SQLSTATE: [HY000](#)

Message: using --replicate-same-server-id in conjunction with --log-replica-updates would lead to infinite loops in this server. However this will be ignored as the --log-bin option is not defined or your server is running with global transaction identifiers enabled.

[ER_RPL_INFINITY_IGNORED](#) was added in 8.0.2.
 - Error number: [MY-010191](#); Symbol: [ER_NDB_TABLES_NOT_READY](#); SQLSTATE: [HY000](#)

Message: NDB : Tables not available after %lu seconds. Consider increasing --ndb-wait-setup value

[ER_NDB_TABLES_NOT_READY](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010192](#); Symbol: [ER_TABLE_CHECK_INTACT](#); SQLSTATE: [HY000](#)

Message: %s

[ER_TABLE_CHECK_INTACT](#) was added in 8.0.2.
 - Error number: [MY-010193](#); Symbol: [ER_DD_TABLESPACE_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Unable to start server. The data dictionary tablespace '%s' does not exist.

[ER_DD_TABLESPACE_NOT_FOUND](#) was added in 8.0.2.
 - Error number: [MY-010194](#); Symbol: [ER_DD_TRG_CONNECTION_COLLATION_MISSING](#); SQLSTATE: [HY000](#)

Message: Connection collation is missing for trigger of table %s. Using default connection collation.

[ER_DD_TRG_CONNECTION_COLLATION_MISSING](#) was added in 8.0.2.
 - Error number: [MY-010195](#); Symbol: [ER_DD_TRG_DB_COLLATION_MISSING](#); SQLSTATE: [HY000](#)

Message: Database collation is missing for trigger of table %s. Using Default character set.

[ER_DD_TRG_DB_COLLATION_MISSING](#) was added in 8.0.2.
 - Error number: [MY-010196](#); Symbol: [ER_DD_TRG_DEFINER_OOM](#); SQLSTATE: [HY000](#)

Message: Error in Memory allocation for Definer %s for Trigger.

[ER_DD_TRG_DEFINER_OOM](#) was added in 8.0.2.
 - Error number: [MY-010197](#); Symbol: [ER_DD_TRG_FILE_UNREADABLE](#); SQLSTATE: [HY000](#)

Message: Error in reading %s.TRG file.

[ER_DD_TRG_FILE_UNREADABLE](#) was added in 8.0.2.
 - Error number: [MY-010198](#); Symbol: [ER_TRG_CANT_PARSE](#); SQLSTATE: [HY000](#)

Message: Error in parsing Triggers from %s.TRG file.

[ER_TRG_CANT_PARSE](#) was added in 8.0.2.
 - Error number: [MY-010199](#); Symbol: [ER_DD_TRG_CANT_ADD](#); SQLSTATE: [HY000](#)

Message: Error in creating DD entry for Trigger %s.%s

[ER_DD_TRG_CANT_ADD](#) was added in 8.0.2.
 - Error number: [MY-010200](#); Symbol: [ER_DD_CANT_RESOLVE_VIEW](#); SQLSTATE: [HY000](#)

Message: Resolving dependency for the view '%s.%s' failed. View is no more valid to use
`ER_DD_CANT_RESOLVE_VIEW` was added in 8.0.2.

- Error number: `MY-010201`; Symbol: `ER_DD_VIEW_WITHOUT_DEFINER`; SQLSTATE: `HY000`

Message: %s.%s has no definer (as per an old view format). Current user is used as definer. Please recreate the view.

`ER_DD_VIEW_WITHOUT_DEFINER` was added in 8.0.2.

- Error number: `MY-010202`; Symbol: `ER_PLUGIN_INIT_FAILED`; SQLSTATE: `HY000`

Message: Plugin '%s' init function returned error.

`ER_PLUGIN_INIT_FAILED` was added in 8.0.2.

- Error number: `MY-010203`; Symbol: `ER_RPL_TRX_DELEGATES_INIT_FAILED`; SQLSTATE: `HY000`

Message: Initialization of transaction delegates failed. Please report a bug.

`ER_RPL_TRX_DELEGATES_INIT_FAILED` was added in 8.0.2.

- Error number: `MY-010204`; Symbol: `ER_RPL_BINLOG_STORAGE_DELEGATES_INIT_FAILED`; SQLSTATE: `HY000`

Message: Initialization binlog storage delegates failed. Please report a bug.

`ER_RPL_BINLOG_STORAGE_DELEGATES_INIT_FAILED` was added in 8.0.2.

- Error number: `MY-010205`; Symbol: `ER_RPL_BINLOG_TRANSMIT_DELEGATES_INIT_FAILED`; SQLSTATE: `HY000`

Message: Initialization of binlog transmit delegates failed. Please report a bug.

`ER_RPL_BINLOG_TRANSMIT_DELEGATES_INIT_FAILED` was added in 8.0.2.

- Error number: `MY-010206`; Symbol: `ER_RPL_BINLOG_RELAY_DELEGATES_INIT_FAILED`; SQLSTATE: `HY000`

Message: Initialization binlog relay IO delegates failed. Please report a bug.

`ER_RPL_BINLOG_RELAY_DELEGATES_INIT_FAILED` was added in 8.0.2.

- Error number: `MY-010207`; Symbol: `ER_RPL_PLUGIN_FUNCTION_FAILED`; SQLSTATE: `HY000`

Message: Run function '...' in plugin '%s' failed

`ER_RPL_PLUGIN_FUNCTION_FAILED` was added in 8.0.2.

- Error number: `MY-010208`; Symbol: `ER_SQL_HA_READ_FAILED`; SQLSTATE: `HY000`

Message: mysql_ha_read: Got error %d when reading table '%s'

`ER_SQL_HA_READ_FAILED` was added in 8.0.2.

- Error number: `MY-010209`; Symbol: `ER_SR_BOGUS_VALUE`; SQLSTATE: `HY000`

Message: Stored routine '%s'.'%s': invalid value in column %s.

`ER_SR_BOGUS_VALUE` was added in 8.0.2.

-
- Error number: `MY-010210`; Symbol: `ER_SR_INVALID_CONTEXT`; SQLSTATE: `HY000`
Message: Invalid creation context '%s.%s'.
`ER_SR_INVALID_CONTEXT` was added in 8.0.2.
 - Error number: `MY-010211`; Symbol: `ER_READING_TABLE_FAILED`; SQLSTATE: `HY000`
Message: Got error %d when reading table '%s'
`ER_READING_TABLE_FAILED` was added in 8.0.2.
 - Error number: `MY-010212`; Symbol: `ER_DES_FILE_WRONG_KEY`; SQLSTATE: `HY000`
Message: load_des_file: Found wrong key_number: %c
`ER_DES_FILE_WRONG_KEY` was added in 8.0.2.
 - Error number: `MY-010213`; Symbol: `ER_CANT_SET_PERSISTED`; SQLSTATE: `HY000`
Message: Failed to set persisted options.
`ER_CANT_SET_PERSISTED` was added in 8.0.2.
 - Error number: `MY-010214`; Symbol: `ER_JSON_PARSE_ERROR`; SQLSTATE: `HY000`
Message: Persisted config file is corrupt. Please ensure mysqld-auto.cnf file is valid JSON.
`ER_JSON_PARSE_ERROR` was added in 8.0.2.
 - Error number: `MY-010215`; Symbol: `ER_CONFIG_OPTION_WITHOUT_GROUP`; SQLSTATE: `HY000`
Message: Found option without preceding group in config file
`ER_CONFIG_OPTION_WITHOUT_GROUP` was added in 8.0.2.
 - Error number: `MY-010216`; Symbol: `ER_VALGRIND_DO_QUICK_LEAK_CHECK`; SQLSTATE: `HY000`
Message: VALGRIND_DO_QUICK_LEAK_CHECK
`ER_VALGRIND_DO_QUICK_LEAK_CHECK` was added in 8.0.2.
 - Error number: `MY-010217`; Symbol: `ER_VALGRIND_COUNT_LEAKS`; SQLSTATE: `HY000`
Message: VALGRIND_COUNT_LEAKS reports %lu leaked bytes for query '%.*s'
`ER_VALGRIND_COUNT_LEAKS` was added in 8.0.2.
 - Error number: `MY-010218`; Symbol: `ER_LOAD_DATA_INFILE_FAILED_IN_UNEXPECTED WAY`; SQLSTATE: `HY000`
Message: LOAD DATA INFILE in the slave SQL Thread can only read from --replica-load-tmpdir.
Please, report a bug.
`ER_LOAD_DATA_INFILE_FAILED_IN_UNEXPECTED WAY` was added in 8.0.2.
 - Error number: `MY-010219`; Symbol: `ER_UNKNOWN_ERROR_NUMBER`; SQLSTATE: `HY000`
Message: Got unknown error: %d
`ER_UNKNOWN_ERROR_NUMBER` was added in 8.0.2.
 - Error number: `MY-010220`; Symbol: `ER_UDF_CANT_ALLOC_FOR_STRUCTURES`; SQLSTATE: `HY000`

Message: Can't allocate memory for udf structures

`ER_UDF_CANT_ALLOC_FOR_STRUCTURES` was added in 8.0.2.

- Error number: `MY-010221`; Symbol: `ER_UDF_CANT_ALLOC_FOR_FUNCTION`; SQLSTATE: `HY000`

Message: Can't alloc memory for udf function: '%s'

`ER_UDF_CANT_ALLOC_FOR_FUNCTION` was added in 8.0.2.

- Error number: `MY-010222`; Symbol: `ER_UDF_INVALID_ROW_IN_FUNCTION_TABLE`; SQLSTATE: `HY000`

Message: Invalid row in mysql.func table for function '%s'

`ER_UDF_INVALID_ROW_IN_FUNCTION_TABLE` was added in 8.0.2.

- Error number: `MY-010223`; Symbol: `ER_UDF_CANT_OPEN_FUNCTION_TABLE`; SQLSTATE: `HY000`

Message: Could not open the mysql.func table. Please perform the MySQL upgrade procedure.

`ER_UDF_CANT_OPEN_FUNCTION_TABLE` was added in 8.0.2.

- Error number: `MY-010224`; Symbol: `ER_XA_RECOVER_FOUND_TRX_IN_SE`; SQLSTATE: `HY000`

Message: Found %d prepared transaction(s) in %s

`ER_XA_RECOVER_FOUND_TRX_IN_SE` was added in 8.0.2.

- Error number: `MY-010225`; Symbol: `ER_XA_RECOVER_FOUND_XA_TRX`; SQLSTATE: `HY000`

Message: Found %d prepared XA transactions

`ER_XA_RECOVER_FOUND_XA_TRX` was added in 8.0.2.

- Error number: `MY-010226`; Symbol: `ER_XA_IGNORING_XID`; SQLSTATE: `HY000`

Message: ignore xid %s

`ER_XA_IGNORING_XID` was added in 8.0.2.

- Error number: `MY-010227`; Symbol: `ER_XA_COMMITTING_XID`; SQLSTATE: `HY000`

Message: commit xid %s

`ER_XA_COMMITTING_XID` was added in 8.0.2.

- Error number: `MY-010228`; Symbol: `ER_XA_ROLLING_BACK_XID`; SQLSTATE: `HY000`

Message: rollback xid %s

`ER_XA_ROLLING_BACK_XID` was added in 8.0.2.

- Error number: `MY-010229`; Symbol: `ER_XA_STARTING_RECOVERY`; SQLSTATE: `HY000`

Message: Starting XA crash recovery...

`ER_XA_STARTING_RECOVERY` was added in 8.0.2.

-
- Error number: [MY-010230](#); Symbol: [ER_XA_NO_MULTI_2PC_HEURISTIC_RECOVER](#); SQLSTATE: [HY000](#)

Message: --tc-heuristic-recover rollback strategy is not safe on systems with more than one 2-phase-commit-capable storage engine. Aborting crash recovery.

[ER_XA_NO_MULTI_2PC_HEURISTIC_RECOVER](#) was added in 8.0.2.

- Error number: [MY-010231](#); Symbol: [ER_XA_RECOVER_EXPLANATION](#); SQLSTATE: [HY000](#)

Message: Found %d prepared transactions! It means that mysqld was not shut down properly last time and critical recovery information (last binlog or %s file) was manually deleted after a crash. You have to start mysqld with --tc-heuristic-recover switch to commit or rollback pending transactions.

[ER_XA_RECOVER_EXPLANATION](#) was added in 8.0.2.

- Error number: [MY-010232](#); Symbol: [ER_XA_RECOVERY_DONE](#); SQLSTATE: [HY000](#)

Message: XA crash recovery finished.

[ER_XA_RECOVERY_DONE](#) was added in 8.0.2.

- Error number: [MY-010233](#); Symbol: [ER_TRX_GTID_COLLECT_REJECT](#); SQLSTATE: [HY000](#)

Message: Failed to collect GTID to send in the response packet!

[ER_TRX_GTID_COLLECT_REJECT](#) was added in 8.0.2.

- Error number: [MY-010234](#); Symbol: [ER_SQL_AUTHOR_DEFAULT_ROLES_FAIL](#); SQLSTATE: [HY000](#)

Message: MYSQL.DEFAULT_ROLES couldn't be updated for authorization identifier %s

[ER_SQL_AUTHOR_DEFAULT_ROLES_FAIL](#) was added in 8.0.2.

- Error number: [MY-010235](#); Symbol: [ER_SQL_USER_TABLE_CREATE_WARNING](#); SQLSTATE: [HY000](#)

Message: Following users were specified in CREATE USER IF NOT EXISTS but they already exist. Corresponding entry in binary log used default authentication plugin '%s' to rewrite authentication information (if any) for them: %s

[ER_SQL_USER_TABLE_CREATE_WARNING](#) was added in 8.0.2.

- Error number: [MY-010236](#); Symbol: [ER_SQL_USER_TABLE_ALTER_WARNING](#); SQLSTATE: [HY000](#)

Message: Following users were specified in ALTER USER IF EXISTS but they do not exist. Corresponding entry in binary log used default authentication plugin '%s' to rewrite authentication information (if any) for them: %s

[ER_SQL_USER_TABLE_ALTER_WARNING](#) was added in 8.0.2.

- Error number: [MY-010237](#); Symbol: [ER_ROW_IN_WRONG_PARTITION PLEASE_REPAIR](#); SQLSTATE: [HY000](#)

Message: Table '%s' corrupted: row in wrong partition: %s -- Please REPAIR the table!

[ER_ROW_IN_WRONG_PARTITION PLEASE_REPAIR](#) was added in 8.0.2.

- Error number: [MY-010238](#); Symbol: [ER_MYISAM_CRASHED_ERROR_IN_THREAD](#); SQLSTATE: [HY000](#)

Message: Got an error from thread_id=%u, %s:%d

`ER_MYISAM_CRASHED_ERROR_IN_THREAD` was added in 8.0.2.

- Error number: `MY-010239`; Symbol: `ER_MYISAM_CRASHED_ERROR_IN`; SQLSTATE: `HY000`

Message: Got an error from unknown thread, %s:%d

`ER_MYISAM_CRASHED_ERROR_IN` was added in 8.0.2.

- Error number: `MY-010240`; Symbol: `ER_TOO_MANY_STORAGE_ENGINES`; SQLSTATE: `HY000`

Message: Too many storage engines!

`ER_TOO_MANY_STORAGE_ENGINES` was added in 8.0.2.

- Error number: `MY-010241`; Symbol: `ER_SE_TYPECODE_CONFLICT`; SQLSTATE: `HY000`

Message: Storage engine '%s' has conflicting typecode. Assigning value %d.

`ER_SE_TYPECODE_CONFLICT` was added in 8.0.2.

- Error number: `MY-010242`; Symbol: `ER_TRX_WRITE_SET_OOM`; SQLSTATE: `HY000`

Message: Out of memory on transaction write set extraction

`ER_TRX_WRITE_SET_OOM` was added in 8.0.2.

- Error number: `MY-010243`; Symbol: `ER_HANDLERTON_OOM`; SQLSTATE: `HY000`

Message: Unable to allocate memory for plugin '%s' handlerton.

`ER_HANDLERTON_OOM` was added in 8.0.2.

- Error number: `MY-010244`; Symbol: `ER_CONN_SHM_LISTENER`; SQLSTATE: `HY000`

Message: Shared memory setting up listener

`ER_CONN_SHM_LISTENER` was added in 8.0.2.

- Error number: `MY-010245`; Symbol: `ER_CONN_SHM_CANT_CREATE_SERVICE`; SQLSTATE: `HY000`

Message: Can't create shared memory service: %s. : %s

`ER_CONN_SHM_CANT_CREATE_SERVICE` was added in 8.0.2.

- Error number: `MY-010246`; Symbol: `ER_CONN_SHM_CANT_CREATE_CONNECTION`; SQLSTATE: `HY000`

Message: Can't create shared memory connection: %s. : %s

`ER_CONN_SHM_CANT_CREATE_CONNECTION` was added in 8.0.2.

- Error number: `MY-010247`; Symbol: `ER_CONN_PIP_CANT_CREATE_EVENT`; SQLSTATE: `HY000`

Message: Can't create event, last error=%u

`ER_CONN_PIP_CANT_CREATE_EVENT` was added in 8.0.2.

- Error number: `MY-010248`; Symbol: `ER_CONN_PIP_CANT_CREATE_PIPE`; SQLSTATE: `HY000`

Message: Can't create new named pipe!: %s

`ER_CONN_PIP_CANT_CREATE_PIPE` was added in 8.0.2.

- Error number: `MY-010249`; Symbol: `ER_CONN_PER_THREAD_NO_THREAD`; SQLSTATE: `HY000`

Message: Can't create thread to handle new connection(errno= %d)

`ER_CONN_PER_THREAD_NO_THREAD` was added in 8.0.2.

- Error number: `MY-010250`; Symbol: `ER_CONN_TCP_NO_SOCKET`; SQLSTATE: `HY000`

Message: Failed to create a socket for %s '%s': errno: %d.

`ER_CONN_TCP_NO_SOCKET` was added in 8.0.2.

- Error number: `MY-010251`; Symbol: `ER_CONN_TCP_CREATED`; SQLSTATE: `HY000`

Message: Server socket created on IP: '%s'.

`ER_CONN_TCP_CREATED` was added in 8.0.2.

- Error number: `MY-010252`; Symbol: `ER_CONN_TCP_ADDRESS`; SQLSTATE: `HY000`

Message: Server hostname (bind-address): '%s'; port: %d

`ER_CONN_TCP_ADDRESS` was added in 8.0.2.

- Error number: `MY-010253`; Symbol: `ER_CONN_TCP_IPV6_AVAILABLE`; SQLSTATE: `HY000`

Message: IPv6 is available.

`ER_CONN_TCP_IPV6_AVAILABLE` was added in 8.0.2.

- Error number: `MY-010254`; Symbol: `ER_CONN_TCP_IPV6_UNAVAILABLE`; SQLSTATE: `HY000`

Message: IPv6 is not available.

`ER_CONN_TCP_IPV6_UNAVAILABLE` was added in 8.0.2.

- Error number: `MY-010255`; Symbol: `ER_CONN_TCP_ERROR_WITH_STRERROR`; SQLSTATE: `HY000`

Message: Can't create IP socket: %s

`ER_CONN_TCP_ERROR_WITH_STRERROR` was added in 8.0.2.

- Error number: `MY-010256`; Symbol: `ER_CONN_TCP_CANT_RESOLVE_HOSTNAME`; SQLSTATE: `HY000`

Message: Can't start server: cannot resolve hostname!

`ER_CONN_TCP_CANT_RESOLVE_HOSTNAME` was added in 8.0.2.

- Error number: `MY-010257`; Symbol: `ER_CONN_TCP_IS THERE_ANOTHER_USING_PORT`; SQLSTATE: `HY000`

Message: Do you already have another mysqld server running on port: %d ?

`ER_CONN_TCP_IS THERE_ANOTHER_USING_PORT` was added in 8.0.2.

- Error number: `MY-010258`; Symbol: `ER_CONN_UNIX_IS THERE_ANOTHER_USING_SOCKET`; SQLSTATE: `HY000`

Message: Do you already have another mysqld server running on socket: %s ?

`ER_CONN_UNIX_IS THERE_ANOTHER_USING_SOCKET` was added in 8.0.2.

- Error number: `MY-010259`; Symbol: `ER_CONN_UNIX_PID_CLAIMED_SOCKET_FILE`; SQLSTATE: `HY000`

Message: Another process with pid %d is using unix socket file.

`ER_CONN_UNIX_PID_CLAIMED_SOCKET_FILE` was added in 8.0.2.

- Error number: `MY-010260`; Symbol: `ER_CONN_TCP_CANT_RESET_V6ONLY`; SQLSTATE: `HY000`

Message: Failed to reset IPV6_V6ONLY flag (error: %d). The server will listen to IPv6 addresses only.

`ER_CONN_TCP_CANT_RESET_V6ONLY` was added in 8.0.2.

- Error number: `MY-010261`; Symbol: `ER_CONN_TCP_BIND_RETRY`; SQLSTATE: `HY000`

Message: Retrying bind on TCP/IP port %u

`ER_CONN_TCP_BIND_RETRY` was added in 8.0.2.

- Error number: `MY-010262`; Symbol: `ER_CONN_TPC_BIND_FAIL`; SQLSTATE: `HY000`

Message: Can't start server: Bind on TCP/IP port: %s

`ER_CONN_TPC_BIND_FAIL` was added in 8.0.2, removed after 8.0.11.

- Error number: `MY-010262`; Symbol: `ER_CONN_TCP_BIND_FAIL`; SQLSTATE: `HY000`

Message: Can't start server: Bind on TCP/IP port: %s

`ER_CONN_TCP_BIND_FAIL` was added in 8.0.12.

- Error number: `MY-010263`; Symbol: `ER_CONN_TCP_IP_NOT_LOGGED`; SQLSTATE: `HY000`

Message: Fails to print out IP-address.

`ER_CONN_TCP_IP_NOT_LOGGED` was added in 8.0.2.

- Error number: `MY-010264`; Symbol: `ER_CONN_TCP_RESOLVE_INFO`; SQLSTATE: `HY000`

Message: - '%s' resolves to '%s';

`ER_CONN_TCP_RESOLVE_INFO` was added in 8.0.2.

- Error number: `MY-010265`; Symbol: `ER_CONN_TCP_START_FAIL`; SQLSTATE: `HY000`

Message: Can't start server: listen() on TCP/IP port: %s

`ER_CONN_TCP_START_FAIL` was added in 8.0.2.

- Error number: `MY-010266`; Symbol: `ER_CONN_TCP_LISTEN_FAIL`; SQLSTATE: `HY000`

Message: listen() on TCP/IP failed with error %d

`ER_CONN_TCP_LISTEN_FAIL` was added in 8.0.2.

- Error number: `MY-010267`; Symbol: `ER_CONN_UNIX_PATH_TOO_LONG`; SQLSTATE: `HY000`

Message: The socket file path is too long (> %u): %s

`ER_CONN_UNIX_PATH_TOO_LONG` was added in 8.0.2.

- Error number: `MY-010268`; Symbol: `ER_CONN_UNIX_LOCK_FILE_FAIL`; SQLSTATE: `HY000`

Message: Unable to setup unix socket lock file.

`ER_CONN_UNIX_LOCK_FILE_FAIL` was added in 8.0.2.

- Error number: `MY-010269`; Symbol: `ER_CONN_UNIX_NO_FD`; SQLSTATE: `HY000`
Message: Can't start server: UNIX Socket : %s
`ER_CONN_UNIX_NO_FD` was added in 8.0.2.
- Error number: `MY-010270`; Symbol: `ER_CONN_UNIX_NO_BIND_NO_START`; SQLSTATE: `HY000`
Message: Can't start server : Bind on unix socket: %s
`ER_CONN_UNIX_NO_BIND_NO_START` was added in 8.0.2.
- Error number: `MY-010271`; Symbol: `ER_CONN_UNIX_LISTEN_FAILED`; SQLSTATE: `HY000`
Message: listen() on Unix socket failed with error %d
`ER_CONN_UNIX_LISTEN_FAILED` was added in 8.0.2.
- Error number: `MY-010272`; Symbol: `ER_CONN_UNIX_LOCK_FILE_GIVING_UP`; SQLSTATE: `HY000`
Message: Unable to create unix socket lock file %s after retries.
`ER_CONN_UNIX_LOCK_FILE_GIVING_UP` was added in 8.0.2.
- Error number: `MY-010273`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_CREATE`; SQLSTATE: `HY000`
Message: Could not create unix socket lock file %s.
`ER_CONN_UNIX_LOCK_FILE_CANT_CREATE` was added in 8.0.2.
- Error number: `MY-010274`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_OPEN`; SQLSTATE: `HY000`
Message: Could not open unix socket lock file %s.
`ER_CONN_UNIX_LOCK_FILE_CANT_OPEN` was added in 8.0.2.
- Error number: `MY-010275`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_READ`; SQLSTATE: `HY000`
Message: Could not read unix socket lock file %s.
`ER_CONN_UNIX_LOCK_FILE_CANT_READ` was added in 8.0.2.
- Error number: `MY-010276`; Symbol: `ER_CONN_UNIX_LOCK_FILE_EMPTY`; SQLSTATE: `HY000`
Message: Unix socket lock file is empty %s.
`ER_CONN_UNIX_LOCK_FILE_EMPTY` was added in 8.0.2.
- Error number: `MY-010277`; Symbol: `ER_CONN_UNIX_LOCK_FILE_PIDLESS`; SQLSTATE: `HY000`
Message: Invalid pid in unix socket lock file %s.
`ER_CONN_UNIX_LOCK_FILE_PIDLESS` was added in 8.0.2.
- Error number: `MY-010278`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_WRITE`; SQLSTATE: `HY000`
Message: Could not write unix socket lock file %s errno %d.
`ER_CONN_UNIX_LOCK_FILE_CANT_WRITE` was added in 8.0.2.

- Error number: [MY-010279](#); Symbol: [ER_CONN_UNIX_LOCK_FILE_CANT_DELETE](#); SQLSTATE: [HY000](#)

Message: Could not remove unix socket lock file %s errno %d.
[ER_CONN_UNIX_LOCK_FILE_CANT_DELETE](#) was added in 8.0.2.
- Error number: [MY-010280](#); Symbol: [ER_CONN_UNIX_LOCK_FILE_CANT_SYNC](#); SQLSTATE: [HY000](#)

Message: Could not sync unix socket lock file %s errno %d.
[ER_CONN_UNIX_LOCK_FILE_CANT_SYNC](#) was added in 8.0.2.
- Error number: [MY-010281](#); Symbol: [ER_CONN_UNIX_LOCK_FILE_CANT_CLOSE](#); SQLSTATE: [HY000](#)

Message: Could not close unix socket lock file %s errno %d.
[ER_CONN_UNIX_LOCK_FILE_CANT_CLOSE](#) was added in 8.0.2.
- Error number: [MY-010282](#); Symbol: [ER_CONN_SOCKET_SELECT_FAILED](#); SQLSTATE: [HY000](#)

Message: mysqld: Got error %d from select
[ER_CONN_SOCKET_SELECT_FAILED](#) was added in 8.0.2.
- Error number: [MY-010283](#); Symbol: [ER_CONN_SOCKET_ACCEPT_FAILED](#); SQLSTATE: [HY000](#)

Message: Error in accept: %s
[ER_CONN_SOCKET_ACCEPT_FAILED](#) was added in 8.0.2.
- Error number: [MY-010284](#); Symbol: [ER_AUTH_RSA_CANT_FIND](#); SQLSTATE: [HY000](#)

Message: RSA %s key file not found: %s. Some authentication plugins will not work.
[ER_AUTH_RSA_CANT_FIND](#) was added in 8.0.2.
- Error number: [MY-010285](#); Symbol: [ER_AUTH_RSA_CANT_PARSE](#); SQLSTATE: [HY000](#)

Message: Failure to parse RSA %s key (file exists): %s: %s
[ER_AUTH_RSA_CANT_PARSE](#) was added in 8.0.2.
- Error number: [MY-010286](#); Symbol: [ER_AUTH_RSA_CANT_READ](#); SQLSTATE: [HY000](#)

Message: Failure to read key file: %s
[ER_AUTH_RSA_CANT_READ](#) was added in 8.0.2.
- Error number: [MY-010287](#); Symbol: [ER_AUTH_RSA_FILES_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: RSA key files not found. Some authentication plugins will not work.
[ER_AUTH_RSA_FILES_NOT_FOUND](#) was added in 8.0.2.
- Error number: [MY-010288](#); Symbol: [ER_CONN_ATTR_TRUNCATED](#); SQLSTATE: [HY000](#)

Message: Connection attributes of length %lu were truncated (%d bytes lost) for connection %llu, user %s@%s (as %s), auth: %s
[ER_CONN_ATTR_TRUNCATED](#) was added in 8.0.2.

-
- Error number: `MY-010289`; Symbol: `ER_X509_CIPHERS_MISMATCH`; SQLSTATE: `HY000`
Message: X.509 ciphers mismatch: should be '%s' but is '%s'
`ER_X509_CIPHERS_MISMATCH` was added in 8.0.2.
 - Error number: `MY-010290`; Symbol: `ER_X509_ISSUER_MISMATCH`; SQLSTATE: `HY000`
Message: X.509 issuer mismatch: should be '%s' but is '%s'
`ER_X509_ISSUER_MISMATCH` was added in 8.0.2.
 - Error number: `MY-010291`; Symbol: `ER_X509_SUBJECT_MISMATCH`; SQLSTATE: `HY000`
Message: X.509 subject mismatch: should be '%s' but is '%s'
`ER_X509_SUBJECT_MISMATCH` was added in 8.0.2.
 - Error number: `MY-010292`; Symbol: `ER_AUTH_CANT_ACTIVATE_ROLE`; SQLSTATE: `HY000`
Message: Failed to activate default role %s for %s
`ER_AUTH_CANT_ACTIVATE_ROLE` was added in 8.0.2.
 - Error number: `MY-010293`; Symbol: `ER_X509_NEEDS_RSA_PRIVKEY`; SQLSTATE: `HY000`
Message: Could not generate RSA private key required for X.509 certificate.
`ER_X509_NEEDS_RSA_PRIVKEY` was added in 8.0.2.
 - Error number: `MY-010294`; Symbol: `ER_X509_CANT_WRITE_KEY`; SQLSTATE: `HY000`
Message: Could not write key file: %s
`ER_X509_CANT_WRITE_KEY` was added in 8.0.2.
 - Error number: `MY-010295`; Symbol: `ER_X509_CANT_CHMOD_KEY`; SQLSTATE: `HY000`
Message: Could not set file permission for %s
`ER_X509_CANT_CHMOD_KEY` was added in 8.0.2.
 - Error number: `MY-010296`; Symbol: `ER_X509_CANT_READ_CA_KEY`; SQLSTATE: `HY000`
Message: Could not read CA key file: %s
`ER_X509_CANT_READ_CA_KEY` was added in 8.0.2.
 - Error number: `MY-010297`; Symbol: `ER_X509_CANT_READ_CA_CERT`; SQLSTATE: `HY000`
Message: Could not read CA certificate file: %s
`ER_X509_CANT_READ_CA_CERT` was added in 8.0.2.
 - Error number: `MY-010298`; Symbol: `ER_X509_CANT_CREATE_CERT`; SQLSTATE: `HY000`
Message: Could not generate X.509 certificate.
`ER_X509_CANT_CREATE_CERT` was added in 8.0.2.
 - Error number: `MY-010299`; Symbol: `ER_X509_CANT_WRITE_CERT`; SQLSTATE: `HY000`
Message: Could not write certificate file: %s
`ER_X509_CANT_WRITE_CERT` was added in 8.0.2.

- Error number: [MY-010300](#); Symbol: [ER_AUTH_CANT_CREATE_RSA_PAIR](#); SQLSTATE: [HY000](#)

Message: Could not generate RSA Private/Public key pair
[ER_AUTH_CANT_CREATE_RSA_PAIR](#) was added in 8.0.2.
- Error number: [MY-010301](#); Symbol: [ER_AUTH_CANT_WRITE_PRIVKEY](#); SQLSTATE: [HY000](#)

Message: Could not write private key file: %s
[ER_AUTH_CANT_WRITE_PRIVKEY](#) was added in 8.0.2.
- Error number: [MY-010302](#); Symbol: [ER_AUTH_CANT_WRITE_PUBKEY](#); SQLSTATE: [HY000](#)

Message: Could not write public key file: %s
[ER_AUTH_CANT_WRITE_PUBKEY](#) was added in 8.0.2.
- Error number: [MY-010303](#); Symbol: [ER_AUTH_SSL_CONF_PREVENTS_CERT_GENERATION](#); SQLSTATE: [HY000](#)

Message: Skipping generation of SSL certificates as options related to SSL are specified.
[ER_AUTH_SSL_CONF_PREVENTS_CERT_GENERATION](#) was added in 8.0.2.
- Error number: [MY-010304](#); Symbol: [ER_AUTH_USING_EXISTING_CERTS](#); SQLSTATE: [HY000](#)

Message: Skipping generation of SSL certificates as certificate files are present in data directory.
[ER_AUTH_USING_EXISTING_CERTS](#) was added in 8.0.2.
- Error number: [MY-010305](#); Symbol: [ER_AUTH_CERTS_SAVED_TO_DATADIR](#); SQLSTATE: [HY000](#)

Message: Auto generated SSL certificates are placed in data directory.
[ER_AUTH_CERTS_SAVED_TO_DATADIR](#) was added in 8.0.2.
- Error number: [MY-010306](#); Symbol: [ER_AUTH_CERT_GENERATION_DISABLED](#); SQLSTATE: [HY000](#)

Message: Skipping generation of SSL certificates as --auto_generate_certs is set to OFF.
[ER_AUTH_CERT_GENERATION_DISABLED](#) was added in 8.0.2.
- Error number: [MY-010307](#); Symbol: [ER_AUTH_RSA_CONF_PREVENTS_KEY_GENERATION](#); SQLSTATE: [HY000](#)

Message: Skipping generation of RSA key pair through %s as options related to RSA keys are specified.
[ER_AUTH_RSA_CONF_PREVENTS_KEY_GENERATION](#) was added in 8.0.2.
- Error number: [MY-010308](#); Symbol: [ER_AUTH_KEY_GENERATION_SKIPPED_PAIR_PRESENT](#); SQLSTATE: [HY000](#)

Message: Skipping generation of RSA key pair through %s as key files are present in data directory.
[ER_AUTH_KEY_GENERATION_SKIPPED_PAIR_PRESENT](#) was added in 8.0.2.
- Error number: [MY-010309](#); Symbol: [ER_AUTH_KEYS_SAVED_TO_DATADIR](#); SQLSTATE: [HY000](#)

Message: Auto generated RSA key files through %s are placed in data directory.
[ER_AUTH_KEYS_SAVED_TO_DATADIR](#) was added in 8.0.2.

-
- Error number: [MY-010310](#); Symbol: [ER_AUTH_KEY_GENERATION_DISABLED](#); SQLSTATE: [HY000](#)

Message: Skipping generation of RSA key pair as %s is set to OFF.
[ER_AUTH_KEY_GENERATION_DISABLED](#) was added in 8.0.2.
 - Error number: [MY-010311](#); Symbol: [ER_AUTHCACHE_PROXY_PRIV_SKIPPED_NEEDS_RESOLVE](#); SQLSTATE: [HY000](#)

Message: 'proxies_priv' entry '%s@%s %s@%s' ignored in --skip-name-resolve mode.
[ER_AUTHCACHE_PROXY_PRIV_SKIPPED_NEEDS_RESOLVE](#) was added in 8.0.2.
 - Error number: [MY-010312](#); Symbol: [ER_AUTHCACHE_PLUGIN_MISSING](#); SQLSTATE: [HY000](#)

Message: The plugin '%.*s' used to authenticate user '%s'@'%.*s' is not loaded. Nobody can currently login using this account.
[ER_AUTHCACHE_PLUGIN_MISSING](#) was added in 8.0.2.
 - Error number: [MY-010313](#); Symbol: [ER_AUTHCACHE_PLUGIN_CONFIG](#); SQLSTATE: [HY000](#)

Message: The plugin '%s' is used to authenticate user '%s'@'%.*s', %s configured. Nobody can currently login using this account.
[ER_AUTHCACHE_PLUGIN_CONFIG](#) was added in 8.0.2.
 - Error number: [MY-010314](#); Symbol: [ER_AUTHCACHE_ROLE_TABLES_DODGY](#); SQLSTATE: [HY000](#)

Message: Could not load mysql.role_edges and mysql.default_roles tables. ACL DDLs will not work unless mysql_upgrade is executed.
[ER_AUTHCACHE_ROLE_TABLES_DODGY](#) was added in 8.0.2, removed after 8.0.4.
 - Error number: [MY-010315](#); Symbol: [ER_AUTHCACHE_USER_SKIPPED_NEEDS_RESOLVE](#); SQLSTATE: [HY000](#)

Message: 'user' entry '%s@%s' ignored in --skip-name-resolve mode.
[ER_AUTHCACHE_USER_SKIPPED_NEEDS_RESOLVE](#) was added in 8.0.2.
 - Error number: [MY-010316](#); Symbol: [ER_AUTHCACHE_USER_TABLE_DODGY](#); SQLSTATE: [HY000](#)

Message: Fatal error: Could not read the column 'authentication_string' from table 'mysql.user'. Please perform the MySQL upgrade procedure.
[ER_AUTHCACHE_USER_TABLE_DODGY](#) was added in 8.0.2.
 - Error number: [MY-010317](#); Symbol: [ER_AUTHCACHE_USER_IGNORED_DEPRECATED_PASSWORD](#); SQLSTATE: [HY000](#)

Message: User entry '%s'@'%s' has a deprecated pre-4.1 password. The user will be ignored and no one can login with this user anymore.
[ER_AUTHCACHE_USER_IGNORED_DEPRECATED_PASSWORD](#) was added in 8.0.2.
 - Error number: [MY-010318](#); Symbol: [ER_AUTHCACHE_USER_IGNORED_NEEDS_PLUGIN](#); SQLSTATE: [HY000](#)

Message: User entry '%s'@'%s' has an empty plugin value. The user will be ignored and no one can login with this user anymore.
[ER_AUTHCACHE_USER_IGNORED_NEEDS_PLUGIN](#) was added in 8.0.2.

- Error number: [MY-010319](#); Symbol: [ER_AUTHCACHE_USER_IGNORED_INVALID_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Found invalid password for user: '%s@%s'; Ignoring user
[ER_AUTHCACHE_USER_IGNORED_INVALID_PASSWORD](#) was added in 8.0.2.
- Error number: [MY-010320](#); Symbol: [ER_AUTHCACHE_EXPIRED_PASSWORD_UNSUPPORTED](#); SQLSTATE: [HY000](#)

Message: 'user' entry '%s@%s' has the password ignore flag raised, but its authentication plugin doesn't support password expiration. The user id will be ignored.
[ER_AUTHCACHE_EXPIRED_PASSWORD_UNSUPPORTED](#) was added in 8.0.2.
- Error number: [MY-010321](#); Symbol: [ER_NO_SUPER_WITHOUT_USER_PLUGIN](#); SQLSTATE: [HY000](#)

Message: Some of the user accounts with SUPER privileges were disabled because of empty mysql.user.plugin value. If you are upgrading from MySQL 5.6 to MySQL 5.7 it means that substitution for the empty plugin column was not possible. Probably because of pre 4.1 password hash. If your account is disabled you will need to perform the MySQL upgrade procedure. For complete instructions on how to upgrade MySQL to a new version please see the 'Upgrading MySQL' section from the MySQL manual.
[ER_NO_SUPER_WITHOUT_USER_PLUGIN](#) was added in 8.0.2.
- Error number: [MY-010322](#); Symbol: [ER_AUTHCACHE_DB_IGNORED_EMPTY_NAME](#); SQLSTATE: [HY000](#)

Message: Found an entry in the 'db' table with empty database name; Skipped
[ER_AUTHCACHE_DB_IGNORED_EMPTY_NAME](#) was added in 8.0.2.
- Error number: [MY-010323](#); Symbol: [ER_AUTHCACHE_DB_SKIPPED_NEEDS_RESOLVE](#); SQLSTATE: [HY000](#)

Message: 'db' entry '%s %s@%s' ignored in --skip-name-resolve mode.
[ER_AUTHCACHE_DB_SKIPPED_NEEDS_RESOLVE](#) was added in 8.0.2.
- Error number: [MY-010324](#); Symbol:
[ER_AUTHCACHE_DB_ENTRY_LOWERCASED_REVOKE_WILL_FAIL](#); SQLSTATE: [HY000](#)

Message: 'db' entry '%s %s@%s' had database in mixed case that has been forced to lowercase because lower_case_table_names is set. It will not be possible to remove this privilege using REVOKE.
[ER_AUTHCACHE_DB_ENTRY_LOWERCASED_REVOKE_WILL_FAIL](#) was added in 8.0.2.
- Error number: [MY-010325](#); Symbol: [ER_AUTHCACHE_TABLE_PROXY_PRIV_MISSING](#); SQLSTATE: [HY000](#)

Message: The system table mysql.proxies_priv is missing. Please perform the MySQL upgrade procedure.
[ER_AUTHCACHE_TABLE_PROXY_PRIV_MISSING](#) was added in 8.0.2.
- Error number: [MY-010326](#); Symbol:
[ER_AUTHCACHE_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES](#); SQLSTATE: [HY000](#)

Message: Fatal error: Can't open and lock privilege tables: %s
[ER_AUTHCACHE_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES](#) was added in 8.0.2.

-
- Error number: [MY-010327](#); Symbol: [ER_AUTHCACHE_CANT_INIT_GRANT_SUBSYSTEM](#); SQLSTATE: [HY000](#)

Message: Fatal: can't initialize grant subsystem - '%s'
[ER_AUTHCACHE_CANT_INIT_GRANT_SUBSYSTEM](#) was added in 8.0.2.
 - Error number: [MY-010328](#); Symbol: [ER_AUTHCACHE_PROCS_PRIV_SKIPPED_NEEDS_RESOLVE](#); SQLSTATE: [HY000](#)

Message: 'procs_priv' entry '%s %s@%s' ignored in --skip-name-resolve mode.
[ER_AUTHCACHE_PROCS_PRIV_SKIPPED_NEEDS_RESOLVE](#) was added in 8.0.2.
 - Error number: [MY-010329](#); Symbol: [ER_AUTHCACHE_PROCS_PRIV_ENTRY_IGNORED_BAD_ROUTINE_TYPE](#); SQLSTATE: [HY000](#)

Message: 'procs_priv' entry '%s' ignored, bad routine type
[ER_AUTHCACHE_PROCS_PRIV_ENTRY_IGNORED_BAD_ROUTINE_TYPE](#) was added in 8.0.2.
 - Error number: [MY-010330](#); Symbol: [ER_AUTHCACHE_TABLES_PRIV_SKIPPED_NEEDS_RESOLVE](#); SQLSTATE: [HY000](#)

Message: 'tables_priv' entry '%s %s@%s' ignored in --skip-name-resolve mode.
[ER_AUTHCACHE_TABLES_PRIV_SKIPPED_NEEDS_RESOLVE](#) was added in 8.0.2.
 - Error number: [MY-010331](#); Symbol: [ER_USER_NOT_IN_EXTRA_USERS_BINLOG_POSSIBLY_INCOMPLETE](#); SQLSTATE: [HY000](#)

Message: Failed to add %s in extra_users. Binary log entry may miss some of the users.
[ER_USER_NOT_IN_EXTRA_USERS_BINLOG_POSSIBLY_INCOMPLETE](#) was added in 8.0.2.
 - Error number: [MY-010332](#); Symbol: [ER_DD_SCHEMA_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Unable to start server. The data dictionary schema '%s' does not exist.
[ER_DD_SCHEMA_NOT_FOUND](#) was added in 8.0.2.
 - Error number: [MY-010333](#); Symbol: [ER_DD_TABLE_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Unable to start server. The data dictionary table '%s' does not exist.
[ER_DD_TABLE_NOT_FOUND](#) was added in 8.0.2.
 - Error number: [MY-010334](#); Symbol: [ER_DD_SE_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to initialize DD Storage Engine
[ER_DD_SE_INIT_FAILED](#) was added in 8.0.2.
 - Error number: [MY-010335](#); Symbol: [ER_DD_ABORTING_PARTIAL_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Found partially upgraded DD. Aborting upgrade and deleting all DD tables. Start the upgrade process again.
[ER_DD_ABORTING_PARTIAL_UPGRADE](#) was added in 8.0.2.
 - Error number: [MY-010336](#); Symbol: [ER_DD_FRM_EXISTS_FOR_TABLE](#); SQLSTATE: [HY000](#)

Message: Found .frm file with same name as one of the Dictionary Tables.

`ER_DD_FRM_EXISTS_FOR_TABLE` was added in 8.0.2.

- Error number: `MY-010337`; Symbol: `ER_DD_CREATED_FOR_UPGRADE`; SQLSTATE: `HY000`

Message: Created Data Dictionary for upgrade

`ER_DD_CREATED_FOR_UPGRADE` was added in 8.0.2.

- Error number: `MY-010338`; Symbol: `ER_ERRMSG_CANT_FIND_FILE`; SQLSTATE: `HY000`

Message: Can't find error-message file '%s'. Check error-message file location and 'lc-messages-dir' configuration directive.

`ER_ERRMSG_CANT_FIND_FILE` was added in 8.0.2.

- Error number: `MY-010339`; Symbol: `ER_ERRMSG_LOADING_55_STYLE`; SQLSTATE: `HY000`

Message: Using pre 5.5 semantics to load error messages from %. If this is not intended, refer to the documentation for valid usage of --lc-messages-dir and --language parameters.

`ER_ERRMSG_LOADING_55_STYLE` was added in 8.0.2.

- Error number: `MY-010340`; Symbol: `ER_ERRMSG_MISSING_IN_FILE`; SQLSTATE: `HY000`

Message: Error message file '%s' had only %d error messages, but it should contain at least %d error messages. Check that the above file is the right version for this program!

`ER_ERRMSG_MISSING_IN_FILE` was added in 8.0.2.

- Error number: `MY-010341`; Symbol: `ER_ERRMSG_OOM`; SQLSTATE: `HY000`

Message: Not enough memory for messagefile '%s'

`ER_ERRMSG_OOM` was added in 8.0.2.

- Error number: `MY-010342`; Symbol: `ER_ERRMSG_CANT_READ`; SQLSTATE: `HY000`

Message: Can't read from messagefile '%s'

`ER_ERRMSG_CANT_READ` was added in 8.0.2.

- Error number: `MY-010343`; Symbol: `ER_TABLE_INCOMPATIBLE_DECIMAL_FIELD`; SQLSTATE: `HY000`

Message: Found incompatible DECIMAL field '%s' in %s; Please do "ALTER TABLE `%%s` FORCE" to fix it!

`ER_TABLE_INCOMPATIBLE_DECIMAL_FIELD` was added in 8.0.2.

- Error number: `MY-010344`; Symbol: `ER_TABLE_INCOMPATIBLE_YEAR_FIELD`; SQLSTATE: `HY000`

Message: Found incompatible YEAR(x) field '%s' in %s; Please do "ALTER TABLE `%%s` FORCE" to fix it!

`ER_TABLE_INCOMPATIBLE_YEAR_FIELD` was added in 8.0.2.

- Error number: `MY-010345`; Symbol: `ER_INVALID_CHARSET_AND_DEFAULT_IS_MB`; SQLSTATE: `HY000`

Message: '%s' had no or invalid character set, and default character set is multi-byte, so character column sizes may have changed

`ER_INVALID_CHARSET_AND_DEFAULT_IS_MB` was added in 8.0.2.

- Error number: `MY-010346`; Symbol: `ER_TABLE_WRONG_KEY_DEFINITION`; SQLSTATE: `HY000`

Message: Found wrong key definition in %s; Please do "ALTER TABLE `'%s` FORCE " to fix it!

`ER_TABLE_WRONG_KEY_DEFINITION` was added in 8.0.2.

- Error number: `MY-010347`; Symbol: `ER_CANT_OPEN_FRM_FILE`; SQLSTATE: `HY000`

Message: Unable to open file %s

`ER_CANT_OPEN_FRM_FILE` was added in 8.0.2.

- Error number: `MY-010348`; Symbol: `ER_CANT_READ_FRM_FILE`; SQLSTATE: `HY000`

Message: Error in reading file %s

`ER_CANT_READ_FRM_FILE` was added in 8.0.2.

- Error number: `MY-010349`; Symbol: `ER_TABLE_CREATED_WITH_DIFFERENT_VERSION`; SQLSTATE: `HY000`

Message: Table '%s' was created with a different version of MySQL and cannot be read

`ER_TABLE_CREATED_WITH_DIFFERENT_VERSION` was added in 8.0.2.

- Error number: `MY-010350`; Symbol: `ER_VIEW_UNPARSABLE`; SQLSTATE: `HY000`

Message: Unable to read view %s

`ER_VIEW_UNPARSABLE` was added in 8.0.2.

- Error number: `MY-010351`; Symbol: `ER_FILE_TYPE_UNKNOWN`; SQLSTATE: `HY000`

Message: File %s has unknown type in its header.

`ER_FILE_TYPE_UNKNOWN` was added in 8.0.2.

- Error number: `MY-010352`; Symbol: `ER_INVALID_INFO_IN_FRM`; SQLSTATE: `HY000`

Message: Incorrect information in file %s

`ER_INVALID_INFO_IN_FRM` was added in 8.0.2.

- Error number: `MY-010353`; Symbol: `ER_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES`; SQLSTATE: `HY000`

Message: Can't open and lock privilege tables: %s

`ER_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES` was added in 8.0.2.

- Error number: `MY-010354`; Symbol: `ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT_AUTH_EVENTS`; SQLSTATE: `HY000`

Message: Plugin '%s' cannot subscribe to MYSQL_AUDIT_AUTHORIZATION events. Currently not supported.

`ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT_AUTH_EVENTS` was added in 8.0.2.

- Error number: `MY-010355`; Symbol: `ER_AUDIT_PLUGIN_HAS_INVALID_DATA`; SQLSTATE: `HY000`

Message: Plugin '%s' has invalid data.

`ER_AUDIT_PLUGIN_HAS_INVALID_DATA` was added in 8.0.2.

- Error number: `MY-010356`; Symbol: `ER_TZ_OOM_INITIALIZING_TIME_ZONES`; SQLSTATE: `HY000`

Message: Fatal error: OOM while initializing time zones

`ER_TZ_OOM_INITIALIZING_TIME_ZONES` was added in 8.0.2.

- Error number: `MY-010357`; Symbol: `ER_TZ_CANT_OPEN_AND_LOCK_TIME_ZONE_TABLE`; SQLSTATE: `HY000`

Message: Can't open and lock time zone table: %s trying to live without them

`ER_TZ_CANT_OPEN_AND_LOCK_TIME_ZONE_TABLE` was added in 8.0.2.

- Error number: `MY-010358`; Symbol: `ER_TZ_OOM_LOADING_LEAP_SECOND_TABLE`; SQLSTATE: `HY000`

Message: Fatal error: Out of memory while loading mysql.time_zone_leap_second table

`ER_TZ_OOM_LOADING_LEAP_SECOND_TABLE` was added in 8.0.2.

- Error number: `MY-010359`; Symbol: `ER_TZ_TOO_MANY_LEAPS_IN_LEAP_SECOND_TABLE`; SQLSTATE: `HY000`

Message: Fatal error: While loading mysql.time_zone_leap_second table: too much leaps

`ER_TZ_TOO_MANY_LEAPS_IN_LEAP_SECOND_TABLE` was added in 8.0.2.

- Error number: `MY-010360`; Symbol: `ER_TZ_ERROR_LOADING_LEAP_SECOND_TABLE`; SQLSTATE: `HY000`

Message: Fatal error: Error while loading mysql.time_zone_leap_second table

`ER_TZ_ERROR_LOADING_LEAP_SECOND_TABLE` was added in 8.0.2.

- Error number: `MY-010361`; Symbol: `ER_TZ_UNKNOWN_OR_ILLEGAL_DEFAULT_TIME_ZONE`; SQLSTATE: `HY000`

Message: Fatal error: Illegal or unknown default time zone '%s'

`ER_TZ_UNKNOWN_OR_ILLEGAL_DEFAULT_TIME_ZONE` was added in 8.0.2.

- Error number: `MY-010362`; Symbol: `ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE`; SQLSTATE: `HY000`

Message: Can't find description of time zone '%.*s'

`ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE` was added in 8.0.2.

- Error number: `MY-010363`; Symbol: `ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE_ID`; SQLSTATE: `HY000`

Message: Can't find description of time zone '%u'

`ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE_ID` was added in 8.0.2.

- Error number: `MY-010364`; Symbol: `ER_TZ_TRANSITION_TYPE_TABLE_TYPE_TOO_LARGE`; SQLSTATE: `HY000`

Message: Error while loading time zone description from mysql.time_zone_transition_type table: too big transition type id

`ER_TZ_TRANSITION_TYPE_TABLE_TYPE_TOO_LARGE` was added in 8.0.2.

- Error number: `MY-010365`; Symbol:

`ER_TZ_TRANSITION_TYPE_TABLE_ABBREVIATIONS_EXCEED_SPACE`; SQLSTATE: `HY000`

Message: Error while loading time zone description from mysql.time_zone_transition_type table: not enough room for abbreviations

`ER_TZ_TRANSITION_TYPE_TABLE_ABBREVIATIONS_EXCEED_SPACE` was added in 8.0.2.

- Error number: `MY-010366`; Symbol: `ER_TZ_TRANSITION_TYPE_TABLE_LOAD_ERROR`; SQLSTATE: `HY000`

Message: Error while loading time zone description from mysql.time_zone_transition_type table

`ER_TZ_TRANSITION_TYPE_TABLE_LOAD_ERROR` was added in 8.0.2.

- Error number: `MY-010367`; Symbol: `ER_TZ_TRANSITION_TABLE_TOO_MANY_TRANSITIONS`; SQLSTATE: `HY000`

Message: Error while loading time zone description from mysql.time_zone_transition table: too much transitions

`ER_TZ_TRANSITION_TABLE_TOO_MANY_TRANSITIONS` was added in 8.0.2.

- Error number: `MY-010368`; Symbol: `ER_TZ_TRANSITION_TABLE_BAD_TRANSITION_TYPE`; SQLSTATE: `HY000`

Message: Error while loading time zone description from mysql.time_zone_transition table: bad transition type id

`ER_TZ_TRANSITION_TABLE_BAD_TRANSITION_TYPE` was added in 8.0.2.

- Error number: `MY-010369`; Symbol: `ER_TZ_TRANSITION_TABLE_LOAD_ERROR`; SQLSTATE: `HY000`

Message: Error while loading time zone description from mysql.time_zone_transition table

`ER_TZ_TRANSITION_TABLE_LOAD_ERROR` was added in 8.0.2.

- Error number: `MY-010370`; Symbol: `ER_TZ_NO_TRANSITION_TYPES_IN_TIME_ZONE`; SQLSTATE: `HY000`

Message: loading time zone without transition types

`ER_TZ_NO_TRANSITION_TYPES_IN_TIME_ZONE` was added in 8.0.2.

- Error number: `MY-010371`; Symbol: `ER_TZ_OOM_LOADING_TIME_ZONE_DESCRIPTION`; SQLSTATE: `HY000`

Message: Out of memory while loading time zone description

`ER_TZ_OOM_LOADING_TIME_ZONE_DESCRIPTION` was added in 8.0.2.

- Error number: `MY-010372`; Symbol: `ER_TZ_CANT_BUILD_MKTIME_MAP`; SQLSTATE: `HY000`

Message: Unable to build mktime map for time zone

`ER_TZ_CANT_BUILD_MKTIME_MAP` was added in 8.0.2.

- Error number: [MY-010373](#); Symbol: [ER_TZ_OOM_WHILE_LOADING_TIME_ZONE](#); SQLSTATE: [HY000](#)

Message: Out of memory while loading time zone

[ER_TZ_OOM_WHILE_LOADING_TIME_ZONE](#) was added in 8.0.2.

- Error number: [MY-010374](#); Symbol: [ER_TZ_OOM_WHILE_SETTING_TIME_ZONE](#); SQLSTATE: [HY000](#)

Message: Fatal error: Out of memory while setting new time zone

[ER_TZ_OOM_WHILE_SETTING_TIME_ZONE](#) was added in 8.0.2.

- Error number: [MY-010375](#); Symbol: [ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_CONDITION_BAD](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread is stopped because UNTIL condition is bad(%s:%llu).

[ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_CONDITION_BAD](#) was added in 8.0.2.

- Error number: [MY-010376](#); Symbol: [ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_POSITION_REACHED](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread stopped because it reached its UNTIL position %llu

[ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_POSITION_REACHED](#) was added in 8.0.2.

- Error number: [MY-010377](#); Symbol: [ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS_ALREADY_APPLIED](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread stopped because UNTIL SQL_BEFORE_GTIDS %s is already applied

[ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS_ALREADY_APPLIED](#) was added in 8.0.2.

- Error number: [MY-010378](#); Symbol: [ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS_REACHED](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread stopped because it reached UNTIL SQL_BEFORE_GTIDS %s

[ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS_REACHED](#) was added in 8.0.2.

- Error number: [MY-010379](#); Symbol: [ER_SLAVE_SQL_THREAD_STOPPED_AFTER_GTIDS_REACHED](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread stopped because it reached UNTIL SQL_AFTER_GTIDS %s

[ER_SLAVE_SQL_THREAD_STOPPED_AFTER_GTIDS_REACHED](#) was added in 8.0.2.

- Error number: [MY-010380](#); Symbol: [ER_SLAVE_SQL_THREAD_STOPPED_GAP_TRX_PROCESSED](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread stopped according to UNTIL SQL_AFTER_MTS_GAPS as it has processed all gap transactions left from the previous slave session.

[ER_SLAVE_SQL_THREAD_STOPPED_GAP_TRX_PROCESSED](#) was added in 8.0.2.

- Error number: [MY-010381](#); Symbol: [ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED](#); SQLSTATE: [HY000](#)

Message: Group Replication plugin is not installed.

[ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED](#) was added in 8.0.2.

- Error number: `MY-010382`; Symbol: `ER_GTID_ALREADY_ADDED_BY_USER`; SQLSTATE: `HY000`

Message: The transaction owned GTID is already in the %s table, which is caused by an explicit modifying from user client.
`ER_GTID_ALREADY_ADDED_BY_USER` was added in 8.0.2.
- Error number: `MY-010383`; Symbol: `ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE`; SQLSTATE: `HY000`

Message: Failed to delete the row: '%s' from the gtid_executed table.
`ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE` was added in 8.0.2.
- Error number: `MY-010384`; Symbol: `ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE`; SQLSTATE: `HY000`

Message: Failed to compress the gtid_executed table.
`ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE` was added in 8.0.2.
- Error number: `MY-010385`; Symbol: `ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE_OOM`; SQLSTATE: `HY000`

Message: Failed to compress the gtid_executed table, because it is failed to allocate the THD.
`ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE_OOM` was added in 8.0.2.
- Error number: `MY-010386`; Symbol: `ER_FAILED_TO_INIT_THREAD_ATTR_FOR_GTID_TABLE_COMPRESSION`; SQLSTATE: `HY000`

Message: Failed to initialize thread attribute when creating compression thread.
`ER_FAILED_TO_INIT_THREAD_ATTR_FOR_GTID_TABLE_COMPRESSION` was added in 8.0.2.
- Error number: `MY-010387`; Symbol: `ER_FAILED_TO_CREATE_GTID_TABLE_COMPRESSION_THREAD`; SQLSTATE: `HY000`

Message: Can not create thread to compress gtid_executed table (errno= %d)
`ER_FAILED_TO_CREATE_GTID_TABLE_COMPRESSION_THREAD` was added in 8.0.2.
- Error number: `MY-010388`; Symbol: `ER_FAILED_TO_JOIN_GTID_TABLE_COMPRESSION_THREAD`; SQLSTATE: `HY000`

Message: Could not join gtid_executed table compression thread. error:%d
`ER_FAILED_TO_JOIN_GTID_TABLE_COMPRESSION_THREAD` was added in 8.0.2.
- Error number: `MY-010389`; Symbol: `ER_NPIPE_FAILED_TO_INIT_SECURITY_DESCRIPTOR`; SQLSTATE: `HY000`

Message: Can't start server : Initialize security descriptor: %s
`ER_NPIPE_FAILED_TO_INIT_SECURITY_DESCRIPTOR` was added in 8.0.2.
- Error number: `MY-010390`; Symbol: `ER_NPIPE_FAILED_TO_SET_SECURITY_DESCRIPTOR`; SQLSTATE: `HY000`

Message: Can't start server : Set security descriptor: %s
`ER_NPIPE_FAILED_TO_SET_SECURITY_DESCRIPTOR` was added in 8.0.2.
- Error number: `MY-010391`; Symbol: `ER_NPIPE_PIPE_ALREADY_IN_USE`; SQLSTATE: `HY000`

Message: Can't start server : Named Pipe "%s" already in use.

`ER_NPIPE_PIPE_ALREADY_IN_USE` was added in 8.0.2.

- Error number: `MY-010392`; Symbol:

`ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS_ON_START`; SQLSTATE: `HY000`

Message: NDB Slave : At SQL thread start applying epoch %llu/%llu (%llu) from Master ServerId %u which is lower than previously applied epoch %llu/%llu (%llu). Group Master Log : %s Group Master Log Pos : %llu. Check slave positioning.

`ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS_ON_START` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010393`; Symbol: `ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS`; SQLSTATE: `HY000`

Message: NDB Slave : SQL thread stopped as applying epoch %llu/%llu (%llu) from Master ServerId %u which is lower than previously applied epoch %llu/%llu (%llu). Group Master Log : %s Group Master Log Pos : %llu

`ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010394`; Symbol: `ER_NDB_SLAVE_SAW_ALREADY_COMMITTED_EPOCH`; SQLSTATE: `HY000`

Message: NDB Slave : SQL thread stopped as attempted to reapply already committed epoch %llu/%llu (%llu) from server id %u. Group Master Log : %s Group Master Log Pos : %llu.

`ER_NDB_SLAVE_SAW_ALREADY_COMMITTED_EPOCH` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010395`; Symbol: `ER_NDB_SLAVE_PREVIOUS_EPOCH_NOT_COMMITTED`; SQLSTATE: `HY000`

Message: NDB Slave : SQL thread stopped as attempting to apply new epoch %llu/%llu (%llu) while lower received epoch %llu/%llu (%llu) has not been committed. Master server id : %u. Group Master Log : %s Group Master Log Pos : %llu.

`ER_NDB_SLAVE_PREVIOUS_EPOCH_NOT_COMMITTED` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010396`; Symbol: `ER_NDB_SLAVE_MISSING_DATA_FOR_TIMESTAMP_COLUMN`; SQLSTATE: `HY000`

Message: NDB Slave: missing data for %s timestamp column %u.

`ER_NDB_SLAVE_MISSING_DATA_FOR_TIMESTAMP_COLUMN` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010397`; Symbol: `ER_NDB_SLAVE_LOGGING_EXCEPTIONS_TO`; SQLSTATE: `HY000`

Message: NDB Slave: Table %s.%s logging exceptions to %s.%s

`ER_NDB_SLAVE_LOGGING_EXCEPTIONS_TO` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010398`; Symbol: `ER_NDB_SLAVE_LOW_EPOCH_RESOLUTION`; SQLSTATE: `HY000`

Message: NDB Slave: Table %s.%s : %s, low epoch resolution

`ER_NDB_SLAVE_LOW_EPOCH_RESOLUTION` was added in 8.0.2, removed after 8.0.13.

-
- Error number: [MY-010399](#); Symbol: [ER_NDB_INFO_FOUND_UNEXPECTED_FIELD_TYPE](#); SQLSTATE: [HY000](#)

Message: Found unexpected field type %u
[ER_NDB_INFO_FOUND_UNEXPECTED_FIELD_TYPE](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010400](#); Symbol: [ER_NDB_INFO_FAILED_TO_CREATE_NDBINFO](#); SQLSTATE: [HY000](#)

Message: Failed to create NdbInfo
[ER_NDB_INFO_FAILED_TO_CREATE_NDBINFO](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010401](#); Symbol: [ER_NDB_INFO_FAILED_TO_INIT_NDBINFO](#); SQLSTATE: [HY000](#)

Message: Failed to init NdbInfo
[ER_NDB_INFO_FAILED_TO_INIT_NDBINFO](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010402](#); Symbol: [ER_NDB_CLUSTER_WRONG_NUMBER_OF_FUNCTION_ARGUMENTS](#); SQLSTATE: [HY000](#)

Message: ndb_serialize_cond: Unexpected mismatch of found and expected number of function arguments %u
[ER_NDB_CLUSTER_WRONG_NUMBER_OF_FUNCTION_ARGUMENTS](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010403](#); Symbol: [ER_NDB_CLUSTER_SCHEMA_INFO](#); SQLSTATE: [HY000](#)

Message: %s - %s.%s
[ER_NDB_CLUSTER_SCHEMA_INFO](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010404](#); Symbol: [ER_NDB_CLUSTER_GENERIC_MESSAGE](#); SQLSTATE: [HY000](#)

Message: %s
[ER_NDB_CLUSTER_GENERIC_MESSAGE](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010405](#); Symbol: [ER_RPL_CANT_OPEN_INFO_TABLE](#); SQLSTATE: [HY000](#)

Message: Info table is not ready to be used. Table '%s.%s' cannot be opened.
[ER_RPL_CANT_OPEN_INFO_TABLE](#) was added in 8.0.2.
 - Error number: [MY-010406](#); Symbol: [ER_RPL_CANT_SCAN_INFO_TABLE](#); SQLSTATE: [HY000](#)

Message: Info table is not ready to be used. Table '%s.%s' cannot be scanned.
[ER_RPL_CANT_SCAN_INFO_TABLE](#) was added in 8.0.2.
 - Error number: [MY-010407](#); Symbol: [ER_RPL_CORRUPTED_INFO_TABLE](#); SQLSTATE: [HY000](#)

Message: Corrupted table %s.%s. Check out table definition.
[ER_RPL_CORRUPTED_INFO_TABLE](#) was added in 8.0.2.

-
- Error number: [MY-010408](#); Symbol: [ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE](#); SQLSTATE: [HY000](#)

Message: Info table has a problem with its key field(s). Table '%s.%s' expected field #%u to be '%s' but found '%s' instead.

[ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE](#) was added in 8.0.2.

- Error number: [MY-010409](#); Symbol: [ER_RPL_WORKER_ID_IS](#); SQLSTATE: [HY000](#)

Message: Choosing worker id %lu, the following is going to be %lu

[ER_RPL_WORKER_ID_IS](#) was added in 8.0.2.

- Error number: [MY-010410](#); Symbol: [ER_RPL_INCONSISTENT_TIMESTAMPS_IN_TRX](#); SQLSTATE: [HY000](#)

Message: Transaction is tagged with inconsistent logical timestamps: sequence_number (%lld) <= last_committed (%lld)

[ER_RPL_INCONSISTENT_TIMESTAMPS_IN_TRX](#) was added in 8.0.2.

- Error number: [MY-010411](#); Symbol: [ER_RPL_INCONSISTENT_SEQUENCE_NO_IN_TRX](#); SQLSTATE: [HY000](#)

Message: Transaction's sequence number is inconsistent with that of a preceding one: sequence_number (%lld) <= previous sequence_number (%lld)

[ER_RPL_INCONSISTENT_SEQUENCE_NO_IN_TRX](#) was added in 8.0.2.

- Error number: [MY-010412](#); Symbol: [ER_RPL_CHANNELS_REQUIRE_TABLES_AS_INFO_REPOSITORIES](#); SQLSTATE: [HY000](#)

Message: For the creation of replication channels the master info and relay log info repositories must be set to TABLE

[ER_RPL_CHANNELS_REQUIRE_TABLES_AS_INFO_REPOSITORIES](#) was added in 8.0.2.

- Error number: [MY-010413](#); Symbol: [ER_RPL_CHANNELS_REQUIRE_NON_ZERO_SERVER_ID](#); SQLSTATE: [HY000](#)

Message: For the creation of replication channels the server id must be different from 0

[ER_RPL_CHANNELS_REQUIRE_NON_ZERO_SERVER_ID](#) was added in 8.0.2.

- Error number: [MY-010414](#); Symbol: [ER_RPL_REPO_SHOULD_BE_TABLE](#); SQLSTATE: [HY000](#)

Message: Slave: Wrong repository. Repository should be TABLE

[ER_RPL_REPO_SHOULD_BE_TABLE](#) was added in 8.0.2.

- Error number: [MY-010415](#); Symbol: [ER_RPL_ERROR_CREATING_MASTER_INFO](#); SQLSTATE: [HY000](#)

Message: Error creating master info: %s.

[ER_RPL_ERROR_CREATING_MASTER_INFO](#) was added in 8.0.2.

-
- Error number: [MY-010416](#); Symbol: [ER_RPL_ERROR_CHANGING_MASTER_INFO_REPO_TYPE](#); SQLSTATE: [HY000](#)

Message: Error changing the type of master info's repository: %s.

[ER_RPL_ERROR_CHANGING_MASTER_INFO_REPO_TYPE](#) was added in 8.0.2.

- Error number: [MY-010417](#); Symbol: [ER_RPL_CHANGING_RELAY_LOG_INFO_REPO_TYPE_FAILED_DUE_TO_GAPS](#); SQLSTATE: [HY000](#)

Message: It is not possible to change the type of the relay log repository because there are workers repositories with possible execution gaps. The value of --relay_log_info_repository is altered to one of the found Worker repositories. The gaps have to be sorted out before resuming with the type change.

[ER_RPL_CHANGING_RELAY_LOG_INFO_REPO_TYPE_FAILED_DUE_TO_GAPS](#) was added in 8.0.2.

- Error number: [MY-010418](#); Symbol: [ER_RPL_ERROR_CREATING_RELAY_LOG_INFO](#); SQLSTATE: [HY000](#)

Message: Error creating relay log info: %s.

[ER_RPL_ERROR_CREATING_RELAY_LOG_INFO](#) was added in 8.0.2.

- Error number: [MY-010419](#); Symbol: [ER_RPL_ERROR_CHANGING_RELAY_LOG_INFO_REPO_TYPE](#); SQLSTATE: [HY000](#)

Message: Error changing the type of relay log info's repository: %s.

[ER_RPL_ERROR_CHANGING_RELAY_LOG_INFO_REPO_TYPE](#) was added in 8.0.2.

- Error number: [MY-010420](#); Symbol: [ER_RPL_FAILED_TO_DELETE_FROM_SLAVE_WORKERS_INFO_REPOSITORY](#); SQLSTATE: [HY000](#)

Message: Could not delete from Slave Workers info repository.

[ER_RPL_FAILED_TO_DELETE_FROM_SLAVE_WORKERS_INFO_REPOSITORY](#) was added in 8.0.2.

- Error number: [MY-010421](#); Symbol: [ER_RPL_FAILED_TO_RESET_STATE_IN_SLAVE_INFO_REPOSITORY](#); SQLSTATE: [HY000](#)

Message: Could not store the reset Slave Worker state into the slave info repository.

[ER_RPL_FAILED_TO_RESET_STATE_IN_SLAVE_INFO_REPOSITORY](#) was added in 8.0.2.

- Error number: [MY-010422](#); Symbol: [ER_RPL_ERROR_CHECKING_REPOSITORY](#); SQLSTATE: [HY000](#)

Message: Error in checking %s repository info type of %s.

[ER_RPL_ERROR_CHECKING_REPOSITORY](#) was added in 8.0.2.

- Error number: [MY-010423](#); Symbol: [ER_RPL_SLAVE_GENERIC_MESSAGE](#); SQLSTATE: [HY000](#)

Message: Slave: %s

[ER_RPL_SLAVE_GENERIC_MESSAGE](#) was added in 8.0.2.

- Error number: [MY-010424](#); Symbol: [ER_RPL_SLAVE_COULD_NOT_CREATE_CHANNEL_LIST](#); SQLSTATE: [HY000](#)

Message: Slave: Could not create channel list

`ER_RPL_SLAVE_COULD_NOT_CREATE_CHANNEL_LIST` was added in 8.0.2.

- Error number: `MY-010425`; Symbol: `ER_RPL_MULTISOURCE_REQUIRES_TABLE_TYPE_REPOSITORIES`; SQLSTATE: `HY000`

Message: Slave: This slave was a multisourced slave previously which is supported only by both TABLE based master info and relay log info repositories. Found one or both of the info repos to be type FILE. Set both repos to type TABLE.

`ER_RPL_MULTISOURCE_REQUIRES_TABLE_TYPE_REPOSITORIES` was added in 8.0.2.

- Error number: `MY-010426`; Symbol: `ER_RPL_SLAVE_FAILED_TO_INIT_A_MASTER_INFO_STRUCTURE`; SQLSTATE: `HY000`

Message: Slave: Failed to initialize the master info structure for channel '%s'; its record may still be present in 'mysql.slave_master_info' table, consider deleting it.

`ER_RPL_SLAVE_FAILED_TO_INIT_A_MASTER_INFO_STRUCTURE` was added in 8.0.2.

- Error number: `MY-010427`; Symbol: `ER_RPL_SLAVE_FAILED_TO_INIT_MASTER_INFO_STRUCTURE`; SQLSTATE: `HY000`

Message: Failed to initialize the master info structure%

`ER_RPL_SLAVE_FAILED_TO_INIT_MASTER_INFO_STRUCTURE` was added in 8.0.2.

- Error number: `MY-010428`; Symbol: `ER_RPL_SLAVE_FAILED_TO_CREATE_CHANNEL_FROM_MASTER_INFO`; SQLSTATE: `HY000`

Message: Slave: Failed to create a channel from master info table repository.

`ER_RPL_SLAVE_FAILED_TO_CREATE_CHANNEL_FROM_MASTER_INFO` was added in 8.0.2.

- Error number: `MY-010429`; Symbol: `ER_RPL_FAILED_TO_CREATE_NEW_INFO_FILE`; SQLSTATE: `HY000`

Message: Failed to create a new info file (file '%s', errno %d)

`ER_RPL_FAILED_TO_CREATE_NEW_INFO_FILE` was added in 8.0.2.

- Error number: `MY-010430`; Symbol: `ER_RPL_FAILED_TO_CREATE_CACHE_FOR_INFO_FILE`; SQLSTATE: `HY000`

Message: Failed to create a cache on info file (file '%s')

`ER_RPL_FAILED_TO_CREATE_CACHE_FOR_INFO_FILE` was added in 8.0.2.

- Error number: `MY-010431`; Symbol: `ER_RPL_FAILED_TO_OPEN_INFO_FILE`; SQLSTATE: `HY000`

Message: Failed to open the existing info file (file '%s', errno %d)

`ER_RPL_FAILED_TO_OPEN_INFO_FILE` was added in 8.0.2.

- Error number: `MY-010432`; Symbol: `ER_RPL_GTIID_MEMORY_FINALLY_AVAILABLE`; SQLSTATE: `HY000`

Message: Server overcomes the temporary 'out of memory' in '%d' tries while allocating a new chunk of intervals for storing GTIDs.

`ER_RPL_GTIID_MEMORY_FINALLY_AVAILABLE` was added in 8.0.2.

-
- Error number: [MY-010433](#); Symbol: [ER_SERVER_COST_UNKNOWN_COST_CONSTANT](#); SQLSTATE: [HY000](#)

Message: Unknown cost constant "%s" in mysql.server_cost table

[ER_SERVER_COST_UNKNOWN_COST_CONSTANT](#) was added in 8.0.2.

- Error number: [MY-010434](#); Symbol: [ER_SERVER_COST_INVALID_COST_CONSTANT](#); SQLSTATE: [HY000](#)

Message: Invalid value for cost constant "%s" in mysql.server_cost table: %.1f

[ER_SERVER_COST_INVALID_COST_CONSTANT](#) was added in 8.0.2.

- Error number: [MY-010435](#); Symbol: [ER_ENGINE_COST_UNKNOWN_COST_CONSTANT](#); SQLSTATE: [HY000](#)

Message: Unknown cost constant "%s" in mysql.engine_cost table

[ER_ENGINE_COST_UNKNOWN_COST_CONSTANT](#) was added in 8.0.2.

- Error number: [MY-010436](#); Symbol: [ER_ENGINE_COST_UNKNOWN_STORAGE_ENGINE](#); SQLSTATE: [HY000](#)

Message: Unknown storage engine "%s" in mysql.engine_cost table

[ER_ENGINE_COST_UNKNOWN_STORAGE_ENGINE](#) was added in 8.0.2.

- Error number: [MY-010437](#); Symbol: [ER_ENGINE_COST_INVALID_DEVICE_TYPE_FOR_SE](#); SQLSTATE: [HY000](#)

Message: Invalid device type %d for "%s" storage engine for cost constant "%s" in mysql.engine_cost table

[ER_ENGINE_COST_INVALID_DEVICE_TYPE_FOR_SE](#) was added in 8.0.2.

- Error number: [MY-010438](#); Symbol: [ER_ENGINE_COST_INVALID_CONST_CONSTANT_FOR_SE_AND_DEVICE](#); SQLSTATE: [HY000](#)

Message: Invalid value for cost constant "%s" for "%s" storage engine and device type %d in mysql.engine_cost table: %.1f

[ER_ENGINE_COST_INVALID_CONST_CONSTANT_FOR_SE_AND_DEVICE](#) was added in 8.0.2.

- Error number: [MY-010439](#); Symbol: [ER_SERVER_COST_FAILED_TO_READ](#); SQLSTATE: [HY000](#)

Message: Error while reading from mysql.server_cost table.

[ER_SERVER_COST_FAILED_TO_READ](#) was added in 8.0.2.

- Error number: [MY-010440](#); Symbol: [ER_ENGINE_COST_FAILED_TO_READ](#); SQLSTATE: [HY000](#)

Message: Error while reading from mysql.engine_cost table.

[ER_ENGINE_COST_FAILED_TO_READ](#) was added in 8.0.2.

- Error number: [MY-010441](#); Symbol: [ER_FAILED_TO_OPEN_COST_CONSTANT_TABLES](#); SQLSTATE: [HY000](#)

Message: Failed to open optimizer cost constant tables

[ER_FAILED_TO_OPEN_COST_CONSTANT_TABLES](#) was added in 8.0.2.

- Error number: [MY-010442](#); Symbol: [ER_RPL_UNSUPPORTED_UNIGNORABLE_EVENT_IN_STREAM](#); SQLSTATE: [HY000](#)

Message: Unsupported non-ignorable event fed into the event stream.

[ER_RPL_UNSUPPORTED_UNIGNORABLE_EVENT_IN_STREAM](#) was added in 8.0.2.

- Error number: [MY-010443](#); Symbol: [ER_RPL_GTID_LOG_EVENT_IN_STREAM](#); SQLSTATE: [HY000](#)

Message: GTID_LOG_EVENT or ANONYMOUS_GTID_LOG_EVENT is not expected in an event stream %s.

[ER_RPL_GTID_LOG_EVENT_IN_STREAM](#) was added in 8.0.2.

- Error number: [MY-010444](#); Symbol: [ER_RPL_UNEXPECTED_BEGIN_IN_STREAM](#); SQLSTATE: [HY000](#)

Message: QUERY(BEGIN) is not expected in an event stream in the middle of a %s.

[ER_RPL_UNEXPECTED_BEGIN_IN_STREAM](#) was added in 8.0.2.

- Error number: [MY-010445](#); Symbol: [ER_RPL_UNEXPECTED_COMMIT_ROLLBACK_OR_XID_LOG_EVENT_IN_STREAM](#); SQLSTATE: [HY000](#)

Message: QUERY(COMMIT or ROLLBACK) or XID_LOG_EVENT is not expected in an event stream %s.

[ER_RPL_UNEXPECTED_COMMIT_ROLLBACK_OR_XID_LOG_EVENT_IN_STREAM](#) was added in 8.0.2.

- Error number: [MY-010446](#); Symbol: [ER_RPL_UNEXPECTED_XA_ROLLBACK_IN_STREAM](#); SQLSTATE: [HY000](#)

Message: QUERY(XA ROLLBACK) is not expected in an event stream %s.

[ER_RPL_UNEXPECTED_XA_ROLLBACK_IN_STREAM](#) was added in 8.0.2.

- Error number: [MY-010447](#); Symbol: [ER_EVENT_EXECUTION_FAILED_CANT_AUTHENTICATE_USER](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: [%s].[%s.%s] execution failed, failed to authenticate the user.

[ER_EVENT_EXECUTION_FAILED_CANT_AUTHENTICATE_USER](#) was added in 8.0.2.

- Error number: [MY-010448](#); Symbol: [ER_EVENT_EXECUTION_FAILED_USER_LOST_EVENT_PRIVILEGE](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: [%s].[%s.%s] execution failed, user no longer has EVENT privilege.

[ER_EVENT_EXECUTION_FAILED_USER_LOST_EVENT_PRIVILEGE](#) was added in 8.0.2.

- Error number: [MY-010449](#); Symbol: [ER_EVENT_ERROR_DURING_COMPILATION](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: %error during compilation of %s.%s

[ER_EVENT_ERROR_DURING_COMPILATION](#) was added in 8.0.2.

-
- Error number: [MY-010450](#); Symbol: [ER_EVENT_DROPPING](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Dropping %s.%s
[ER_EVENT_DROPPING](#) was added in 8.0.2.
 - Error number: [MY-010451](#); Symbol: [ER_NDB_SCHEMA_GENERIC_MESSAGE](#); SQLSTATE: [HY000](#)

Message: Ndb schema[%s.%s]: %s
[ER_NDB_SCHEMA_GENERIC_MESSAGE](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010452](#); Symbol: [ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR](#); SQLSTATE: [HY000](#)

Message: In RBR mode, Slave received incompatible DECIMAL field (old-style decimal field) from Master while creating conversion table. Please consider changing datatype on Master to new style decimal by executing ALTER command for column Name: %s.%s.%s.
[ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR](#) was added in 8.0.2.
 - Error number: [MY-010453](#); Symbol: [ER_INIT_ROOT_WITHOUT_PASSWORD](#); SQLSTATE: [HY000](#)

Message: root@localhost is created with an empty password ! Please consider switching off the --initialize-insecure option.
[ER_INIT_ROOT_WITHOUT_PASSWORD](#) was added in 8.0.2.
 - Error number: [MY-010454](#); Symbol: [ER_INIT_GENERATING_TEMP_PASSWORD_FOR_ROOT](#); SQLSTATE: [HY000](#)

Message: A temporary password is generated for root@localhost: %s
[ER_INIT_GENERATING_TEMP_PASSWORD_FOR_ROOT](#) was added in 8.0.2.
 - Error number: [MY-010455](#); Symbol: [ER_INIT_CANT_OPEN_BOOTSTRAP_FILE](#); SQLSTATE: [HY000](#)

Message: Failed to open the bootstrap file %s
[ER_INIT_CANT_OPEN_BOOTSTRAP_FILE](#) was added in 8.0.2.
 - Error number: [MY-010456](#); Symbol: [ER_INIT_BOOTSTRAP_COMPLETE](#); SQLSTATE: [HY000](#)

Message: Bootstrapping complete
[ER_INIT_BOOTSTRAP_COMPLETE](#) was added in 8.0.2.
 - Error number: [MY-010457](#); Symbol: [ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE](#); SQLSTATE: [HY000](#)

Message: --initialize specified but the data directory has files in it. Aborting.
[ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE](#) was added in 8.0.2.
 - Error number: [MY-010458](#); Symbol: [ER_INIT_DATADIR_EXISTS_WONT_INITIALIZE](#); SQLSTATE: [HY000](#)

Message: --initialize specified on an existing data directory.
[ER_INIT_DATADIR_EXISTS_WONT_INITIALIZE](#) was added in 8.0.2.
 - Error number: [MY-010459](#); Symbol: [ER_INIT_DATADIR_EXISTS_AND_PATH_TOO_LONG_WONT_INITIALIZE](#); SQLSTATE: [HY000](#)

Message: --initialize specified but the data directory exists and the path is too long. Aborting.

`ER_INIT_DATADIR_EXISTS_AND_PATH_TOO_LONG_WONT_INITIALIZE` was added in 8.0.2.

- Error number: `MY-010460`; Symbol:

`ER_INIT_DATADIR_EXISTS_AND_NOT_WRITABLE_WONT_INITIALIZE`; SQLSTATE: `HY000`

Message: --initialize specified but the data directory exists and is not writable. Aborting.

`ER_INIT_DATADIR_EXISTS_AND_NOT_WRITABLE_WONT_INITIALIZE` was added in 8.0.2.

- Error number: `MY-010461`; Symbol: `ER_INIT_CREATING_DD`; SQLSTATE: `HY000`

Message: Creating the data directory %s

`ER_INIT_CREATING_DD` was added in 8.0.2.

- Error number: `MY-010462`; Symbol: `ER_RPL_BINLOG_STARTING_DUMP`; SQLSTATE: `HY000`

Message: Start binlog_dump to master_thread_id(%u) slave_server(%u), pos(%s, %lu)

`ER_RPL_BINLOG_STARTING_DUMP` was added in 8.0.2.

- Error number: `MY-010463`; Symbol: `ER_RPL_BINLOG_MASTER_SENDS_HEARTBEAT`; SQLSTATE: `HY000`

Message: master sends heartbeat message

`ER_RPL_BINLOG_MASTER_SENDS_HEARTBEAT` was added in 8.0.2.

- Error number: `MY-010464`; Symbol:

`ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEAT_INFO`; SQLSTATE: `HY000`

Message: the rest of heartbeat info skipped ...

`ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEAT_INFO` was added in 8.0.2.

- Error number: `MY-010465`; Symbol:

`ER_RPL_BINLOG_MASTERUSES_CHECKSUM_AND_SLAVE_CANT`; SQLSTATE: `HY000`

Message: Master is configured to log replication events with checksum, but will not send such events to slaves that cannot process them

`ER_RPL_BINLOG_MASTERUSES_CHECKSUM_AND_SLAVE_CANT` was added in 8.0.2.

- Error number: `MY-010466`; Symbol: `ER_NDB_QUERY_FAILED`; SQLSTATE: `HY000`

Message: NDB: Query '%s' failed, error: %d: %s

`ER_NDB_QUERY_FAILED` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010467`; Symbol: `ER_KILLING_THREAD`; SQLSTATE: `HY000`

Message: Killing thread %lu

`ER_KILLING_THREAD` was added in 8.0.2.

- Error number: `MY-010468`; Symbol: `ER_DETACHING_SESSION_LEFT_BY_PLUGIN`; SQLSTATE: `HY000`

Message: Plugin %s is deinitializing a thread but left a session attached. Detaching it forcefully.

`ER_DETACHING_SESSION_LEFT_BY_PLUGIN` was added in 8.0.2.

- Error number: [MY-010469](#); Symbol: [ER_CANT_DETACH_SESSION_LEFT_BY_PLUGIN](#); SQLSTATE: [HY000](#)

Message: Failed to detach the session.
[ER_CANT_DETACH_SESSION_LEFT_BY_PLUGIN](#) was added in 8.0.2.
- Error number: [MY-010470](#); Symbol: [ER_DETACHED_SESSIONS_LEFT_BY_PLUGIN](#); SQLSTATE: [HY000](#)

Message: Closed forcefully %u session%s left opened by plugin %s
[ER_DETACHED_SESSIONS_LEFT_BY_PLUGIN](#) was added in 8.0.2.
- Error number: [MY-010471](#); Symbol: [ER_FAILED_TO_DECREMENT_NUMBER_OF_THREADS](#); SQLSTATE: [HY000](#)

Message: Failed to decrement the number of threads
[ER_FAILED_TO_DECREMENT_NUMBER_OF_THREADS](#) was added in 8.0.2.
- Error number: [MY-010472](#); Symbol: [ER_PLUGIN_DID_NOT_DEINITIALIZE_THREADS](#); SQLSTATE: [HY000](#)

Message: Plugin %s did not deinitialize %u threads
[ER_PLUGIN_DID_NOT_DEINITIALIZE_THREADS](#) was added in 8.0.2.
- Error number: [MY-010473](#); Symbol: [ER_KILLED_THREADS_OF_PLUGIN](#); SQLSTATE: [HY000](#)

Message: Killed %u threads of plugin %s
[ER_KILLED_THREADS_OF_PLUGIN](#) was added in 8.0.2.
- Error number: [MY-010474](#); Symbol: [ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: NDB Slave : Could not determine maximum replicated epoch from %s.%s at Slave start, error %u %s
[ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_UNKNOWN](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010475](#); Symbol: [ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_SET_TO](#); SQLSTATE: [HY000](#)

Message: NDB Slave : MaxReplicatedEpoch set to %llu (%u/%u) at Slave start
[ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_SET_TO](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010476](#); Symbol: [ER_NDB_NODE_ID_AND_MANAGEMENT_SERVER_INFO](#); SQLSTATE: [HY000](#)

Message: NDB: NodeID is %lu, management server '%s:%lu'
[ER_NDB_NODE_ID_AND_MANAGEMENT_SERVER_INFO](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010477](#); Symbol: [ER_NDB_DISCONNECT_INFO](#); SQLSTATE: [HY000](#)

Message: tid %u: node[%u] transaction_hint=%u, transaction_no_hint=%u
[ER_NDB_DISCONNECT_INFO](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010478](#); Symbol: [ER_NDB_COLUMN_DEFAULTS_DIFFER](#); SQLSTATE: [HY000](#)

Message: NDB Internal error: Default values differ for column %u, ndb_default: %d

`ER_NDB_COLUMN_DEFAULTS_DIFFER` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010479`; Symbol: `ER_NDB_COLUMN_SHOULD_NOT_HAVE_NATIVE_DEFAULT`; SQLSTATE: `HY000`

Message: NDB Internal error: Column %u has native default, but shouldn't. Flags=%u, type=%u

`ER_NDB_COLUMN_SHOULD_NOT_HAVE_NATIVE_DEFAULT` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010480`; Symbol: `ER_NDB_FIELD_INFO`; SQLSTATE: `HY000`

Message: field[name: '%s', type: %u, real_type: %u, flags: 0x%x, is_null: %d]

`ER_NDB_FIELD_INFO` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010481`; Symbol: `ER_NDB_COLUMN_INFO`; SQLSTATE: `HY000`

Message: ndbCol[name: '%s', type: %u, column_no: %d, nullable: %d]

`ER_NDB_COLUMN_INFO` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010482`; Symbol: `ER_NDB_OOM_IN_FIX_UNIQUE_INDEX_ATTR_ORDER`; SQLSTATE: `HY000`

Message: fix_unique_index_attr_order: my_malloc(%u) failure

`ER_NDB_OOM_IN_FIX_UNIQUE_INDEX_ATTR_ORDER` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010483`; Symbol: `ER_NDB_SLAVE_MALFORMED_EVENT RECEIVED ON TABLE`; SQLSTATE: `HY000`

Message: NDB Slave : Malformed event received on table %s cannot parse. Stopping Slave.

`ER_NDB_SLAVE_MALFORMED_EVENT RECEIVED ON TABLE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010484`; Symbol: `ER_NDB_SLAVE_CONFLICT_FUNCTIONQUIRES_ROLE`; SQLSTATE: `HY000`

Message: NDB Slave : Conflict function %s defined on table %s requires `ndb_slave_conflict_role` variable to be set. Stopping slave.

`ER_NDB_SLAVE_CONFLICT_FUNCTIONQUIRES_ROLE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010485`; Symbol: `ER_NDB_SLAVE_CONFLICT_DETECTIONQUIRES_TRANSACTION_IDS`; SQLSTATE: `HY000`

Message: NDB Slave : Transactional conflict detection defined on table %s, but events received without transaction ids. Check --ndb-log-transaction-id setting on upstream Cluster.

`ER_NDB_SLAVE_CONFLICT_DETECTIONQUIRES_TRANSACTION_IDS` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010486`; Symbol: `ER_NDB_SLAVE_BINLOG_MISSING_INFO_FOR_CONFLICT_DETECTION`; SQLSTATE: `HY000`

Message: NDB Slave : Binlog event on table %s missing info necessary for conflict detection. Check binlog format options on upstream cluster.

`ER_NDB_SLAVE_BINLOG_MISSING_INFO_FOR_CONFLICT_DETECTION` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010487`; Symbol: `ER_NDB_ERROR_IN_READAUTOINCREMENTVALUE`; SQLSTATE: `HY000`

Message: Error %lu in readAutoIncrementValue(): %s

`ER_NDB_ERROR_IN_READAUTOINCREMENTVALUE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010488`; Symbol: `ER_NDB_FOUND_UNCOMMITTED_AUTOCOMMIT`; SQLSTATE: `HY000`

Message: found uncommitted autocommit+rbwr transaction, commit status: %d

`ER_NDB_FOUND_UNCOMMITTED_AUTOCOMMIT` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010489`; Symbol: `ER_NDB_SLAVE_TOO_MANY_RETRIES`; SQLSTATE: `HY000`

Message: Ndb slave retried transaction %u time(s) in vain. Giving up.

`ER_NDB_SLAVE_TOO_MANY_RETRIES` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010490`; Symbol: `ER_NDB_SLAVE_ERROR_IN_UPDATE_CREATE_INFO`; SQLSTATE: `HY000`

Message: Error %lu in ::update_create_info(): %s

`ER_NDB_SLAVE_ERROR_IN_UPDATE_CREATE_INFO` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010491`; Symbol: `ER_NDB_SLAVE_CANT_ALLOCATE_TABLE_SHARE`; SQLSTATE: `HY000`

Message: NDB: allocating table share for %s failed

`ER_NDB_SLAVE_CANT_ALLOCATE_TABLE_SHARE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010492`; Symbol: `ER_NDB_BINLOG_ERROR_INFO_FROM_DA`; SQLSTATE: `HY000`

Message: NDB Binlog: (%d)%s

`ER_NDB_BINLOG_ERROR_INFO_FROM_DA` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010493`; Symbol: `ER_NDB_BINLOG_CREATE_TABLE_EVENT`; SQLSTATE: `HY000`

Message: NDB Binlog: CREATE TABLE Event: %s

`ER_NDB_BINLOG_CREATE_TABLE_EVENT` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010494`; Symbol: `ER_NDB_BINLOG_FAILED_CREATE_TABLE_EVENT_OPERATIONS`; SQLSTATE: `HY000`

Message: NDB Binlog: FAILED CREATE TABLE event operations. Event: %s

`ER_NDB_BINLOG_FAILED_CREATE_TABLE_EVENT_OPERATIONS` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010495`; Symbol: `ER_NDB_BINLOG_RENAME_EVENT`; SQLSTATE: `HY000`

Message: NDB Binlog: RENAME Event: %s

`ER_NDB_BINLOG_RENAME_EVENT` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010496`; Symbol: `ER_NDB_BINLOG_FAILED_CREATE_EVENT_OPERATIONS_DURING_RENAME`; SQLSTATE: `HY000`

Message: NDB Binlog: FAILED create event operations during RENAME. Event %s
`ER_NDB_BINLOG_FAILED_CREATE_EVENT_OPERATIONS_DURING_RENAME` was added in 8.0.2, removed after 8.0.13.
- Error number: `MY-010497`; Symbol: `ER_NDB_UNEXPECTED_RENAME_TYPE`; SQLSTATE: `HY000`

Message: Unexpected rename case detected, sql_command: %d
`ER_NDB_UNEXPECTED_RENAME_TYPE` was added in 8.0.2, removed after 8.0.13.
- Error number: `MY-010498`; Symbol: `ER_NDB_ERROR_IN_GET_AUTO_INCREMENT`; SQLSTATE: `HY000`

Message: Error %lu in ::get_auto_increment(): %s
`ER_NDB_ERROR_IN_GET_AUTO_INCREMENT` was added in 8.0.2, removed after 8.0.13.
- Error number: `MY-010499`; Symbol: `ER_NDB_CREATING_SHARE_IN_OPEN`; SQLSTATE: `HY000`

Message: Calling ndbcluster_create_binlog_setup(%s) in ::open
`ER_NDB_CREATING_SHARE_IN_OPEN` was added in 8.0.2, removed after 8.0.13.
- Error number: `MY-010500`; Symbol: `ER_NDB_TABLE_OPENED_READ_ONLY`; SQLSTATE: `HY000`

Message: table '%s' opened read only
`ER_NDB_TABLE_OPENED_READ_ONLY` was added in 8.0.2, removed after 8.0.13.
- Error number: `MY-010501`; Symbol: `ER_NDB_INITIALIZE_GIVEN_CLUSTER_PLUGIN_DISABLED`; SQLSTATE: `HY000`

Message: NDB: '--initialize' -> ndbcluster plugin disabled
`ER_NDB_INITIALIZE_GIVEN_CLUSTER_PLUGIN_DISABLED` was added in 8.0.2, removed after 8.0.13.
- Error number: `MY-010502`; Symbol: `ER_NDB_BINLOG_FORMAT_CHANGED_FROM_STMT_TO_MIXED`; SQLSTATE: `HY000`

Message: NDB: Changed global value of binlog_format from STATEMENT to MIXED
`ER_NDB_BINLOG_FORMAT_CHANGED_FROM_STMT_TO_MIXED` was added in 8.0.2, removed after 8.0.13.
- Error number: `MY-010503`; Symbol: `ER_NDB_TRAILING_SHARE_RELEASED_BY_CLOSE_CACHED_TABLES`; SQLSTATE: `HY000`

Message: NDB_SHARE: trailing share %s, released by close_cached_tables
`ER_NDB_TRAILING_SHARE_RELEASED_BY_CLOSE_CACHED_TABLES` was added in 8.0.2, removed after 8.0.13.
- Error number: `MY-010504`; Symbol: `ER_NDB_SHARE_ALREADY_EXISTS`; SQLSTATE: `HY000`

Message: NDB_SHARE: %s already exists use_count=%d. Moving away for safety, but possible memleak.

`ER_NDB_SHARE_ALREADY_EXISTS` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010505`; Symbol: `ER_NDB_HANDLE_TRAILING_SHARE_INFO`; SQLSTATE: `HY000`

Message: handle_trailing_share: %s use_count: %u

`ER_NDB_HANDLE_TRAILING_SHARE_INFO` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010506`; Symbol: `ER_NDB_CLUSTER_GET_SHARE_INFO`; SQLSTATE: `HY000`

Message: ndbcluster_get_share: %s use_count: %u

`ER_NDB_CLUSTER_GET_SHARE_INFO` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010507`; Symbol: `ER_NDB_CLUSTER_REAL_FREE_SHARE_INFO`; SQLSTATE: `HY000`

Message: ndbcluster_real_free_share: %s use_count: %u

`ER_NDB_CLUSTER_REAL_FREE_SHARE_INFO` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010508`; Symbol: `ER_NDB_CLUSTER_REAL_FREE_SHARE_DROP_FAILED`; SQLSTATE: `HY000`

Message: ndbcluster_real_free_share: %s, still open - ignored 'free' (leaked?)

`ER_NDB_CLUSTER_REAL_FREE_SHARE_DROP_FAILED` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010509`; Symbol: `ER_NDB_CLUSTER_FREE_SHARE_INFO`; SQLSTATE: `HY000`

Message: ndbcluster_free_share: %s use_count: %u

`ER_NDB_CLUSTER_FREE_SHARE_INFO` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010510`; Symbol: `ER_NDB_CLUSTER_MARK_SHARE_DROPPED_INFO`; SQLSTATE: `HY000`

Message: ndbcluster_mark_share_dropped: %s use_count: %u

`ER_NDB_CLUSTER_MARK_SHARE_DROPPED_INFO` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010511`; Symbol: `ER_NDB_CLUSTER_MARK_SHARE_DROPPED_DESTROYING_SHARE`; SQLSTATE: `HY000`

Message: ndbcluster_mark_share_dropped: destroys share %s

`ER_NDB_CLUSTER_MARK_SHARE_DROPPED_DESTROYING_SHARE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010512`; Symbol: `ER_NDB_CLUSTER_OOM_THD_NDB`; SQLSTATE: `HY000`

Message: Could not allocate Thd_ndb object

`ER_NDB_CLUSTER_OOM_THD_NDB` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010513`; Symbol: `ER_NDB_BINLOG_NDB_TABLES_INITIALLY_READ_ONLY`; SQLSTATE: `HY000`

Message: NDB Binlog: Ndb tables initially read only.

`ER_NDB_BINLOG_NDB_TABLES_INITIALLY_READ_ONLY` was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010514](#); Symbol: [ER_NDB_UTIL_THREAD_OOM](#); SQLSTATE: [HY000](#)

Message: ndb util thread: malloc failure, query cache not maintained properly
[ER_NDB_UTIL_THREAD_OOM](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010515](#); Symbol: [ER_NDB_ILLEGAL_VALUE_FOR_NDB_RECV_THREAD_CPU_MASK](#); SQLSTATE: [HY000](#)

Message: Trying to set ndb_recv_thread_cpu_mask to illegal value = %s, ignored
[ER_NDB_ILLEGAL_VALUE_FOR_NDB_RECV_THREAD_CPU_MASK](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010516](#); Symbol: [ER_NDB_TOO_MANY_CPUS_IN_NDB_RECV_THREAD_CPU_MASK](#); SQLSTATE: [HY000](#)

Message: Trying to set too many CPU's in ndb_recv_thread_cpu_mask, ignored this variable, erroneous value = %s
[ER_NDB_TOO_MANY_CPUS_IN_NDB_RECV_THREAD_CPU_MASK](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010517](#); Symbol: [ER_DBUG_CHECK_SHARES_OPEN](#); SQLSTATE: [HY000](#)

Message: dbug_check_shares open:
[ER_DBUG_CHECK_SHARES_OPEN](#) was added in 8.0.2.
- Error number: [MY-010518](#); Symbol: [ER_DBUG_CHECK_SHARES_INFO](#); SQLSTATE: [HY000](#)

Message: %s.%s: state: %s(%u) use_count: %u
[ER_DBUG_CHECK_SHARES_INFO](#) was added in 8.0.2.
- Error number: [MY-010519](#); Symbol: [ER_DBUG_CHECK_SHARES_DROPPED](#); SQLSTATE: [HY000](#)

Message: dbug_check_shares dropped:
[ER_DBUG_CHECK_SHARES_DROPPED](#) was added in 8.0.2.
- Error number: [MY-010520](#); Symbol: [ER_INVALID_OR_OLD_TABLE_OR_DB_NAME](#); SQLSTATE: [HY000](#)

Message: Invalid (old?) table or database name '%s'
[ER_INVALID_OR_OLD_TABLE_OR_DB_NAME](#) was added in 8.0.2.
- Error number: [MY-010521](#); Symbol: [ER_TC_RECOVERING_AFTER_CRASH_USING](#); SQLSTATE: [HY000](#)

Message: Recovering after a crash using %s
[ER_TC_RECOVERING_AFTER_CRASH_USING](#) was added in 8.0.2.
- Error number: [MY-010522](#); Symbol: [ER_TC_CANT_AUTO_RECOVER_WITH_TC_HEURISTIC_RECOVER](#); SQLSTATE: [HY000](#)

Message: Cannot perform automatic crash recovery when --tc-heuristic-recover is used
[ER_TC_CANT_AUTO_RECOVER_WITH_TC_HEURISTIC_RECOVER](#) was added in 8.0.2.
- Error number: [MY-010523](#); Symbol: [ER_TC_BAD_MAGIC_IN_TC_LOG](#); SQLSTATE: [HY000](#)

Message: Bad magic header in tc log

`ER_TC_BAD_MAGIC_IN_TC_LOG` was added in 8.0.2.

- Error number: `MY-010524`; Symbol: `ER_TC_NEED_N_SE_SUPPORTING_2PC_FOR_RECOVERY`; SQLSTATE: `HY000`

Message: Recovery failed! You must enable exactly %d storage engines that support two-phase commit protocol

`ER_TC_NEED_N_SE_SUPPORTING_2PC_FOR_RECOVERY` was added in 8.0.2.

- Error number: `MY-010525`; Symbol: `ER_TC_RECOVERY_FAILED_THESE_ARE_YOUR_OPTIONS`; SQLSTATE: `HY000`

Message: Crash recovery failed. Either correct the problem (if it's, for example, out of memory error) and restart, or delete tc log and start mysqld with --tc-heuristic-recover={commit|rollback}

`ER_TC_RECOVERY_FAILED_THESE_ARE_YOUR_OPTIONS` was added in 8.0.2.

- Error number: `MY-010526`; Symbol: `ER_TC_HEURISTIC_RECOVERY_MODE`; SQLSTATE: `HY000`

Message: Heuristic crash recovery mode

`ER_TC_HEURISTIC_RECOVERY_MODE` was added in 8.0.2.

- Error number: `MY-010527`; Symbol: `ER_TC_HEURISTIC_RECOVERY_FAILED`; SQLSTATE: `HY000`

Message: Heuristic crash recovery failed

`ER_TC_HEURISTIC_RECOVERY_FAILED` was added in 8.0.2.

- Error number: `MY-010528`; Symbol: `ER_TC_RESTART_WITHOUT_TC_HEURISTIC_RECOVER`; SQLSTATE: `HY000`

Message: Please restart mysqld without --tc-heuristic-recover

`ER_TC_RESTART_WITHOUT_TC_HEURISTIC_RECOVER` was added in 8.0.2.

- Error number: `MY-010529`; Symbol: `ER_RPL_SLAVE_FAILED_TO_CREATE_OR_RECOVER_INFO_REPOSITORIES`; SQLSTATE: `HY000`

Message: Failed to create or recover replication info repositories.

`ER_RPL_SLAVE_FAILED_TO_CREATE_OR_RECOVER_INFO_REPOSITORIES` was added in 8.0.2.

- Error number: `MY-010530`; Symbol: `ER_RPL_SLAVE_AUTO_POSITION_IS_1_AND_GTID_MODE_IS_OFF`; SQLSTATE: `HY000`

Message: Detected misconfiguration: replication channel '%s' was configured with AUTO_POSITION = 1, but the server was started with --gtid-mode=off. Either reconfigure replication using CHANGE MASTER TO MASTER_AUTO_POSITION = 0 FOR CHANNEL '%s', or change GTID_MODE to some value other than OFF, before starting the slave receiver thread.

`ER_RPL_SLAVE_AUTO_POSITION_IS_1_AND_GTID_MODE_IS_OFF` was added in 8.0.2.

- Error number: `MY-010531`; Symbol: `ER_RPL_SLAVE_CANT_START_SLAVE_FOR_CHANNEL`; SQLSTATE: `HY000`

Message: Slave: Could not start slave for channel '%s'. operation discontinued

`ER_RPL_SLAVE_CANT_START_SLAVE_FOR_CHANNEL` was added in 8.0.2.

- Error number: [MY-010532](#); Symbol: [ER_RPL_SLAVE_CANT_STOP_SLAVE_FOR_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Slave: Could not stop slave for channel '%s' operation discontinued
[ER_RPL_SLAVE_CANT_STOP_SLAVE_FOR_CHANNEL](#) was added in 8.0.2.
- Error number: [MY-010533](#); Symbol: [ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_MASTER](#); SQLSTATE: [HY000](#)

Message: Error during --relay-log-recovery: Could not locate rotate event from the master.
[ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_MASTER](#) was added in 8.0.2.
- Error number: [MY-010534](#); Symbol: [ER_RPL_RECOVERY_ERROR_READ_RELAY_LOG](#); SQLSTATE: [HY000](#)

Message: Error during --relay-log-recovery: Error reading events from relay log: %d
[ER_RPL_RECOVERY_ERROR_READ_RELAY_LOG](#) was added in 8.0.2.
- Error number: [MY-010535](#); Symbol: [ER_RPL_RECOVERY_ERROR_FREEING_IO_CACHE](#); SQLSTATE: [HY000](#)

Message: Error during --relay-log-recovery: Error while freeing IO_CACHE object
[ER_RPL_RECOVERY_ERROR_FREEING_IO_CACHE](#) was added in 8.0.2, removed after 8.0.12.
- Error number: [MY-010536](#); Symbol: [ER_RPL_RECOVERY_SKIPPED_GROUP_REPLICATION_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Relay log recovery skipped for group replication channel.
[ER_RPL_RECOVERY_SKIPPED_GROUP_REPLICATION_CHANNEL](#) was added in 8.0.2.
- Error number: [MY-010537](#); Symbol: [ER_RPL_RECOVERY_ERROR](#); SQLSTATE: [HY000](#)

Message: Error during --relay-log-recovery: %s
[ER_RPL_RECOVERY_ERROR](#) was added in 8.0.2.
- Error number: [MY-010538](#); Symbol: [ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG_INDEX](#); SQLSTATE: [HY000](#)

Message: Error during --relay-log-recovery: Could not read relay log index file due to an IO error.
[ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG_INDEX](#) was added in 8.0.2.
- Error number: [MY-010539](#); Symbol: [ER_RPL_RECOVERY_FILE_MASTER_POS_INFO](#); SQLSTATE: [HY000](#)

Message: Recovery from master pos %ld and file %s%. Previous relay log pos and relay log file had been set to %lld, %s respectively.
[ER_RPL_RECOVERY_FILE_MASTER_POS_INFO](#) was added in 8.0.2.
- Error number: [MY-010540](#); Symbol: [ER_RPL_RECOVERY_REPLICATE_SAME_SERVER_IDQUIRES_POSITION](#); SQLSTATE: [HY000](#)

Message: Error during --relay-log-recovery: replicate_same_server_id is in use and sql thread's positions are not initialized, hence relay log recovery cannot happen.
[ER_RPL_RECOVERY_REPLICATE_SAME_SERVER_IDQUIRES_POSITION](#) was added in 8.0.2.

- Error number: [MY-010541](#); Symbol: [ER_RPL_MTS_RECOVERY_STARTING_COORDINATOR](#); SQLSTATE: [HY000](#)

Message: MTS recovery: starting coordinator thread to fill MTS gaps.
[ER_RPL_MTS_RECOVERY_STARTING_COORDINATOR](#) was added in 8.0.2.
- Error number: [MY-010542](#); Symbol: [ER_RPL_MTS_RECOVERY_FAILED_TO_START_COORDINATOR](#); SQLSTATE: [HY000](#)

Message: MTS recovery: failed to start the coordinator thread. Check the error log for additional details.
[ER_RPL_MTS_RECOVERY_FAILED_TO_START_COORDINATOR](#) was added in 8.0.2.
- Error number: [MY-010543](#); Symbol: [ER_RPL_MTS_AUTOMATIC_RECOVERY_FAILED](#); SQLSTATE: [HY000](#)

Message: MTS recovery: automatic recovery failed. Either the slave server had stopped due to an error during an earlier session or relay logs are corrupted. Fix the cause of the slave side error and restart the slave server or consider using RESET SLAVE.
[ER_RPL_MTS_AUTOMATIC_RECOVERY_FAILED](#) was added in 8.0.2.
- Error number: [MY-010544](#); Symbol: [ER_RPL_MTS_RECOVERY_CANT_OPEN_RELAY_LOG](#); SQLSTATE: [HY000](#)

Message: Failed to open the relay log '%s' (relay_log_pos %s).
[ER_RPL_MTS_RECOVERY_CANT_OPEN_RELAY_LOG](#) was added in 8.0.2.
- Error number: [MY-010545](#); Symbol: [ER_RPL_MTS_RECOVERY_SUCCESSFUL](#); SQLSTATE: [HY000](#)

Message: MTS recovery: completed successfully.
[ER_RPL_MTS_RECOVERY_SUCCESSFUL](#) was added in 8.0.2.
- Error number: [MY-010546](#); Symbol: [ER_RPL_SERVER_ID_MISSING](#); SQLSTATE: [HY000](#)

Message: Server id not set, will not start slave%s
[ER_RPL_SERVER_ID_MISSING](#) was added in 8.0.2.
- Error number: [MY-010547](#); Symbol: [ER_RPL_CANT_CREATE_SLAVE_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create slave thread%.
[ER_RPL_CANT_CREATE_SLAVE_THREAD](#) was added in 8.0.2.
- Error number: [MY-010548](#); Symbol: [ER_RPL_SLAVE_IO_THREAD_WAS_KILLED](#); SQLSTATE: [HY000](#)

Message: The slave IO thread%s was killed while executing initialization query '%s'
[ER_RPL_SLAVE_IO_THREAD_WAS_KILLED](#) was added in 8.0.2.
- Error number: [MY-010549](#); Symbol: [ER_RPL_SLAVE_MASTER_UUID_HAS_CHANGED](#); SQLSTATE: [HY000](#)

Message: The master's UUID has changed, although this should not happen unless you have changed it manually. The old UUID was %.
[ER_RPL_SLAVE_MASTER_UUID_HAS_CHANGED](#) was added in 8.0.2.

- Error number: [MY-010550](#); Symbol: [ER_RPL_SLAVE_USES_CHECKSUM_AND_MASTER_PRE_50](#); SQLSTATE: [HY000](#)

Message: Found a master with MySQL server version older than 5.0. With checksums enabled on the slave, replication might not work correctly. To ensure correct replication, restart the slave server with --replica_sql_verify_checksum=0.

[ER_RPL_SLAVE_USES_CHECKSUM_AND_MASTER_PRE_50](#) was added in 8.0.2.

- Error number: [MY-010551](#); Symbol: [ER_RPL_SLAVE_SECONDS_BEHIND_MASTER_DUBIOUS](#); SQLSTATE: [HY000](#)

Message: "SELECT UNIX_TIMESTAMP()" failed on master, do not trust column Seconds_Behind_Master of SHOW SLAVE STATUS. Error: %s (%d)

[ER_RPL_SLAVE_SECONDS_BEHIND_MASTER_DUBIOUS](#) was added in 8.0.2.

- Error number: [MY-010552](#); Symbol: [ER_RPL_SLAVE_CANT_FLUSH_MASTER_INFO_FILE](#); SQLSTATE: [HY000](#)

Message: Failed to flush master info file.

[ER_RPL_SLAVE_CANT_FLUSH_MASTER_INFO_FILE](#) was added in 8.0.2.

- Error number: [MY-010553](#); Symbol: [ER_RPL_SLAVE_REPORT_HOST_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: The length of report_host is %zu. It is larger than the max length(%d), so this slave cannot be registered to the master%s.

[ER_RPL_SLAVE_REPORT_HOST_TOO_LONG](#) was added in 8.0.2.

- Error number: [MY-010554](#); Symbol: [ER_RPL_SLAVE_REPORT_USER_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: The length of report_user is %zu. It is larger than the max length(%d), so this slave cannot be registered to the master%s.

[ER_RPL_SLAVE_REPORT_USER_TOO_LONG](#) was added in 8.0.2.

- Error number: [MY-010555](#); Symbol: [ER_RPL_SLAVE_REPORT_PASSWORD_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: The length of report_password is %zu. It is larger than the max length(%d), so this slave cannot be registered to the master%s.

[ER_RPL_SLAVE_REPORT_PASSWORD_TOO_LONG](#) was added in 8.0.2.

- Error number: [MY-010556](#); Symbol: [ER_RPL_SLAVE_ERROR_RETRYING](#); SQLSTATE: [HY000](#)

Message: Error on %s: %d %s, will retry in %d secs

[ER_RPL_SLAVE_ERROR_RETRYING](#) was added in 8.0.2.

- Error number: [MY-010557](#); Symbol: [ER_RPL_SLAVE_ERROR_READING_FROM_SERVER](#); SQLSTATE: [HY000](#)

Message: Error reading packet from server%s: %s (server_errno=%d)

[ER_RPL_SLAVE_ERROR_READING_FROM_SERVER](#) was added in 8.0.2.

- Error number: [MY-010558](#); Symbol: [ER_RPL_SLAVE_DUMP_THREAD_KILLED_BY_MASTER](#); SQLSTATE: [HY000](#)

Message: Slave%~~: received end packet from server due to dump thread being killed on master.
Dump threads are killed for example during master shutdown, explicitly by a user, or when the
master receives a binlog send request from a duplicate server UUID <%s> : Error %s~~

[ER_RPL_SLAVE_DUMP_THREAD_KILLED_BY_MASTER](#) was added in 8.0.2.

- Error number: [MY-010559](#); Symbol: [ER_RPL_MTS_STATISTICS](#); SQLSTATE: [HY000](#)

Message: Multi-threaded slave statistics%~~: seconds elapsed = %lu; events assigned = %llu; worker
queues filled over overrun level = %lu; waited due a Worker queue full = %lu; waited due the total
size = %lu; waited at clock conflicts = %llu waited (count) when Workers occupied = %lu waited
when Workers occupied = %llu~~

[ER_RPL_MTS_STATISTICS](#) was added in 8.0.2.

- Error number: [MY-010560](#); Symbol: [ER_RPL_MTS_RECOVERY_COMPLETE](#); SQLSTATE: [HY000](#)

Message: Slave%~~: MTS Recovery has completed at relay log %s, position %llu master log %s,
position %llu.~~

[ER_RPL_MTS_RECOVERY_COMPLETE](#) was added in 8.0.2.

- Error number: [MY-010561](#); Symbol: [ER_RPL_SLAVE_CANT_INIT_RELAY_LOG_POSITION](#); SQLSTATE: [HY000](#)

Message: Error initializing relay log position%~~: %s~~

[ER_RPL_SLAVE_CANT_INIT_RELAY_LOG_POSITION](#) was added in 8.0.2.

- Error number: [MY-010562](#); Symbol: [ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION_STARTED](#); SQLSTATE: [HY000](#)

Message: Slave I/O thread%~~: connected to master '%s@%s:%d', replication started in log '%s' at
position %s~~

[ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION_STARTED](#) was added in 8.0.2.

- Error number: [MY-010563](#); Symbol: [ER_RPL_SLAVE_IO_THREAD_KILLED](#); SQLSTATE: [HY000](#)

Message: Slave I/O thread% ~~killed while connecting to master~~

[ER_RPL_SLAVE_IO_THREAD_KILLED](#) was added in 8.0.2.

- Error number: [MY-010564](#); Symbol: [ER_RPL_SLAVE_IO_THREAD_CANT_REGISTER_ON_MASTER](#); SQLSTATE: [HY000](#)

Message: Slave I/O thread couldn't register on master

[ER_RPL_SLAVE_IO_THREAD_CANT_REGISTER_ON_MASTER](#) was added in 8.0.2.

- Error number: [MY-010565](#); Symbol: [ER_RPL_SLAVE_FORCING_TO_RECONNECT_IO_THREAD](#); SQLSTATE: [HY000](#)

Message: Forcing to reconnect slave I/O thread%

[ER_RPL_SLAVE_FORCING_TO_RECONNECT_IO_THREAD](#) was added in 8.0.2.

- Error number: [MY-010566](#); Symbol: [ER_RPL_SLAVE_ERROR_REQUESTING_BINLOG_DUMP](#); SQLSTATE: [HY000](#)

Message: Failed on request_dump()%s

[ER_RPL_SLAVE_ERROR_REQUESTING_BINLOG_DUMP](#) was added in 8.0.2.

- Error number: [MY-010567](#); Symbol: [ER_RPL_LOG_ENTRY_EXCEEDS_SLAVE_MAX_ALLOWED_PACKET](#); SQLSTATE: [HY000](#)

Message: Log entry on master is longer than slave_max_allowed_packet (%lu) on slave. If the entry is correct, restart the server with a higher value of slave_max_allowed_packet

[ER_RPL_LOG_ENTRY_EXCEEDS_SLAVE_MAX_ALLOWED_PACKET](#) was added in 8.0.2, removed after 8.0.25.

- Error number: [MY-010567](#); Symbol: [ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOWED_PACKET](#); SQLSTATE: [HY000](#)

Message: Log entry on master is longer than replica_max_allowed_packet (%lu) on slave. If the entry is correct, restart the server with a higher value of replica_max_allowed_packet

[ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOWED_PACKET](#) was added in 8.0.26.

- Error number: [MY-010568](#); Symbol: [ER_RPL_SLAVE_STOPPING_AS_MASTER_OOM](#); SQLSTATE: [HY000](#)

Message: Stopping slave I/O thread due to out-of-memory error from master

[ER_RPL_SLAVE_STOPPING_AS_MASTER_OOM](#) was added in 8.0.2.

- Error number: [MY-010569](#); Symbol: [ER_RPL_SLAVE_IO_THREAD_ABORTED_WAITING_FOR_RELAY_LOG_SPACE](#); SQLSTATE: [HY000](#)

Message: Slave I/O thread aborted while waiting for relay log space

[ER_RPL_SLAVE_IO_THREAD_ABORTED_WAITING_FOR_RELAY_LOG_SPACE](#) was added in 8.0.2.

- Error number: [MY-010570](#); Symbol: [ER_RPL_SLAVE_IO_THREAD_EXITING](#); SQLSTATE: [HY000](#)

Message: Slave I/O thread exiting%s, read up to log '%s', position %s

[ER_RPL_SLAVE_IO_THREAD_EXITING](#) was added in 8.0.2.

- Error number: [MY-010571](#); Symbol: [ER_RPL_SLAVE_CANT_INITIALIZE_SLAVE_WORKER](#); SQLSTATE: [HY000](#)

Message: Failed during slave worker initialization%

[ER_RPL_SLAVE_CANT_INITIALIZE_SLAVE_WORKER](#) was added in 8.0.2.

- Error number: [MY-010572](#); Symbol: [ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO_FOR_WORKER](#); SQLSTATE: [HY000](#)

Message: Slave: MTS group recovery relay log info based on Worker-Id %lu, group_relay_log_name %s, group_relay_log_pos %llu group_master_log_name %s, group_master_log_pos %lu

[ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO_FOR_WORKER](#) was added in 8.0.2.

- Error number: [MY-010573](#); Symbol: [ER_RPL_ERROR_LOOKING_FOR_LOG](#); SQLSTATE: [HY000](#)

Message: Error looking for %s.
[ER_RPL_ERROR_LOOKING_FOR_LOG](#) was added in 8.0.2.
- Error number: [MY-010574](#); Symbol: [ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO](#); SQLSTATE: [HY000](#)

Message: Slave: MTS group recovery relay log info group_master_log_name %s, event_master_log_pos %lu.
[ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO](#) was added in 8.0.2.
- Error number: [MY-010575](#); Symbol: [ER_RPL_CANT_FIND_FOLLOWUP_FILE](#); SQLSTATE: [HY000](#)

Message: Error looking for file after %s.
[ER_RPL_CANT_FIND_FOLLOWUP_FILE](#) was added in 8.0.2.
- Error number: [MY-010576](#); Symbol: [ER_RPL_MTS_CHECKPOINT_PERIOD_DIFFERS_FROM_CNT](#); SQLSTATE: [HY000](#)

Message: This an error cnt != mta_checkpoint_period
[ER_RPL_MTS_CHECKPOINT_PERIOD_DIFFERS_FROM_CNT](#) was added in 8.0.2.
- Error number: [MY-010577](#); Symbol: [ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed during slave worker thread creation%
[ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED](#) was added in 8.0.2.
- Error number: [MY-010578](#); Symbol: [ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED_WITH_ERRNO](#); SQLSTATE: [HY000](#)

Message: Failed during slave worker thread creation% (errno= %d)
[ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED_WITH_ERRNO](#) was added in 8.0.2.
- Error number: [MY-010579](#); Symbol: [ER_RPL_SLAVE_FAILED_TO_INIT_PARTITIONS_HASH](#); SQLSTATE: [HY000](#)

Message: Failed to init partitions hash
[ER_RPL_SLAVE_FAILED_TO_INIT_PARTITIONS_HASH](#) was added in 8.0.2.
- Error number: [MY-010580](#); Symbol: [ER_RPL_SLAVE_NDB_TABLES_NOT_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread : NDB : Tables not available after %lu seconds. Consider increasing --ndb-wait-setup value
[ER_RPL_SLAVE_NDB_TABLES_NOT_AVAILABLE](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010581](#); Symbol: [ER_RPL_SLAVE_SQL_THREAD_STARTING](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread% initialized, starting replication in log '%s' at position %s, relay log '%s' position: %s
[ER_RPL_SLAVE_SQL_THREAD_STARTING](#) was added in 8.0.2.

-
- Error number: [MY-010582](#); Symbol: [ER_RPL_SLAVE_SKIP_COUNTER_EXECUTED](#); SQLSTATE: [HY000](#)

Message: 'SQL_REPLICA_SKIP_COUNTER=%ld' executed at relay_log_file=''%s', relay_log_pos=''%ld', master_log_name=''%s', master_log_pos=''%ld' and new position at relay_log_file=''%s', relay_log_pos=''%ld', master_log_name=''%s', master_log_pos=''%ld'

[ER_RPL_SLAVE_SKIP_COUNTER_EXECUTED](#) was added in 8.0.2.

- Error number: [MY-010583](#); Symbol: [ER_RPL_SLAVE_ADDITIONAL_ERROR_INFO_FROM_DA](#); SQLSTATE: [HY000](#)

Message: Slave (additional info): %s Error_code: MY-%06d

[ER_RPL_SLAVE_ADDITIONAL_ERROR_INFO_FROM_DA](#) was added in 8.0.2.

- Error number: [MY-010584](#); Symbol: [ER_RPL_SLAVE_ERROR_INFO_FROM_DA](#); SQLSTATE: [HY000](#)

Message: Slave: %s Error_code: MY-%06d

[ER_RPL_SLAVE_ERROR_INFO_FROM_DA](#) was added in 8.0.2.

- Error number: [MY-010585](#); Symbol: [ER_RPL_SLAVE_ERROR_LOADING_USER_DEFINED_LIBRARY](#); SQLSTATE: [HY000](#)

Message: Error loading user-defined library, slave SQL thread aborted. Install the missing library, and restart the slave SQL thread with "SLAVE START". We stopped at log '%s' position %s

[ER_RPL_SLAVE_ERROR_LOADING_USER_DEFINED_LIBRARY](#) was added in 8.0.2.

- Error number: [MY-010586](#); Symbol: [ER_RPL_SLAVE_ERROR_RUNNING_QUERY](#); SQLSTATE: [HY000](#)

Message: Error running query, slave SQL thread aborted. Fix the problem, and restart the slave SQL thread with "SLAVE START". We stopped at log '%s' position %s

[ER_RPL_SLAVE_ERROR_RUNNING_QUERY](#) was added in 8.0.2.

- Error number: [MY-010587](#); Symbol: [ER_RPL_SLAVE_SQL_THREAD_EXITING](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread %s exiting, replication stopped in log '%s' at position %s

[ER_RPL_SLAVE_SQL_THREAD_EXITING](#) was added in 8.0.2.

- Error number: [MY-010588](#); Symbol: [ER_RPL_SLAVE_READ_INVALID_EVENT_FROM_MASTER](#); SQLSTATE: [HY000](#)

Message: Read invalid event from master: '%s', master could be corrupt but a more likely cause of this is a bug

[ER_RPL_SLAVE_READ_INVALID_EVENT_FROM_MASTER](#) was added in 8.0.2.

- Error number: [MY-010589](#); Symbol: [ER_RPL_SLAVE_QUEUE_EVENT_FAILED_INVALID_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: The queue event failed for channel '%s' as its configuration is invalid.

[ER_RPL_SLAVE_QUEUE_EVENT_FAILED_INVALID_CONFIGURATION](#) was added in 8.0.2.

-
- Error number: [MY-010590](#); Symbol: [ER_RPL_SLAVE_IO_THREAD_DETECTED_UNEXPECTED_EVENT_SEQUENCE](#); SQLSTATE: [HY000](#)

Message: An unexpected event sequence was detected by the IO thread while queuing the event received from master '%s' binary log file, at position %lu.

[ER_RPL_SLAVE_IO_THREAD_DETECTED_UNEXPECTED_EVENT_SEQUENCE](#) was added in 8.0.2.

- Error number: [MY-010591](#); Symbol: [ER_RPL_SLAVE_CANT_USE_CHARSET](#); SQLSTATE: [HY000](#)

Message: '%s' can not be used as client character set. '%s' will be used as default client character set while connecting to master.

[ER_RPL_SLAVE_CANT_USE_CHARSET](#) was added in 8.0.2.

- Error number: [MY-010592](#); Symbol: [ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION_RESUMED](#); SQLSTATE: [HY000](#)

Message: Slave%s: connected to master '%s@%s:%d', replication resumed in log '%s' at position %s

[ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION_RESUMED](#) was added in 8.0.2.

- Error number: [MY-010593](#); Symbol: [ER_RPL_SLAVE_NEXT_LOG_IS_ACTIVE](#); SQLSTATE: [HY000](#)

Message: next log '%s' is active

[ER_RPL_SLAVE_NEXT_LOG_IS_ACTIVE](#) was added in 8.0.2.

- Error number: [MY-010594](#); Symbol: [ER_RPL_SLAVE_NEXT_LOG_IS_INACTIVE](#); SQLSTATE: [HY000](#)

Message: next log '%s' is not active

[ER_RPL_SLAVE_NEXT_LOG_IS_INACTIVE](#) was added in 8.0.2.

- Error number: [MY-010595](#); Symbol: [ER_RPL_SLAVE_SQL_THREAD_IO_ERROR_READING_EVENT](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread%s: I/O error reading event (errno: %d cur_log->error: %d)

[ER_RPL_SLAVE_SQL_THREAD_IO_ERROR_READING_EVENT](#) was added in 8.0.2.

- Error number: [MY-010596](#); Symbol: [ER_RPL_SLAVE_ERROR_READING_RELAY_LOG_EVENTS](#); SQLSTATE: [HY000](#)

Message: Error reading relay log event%s: %s

[ER_RPL_SLAVE_ERROR_READING_RELAY_LOG_EVENTS](#) was added in 8.0.2.

- Error number: [MY-010597](#); Symbol: [ER_SLAVE_CHANGE_MASTER_TO_EXECUTED](#); SQLSTATE: [HY000](#)

Message: 'CHANGE MASTER TO%s executed'. Previous state master_host='%', master_port=%u, master_log_file='%', master_log_pos= %ld, master_bind='>'. New state master_host='%', master_port= %u, master_log_file='%', master_log_pos= %ld, master_bind='>'.

[ER_SLAVE_CHANGE_MASTER_TO_EXECUTED](#) was added in 8.0.2.

- Error number: [MY-010598](#); Symbol: [ER_RPL_SLAVE_NEW_MASTER_INFO_NEEDS_REPOS_TYPE_OTHER_THAN_FILE](#); SQLSTATE: [HY000](#)

Message: Slave: Cannot create new master info structure when repositories are of type FILE.
Convert slave repositories to TABLE to replicate from multiple sources.

[ER_RPL_SLAVE_NEW_MASTER_INFO_NEEDS_REPOS_TYPE_OTHER_THAN_FILE](#) was added in 8.0.2.

- Error number: [MY-010599](#); Symbol: [ER_RPL_FAILED_TO_STAT_LOG_IN_INDEX](#); SQLSTATE: [HY000](#)

Message: log %s listed in the index, but failed to stat.

[ER_RPL_FAILED_TO_STAT_LOG_IN_INDEX](#) was added in 8.0.2.

- Error number: [MY-010600](#); Symbol: [ER_RPL_LOG_NOT_FOUND_WHILE_COUNTING_RELAY_LOG_SPACE](#); SQLSTATE: [HY000](#)

Message: Could not find first log while counting relay log space.

[ER_RPL_LOG_NOT_FOUND_WHILE_COUNTING_RELAY_LOG_SPACE](#) was added in 8.0.2.

- Error number: [MY-010601](#); Symbol: [ER_SLAVE_CANT_USE_TEMPDIR](#); SQLSTATE: [HY000](#)

Message: Unable to use slave's temporary directory '%s'.

[ER_SLAVE_CANT_USE_TEMPDIR](#) was added in 8.0.2.

- Error number: [MY-010602](#); Symbol: [ER_RPL_RELAY_LOG_NEEDS_FILE_NOT_DIRECTORY](#); SQLSTATE: [HY000](#)

Message: Path '%s' is a directory name, please specify a file name for --relay-log option.

[ER_RPL_RELAY_LOG_NEEDS_FILE_NOT_DIRECTORY](#) was added in 8.0.2.

- Error number: [MY-010603](#); Symbol: [ER_RPL_RELAY_LOG_INDEX_NEEDS_FILE_NOT_DIRECTORY](#); SQLSTATE: [HY000](#)

Message: Path '%s' is a directory name, please specify a file name for --relay-log-index option.

[ER_RPL_RELAY_LOG_INDEX_NEEDS_FILE_NOT_DIRECTORY](#) was added in 8.0.2.

- Error number: [MY-010604](#); Symbol: [ER_RPL_PLEASE_USE_OPTION_RELAY_LOG](#); SQLSTATE: [HY000](#)

Message: Neither --relay-log nor --relay-log-index were used; so replication may break when this MySQL server acts as a slave and has his hostname changed!! Please use '--relay-log=%s' to avoid this problem.

[ER_RPL_PLEASE_USE_OPTION_RELAY_LOG](#) was added in 8.0.2.

- Error number: [MY-010605](#); Symbol: [ER_RPL_OPEN_INDEX_FILE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed in open_index_file() called from Relay_log_info::rli_init_info().

[ER_RPL_OPEN_INDEX_FILE_FAILED](#) was added in 8.0.2.

- Error number: [MY-010606](#); Symbol: [ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_RLI_INIT_INFO](#); SQLSTATE: [HY000](#)

Message: Failed in init_gtid_sets() called from Relay_log_info::rli_init_info().

`ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_RLI_INIT_INFO` was added in 8.0.2.

- Error number: `MY-010607`; Symbol: `ER_RPL_CANT_OPEN_LOG_IN_RLI_INIT_INFO`; SQLSTATE: `HY000`

Message: Failed in open_log() called from Relay_log_info::rli_init_info().

`ER_RPL_CANT_OPEN_LOG_IN_RLI_INIT_INFO` was added in 8.0.2.

- Error number: `MY-010608`; Symbol: `ER_RPL_ERROR_WRITING_RELAY_LOG_CONFIGURATION`; SQLSTATE: `HY000`

Message: Error writing relay log configuration.

`ER_RPL_ERROR_WRITING_RELAY_LOG_CONFIGURATION` was added in 8.0.2.

- Error number: `MY-010609`; Symbol: `ER_NDB_OOM_GET_NDB_BLOBS_VALUE`; SQLSTATE: `HY000`

Message: get_ndb_blobs_value: my_malloc(%u) failed

`ER_NDB_OOM_GET_NDB_BLOBS_VALUE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010610`; Symbol: `ER_NDB_THREAD_TIMED_OUT`; SQLSTATE: `HY000`

Message: NDB: Thread id %u timed out (30s) waiting for epoch %u/%u to be handled. Progress : %u/%u -> %u/%u.

`ER_NDB_THREAD_TIMED_OUT` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010611`; Symbol: `ER_NDB_TABLE_IS_NOT_DISTRIBUTED`; SQLSTATE: `HY000`

Message: NDB: Inconsistency detected in distributed privilege tables. Table '%s.%s' is not distributed

`ER_NDB_TABLE_IS_NOT_DISTRIBUTED` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010612`; Symbol: `ER_NDB_CREATING_TABLE`; SQLSTATE: `HY000`

Message: NDB: Creating %s.%s

`ER_NDB_CREATING_TABLE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010613`; Symbol: `ER_NDB_FLUSHING_TABLE_INFO`; SQLSTATE: `HY000`

Message: NDB: Flushing %s.%s

`ER_NDB_FLUSHING_TABLE_INFO` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010614`; Symbol: `ER_NDB_CLEANING_STRAY_TABLES`; SQLSTATE: `HY000`

Message: NDB: Cleaning stray tables from database '%s'

`ER_NDB_CLEANING_STRAY_TABLES` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010615`; Symbol: `ER_NDB_DISCOVERED_MISSING_DB`; SQLSTATE: `HY000`

Message: NDB: Discovered missing database '%s'

`ER_NDB_DISCOVERED_MISSING_DB` was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010616](#); Symbol: [ER_NDB_DISCOVERED_REMAINING_DB](#); SQLSTATE: [HY000](#)

Message: NDB: Discovered remaining database '%s'
[ER_NDB_DISCOVERED_REMAINING_DB](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010617](#); Symbol: [ER_NDB_CLUSTER_FIND_ALL_DBs_RETRY](#); SQLSTATE: [HY000](#)

Message: NDB: ndbcluster_find_all_databases retry: %u - %s
[ER_NDB_CLUSTER_FIND_ALL_DBs_RETRY](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010618](#); Symbol: [ER_NDB_CLUSTER_FIND_ALL_DBs_FAIL](#); SQLSTATE: [HY000](#)

Message: NDB: ndbcluster_find_all_databases fail: %u - %s
[ER_NDB_CLUSTER_FIND_ALL_DBs_FAIL](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010619](#); Symbol: [ER_NDB_SKIPPING_SETUP_TABLE](#); SQLSTATE: [HY000](#)

Message: NDB: skipping setup table %s.%s, in state %d
[ER_NDB_SKIPPING_SETUP_TABLE](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010620](#); Symbol: [ER_NDB_FAILED_TO_SET_UP_TABLE](#); SQLSTATE: [HY000](#)

Message: NDB: failed to setup table %s.%s, error: %d, %s
[ER_NDB_FAILED_TO_SET_UP_TABLE](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010621](#); Symbol: [ER_NDB_MISSING_FRM_DISCOVERING](#); SQLSTATE: [HY000](#)

Message: NDB: missing frm for %s.%s, discovering...
[ER_NDB_MISSING_FRM_DISCOVERING](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010622](#); Symbol: [ER_NDB_MISMATCH_IN_FRM_DISCOVERING](#); SQLSTATE: [HY000](#)

Message: NDB: mismatch in frm for %s.%s, discovering...
[ER_NDB_MISMATCH_IN_FRM_DISCOVERING](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010623](#); Symbol: [ER_NDB_BINLOG_CLEANING_UP_SETUP_LEFTOVERS](#); SQLSTATE: [HY000](#)

Message: ndb_binlog_setup: Clean up leftovers
[ER_NDB_BINLOG_CLEANING_UP_SETUP_LEFTOVERS](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010624](#); Symbol: [ER_NDB_WAITING_INFO](#); SQLSTATE: [HY000](#)

Message: NDB %s: waiting max %u sec for %s %s. epochs: (%u/%u,%u/%u,%u/%u) injector proc_info: %s
[ER_NDB_WAITING_INFO](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010625](#); Symbol: [ER_NDB_WAITING_INFO_WITH_MAP](#); SQLSTATE: [HY000](#)

Message: NDB %s: waiting max %u sec for %s %s. epochs: (%u/%u,%u/%u,%u/%u) injector proc_info: %s map: %x%08x

`ER_NDB_WAITING_INFO_WITH_MAP` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010626`; Symbol: `ER_NDB_TIMEOUT_WHILE_DISTRIBUTING`; SQLSTATE: `HY000`

Message: NDB %s: distributing %s timed out. Ignoring...

`ER_NDB_TIMEOUT_WHILE_DISTRIBUTING` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010627`; Symbol: `ER_NDB_NOT_WAITING_FOR_DISTRIBUTING`; SQLSTATE: `HY000`

Message: NDB %s: not waiting for distributing %s

`ER_NDB_NOT_WAITING_FOR_DISTRIBUTING` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010628`; Symbol: `ER_NDB DISTRIBUTED_INFO`; SQLSTATE: `HY000`

Message: NDB: distributed %s.%s(%u/%u) type: %s(%u) query: '\%s' to %x%08x

`ER_NDB DISTRIBUTED_INFO` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010629`; Symbol: `ER_NDB DISTRIBUTION_COMPLETE`; SQLSTATE: `HY000`

Message: NDB: distribution of %s.%s(%u/%u) type: %s(%u) query: '\%s' - complete!

`ER_NDB DISTRIBUTION_COMPLETE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010630`; Symbol: `ER_NDB_SCHEMA DISTRIBUTION FAILED`; SQLSTATE: `HY000`

Message: NDB Schema dist: Data node: %d failed, subscriber bitmask %x%08x

`ER_NDB_SCHEMA DISTRIBUTION FAILED` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010631`; Symbol: `ER_NDB_SCHEMA DISTRIBUTION REPORTS SUBSCRIBE`; SQLSTATE: `HY000`

Message: NDB Schema dist: Data node: %d reports subscribe from node %d, subscriber bitmask %x%08x

`ER_NDB_SCHEMA DISTRIBUTION REPORTS SUBSCRIBE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010632`; Symbol: `ER_NDB_SCHEMA DISTRIBUTION REPORTS UNSUBSCRIBE`; SQLSTATE: `HY000`

Message: NDB Schema dist: Data node: %d reports unsubscribe from node %d, subscriber bitmask %x%08x

`ER_NDB_SCHEMA DISTRIBUTION REPORTS UNSUBSCRIBE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010633`; Symbol: `ER_NDB_BINLOG CANT DISCOVER_TABLE_FROM_SCHEMA_EVENT`; SQLSTATE: `HY000`

Message: NDB Binlog: Could not discover table '%s.%s' from binlog schema event '%s' from node %d. my_errno: %d

`ER_NDB_BINLOG CANT DISCOVER_TABLE_FROM_SCHEMA_EVENT` was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010634](#); Symbol: [ER_NDB_BINLOG_SIGNALLING_UNKNOWN_VALUE](#); SQLSTATE: [HY000](#)

Message: NDB: unknown value for binlog signalling 0x%X, %s not logged
[ER_NDB_BINLOG_SIGNALLING_UNKNOWN_VALUE](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010635](#); Symbol: [ER_NDB_BINLOG_REPLY_TO](#); SQLSTATE: [HY000](#)

Message: NDB: reply to %s.%s(%u/%u) from %s to %x%08x
[ER_NDB_BINLOG_REPLY_TO](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010636](#); Symbol: [ER_NDB_BINLOG_CANT_RELEASE_SLOCK](#); SQLSTATE: [HY000](#)

Message: NDB: Could not release slock on '%s.%s', Error code: %d Message: %s
[ER_NDB_BINLOG_CANT_RELEASE_SLOCK](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010637](#); Symbol: [ER_NDB_CANT_FIND_TABLE](#); SQLSTATE: [HY000](#)

Message: NDB schema: Could not find table '%s.%s' in NDB
[ER_NDB_CANT_FIND_TABLE](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010638](#); Symbol: [ER_NDB_DISCARDING_EVENT_NO_OBJ](#); SQLSTATE: [HY000](#)

Message: NDB: Discarding event...no obj: %s (%u/%u)
[ER_NDB_DISCARDING_EVENT_NO_OBJ](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010639](#); Symbol: [ER_NDB_DISCARDING_EVENT_ID_VERSION_MISMATCH](#); SQLSTATE: [HY000](#)

Message: NDB: Discarding event...key: %s non matching id/version [%u/%u] != [%u/%u]
[ER_NDB_DISCARDING_EVENT_ID_VERSION_MISMATCH](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010640](#); Symbol: [ER_NDB_CLEAR_SLOCK_INFO](#); SQLSTATE: [HY000](#)

Message: NDB: CLEAR_SLOCK key: %s(%u/%u) %x%08x, from %s to %x%08x
[ER_NDB_CLEAR_SLOCK_INFO](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010641](#); Symbol: [ER_NDB_BINLOG_SKIPPING_LOCAL_TABLE](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Skipping locally defined table '%s.%s' from binlog schema event '%s' from node %d.
[ER_NDB_BINLOG_SKIPPING_LOCAL_TABLE](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010642](#); Symbol: [ER_NDB_BINLOG_ONLINE_ALTER_RENAME](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: handling online alter/rename
[ER_NDB_BINLOG_ONLINE_ALTER_RENAME](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010643](#); Symbol: [ER_NDB_BINLOG_CANT_REOPEN_SHADOW_TABLE](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Failed to re-open shadow table %s.%s

`ER_NDB_BINLOG_CANT_REOPEN_SHADOW_TABLE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010644`; Symbol: `ER_NDB_BINLOG_ONLINE_ALTER_RENAME_COMPLETE`; SQLSTATE: `HY000`

Message: NDB Binlog: handling online alter/rename done

`ER_NDB_BINLOG_ONLINE_ALTER_RENAME_COMPLETE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010645`; Symbol: `ER_NDB_BINLOG_SKIPPING_DROP_OF_LOCAL_TABLE`; SQLSTATE: `HY000`

Message: NDB Binlog: Skipping drop of locally defined table '%s.%s' from binlog schema event '%s' from node %d.

`ER_NDB_BINLOG_SKIPPING_DROP_OF_LOCAL_TABLE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010646`; Symbol: `ER_NDB_BINLOG_SKIPPING_RENAME_OF_LOCAL_TABLE`; SQLSTATE: `HY000`

Message: NDB Binlog: Skipping renaming locally defined table '%s.%s' from binlog schema event '%s' from node %d.

`ER_NDB_BINLOG_SKIPPING_RENAME_OF_LOCAL_TABLE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010647`; Symbol: `ER_NDB_BINLOG_SKIPPING_DROP_OF_DB_CONTAINING_LOCAL_TABLES`; SQLSTATE: `HY000`

Message: NDB Binlog: Skipping drop database '%s' since it contained local tables binlog schema event '%s' from node %d.

`ER_NDB_BINLOG_SKIPPING_DROP_OF_DB_CONTAINING_LOCAL_TABLES` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010648`; Symbol: `ER_NDB_BINLOG_GOT_DIST_PRIV_EVENT_FLUSHING_PRIVILEGES`; SQLSTATE: `HY000`

Message: Got dist_priv event: %s, flushing privileges

`ER_NDB_BINLOG_GOT_DIST_PRIV_EVENT_FLUSHING_PRIVILEGES` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010649`; Symbol: `ER_NDB_BINLOG_GOT_SCHEMA_EVENT`; SQLSTATE: `HY000`

Message: NDB: got schema event on %s.%s(%u/%u) query: '%s' type: %s(%d) node: %u slot: %x %08x

`ER_NDB_BINLOG_GOT_SCHEMA_EVENT` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010650`; Symbol: `ER_NDB_BINLOG_SKIPPING_OLD_SCHEMA_OPERATION`; SQLSTATE: `HY000`

Message: NDB schema: Skipping old schema operation(RENAME_TABLE_NEW) on %s.%s

`ER_NDB_BINLOG_SKIPPING_OLD_SCHEMA_OPERATION` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010651`; Symbol: `ER_NDB_CLUSTER_FAILURE`; SQLSTATE: `HY000`

Message: NDB Schema dist: cluster failure at epoch %u/%u.

`ER_NDB_CLUSTER_FAILURE` was added in 8.0.2, removed after 8.0.13.

-
- Error number: [MY-010652](#); Symbol: [ER_NDB_TABLES_INITIALIZALLY_READ_ONLY_ON_RECONNECT](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: ndb tables initially read only on reconnect.

[ER_NDB_TABLES_INITIALIZALLY_READ_ONLY_ON_RECONNECT](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010653](#); Symbol: [ER_NDB_IGNORING_UNKNOWN_EVENT](#); SQLSTATE: [HY000](#)

Message: NDB Schema dist: unknown event %u, ignoring...

[ER_NDB_IGNORING_UNKNOWN_EVENT](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010654](#); Symbol: [ER_NDB_BINLOG_OPENING_INDEX](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Opening ndb_binlog_index: %d, '%s'

[ER_NDB_BINLOG_OPENING_INDEX](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010655](#); Symbol: [ER_NDB_BINLOG_CANT_LOCK_NDB_BINLOG_INDEX](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Unable to lock table ndb_binlog_index

[ER_NDB_BINLOG_CANT_LOCK_NDB_BINLOG_INDEX](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010656](#); Symbol: [ER_NDB_BINLOG_INJECTING_RANDOM_WRITE_FAILURE](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Injecting random write failure

[ER_NDB_BINLOG_INJECTING_RANDOM_WRITE_FAILURE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010657](#); Symbol: [ER_NDB_BINLOG_CANT_WRITE_TO_NDB_BINLOG_INDEX](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Failed writing to ndb_binlog_index for epoch %u/%u orig_server_id %u orig_epoch %u/%u with error %d.

[ER_NDB_BINLOG_CANT_WRITE_TO_NDB_BINLOG_INDEX](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010658](#); Symbol: [ER_NDB_BINLOG_WRITING_TO_NDB_BINLOG_INDEX](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Writing row (%s) to ndb_binlog_index - %s

[ER_NDB_BINLOG_WRITING_TO_NDB_BINLOG_INDEX](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010659](#); Symbol: [ER_NDB_BINLOG_CANT_COMMIT_TO_NDB_BINLOG_INDEX](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Failed committing transaction to ndb_binlog_index with error %d.

[ER_NDB_BINLOG_CANT_COMMIT_TO_NDB_BINLOG_INDEX](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010660](#); Symbol: [ER_NDB_BINLOG_WRITE_TO_NDB_BINLOG_INDEX_FAILED_AFTER_KILL](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Failed writing to ndb_binlog_index table while retrying after kill during shutdown

[ER_NDB_BINLOG_WRITE_TO_NDB_BINLOG_INDEX_FAILED_AFTER_KILL](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010661](#); Symbol: [ER_NDB_BINLOG_USING_SERVER_ID_0_SLAVES_WILL_NOT](#); SQLSTATE: [HY000](#)

Message: NDB: server id set to zero - changes logged to bin log with server id zero will be logged with another server id by slave mysqlds

[ER_NDB_BINLOG_USING_SERVER_ID_0_SLAVES_WILL_NOT](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010662](#); Symbol: [ER_NDB_SERVER_ID_RESERVED_OR_TOO_LARGE](#); SQLSTATE: [HY000](#)

Message: NDB: server id provided is too large to be represented in opt_server_id_bits or is reserved

[ER_NDB_SERVER_ID_RESERVED_OR_TOO_LARGE](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010663](#); Symbol: [ER_NDB_BINLOG_NDB_LOG_TRANSACTION_ID_REQUIRES_V2_ROW_EVENTS](#); SQLSTATE: [HY000](#)

Message: NDB: --ndb-log-transaction-id requires v2 Binlog row events but server is using v1.

[ER_NDB_BINLOG_NDB_LOG_TRANSACTION_ID_REQUIRES_V2_ROW_EVENTS](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010664](#); Symbol: [ER_NDB_BINLOG_NDB_LOG_APPLY_STATUS_FORCING_FULL_USE_WRITE](#); SQLSTATE: [HY000](#)

Message: NDB: ndb-log-apply-status forcing %s.%s to FULL USE_WRITE

[ER_NDB_BINLOG_NDB_LOG_APPLY_STATUS_FORCING_FULL_USE_WRITE](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010665](#); Symbol: [ER_NDB_BINLOG_GENERIC_MESSAGE](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: %s

[ER_NDB_BINLOG_GENERIC_MESSAGE](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010666](#); Symbol: [ER_NDB_CONFLICT_GENERIC_MESSAGE](#); SQLSTATE: [HY000](#)

Message: %s

[ER_NDB_CONFLICT_GENERIC_MESSAGE](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010667](#); Symbol: [ER_NDB_TRANS_DEPENDENCY_TRACKER_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

[ER_NDB_TRANS_DEPENDENCY_TRACKER_ERROR](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010668](#); Symbol: [ER_NDB_CONFLICT_FN_PARSE_ERROR](#); SQLSTATE: [HY000](#)

Message: NDB Slave: Table %s.%s : Parse error on conflict fn : %s
[ER_NDB_CONFLICT_FN_PARSE_ERROR](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010669](#); Symbol: [ER_NDB_CONFLICT_FN_SETUP_ERROR](#); SQLSTATE: [HY000](#)

Message: NDB Slave: Table %s.%s : %s
[ER_NDB_CONFLICT_FN_SETUP_ERROR](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010670](#); Symbol: [ER_NDB_BINLOG_FAILED_TO_GET_TABLE](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Failed to get table %s from ndb: %s, %d
[ER_NDB_BINLOG_FAILED_TO_GET_TABLE](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010671](#); Symbol: [ER_NDB_BINLOG_NOT_LOGGING](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: NOT logging %s
[ER_NDB_BINLOG_NOT_LOGGING](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010672](#); Symbol: [ER_NDB_BINLOG_CREATE_TABLE_EVENT_FAILED](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: FAILED CREATE (DISCOVER) TABLE Event: %s
[ER_NDB_BINLOG_CREATE_TABLE_EVENT_FAILED](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010673](#); Symbol: [ER_NDB_BINLOG_CREATE_TABLE_EVENT_INFO](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: CREATE (DISCOVER) TABLE Event: %s
[ER_NDB_BINLOG_CREATE_TABLE_EVENT_INFO](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010674](#); Symbol: [ER_NDB_BINLOG_DISCOVER_TABLE_EVENT_INFO](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: DISCOVER TABLE Event: %s
[ER_NDB_BINLOG_DISCOVER_TABLE_EVENT_INFO](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010675](#); Symbol: [ER_NDB_BINLOG_BLOB_REQUIRES_PK](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: logging of table %s with BLOB attribute and no PK is not supported
[ER_NDB_BINLOG_BLOB_REQUIRES_PK](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010676](#); Symbol: [ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Unable to create event in database. Event: %s Error Code: %d Message: %s
[ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010677](#); Symbol: [ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB_AND_CANT_DROP](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Unable to create event in database. Attempt to correct with drop failed. Event: %s Error Code: %d Message: %s

`ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB_AND_CANT_DROP` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010678`; Symbol: `ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB_DROPPED`; SQLSTATE: `HY000`

Message: NDB Binlog: Unable to create event in database. Attempt to correct with drop ok, but create failed. Event: %s Error Code: %d Message: %s

`ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB_DROPPED` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010679`; Symbol: `ER_NDB_BINLOG_DISCOVER_REUSE_OLD_EVENT_OPS`; SQLSTATE: `HY000`

Message: NDB Binlog: discover reusing old ev op

`ER_NDB_BINLOG_DISCOVER_REUSE_OLD_EVENT_OPS` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010680`; Symbol: `ER_NDB_BINLOG_CREATING_NDBEVENTOPERATION_FAILED`; SQLSTATE: `HY000`

Message: NDB Binlog: Creating NdbEventOperation failed for %s

`ER_NDB_BINLOG_CREATING_NDBEVENTOPERATION_FAILED` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010681`; Symbol: `ER_NDB_BINLOG_CANT_CREATE_BLOB`; SQLSTATE: `HY000`

Message: NDB Binlog: Creating NdbEventOperation blob field %u handles failed (code=%d) for %s

`ER_NDB_BINLOG_CANT_CREATE_BLOB` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010682`; Symbol: `ER_NDB_BINLOG_NDBEVENT_EXECUTE_FAILED`; SQLSTATE: `HY000`

Message: NDB Binlog: ndbevent->execute failed for %s; %d %s

`ER_NDB_BINLOG_NDBEVENT_EXECUTE_FAILED` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010683`; Symbol: `ER_NDB_CREATE_EVENT_OPS_LOGGING_INFO`; SQLSTATE: `HY000`

Message: NDB Binlog: logging %s (%s,%s)

`ER_NDB_CREATE_EVENT_OPS_LOGGING_INFO` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010684`; Symbol: `ER_NDB_BINLOG_CANT_DROP_EVENT_FROM_DB`; SQLSTATE: `HY000`

Message: NDB Binlog: Unable to drop event in database. Event: %s Error Code: %d Message: %s

`ER_NDB_BINLOG_CANT_DROP_EVENT_FROM_DB` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010685`; Symbol: `ER_NDB_TIMED_OUT_IN_DROP_TABLE`; SQLSTATE: `HY000`

Message: NDB %s: %s timed out. Ignoring...

`ER_NDB_TIMED_OUT_IN_DROP_TABLE` was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010686](#); Symbol: [ER_NDB_BINLOG_UNHANDLED_ERROR_FOR_TABLE](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: unhandled error %d for table %s
[ER_NDB_BINLOG_UNHANDLED_ERROR_FOR_TABLE](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010687](#); Symbol: [ER_NDB_BINLOG_CLUSTER_FAILURE](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: cluster failure for %s at epoch %u/%u.
[ER_NDB_BINLOG_CLUSTER_FAILURE](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010688](#); Symbol: [ER_NDB_BINLOG_UNKNOWN_NON_DATA_EVENT](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: unknown non data event %d for %s. Ignoring...
[ER_NDB_BINLOG_UNKNOWN_NON_DATA_EVENT](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010689](#); Symbol: [ER_NDB_BINLOG_INJECTOR_DISCARDING_ROW_EVENT_METADATA](#); SQLSTATE: [HY000](#)

Message: NDB: Binlog Injector discarding row event meta data as server is using v1 row events. (%u %x)
[ER_NDB_BINLOG_INJECTOR_DISCARDING_ROW_EVENT_METADATA](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010690](#); Symbol: [ER_NDB_REMAINING_OPEN_TABLES](#); SQLSTATE: [HY000](#)

Message: remove_all_event_operations: Remaining open tables:
[ER_NDB_REMAINING_OPEN_TABLES](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010691](#); Symbol: [ER_NDB_REMAINING_OPEN_TABLE_INFO](#); SQLSTATE: [HY000](#)

Message: %s.%s, use_count: %u
[ER_NDB_REMAINING_OPEN_TABLE_INFO](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010692](#); Symbol: [ER_NDB_COULD_NOT_GET_APPLY_STATUS_SHARE](#); SQLSTATE: [HY000](#)

Message: NDB: Could not get apply status share
[ER_NDB_COULD_NOT_GET_APPLY_STATUS_SHARE](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010693](#); Symbol: [ER_NDB_BINLOG_SERVER_SHUTDOWN_DURING_NDB_CLUSTER_START](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Server shutdown detected while waiting for ndbcluster to start...
[ER_NDB_BINLOG_SERVER_SHUTDOWN_DURING_NDB_CLUSTER_START](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010694](#); Symbol: [ER_NDB_BINLOG_CLUSTER_RESTARTED_RESET_MASTER_SUGGESTED](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: cluster has been restarted --initial or with older filesystem.
ndb_latest_handled_binlog_epoch: %u/%u, while current epoch: %u/%u. RESET MASTER should be issued. Resetting ndb_latest_handled_binlog_epoch.

`ER_NDB_BINLOG_CLUSTER_RESTARTED_RESET_MASTER_SUGGESTED` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010695`; Symbol: `ER_NDB_BINLOG_CLUSTER_HAS_RECONNECTED`; SQLSTATE: `HY000`

Message: NDB Binlog: cluster has reconnected. Changes to the database that occurred while disconnected will not be in the binlog

`ER_NDB_BINLOG_CLUSTER_HAS_RECONNECTED` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010696`; Symbol: `ER_NDB_BINLOG_STARTING_LOG_AT_EPOCH`; SQLSTATE: `HY000`

Message: NDB Binlog: starting log at epoch %u/%u

`ER_NDB_BINLOG_STARTING_LOG_AT_EPOCH` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010697`; Symbol: `ER_NDB_BINLOG_NDB_TABLES_WRITABLE`; SQLSTATE: `HY000`

Message: NDB Binlog: ndb tables writable

`ER_NDB_BINLOG_NDB_TABLES_WRITABLE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010698`; Symbol: `ER_NDB_BINLOG_SHUTDOWN_DETECTED`; SQLSTATE: `HY000`

Message: NDB Binlog: Server shutdown detected...

`ER_NDB_BINLOG_SHUTDOWN_DETECTED` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010699`; Symbol: `ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_WAITING`; SQLSTATE: `HY000`

Message: NDB Binlog: Just lost schema connection, hanging around

`ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_WAITING` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010700`; Symbol: `ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_CONTINUING`; SQLSTATE: `HY000`

Message: NDB Binlog: ...and on our way

`ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_CONTINUING` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010701`; Symbol: `ER_NDB_BINLOG_ERROR_HANDLING_SCHEMA_EVENT`; SQLSTATE: `HY000`

Message: NDB: error %lu (%s) on handling binlog schema event

`ER_NDB_BINLOG_ERROR_HANDLING_SCHEMA_EVENT` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010702`; Symbol: `ER_NDB_BINLOG_CANT_INJECT_APPLY_STATUS_WRITE_ROW`; SQLSTATE: `HY000`

Message: NDB Binlog: Failed to inject apply status write row

`ER_NDB_BINLOG_CANT_INJECT_APPLY_STATUS_WRITE_ROW` was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010703](#); Symbol: [ER_NDB_BINLOG_ERROR_DURING_GCI_ROLLBACK](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Error during ROLLBACK of GCI %u/%u. Error: %d
[ER_NDB_BINLOG_ERROR_DURING_GCI_ROLLBACK](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010704](#); Symbol: [ER_NDB_BINLOG_ERROR_DURING_GCI_COMMIT](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Error during COMMIT of GCI. Error: %d
[ER_NDB_BINLOG_ERROR_DURING_GCI_COMMIT](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010705](#); Symbol: [ER_NDB_BINLOG_LATEST_TRX_IN_EPOCH_NOT_IN_BINLOG](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: latest transaction in epoch %u/%u not in binlog as latest handled epoch is %u/%u
[ER_NDB_BINLOG_LATEST_TRX_IN_EPOCH_NOT_IN_BINLOG](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010706](#); Symbol: [ER_NDB_BINLOG_RELEASEING_EXTRA_SHARE_REFERENCES](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Release extra share references
[ER_NDB_BINLOG_RELEASEING_EXTRA_SHARE_REFERENCES](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010707](#); Symbol: [ER_NDB_BINLOG_REMAINING_OPEN_TABLES](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: remaining open tables:
[ER_NDB_BINLOG_REMAINING_OPEN_TABLES](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010708](#); Symbol: [ER_NDB_BINLOG_REMAINING_OPEN_TABLE_INFO](#); SQLSTATE: [HY000](#)

Message: %s.%s state: %u use_count: %u
[ER_NDB_BINLOG_REMAINING_OPEN_TABLE_INFO](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010709](#); Symbol: [ER_TREE_CORRUPT_PARENT_SHOULD_POINT_AT_PARENT](#); SQLSTATE: [HY000](#)

Message: Wrong tree: Parent doesn't point at parent
[ER_TREE_CORRUPT_PARENT_SHOULD_POINT_AT_PARENT](#) was added in 8.0.2.
- Error number: [MY-010710](#); Symbol: [ER_TREE_CORRUPT_ROOT_SHOULD_BE_BLACK](#); SQLSTATE: [HY000](#)

Message: Wrong tree: Root should be black
[ER_TREE_CORRUPT_ROOT_SHOULD_BE_BLACK](#) was added in 8.0.2.
- Error number: [MY-010711](#); Symbol: [ER_TREE_CORRUPT_2_CONSECUTIVE_RED](#); SQLSTATE: [HY000](#)

Message: Wrong tree: Found two red in a row

`ER_TREE_CORRUPT_2_CONSECUTIVE_RED`s was added in 8.0.2.

- Error number: `MY-010712`; Symbol: `ER_TREE_CORRUPT_RIGHT_IS_LEFT`; SQLSTATE: `HY000`

Message: Wrong tree: Found right == left

`ER_TREE_CORRUPT_RIGHT_IS_LEFT` was added in 8.0.2.

- Error number: `MY-010713`; Symbol: `ER_TREE_CORRUPT_INCORRECT_BLACK_COUNT`; SQLSTATE: `HY000`

Message: Wrong tree: Incorrect black-count: %d - %d

`ER_TREE_CORRUPT_INCORRECT_BLACK_COUNT` was added in 8.0.2.

- Error number: `MY-010714`; Symbol: `ER_WRONG_COUNT_FOR_ORIGIN`; SQLSTATE: `HY000`

Message: Use_count: Wrong count %lu for origin %p

`ER_WRONG_COUNT_FOR_ORIGIN` was added in 8.0.2.

- Error number: `MY-010715`; Symbol: `ER_WRONG_COUNT_FOR_KEY`; SQLSTATE: `HY000`

Message: Use_count: Wrong count for key at %p, %lu should be %lu

`ER_WRONG_COUNT_FOR_KEY` was added in 8.0.2.

- Error number: `MY-010716`; Symbol: `ER_WRONG_COUNT_OF_ELEMENTS`; SQLSTATE: `HY000`

Message: Wrong number of elements: %u (should be %u) for tree at %p

`ER_WRONG_COUNT_OF_ELEMENTS` was added in 8.0.2.

- Error number: `MY-010717`; Symbol:

`ER_RPL_ERROR_READING_SLAVE_WORKER_CONFIGURATION`; SQLSTATE: `HY000`

Message: Error reading slave worker configuration

`ER_RPL_ERROR_READING_SLAVE_WORKER_CONFIGURATION` was added in 8.0.2.

- Error number: `MY-010718`; Symbol:

`ER_RPL_ERROR_WRITING_SLAVE_WORKER_CONFIGURATION`; SQLSTATE: `HY000`

Message: Error writing slave worker configuration

`ER_RPL_ERROR_WRITING_SLAVE_WORKER_CONFIGURATION` was added in 8.0.2, removed after 8.0.18.

- Error number: `MY-010719`; Symbol: `ER_RPL_FAILED_TO_OPEN_RELAY_LOG`; SQLSTATE: `HY000`

Message: Failed to open relay log %s, error: %s

`ER_RPL_FAILED_TO_OPEN_RELAY_LOG` was added in 8.0.2.

- Error number: `MY-010720`; Symbol: `ER_RPL_WORKER_CANT_READ_RELAY_LOG`; SQLSTATE: `HY000`

Message: Error when worker read relay log events,relay log name %s, position %llu

`ER_RPL_WORKER_CANT_READ_RELAY_LOG` was added in 8.0.2.

- Error number: `MY-010721`; Symbol: `ER_RPL_WORKER_CANT_FIND_NEXT_RELAY_LOG`; SQLSTATE: `HY000`

Message: Failed to find next relay log when retrying the transaction, current relay log is %s

`ER_RPL_WORKER_CANT_FIND_NEXT_RELAY_LOG` was added in 8.0.2.

- Error number: `MY-010722`; Symbol: `ER_RPL_MTS_SLAVE_COORDINATOR_HAS_WAITED`; SQLSTATE: `HY000`

Message: Multi-threaded slave: Coordinator has waited %lu times hitting replica_pending_jobs_size_max; current event size = %zu.

`ER_RPL_MTS_SLAVE_COORDINATOR_HAS_WAITED` was added in 8.0.2.

- Error number: `MY-010723`; Symbol: `ER_BINLOG_FAILED_TO_WRITE_DROP_FOR_TEMP_TABLES`; SQLSTATE: `HY000`

Message: Failed to write the DROP statement for temporary tables to binary log

`ER_BINLOG_FAILED_TO_WRITE_DROP_FOR_TEMP_TABLES` was added in 8.0.2.

- Error number: `MY-010724`; Symbol: `ER_BINLOG_OOM_WRITING_DELETE WHILE_OPENING_HEAP_TABLE`; SQLSTATE: `HY000`

Message: When opening HEAP table, could not allocate memory to write 'DELETE FROM `'%s`.%s`'

to the binary log

`ER_BINLOG_OOM_WRITING_DELETE WHILE_OPENING_HEAP_TABLE` was added in 8.0.2.

- Error number: `MY-010725`; Symbol: `ER_FAILED_TO_REPAIR_TABLE`; SQLSTATE: `HY000`

Message: Couldn't repair table: %s.%s

`ER_FAILED_TO_REPAIR_TABLE` was added in 8.0.2.

- Error number: `MY-010726`; Symbol: `ER_FAILED_TO_REMOVE_TEMP_TABLE`; SQLSTATE: `HY000`

Message: Could not remove temporary table: '%s', error: %d

`ER_FAILED_TO_REMOVE_TEMP_TABLE` was added in 8.0.2.

- Error number: `MY-010727`; Symbol: `ER_SYSTEM_TABLE_NOT_TRANSACTIONAL`; SQLSTATE: `HY000`

Message: System table '%.*s' is expected to be transactional.

`ER_SYSTEM_TABLE_NOT_TRANSACTIONAL` was added in 8.0.2.

- Error number: `MY-010728`; Symbol: `ER_RPL_ERROR_WRITING_MASTER_CONFIGURATION`; SQLSTATE: `HY000`

Message: Error writing master configuration.

`ER_RPL_ERROR_WRITING_MASTER_CONFIGURATION` was added in 8.0.2.

- Error number: `MY-010729`; Symbol: `ER_RPL_ERROR_READING_MASTER_CONFIGURATION`; SQLSTATE: `HY000`

Message: Error reading master configuration.

`ER_RPL_ERROR_READING_MASTER_CONFIGURATION` was added in 8.0.2.

- Error number: `MY-010730`; Symbol: `ER_RPL_SSL_INFO_IN_MASTER_INFO_IGNORED`; SQLSTATE: `HY000`

Message: SSL information in the master info file are ignored because this MySQL slave was compiled without SSL support.

`ER_RPL_SSL_INFO_IN_MASTER_INFO_IGNORED` was added in 8.0.2.

- Error number: `MY-010731`; Symbol: `ER_PLUGIN_FAILED_DEINITIALIZATION`; SQLSTATE: `HY000`

Message: Plugin '%s' of type %s failed deinitialization

`ER_PLUGIN_FAILED_DEINITIALIZATION` was added in 8.0.2.

- Error number: `MY-010732`; Symbol: `ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_DEINITIALIZATION`; SQLSTATE: `HY000`

Message: Plugin '%s' has ref_count=%d after deinitialization.

`ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_DEINITIALIZATION` was added in 8.0.2.

- Error number: `MY-010733`; Symbol: `ER_PLUGIN_SHUTTING_DOWN_PLUGIN`; SQLSTATE: `HY000`

Message: Shutting down plugin '%s'

`ER_PLUGIN_SHUTTING_DOWN_PLUGIN` was added in 8.0.2.

- Error number: `MY-010734`; Symbol: `ER_PLUGIN_REGISTRATION_FAILED`; SQLSTATE: `HY000`

Message: Plugin '%s' registration as a %s failed.

`ER_PLUGIN_REGISTRATION_FAILED` was added in 8.0.2.

- Error number: `MY-010735`; Symbol: `ER_PLUGIN_CANT_OPEN_PLUGIN_TABLE`; SQLSTATE: `HY000`

Message: Could not open the mysql.plugin table. Please perform the MySQL upgrade procedure.

`ER_PLUGIN_CANT_OPEN_PLUGIN_TABLE` was added in 8.0.2.

- Error number: `MY-010736`; Symbol: `ER_PLUGIN_CANT_LOAD`; SQLSTATE: `HY000`

Message: Couldn't load plugin named '%s' with soname '%s'.

`ER_PLUGIN_CANT_LOAD` was added in 8.0.2.

- Error number: `MY-010737`; Symbol: `ER_PLUGIN_LOAD_PARAMETER_TOO_LONG`; SQLSTATE: `HY000`

Message: plugin-load parameter too long

`ER_PLUGIN_LOAD_PARAMETER_TOO_LONG` was added in 8.0.2.

- Error number: `MY-010738`; Symbol: `ER_PLUGIN_FORCING_SHUTDOWN`; SQLSTATE: `HY000`

Message: Plugin '%s' will be forced to shutdown

`ER_PLUGIN_FORCING_SHUTDOWN` was added in 8.0.2.

- Error number: `MY-010739`; Symbol: `ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_SHUTDOWN`; SQLSTATE: `HY000`

Message: Plugin '%s' has ref_count=%d after shutdown.

`ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_SHUTDOWN` was added in 8.0.2.

- Error number: [MY-010740](#); Symbol: [ER_PLUGIN_UNKNOWN_VARIABLE_TYPE](#); SQLSTATE: [HY000](#)

Message: Unknown variable type code 0x%*x* in plugin '%s'.
[ER_PLUGIN_UNKNOWN_VARIABLE_TYPE](#) was added in 8.0.2.
- Error number: [MY-010741](#); Symbol: [ER_PLUGIN_VARIABLE_SET_READ_ONLY](#); SQLSTATE: [HY000](#)

Message: Server variable %s of plugin %s was forced to be read-only: string variable without update_func and PLUGIN_VAR_MEMALLOC flag
[ER_PLUGIN_VARIABLE_SET_READ_ONLY](#) was added in 8.0.2.
- Error number: [MY-010742](#); Symbol: [ER_PLUGIN_VARIABLE_MISSING_NAME](#); SQLSTATE: [HY000](#)

Message: Missing variable name in plugin '%s'.
[ER_PLUGIN_VARIABLE_MISSING_NAME](#) was added in 8.0.2.
- Error number: [MY-010743](#); Symbol: [ER_PLUGIN_VARIABLE_NOT_ALLOCATED_THREAD_LOCAL](#); SQLSTATE: [HY000](#)

Message: Thread local variable '%s' not allocated in plugin '%s'.
[ER_PLUGIN_VARIABLE_NOT_ALLOCATED_THREAD_LOCAL](#) was added in 8.0.2.
- Error number: [MY-010744](#); Symbol: [ER_PLUGIN_OOM](#); SQLSTATE: [HY000](#)

Message: Out of memory for plugin '%s'.
[ER_PLUGIN_OOM](#) was added in 8.0.2.
- Error number: [MY-010745](#); Symbol: [ER_PLUGIN_BAD_OPTIONS](#); SQLSTATE: [HY000](#)

Message: Bad options for plugin '%s'.
[ER_PLUGIN_BAD_OPTIONS](#) was added in 8.0.2.
- Error number: [MY-010746](#); Symbol: [ER_PLUGIN_PARSING_OPTIONS_FAILED](#); SQLSTATE: [HY000](#)

Message: Parsing options for plugin '%s' failed.
[ER_PLUGIN_PARSING_OPTIONS_FAILED](#) was added in 8.0.2.
- Error number: [MY-010747](#); Symbol: [ER_PLUGIN_DISABLED](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' is disabled.
[ER_PLUGIN_DISABLED](#) was added in 8.0.2.
- Error number: [MY-010748](#); Symbol: [ER_PLUGIN_HAS_CONFLICTING_SYSTEM_VARIABLES](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' has conflicting system variables
[ER_PLUGIN_HAS_CONFLICTING_SYSTEM_VARIABLES](#) was added in 8.0.2.
- Error number: [MY-010749](#); Symbol: [ER_PLUGIN_CANT_SET_PERSISTENT_OPTIONS](#); SQLSTATE: [HY000](#)

Message: Setting persistent options for plugin '%s' failed.

`ER_PLUGIN_CANT_SET_PERSISTENT_OPTIONS` was added in 8.0.2.

- Error number: `MY-010750`; Symbol: `ER_MY_NET_WRITE_FAILED_FALLING_BACK_ON_STDERR`; SQLSTATE: `HY000`

Message: Failed on my_net_write, writing to stderr instead: %s

`ER_MY_NET_WRITE_FAILED_FALLING_BACK_ON_STDERR` was added in 8.0.2.

- Error number: `MY-010751`; Symbol: `ER_RETRYING_REPAIR_WITHOUT_QUICK`; SQLSTATE: `HY000`

Message: Retrying repair of: '%s' without quick

`ER_RETRYING_REPAIR_WITHOUT_QUICK` was added in 8.0.2.

- Error number: `MY-010752`; Symbol: `ER_RETRYING_REPAIR_WITH_KEYCACHE`; SQLSTATE: `HY000`

Message: Retrying repair of: '%s' with keycache

`ER_RETRYING_REPAIR_WITH_KEYCACHE` was added in 8.0.2.

- Error number: `MY-010753`; Symbol: `ER_FOUND_ROWS_WHILE_REPAIRING`; SQLSTATE: `HY000`

Message: Found %s of %s rows when repairing '%s'

`ER_FOUND_ROWS_WHILE_REPAIRING` was added in 8.0.2.

- Error number: `MY-010754`; Symbol: `ER_ERROR_DURING_OPTIMIZE_TABLE`; SQLSTATE: `HY000`

Message: Warning: Optimize table got errno %d on %s.%s, retrying

`ER_ERROR_DURING_OPTIMIZE_TABLE` was added in 8.0.2.

- Error number: `MY-010755`; Symbol: `ER_ERROR_ENABLING_KEYS`; SQLSTATE: `HY000`

Message: Warning: Enabling keys got errno %d on %s.%s, retrying

`ER_ERROR_ENABLING_KEYS` was added in 8.0.2.

- Error number: `MY-010756`; Symbol: `ER_CHECKING_TABLE`; SQLSTATE: `HY000`

Message: Checking table: '%s'

`ER_CHECKING_TABLE` was added in 8.0.2.

- Error number: `MY-010757`; Symbol: `ER_RECOVERING_TABLE`; SQLSTATE: `HY000`

Message: Recovering table: '%s'

`ER_RECOVERING_TABLE` was added in 8.0.2.

- Error number: `MY-010758`; Symbol: `ER_CANT_CREATE_TABLE_SHARE_FROM_FRM`; SQLSTATE: `HY000`

Message: Error in creating TABLE_SHARE from %s.frm file.

`ER_CANT_CREATE_TABLE_SHARE_FROM_FRM` was added in 8.0.2.

- Error number: `MY-010759`; Symbol: `ER_CANT_LOCK_TABLE`; SQLSTATE: `HY000`

Message: Unable to acquire lock on %s.%s

`ER_CANT_LOCK_TABLE` was added in 8.0.2.

- Error number: `MY-010760`; Symbol: `ER_CANT_ALLOC_TABLE_OBJECT`; SQLSTATE: `HY000`

Message: Error in allocation memory for TABLE object.

`ER_CANT_ALLOC_TABLE_OBJECT` was added in 8.0.2.

- Error number: `MY-010761`; Symbol: `ER_CANT_CREATE_HANDLER_OBJECT_FOR_TABLE`; SQLSTATE: `HY000`

Message: Error in creating handler object for table %s.%s

`ER_CANT_CREATE_HANDLER_OBJECT_FOR_TABLE` was added in 8.0.2.

- Error number: `MY-010762`; Symbol: `ER_CANT_SET_HANDLER_REFERENCE_FOR_TABLE`; SQLSTATE: `HY000`

Message: Error in setting handler reference for table %s.%s

`ER_CANT_SET_HANDLER_REFERENCE_FOR_TABLE` was added in 8.0.2.

- Error number: `MY-010763`; Symbol: `ER_CANT_LOCK_TABLESPACE`; SQLSTATE: `HY000`

Message: Unable to acquire lock on tablespace name %s

`ER_CANT_LOCK_TABLESPACE` was added in 8.0.2.

- Error number: `MY-010764`; Symbol: `ER_CANT_UPGRADE_GENERATED_COLUMNS_TO_DD`; SQLSTATE: `HY000`

Message: Error in processing generated columns for table %s.%s

`ER_CANT_UPGRADE_GENERATED_COLUMNS_TO_DD` was added in 8.0.2.

- Error number: `MY-010765`; Symbol: `ER_DD_ERROR_CREATING_ENTRY`; SQLSTATE: `HY000`

Message: Error in Creating DD entry for %s.%s

`ER_DD_ERROR_CREATING_ENTRY` was added in 8.0.2.

- Error number: `MY-010766`; Symbol: `ER_DD_CANT_FETCH_TABLE_DATA`; SQLSTATE: `HY000`

Message: Error in fetching %s.%s table data from dictionary

`ER_DD_CANT_FETCH_TABLE_DATA` was added in 8.0.2.

- Error number: `MY-010767`; Symbol: `ER_DD_CANT_FIX_SE_DATA`; SQLSTATE: `HY000`

Message: Error in fixing SE data for %s.%s

`ER_DD_CANT_FIX_SE_DATA` was added in 8.0.2.

- Error number: `MY-010768`; Symbol: `ER_DD_CANT_CREATE_SP`; SQLSTATE: `HY000`

Message: Error in creating stored program '%s.%s'

`ER_DD_CANT_CREATE_SP` was added in 8.0.2.

- Error number: `MY-010769`; Symbol: `ER_CANT_OPEN_DB_OPT_USING_DEFAULT_CHARSET`; SQLSTATE: `HY000`

Message: Unable to open db.opt file %s. Using default Character set.

`ER_CANT_OPEN_DB_OPT_USING_DEFAULT_CHARSET` was added in 8.0.2.

- Error number: `MY-010770`; Symbol: `ER_CANT_CREATE_CACHE_FOR_DB_OPT`; SQLSTATE: `HY000`

Message: Unable to initialize IO cache to open db.opt file %s.

`ER_CANT_CREATE_CACHE_FOR_DB_OPT` was added in 8.0.2.

- Error number: `MY-010771`; Symbol: `ER_CANT_IDENTIFY_CHARSET_USING_DEFAULT`; SQLSTATE: `HY000`

Message: Unable to identify the charset in %s. Using default character set.

`ER_CANT_IDENTIFY_CHARSET_USING_DEFAULT` was added in 8.0.2.

- Error number: `MY-010772`; Symbol: `ER_DB_OPT_NOT_FOUND_USING_DEFAULT_CHARSET`; SQLSTATE: `HY000`

Message: db.opt file not found for %s database. Using default Character set.

`ER_DB_OPT_NOT_FOUND_USING_DEFAULT_CHARSET` was added in 8.0.2.

- Error number: `MY-010773`; Symbol: `ER_EVENT_CANT_GET_TIMEZONE_FROM_FIELD`; SQLSTATE: `HY000`

Message: Event '%s'.'%s': invalid value in column mysql.event.time_zone.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.

`ER_EVENT_CANT_GET_TIMEZONE_FROM_FIELD` was added in 8.0.2.

- Error number: `MY-010774`; Symbol: `ER_EVENT_CANT_FIND_TIMEZONE`; SQLSTATE: `HY000`

Message: Event '%s'.'%s': has invalid time zone value

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.

`ER_EVENT_CANT_FIND_TIMEZONE` was added in 8.0.2.

- Error number: `MY-010775`; Symbol: `ER_EVENT_CANT_GET_CHARSET`; SQLSTATE: `HY000`

Message: Event '%s'.'%s': invalid value in column mysql.event.character_set_client.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.

`ER_EVENT_CANT_GET_CHARSET` was added in 8.0.2.

- Error number: `MY-010776`; Symbol: `ER_EVENT_CANT_GET_COLLATION`; SQLSTATE: `HY000`

Message: Event '%s'.'%s': invalid value in column mysql.event.collation_connection.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.

`ER_EVENT_CANT_GET_COLLATION` was added in 8.0.2.

- Error number: [MY-010777](#); Symbol: [ER_EVENT_CANT_OPEN_TABLE_MYSQL_EVENT](#); SQLSTATE: [HY000](#)

Message: Failed to open mysql.event Table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.

[ER_EVENT_CANT_OPEN_TABLE_MYSQL_EVENT](#) was added in 8.0.2.

- Error number: [MY-010778](#); Symbol: [ER_CANT_PARSE_STORED_ROUTINE_BODY](#); SQLSTATE: [HY000](#)

Message: Parsing '%s.%s' routine body failed.%s

[ER_CANT_PARSE_STORED_ROUTINE_BODY](#) was added in 8.0.2.

- Error number: [MY-010779](#); Symbol: [ER_CANT_OPEN_TABLE_MYSQL_PROC](#); SQLSTATE: [HY000](#)

Message: Failed to open mysql.proc Table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.proc` system table and migrates its contents to the internal data dictionary.

[ER_CANT_OPEN_TABLE_MYSQL_PROC](#) was added in 8.0.2.

- Error number: [MY-010780](#); Symbol: [ER_CANT_READ_TABLE_MYSQL_PROC](#); SQLSTATE: [HY000](#)

Message: Failed to read mysql.proc table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.proc` system table and migrates its contents to the internal data dictionary.

[ER_CANT_READ_TABLE_MYSQL_PROC](#) was added in 8.0.2.

- Error number: [MY-010781](#); Symbol: [ER_FILE_EXISTS_DURING_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Found %s file in mysql schema. DD will create .ibd file with same name. Please rename table and start upgrade process again.

[ER_FILE_EXISTS_DURING_UPGRADE](#) was added in 8.0.2.

- Error number: [MY-010782](#); Symbol: [ER_CANT_OPEN_DATADIR_AFTER_UPGRADE_FAILURE](#); SQLSTATE: [HY000](#)

Message: Unable to open the data directory %s during clean up after upgrade failed

[ER_CANT_OPEN_DATADIR_AFTER_UPGRADE_FAILURE](#) was added in 8.0.2.

- Error number: [MY-010783](#); Symbol: [ER_CANT_SET_PATH_FOR](#); SQLSTATE: [HY000](#)

Message: Failed to set path %s

[ER_CANT_SET_PATH_FOR](#) was added in 8.0.2.

- Error number: [MY-010784](#); Symbol: [ER_CANT_OPEN_DIR](#); SQLSTATE: [HY000](#)

Message: Failed to open dir %s

[ER_CANT_OPEN_DIR](#) was added in 8.0.2.

- Error number: [MY-010785](#); Symbol: [ER_NDB_EMPTY_NODEID_IN_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#); SQLSTATE: [HY000](#)

Message: NDB: Found empty nodeid specified in --ndb-cluster-connection-pool-nodeids='%.s'.
[ER_NDB_EMPTY_NODEID_IN_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010786](#); Symbol: [ER_NDB_CANT_PARSE_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#); SQLSTATE: [HY000](#)

Message: NDB: Could not parse '%s' in --ndb-cluster-connection-pool-nodeids='%.s'.
[ER_NDB_CANT_PARSE_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010787](#); Symbol: [ER_NDB_INVALID_NODEID_IN_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#); SQLSTATE: [HY000](#)

Message: NDB: Invalid nodeid %d in --ndb-cluster-connection-pool-nodeids='%.s'.
[ER_NDB_INVALID_NODEID_IN_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010788](#); Symbol: [ER_NDB_DUPLICATE_NODEID_IN_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#); SQLSTATE: [HY000](#)

Message: NDB: Found duplicate nodeid %d in --ndb-cluster-connection-pool-nodeids='%.s'.
[ER_NDB_DUPLICATE_NODEID_IN_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010789](#); Symbol: [ER_NDB_POOL_SIZE_MUST_MATCH_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#); SQLSTATE: [HY000](#)

Message: NDB: The size of the cluster connection pool must be equal to the number of nodeids in --ndb-cluster-connection-pool-nodeids='%.s'.
[ER_NDB_POOL_SIZE_MUST_MATCH_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010790](#); Symbol: [ER_NDB_NODEID_NOT_FIRST_IN_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#); SQLSTATE: [HY000](#)

Message: NDB: The nodeid specified by --ndb-nodeid must be equal to the first nodeid in --ndb-cluster-connection-pool-nodeids='%.s'.
[ER_NDB_NODEID_NOT_FIRST_IN_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010791](#); Symbol: [ER_NDB_USING_NODEID](#); SQLSTATE: [HY000](#)

Message: NDB: using nodeid %u
[ER_NDB_USING_NODEID](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010792](#); Symbol: [ER_NDB_CANT_ALLOC_GLOBAL_NDB_CLUSTER_CONNECTION](#); SQLSTATE: [HY000](#)

Message: NDB: failed to allocate global ndb cluster connection

[ER_NDB_CANT_ALLOC_GLOBAL_NDB_CLUSTER_CONNECTION](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010793](#); Symbol: [ER_NDB_CANT_ALLOC_GLOBAL_NDB_OBJECT](#); SQLSTATE: [HY000](#)

Message: NDB: failed to allocate global ndb object

[ER_NDB_CANT_ALLOC_GLOBAL_NDB_OBJECT](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010794](#); Symbol: [ER_NDB_USING_NODEID_LIST](#); SQLSTATE: [HY000](#)

Message: NDB[%u]: using nodeid %u

[ER_NDB_USING_NODEID_LIST](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010795](#); Symbol: [ER_NDB_CANT_ALLOC_NDB_CLUSTER_CONNECTION](#); SQLSTATE: [HY000](#)

Message: NDB[%u]: failed to allocate cluster connect object

[ER_NDB_CANT_ALLOC_NDB_CLUSTER_CONNECTION](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010796](#); Symbol: [ER_NDB_STARTING_CONNECT_THREAD](#); SQLSTATE: [HY000](#)

Message: NDB[%u]: starting connect thread

[ER_NDB_STARTING_CONNECT_THREAD](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010797](#); Symbol: [ER_NDB_NODE_INFO](#); SQLSTATE: [HY000](#)

Message: NDB[%u]: NodeID: %d, %s

[ER_NDB_NODE_INFO](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010798](#); Symbol: [ER_NDB_CANT_START_CONNECT_THREAD](#); SQLSTATE: [HY000](#)

Message: NDB[%u]: failed to start connect thread

[ER_NDB_CANT_START_CONNECT_THREAD](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010799](#); Symbol: [ER_NDB_GENERIC_ERROR](#); SQLSTATE: [HY000](#)

Message: NDB: error (%u) %s

[ER_NDB_GENERIC_ERROR](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010800](#); Symbol: [ER_NDB_CPU_MASK_TOO_SHORT](#); SQLSTATE: [HY000](#)

Message: Ignored receive thread CPU mask, mask too short, %u CPUs needed in mask, only %u CPUs provided

[ER_NDB_CPU_MASK_TOO_SHORT](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010801](#); Symbol: [ER_EVENT_ERROR_CREATING_QUERY_TO_WRITE_TO_BINLOG](#); SQLSTATE: [HY000](#)

Message: Event Error: An error occurred while creating query string, before writing it into binary log.

[ER_EVENT_ERROR_CREATING_QUERY_TO_WRITE_TO_BINLOG](#) was added in 8.0.2.

-
- Error number: [MY-010802](#); Symbol: [ER_EVENT_SCHEDULER_ERROR_LOADING_FROM_DB](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Error while loading from disk.
[ER_EVENT_SCHEDULER_ERROR_LOADING_FROM_DB](#) was added in 8.0.2.
 - Error number: [MY-010803](#); Symbol: [ER_EVENT_SCHEDULER_ERROR_GETTING_EVENT_OBJECT](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Error getting event object.
[ER_EVENT_SCHEDULER_ERROR_GETTING_EVENT_OBJECT](#) was added in 8.0.2.
 - Error number: [MY-010804](#); Symbol: [ER_EVENT_SCHEDULER_GOT_BAD_DATA_FROM_TABLE](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Error while loading events from mysql.events.The table probably contains bad data or is corrupted
[ER_EVENT_SCHEDULER_GOT_BAD_DATA_FROM_TABLE](#) was added in 8.0.2.
 - Error number: [MY-010805](#); Symbol: [ER_EVENT_CANT_GET_LOCK_FOR_DROPPING_EVENT](#); SQLSTATE: [HY000](#)

Message: Unable to obtain lock for dropping event %s from schema %s
[ER_EVENT_CANT_GET_LOCK_FOR_DROPPING_EVENT](#) was added in 8.0.2.
 - Error number: [MY-010806](#); Symbol: [ER_EVENT_UNABLE_TO_DROP_EVENT](#); SQLSTATE: [HY000](#)

Message: Unable to drop event %s from schema %s
[ER_EVENT_UNABLE_TO_DROP_EVENT](#) was added in 8.0.2.
 - Error number: [MY-010807](#); Symbol: [ER_BINLOG_ATTACHING_THREAD_MEMORY_FINALLY_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: Server overcomes the temporary 'out of memory' in '%d' tries while attaching to session thread during the group commit phase.
[ER_BINLOG_ATTACHING_THREAD_MEMORY_FINALLY_AVAILABLE](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010808](#); Symbol: [ER_BINLOG_CANT_RESIZE_CACHE](#); SQLSTATE: [HY000](#)

Message: Unable to resize binlog IOCACHE auxiliary file
[ER_BINLOG_CANT_RESIZE_CACHE](#) was added in 8.0.2.
 - Error number: [MY-010809](#); Symbol: [ER_BINLOG_FILE_BEING_READ_NOT_PURGED](#); SQLSTATE: [HY000](#)

Message: file %s was not purged because it was being read by thread number %u
[ER_BINLOG_FILE_BEING_READ_NOT_PURGED](#) was added in 8.0.2.
 - Error number: [MY-010810](#); Symbol: [ER_BINLOG_IO_ERROR_READING_HEADER](#); SQLSTATE: [HY000](#)

Message: I/O error reading the header from the binary log, errno=%d, io cache code=%d
[ER_BINLOG_IO_ERROR_READING_HEADER](#) was added in 8.0.2.

- Error number: [MY-010811](#); Symbol: [ER_BINLOG_CANT_OPEN_LOG](#); SQLSTATE: [HY000](#)

Message: Failed to open log (file '%s', errno %d)
[ER_BINLOG_CANT_OPEN_LOG](#) was added in 8.0.2, removed after 8.0.12.
- Error number: [MY-010812](#); Symbol: [ER_BINLOG_CANT_CREATE_CACHE_FOR_LOG](#); SQLSTATE: [HY000](#)

Message: Failed to create a cache on log (file '%s')
[ER_BINLOG_CANT_CREATE_CACHE_FOR_LOG](#) was added in 8.0.2, removed after 8.0.12.
- Error number: [MY-010813](#); Symbol: [ER_BINLOG_FILE_EXTENSION_NUMBER_EXHAUSTED](#); SQLSTATE: [HY000](#)

Message: Log filename extension number exhausted: %06lu. Please fix this by archiving old logs and updating the index files.
[ER_BINLOG_FILE_EXTENSION_NUMBER_EXHAUSTED](#) was added in 8.0.2.
- Error number: [MY-010814](#); Symbol: [ER_BINLOG_FILE_NAME_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: Log filename too large: %s%s (%zu). Please fix this by archiving old logs and updating the index files.
[ER_BINLOG_FILE_NAME_TOO_LONG](#) was added in 8.0.2.
- Error number: [MY-010815](#); Symbol: [ER_BINLOG_FILE_EXTENSION_NUMBER_RUNNING_LOW](#); SQLSTATE: [HY000](#)

Message: Next log extension: %lu. Remaining log filename extensions: %lu. Please consider archiving some logs.
[ER_BINLOG_FILE_EXTENSION_NUMBER_RUNNING_LOW](#) was added in 8.0.2.
- Error number: [MY-010816](#); Symbol: [ER_BINLOG_CANT_OPEN_FOR_LOGGING](#); SQLSTATE: [HY000](#)

Message: Could not open %s for logging (error %d). Turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and restart it.
[ER_BINLOG_CANT_OPEN_FOR_LOGGING](#) was added in 8.0.2.
- Error number: [MY-010817](#); Symbol: [ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::open_index_file failed to sync the index file.
[ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE](#) was added in 8.0.2.
- Error number: [MY-010818](#); Symbol: [ER_BINLOG_ERROR_READING_GTIDS_FROM_RELAY_LOG](#); SQLSTATE: [HY000](#)

Message: Error reading GTIDs from relaylog: %d
[ER_BINLOG_ERROR_READING_GTIDS_FROM_RELAY_LOG](#) was added in 8.0.2.

- Error number: [MY-010819](#); Symbol: [ER_BINLOG_EVENTS_READ_FROM_RELAY_LOG_INFO](#); SQLSTATE: [HY000](#)

Message: %lu events read in relaylog file '%s' for updating Retrieved_Gtid_Set and/or IO thread transaction parser state.

[ER_BINLOG_EVENTS_READ_FROM_RELAY_LOG_INFO](#) was added in 8.0.2.
- Error number: [MY-010820](#); Symbol: [ER_BINLOG_ERROR_READING_GTIDS_FROM_BINARY_LOG](#); SQLSTATE: [HY000](#)

Message: Error reading GTIDs from binary log: %d

[ER_BINLOG_ERROR_READING_GTIDS_FROM_BINARY_LOG](#) was added in 8.0.2.
- Error number: [MY-010821](#); Symbol: [ER_BINLOG_EVENTS_READ_FROM_BINLOG_INFO](#); SQLSTATE: [HY000](#)

Message: Read %lu events from binary log file '%s' to determine the GTIDs purged from binary logs.

[ER_BINLOG_EVENTS_READ_FROM_BINLOG_INFO](#) was added in 8.0.2.
- Error number: [MY-010822](#); Symbol: [ER_BINLOG_CANT_GENERATE_NEW_FILE_NAME](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::open failed to generate new file name.

[ER_BINLOG_CANT_GENERATE_NEW_FILE_NAME](#) was added in 8.0.2.
- Error number: [MY-010823](#); Symbol: [ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE_IN_OPEN](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::open failed to sync the index file.

[ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE_IN_OPEN](#) was added in 8.0.2.
- Error number: [MY-010824](#); Symbol: [ER_BINLOG_CANT_USE_FOR_LOGGING](#); SQLSTATE: [HY000](#)

Message: Could not use %s for logging (error %d). Turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and restart it.

[ER_BINLOG_CANT_USE_FOR_LOGGING](#) was added in 8.0.2.
- Error number: [MY-010825](#); Symbol: [ER_BINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE_REBUILDING](#); SQLSTATE: [HY000](#)

Message: While rebuilding index file %s: Failed to close the index file.

[ER_BINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE_REBUILDING](#) was added in 8.0.2.
- Error number: [MY-010826](#); Symbol: [ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REBUILDING](#); SQLSTATE: [HY000](#)

Message: While rebuilding index file %s: Failed to delete the existing index file. It could be that file is being used by some other process.

[ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REBUILDING](#) was added in 8.0.2.

- Error number: [MY-010827](#); Symbol: [ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_REBUILDING](#); SQLSTATE: [HY000](#)

Message: While rebuilding index file %s: Failed to rename the new index file to the existing index file.
[ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_REBUILDING](#) was added in 8.0.2.
- Error number: [MY-010828](#); Symbol: [ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBUILDING](#); SQLSTATE: [HY000](#)

Message: After rebuilding the index file %s: Failed to open the index file.
[ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBUILDING](#) was added in 8.0.2.
- Error number: [MY-010829](#); Symbol: [ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::add_log_to_index failed to append log file name: %s, to crash safe index file.
[ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX](#) was added in 8.0.2.
- Error number: [MY-010830](#); Symbol: [ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAY_LOG_FILES](#); SQLSTATE: [HY000](#)

Message: Failed to locate old binlog or relay log files
[ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAY_LOG_FILES](#) was added in 8.0.2.
- Error number: [MY-010831](#); Symbol: [ER_BINLOG_CANT_DELETE_FILE](#); SQLSTATE: [HY000](#)

Message: Failed to delete file '%s'
[ER_BINLOG_CANT_DELETE_FILE](#) was added in 8.0.2.
- Error number: [MY-010832](#); Symbol: [ER_BINLOG_CANT_SET_TMP_INDEX_NAME](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::set_crash_safe_index_file_name failed to set file name.
[ER_BINLOG_CANT_SET_TMP_INDEX_NAME](#) was added in 8.0.2.
- Error number: [MY-010833](#); Symbol: [ER_BINLOG_FAILED_TO_OPEN_TEMPORARY_INDEX_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::open_crash_safe_index_file failed to open temporary index file.
[ER_BINLOG_FAILED_TO_OPEN_TEMPORARY_INDEX_FILE](#) was added in 8.0.2.
- Error number: [MY-010834](#); Symbol: [ER_BINLOG_ERROR_GETTING_NEXT_LOG_FROM_INDEX](#); SQLSTATE: [HY000](#)

Message: next log error: %d offset: %s log: %s included: %d
[ER_BINLOG_ERROR_GETTING_NEXT_LOG_FROM_INDEX](#) was added in 8.0.2, removed after 8.0.12.
- Error number: [MY-010835](#); Symbol: [ER_BINLOG_CANT_OPEN_TMP_INDEX](#); SQLSTATE: [HY000](#)

Message: %s failed to open the crash safe index file.
[ER_BINLOG_CANT_OPEN_TMP_INDEX](#) was added in 8.0.2.
- Error number: [MY-010836](#); Symbol: [ER_BINLOG_CANT_COPY_INDEX_TO_TMP](#); SQLSTATE: [HY000](#)

Message: %s failed to copy index file to crash safe index file.

`ER_BINLOG_CANT_COPY_INDEX_TO_TMP` was added in 8.0.2.

- Error number: `MY-010837`; Symbol: `ER_BINLOG_CANT_CLOSE_TMP_INDEX`; SQLSTATE: `HY000`

Message: %s failed to close the crash safe index file.

`ER_BINLOG_CANT_CLOSE_TMP_INDEX` was added in 8.0.2.

- Error number: `MY-010838`; Symbol: `ER_BINLOG_CANT_MOVE_TMP_TO_INDEX`; SQLSTATE: `HY000`

Message: %s failed to move crash safe index file to index file.

`ER_BINLOG_CANT_MOVE_TMP_TO_INDEX` was added in 8.0.2.

- Error number: `MY-010839`; Symbol: `ER_BINLOG_PURGE_LOGS_CALLED_WITH_FILE_NOT_IN_INDEX`; SQLSTATE: `HY000`

Message: `MYSQL_BIN_LOG::purge_logs` was called with file %s not listed in the index.

`ER_BINLOG_PURGE_LOGS_CALLED_WITH_FILE_NOT_IN_INDEX` was added in 8.0.2.

- Error number: `MY-010840`; Symbol: `ER_BINLOG_PURGE_LOGS_CANT_SYNC_INDEX_FILE`; SQLSTATE: `HY000`

Message: `MYSQL_BIN_LOG::purge_logs` failed to sync the index file.

`ER_BINLOG_PURGE_LOGS_CANT_SYNC_INDEX_FILE` was added in 8.0.2.

- Error number: `MY-010841`; Symbol: `ER_BINLOG_PURGE_LOGS_CANT_COPY_TO_REGISTER_FILE`; SQLSTATE: `HY000`

Message: `MYSQL_BIN_LOG::purge_logs` failed to copy %s to register file.

`ER_BINLOG_PURGE_LOGS_CANT_COPY_TO_REGISTER_FILE` was added in 8.0.2.

- Error number: `MY-010842`; Symbol: `ER_BINLOG_PURGE_LOGS_CANT_FLUSH_REGISTER_FILE`; SQLSTATE: `HY000`

Message: `MYSQL_BIN_LOG::purge_logs` failed to flush register file.

`ER_BINLOG_PURGE_LOGS_CANT_FLUSH_REGISTER_FILE` was added in 8.0.2.

- Error number: `MY-010843`; Symbol: `ER_BINLOG_PURGE_LOGS_CANT_UPDATE_INDEX_FILE`; SQLSTATE: `HY000`

Message: `MYSQL_BIN_LOG::purge_logs` failed to update the index file

`ER_BINLOG_PURGE_LOGS_CANT_UPDATE_INDEX_FILE` was added in 8.0.2.

- Error number: `MY-010844`; Symbol: `ER_BINLOG_PURGE_LOGS_FAILED_TO_PURGE_LOG`; SQLSTATE: `HY000`

Message: `MYSQL_BIN_LOG::purge_logs` failed to process registered files that would be purged.

`ER_BINLOG_PURGE_LOGS_FAILED_TO_PURGE_LOG` was added in 8.0.2.

- Error number: `MY-010845`; Symbol: `ER_BINLOG_FAILED_TO_SET_PURGE_INDEX_FILE_NAME`; SQLSTATE: `HY000`

Message: `MYSQL_BIN_LOG::set_purge_index_file_name` failed to set file name.

`ER_BINLOG_FAILED_TO_SET_PURGE_INDEX_FILE_NAME` was added in 8.0.2.

- Error number: `MY-010846`; Symbol: `ER_BINLOG_FAILED_TO_OPEN_REGISTER_FILE`; SQLSTATE: `HY000`

Message: `MYSQL_BIN_LOG::open_purge_index_file` failed to open register file.

`ER_BINLOG_FAILED_TO_OPEN_REGISTER_FILE` was added in 8.0.2.

- Error number: `MY-010847`; Symbol: `ER_BINLOG_FAILED_TO_REINIT_REGISTER_FILE`; SQLSTATE: `HY000`

Message: `MYSQL_BIN_LOG::purge_index_entry` failed to reinit register file for read

`ER_BINLOG_FAILED_TO_REINIT_REGISTER_FILE` was added in 8.0.2.

- Error number: `MY-010848`; Symbol: `ER_BINLOG_FAILED_TO_READ_REGISTER_FILE`; SQLSTATE: `HY000`

Message: `MYSQL_BIN_LOG::purge_index_entry` error %d reading from register file.

`ER_BINLOG_FAILED_TO_READ_REGISTER_FILE` was added in 8.0.2.

- Error number: `MY-010849`; Symbol: `ER_CANT_STAT_FILE`; SQLSTATE: `HY000`

Message: Failed to execute `mysql_file_stat` on file '%s'

`ER_CANT_STAT_FILE` was added in 8.0.2.

- Error number: `MY-010850`; Symbol: `ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX_MATCH_FILES`; SQLSTATE: `HY000`

Message: Failed to delete log file '%s'; consider examining correspondence of your binlog index file to the actual binlog files

`ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX_MATCH_FILES` was added in 8.0.2.

- Error number: `MY-010851`; Symbol: `ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG_INDEX`; SQLSTATE: `HY000`

Message: Failed to delete file '%s' and read the binlog index file

`ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG_INDEX` was added in 8.0.2.

- Error number: `MY-010852`; Symbol: `ER_BINLOG_FAILED_TO_DELETE_LOG_FILE`; SQLSTATE: `HY000`

Message: Failed to delete log file '%s'

`ER_BINLOG_FAILED_TO_DELETE_LOG_FILE` was added in 8.0.2.

- Error number: `MY-010853`; Symbol: `ER_BINLOG_LOGGING INCIDENT_TO_STOP_SLAVES`; SQLSTATE: `HY000`

Message: %s An incident event has been written to the binary log which will stop the slaves.

`ER_BINLOG_LOGGING INCIDENT_TO_STOP_SLAVES` was added in 8.0.2.

- Error number: `MY-010854`; Symbol: `ER_BINLOG_CANT_FIND_LOG_IN_INDEX`; SQLSTATE: `HY000`

Message: `find_log_pos()` failed (error: %d)

`ER_BINLOG_CANT_FIND_LOG_IN_INDEX` was added in 8.0.2.

- Error number: `MY-010855`; Symbol: `ER_BINLOG_RECOVERING_AFTER_CRASH_USING`; SQLSTATE: `HY000`

Message: Recovering after a crash using %s

`ER_BINLOG_RECOVERING_AFTER_CRASH_USING` was added in 8.0.2.

- Error number: `MY-010856`; Symbol: `ER_BINLOG_CANT_OPEN_CRASHED_BINLOG`; SQLSTATE: `HY000`

Message: Failed to open the crashed binlog file when master server is recovering it.

`ER_BINLOG_CANT_OPEN_CRASHED_BINLOG` was added in 8.0.2.

- Error number: `MY-010857`; Symbol: `ER_BINLOG_CANT_TRIM_CRASHED_BINLOG`; SQLSTATE: `HY000`

Message: Failed to trim the crashed binlog file when master server is recovering it.

`ER_BINLOG_CANT_TRIM_CRASHED_BINLOG` was added in 8.0.2.

- Error number: `MY-010858`; Symbol: `ER_BINLOG_CRASHED_BINLOG_TRIMMED`; SQLSTATE: `HY000`

Message: Crashed binlog file %s size is %llu, but recovered up to %llu. Binlog trimmed to %llu bytes.

`ER_BINLOG_CRASHED_BINLOG_TRIMMED` was added in 8.0.2.

- Error number: `MY-010859`; Symbol: `ER_BINLOG_CANT_CLEAR_IN_USE_FLAG_FOR_CRASHED_BINLOG`; SQLSTATE: `HY000`

Message: Failed to clear LOG_EVENT_BINLOG_IN_USE_F for the crashed binlog file when master server is recovering it.

`ER_BINLOG_CANT_CLEAR_IN_USE_FLAG_FOR_CRASHED_BINLOG` was added in 8.0.2.

- Error number: `MY-010860`; Symbol: `ER_BINLOG_FAILED_TO_RUN_AFTER_SYNC_HOOK`; SQLSTATE: `HY000`

Message: Failed to run 'after_sync' hooks

`ER_BINLOG_FAILED_TO_RUN_AFTER_SYNC_HOOK` was added in 8.0.2.

- Error number: `MY-010861`; Symbol: `ER_TURNING_LOGGING_OFF_FOR_THE_DURATION`; SQLSTATE: `HY000`

Message: %s Hence turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and restart it.

`ER_TURNING_LOGGING_OFF_FOR_THE_DURATION` was added in 8.0.2.

- Error number: `MY-010862`; Symbol: `ER_BINLOG_FAILED_TO_RUN_AFTER_FLUSH_HOOK`; SQLSTATE: `HY000`

Message: Failed to run 'after_flush' hooks

`ER_BINLOG_FAILED_TO_RUN_AFTER_FLUSH_HOOK` was added in 8.0.2.

- Error number: [MY-010863](#); Symbol: [ER_BINLOG_CRASH_RECOVERY_FAILED](#); SQLSTATE: [HY000](#)

Message: Crash recovery failed. Either correct the problem (if it's, for example, out of memory error) and restart, or delete (or rename) binary log and start mysqld with --tc-heuristic-recover={commit|rollback}

[ER_BINLOG_CRASH_RECOVERY_FAILED](#) was added in 8.0.2.
- Error number: [MY-010864](#); Symbol: [ER_BINLOG_WARNING_SUPPRESSED](#); SQLSTATE: [HY000](#)

Message: The following warning was suppressed %d times during the last %d seconds in the error log

[ER_BINLOG_WARNING_SUPPRESSED](#) was added in 8.0.2.
- Error number: [MY-010865](#); Symbol: [ER_NDB_LOG_ENTRY](#); SQLSTATE: [HY000](#)

Message: NDB: %s

[ER_NDB_LOG_ENTRY](#) was added in 8.0.2.
- Error number: [MY-010866](#); Symbol: [ER_NDB_LOG_ENTRY_WITH_PREFIX](#); SQLSTATE: [HY000](#)

Message: NDB %s: %s

[ER_NDB_LOG_ENTRY_WITH_PREFIX](#) was added in 8.0.2.
- Error number: [MY-010867](#); Symbol: [ER_NDB_BINLOG_CANT_CREATE_PURGE_THD](#); SQLSTATE: [HY000](#)

Message: NDB: Unable to purge %.%s File=%s (failed to setup thd)

[ER_NDB_BINLOG_CANT_CREATE_PURGE_THD](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010868](#); Symbol: [ER_INNODB_UNKNOWN_COLLATION](#); SQLSTATE: [HY000](#)

Message: Unknown collation #%-lu.

[ER_INNODB_UNKNOWN_COLLATION](#) was added in 8.0.2.
- Error number: [MY-010869](#); Symbol: [ER_INNODB_INVALID_LOG_GROUP_HOME_DIR](#); SQLSTATE: [HY000](#)

Message: syntax error in innodb_log_group_home_dir

[ER_INNODB_INVALID_LOG_GROUP_HOME_DIR](#) was added in 8.0.2.
- Error number: [MY-010870](#); Symbol: [ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY](#); SQLSTATE: [HY000](#)

Message: syntax error in innodb_undo_directory

[ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY](#) was added in 8.0.2.
- Error number: [MY-010871](#); Symbol: [ER_INNODB_ILLEGAL_COLON_IN_POOL](#); SQLSTATE: [HY000](#)

Message: InnoDB: innodb_buffer_pool_filename cannot have colon (:) in the file name.

[ER_INNODB_ILLEGAL_COLON_IN_POOL](#) was added in 8.0.2.
- Error number: [MY-010872](#); Symbol: [ER_INNODB_INVALID_PAGE_SIZE](#); SQLSTATE: [HY000](#)

Message: InnoDB: Invalid page size=%lu.

`ER_INNODB_INVALID_PAGE_SIZE` was added in 8.0.2.

- Error number: `MY-010873`; Symbol: `ER_INNODB_DIRTY_WATER_MARK_NOT_LOW`; SQLSTATE: `HY000`

Message: InnoDB: innodb_max_dirty_pages_pct_lwm cannot be set higher than innodb_max_dirty_pages_pct. Setting innodb_max_dirty_pages_pct_lwm to %lf

`ER_INNODB_DIRTY_WATER_MARK_NOT_LOW` was added in 8.0.2.

- Error number: `MY-010874`; Symbol: `ER_INNODB_IO_CAPACITY_EXCEEDS_MAX`; SQLSTATE: `HY000`

Message: InnoDB: innodb_io_capacity cannot be set higher than innodb_io_capacity_max. Setting innodb_io_capacity to %lu

`ER_INNODB_IO_CAPACITY_EXCEEDS_MAX` was added in 8.0.2.

- Error number: `MY-010875`; Symbol: `ER_INNODB_FILES SAME`; SQLSTATE: `HY000`

Message: %s and %s file names seem to be the same.

`ER_INNODB_FILES SAME` was added in 8.0.2.

- Error number: `MY-010876`; Symbol: `ER_INNODB_UNREGISTERED_TRX_ACTIVE`; SQLSTATE: `HY000`

Message: Transaction not registered for MySQL 2PC, but transaction is active

`ER_INNODB_UNREGISTERED_TRX_ACTIVE` was added in 8.0.2.

- Error number: `MY-010877`; Symbol: `ER_INNODB_CLOSING_CONNECTION_ROLLS_BACK`; SQLSTATE: `HY000`

Message: MySQL is closing a connection that has an active InnoDB transaction. %llu row modifications will roll back.

`ER_INNODB_CLOSING_CONNECTION_ROLLS_BACK` was added in 8.0.2.

- Error number: `MY-010878`; Symbol: `ER_INNODB_TRX_XLATION_TABLE_OOM`; SQLSTATE: `HY000`

Message: InnoDB: fail to allocate memory for index translation table. Number of Index:%lu, array size:%lu

`ER_INNODB_TRX_XLATION_TABLE_OOM` was added in 8.0.2.

- Error number: `MY-010879`; Symbol: `ER_INNODB_CANT_FIND_INDEX_IN_INNODB_DD`; SQLSTATE: `HY000`

Message: Cannot find index %s in InnoDB index dictionary.

`ER_INNODB_CANT_FIND_INDEX_IN_INNODB_DD` was added in 8.0.2.

- Error number: `MY-010880`; Symbol: `ER_INNODB_INDEX_COLUMN_INFO_UNLIKE_MYSQLS`; SQLSTATE: `HY000`

Message: Found index %s whose column info does not match that of MySQL.

`ER_INNODB_INDEX_COLUMN_INFO_UNLIKE_MYSQLS` was added in 8.0.2.

- Error number: `MY-010881`; Symbol: `ER_INNODB_CANT_OPEN_TABLE`; SQLSTATE: `HY000`

Message: Failed to open table %s.

`ER_INNODB_CANT_OPEN_TABLE` was added in 8.0.2, removed after 8.0.18.

- Error number: `MY-010882`; Symbol: `ER_INNODB_CANT_BUILD_INDEX_XLATION_TABLE_FOR`; SQLSTATE: `HY000`

Message: Build InnoDB index translation table for Table %s failed

`ER_INNODB_CANT_BUILD_INDEX_XLATION_TABLE_FOR` was added in 8.0.2.

- Error number: `MY-010883`; Symbol: `ER_INNODB_PK_NOT_IN_MYSQL`; SQLSTATE: `HY000`

Message: Table %s has a primary key in InnoDB data dictionary, but not in MySQL!

`ER_INNODB_PK_NOT_IN_MYSQL` was added in 8.0.2.

- Error number: `MY-010884`; Symbol: `ER_INNODB_PK_ONLY_IN_MYSQL`; SQLSTATE: `HY000`

Message: Table %s has no primary key in InnoDB data dictionary, but has one in MySQL! If you created the table with a MySQL version < 3.23.54 and did not define a primary key, but defined a unique key with all non-NULL columns, then MySQL internally treats that key as the primary key. You can fix this error by dump + DROP + CREATE + reimport of the table.

`ER_INNODB_PK_ONLY_IN_MYSQL` was added in 8.0.2.

- Error number: `MY-010885`; Symbol: `ER_INNODB_CLUSTERED_INDEX_PRIVATE`; SQLSTATE: `HY000`

Message: Table %s key_used_on_scan is %lu even though there is no primary key inside InnoDB.

`ER_INNODB_CLUSTERED_INDEX_PRIVATE` was added in 8.0.2.

- Error number: `MY-010886`; Symbol: `ER_INNODB_PARTITION_TABLE_LOWERCASED`; SQLSTATE: `HY000`

Message: Partition table %s opened after converting to lower case. The table may have been moved from a case-insensitive file system. Please recreate the table in the current file system.

`ER_INNODB_PARTITION_TABLE_LOWERCASED` was added in 8.0.2, removed after 8.0.18.

- Error number: `MY-010887`; Symbol: `ER_ERRMSG_REPLACEMENT_DODGY`; SQLSTATE: `HY000`

Message: Cannot replace error message (%s,%s,%s) "%s" with "%s"; wrong number or type of %% substitutions.

`ER_ERRMSG_REPLACEMENT_DODGY` was added in 8.0.2.

- Error number: `MY-010888`; Symbol: `ER_ERRMSG_REPLACEMENTS_FAILED`; SQLSTATE: `HY000`

Message: Table for error message replacements could not be found or read, or one or more replacements could not be applied.

`ER_ERRMSG_REPLACEMENTS_FAILED` was added in 8.0.2.

- Error number: `MY-010889`; Symbol: `ER_NPIPE_CANT_CREATE`; SQLSTATE: `HY000`

Message: %s: %s

`ER_NPIPE_CANT_CREATE` was added in 8.0.2.

-
- Error number: [MY-010890](#); Symbol: [ER_PARTITION_MOVE_CREATED_DUPLICATE_ROW_PLEASE_FIX](#); SQLSTATE: [HY000](#)

Message: Table '%s': Delete from part %d failed with error %d. But it was already inserted into part %d, when moving the misplaced row! Please manually fix the duplicate row: %s
[ER_PARTITION_MOVE_CREATED_DUPLICATE_ROW_PLEASE_FIX](#) was added in 8.0.2.
 - Error number: [MY-010891](#); Symbol: [ER_AUDIT_CANT_ABORT_COMMAND](#); SQLSTATE: [HY000](#)

Message: Command '%s' cannot be aborted. The trigger error was (%d) [%s]: %s
[ER_AUDIT_CANT_ABORT_COMMAND](#) was added in 8.0.2.
 - Error number: [MY-010892](#); Symbol: [ER_AUDIT_CANT_ABORT_EVENT](#); SQLSTATE: [HY000](#)

Message: Event '%s' cannot be aborted. The trigger error was (%d) [%s]: %s
[ER_AUDIT_CANT_ABORT_EVENT](#) was added in 8.0.2.
 - Error number: [MY-010893](#); Symbol: [ER_AUDIT_WARNING](#); SQLSTATE: [HY000](#)

Message: %. The trigger error was (%d) [%s]: %s
[ER_AUDIT_WARNING](#) was added in 8.0.2.
 - Error number: [MY-010894](#); Symbol: [ER_NDB_NUMBER_OF_CHANNELS](#); SQLSTATE: [HY000](#)

Message: Slave SQL: Configuration with number of replication masters = %u' is not supported when applying to Ndb
[ER_NDB_NUMBER_OF_CHANNELS](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010895](#); Symbol: [ER_NDB_SLAVE_PARALLEL_WORKERS](#); SQLSTATE: [HY000](#)

Message: Slave SQL: Configuration 'slave_parallel_workers = %lu' is not supported when applying to Ndb
[ER_NDB_SLAVE_PARALLEL_WORKERS](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010896](#); Symbol: [ER_NDB_DISTRIBUTING_ERR](#); SQLSTATE: [HY000](#)

Message: NDB %s: distributing %s err: %u
[ER_NDB_DISTRIBUTING_ERR](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010897](#); Symbol: [ER_RPL_SLAVE_INSECURE_CHANGE_MASTER](#); SQLSTATE: [HY000](#)

Message: Storing MySQL user name or password information in the master info repository is not secure and is therefore not recommended. Please consider using the USER and PASSWORD connection options for START SLAVE; see the 'START SLAVE Syntax' in the MySQL Manual for more information.
[ER_RPL_SLAVE_INSECURE_CHANGE_MASTER](#) was added in 8.0.4.
 - Error number: [MY-010898](#); Symbol: [ER_RPL_SLAVE_FLUSH_RELAY_LOGS_NOT_ALLOWED](#); SQLSTATE: [HY000](#)

Message: FLUSH RELAY LOGS cannot be performed on channel '%s'.
[ER_RPL_SLAVE_FLUSH_RELAY_LOGS_NOT_ALLOWED](#) was added in 8.0.4, removed after 8.0.15.
 - Error number: [MY-010899](#); Symbol: [ER_RPL_SLAVE_INCORRECT_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Slave channel '%s' does not exist.

`ER_RPL_SLAVE_INCORRECT_CHANNEL` was added in 8.0.4.

- Error number: `MY-010900`; Symbol: `ER_FAILED_TO_FIND_DL_ENTRY`; SQLSTATE: `HY000`

Message: Can't find symbol '%s' in library.

`ER_FAILED_TO_FIND_DL_ENTRY` was added in 8.0.4.

- Error number: `MY-010901`; Symbol: `ER_FAILED_TO_OPEN_SHARED_LIBRARY`; SQLSTATE: `HY000`

Message: Can't open shared library '%s' (errno: %d %s).

`ER_FAILED_TO_OPEN_SHARED_LIBRARY` was added in 8.0.4.

- Error number: `MY-010902`; Symbol: `ER_THREAD_PRIORITY_IGNORED`; SQLSTATE: `HY000`

Message: Thread priority attribute setting in Resource Group SQL shall be ignored due to unsupported platform or insufficient privilege.

`ER_THREAD_PRIORITY_IGNORED` was added in 8.0.4.

- Error number: `MY-010903`; Symbol: `ER_BINLOG_CACHE_SIZE_TOO_LARGE`; SQLSTATE: `HY000`

Message: Option binlog_cache_size (%lu) is greater than max_binlog_cache_size (%lu); setting binlog_cache_size equal to max_binlog_cache_size.

`ER_BINLOG_CACHE_SIZE_TOO_LARGE` was added in 8.0.4.

- Error number: `MY-010904`; Symbol: `ER_BINLOG_STMT_CACHE_SIZE_TOO_LARGE`; SQLSTATE: `HY000`

Message: Option binlog_stmt_cache_size (%lu) is greater than max_binlog_stmt_cache_size (%lu); setting binlog_stmt_cache_size equal to max_binlog_stmt_cache_size.

`ER_BINLOG_STMT_CACHE_SIZE_TOO_LARGE` was added in 8.0.4.

- Error number: `MY-010905`; Symbol: `ER_FAILED_TO_GENERATE_UNIQUE_LOGFILE`; SQLSTATE: `HY000`

Message: Can't generate a unique log-filename %s.(1-999).

`ER_FAILED_TO_GENERATE_UNIQUE_LOGFILE` was added in 8.0.4.

- Error number: `MY-010906`; Symbol: `ER_FAILED_TO_READ_FILE`; SQLSTATE: `HY000`

Message: Error reading file '%s' (errno: %d - %s)

`ER_FAILED_TO_READ_FILE` was added in 8.0.4.

- Error number: `MY-010907`; Symbol: `ER_FAILED_TO_WRITE_TO_FILE`; SQLSTATE: `HY000`

Message: Error writing file '%s' (errno: %d - %s)

`ER_FAILED_TO_WRITE_TO_FILE` was added in 8.0.4.

- Error number: `MY-010908`; Symbol: `ER_BINLOG_UNSAFE_MESSAGE_AND_STATEMENT`; SQLSTATE: `HY000`

Message: %s Statement: %s

`ER_BINLOG_UNSAFE_MESSAGE_AND_STATEMENT` was added in 8.0.4.

- Error number: `MY-010909`; Symbol: `ER_FORCE_CLOSE_THREAD`; SQLSTATE: `HY000`

Message: %s: Forcing close of thread %ld user: '%s'.

`ER_FORCE_CLOSE_THREAD` was added in 8.0.4.

- Error number: `MY-010910`; Symbol: `ER_SERVER_SHUTDOWN_COMPLETE`; SQLSTATE: `HY000`

Message: %s: Shutdown complete (mysqld %s) %s.

`ER_SERVER_SHUTDOWN_COMPLETE` was added in 8.0.4.

- Error number: `MY-010911`; Symbol: `ER_RPL_CANT_HAVE_SAME_BASENAME`; SQLSTATE: `HY000`

Message: Cannot have same base name '%s' for both binary and relay logs. Please check %s (default '%s' if --log-bin option is not used, default '%s' if --log-bin option is used without argument) and %s (default '%s') options to ensure they do not conflict.

`ER_RPL_CANT_HAVE_SAME_BASENAME` was added in 8.0.3.

- Error number: `MY-010912`; Symbol: `ER_RPL_GTID_MODE_REQUIRES_ENFORCE_GTID_CONSISTENCY_ON`; SQLSTATE: `HY000`

Message: GTID_MODE = ON requires ENFORCE_GTID_CONSISTENCY = ON.

`ER_RPL_GTID_MODE_REQUIRES_ENFORCE_GTID_CONSISTENCY_ON` was added in 8.0.4.

- Error number: `MY-010913`; Symbol: `ER_WARN_NO_SERVERID_SPECIFIED`; SQLSTATE: `HY000`

Message: You have not provided a mandatory server-id. Servers in a replication topology must have unique server-ids. Please refer to the proper server start-up parameters documentation.

`ER_WARN_NO_SERVERID_SPECIFIED` was added in 8.0.3.

- Error number: `MY-010914`; Symbol: `ER_ABORTING_USER_CONNECTION`; SQLSTATE: `HY000`

Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s).

`ER_ABORTING_USER_CONNECTION` was added in 8.0.4.

- Error number: `MY-010915`; Symbol: `ER_SQL_MODE_MERGED_WITH_STRICT_MODE`; SQLSTATE: `HY000`

Message: 'NO_ZERO_DATE', 'NO_ZERO_IN_DATE' and 'ERROR_FOR_DIVISION_BY_ZERO' sql modes should be used with strict mode. They will be merged with strict mode in a future release.

`ER_SQL_MODE_MERGED_WITH_STRICT_MODE` was added in 8.0.4.

- Error number: `MY-010916`; Symbol: `ER_GTIID_PURGED_WAS_UPDATED`; SQLSTATE: `HY000`

Message: @@GLOBAL.GTID_PURGED was changed from '%s' to '%s'.

`ER_GTIID_PURGED_WAS_UPDATED` was added in 8.0.4.

- Error number: `MY-010917`; Symbol: `ER_GTIID_EXECUTED_WAS_UPDATED`; SQLSTATE: `HY000`

Message: @@GLOBAL.GTID_EXECUTED was changed from '%s' to '%s'.

`ER_GTIID_EXECUTED_WAS_UPDATED` was added in 8.0.4.

- Error number: [MY-010918](#); Symbol: [ER_DEPRECATED_MSG_WITH_REPLACEMENT](#); SQLSTATE: [HY000](#)

Message: '%s' is deprecated and will be removed in a future release. Please use %s instead.
[ER_DEPRECATED_MSG_WITH_REPLACEMENT](#) was added in 8.0.4.
- Error number: [MY-010919](#); Symbol: [ER_TRG_CREATION_CTX_NOT_SET](#); SQLSTATE: [HY000](#)

Message: Triggers for table `'%s`.`%s` have no creation context
[ER_TRG_CREATION_CTX_NOT_SET](#) was added in 8.0.4.
- Error number: [MY-010920](#); Symbol: [ER_FILE_HAS_OLD_FORMAT](#); SQLSTATE: [HY000](#)

Message: '%s' has an old format, you should re-create the '%s' object(s)
[ER_FILE_HAS_OLD_FORMAT](#) was added in 8.0.4.
- Error number: [MY-010921](#); Symbol: [ER_VIEW_CREATION_CTX_NOT_SET](#); SQLSTATE: [HY000](#)

Message: View `'%s`.`%s` has no creation context
[ER_VIEW_CREATION_CTX_NOT_SET](#) was added in 8.0.4.
- Error number: [MY-010923](#); Symbol: [ER_TABLE_UPGRADE_REQUIRED](#); SQLSTATE: [HY000](#)

Message: Table upgrade required. Please do "REPAIR TABLE `'%s'" or dump/reload to fix it!
[ER_TABLE_UPGRADE_REQUIRED](#) was added in 8.0.4.
- Error number: [MY-010924](#); Symbol: [ER_GET_ERRNO_FROM_STORAGE_ENGINE](#); SQLSTATE: [HY000](#)

Message: Got error %d - '%s' from storage engine.
[ER_GET_ERRNO_FROM_STORAGE_ENGINE](#) was added in 8.0.4.
- Error number: [MY-010925](#); Symbol: [ER_ACCESS_DENIED_ERROR_WITHOUT_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s'
[ER_ACCESS_DENIED_ERROR_WITHOUT_PASSWORD](#) was added in 8.0.4.
- Error number: [MY-010926](#); Symbol: [ER_ACCESS_DENIED_ERROR_WITH_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s' (using password: %s)
[ER_ACCESS_DENIED_ERROR_WITH_PASSWORD](#) was added in 8.0.4.
- Error number: [MY-010927](#); Symbol: [ER_ACCESS_DENIED_FOR_USER_ACCOUNT_LOCKED](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s'. Account is locked.
[ER_ACCESS_DENIED_FOR_USER_ACCOUNT_LOCKED](#) was added in 8.0.4.
- Error number: [MY-010928](#); Symbol: [ER_MUST_CHANGE_EXPIRED_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Your password has expired. To log in you must change it using a client that supports expired passwords.

`ER_MUST_CHANGE_EXPIRED_PASSWORD` was added in 8.0.4.

- Error number: `MY-010929`; Symbol: `ER_SYSTEM_TABLES_NOT_SUPPORTED_BY_STORAGE_ENGINE`; SQLSTATE: `HY000`

Message: Storage engine '%s' does not support system tables. [%s.%s].

`ER_SYSTEM_TABLES_NOT_SUPPORTED_BY_STORAGE_ENGINE` was added in 8.0.4.

- Error number: `MY-010930`; Symbol: `ER_FILESORT_TERMINATED`; SQLSTATE: `HY000`

Message: Sort aborted

`ER_FILESORT_TERMINATED` was added in 8.0.4, removed after 8.0.18.

- Error number: `MY-010931`; Symbol: `ER_SERVER_STARTUP_MSG`; SQLSTATE: `HY000`

Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d %s.

`ER_SERVER_STARTUP_MSG` was added in 8.0.4.

- Error number: `MY-010932`; Symbol: `ER_FAILED_TO_FIND_LOCALE_NAME`; SQLSTATE: `HY000`

Message: Unknown locale: '%s'.

`ER_FAILED_TO_FIND_LOCALE_NAME` was added in 8.0.4.

- Error number: `MY-010933`; Symbol: `ER_FAILED_TO_FIND_COLLATION_NAME`; SQLSTATE: `HY000`

Message: Unknown collation: '%s'.

`ER_FAILED_TO_FIND_COLLATION_NAME` was added in 8.0.4.

- Error number: `MY-010934`; Symbol: `ER_SERVER_OUT_OF_RESOURCES`; SQLSTATE: `HY000`

Message: Out of memory; check if mysqld or some other process uses all available memory; if not, you may have to use 'ulimit' to allow mysqld to use more memory or you can add more swap space

`ER_SERVER_OUT_OF_RESOURCES` was added in 8.0.4.

- Error number: `MY-010935`; Symbol: `ER_SERVER_OUTOFMEMORY`; SQLSTATE: `HY000`

Message: Out of memory; restart server and try again (needed %d bytes)

`ER_SERVER_OUTOFMEMORY` was added in 8.0.4.

- Error number: `MY-010936`; Symbol: `ER_INVALID_COLLATION_FOR_CHARSET`; SQLSTATE: `HY000`

Message: COLLATION '%s' is not valid for CHARACTER SET '%s'

`ER_INVALID_COLLATION_FOR_CHARSET` was added in 8.0.4.

- Error number: `MY-010937`; Symbol: `ER_CANT_START_ERROR_LOG_SERVICE`; SQLSTATE: `HY000`

Message: Failed to set %s at or around "%s" -- service is valid, but can not be initialized; please check its configuration and make sure it can read its input(s) and write to its output(s).

`ER_CANT_START_ERROR_LOG_SERVICE` was added in 8.0.4.

- Error number: `MY-010938`; Symbol: `ER_CREATING_NEW_UUID_FIRST_START`; SQLSTATE: `HY000`

Message: Generating a new UUID: %s.

`ER_CREATING_NEW_UUID_FIRST_START` was added in 8.0.4.

- Error number: `MY-010939`; Symbol: `ER_FAILED_TO_GET_ABSOLUTE_PATH`; SQLSTATE: `HY000`

Message: Failed to get absolute path of program executable %s

`ER_FAILED_TO_GET_ABSOLUTE_PATH` was added in 8.0.4.

- Error number: `MY-010940`; Symbol: `ER_PERFSHEMA_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP`; SQLSTATE: `HY000`

Message: Failed to bootstrap performance schema components infrastructure.

`ER_PERFSHEMA_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP` was added in 8.0.4.

- Error number: `MY-010941`; Symbol: `ER_PERFSHEMA_COMPONENTS_INFRASTRUCTURE_SHUTDOWN`; SQLSTATE: `HY000`

Message: Failed to_deinit performance schema components infrastructure.

`ER_PERFSHEMA_COMPONENTS_INFRASTRUCTURE_SHUTDOWN` was added in 8.0.4.

- Error number: `MY-010942`; Symbol: `ER_DUP_FD_OPEN_FAILED`; SQLSTATE: `HY000`

Message: Could not open duplicate fd for %s: %s.

`ER_DUP_FD_OPEN_FAILED` was added in 8.0.4.

- Error number: `MY-010943`; Symbol: `ER_SYSTEM_VIEW_INIT_FAILED`; SQLSTATE: `HY000`

Message: System views initialization failed.

`ER_SYSTEM_VIEW_INIT_FAILED` was added in 8.0.4.

- Error number: `MY-010944`; Symbol: `ER_RESOURCE_GROUP_POST_INIT_FAILED`; SQLSTATE: `HY000`

Message: Resource group post initialization failed.

`ER_RESOURCE_GROUP_POST_INIT_FAILED` was added in 8.0.4.

- Error number: `MY-010945`; Symbol: `ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED`; SQLSTATE: `HY000`

Message: Resource Group subsystem initialization failed.

`ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED` was added in 8.0.4.

- Error number: `MY-010946`; Symbol: `ER_FAILED_START_MYSQLD_DAEMON`; SQLSTATE: `HY000`

Message: Failed to start mysqld daemon. Check mysqld error log.

`ER_FAILED_START_MYSQLD_DAEMON` was added in 8.0.4.

- Error number: `MY-010947`; Symbol: `ER_CANNOT_CHANGE_TO_ROOT_DIR`; SQLSTATE: `HY000`

Message: Cannot change to root directory: %s.

`ER_CANNOT_CHANGE_TO_ROOT_DIR` was added in 8.0.4.

-
- Error number: [MY-010948](#); Symbol: [ER_PERSISTENT_PRIVILEGES_BOOTSTRAP](#); SQLSTATE: [HY000](#)

Message: Failed to bootstrap persistent privileges.
[ER_PERSISTENT_PRIVILEGES_BOOTSTRAP](#) was added in 8.0.4.
 - Error number: [MY-010949](#); Symbol: [ER_BASEDIR_SET_TO](#); SQLSTATE: [HY000](#)

Message: Basedir set to %s.
[ER_BASEDIR_SET_TO](#) was added in 8.0.4.
 - Error number: [MY-010950](#); Symbol: [ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED](#); SQLSTATE: [HY000](#)

Message: Could not add wild do table rule '%s'!
[ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED](#) was added in 8.0.4.
 - Error number: [MY-010951](#); Symbol: [ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED](#); SQLSTATE: [HY000](#)

Message: Could not add wild ignore table rule '%s'!
[ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED](#) was added in 8.0.4.
 - Error number: [MY-010952](#); Symbol: [ER_PRIVILEGE_SYSTEM_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: The privilege system failed to initialize correctly. For complete instructions on how to upgrade MySQL to a new version please see the 'Upgrading MySQL' section from the MySQL manual.
[ER_PRIVILEGE_SYSTEM_INIT_FAILED](#) was added in 8.0.4.
 - Error number: [MY-010953](#); Symbol: [ER_CANNOT_SET_LOG_ERROR_SERVICES](#); SQLSTATE: [HY000](#)

Message: Cannot set services "%s" requested in --log-error-services, using defaults.
[ER_CANNOT_SET_LOG_ERROR_SERVICES](#) was added in 8.0.4.
 - Error number: [MY-010954](#); Symbol: [ER_PERFSHEMA_TABLES_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Performance schema tables initialization failed.
[ER_PERFSHEMA_TABLES_INIT_FAILED](#) was added in 8.0.4.
 - Error number: [MY-010955](#); Symbol: [ER_TX_EXTRACTION_ALGORITHM_FOR_BINLOG_TX_DEPENDEDENCY_TRACKING](#); SQLSTATE: [HY000](#)

Message: The transaction_write_set_extraction must be set to %s when binlog_transaction_dependency_tracking is %s.
[ER_TX_EXTRACTION_ALGORITHM_FOR_BINLOG_TX_DEPENDEDENCY_TRACKING](#) was added in 8.0.4.
 - Error number: [MY-010956](#); Symbol: [ER_INVALID_REPLICATION_TIMESTAMPS](#); SQLSTATE: [HY000](#)

Message: Invalid replication timestamps: original commit timestamp is more recent than the immediate commit timestamp. This may be an issue if delayed replication is active. Make sure

that servers have their clocks set to the correct time. No further message will be emitted until after timestamps become valid again.

`ER_INVALID_REPLICATION_TIMESTAMPS` was added in 8.0.4, removed after 8.0.25.

- Error number: `MY-010957`; Symbol: `ER_RPL_TIMESTAMPS_RETURNED_TO_NORMAL`; SQLSTATE: `HY000`

Message: The replication timestamps have returned to normal values.

`ER_RPL_TIMESTAMPS_RETURNED_TO_NORMAL` was added in 8.0.4, removed after 8.0.25.

- Error number: `MY-010958`; Symbol: `ER_BINLOG_FILE_OPEN_FAILED`; SQLSTATE: `HY000`

Message: %s.

`ER_BINLOG_FILE_OPEN_FAILED` was added in 8.0.4.

- Error number: `MY-010959`; Symbol: `ER_BINLOG_EVENT_WRITE_TO_STMT_CACHE_FAILED`; SQLSTATE: `HY000`

Message: Failed to write an incident event into stmt_cache.

`ER_BINLOG_EVENT_WRITE_TO_STMT_CACHE_FAILED` was added in 8.0.4.

- Error number: `MY-010960`; Symbol: `ER_SLAVE_RELAY_LOG_TRUNCATE_INFO`; SQLSTATE: `HY000`

Message: Relaylog file %s size was %llu, but was truncated at %llu.

`ER_SLAVE_RELAY_LOG_TRUNCATE_INFO` was added in 8.0.4.

- Error number: `MY-010961`; Symbol: `ER_SLAVE_RELAY_LOG_PURGE_FAILED`; SQLSTATE: `HY000`

Message: Unable to purge relay log files. %s:%s.

`ER_SLAVE_RELAY_LOG_PURGE_FAILED` was added in 8.0.4.

- Error number: `MY-010962`; Symbol: `ER_RPL_SLAVE_FILTER_CREATE_FAILED`; SQLSTATE: `HY000`

Message: Slave: failed in creating filter for channel '%s'.

`ER_RPL_SLAVE_FILTER_CREATE_FAILED` was added in 8.0.4.

- Error number: `MY-010963`; Symbol: `ER_RPL_SLAVE_GLOBAL_FILTERS_COPY_FAILED`; SQLSTATE: `HY000`

Message: Slave: failed in copying the global filters to its own per-channel filters on configuration for channel '%s'.

`ER_RPL_SLAVE_GLOBAL_FILTERS_COPY_FAILED` was added in 8.0.4.

- Error number: `MY-010964`; Symbol: `ER_RPL_SLAVE_RESET_FILTER_OPTIONS`; SQLSTATE: `HY000`

Message: There are per-channel replication filter(s) configured for channel '%s' which does not exist. The filter(s) have been discarded.

`ER_RPL_SLAVE_RESET_FILTER_OPTIONS` was added in 8.0.4.

-
- Error number: [MY-010965](#); Symbol: [ER_MISSING_GRANT_SYSTEM_TABLE](#); SQLSTATE: [HY000](#)

Message: The system table mysql.global_grants is missing. Please perform the MySQL upgrade procedure.
[ER_MISSING_GRANT_SYSTEM_TABLE](#) was added in 8.0.4.
 - Error number: [MY-010966](#); Symbol: [ER_MISSING_ACL_SYSTEM_TABLE](#); SQLSTATE: [HY000](#)

Message: ACL table mysql.%.*s missing. Some operations may fail.
[ER_MISSING_ACL_SYSTEM_TABLE](#) was added in 8.0.4.
 - Error number: [MY-010967](#); Symbol: [ER_ANONYMOUS_AUTH_ID_NOT_ALLOWED_IN_MANDATORY_ROLES](#); SQLSTATE: [HY000](#)

Message: Can't set mandatory_role %s@%s: Anonymous authorization IDs are not allowed as roles.
[ER_ANONYMOUS_AUTH_ID_NOT_ALLOWED_IN_MANDATORY_ROLES](#) was added in 8.0.4.
 - Error number: [MY-010968](#); Symbol: [ER_UNKNOWN_AUTH_ID_IN_MANDATORY_ROLE](#); SQLSTATE: [HY000](#)

Message: Can't set mandatory_role: There's no such authorization ID %s@%s.
[ER_UNKNOWN_AUTH_ID_IN_MANDATORY_ROLE](#) was added in 8.0.4.
 - Error number: [MY-010969](#); Symbol: [ER_WRITE_ROW_TO_PARTITION_FAILED](#); SQLSTATE: [HY000](#)

Message: Table '%s' failed to move/insert a row from part %d into part %d: %s.
[ER_WRITE_ROW_TO_PARTITION_FAILED](#) was added in 8.0.4.
 - Error number: [MY-010970](#); Symbol: [ER_RESOURCE_GROUP_METADATA_UPDATE_SKIPPED](#); SQLSTATE: [HY000](#)

Message: Skipped updating resource group metadata in InnoDB read only mode.
[ER_RESOURCE_GROUP_METADATA_UPDATE_SKIPPED](#) was added in 8.0.4.
 - Error number: [MY-010971](#); Symbol: [ER_FAILED_TO_PERSIST_RESOURCE_GROUP_METADATA](#); SQLSTATE: [HY000](#)

Message: Failed to persist resource group %s to Data Dictionary.
[ER_FAILED_TO_PERSIST_RESOURCE_GROUP_METADATA](#) was added in 8.0.4.
 - Error number: [MY-010972](#); Symbol: [ER_FAILED_TO_DESERIALIZE_RESOURCE_GROUP](#); SQLSTATE: [HY000](#)

Message: Failed to deserialize resource group %s.
[ER_FAILED_TO_DESERIALIZE_RESOURCE_GROUP](#) was added in 8.0.4.
 - Error number: [MY-010973](#); Symbol: [ER_FAILED_TO_UPDATE_RESOURCE_GROUP](#); SQLSTATE: [HY000](#)

Message: Update of resource group %s failed.
[ER_FAILED_TO_UPDATE_RESOURCE_GROUP](#) was added in 8.0.4.
 - Error number: [MY-010974](#); Symbol: [ER_RESOURCE_GROUP_VALIDATION_FAILED](#); SQLSTATE: [HY000](#)

Message: Validation of resource group %s failed. Resource group is disabled.

`ER_RESOURCE_GROUP_VALIDATION_FAILED` was added in 8.0.4.

- Error number: `MY-010975`; Symbol:

`ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP`; SQLSTATE: `HY000`

Message: Unable to allocate memory for Resource Group %s.

`ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP` was added in 8.0.4.

- Error number: `MY-010976`; Symbol:

`ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP_HASH`; SQLSTATE: `HY000`

Message: Failed to allocate memory for resource group hash.

`ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP_HASH` was added in 8.0.4.

- Error number: `MY-010977`; Symbol: `ER_FAILED_TO_ADD_RESOURCE_GROUP_TO_MAP`; SQLSTATE: `HY000`

Message: Failed to add resource group %s to resource group map.

`ER_FAILED_TO_ADD_RESOURCE_GROUP_TO_MAP` was added in 8.0.4.

- Error number: `MY-010978`; Symbol: `ER_RESOURCE_GROUP_IS_DISABLED`; SQLSTATE: `HY000`

Message: Resource group feature is disabled. (Server is compiled with `DISABLE_PSI_THREAD`).

`ER_RESOURCE_GROUP_IS_DISABLED` was added in 8.0.4.

- Error number: `MY-010979`; Symbol: `ER_FAILED_TO_APPLY_RESOURCE_GROUP_CONTROLLER`; SQLSTATE: `HY000`

Message: Unable to apply resource group controller %s.

`ER_FAILED_TO_APPLY_RESOURCE_GROUP_CONTROLLER` was added in 8.0.4.

- Error number: `MY-010980`; Symbol: `ER_FAILED_TO_ACQUIRE_LOCK_ON_RESOURCE_GROUP`; SQLSTATE: `HY000`

Message: Unable to acquire lock on the resource group %s. Hint to switch resource group shall be ignored.

`ER_FAILED_TO_ACQUIRE_LOCK_ON_RESOURCE_GROUP` was added in 8.0.4.

- Error number: `MY-010981`; Symbol: `ER_PFS_NOTIFICATION_FUNCTION_REGISTER_FAILED`; SQLSTATE: `HY000`

Message: PFS %s notification function registration failed.

`ER_PFS_NOTIFICATION_FUNCTION_REGISTER_FAILED` was added in 8.0.4.

- Error number: `MY-010982`; Symbol: `ER_RES_GRP_SET_THR_AFFINITY_FAILED`; SQLSTATE: `HY000`

Message: Unable to bind thread id %llu to cpu id %u (error code %d - %s).

`ER_RES_GRP_SET_THR_AFFINITY_FAILED` was added in 8.0.4.

- Error number: `MY-010983`; Symbol: `ER_RES_GRP_SET_THR_AFFINITY_TO_CPUS_FAILED`; SQLSTATE: `HY000`

Message: Unable to bind thread id %llu to cpu ids (error code %d - %s).

`ER_RES_GRP_SET_THR_AFFINITY_TO_CPUS_FAILED` was added in 8.0.4.

- Error number: `MY-010984`; Symbol: `ER_RES_GRP_THD_UNBIND_FROM_CPU_FAILED`; SQLSTATE: `HY000`

Message: Unbind thread id %llu failed. (error code %d - %s).

`ER_RES_GRP_THD_UNBIND_FROM_CPU_FAILED` was added in 8.0.4.

- Error number: `MY-010985`; Symbol: `ER_RES_GRP_SET_THREAD_PRIORITY_FAILED`; SQLSTATE: `HY000`

Message: Setting thread priority %d to thread id %llu failed. (error code %d - %s).

`ER_RES_GRP_SET_THREAD_PRIORITY_FAILED` was added in 8.0.4.

- Error number: `MY-010986`; Symbol: `ER_RES_GRP_FAILED_TO_DETERMINE_NICE_CAPABILITY`; SQLSTATE: `HY000`

Message: Unable to determine CAP_SYS_NICE capability.

`ER_RES_GRP_FAILED_TO_DETERMINE_NICE_CAPABILITY` was added in 8.0.4.

- Error number: `MY-010987`; Symbol: `ER_RES_GRP_FAILED_TO_GET_THREAD_HANDLE`; SQLSTATE: `HY000`

Message: %s failed: Failed to get handle for thread %llu.

`ER_RES_GRP_FAILED_TO_GET_THREAD_HANDLE` was added in 8.0.4.

- Error number: `MY-010988`; Symbol: `ER_RES_GRP_GET_THREAD_PRIO_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Retrieval of thread priority unsupported on %s.

`ER_RES_GRP_GET_THREAD_PRIO_NOT_SUPPORTED` was added in 8.0.4.

- Error number: `MY-010989`; Symbol: `ER_RES_GRP_FAILED_DETERMINE_CPU_COUNT`; SQLSTATE: `HY000`

Message: Unable to determine the number of CPUs.

`ER_RES_GRP_FAILED_DETERMINE_CPU_COUNT` was added in 8.0.4.

- Error number: `MY-010990`; Symbol: `ER_RES_GRP_FEATURE_NOT_AVAILABLE`; SQLSTATE: `HY000`

Message: Resource group feature shall not be available. Incompatible thread handling option.

`ER_RES_GRP_FEATURE_NOT_AVAILABLE` was added in 8.0.4.

- Error number: `MY-010991`; Symbol: `ER_RES_GRP_INVALID_THREAD_PRIORITY`; SQLSTATE: `HY000`

Message: Invalid thread priority %d for a %s resource group. Allowed range is [%d, %d].

`ER_RES_GRP_INVALID_THREAD_PRIORITY` was added in 8.0.4.

- Error number: `MY-010992`; Symbol: `ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_CPUID_FAILED`; SQLSTATE: `HY000`

Message: bind_to_cpu failed: processor_bind for cpuid %u failed (error code %d - %s).

`ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_CPUID_FAILED` was added in 8.0.4.

- Error number: `MY-010993`; Symbol:

`ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_THREAD_FAILED`; SQLSTATE: `HY000`

Message: bind_to_cpu failed: processor_bind for thread %%llx with cpu id %u (error code %d - %s).

`ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_THREAD_FAILED` was added in 8.0.4.

- Error number: `MY-010994`; Symbol: `ER_RES_GRP_SOLARIS_PROCESSOR_AFFINITY_FAILED`; SQLSTATE: `HY000`

Message: %s failed: processor_affinity failed (error code %d - %s).

`ER_RES_GRP_SOLARIS_PROCESSOR_AFFINITY_FAILED` was added in 8.0.4.

- Error number: `MY-010995`; Symbol: `ER_DD_UPGRADE_RENAME_IDX_STATS_FILE_FAILED`; SQLSTATE: `HY000`

Message: Error in renaming mysql_index_stats.ibd.

`ER_DD_UPGRADE_RENAME_IDX_STATS_FILE_FAILED` was added in 8.0.4.

- Error number: `MY-010996`; Symbol: `ER_DD_UPGRADE_DD_OPEN_FAILED`; SQLSTATE: `HY000`

Message: Error in opening data directory %s.

`ER_DD_UPGRADE_DD_OPEN_FAILED` was added in 8.0.4.

- Error number: `MY-010997`; Symbol: `ER_DD_UPGRADE_FAILED_TO_FETCH_TABLESPACES`; SQLSTATE: `HY000`

Message: Error in fetching list of tablespaces.

`ER_DD_UPGRADE_FAILED_TO_FETCH_TABLESPACE` was added in 8.0.4.

- Error number: `MY-010998`; Symbol: `ER_DD_UPGRADE_FAILED_TO_ACQUIRE_TABLESPACE`; SQLSTATE: `HY000`

Message: Error in acquiring Tablespace for SDI insertion %s.

`ER_DD_UPGRADE_FAILED_TO_ACQUIRE_TABLESPACE` was added in 8.0.4.

- Error number: `MY-010999`; Symbol:

`ER_DD_UPGRADE_FAILED_TO_RESOLVE_TABLESPACE_ENGINE`; SQLSTATE: `HY000`

Message: Error in resolving Engine name for tablespace %s with engine %s.

`ER_DD_UPGRADE_FAILED_TO_RESOLVE_TABLESPACE_ENGINE` was added in 8.0.4.

- Error number: `MY-011000`; Symbol: `ER_FAILED_TO_CREATE_SDIFOR_TABLESPACE`; SQLSTATE: `HY000`

Message: Error in creating SDI for %s tablespace.

`ER_FAILED_TO_CREATE_SDIFOR_TABLESPACE` was added in 8.0.4.

- Error number: `MY-011001`; Symbol: `ER_FAILED_TO_STORE_SDIFOR_TABLESPACE`; SQLSTATE: `HY000`

Message: Error in storing SDI for %s tablespace.

`ER_FAILED_TO_STORE_SDI_FOR_TABLESPACE` was added in 8.0.4.

- Error number: `MY-011002`; Symbol: `ER_DD_UPGRADE_FAILED_TO_FETCH_TABLES`; SQLSTATE: `HY000`

Message: Error in fetching list of tables.

`ER_DD_UPGRADE_FAILED_TO_FETCH_TABLES` was added in 8.0.4.

- Error number: `MY-011003`; Symbol: `ER_DD_UPGRADE_DD_POPULATED`; SQLSTATE: `HY000`

Message: Finished populating Data Dictionary tables with data.

`ER_DD_UPGRADE_DD_POPULATED` was added in 8.0.4.

- Error number: `MY-011004`; Symbol: `ER_DD_UPGRADE_INFO_FILE_OPEN_FAILED`; SQLSTATE: `HY000`

Message: Could not open the upgrade info file '%s' in the MySQL servers datadir, errno: %d.

`ER_DD_UPGRADE_INFO_FILE_OPEN_FAILED` was added in 8.0.4.

- Error number: `MY-011005`; Symbol: `ER_DD_UPGRADE_INFO_FILE_CLOSE_FAILED`; SQLSTATE: `HY000`

Message: Could not close the upgrade info file '%s' in the MySQL servers datadir, errno: %d.

`ER_DD_UPGRADE_INFO_FILE_CLOSE_FAILED` was added in 8.0.4.

- Error number: `MY-011006`; Symbol: `ER_DD_UPGRADE_TABLESPACE_MIGRATION_FAILED`; SQLSTATE: `HY000`

Message: Got error %d from SE while migrating tablespaces.

`ER_DD_UPGRADE_TABLESPACE_MIGRATION_FAILED` was added in 8.0.4.

- Error number: `MY-011007`; Symbol: `ER_DD_UPGRADE_FAILED_TO_CREATE_TABLE_STATS`; SQLSTATE: `HY000`

Message: Error in creating TABLE statistics entry. Fix statistics data by using ANALYZE command.

`ER_DD_UPGRADE_FAILED_TO_CREATE_TABLE_STATS` was added in 8.0.4.

- Error number: `MY-011008`; Symbol: `ER_DD_UPGRADE_TABLE_STATS_MIGRATE_COMPLETED`; SQLSTATE: `HY000`

Message: Finished migrating TABLE statistics data.

`ER_DD_UPGRADE_TABLE_STATS_MIGRATE_COMPLETED` was added in 8.0.4.

- Error number: `MY-011009`; Symbol: `ER_DD_UPGRADE_FAILED_TO_CREATE_INDEX_STATS`; SQLSTATE: `HY000`

Message: Error in creating Index statistics entry. Fix statistics data by using ANALYZE command.

`ER_DD_UPGRADE_FAILED_TO_CREATE_INDEX_STATS` was added in 8.0.4.

- Error number: `MY-011010`; Symbol: `ER_DD_UPGRADE_INDEX_STATS_MIGRATE_COMPLETED`; SQLSTATE: `HY000`

Message: Finished migrating INDEX statistics data.

`ER_DD_UPGRADE_INDEX_STATS_MIGRATE_COMPLETED` was added in 8.0.4.

- Error number: [MY-011011](#); Symbol: [ER_DD_UPGRADE_FAILED_FIND_VALID_DATA_DIR](#); SQLSTATE: [HY000](#)

Message: Failed to find valid data directory.
[ER_DD_UPGRADE_FAILED_FIND_VALID_DATA_DIR](#) was added in 8.0.4.
- Error number: [MY-011012](#); Symbol: [ER_DD_UPGRADE_START](#); SQLSTATE: [HY000](#)

Message: Starting upgrade of data directory.
[ER_DD_UPGRADE_START](#) was added in 8.0.4.
- Error number: [MY-011013](#); Symbol: [ER_DD_UPGRADE_FAILED_INIT_DD_SE](#); SQLSTATE: [HY000](#)

Message: Failed to initialize DD Storage Engine.
[ER_DD_UPGRADE_FAILED_INIT_DD_SE](#) was added in 8.0.4.
- Error number: [MY-011014](#); Symbol: [ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_ABORT](#); SQLSTATE: [HY000](#)

Message: Found partially upgraded DD. Aborting upgrade and deleting all DD tables. Start the upgrade process again.
[ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_ABORT](#) was added in 8.0.4.
- Error number: [MY-011015](#); Symbol: [ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_CONTINUE](#); SQLSTATE: [HY000](#)

Message: Found partially upgraded DD. Upgrade will continue and start the server.
[ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_CONTINUE](#) was added in 8.0.4.
- Error number: [MY-011016](#); Symbol: [ER_DD_UPGRADE_SE_LOGS_FAILED](#); SQLSTATE: [HY000](#)

Message: Error in upgrading engine logs.
[ER_DD_UPGRADE_SE_LOGS_FAILED](#) was added in 8.0.4.
- Error number: [MY-011017](#); Symbol: [ER_DD_UPGRADE_SDI_INFO_UPDATE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error in updating SDI information.
[ER_DD_UPGRADE_SDI_INFO_UPDATE_FAILED](#) was added in 8.0.4.
- Error number: [MY-011018](#); Symbol: [ER_SKIP_UPDATING_METADATA_IN_SE_RO_MODE](#); SQLSTATE: [HY000](#)

Message: Skip updating %s metadata in InnoDB read-only mode.
[ER_SKIP_UPDATING_METADATA_IN_SE_RO_MODE](#) was added in 8.0.4.
- Error number: [MY-011019](#); Symbol: [ER_CREATED_SYSTEM_WITH_VERSION](#); SQLSTATE: [HY000](#)

Message: Created system views with I_S version %d.
[ER_CREATED_SYSTEM_WITH_VERSION](#) was added in 8.0.4.
- Error number: [MY-011020](#); Symbol: [ER_UNKNOWN_ERROR_DETECTED_IN_SE](#); SQLSTATE: [HY000](#)

Message: Unknown error detected %d in handler.

`ER_UNKNOWN_ERROR_DETECTED_IN_SE` was added in 8.0.4.

- Error number: `MY-011021`; Symbol: `ER_READ_LOG_EVENT_FAILED`; SQLSTATE: `HY000`

Message: Error in Log_event::read_log_event(): '%s', data_len: %lu, event_type: %d.

`ER_READ_LOG_EVENT_FAILED` was added in 8.0.4.

- Error number: `MY-011022`; Symbol: `ER_ROW_DATA_TOO_BIG_TO_WRITE_IN_BINLOG`; SQLSTATE: `HY000`

Message: The row data is greater than 4GB, which is too big to write to the binary log.

`ER_ROW_DATA_TOO_BIG_TO_WRITE_IN_BINLOG` was added in 8.0.4.

- Error number: `MY-011023`; Symbol: `ER_FAILED_TO_CONSTRUCT_DROP_EVENT_QUERY`; SQLSTATE: `HY000`

Message: Unable to construct DROP EVENT SQL query string.

`ER_FAILED_TO_CONSTRUCT_DROP_EVENT_QUERY` was added in 8.0.4.

- Error number: `MY-011024`; Symbol: `ER_FAILED_TO_BINLOG_DROP_EVENT`; SQLSTATE: `HY000`

Message: Unable to binlog drop event %s.%s.

`ER_FAILED_TO_BINLOG_DROP_EVENT` was added in 8.0.4.

- Error number: `MY-011025`; Symbol: `ER_FAILED_TO_START_SLAVE_THREAD`; SQLSTATE: `HY000`

Message: Failed to start slave threads for channel '%s'.

`ER_FAILED_TO_START_SLAVE_THREAD` was added in 8.0.4.

- Error number: `MY-011026`; Symbol: `ER_RPL_IO_THREAD_KILLED`; SQLSTATE: `HY000`

Message: %s%.

`ER_RPL_IO_THREAD_KILLED` was added in 8.0.4.

- Error number: `MY-011027`; Symbol: `ER_SLAVE_RECONNECT_FAILED`; SQLSTATE: `HY000`

Message: Failed registering on master, reconnecting to try again, log '%s' at position %s. %s.

`ER_SLAVE_RECONNECT_FAILED` was added in 8.0.4.

- Error number: `MY-011028`; Symbol: `ER_SLAVE_KILLED_AFTER_RECONNECT`; SQLSTATE: `HY000`

Message: Slave I/O thread killed during or after reconnect.

`ER_SLAVE_KILLED_AFTER_RECONNECT` was added in 8.0.4.

- Error number: `MY-011029`; Symbol: `ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS`; SQLSTATE: `HY000`

Message: Some of the channels are not created/initialized properly. Check for additional messages above. You will not be able to start replication on those channels until the issue is resolved and the server restarted.

`ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS` was added in 8.0.4.

- Error number: `MY-011030`; Symbol: `ER_FAILED_TO_ADD_RPL_FILTER`; SQLSTATE: `HY000`

Message: Failed to add a replication filter into filter map for channel '%s'.

`ER_FAILED_TO_ADD_RPL_FILTER` was added in 8.0.4.

- Error number: `MY-011031`; Symbol: `ER_PER_CHANNEL_RPL_FILTER_CONF_FOR_GRP_RPL`; SQLSTATE: `HY000`

Message: There are per-channel replication filter(s) configured for group replication channel '%s' which is disallowed. The filter(s) have been discarded.

`ER_PER_CHANNEL_RPL_FILTER_CONF_FOR_GRP_RPL` was added in 8.0.4.

- Error number: `MY-011032`; Symbol: `ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL`; SQLSTATE: `HY000`

Message: There are per-channel replication filter(s) configured for channel '%s' which does not exist. The filter(s) have been discarded.

`ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL` was added in 8.0.4.

- Error number: `MY-011033`; Symbol: `ER_FAILED_TO_BUILD_DO_AND_IGNORE_TABLE_HASHES`; SQLSTATE: `HY000`

Message: An error occurred while building do_table and ignore_table rules to hashes for per-channel filter.

`ER_FAILED_TO_BUILD_DO_AND_IGNORE_TABLE_HASHES` was added in 8.0.4.

- Error number: `MY-011034`; Symbol: `ER_CLONE_PLUGIN_NOT_LOADED`; SQLSTATE: `HY000`

Message: Clone plugin not loaded.

`ER_CLONE_PLUGIN_NOT_LOADED` was added in 8.0.4, removed after 8.0.16.

- Error number: `MY-011034`; Symbol: `ER_CLONE_PLUGIN_NOT_LOADED_TRACE`; SQLSTATE: `HY000`

Message: Clone plugin cannot be loaded.

`ER_CLONE_PLUGIN_NOT_LOADED_TRACE` was added in 8.0.17.

- Error number: `MY-011035`; Symbol: `ER_CLONE_HANDLER_EXISTS`; SQLSTATE: `HY000`

Message: Clone Handler exists.

`ER_CLONE_HANDLER_EXISTS` was added in 8.0.4, removed after 8.0.16.

- Error number: `MY-011035`; Symbol: `ER_CLONE_HANDLER_EXIST_TRACE`; SQLSTATE: `HY000`

Message: Clone Handler exists.

`ER_CLONE_HANDLER_EXIST_TRACE` was added in 8.0.17.

- Error number: `MY-011036`; Symbol: `ER_FAILED_TO_CREATE_CLONE_HANDLER`; SQLSTATE: `HY000`

Message: Could not create Clone Handler.

`ER_FAILED_TO_CREATE_CLONE_HANDLER` was added in 8.0.4, removed after 8.0.16.

- Error number: `MY-011036`; Symbol: `ER_CLONE_CREATE_HANDLER_FAIL_TRACE`; SQLSTATE: `HY000`

Message: Could not create Clone Handler.

`ER_CLONE_CREATE_HANDLER_FAIL_TRACE` was added in 8.0.17.

- Error number: `MY-011037`; Symbol: `ER_CYCLE_TIMER_IS_NOT_AVAILABLE`; SQLSTATE: `HY000`

Message: The CYCLE timer is not available. WAIT events in the performance_schema will not be timed.

`ER_CYCLE_TIMER_IS_NOT_AVAILABLE` was added in 8.0.4.

- Error number: `MY-011038`; Symbol: `ER_NANOSECOND_TIMER_IS_NOT_AVAILABLE`; SQLSTATE: `HY000`

Message: The NANOSECOND timer is not available. IDLE/STAGE/STATEMENT/TRANSACTION events in the performance_schema will not be timed.

`ER_NANOSECOND_TIMER_IS_NOT_AVAILABLE` was added in 8.0.4.

- Error number: `MY-011039`; Symbol: `ER_MICROSECOND_TIMER_IS_NOT_AVAILABLE`; SQLSTATE: `HY000`

Message: The MICROSECOND timer is not available. IDLE/STAGE/STATEMENT/TRANSACTION events in the performance_schema will not be timed.

`ER_MICROSECOND_TIMER_IS_NOT_AVAILABLE` was added in 8.0.4.

- Error number: `MY-011040`; Symbol: `ER_PFS_MALLOC_ARRAY_OVERFLOW`; SQLSTATE: `HY000`

Message: Failed to allocate memory for %zu chunks each of size %zu for buffer '%s' due to overflow.

`ER_PFS_MALLOC_ARRAY_OVERFLOW` was added in 8.0.4.

- Error number: `MY-011041`; Symbol: `ER_PFS_MALLOC_ARRAY_OOM`; SQLSTATE: `HY000`

Message: Failed to allocate %zu bytes for buffer '%s' due to out-of-memory.

`ER_PFS_MALLOC_ARRAY_OOM` was added in 8.0.4.

- Error number: `MY-011042`; Symbol: `ER_INNODB_FAILED_TO_FIND_IDX_WITH_KEY_NO`; SQLSTATE: `HY000`

Message: InnoDB could not find index %s key no %u for table %s through its index translation table.

`ER_INNODB_FAILED_TO_FIND_IDX_WITH_KEY_NO` was added in 8.0.4.

- Error number: `MY-011043`; Symbol: `ER_INNODB_FAILED_TO_FIND_IDX`; SQLSTATE: `HY000`

Message: Cannot find index %s in InnoDB index translation table.

`ER_INNODB_FAILED_TO_FIND_IDX` was added in 8.0.4.

- Error number: `MY-011044`; Symbol: `ER_INNODB_FAILED_TO_FIND_IDX_FROM_DICT_CACHE`; SQLSTATE: `HY000`

Message: InnoDB could not find key no %u with name %s from dict cache for table %s.

`ER_INNODB_FAILED_TO_FIND_IDX_FROM_DICT_CACHE` was added in 8.0.4.

- Error number: `MY-011045`; Symbol: `ER_INNODB_ACTIVE_INDEX_CHANGE_FAILED`; SQLSTATE: `HY000`

Message: InnoDB: change_active_index(%u) failed.

`ER_INNODB_ACTIVE_INDEX_CHANGE_FAILED` was added in 8.0.4.

- Error number: `MY-011046`; Symbol: `ER_INNODB_DIFF_IN_REF_LEN`; SQLSTATE: `HY000`

Message: Stored ref len is %lu, but table ref len is %lu.

`ER_INNODB_DIFF_IN_REF_LEN` was added in 8.0.4.

- Error number: `MY-011047`; Symbol: `ER_WRONG_TYPE_FOR_COLUMN_PREFIX_IDX_FLD`; SQLSTATE: `HY000`

Message: MySQL is trying to create a column prefix index field, on an inappropriate data type. Table name %s, column name %s.

`ER_WRONG_TYPE_FOR_COLUMN_PREFIX_IDX_FLD` was added in 8.0.4.

- Error number: `MY-011048`; Symbol: `ER_INNODB_CANNOT_CREATE_TABLE`; SQLSTATE: `HY000`

Message: Cannot create table %s.

`ER_INNODB_CANNOT_CREATE_TABLE` was added in 8.0.4.

- Error number: `MY-011049`; Symbol: `ER_INNODB_INTERNAL_INDEX`; SQLSTATE: `HY000`

Message: Found index %s in InnoDB index list but not its MySQL index number. It could be an InnoDB internal index.

`ER_INNODB_INTERNAL_INDEX` was added in 8.0.4.

- Error number: `MY-011050`; Symbol: `ER_INNODB_IDX_CNT_MORE_THAN_DEFINED_IN_MYSQL`; SQLSTATE: `HY000`

Message: InnoDB: Table %s contains %lu indexes inside InnoDB, which is different from the number of indexes %u defined in MySQL.

`ER_INNODB_IDX_CNT_MORE_THAN_DEFINED_IN_MYSQL` was added in 8.0.4.

- Error number: `MY-011051`; Symbol: `ER_INNODB_IDX_CNT_FEWER_THAN_DEFINED_IN_MYSQL`; SQLSTATE: `HY000`

Message: Table %s contains fewer indexes inside InnoDB than are defined in the MySQL. Have you mixed up with data dictionary from different installation?

`ER_INNODB_IDX_CNT_FEWER_THAN_DEFINED_IN_MYSQL` was added in 8.0.4.

- Error number: `MY-011052`; Symbol: `ER_INNODB_IDX_COLUMN_CNT_DIFF`; SQLSTATE: `HY000`

Message: Index %s of %s has %lu columns unique inside InnoDB, but MySQL is asking statistics for %lu columns. Have you mixed data dictionary from different installation?

`ER_INNODB_IDX_COLUMN_CNT_DIFF` was added in 8.0.4.

- Error number: `MY-011053`; Symbol: `ER_INNODB_USE_MONITOR_GROUP_NAME`; SQLSTATE: `HY000`

Message: Monitor counter '%s' cannot be turned on/off individually. Please use its module name to turn on/off the counters in the module as a group.

`ER_INNODB_USE_MONITOR_GROUP_NAME` was added in 8.0.4.

- Error number: `MY-011054`; Symbol: `ER_INNODB_MONITOR_DEFAULT_VALUE_NOT_DEFINED`; SQLSTATE: `HY000`

Message: Default value is not defined for this set option. Please specify correct counter or module name.

`ER_INNODB_MONITOR_DEFAULT_VALUE_NOT_DEFINED` was added in 8.0.4.

- Error number: `MY-011055`; Symbol: `ER_INNODB_MONITOR_IS_ENABLED`; SQLSTATE: `HY000`

Message: InnoDB: Monitor %s is already enabled.

`ER_INNODB_MONITOR_IS_ENABLED` was added in 8.0.4.

- Error number: `MY-011056`; Symbol: `ER_INNODB_INVALID_MONITOR_COUNTER_NAME`; SQLSTATE: `HY000`

Message: Invalid monitor counter : %s.

`ER_INNODB_INVALID_MONITOR_COUNTER_NAME` was added in 8.0.4.

- Error number: `MY-011057`; Symbol: `ER_WIN_LOAD_LIBRARY_FAILED`; SQLSTATE: `HY000`

Message: LoadLibrary("%s") failed: GetLastError returns %lu.

`ER_WIN_LOAD_LIBRARY_FAILED` was added in 8.0.4.

- Error number: `MY-011058`; Symbol: `ER_PARTITION_HANDLER_ADMIN_MSG`; SQLSTATE: `HY000`

Message: %s.

`ER_PARTITION_HANDLER_ADMIN_MSG` was added in 8.0.4.

- Error number: `MY-011059`; Symbol: `ER_RPL_RLI_INIT_INFO_MSG`; SQLSTATE: `HY000`

Message: %s.

`ER_RPL_RLI_INIT_INFO_MSG` was added in 8.0.4.

- Error number: `MY-011060`; Symbol: `ER_DD_UPGRADE_TABLE_INTACT_ERROR`; SQLSTATE: `HY000`

Message: %s.

`ER_DD_UPGRADE_TABLE_INTACT_ERROR` was added in 8.0.4.

- Error number: `MY-011061`; Symbol: `ER_SERVER_INIT_COMPILED_IN_COMMANDS`; SQLSTATE: `HY000`

Message: %s.

`ER_SERVER_INIT_COMPILED_IN_COMMANDS` was added in 8.0.4.

- Error number: `MY-011062`; Symbol: `ER_MYISAM_CHECK_METHOD_ERROR`; SQLSTATE: `HY000`

Message: %s.

`ER_MYISAM_CHECK_METHOD_ERROR` was added in 8.0.4.

- Error number: `MY-011063`; Symbol: `ER_MYISAM_CRASHED_ERROR`; SQLSTATE: `HY000`

Message: %s.

`ER_MYISAM_CRASHED_ERROR` was added in 8.0.4.

- Error number: `MY-011064`; Symbol: `ER_WAITPID_FAILED`; SQLSTATE: `HY000`

Message: Unable to wait for process %lld.

`ER_WAITPID_FAILED` was added in 8.0.4.

- Error number: `MY-011065`; Symbol: `ER_FAILED_TO_FIND_MYSQLD_STATUS`; SQLSTATE: `HY000`

Message: Unable to determine if daemon is running: %s (rc=%d).

`ER_FAILED_TO_FIND_MYSQLD_STATUS` was added in 8.0.4.

- Error number: `MY-011066`; Symbol: `ER_INNODB_ERROR_LOGGER_MSG`; SQLSTATE: `HY000`

Message: %s

`ER_INNODB_ERROR_LOGGER_MSG` was added in 8.0.4.

- Error number: `MY-011067`; Symbol: `ER_INNODB_ERROR_LOGGER_FATAL_MSG`; SQLSTATE: `HY000`

Message: [FATAL] InnoDB: %s

`ER_INNODB_ERROR_LOGGER_FATAL_MSG` was added in 8.0.4.

- Error number: `MY-011068`; Symbol: `ER_DEPRECATED_SYNTAX_WITH_REPLACEMENT`; SQLSTATE: `HY000`

Message: The syntax '%s' is deprecated and will be removed in a future release. Please use %s instead.

`ER_DEPRECATED_SYNTAX_WITH_REPLACEMENT` was added in 8.0.4.

- Error number: `MY-011069`; Symbol: `ER_DEPRECATED_SYNTAX_NO REPLACEMENT`; SQLSTATE: `HY000`

Message: The syntax '%s' is deprecated and will be removed in a future release.

`ER_DEPRECATED_SYNTAX_NO REPLACEMENT` was added in 8.0.4.

- Error number: `MY-011070`; Symbol: `ER_DEPRECATED_MSG_NO REPLACEMENT`; SQLSTATE: `HY000`

Message: '%s' is deprecated and will be removed in a future release.

`ER_DEPRECATED_MSG_NO REPLACEMENT` was added in 8.0.4.

- Error number: `MY-011071`; Symbol: `ER_LOG_PRINTF_MSG`; SQLSTATE: `HY000`

Message: %s

`ER_LOG_PRINTF_MSG` was added in 8.0.4.

- Error number: `MY-011072`; Symbol: `ER_BINLOG_LOGGING_NOT_POSSIBLE`; SQLSTATE: `HY000`

Message: Binary logging not possible. Message: %s.

`ER_BINLOG_LOGGING_NOT_POSSIBLE` was added in 8.0.4.

- Error number: `MY-011073`; Symbol: `ER_FAILED_TO_SET_PERSISTED_OPTIONS`; SQLSTATE: `HY000`

Message: Failed to set persisted options.

`ER_FAILED_TO_SET_PERSISTED_OPTIONS` was added in 8.0.4.

- Error number: [MY-011074](#); Symbol: [ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION](#); SQLSTATE: [HY000](#)

Message: Cannot acquire specified service implementation: '%s'.
[ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION](#) was added in 8.0.4.
- Error number: [MY-011075](#); Symbol: [ER_RES_GRP_INVALID_VCPU_RANGE](#); SQLSTATE: [HY000](#)

Message: Invalid VCPU range %u-%u.
[ER_RES_GRP_INVALID_VCPU_RANGE](#) was added in 8.0.4.
- Error number: [MY-011076](#); Symbol: [ER_RES_GRP_INVALID_VCPU_ID](#); SQLSTATE: [HY000](#)

Message: Invalid cpu id %u.
[ER_RES_GRP_INVALID_VCPU_ID](#) was added in 8.0.4.
- Error number: [MY-011077](#); Symbol: [ER_ERROR_DURING_FLUSH_LOG_COMMIT_PHASE](#); SQLSTATE: [HY000](#)

Message: Got error %d during FLUSH_LOGS.
[ER_ERROR_DURING_FLUSH_LOG_COMMIT_PHASE](#) was added in 8.0.4.
- Error number: [MY-011078](#); Symbol: [ER_DROP_DATABASE_FAILED_RMDIR_MANUALLY](#); SQLSTATE: [HY000](#)

Message: Problem while dropping database. Can't remove database directory (%s). Please remove it manually.
[ER_DROP_DATABASE_FAILED_RMDIR_MANUALLY](#) was added in 8.0.4.
- Error number: [MY-011079](#); Symbol: [ER_BINLOG_EXPIRAY_LOG_DAYS_AND_SECS_USED_TOGETHER](#); SQLSTATE: [HY000](#)

Message: The option expire_logs_days cannot be used together with option binlog_expire_logs_seconds. Therefore, value of expire_logs_days is ignored.
[ER_BINLOG_EXPIRAY_LOG_DAYS_AND_SECS_USED_TOGETHER](#) was added in 8.0.4, removed after 8.0.4.
- Error number: [MY-011079](#); Symbol: [ER_EXPIRE_LOGS_DAYS_IGNORED](#); SQLSTATE: [HY000](#)

Message: The option expire_logs_days cannot be used together with option binlog_expire_logs_seconds. Therefore, value of expire_logs_days is ignored.
[ER_EXPIRE_LOGS_DAYS_IGNORED](#) was added in 8.0.4.
- Error number: [MY-011080](#); Symbol: [ER_BINLOG_MALFORMED_OR_OLD_RELAY_LOG](#); SQLSTATE: [HY000](#)

Message: malformed or very old relay log which does not have FormatDescriptor.
[ER_BINLOG_MALFORMED_OR_OLD_RELAY_LOG](#) was added in 8.0.4.

- Error number: [MY-011081](#); Symbol: [ER_DD_UPGRADE_VIEW_COLUMN_NAME_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: Upgrade of view '%s.%s' failed. Re-create the view with the explicit column name lesser than 64 characters.

[ER_DD_UPGRADE_VIEW_COLUMN_NAME_TOO_LONG](#) was added in 8.0.4.
- Error number: [MY-011082](#); Symbol: [ER_TABLE_NEEDS_DUMP_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Table upgrade required for `'%s`.%s`. Please dump/reload table to fix it!

[ER_TABLE_NEEDS_DUMP_UPGRADE](#) was added in 8.0.4.
- Error number: [MY-011083](#); Symbol: [ER_DD_UPGRADE_FAILED_TO_UPDATE_VER_NO_IN_TABLESPACE](#); SQLSTATE: [HY000](#)

Message: Error in updating version number in %s tablespace.

[ER_DD_UPGRADE_FAILED_TO_UPDATE_VER_NO_IN_TABLESPACE](#) was added in 8.0.4.
- Error number: [MY-011084](#); Symbol: [ER_KEYRING_MIGRATION_FAILED](#); SQLSTATE: [HY000](#)

Message: Keyring migration failed.

[ER_KEYRING_MIGRATION_FAILED](#) was added in 8.0.4.
- Error number: [MY-011085](#); Symbol: [ER_KEYRING_MIGRATION_SUCCESSFUL](#); SQLSTATE: [HY000](#)

Message: Keyring migration successful.

[ER_KEYRING_MIGRATION_SUCCESSFUL](#) was added in 8.0.4.
- Error number: [MY-011086](#); Symbol: [ER_RESTART_RECEIVED_INFO](#); SQLSTATE: [HY000](#)

Message: Received RESTART from user %. Restarting mysqld (Version: %s).

[ER_RESTART_RECEIVED_INFO](#) was added in 8.0.4.
- Error number: [MY-011087](#); Symbol: [ER_LCTN_CHANGED](#); SQLSTATE: [HY000](#)

Message: Different lower_case_table_names settings for server ('%u') and data dictionary ('%u').

[ER_LCTN_CHANGED](#) was added in 8.0.4.
- Error number: [MY-011088](#); Symbol: [ER_DD_INITIALIZE](#); SQLSTATE: [HY000](#)

Message: Data dictionary initializing version '%u'.

[ER_DD_INITIALIZE](#) was added in 8.0.4.
- Error number: [MY-011089](#); Symbol: [ER_DD_RESTART](#); SQLSTATE: [HY000](#)

Message: Data dictionary restarting version '%u'.

[ER_DD_RESTART](#) was added in 8.0.4.
- Error number: [MY-011090](#); Symbol: [ER_DD_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Data dictionary upgrading from version '%u' to '%u'.

[ER_DD_UPGRADE](#) was added in 8.0.4.
- Error number: [MY-011091](#); Symbol: [ER_DD_UPGRADE_OFF](#); SQLSTATE: [HY000](#)

Message: Data dictionary upgrade prohibited by the command line option '--no_dd_upgrade'.

`ER_DD_UPGRADE_OFF` was added in 8.0.4.

- Error number: `MY-011092`; Symbol: `ER_DD_UPGRADE_VERSION_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Upgrading the data dictionary from dictionary version '%u' is not supported.

`ER_DD_UPGRADE_VERSION_NOT_SUPPORTED` was added in 8.0.4.

- Error number: `MY-011093`; Symbol: `ER_DD_UPGRADE_SCHEMA_UNAVAILABLE`; SQLSTATE: `HY000`

Message: Upgrading the data dictionary failed, temporary schema name '%s' not available.

`ER_DD_UPGRADE_SCHEMA_UNAVAILABLE` was added in 8.0.4.

- Error number: `MY-011094`; Symbol: `ER_DD_MINOR_DOWNGRADE`; SQLSTATE: `HY000`

Message: Data dictionary minor downgrade from version '%u' to '%u'.

`ER_DD_MINOR_DOWNGRADE` was added in 8.0.4.

- Error number: `MY-011095`; Symbol: `ER_DD_MINOR_DOWNGRADE_VERSION_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Minor downgrade of the Data dictionary from dictionary version '%u' is not supported.

`ER_DD_MINOR_DOWNGRADE_VERSION_NOT_SUPPORTED` was added in 8.0.4.

- Error number: `MY-011096`; Symbol: `ER_DD_NO_VERSION_FOUND`; SQLSTATE: `HY000`

Message: No data dictionary version number found.

`ER_DD_NO_VERSION_FOUND` was added in 8.0.4.

- Error number: `MY-011097`; Symbol: `ER_THREAD_POOL_NOT_SUPPORTED_ON_PLATFORM`; SQLSTATE: `HY000`

Message: Thread pool not supported, requires a minimum of %s.

`ER_THREAD_POOL_NOT_SUPPORTED_ON_PLATFORM` was added in 8.0.4.

- Error number: `MY-011098`; Symbol: `ER_THREAD_POOL_SIZE_TOO_LOW`; SQLSTATE: `HY000`

Message: thread_pool_size=0 means thread pool disabled, Allowed range of thread_pool_size is %d-%d.

`ER_THREAD_POOL_SIZE_TOO_LOW` was added in 8.0.4.

- Error number: `MY-011099`; Symbol: `ER_THREAD_POOL_SIZE_TOO_HIGH`; SQLSTATE: `HY000`

Message: thread_pool_size=%lu is too high, %d is maximum, thread pool is disabled. Allowed range of thread_pool_size is %d-%d.

`ER_THREAD_POOL_SIZE_TOO_HIGH` was added in 8.0.4.

- Error number: `MY-011100`; Symbol: `ER_THREAD_POOL_ALGORITHM_INVALID`; SQLSTATE: `HY000`

Message: thread_pool_algorithm can be set to 0 and 1, 0 indicates the default low concurrency algorithm, 1 means a high concurrency algorithm.

`ER_THREAD_POOL_ALGORITHM_INVALID` was added in 8.0.4.

- Error number: `MY-011101`; Symbol: `ER_THREAD_POOL_INVALID_STALL_LIMIT`; SQLSTATE: `HY000`

Message: thread_pool_stall_limit can be %d at minimum and %d at maximum, smaller values would render the thread pool fairly useless and higher values could make it possible to have undetected deadlock issues in the MySQL Server.

`ER_THREAD_POOL_INVALID_STALL_LIMIT` was added in 8.0.4.

- Error number: `MY-011102`; Symbol: `ER_THREAD_POOL_INVALID_PRIO_KICKUP_TIMER`; SQLSTATE: `HY000`

Message: Invalid value of thread_pool_prio_kickup_timer specified. Value of thread_pool_prio_kickup_timer should be in range 0-4294967294.

`ER_THREAD_POOL_INVALID_PRIO_KICKUP_TIMER` was added in 8.0.4.

- Error number: `MY-011103`; Symbol: `ER_THREAD_POOL_MAX_UNUSED_THREADS_INVALID`; SQLSTATE: `HY000`

Message: thread_pool_max_unused_threads cannot be set higher than %d.

`ER_THREAD_POOL_MAX_UNUSED_THREADS_INVALID` was added in 8.0.4.

- Error number: `MY-011104`; Symbol: `ER_THREAD_POOL_CON_HANDLER_INIT_FAILED`; SQLSTATE: `HY000`

Message: Failed to instantiate the connection handler object.

`ER_THREAD_POOL_CON_HANDLER_INIT_FAILED` was added in 8.0.4.

- Error number: `MY-011105`; Symbol: `ER_THREAD_POOL_INIT_FAILED`; SQLSTATE: `HY000`

Message: Failed to initialize thread pool plugin.

`ER_THREAD_POOL_INIT_FAILED` was added in 8.0.4.

- Error number: `MY-011106`; Symbol: `ER_THREAD_POOL_PLUGIN_STARTED`; SQLSTATE: `HY000`

Message: Thread pool plugin started successfully with parameters: thread_pool_size = %lu, thread_pool_algorithm = %s, thread_pool_stall_limit = %u, thread_pool_prio_kickup_timer = %u, thread_pool_max_unused_threads = %u, thread_pool_high_priority_connection = %d.

`ER_THREAD_POOL_PLUGIN_STARTED` was added in 8.0.4.

- Error number: `MY-011107`; Symbol: `ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC_DATA`; SQLSTATE: `HY000`

Message: Can't setup connection teardown thread-specific data.

`ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC_DATA` was added in 8.0.4.

- Error number: `MY-011108`; Symbol: `ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT_HANDLER_THD`; SQLSTATE: `HY000`

Message: Creation of connect handler thread failed.

`ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT_HANDLER_THD` was added in 8.0.4.

- Error number: `MY-011109`; Symbol: `ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_AUTH_CONN`; SQLSTATE: `HY000`

Message: Failed to create thd and authenticate connection.
`ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_AUTH_CONN` was added in 8.0.4.
- Error number: `MY-011110`; Symbol: `ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT`; SQLSTATE: `HY000`

Message: Failed to process connection event.
`ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT` was added in 8.0.4.
- Error number: `MY-011111`; Symbol: `ER_THREAD_POOL_FAILED_TO_CREATE_POOL`; SQLSTATE: `HY000`

Message: Can't create pool thread (error %d, errno: %d).
`ER_THREAD_POOL_FAILED_TO_CREATE_POOL` was added in 8.0.4.
- Error number: `MY-011112`; Symbol: `ER_THREAD_POOL_RATE_LIMITED_ERROR_MSGS`; SQLSTATE: `HY000`

Message: %.*s.
`ER_THREAD_POOL_RATE_LIMITED_ERROR_MSGS` was added in 8.0.4.
- Error number: `MY-011113`; Symbol: `ER_THREAD_POOL_LOW_LEVEL_INIT_FAILED`; SQLSTATE: `HY000`

Message: tp_group_low_level_init() failed.
`ER_THREAD_POOL_LOW_LEVEL_INIT_FAILED` was added in 8.0.4.
- Error number: `MY-011114`; Symbol: `ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED`; SQLSTATE: `HY000`

Message: Rarm failed even after 30 seconds, can't continue without notify socket.
`ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED` was added in 8.0.4.
- Error number: `MY-011115`; Symbol: `ER_THREAD_POOL_BUFFER_TOO_SMALL`; SQLSTATE: `HY000`

Message: %s: %s buffer is too small
`ER_THREAD_POOL_BUFFER_TOO_SMALL` was added in 8.0.4.
- Error number: `MY-011116`; Symbol: `ER_MECA_B_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Mecab v%s is not supported, the lowest version supported is v%.
`ER_MECA_B_NOT_SUPPORTED` was added in 8.0.4.
- Error number: `MY-011117`; Symbol: `ER_MECA_B_NOT_VERIFIED`; SQLSTATE: `HY000`

Message: Mecab v%s is not verified, the highest version supported is v%.
`ER_MECA_B_NOT_VERIFIED` was added in 8.0.4.
- Error number: `MY-011118`; Symbol: `ER_MECA_B_CREATING_MODEL`; SQLSTATE: `HY000`

Message: Mecab: Trying createModel(%s).

`ER_MECAB_CREATING_MODEL` was added in 8.0.4.

- Error number: `MY-011119`; Symbol: `ER_MECAB_FAILED_TO_CREATE_MODEL`; SQLSTATE: `HY000`

Message: Mecab: createModel() failed: %s.

`ER_MECAB_FAILED_TO_CREATE_MODEL` was added in 8.0.4.

- Error number: `MY-011120`; Symbol: `ER_MECAB_FAILED_TO_CREATE_TRIGGER`; SQLSTATE: `HY000`

Message: Mecab: createTagger() failed: %s.

`ER_MECAB_FAILED_TO_CREATE_TRIGGER` was added in 8.0.4.

- Error number: `MY-011121`; Symbol: `ER_MECAB_UNSUPPORTED_CHARSET`; SQLSTATE: `HY000`

Message: Mecab: Unsupported dictionary charset %s.

`ER_MECAB_UNSUPPORTED_CHARSET` was added in 8.0.4.

- Error number: `MY-011122`; Symbol: `ER_MECAB_CHARSET_LOADED`; SQLSTATE: `HY000`

Message: Mecab: Loaded dictionary charset is %s.

`ER_MECAB_CHARSET_LOADED` was added in 8.0.4.

- Error number: `MY-011123`; Symbol: `ER_MECAB_PARSE_FAILED`; SQLSTATE: `HY000`

Message: Mecab: parse() failed: %s.

`ER_MECAB_PARSE_FAILED` was added in 8.0.4.

- Error number: `MY-011124`; Symbol: `ER_MECAB_OOM_WHILE_PARSING_TEXT`; SQLSTATE: `HY000`

Message: Mecab: parse() failed: out of memory.

`ER_MECAB_OOM_WHILE_PARSING_TEXT` was added in 8.0.4.

- Error number: `MY-011125`; Symbol: `ER_MECAB_CREATE_LATTICE_FAILED`; SQLSTATE: `HY000`

Message: Mecab: createLattice() failed: %s.

`ER_MECAB_CREATE_LATTICE_FAILED` was added in 8.0.4.

- Error number: `MY-011126`; Symbol: `ER_SEMISYNC_TRACE_ENTER_FUNC`; SQLSTATE: `HY000`

Message: ---> %s enter.

`ER_SEMISYNC_TRACE_ENTER_FUNC` was added in 8.0.4.

- Error number: `MY-011127`; Symbol: `ER_SEMISYNC_TRACE_EXIT_WITH_INT_EXIT_CODE`; SQLSTATE: `HY000`

Message: <--- %s exit (%d).

`ER_SEMISYNC_TRACE_EXIT_WITH_INT_EXIT_CODE` was added in 8.0.4.

-
- Error number: [MY-011128](#); Symbol: [ER_SEMISYNC_TRACE_EXIT_WITH_BOOL_EXIT_CODE](#); SQLSTATE: [HY000](#)

Message: <--- %s exit (%s).

[ER_SEMISYNC_TRACE_EXIT_WITH_BOOL_EXIT_CODE](#) was added in 8.0.4.
 - Error number: [MY-011129](#); Symbol: [ER_SEMISYNC_TRACE_EXIT](#); SQLSTATE: [HY000](#)

Message: <--- %s exit.

[ER_SEMISYNC_TRACE_EXIT](#) was added in 8.0.4.
 - Error number: [MY-011130](#); Symbol: [ER_SEMISYNC_RPL_INIT_FOR_TRX](#); SQLSTATE: [HY000](#)

Message: Semi-sync replication initialized for transactions.

[ER_SEMISYNC_RPL_INIT_FOR_TRX](#) was added in 8.0.4.
 - Error number: [MY-011131](#); Symbol: [ER_SEMISYNC_FAILED_TO_ALLOCATE_TRX_NODE](#); SQLSTATE: [HY000](#)

Message: %s: transaction node allocation failed for: (%s, %lu).

[ER_SEMISYNC_FAILED_TO_ALLOCATE_TRX_NODE](#) was added in 8.0.4.
 - Error number: [MY-011132](#); Symbol: [ER_SEMISYNC_BINLOG_WRITE_OUT_OF_ORDER](#); SQLSTATE: [HY000](#)

Message: %s: binlog write out-of-order, tail (%s, %lu), new node (%s, %lu).

[ER_SEMISYNC_BINLOG_WRITE_OUT_OF_ORDER](#) was added in 8.0.4.
 - Error number: [MY-011133](#); Symbol: [ER_SEMISYNC_INSERT_LOG_INFO_IN_ENTRY](#); SQLSTATE: [HY000](#)

Message: %s: insert (%s, %lu) in entry(%u).

[ER_SEMISYNC_INSERT_LOG_INFO_IN_ENTRY](#) was added in 8.0.4.
 - Error number: [MY-011134](#); Symbol: [ER_SEMISYNC_PROBE_LOG_INFO_IN_ENTRY](#); SQLSTATE: [HY000](#)

Message: %s: probe (%s, %lu) in entry(%u).

[ER_SEMISYNC_PROBE_LOG_INFO_IN_ENTRY](#) was added in 8.0.4.
 - Error number: [MY-011135](#); Symbol: [ER_SEMISYNC_CLEARED_ALL_ACTIVE_TRANSACTION_NODES](#); SQLSTATE: [HY000](#)

Message: %s: cleared all nodes.

[ER_SEMISYNC_CLEARED_ALL_ACTIVE_TRANSACTION_NODES](#) was added in 8.0.4.
 - Error number: [MY-011136](#); Symbol: [ER_SEMISYNC_CLEARED_ACTIVE_TRANSACTION_TILL_POS](#); SQLSTATE: [HY000](#)

Message: %s: cleared %d nodes back until pos (%s, %lu).

[ER_SEMISYNC_CLEARED_ACTIVE_TRANSACTION_TILL_POS](#) was added in 8.0.4.
 - Error number: [MY-011137](#); Symbol: [ER_SEMISYNC_REPLY_MAGIC_NO_ERROR](#); SQLSTATE: [HY000](#)

Message: Read semi-sync reply magic number error.

`ER_SEMISYNC_REPLY_MAGIC_NO_ERROR` was added in 8.0.4.

- Error number: `MY-011138`; Symbol: `ER_SEMISYNC_REPLY_PKT_LENGTH_TOO_SMALL`; SQLSTATE: `HY000`

Message: Read semi-sync reply length error: packet is too small.

`ER_SEMISYNC_REPLY_PKT_LENGTH_TOO_SMALL` was added in 8.0.4.

- Error number: `MY-011139`; Symbol: `ER_SEMISYNC_REPLY_BINLOG_FILE_TOO_LARGE`; SQLSTATE: `HY000`

Message: Read semi-sync reply binlog file length too large.

`ER_SEMISYNC_REPLY_BINLOG_FILE_TOO_LARGE` was added in 8.0.4.

- Error number: `MY-011140`; Symbol: `ER_SEMISYNC_SERVER_REPLY`; SQLSTATE: `HY000`

Message: %s: Got reply(%s, %lu) from server %u.

`ER_SEMISYNC_SERVER_REPLY` was added in 8.0.4.

- Error number: `MY-011141`; Symbol: `ER_SEMISYNC_FUNCTION_CALLED_TWICE`; SQLSTATE: `HY000`

Message: %s called twice.

`ER_SEMISYNC_FUNCTION_CALLED_TWICE` was added in 8.0.4.

- Error number: `MY-011142`; Symbol: `ER_SEMISYNC_RPL_ENABLED_ON_MASTER`; SQLSTATE: `HY000`

Message: Semi-sync replication enabled on the master.

`ER_SEMISYNC_RPL_ENABLED_ON_MASTER` was added in 8.0.4.

- Error number: `MY-011143`; Symbol: `ER_SEMISYNC_MASTER_OOM`; SQLSTATE: `HY000`

Message: Cannot allocate memory to enable semi-sync on the master.

`ER_SEMISYNC_MASTER_OOM` was added in 8.0.4.

- Error number: `MY-011144`; Symbol: `ER_SEMISYNC_DISABLED_ON_MASTER`; SQLSTATE: `HY000`

Message: Semi-sync replication disabled on the master.

`ER_SEMISYNC_DISABLED_ON_MASTER` was added in 8.0.4.

- Error number: `MY-011145`; Symbol: `ER_SEMISYNC_FORCED_SHUTDOWN`; SQLSTATE: `HY000`

Message: SEMISYNC: Forced shutdown. Some updates might not be replicated.

`ER_SEMISYNC_FORCED_SHUTDOWN` was added in 8.0.4.

- Error number: `MY-011146`; Symbol: `ER_SEMISYNC_MASTER_GOT_REPLY_AT_POS`; SQLSTATE: `HY000`

Message: %s: Got reply at (%s, %lu).

`ER_SEMISYNC_MASTER_GOT_REPLY_AT_POS` was added in 8.0.4.

- Error number: [MY-011147](#); Symbol: [ER_SEMISYNC_MASTER_SIGNAL_ALL_WAITING_THREADS](#); SQLSTATE: [HY000](#)

Message: %s: signal all waiting threads.
[ER_SEMISYNC_MASTER_SIGNAL_ALL_WAITING_THREADS](#) was added in 8.0.4.
- Error number: [MY-011148](#); Symbol: [ER_SEMISYNC_MASTER_TRX_WAIT_POS](#); SQLSTATE: [HY000](#)

Message: %s: wait pos (%s, %lu), repl(%d).
[ER_SEMISYNC_MASTER_TRX_WAIT_POS](#) was added in 8.0.4.
- Error number: [MY-011149](#); Symbol: [ER_SEMISYNC_BINLOG_REPLY_IS_AHEAD](#); SQLSTATE: [HY000](#)

Message: %s: Binlog reply is ahead (%s, %lu).
[ER_SEMISYNC_BINLOG_REPLY_IS_AHEAD](#) was added in 8.0.4.
- Error number: [MY-011150](#); Symbol: [ER_SEMISYNC_MOVE_BACK_WAIT_POS](#); SQLSTATE: [HY000](#)

Message: %s: move back wait position (%s, %lu).
[ER_SEMISYNC_MOVE_BACK_WAIT_POS](#) was added in 8.0.4.
- Error number: [MY-011151](#); Symbol: [ER_SEMISYNC_INIT_WAIT_POS](#); SQLSTATE: [HY000](#)

Message: %s: init wait position (%s, %lu).
[ER_SEMISYNC_INIT_WAIT_POS](#) was added in 8.0.4.
- Error number: [MY-011152](#); Symbol: [ER_SEMISYNC_WAIT_TIME_FOR_BINLOG_SENT](#); SQLSTATE: [HY000](#)

Message: %s: wait %lu ms for binlog sent (%s, %lu).
[ER_SEMISYNC_WAIT_TIME_FOR_BINLOG_SENT](#) was added in 8.0.4.
- Error number: [MY-011153](#); Symbol: [ER_SEMISYNC_WAIT_FOR_BINLOG_TIMEDOUT](#); SQLSTATE: [HY000](#)

Message: Timeout waiting for reply of binlog (file: %s, pos: %lu), semi-sync up to file %s, position %lu.
[ER_SEMISYNC_WAIT_FOR_BINLOG_TIMEDOUT](#) was added in 8.0.4.
- Error number: [MY-011154](#); Symbol: [ER_SEMISYNC_WAIT_TIME_ASSESSMENT_FOR_COMMIT_TRX_FAILED](#); SQLSTATE: [HY000](#)

Message: Assessment of waiting time for commitTrx failed at wait position (%s, %lu).
[ER_SEMISYNC_WAIT_TIME_ASSESSMENT_FOR_COMMIT_TRX_FAILED](#) was added in 8.0.4.
- Error number: [MY-011155](#); Symbol: [ER_SEMISYNC_RPL_SWITCHED_OFF](#); SQLSTATE: [HY000](#)

Message: Semi-sync replication switched OFF.
[ER_SEMISYNC_RPL_SWITCHED_OFF](#) was added in 8.0.4.
- Error number: [MY-011156](#); Symbol: [ER_SEMISYNC_RPL_SWITCHED_ON](#); SQLSTATE: [HY000](#)

Message: Semi-sync replication switched ON at (%s, %lu).

`ER_SEMISYNC_RPL_SWITCHED_ON` was added in 8.0.4.

- Error number: `MY-011157`; Symbol: `ER_SEMISYNC_NO_SPACE_IN_THE_PKT`; SQLSTATE: `HY000`

Message: No enough space in the packet for semi-sync extra header, semi-sync replication disabled.

`ER_SEMISYNC_NO_SPACE_IN_THE_PKT` was added in 8.0.4.

- Error number: `MY-011158`; Symbol: `ER_SEMISYNC_SYNC_HEADER_UPDATE_INFO`; SQLSTATE: `HY000`

Message: %s: server(%d), (%s, %lu) sync(%d), repl(%d).

`ER_SEMISYNC_SYNC_HEADER_UPDATE_INFO` was added in 8.0.4.

- Error number: `MY-011159`; Symbol: `ER_SEMISYNC_FAILED_TO_INSERT_TRX_NODE`; SQLSTATE: `HY000`

Message: Semi-sync failed to insert tranx_node for binlog file: %s, position: %lu.

`ER_SEMISYNC_FAILED_TO_INSERT_TRX_NODE` was added in 8.0.4.

- Error number: `MY-011160`; Symbol: `ER_SEMISYNC_TRX_SKIPPED_AT_POS`; SQLSTATE: `HY000`

Message: %s: Transaction skipped at (%s, %lu).

`ER_SEMISYNC_TRX_SKIPPED_AT_POS` was added in 8.0.4.

- Error number: `MY-011161`; Symbol: `ER_SEMISYNC_MASTER_FAILED_ON_NET_FLUSH`; SQLSTATE: `HY000`

Message: Semi-sync master failed on net_flush() before waiting for replica reply.

`ER_SEMISYNC_MASTER_FAILED_ON_NET_FLUSH` was added in 8.0.4.

- Error number: `MY-011162`; Symbol: `ER_SEMISYNC_RECEIVED_ACK_IS_SMALLER`; SQLSTATE: `HY000`

Message: The received ack is smaller than m_greatest_ack.

`ER_SEMISYNC_RECEIVED_ACK_IS_SMALLER` was added in 8.0.4.

- Error number: `MY-011163`; Symbol: `ER_SEMISYNC_ADD_ACK_TO_SLOT`; SQLSTATE: `HY000`

Message: Add the ack into slot %u.

`ER_SEMISYNC_ADD_ACK_TO_SLOT` was added in 8.0.4.

- Error number: `MY-011164`; Symbol: `ER_SEMISYNC_UPDATE_EXISTING_SLAVE_ACK`; SQLSTATE: `HY000`

Message: Update an existing ack in slot %u.

`ER_SEMISYNC_UPDATE_EXISTING_SLAVE_ACK` was added in 8.0.4.

- Error number: `MY-011165`; Symbol: `ER_SEMISYNC_FAILED_TO_START_ACK_RECEIVER_THD`; SQLSTATE: `HY000`

Message: Failed to start semi-sync ACK receiver thread, could not create thread(errno:%d).

`ER_SEMISYNC_FAILED_TO_START_ACK_RECEIVER_THD` was added in 8.0.4.

-
- Error number: [MY-011166](#); Symbol: [ER_SEMISYNC_STARTING_ACK_RECEIVER_THD](#); SQLSTATE: [HY000](#)

Message: Starting ack receiver thread.

[ER_SEMISYNC_STARTING_ACK_RECEIVER_THD](#) was added in 8.0.4.

- Error number: [MY-011167](#); Symbol: [ER_SEMISYNC_FAILED_TO_WAIT_ON_DUMP_SOCKET](#); SQLSTATE: [HY000](#)

Message: Failed to wait on semi-sync dump sockets, error: errno=%d.

[ER_SEMISYNC_FAILED_TO_WAIT_ON_DUMP_SOCKET](#) was added in 8.0.4.

- Error number: [MY-011168](#); Symbol: [ER_SEMISYNC_STOPPING_ACK_RECEIVER_THREAD](#); SQLSTATE: [HY000](#)

Message: Stopping ack receiver thread.

[ER_SEMISYNC_STOPPING_ACK_RECEIVER_THREAD](#) was added in 8.0.4.

- Error number: [MY-011169](#); Symbol: [ER_SEMISYNC_FAILED_REGISTER_SLAVE_TO_RECEIVER](#); SQLSTATE: [HY000](#)

Message: Failed to register slave to semi-sync ACK receiver thread.

[ER_SEMISYNC_FAILED_REGISTER_SLAVE_TO_RECEIVER](#) was added in 8.0.4.

- Error number: [MY-011170](#); Symbol: [ER_SEMISYNC_START_BINLOG_DUMP_TO_SLAVE](#); SQLSTATE: [HY000](#)

Message: Start %s binlog_dump to slave (server_id: %d), pos(%s, %lu).

[ER_SEMISYNC_START_BINLOG_DUMP_TO_SLAVE](#) was added in 8.0.4.

- Error number: [MY-011171](#); Symbol: [ER_SEMISYNC_STOP_BINLOG_DUMP_TO_SLAVE](#); SQLSTATE: [HY000](#)

Message: Stop %s binlog_dump to slave (server_id: %d).

[ER_SEMISYNC_STOP_BINLOG_DUMP_TO_SLAVE](#) was added in 8.0.4.

- Error number: [MY-011172](#); Symbol: [ER_SEMISYNC_UNREGISTER_TRX_OBSERVER_FAILED](#); SQLSTATE: [HY000](#)

Message: unregister_trans_observer failed.

[ER_SEMISYNC_UNREGISTER_TRX_OBSERVER_FAILED](#) was added in 8.0.4.

- Error number: [MY-011173](#); Symbol: [ER_SEMISYNC_UNREGISTER_BINLOG_STORAGE_OBSERVER_FAILED](#); SQLSTATE: [HY000](#)

Message: unregister_binlog_storage_observer failed.

[ER_SEMISYNC_UNREGISTER_BINLOG_STORAGE_OBSERVER_FAILED](#) was added in 8.0.4.

- Error number: [MY-011174](#); Symbol: [ER_SEMISYNC_UNREGISTER_BINLOG_TRANSMIT_OBSERVER_FAILED](#); SQLSTATE: [HY000](#)

Message: unregister_binlog_transmit_observer failed.

[ER_SEMISYNC_UNREGISTER_BINLOG_TRANSMIT_OBSERVER_FAILED](#) was added in 8.0.4.

- Error number: [MY-011175](#); Symbol: [ER_SEMISYNC_UNREGISTERED_REPLICATOR](#); SQLSTATE: [HY000](#)

Message: unregister_replicator OK.
[ER_SEMISYNC_UNREGISTERED_REPLICATOR](#) was added in 8.0.4.
- Error number: [MY-011176](#); Symbol: [ER_SEMISYNC_SOCKET_FD_TOO_LARGE](#); SQLSTATE: [HY000](#)

Message: Semisync slave socket fd is %u. select() cannot handle if the socket fd is bigger than %u (FD_SETSIZE).
[ER_SEMISYNC_SOCKET_FD_TOO_LARGE](#) was added in 8.0.4.
- Error number: [MY-011177](#); Symbol: [ER_SEMISYNC_SLAVE_REPLY](#); SQLSTATE: [HY000](#)

Message: %s: reply - %d.
[ER_SEMISYNC_SLAVE_REPLY](#) was added in 8.0.4.
- Error number: [MY-011178](#); Symbol: [ER_SEMISYNC_MISSING_MAGIC_NO_FOR_SEMISYNC_PKT](#); SQLSTATE: [HY000](#)

Message: Missing magic number for semi-sync packet, packet len: %lu.
[ER_SEMISYNC_MISSING_MAGIC_NO_FOR_SEMISYNC_PKT](#) was added in 8.0.4.
- Error number: [MY-011179](#); Symbol: [ER_SEMISYNC_SLAVE_START](#); SQLSTATE: [HY000](#)

Message: Slave I/O thread: Start %s replication to master '%s@%s:%d' in log '%s' at position %lu.
[ER_SEMISYNC_SLAVE_START](#) was added in 8.0.4.
- Error number: [MY-011180](#); Symbol: [ER_SEMISYNC_SLAVE_REPLY_WITH_BINLOG_INFO](#); SQLSTATE: [HY000](#)

Message: %s: reply (%s, %lu).
[ER_SEMISYNC_SLAVE_REPLY_WITH_BINLOG_INFO](#) was added in 8.0.4.
- Error number: [MY-011181](#); Symbol: [ER_SEMISYNC_SLAVE_NET_FLUSH_REPLY_FAILED](#); SQLSTATE: [HY000](#)

Message: Semi-sync slave net_flush() reply failed.
[ER_SEMISYNC_SLAVE_NET_FLUSH_REPLY_FAILED](#) was added in 8.0.4.
- Error number: [MY-011182](#); Symbol: [ER_SEMISYNC_SLAVE_SEND_REPLY_FAILED](#); SQLSTATE: [HY000](#)

Message: Semi-sync slave send reply failed: %s (%d).
[ER_SEMISYNC_SLAVE_SEND_REPLY_FAILED](#) was added in 8.0.4.
- Error number: [MY-011183](#); Symbol: [ER_SEMISYNC_EXECUTION_FAILED_ON_MASTER](#); SQLSTATE: [HY000](#)

Message: Execution failed on master: %s; error %d
[ER_SEMISYNC_EXECUTION_FAILED_ON_MASTER](#) was added in 8.0.4.
- Error number: [MY-011184](#); Symbol: [ER_SEMISYNC_NOT_SUPPORTED_BY_MASTER](#); SQLSTATE: [HY000](#)

Message: Master server does not support semi-sync, fallback to asynchronous replication

`ER_SEMISYNC_NOT_SUPPORTED_BY_MASTER` was added in 8.0.4.

- Error number: `MY-011185`; Symbol: `ER_SEMISYNC_SLAVE_SET_FAILED`; SQLSTATE: `HY000`

Message: Set 'rpl_semi_sync_replica=1' on master failed

`ER_SEMISYNC_SLAVE_SET_FAILED` was added in 8.0.4.

- Error number: `MY-011186`; Symbol: `ER_SEMISYNC_FAILED_TO_STOP_ACK_RECEIVER_THD`; SQLSTATE: `HY000`

Message: Failed to stop ack receiver thread on my_thread_join, errno(%d).

`ER_SEMISYNC_FAILED_TO_STOP_ACK_RECEIVER_THD` was added in 8.0.4.

- Error number: `MY-011187`; Symbol: `ER_FIREWALL_FAILED_TO_READ_FIREWALL_TABLES`; SQLSTATE: `HY000`

Message: Failed to read the firewall tables

`ER_FIREWALL_FAILED_TO_READ_FIREWALL_TABLES` was added in 8.0.4.

- Error number: `MY-011188`; Symbol: `ER_FIREWALL_FAILED_TO_REG_DYNAMIC_PRIVILEGES`; SQLSTATE: `HY000`

Message: Failed to register dynamic privileges

`ER_FIREWALL_FAILED_TO_REG_DYNAMIC_PRIVILEGES` was added in 8.0.4.

- Error number: `MY-011189`; Symbol: `ER_FIREWALL_RECORDING_STMT_WAS_TRUNCATED`; SQLSTATE: `HY000`

Message: Statement was truncated and not recorded: %s

`ER_FIREWALL_RECORDING_STMT_WAS_TRUNCATED` was added in 8.0.4.

- Error number: `MY-011190`; Symbol: `ER_FIREWALL_RECORDING_STMT_WITHOUT_TEXT`; SQLSTATE: `HY000`

Message: Statement with no text was not recorded

`ER_FIREWALL_RECORDING_STMT_WITHOUT_TEXT` was added in 8.0.4.

- Error number: `MY-011191`; Symbol: `ER_FIREWALL_SUSPICIOUS_STMT`; SQLSTATE: `HY000`

Message: SUSPICIOUS STATEMENT from '%s'. Reason: %s Statement: %s

`ER_FIREWALL_SUSPICIOUS_STMT` was added in 8.0.4.

- Error number: `MY-011192`; Symbol: `ER_FIREWALL_ACCESS_DENIED`; SQLSTATE: `HY000`

Message: ACCESS DENIED for '%s'. Reason: %s Statement: %s

`ER_FIREWALL_ACCESS_DENIED` was added in 8.0.4.

- Error number: `MY-011193`; Symbol: `ER_FIREWALL_SKIPPED_UNKNOWN_USER_MODE`; SQLSTATE: `HY000`

Message: Skipped unknown user mode '%s'

`ER_FIREWALL_SKIPPED_UNKNOWN_USER_MODE` was added in 8.0.4.

- Error number: [MY-011194](#); Symbol: [ER_FIREWALL_RELOADING_CACHE](#); SQLSTATE: [HY000](#)

Message: Reloading cache from disk

[ER_FIREWALL_RELOADING_CACHE](#) was added in 8.0.4.

- Error number: [MY-011195](#); Symbol: [ER_FIREWALL_RESET_FOR_USER](#); SQLSTATE: [HY000](#)

Message: FIREWALL RESET for '%s'

[ER_FIREWALL_RESET_FOR_USER](#) was added in 8.0.4.

- Error number: [MY-011196](#); Symbol: [ER_FIREWALL_STATUS_FLUSHED](#); SQLSTATE: [HY000](#)

Message: Counters are reset to zero

[ER_FIREWALL_STATUS_FLUSHED](#) was added in 8.0.4.

- Error number: [MY-011197](#); Symbol: [ER_KEYRING_LOGGER_ERROR_MSG](#); SQLSTATE: [HY000](#)

Message: %s

[ER_KEYRING_LOGGER_ERROR_MSG](#) was added in 8.0.4.

- Error number: [MY-011198](#); Symbol: [ER_AUDIT_LOG_FILTER_IS_NOT_INSTALLED](#); SQLSTATE: [HY000](#)

Message: Audit Log plugin supports a filtering, which has not been installed yet. Audit Log plugin will run in the legacy mode, which will be disabled in the next release.

[ER_AUDIT_LOG_FILTER_IS_NOT_INSTALLED](#) was added in 8.0.4.

- Error number: [MY-011199](#); Symbol: [ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST](#); SQLSTATE: [HY000](#)

Message: Previously exclude list is used, now we start using include list, exclude list is set to NULL.

[ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST](#) was added in 8.0.4.

- Error number: [MY-011200](#); Symbol: [ER_AUDIT_LOG_CANNOT_SET_LOG_POLICY_WITH_OTHER_POLICIES](#); SQLSTATE: [HY000](#)

Message: Cannot set audit_log_policy simultaneously with either audit_log_connection_policy or audit_log_statement_policy, setting audit_log_connection_policy and audit_log_statement_policy based on audit_log_policy.

[ER_AUDIT_LOG_CANNOT_SET_LOG_POLICY_WITH_OTHER_POLICIES](#) was added in 8.0.4.

- Error number: [MY-011201](#); Symbol: [ER_AUDIT_LOG_ONLY_INCLUDE_LIST_USED](#); SQLSTATE: [HY000](#)

Message: Both include and exclude lists provided, include list is preferred, exclude list is set to NULL.

[ER_AUDIT_LOG_ONLY_INCLUDE_LIST_USED](#) was added in 8.0.4.

- Error number: [MY-011202](#); Symbol: [ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIR](#); SQLSTATE: [HY000](#)

Message: Could not access '%s' directory.

[ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIR](#) was added in 8.0.4.

-
- Error number: `MY-011203`; Symbol: `ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED`; SQLSTATE: `HY000`

Message: Could not rename file from '%s' to '%s'.
`ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED` was added in 8.0.4.
 - Error number: `MY-011204`; Symbol: `ER_AUDIT_LOG_WRITER_DEST_FILE_ALREADY_EXISTS`; SQLSTATE: `HY000`

Message: File '%s' should not exist. It may be incomplete. The server crashed.
`ER_AUDIT_LOG_WRITER_DEST_FILE_ALREADY_EXISTS` was added in 8.0.4.
 - Error number: `MY-011205`; Symbol: `ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED_REMOVE_FILE_MANUALLY`; SQLSTATE: `HY000`

Message: Could not rename file from '%s' to '%s'. Remove the file manually.
`ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED_REMOVE_FILE_MANUALLY` was added in 8.0.4.
 - Error number: `MY-011206`; Symbol: `ER_AUDIT_LOG_WRITER_INCOMPLETE_FILE_RENAMED`; SQLSTATE: `HY000`

Message: Incomplete file renamed from '%s' to '%s'.
`ER_AUDIT_LOG_WRITER_INCOMPLETE_FILE_RENAMED` was added in 8.0.4.
 - Error number: `MY-011207`; Symbol: `ER_AUDIT_LOG_WRITER_FAILED_TO_WRITE_TO_FILE`; SQLSTATE: `HY000`

Message: Error writing file '\%s' (errno: %d - %s).
`ER_AUDIT_LOG_WRITER_FAILED_TO_WRITE_TO_FILE` was added in 8.0.4.
 - Error number: `MY-011208`; Symbol: `ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_ENCRYPTION`; SQLSTATE: `HY000`

Message: Could not initialize audit log file encryption.
`ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_ENCRYPTION` was added in 8.0.4.
 - Error number: `MY-011209`; Symbol: `ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_COMPRESSION`; SQLSTATE: `HY000`

Message: Could not initialize audit log file compression.
`ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_COMPRESSION` was added in 8.0.4.
 - Error number: `MY-011210`; Symbol: `ER_AUDIT_LOG_EC_WRITER_FAILED_TO_CREATE_FILE`; SQLSTATE: `HY000`

Message: Could not create '%s' file for audit logging.
`ER_AUDIT_LOG_EC_WRITER_FAILED_TO_CREATE_FILE` was added in 8.0.4.
 - Error number: `MY-011211`; Symbol: `ER_AUDIT_LOG_RENAME_LOG_FILE_BEFORE_FLUSH`; SQLSTATE: `HY000`

Message: Audit log file (%s) must be manually renamed before audit_log_flush is set to true.
`ER_AUDIT_LOG_RENAME_LOG_FILE_BEFORE_FLUSH` was added in 8.0.4.

-
- Error number: [MY-011212](#); Symbol: [ER_AUDIT_LOG_FILTER_RESULT_MSG](#); SQLSTATE: [HY000](#)

Message: %s

[ER_AUDIT_LOG_FILTER_RESULT_MSG](#) was added in 8.0.4.

- Error number: [MY-011213](#); Symbol: [ER_AUDIT_LOG_JSON_READER_FAILED_TO_PARSE](#); SQLSTATE: [HY000](#)

Message: Error parsing JSON event. Event not accessible.

[ER_AUDIT_LOG_JSON_READER_FAILED_TO_PARSE](#) was added in 8.0.4.

- Error number: [MY-011214](#); Symbol: [ER_AUDIT_LOG_JSON_READER_BUF_TOO_SMALL](#); SQLSTATE: [HY000](#)

Message: Buffer is too small to hold JSON event. Number of events skipped: %zu.

[ER_AUDIT_LOG_JSON_READER_BUF_TOO_SMALL](#) was added in 8.0.4.

- Error number: [MY-011215](#); Symbol: [ER_AUDIT_LOG_JSON_READER_FAILED_TO_OPEN_FILE](#); SQLSTATE: [HY000](#)

Message: Could not open JSON file for reading. Reading next file if exists.

[ER_AUDIT_LOG_JSON_READER_FAILED_TO_OPEN_FILE](#) was added in 8.0.4.

- Error number: [MY-011216](#); Symbol: [ER_AUDIT_LOG_JSON_READER_FILE_PARSING_ERROR](#); SQLSTATE: [HY000](#)

Message: JSON file parsing error. Reading next file if exists

[ER_AUDIT_LOG_JSON_READER_FILE_PARSING_ERROR](#) was added in 8.0.4.

- Error number: [MY-011217](#); Symbol: [ER_AUDIT_LOG_FILTER_INVALID_COLUMN_COUNT](#); SQLSTATE: [HY000](#)

Message: Invalid column count in the '%s.%s' table.

[ER_AUDIT_LOG_FILTER_INVALID_COLUMN_COUNT](#) was added in 8.0.4, removed after 8.0.25.

- Error number: [MY-011218](#); Symbol: [ER_AUDIT_LOG_FILTER_INVALID_COLUMN_DEFINITION](#); SQLSTATE: [HY000](#)

Message: Invalid column definition of the '%s.%s' table.

[ER_AUDIT_LOG_FILTER_INVALID_COLUMN_DEFINITION](#) was added in 8.0.4, removed after 8.0.25.

- Error number: [MY-011219](#); Symbol: [ER_AUDIT_LOG_FILTER_FAILED_TO_STORE_TABLE_FLDS](#); SQLSTATE: [HY000](#)

Message: Could not store field of the %s table.

[ER_AUDIT_LOG_FILTER_FAILED_TO_STORE_TABLE_FLDS](#) was added in 8.0.4.

- Error number: [MY-011220](#); Symbol: [ER_AUDIT_LOG_FILTER_FAILED_TO_UPDATE_TABLE](#); SQLSTATE: [HY000](#)

Message: Could not update %s table.

[ER_AUDIT_LOG_FILTER_FAILED_TO_UPDATE_TABLE](#) was added in 8.0.4.

- Error number: `MY-011221`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_INSERT_INTO_TABLE`; SQLSTATE: `HY000`

Message: Could not insert into %s table.
`ER_AUDIT_LOG_FILTER_FAILED_TO_INSERT_INTO_TABLE` was added in 8.0.4.
- Error number: `MY-011222`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_DELETE_FROM_TABLE`; SQLSTATE: `HY000`

Message: Could not delete from %s table.
`ER_AUDIT_LOG_FILTER_FAILED_TO_DELETE_FROM_TABLE` was added in 8.0.4.
- Error number: `MY-011223`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_INIT_TABLE_FOR_READ`; SQLSTATE: `HY000`

Message: Could not initialize %s table for reading.
`ER_AUDIT_LOG_FILTER_FAILED_TO_INIT_TABLE_FOR_READ` was added in 8.0.4.
- Error number: `MY-011224`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_READ_TABLE`; SQLSTATE: `HY000`

Message: Could not read %s table.
`ER_AUDIT_LOG_FILTER_FAILED_TO_READ_TABLE` was added in 8.0.4.
- Error number: `MY-011225`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_CLOSE_TABLE_AFTER_READING`; SQLSTATE: `HY000`

Message: Could not close %s table reading.
`ER_AUDIT_LOG_FILTER_FAILED_TO_CLOSE_TABLE_AFTER_READING` was added in 8.0.4.
- Error number: `MY-011226`; Symbol: `ER_AUDIT_LOG_FILTER_USER_AND_HOST_CANNOT_BE_EMPTY`; SQLSTATE: `HY000`

Message: Both user and host columns of %s table cannot be empty.
`ER_AUDIT_LOG_FILTER_USER_AND_HOST_CANNOT_BE_EMPTY` was added in 8.0.4.
- Error number: `MY-011227`; Symbol: `ER_AUDIT_LOG_FILTER_FLD_FILTERNAME_CANNOT_BE_EMPTY`; SQLSTATE: `HY000`

Message: Filtername column of %s table cannot be empty.
`ER_AUDIT_LOG_FILTER_FLD_FILTERNAME_CANNOT_BE_EMPTY` was added in 8.0.4.
- Error number: `MY-011228`; Symbol: `ER_VALIDATE_PWD_DICT_FILE_NOT_SPECIFIED`; SQLSTATE: `HY000`

Message: Dictionary file not specified
`ER_VALIDATE_PWD_DICT_FILE_NOT_SPECIFIED` was added in 8.0.4.
- Error number: `MY-011229`; Symbol: `ER_VALIDATE_PWD_DICT_FILE_NOT_LOADED`; SQLSTATE: `HY000`

Message: Dictionary file not loaded
`ER_VALIDATE_PWD_DICT_FILE_NOT_LOADED` was added in 8.0.4.

-
- Error number: [MY-011230](#); Symbol: [ER_VALIDATE_PWD_DICT_FILE_TOO_BIG](#); SQLSTATE: [HY000](#)

Message: Dictionary file size exceeded MAX_DICTIONARY_FILE_LENGTH, not loaded

[ER_VALIDATE_PWD_DICT_FILE_TOO_BIG](#) was added in 8.0.4.

- Error number: [MY-011231](#); Symbol: [ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE](#); SQLSTATE: [HY000](#)

Message: Exception while reading the dictionary file

[ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE](#) was added in 8.0.4.

- Error number: [MY-011232](#); Symbol: [ER_VALIDATE_PWD_FAILED_TO_GET_FLD_FROM_SECURITY_CTX](#); SQLSTATE: [HY000](#)

Message: Can't retrieve the %s from the security context

[ER_VALIDATE_PWD_FAILED_TO_GET_FLD_FROM_SECURITY_CTX](#) was added in 8.0.4.

- Error number: [MY-011233](#); Symbol: [ER_VALIDATE_PWD_FAILED_TO_GET_SECURITY_CTX](#); SQLSTATE: [HY000](#)

Message: Can't retrieve the security context

[ER_VALIDATE_PWD_FAILED_TO_GET_SECURITY_CTX](#) was added in 8.0.4.

- Error number: [MY-011234](#); Symbol: [ER_VALIDATE_PWD_LENGTH_CHANGED](#); SQLSTATE: [HY000](#)

Message: Effective value of validate_password_length is changed. New value is %d

[ER_VALIDATE_PWD_LENGTH_CHANGED](#) was added in 8.0.4.

- Error number: [MY-011235](#); Symbol: [ER_REWRITER_QUERY_ERROR_MSG](#); SQLSTATE: [HY000](#)

Message: %s

[ER_REWRITER_QUERY_ERROR_MSG](#) was added in 8.0.4.

- Error number: [MY-011236](#); Symbol: [ER_REWRITER_QUERY_FAILED](#); SQLSTATE: [HY000](#)

Message: Rewritten query failed to parse:%s

[ER_REWRITER_QUERY_FAILED](#) was added in 8.0.4.

- Error number: [MY-011237](#); Symbol: [ER_XPLUGIN_STARTUP_FAILED](#); SQLSTATE: [HY000](#)

Message: Startup failed with error "%s"

[ER_XPLUGIN_STARTUP_FAILED](#) was added in 8.0.4.

- Error number: [MY-011238](#); Symbol: [ER_XPLUGIN_SERVER_EXITING](#); SQLSTATE: [HY000](#)

Message: Exiting

[ER_XPLUGIN_SERVER_EXITING](#) was added in 8.0.4, removed after 8.0.12.

- Error number: [MY-011239](#); Symbol: [ER_XPLUGIN_SERVER_EXITED](#); SQLSTATE: [HY000](#)

Message: Exit done

[ER_XPLUGIN_SERVER_EXITED](#) was added in 8.0.4, removed after 8.0.12.

-
- Error number: `MY-011240`; Symbol: `ER_XPLUGIN_USING_SSL_CONF_FROM_SERVER`; SQLSTATE: `HY000`

Message: Using SSL configuration from MySQL Server

`ER_XPLUGIN_USING_SSL_CONF_FROM_SERVER` was added in 8.0.4.

- Error number: `MY-011241`; Symbol: `ER_XPLUGIN_USING_SSL_CONF_FROM_MYSQLX`; SQLSTATE: `HY000`

Message: Using SSL configuration from Mysqlx Plugin

`ER_XPLUGIN_USING_SSL_CONF_FROM_MYSQLX` was added in 8.0.4.

- Error number: `MY-011242`; Symbol: `ER_XPLUGIN_FAILED_TO_USE_SSL_CONF`; SQLSTATE: `HY000`

Message: Neither MySQL Server nor Mysqlx Plugin has valid SSL configuration

`ER_XPLUGIN_FAILED_TO_USE_SSL_CONF` was added in 8.0.4.

- Error number: `MY-011243`; Symbol: `ER_XPLUGIN_USING_SSL_FOR_TLS_CONNECTION`; SQLSTATE: `HY000`

Message: Using %s for TLS connections

`ER_XPLUGIN_USING_SSL_FOR_TLS_CONNECTION` was added in 8.0.4.

- Error number: `MY-011244`; Symbol: `ER_XPLUGIN_REFERENCE_TO_SECURE_CONN_WITH_XPLUGIN`; SQLSTATE: `HY000`

Message: For more information, please see the Using Secure Connections with X Plugin section in the MySQL documentation

`ER_XPLUGIN_REFERENCE_TO_SECURE_CONN_WITH_XPLUGIN` was added in 8.0.4.

- Error number: `MY-011245`; Symbol: `ER_XPLUGIN_ERROR_MSG`; SQLSTATE: `HY000`

Message: %s

`ER_XPLUGIN_ERROR_MSG` was added in 8.0.4.

- Error number: `MY-011246`; Symbol: `ER_SHA_PWD_FAILED_TO_PARSE_AUTH_STRING`; SQLSTATE: `HY000`

Message: Failed to parse stored authentication string for %s. Please check if mysql.user table not corrupted

`ER_SHA_PWD_FAILED_TO_PARSE_AUTH_STRING` was added in 8.0.4.

- Error number: `MY-011247`; Symbol: `ER_SHA_PWD_FAILED_TO_GENERATE_MULTI_ROUND_HASH`; SQLSTATE: `HY000`

Message: Error in generating multi-round hash for %s. Plugin can not perform authentication without it. This may be a transient problem

`ER_SHA_PWD_FAILED_TO_GENERATE_MULTI_ROUND_HASH` was added in 8.0.4.

- Error number: [MY-011248](#); Symbol: [ER_SHA_PWD_AUTH_REQUIRE_RSA_OR_SSL](#); SQLSTATE: [HY000](#)

Message: Authentication requires either RSA keys or SSL encryption
[ER_SHA_PWD_AUTH_REQUIRE_RSA_OR_SSL](#) was added in 8.0.4.
- Error number: [MY-011249](#); Symbol: [ER_SHA_PWD_RSA_KEY_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: RSA key cipher length of %u is too long. Max value is %u
[ER_SHA_PWD_RSA_KEY_TOO_LONG](#) was added in 8.0.4.
- Error number: [MY-011250](#); Symbol: [ER_PLUGIN_COMMON_FAILED_TO_OPEN_FILTER_TABLES](#); SQLSTATE: [HY000](#)

Message: Failed to open the %s filter tables
[ER_PLUGIN_COMMON_FAILED_TO_OPEN_FILTER_TABLES](#) was added in 8.0.4.
- Error number: [MY-011251](#); Symbol: [ER_PLUGIN_COMMON_FAILED_TO_OPEN_TABLE](#); SQLSTATE: [HY000](#)

Message: Failed to open '%s.%s' %s table
[ER_PLUGIN_COMMON_FAILED_TO_OPEN_TABLE](#) was added in 8.0.4.
- Error number: [MY-011252](#); Symbol: [ER_AUTH_LDAP_ERROR_LOGGER_ERROR_MSG](#); SQLSTATE: [HY000](#)

Message: %s
[ER_AUTH_LDAP_ERROR_LOGGER_ERROR_MSG](#) was added in 8.0.4.
- Error number: [MY-011253](#); Symbol: [ER_CONN_CONTROL_ERROR_MSG](#); SQLSTATE: [HY000](#)

Message: %s
[ER_CONN_CONTROL_ERROR_MSG](#) was added in 8.0.4.
- Error number: [MY-011254](#); Symbol: [ER_GRP_RPL_ERROR_MSG](#); SQLSTATE: [HY000](#)

Message: %s
[ER_GRP_RPL_ERROR_MSG](#) was added in 8.0.4.
- Error number: [MY-011255](#); Symbol: [ER_SHA_PWD_SALT_FOR_USER_CORRUPT](#); SQLSTATE: [HY000](#)

Message: Password salt for user '%s' is corrupt
[ER_SHA_PWD_SALT_FOR_USER_CORRUPT](#) was added in 8.0.4.
- Error number: [MY-011256](#); Symbol: [ER_SYS_VAR_COMPONENT_OOM](#); SQLSTATE: [HY000](#)

Message: Out of memory for component system variable '%s'.
[ER_SYS_VAR_COMPONENT_OOM](#) was added in 8.0.4.
- Error number: [MY-011257](#); Symbol: [ER_SYS_VAR_COMPONENT_VARIABLE_SET_READ_ONLY](#); SQLSTATE: [HY000](#)

Message: variable %s of component %s was forced to be read-only: string variable without update_func and PLUGIN_VAR_MEMALLOC flag.

`ER_SYS_VAR_COMPONENT_VARIABLE_SET_READ_ONLY` was added in 8.0.4.

- Error number: `MY-011258`; Symbol: `ER_SYS_VAR_COMPONENT_UNKNOWN_VARIABLE_TYPE`; SQLSTATE: `HY000`

Message: Unknown variable type code 0x%x in component '%s'.

`ER_SYS_VAR_COMPONENT_UNKNOWN_VARIABLE_TYPE` was added in 8.0.4.

- Error number: `MY-011259`; Symbol: `ER_SYS_VAR_COMPONENT_FAILED_TO_PARSE_VARIABLE_OPTIONS`; SQLSTATE: `HY000`

Message: Parsing options for variable '%s' failed.

`ER_SYS_VAR_COMPONENT_FAILED_TO_PARSE_VARIABLE_OPTIONS` was added in 8.0.4.

- Error number: `MY-011260`; Symbol: `ER_SYS_VAR_COMPONENT_FAILED_TO_MAKE_VARIABLE_PERSISTENT`; SQLSTATE: `HY000`

Message: Setting persistent options for component variable '%s' failed.

`ER_SYS_VAR_COMPONENT_FAILED_TO_MAKE_VARIABLE_PERSISTENT` was added in 8.0.4.

- Error number: `MY-011261`; Symbol: `ER_COMPONENT_FILTER_CONFUSED`; SQLSTATE: `HY000`

Message: The log-filter component "%s" got confused at "%s" (state: %s) ...

`ER_COMPONENT_FILTER_CONFUSED` was added in 8.0.4.

- Error number: `MY-011262`; Symbol: `ER_STOP_SLAVE_IO_THREAD_DISK_SPACE`; SQLSTATE: `HY000`

Message: Waiting until I/O thread for channel '%s' finish writing to disk before stopping. Free some disk space or use 'KILL' to abort I/O thread operation. Notice that aborting the I/O thread while rotating the relay log might corrupt the relay logs, requiring a server restart to fix it.

`ER_STOP_SLAVE_IO_THREAD_DISK_SPACE` was added in 8.0.2.

- Error number: `MY-011263`; Symbol: `ER_LOG_FILE_CANNOT_OPEN`; SQLSTATE: `HY000`

Message: Could not use %s for logging (error %d - %s). Turning logging off for the server process. To turn it on again: fix the cause, then %s restart the MySQL server.

`ER_LOG_FILE_CANNOT_OPEN` was added in 8.0.2.

- Error number: `MY-011268`; Symbol: `ER_PERSIST_OPTION_STATUS`; SQLSTATE: `HY000`

Message: Configuring persisted options failed: "%s".

`ER_PERSIST_OPTION_STATUS` was added in 8.0.11.

- Error number: `MY-011269`; Symbol: `ER_NOT_IMPLEMENTED_GET_TABLESPACE_STATISTICS`; SQLSTATE: `HY000`

Message: The storage engine '%s' does not provide dynamic table statistics

`ER_NOT_IMPLEMENTED_GET_TABLESPACE_STATISTICS` was added in 8.0.11.

- Error number: `MY-011272`; Symbol: `ER_SSL_FIPS_MODE_ERROR`; SQLSTATE: `HY000`

Message: SSL fips mode error: %s

`ER_SSL_FIPS_MODE_ERROR` was added in 8.0.11.

- Error number: [MY-011273](#); Symbol: [ER_CONN_INIT_CONNECT_IGNORED](#); SQLSTATE: [HY000](#)

Message: init_connect variable is ignored for user: %s host: %s due to expired password.
[ER_CONN_INIT_CONNECT_IGNORED](#) was added in 8.0.11.
- Error number: [MY-011275](#); Symbol: [ER_REWRITER_OOM](#); SQLSTATE: [HY000](#)

Message: Out of memory.
[ER_REWRITER_OOM](#) was added in 8.0.11.
- Error number: [MY-011276](#); Symbol: [ER_REWRITER_TABLE_MALFORMED_ERROR](#); SQLSTATE: [HY000](#)

Message: Wrong column count or names when loading rules.
[ER_REWRITER_TABLE_MALFORMED_ERROR](#) was added in 8.0.11.
- Error number: [MY-011277](#); Symbol: [ER_REWRITER_LOAD_FAILED](#); SQLSTATE: [HY000](#)

Message: Some rules failed to load.
[ER_REWRITER_LOAD_FAILED](#) was added in 8.0.11.
- Error number: [MY-011278](#); Symbol: [ER_REWRITER_READ_FAILED](#); SQLSTATE: [HY000](#)

Message: Got error from storage engine while refreshing rewrite rules.
[ER_REWRITER_READ_FAILED](#) was added in 8.0.11.
- Error number: [MY-011279](#); Symbol: [ER_CONN_CONTROL_EVENT_COORDINATOR_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to initialize Connection_event_coordinator
[ER_CONN_CONTROL_EVENT_COORDINATOR_INIT_FAILED](#) was added in 8.0.11.
- Error number: [MY-011280](#); Symbol: [ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_UPDATE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to update connection delay triggered stats
[ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_UPDATE_FAILED](#) was added in 8.0.11.
- Error number: [MY-011281](#); Symbol: [ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_RESET_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to reset connection delay triggered stats
[ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_RESET_FAILED](#) was added in 8.0.11.
- Error number: [MY-011282](#); Symbol: [ER_CONN_CONTROL_INVALID_CONN_DELAY_TYPE](#); SQLSTATE: [HY000](#)

Message: Unexpected option type for connection delay.
[ER_CONN_CONTROL_INVALID_CONN_DELAY_TYPE](#) was added in 8.0.11.
- Error number: [MY-011283](#); Symbol: [ER_CONN_CONTROL_DELAY_ACTION_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to initialize Connection_delay_action

`ER_CONN_CONTROL_DELAY_ACTION_INIT_FAILED` was added in 8.0.11.

- Error number: `MY-011284`; Symbol: `ER_CONN_CONTROL_FAILED_TO_SET_CONN_DELAY`; SQLSTATE: `HY000`

Message: Could not set %s delay for connection delay.

`ER_CONN_CONTROL_FAILED_TO_SET_CONN_DELAY` was added in 8.0.11.

- Error number: `MY-011285`; Symbol: `ER_CONN_CONTROL_FAILED_TO_UPDATE_CONN_DELAY_HASH`; SQLSTATE: `HY000`

Message: Failed to update connection delay hash for account : %s

`ER_CONN_CONTROL_FAILED_TO_UPDATE_CONN_DELAY_HASH` was added in 8.0.11.

- Error number: `MY-011286`; Symbol: `ER_XPLUGIN_FORCE_STOP_CLIENT`; SQLSTATE: `HY000`

Message: %s: Force stopping client because exception occurred: %s

`ER_XPLUGIN_FORCE_STOP_CLIENT` was added in 8.0.11.

- Error number: `MY-011287`; Symbol: `ER_XPLUGIN_MAX_AUTH_ATTEMPTS_REACHED`; SQLSTATE: `HY000`

Message: %s.%u: Maximum number of authentication attempts reached, login failed.

`ER_XPLUGIN_MAX_AUTH_ATTEMPTS_REACHED` was added in 8.0.11.

- Error number: `MY-011288`; Symbol: `ER_XPLUGIN_BUFFER_PAGE_ALLOC_FAILED`; SQLSTATE: `HY000`

Message: Error allocating Buffer_page: %s

`ER_XPLUGIN_BUFFER_PAGE_ALLOC_FAILED` was added in 8.0.11.

- Error number: `MY-011289`; Symbol: `ER_XPLUGIN_DETECTED_HANGING_CLIENTS`; SQLSTATE: `HY000`

Message: Detected %u hanging client(s)

`ER_XPLUGIN_DETECTED_HANGING_CLIENTS` was added in 8.0.11.

- Error number: `MY-011290`; Symbol: `ER_XPLUGIN_FAILED_TO_ACCEPT_CLIENT`; SQLSTATE: `HY000`

Message: Error accepting client

`ER_XPLUGIN_FAILED_TO_ACCEPT_CLIENT` was added in 8.0.11.

- Error number: `MY-011291`; Symbol: `ER_XPLUGIN_FAILED_TO_SCHEDULE_CLIENT`; SQLSTATE: `HY000`

Message: Internal error scheduling client for execution

`ER_XPLUGIN_FAILED_TO_SCHEDULE_CLIENT` was added in 8.0.11.

- Error number: `MY-011292`; Symbol: `ER_XPLUGIN_FAILED_TO_PREPARE_IO_INTERFACES`; SQLSTATE: `HY000`

Message: Preparation of I/O interfaces failed, X Protocol won't be accessible

`ER_XPLUGIN_FAILED_TO_PREPARE_IO_INTERFACES` was added in 8.0.11.

-
- Error number: [MY-011293](#); Symbol: [ER_XPLUGIN_SRV_SESSION_INIT_THREAD_FAILED](#); SQLSTATE: [HY000](#)

Message: srv_session_init_thread returned error

[ER_XPLUGIN_SRV_SESSION_INIT_THREAD_FAILED](#) was added in 8.0.11.

- Error number: [MY-011294](#); Symbol: [ER_XPLUGIN_UNABLE_TO_USE_USER_SESSION_ACCOUNT](#); SQLSTATE: [HY000](#)

Message: Unable to use user mysql.session account when connecting the server for internal plugin requests.

[ER_XPLUGIN_UNABLE_TO_USE_USER_SESSION_ACCOUNT](#) was added in 8.0.11.

- Error number: [MY-011295](#); Symbol: [ER_XPLUGIN_REFERENCE_TO_USER_ACCOUNT_DOC_SECTION](#); SQLSTATE: [HY000](#)

Message: For more information, please see the X Plugin User Account section in the MySQL documentation

[ER_XPLUGIN_REFERENCE_TO_USER_ACCOUNT_DOC_SECTION](#) was added in 8.0.11.

- Error number: [MY-011296](#); Symbol: [ER_XPLUGIN_UNEXPECTED_EXCEPTION_DISPATCHING_CMD](#); SQLSTATE: [HY000](#)

Message: %s: Unexpected exception dispatching command: %s

[ER_XPLUGIN_UNEXPECTED_EXCEPTION_DISPATCHING_CMD](#) was added in 8.0.11.

- Error number: [MY-011297](#); Symbol: [ER_XPLUGIN_EXCEPTION_IN_TASK_SCHEDULER](#); SQLSTATE: [HY000](#)

Message: Exception in post: %s

[ER_XPLUGIN_EXCEPTION_IN_TASK_SCHEDULER](#) was added in 8.0.11.

- Error number: [MY-011298](#); Symbol: [ER_XPLUGIN_TASK_SCHEDULING_FAILED](#); SQLSTATE: [HY000](#)

Message: Internal error scheduling task

[ER_XPLUGIN_TASK_SCHEDULING_FAILED](#) was added in 8.0.11.

- Error number: [MY-011299](#); Symbol: [ER_XPLUGIN_EXCEPTION_IN_EVENT_LOOP](#); SQLSTATE: [HY000](#)

Message: Exception in event loop: "%s": %s

[ER_XPLUGIN_EXCEPTION_IN_EVENT_LOOP](#) was added in 8.0.11.

- Error number: [MY-011300](#); Symbol: [ER_XPLUGIN_LISTENER_SETUP_FAILED](#); SQLSTATE: [HY000](#)

Message: Setup of %s failed, %s

[ER_XPLUGIN_LISTENER_SETUP_FAILED](#) was added in 8.0.11.

- Error number: [MY-011301](#); Symbol: [ER_XPLUING_NET_STARTUP_FAILED](#); SQLSTATE: [HY000](#)

Message: %s

[ER_XPLUING_NET_STARTUP_FAILED](#) was added in 8.0.11.

-
- Error number: [MY-011302](#); Symbol: [ER_XPLUGIN_FAILED_AT_SSL_CONF](#); SQLSTATE: [HY000](#)
Message: Failed at SSL configuration: "%s"
[ER_XPLUGIN_FAILED_AT_SSL_CONF](#) was added in 8.0.11.
 - Error number: [MY-011303](#); Symbol: [ER_XPLUGIN_CLIENT_SSL_HANDSHAKE_FAILED](#); SQLSTATE: [HY000](#)
Message: Error during SSL handshake for client connection (%i)
[ER_XPLUGIN_CLIENT_SSL_HANDSHAKE_FAILED](#) was added in 8.0.11, removed after 8.0.12.
 - Error number: [MY-011304](#); Symbol: [ER_XPLUGIN_SSL_HANDSHAKE_WITH_SERVER_FAILED](#); SQLSTATE: [HY000](#)
Message: %s: Error during SSL handshake
[ER_XPLUGIN_SSL_HANDSHAKE_WITH_SERVER_FAILED](#) was added in 8.0.11, removed after 8.0.12.
 - Error number: [MY-011305](#); Symbol: [ER_XPLUGIN_FAILED_TO_CREATE_SESSION_FOR_CONN](#); SQLSTATE: [HY000](#)
Message: %s: Error creating session for connection from %s
[ER_XPLUGIN_FAILED_TO_CREATE_SESSION_FOR_CONN](#) was added in 8.0.11.
 - Error number: [MY-011306](#); Symbol: [ER_XPLUGIN_FAILED_TO_INITIALIZE_SESSION](#); SQLSTATE: [HY000](#)
Message: %s: Error initializing session for connection: %s
[ER_XPLUGIN_FAILED_TO_INITIALIZE_SESSION](#) was added in 8.0.11.
 - Error number: [MY-011307](#); Symbol: [ER_XPLUGIN_MESSAGE_TOO_LONG](#); SQLSTATE: [HY000](#)
Message: %s: Message of size %u received, exceeding the limit of %i
[ER_XPLUGIN_MESSAGE_TOO_LONG](#) was added in 8.0.11.
 - Error number: [MY-011308](#); Symbol: [ER_XPLUGIN_UNINITIALIZED_MESSAGE](#); SQLSTATE: [HY000](#)
Message: Message is not properly initialized: %s
[ER_XPLUGIN_UNINITIALIZED_MESSAGE](#) was added in 8.0.11.
 - Error number: [MY-011309](#); Symbol: [ER_XPLUGIN_FAILED_TO_SET_MIN_NUMBER_OF_WORKERS](#); SQLSTATE: [HY000](#)
Message: Unable to set minimal number of workers to %u; actual value is %i
[ER_XPLUGIN_FAILED_TO_SET_MIN_NUMBER_OF_WORKERS](#) was added in 8.0.11.
 - Error number: [MY-011310](#); Symbol: [ER_XPLUGIN_UNABLE_TO_ACCEPT_CONNECTION](#); SQLSTATE: [HY000](#)
Message: Unable to accept connection, disconnecting client
[ER_XPLUGIN_UNABLE_TO_ACCEPT_CONNECTION](#) was added in 8.0.11.
 - Error number: [MY-011311](#); Symbol: [ER_XPLUGIN_ALL_IO_INTERFACES_DISABLED](#); SQLSTATE: [HY000](#)

Message: All I/O interfaces are disabled, X Protocol won't be accessible

`ER_XPLUGIN_ALL_IO_INTERFACES_DISABLED` was added in 8.0.11.

- Error number: `MY-011312`; Symbol: `ER_XPLUGIN_INVALID_MSG_DURING_CLIENT_INIT`; SQLSTATE: `HY000`

Message: %s: Invalid message %i received during client initialization

`ER_XPLUGIN_INVALID_MSG_DURING_CLIENT_INIT` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011313`; Symbol: `ER_XPLUGIN_CLOSING_CLIENTS_ON_SHUTDOWN`; SQLSTATE: `HY000`

Message: %s: closing client because of shutdown (state: %i)

`ER_XPLUGIN_CLOSING_CLIENTS_ON_SHUTDOWN` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011314`; Symbol: `ER_XPLUGIN_ERROR_READING_SOCKET`; SQLSTATE: `HY000`

Message: %s: Error reading from socket %s (%i)

`ER_XPLUGIN_ERROR_READING_SOCKET` was added in 8.0.11.

- Error number: `MY-011315`; Symbol: `ER_XPLUGIN_PEER_DISCONNECTED_WHILE_READING_MSG_BODY`; SQLSTATE: `HY000`

Message: %s: peer disconnected while reading message body

`ER_XPLUGIN_PEER_DISCONNECTED_WHILE_READING_MSG_BODY` was added in 8.0.11.

- Error number: `MY-011316`; Symbol: `ER_XPLUGIN_READ_FAILED_CLOSING_CONNECTION`; SQLSTATE: `HY000`

Message: client_id:%s - %s while reading from socket, closing connection

`ER_XPLUGIN_READ_FAILED_CLOSING_CONNECTION` was added in 8.0.11.

- Error number: `MY-011317`; Symbol: `ER_XPLUGIN_INVALID_AUTH_METHOD`; SQLSTATE: `HY000`

Message: %s.%u: Invalid authentication method %s

`ER_XPLUGIN_INVALID_AUTH_METHOD` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011318`; Symbol: `ER_XPLUGIN_UNEXPECTED_MSG_DURING_AUTHENTICATION`; SQLSTATE: `HY000`

Message: %s: Unexpected message of type %i received during authentication

`ER_XPLUGIN_UNEXPECTED_MSG_DURING_AUTHENTICATION` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011319`; Symbol: `ER_XPLUGIN_ERROR_WRITING_TO_CLIENT`; SQLSTATE: `HY000`

Message: Error writing to client: %s (%i)

`ER_XPLUGIN_ERROR_WRITING_TO_CLIENT` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011320`; Symbol: `ER_XPLUGIN_SCHEDULER_STARTED`; SQLSTATE: `HY000`

Message: Scheduler "%s" started.

`ER_XPLUGIN_SCHEDULER_STARTED` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011321`; Symbol: `ER_XPLUGIN_SCHEDULER_STOPPED`; SQLSTATE: `HY000`

Message: Scheduler "%s" stopped.

`ER_XPLUGIN_SCHEDULER_STOPPED` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011322`; Symbol: `ER_XPLUGIN_LISTENER_SYS_VARIABLE_ERROR`; SQLSTATE: `HY000`

Message: Please see the MySQL documentation for '%s' system variables to fix the error

`ER_XPLUGIN_LISTENER_SYS_VARIABLE_ERROR` was added in 8.0.11.

- Error number: `MY-011323`; Symbol: `ER_XPLUGIN_LISTENER_STATUS_MSG`; SQLSTATE: `HY000`

Message: X Plugin ready for connections. %s

`ER_XPLUGIN_LISTENER_STATUS_MSG` was added in 8.0.11.

- Error number: `MY-011324`; Symbol: `ER_XPLUGIN_RETRYING_BIND_ON_PORT`; SQLSTATE: `HY000`

Message: Retrying `bind()` on TCP/IP port %i

`ER_XPLUGIN_RETRYING_BIND_ON_PORT` was added in 8.0.11.

- Error number: `MY-011325`; Symbol: `ER_XPLUGIN_SHUTDOWN_TRIGGERED`; SQLSTATE: `HY000`

Message: Shutdown triggered by mysqld abort flag

`ER_XPLUGIN_SHUTDOWN_TRIGGERED` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011326`; Symbol: `ER_XPLUGIN_USER_ACCOUNT_WITH_ALL_PERMISSIONS`; SQLSTATE: `HY000`

Message: Using %s account for authentication which has all required permissions

`ER_XPLUGIN_USER_ACCOUNT_WITH_ALL_PERMISSIONS` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011327`; Symbol: `ER_XPLUGIN_EXISTING_USER_ACCOUNT_WITH_INCOMPLETE_GRANTS`; SQLSTATE: `HY000`

Message: Using existing %s account for authentication. Incomplete grants will be fixed

`ER_XPLUGIN_EXISTING_USER_ACCOUNT_WITH_INCOMPLETE_GRANTS` was added in 8.0.11.

- Error number: `MY-011328`; Symbol: `ER_XPLUGIN_SERVER_STARTS_HANDLING_CONNECTIONS`; SQLSTATE: `HY000`

Message: Server starts handling incoming connections

`ER_XPLUGIN_SERVER_STARTS_HANDLING_CONNECTIONS` was added in 8.0.11, removed after 8.0.12.

-
- Error number: [MY-011329](#); Symbol: [ER_XPLUGIN_SERVER_STOPPED_HANDLING_CONNECTIONS](#); SQLSTATE: [HY000](#)

Message: Stopped handling incoming connections

[ER_XPLUGIN_SERVER_STOPPED_HANDLING_CONNECTIONS](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011330](#); Symbol: [ER_XPLUGIN_FAILED_TO_INTERRUPT_SESSION](#); SQLSTATE: [HY000](#)

Message: %s: Could not interrupt client session

[ER_XPLUGIN_FAILED_TO_INTERRUPT_SESSION](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011331](#); Symbol: [ER_XPLUGIN_CLIENT_RELEASE_TRIGGERED](#); SQLSTATE: [HY000](#)

Message: %s: release triggered by timeout in state:%i

[ER_XPLUGIN_CLIENT_RELEASE_TRIGGERED](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011332](#); Symbol: [ER_XPLUGIN_IPV6_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: IPv6 is available

[ER_XPLUGIN_IPV6_AVAILABLE](#) was added in 8.0.11.

- Error number: [MY-011333](#); Symbol: [ER_XPLUGIN_UNIX_SOCKET_NOT_CONFIGURED](#); SQLSTATE: [HY000](#)

Message: UNIX socket not configured

[ER_XPLUGIN_UNIX_SOCKET_NOT_CONFIGURED](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011334](#); Symbol: [ER_XPLUGIN_CLIENT_KILL_MSG](#); SQLSTATE: [HY000](#)

Message: Kill client: %i %s

[ER_XPLUGIN_CLIENT_KILL_MSG](#) was added in 8.0.11.

- Error number: [MY-011335](#); Symbol: [ER_XPLUGIN_FAILED_TO_GET_SECURITY_CTX](#); SQLSTATE: [HY000](#)

Message: Could not get security context for session

[ER_XPLUGIN_FAILED_TO_GET_SECURITY_CTX](#) was added in 8.0.11.

- Error number: [MY-011336](#); Symbol: [ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX_TO_ROOT](#); SQLSTATE: [HY000](#)

Message: Unable to switch security context to root

[ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX_TO_ROOT](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011337](#); Symbol: [ER_XPLUGIN_FAILED_TO_CLOSE_SQL_SESSION](#); SQLSTATE: [HY000](#)

Message: Error closing SQL session

[ER_XPLUGIN_FAILED_TO_CLOSE_SQL_SESSION](#) was added in 8.0.11.

-
- Error number: `MY-011338`; Symbol: `ER_XPLUGIN_FAILED_TO_EXECUTE_ADMIN_CMD`; SQLSTATE: `HY000`

Message: Error executing admin command %s: %s
`ER_XPLUGIN_FAILED_TO_EXECUTE_ADMIN_CMD` was added in 8.0.11.
 - Error number: `MY-011339`; Symbol: `ER_XPLUGIN_EMPTY_ADMIN_CMD`; SQLSTATE: `HY000`

Message: Error executing empty admin command
`ER_XPLUGIN_EMPTY_ADMIN_CMD` was added in 8.0.11.
 - Error number: `MY-011340`; Symbol: `ER_XPLUGIN_FAILED_TO_GET_SYS_VAR`; SQLSTATE: `HY000`

Message: Unable to retrieve system variable '\%s'\br/>`ER_XPLUGIN_FAILED_TO_GET_SYS_VAR` was added in 8.0.11.
 - Error number: `MY-011341`; Symbol: `ER_XPLUGIN_FAILED_TO_GET_CREATION_STMT`; SQLSTATE: `HY000`

Message: Unable to get creation stmt for collection '\%s\'; query result size: %lu
`ER_XPLUGIN_FAILED_TO_GET_CREATION_STMT` was added in 8.0.11.
 - Error number: `MY-011342`; Symbol: `ER_XPLUGIN_FAILED_TO_GET_ENGINE_INFO`; SQLSTATE: `HY000`

Message: Unable to get engine info for collection '\%s\'; creation stmt: %s
`ER_XPLUGIN_FAILED_TO_GET_ENGINE_INFO` was added in 8.0.11.
 - Error number: `MY-011343`; Symbol: `ER_XPLUGIN_FAIL_TO_GET_RESULT_DATA`; SQLSTATE: `HY000`

Message: Error getting result data: %s
`ER_XPLUGIN_FAIL_TO_GET_RESULT_DATA` was added in 8.0.11, removed after 8.0.12.
 - Error number: `MY-011344`; Symbol: `ER_XPLUGIN_CAPABILITY_EXPIRED_PASSWORD`; SQLSTATE: `HY000`

Message: Capability expired password failed with error: %s
`ER_XPLUGIN_CAPABILITY_EXPIRED_PASSWORD` was added in 8.0.11, removed after 8.0.12.
 - Error number: `MY-011345`; Symbol: `ER_XPLUGIN_FAILED_TO_SET_SO_REUSEADDR_FLAG`; SQLSTATE: `HY000`

Message: Failed to set SO_REUSEADDR flag (error: %d).
`ER_XPLUGIN_FAILED_TO_SET_SO_REUSEADDR_FLAG` was added in 8.0.11.
 - Error number: `MY-011346`; Symbol: `ER_XPLUGIN_FAILED_TO_OPEN_INTERNAL_SESSION`; SQLSTATE: `HY000`

Message: Could not open internal MySQL session
`ER_XPLUGIN_FAILED_TO_OPEN_INTERNAL_SESSION` was added in 8.0.11.
 - Error number: `MY-011347`; Symbol: `ER_XPLUGIN_FAILED_TO_SWITCH_CONTEXT`; SQLSTATE: `HY000`

Message: Unable to switch context to user %s

`ER_XPLUGIN_FAILED_TO_SWITCH_CONTEXT` was added in 8.0.11.

- Error number: `MY-011348`; Symbol: `ER_XPLUGIN_FAILED_TO_UNREGISTER_UDF`; SQLSTATE: `HY000`

Message: Can't unregister '\%s\' user defined function

`ER_XPLUGIN_FAILED_TO_UNREGISTER_UDF` was added in 8.0.11.

- Error number: `MY-011349`; Symbol: `ER_XPLUGIN_GET_PEER_ADDRESS_FAILED`; SQLSTATE: `HY000`

Message: %s: get peer address failed, can't resolve IP to hostname

`ER_XPLUGIN_GET_PEER_ADDRESS_FAILED` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011350`; Symbol: `ER_XPLUGIN_CAPABILITY_CLIENT_INTERACTIVE_FAILED`; SQLSTATE: `HY000`

Message: Capability client interactive failed with error: %s

`ER_XPLUGIN_CAPABILITY_CLIENT_INTERACTIVE_FAILED` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011351`; Symbol: `ER_XPLUGIN_FAILED_TO_RESET_IPV6_V6ONLY_FLAG`; SQLSTATE: `HY000`

Message: Failed to reset IPV6_V6ONLY flag (error: %d). The server will listen to IPv6 addresses only.

`ER_XPLUGIN_FAILED_TO_RESET_IPV6_V6ONLY_FLAG` was added in 8.0.11.

- Error number: `MY-011352`; Symbol: `ER_KEYRING_INVALID_KEY_TYPE`; SQLSTATE: `HY000`

Message: Invalid key type

`ER_KEYRING_INVALID_KEY_TYPE` was added in 8.0.11.

- Error number: `MY-011353`; Symbol: `ER_KEYRING_INVALID_KEY_LENGTH`; SQLSTATE: `HY000`

Message: Invalid key length for given block cipher

`ER_KEYRING_INVALID_KEY_LENGTH` was added in 8.0.11.

- Error number: `MY-011354`; Symbol: `ER_KEYRING_FAILED_TO_CREATE_KEYRING_DIR`; SQLSTATE: `HY000`

Message: Could not create keyring directory. The keyring_file will stay unusable until correct path to the keyring directory gets provided

`ER_KEYRING_FAILED_TO_CREATE_KEYRING_DIR` was added in 8.0.11.

- Error number: `MY-011355`; Symbol: `ER_KEYRING_FILE_INIT_FAILED`; SQLSTATE: `HY000`

Message: keyring_file initialization failure. Please check if the keyring_file_data points to readable keyring file or keyring file can be created in the specified location. The keyring_file will stay unusable until correct path to the keyring file gets provided

`ER_KEYRING_FILE_INIT_FAILED` was added in 8.0.11.

-
- Error number: [MY-011356](#); Symbol: [ER_KEYRING_INTERNAL_EXCEPTION_FAILED_FILE_INIT](#); SQLSTATE: [HY000](#)

Message: keyring_file initialization failure due to internal exception inside the plugin.
[ER_KEYRING_INTERNAL_EXCEPTION_FAILED_FILE_INIT](#) was added in 8.0.11.
 - Error number: [MY-011357](#); Symbol: [ER_KEYRING_FAILED_TO_GENERATE_KEY](#); SQLSTATE: [HY000](#)

Message: Failed to generate a key due to internal exception inside keyring_file plugin
[ER_KEYRING_FAILED_TO_GENERATE_KEY](#) was added in 8.0.11.
 - Error number: [MY-011358](#); Symbol: [ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_INVALID_KEY](#); SQLSTATE: [HY000](#)

Message: Error while %s key: invalid key_type
[ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_INVALID_KEY](#) was added in 8.0.11.
 - Error number: [MY-011359](#); Symbol: [ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_EMPTY_KEY_ID](#); SQLSTATE: [HY000](#)

Message: Error while %s key: key_id cannot be empty
[ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_EMPTY_KEY_ID](#) was added in 8.0.11.
 - Error number: [MY-011360](#); Symbol: [ER_KEYRING_OPERATION_FAILED_DUE_TO_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)

Message: Failed to %s due to internal exception inside %s plugin
[ER_KEYRING_OPERATION_FAILED_DUE_TO_INTERNAL_ERROR](#) was added in 8.0.11.
 - Error number: [MY-011361](#); Symbol: [ER_KEYRING_INCORRECT_FILE](#); SQLSTATE: [HY000](#)

Message: Incorrect Keyring file
[ER_KEYRING_INCORRECT_FILE](#) was added in 8.0.11.
 - Error number: [MY-011362](#); Symbol: [ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE](#); SQLSTATE: [HY000](#)

Message: Found malformed keyring backup file - removing it
[ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE](#) was added in 8.0.11.
 - Error number: [MY-011363](#); Symbol: [ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP_FILE](#); SQLSTATE: [HY000](#)

Message: Error while restoring keyring from backup file cannot overwrite keyring with backup
[ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP_FILE](#) was added in 8.0.11.
 - Error number: [MY-011364](#); Symbol: [ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE](#); SQLSTATE: [HY000](#)

Message: Error while flushing in-memory keyring into keyring file
[ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE](#) was added in 8.0.11.
 - Error number: [MY-011365](#); Symbol: [ER_KEYRING_FAILED_TO_GET_FILE_STAT](#); SQLSTATE: [HY000](#)

Message: Error while reading stat for %s. Please check if file %s was not removed. OS returned this error: %s

`ER_KEYRING_FAILED_TO_GET_FILE_STAT` was added in 8.0.11.

- Error number: `MY-011366`; Symbol: `ER_KEYRING_FAILED_TO_REMOVE_FILE`; SQLSTATE: `HY000`

Message: Could not remove file %s OS retuned this error: %s

`ER_KEYRING_FAILED_TO_REMOVE_FILE` was added in 8.0.11.

- Error number: `MY-011367`; Symbol: `ER_KEYRING_FAILED_TO_TRUNCATE_FILE`; SQLSTATE: `HY000`

Message: Could not truncate file %. OS retuned this error: %s

`ER_KEYRING_FAILED_TO_TRUNCATE_FILE` was added in 8.0.11.

- Error number: `MY-011368`; Symbol: `ER_KEYRING_UNKNOWN_ERROR`; SQLSTATE: `HY000`

Message: Unknown error %d

`ER_KEYRING_UNKNOWN_ERROR` was added in 8.0.11.

- Error number: `MY-011369`; Symbol: `ER_KEYRING_FAILED_TO_SET_KEYRING_FILE_DATA`; SQLSTATE: `HY000`

Message: keyring_file_data cannot be set to new value as the keyring file cannot be created/ accessed in the provided path

`ER_KEYRING_FAILED_TO_SET_KEYRING_FILE_DATA` was added in 8.0.11.

- Error number: `MY-011370`; Symbol: `ER_KEYRING_FILE_IO_ERROR`; SQLSTATE: `HY000`

Message: %s

`ER_KEYRING_FILE_IO_ERROR` was added in 8.0.11.

- Error number: `MY-011371`; Symbol: `ER_KEYRING_FAILED_TO_LOAD_KEYRING_CONTENT`; SQLSTATE: `HY000`

Message: Error while loading keyring content. The keyring might be malformed

`ER_KEYRING_FAILED_TO_LOAD_KEYRING_CONTENT` was added in 8.0.11.

- Error number: `MY-011372`; Symbol: `ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING`; SQLSTATE: `HY000`

Message: Could not flush keys to keyring

`ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING` was added in 8.0.11.

- Error number: `MY-011373`; Symbol: `ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING_BACKUP`; SQLSTATE: `HY000`

Message: Could not flush keys to keyring's backup

`ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING_BACKUP` was added in 8.0.11.

- Error number: `MY-011374`; Symbol: `ER_KEYRING_KEY_FETCH_FAILED_DUE_TO_EMPTY_KEY_ID`; SQLSTATE: `HY000`

Message: Error while fetching key: key_id cannot be empty

`ER_KEYRING_KEY_FETCH_FAILED_DUE_TO_EMPTY_KEY_ID` was added in 8.0.11.

- Error number: `MY-011375`; Symbol:

`ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_EMPTY_ID`; SQLSTATE: `HY000`

Message: Error while removing key: key_id cannot be empty

`ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_EMPTY_ID` was added in 8.0.11.

- Error number: `MY-011376`; Symbol: `ER_KEYRING_OKV_INCORRECT_KEY_VAULT_CONFIGURED`; SQLSTATE: `HY000`

Message: For keyring_okv to be initialized, please point keyring_okv_conf_dir variable to a directory with Oracle Key Vault configuration file and ssl materials

`ER_KEYRING_OKV_INCORRECT_KEY_VAULT_CONFIGURED` was added in 8.0.11.

- Error number: `MY-011377`; Symbol:

`ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INCORRECT_CONF`; SQLSTATE: `HY000`

Message: keyring_okv initialization failure. Please check that the keyring_okv_conf_dir points to a readable directory and that the directory contains Oracle Key Vault configuration file and ssl materials. Please also check that Oracle Key Vault is up and running.

`ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INCORRECT_CONF` was added in 8.0.11.

- Error number: `MY-011378`; Symbol:

`ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`

Message: keyring_okv initialization failure due to internal exception inside the plugin

`ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INTERNAL_ERROR` was added in 8.0.11.

- Error number: `MY-011379`; Symbol: `ER_KEYRING_OKV_INVALID_KEY_TYPE`; SQLSTATE: `HY000`

Message: Invalid key type

`ER_KEYRING_OKV_INVALID_KEY_TYPE` was added in 8.0.11.

- Error number: `MY-011380`; Symbol: `ER_KEYRING_OKV_INVALID_KEY_LENGTH_FOR_CIPHER`; SQLSTATE: `HY000`

Message: Invalid key length for given block cipher

`ER_KEYRING_OKV_INVALID_KEY_LENGTH_FOR_CIPHER` was added in 8.0.11.

- Error number: `MY-011381`; Symbol:

`ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`

Message: Failed to generate a key due to internal exception inside keyring_okv plugin

`ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR` was added in 8.0.11.

- Error number: [MY-011382](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_FIND_SERVER_ENTRY](#); SQLSTATE: [HY000](#)

Message: Could not find entry for server in configuration file %s

[ER_KEYRING_OKV_FAILED_TO_FIND_SERVER_ENTRY](#) was added in 8.0.11.

- Error number: [MY-011383](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_FIND_STANDBY_SERVER_ENTRY](#); SQLSTATE: [HY000](#)

Message: Could not find entry for standby server in configuration file %s

[ER_KEYRING_OKV_FAILED_TO_FIND_STANDBY_SERVER_ENTRY](#) was added in 8.0.11.

- Error number: [MY-011384](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_PARSE_CONF_FILE](#); SQLSTATE: [HY000](#)

Message: Could not parse the %s file provided

[ER_KEYRING_OKV_FAILED_TO_PARSE_CONF_FILE](#) was added in 8.0.11.

- Error number: [MY-011385](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_LOAD_KEY_UID](#); SQLSTATE: [HY000](#)

Message: Could not load keys' uids from the OKV server

[ER_KEYRING_OKV_FAILED_TO_LOAD_KEY_UID](#) was added in 8.0.11.

- Error number: [MY-011386](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_INIT_SSL_LAYER](#); SQLSTATE: [HY000](#)

Message: Could not initialize ssl layer

[ER_KEYRING_OKV_FAILED_TO_INIT_SSL_LAYER](#) was added in 8.0.11.

- Error number: [MY-011387](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_INIT_CLIENT](#); SQLSTATE: [HY000](#)

Message: Could not initialize OKV client

[ER_KEYRING_OKV_FAILED_TO_INIT_CLIENT](#) was added in 8.0.11.

- Error number: [MY-011388](#); Symbol: [ER_KEYRING_OKV_CONNECTION_TO_SERVER_FAILED](#); SQLSTATE: [HY000](#)

Message: Could not connect to the OKV server

[ER_KEYRING_OKV_CONNECTION_TO_SERVER_FAILED](#) was added in 8.0.11.

- Error number: [MY-011389](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_REMOVE_KEY](#); SQLSTATE: [HY000](#)

Message: Could not remove the key

[ER_KEYRING_OKV_FAILED_TO_REMOVE_KEY](#) was added in 8.0.11.

- Error number: [MY-011390](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_ADD_ATTRIBUTE](#); SQLSTATE: [HY000](#)

Message: Could not add attribute, attribute_name=%s attribute value=%s

[ER_KEYRING_OKV_FAILED_TO_ADD_ATTRIBUTE](#) was added in 8.0.11.

-
- Error number: [MY-011391](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY](#); SQLSTATE: [HY000](#)

Message: Could not generate the key.

[ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY](#) was added in 8.0.11.

- Error number: [MY-011392](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_STORE_KEY](#); SQLSTATE: [HY000](#)

Message: Could not store the key.

[ER_KEYRING_OKV_FAILED_TO_STORE_KEY](#) was added in 8.0.11.

- Error number: [MY-011393](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_ACTIVATE_KEYS](#); SQLSTATE: [HY000](#)

Message: Could not activate the key.

[ER_KEYRING_OKV_FAILED_TO_ACTIVATE_KEYS](#) was added in 8.0.11.

- Error number: [MY-011394](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_FETCH_KEY](#); SQLSTATE: [HY000](#)

Message: Could not fetch generated key

[ER_KEYRING_OKV_FAILED_TO_FETCH_KEY](#) was added in 8.0.11.

- Error number: [MY-011395](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_STORE_OR_GENERATE_KEY](#); SQLSTATE: [HY000](#)

Message: Could not store/generate the key - failed to set key attribute x-key-ready

[ER_KEYRING_OKV_FAILED_TO_STORE_OR_GENERATE_KEY](#) was added in 8.0.11.

- Error number: [MY-011396](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY_SIGNATURE](#); SQLSTATE: [HY000](#)

Message: Could not retrieve key signature from custom attributes

[ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY_SIGNATURE](#) was added in 8.0.11.

- Error number: [MY-011397](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY](#); SQLSTATE: [HY000](#)

Message: Could not retrieve key from OKV

[ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY](#) was added in 8.0.11.

- Error number: [MY-011398](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_LOAD_SSL_TRUST_STORE](#); SQLSTATE: [HY000](#)

Message: Error loading trust store

[ER_KEYRING_OKV_FAILED_TO_LOAD_SSL_TRUST_STORE](#) was added in 8.0.11.

- Error number: [MY-011399](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_SET_CERTIFICATE_FILE](#); SQLSTATE: [HY000](#)

Message: Error setting the certificate file.

[ER_KEYRING_OKV_FAILED_TO_SET_CERTIFICATE_FILE](#) was added in 8.0.11.

-
- Error number: [MY-011400](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_SET_KEY_FILE](#); SQLSTATE: [HY000](#)

Message: Error setting the key file.

[ER_KEYRING_OKV_FAILED_TO_SET_KEY_FILE](#) was added in 8.0.11.

- Error number: [MY-011401](#); Symbol: [ER_KEYRING_OKV_KEY_MISMATCH](#); SQLSTATE: [HY000](#)

Message: Private key does not match the certificate public key

[ER_KEYRING_OKV_KEY_MISMATCH](#) was added in 8.0.11.

- Error number: [MY-011402](#); Symbol: [ER_KEYRING_ENCRYPTED_FILE_INCORRECT_KEYRING_FILE](#); SQLSTATE: [HY000](#)

Message: Incorrect Keyring file

[ER_KEYRING_ENCRYPTED_FILE_INCORRECT_KEYRING_FILE](#) was added in 8.0.11.

- Error number: [MY-011403](#); Symbol: [ER_KEYRING_ENCRYPTED_FILE_DECRIPTION_FAILED](#); SQLSTATE: [HY000](#)

Message: Keyring_encrypted_file decryption failed. Please verify --keyring-encrypted-file-password option value.

[ER_KEYRING_ENCRYPTED_FILE_DECRIPTION_FAILED](#) was added in 8.0.11.

- Error number: [MY-011404](#); Symbol: [ER_KEYRING_ENCRYPTED_FILE_FOUND_MALFORMED_BACKUP_FILE](#); SQLSTATE: [HY000](#)

Message: Found malformed keyring backup file - removing it

[ER_KEYRING_ENCRYPTED_FILE_FOUND_MALFORMED_BACKUP_FILE](#) was added in 8.0.11.

- Error number: [MY-011405](#); Symbol: [ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_RESTORE_KEYRING](#); SQLSTATE: [HY000](#)

Message: Error while restoring keyring from backup file cannot overwrite keyring with backup

[ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_RESTORE_KEYRING](#) was added in 8.0.11.

- Error number: [MY-011406](#); Symbol: [ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_FLUSH_KEYRING](#); SQLSTATE: [HY000](#)

Message: Error while flushing in-memory keyring into keyring file

[ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_FLUSH_KEYRING](#) was added in 8.0.11.

- Error number: [MY-011407](#); Symbol: [ER_KEYRING_ENCRYPTED_FILE_ENCRYPTION_FAILED](#); SQLSTATE: [HY000](#)

Message: Keyring_encrypted_file encryption failed. Please verify --keyring-encrypted-file-password option value.

[ER_KEYRING_ENCRYPTED_FILE_ENCRYPTION_FAILED](#) was added in 8.0.11.

-
- Error number: [MY-011408](#); Symbol: [ER_KEYRING_ENCRYPTED_FILE_INVALID_KEYRING_DIR](#); SQLSTATE: [HY000](#)

Message: keyring_encrypted_file_data cannot be set to new value as the keyring file cannot be created/accessed in the provided path

[ER_KEYRING_ENCRYPTED_FILE_INVALID_KEYRING_DIR](#) was added in 8.0.11.

- Error number: [MY-011409](#); Symbol: [ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_CREATE_KEYRING_DIR](#); SQLSTATE: [HY000](#)

Message: Could not create keyring directory The keyring_encrypted_file will stay unusable until correct path to the keyring directory gets provided

[ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_CREATE_KEYRING_DIR](#) was added in 8.0.11.

- Error number: [MY-011410](#); Symbol: [ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_INVALID](#); SQLSTATE: [HY000](#)

Message: The keyring_encrypted_file_password must be set to a valid value.

[ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_INVALID](#) was added in 8.0.11.

- Error number: [MY-011411](#); Symbol: [ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: Too long keyring_encrypted_file_password value.

[ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_TOO_LONG](#) was added in 8.0.11.

- Error number: [MY-011412](#); Symbol: [ER_KEYRING_ENCRYPTED_FILE_INIT_FAILURE](#); SQLSTATE: [HY000](#)

Message: keyring_encrypted_file initialization failure. Please check if the keyring_encrypted_file_data points to readable keyring file or keyring file can be created in the specified location or password to decrypt keyring file is correct.

[ER_KEYRING_ENCRYPTED_FILE_INIT_FAILURE](#) was added in 8.0.11.

- Error number: [MY-011413](#); Symbol: [ER_KEYRING_ENCRYPTED_FILE_INIT_FAILED_DUE_TO_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)

Message: keyring_encrypted_file initialization failure due to internal exception inside the plugin

[ER_KEYRING_ENCRYPTED_FILE_INIT_FAILED_DUE_TO_INTERNAL_ERROR](#) was added in 8.0.11.

- Error number: [MY-011414](#); Symbol: [ER_KEYRING_ENCRYPTED_FILE_GEN_KEY_FAILED_DUE_TO_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)

Message: Failed to generate a key due to internal exception inside keyring_encrypted_file plugin

[ER_KEYRING_ENCRYPTED_FILE_GEN_KEY_FAILED_DUE_TO_INTERNAL_ERROR](#) was added in 8.0.11.

- Error number: [MY-011415](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID](#); SQLSTATE: [HY000](#)

Message: keyring_aws_cmk_id cannot be set to the new value as AWS KMS seems to not understand the id provided. Please check that CMK id provided is correct.

`ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID` was added in 8.0.11.

- Error number: `MY-011416`; Symbol: `ER_KEYRING_AWS_FAILED_TO_SET_REGION`; SQLSTATE: `HY000`

Message: keyring_aws_region cannot be set to the new value as AWS KMS seems to not understand the region provided. Please check that region provided is correct.

`ER_KEYRING_AWS_FAILED_TO_SET_REGION` was added in 8.0.11.

- Error number: `MY-011417`; Symbol: `ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE`; SQLSTATE: `HY000`

Message: Could not open keyring_aws configuration file: %s. OS returned this error: %s

`ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE` was added in 8.0.11.

- Error number: `MY-011418`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID_FROM_CONF_FILE`; SQLSTATE: `HY000`

Message: Could not read AWS access key id from keyring_aws configuration file: %s. OS returned this error: %s

`ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID_FROM_CONF_FILE` was added in 8.0.11.

- Error number: `MY-011419`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_FROM_CONF_FILE`; SQLSTATE: `HY000`

Message: Could not read AWS access key from keyring_aws configuration file: %s. OS returned this error: %s

`ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_FROM_CONF_FILE` was added in 8.0.11.

- Error number: `MY-011420`; Symbol: `ER_KEYRING_AWS_INVALID_CONF_FILE_PATH`; SQLSTATE: `HY000`

Message: Path to keyring aws configuration file cannot be empty

`ER_KEYRING_AWS_INVALID_CONF_FILE_PATH` was added in 8.0.11.

- Error number: `MY-011421`; Symbol: `ER_KEYRING_AWS_INVALID_DATA_FILE_PATH`; SQLSTATE: `HY000`

Message: Path to keyring_aws storage file cannot be empty.

`ER_KEYRING_AWS_INVALID_DATA_FILE_PATH` was added in 8.0.11.

- Error number: `MY-011422`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DIR`; SQLSTATE: `HY000`

Message: Unable to create/access keyring directory.

`ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DIR` was added in 8.0.11.

- Error number: [MY-011423](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DATA_FILE](#); SQLSTATE: [HY000](#)

Message: Unable to create/access keyring_aws storage file. Please check if keyring_aws_data_file points to location where keyring file can be created/accessible. Please also make sure that MySQL server's user has high enough privileges to access this location.

[ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DATA_FILE](#) was added in 8.0.11.
- Error number: [MY-011424](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)

Message: keyring_aws initialization failed due to internal error when initializing synchronization primitive - %s. OS returned this error: %s:

[ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_ERROR](#) was added in 8.0.11.
- Error number: [MY-011425](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_ACCESS_DATA_FILE](#); SQLSTATE: [HY000](#)

Message: Could not access keyring_aws storage file in the path provided. Please check if the keyring_aws directory can be accessed by MySQL Server

[ER_KEYRING_AWS_FAILED_TO_ACCESS_DATA_FILE](#) was added in 8.0.11.
- Error number: [MY-011426](#); Symbol: [ER_KEYRING_AWS_CMK_ID_NOT_SET](#); SQLSTATE: [HY000](#)

Message: keyring_aws_cmk_id has to be set

[ER_KEYRING_AWS_CMK_ID_NOT_SET](#) was added in 8.0.11.
- Error number: [MY-011427](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIAL_FROM_CONF_FILE](#); SQLSTATE: [HY000](#)

Message: Could not get AWS KMS credentials from the configuration file

[ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIAL_FROM_CONF_FILE](#) was added in 8.0.11.
- Error number: [MY-011428](#); Symbol: [ER_KEYRING_AWS_INIT_FAILURE](#); SQLSTATE: [HY000](#)

Message: keyring_aws initialization failure.

[ER_KEYRING_AWS_INIT_FAILURE](#) was added in 8.0.11.
- Error number: [MY-011429](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)

Message: keyring_aws initialization failure due to internal exception inside the plugin

[ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_INTERNAL_ERROR](#) was added in 8.0.11.
- Error number: [MY-011430](#); Symbol: [ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER](#); SQLSTATE: [HY000](#)

Message: Invalid key length for given block cipher

[ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER](#) was added in 8.0.11.
- Error number: [MY-011431](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)

Message: Failed to generate a key due to internal exception inside keyring_file plugin

`ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR` was added in 8.0.11.

- Error number: `MY-011432`; Symbol: `ER_KEYRING_AWS_INCORRECT_FILE`; SQLSTATE: `HY000`

Message: Incorrect Keyring file

`ER_KEYRING_AWS_INCORRECT_FILE` was added in 8.0.11.

- Error number: `MY-011433`; Symbol: `ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_FILE`; SQLSTATE: `HY000`

Message: Found malformed keyring backup file - removing it

`ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_FILE` was added in 8.0.11.

- Error number: `MY-011434`; Symbol: `ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP_FILE`; SQLSTATE: `HY000`

Message: Error while restoring keyring from backup file cannot overwrite keyring with backup

`ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP_FILE` was added in 8.0.11.

- Error number: `MY-011435`; Symbol: `ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_FILE`; SQLSTATE: `HY000`

Message: Error while flushing in-memory keyring into keyring file

`ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_FILE` was added in 8.0.11.

- Error number: `MY-011436`; Symbol: `ER_KEYRING_AWS_INCORRECT_REGION`; SQLSTATE: `HY000`

Message: Wrong region

`ER_KEYRING_AWS_INCORRECT_REGION` was added in 8.0.11.

- Error number: `MY-011437`; Symbol: `ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS`; SQLSTATE: `HY000`

Message: Could not connect to AWS KMS with the credentials provided. Please make sure they are correct. AWS KMS returned this error: %s

`ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS` was added in 8.0.11.

- Error number: `MY-011438`; Symbol: `ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEY`; SQLSTATE: `HY000`

Message: Could not generate a new key. AWS KMS returned this error: %s

`ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEY` was added in 8.0.11.

- Error number: `MY-011439`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ENCRYPT_KEY`; SQLSTATE: `HY000`

Message: Could not encrypt key. AWS KMS returned this error: %s

`ER_KEYRING_AWS_FAILED_TO_ENCRYPT_KEY` was added in 8.0.11.

- Error number: `MY-011440`; Symbol: `ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY`; SQLSTATE: `HY000`

Message: Could not re-encrypt key. AWS KMS returned this error: %s

`ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY` was added in 8.0.11.

- Error number: `MY-011441`; Symbol: `ER_KEYRING_AWS_FAILED_TO_DECRYPT_KEY`; SQLSTATE: `HY000`

Message: Could not decrypt key. AWS KMS returned this error: %s

`ER_KEYRING_AWS_FAILED_TO_DECRYPT_KEY` was added in 8.0.11.

- Error number: `MY-011442`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK`; SQLSTATE: `HY000`

Message: Could not rotate the CMK. AWS KMS returned this error: %s

`ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK` was added in 8.0.11.

- Error number: `MY-011443`; Symbol: `ER_GRP_RPL_GTID_ALREADY_USED`; SQLSTATE: `HY000`

Message: The requested GTID '%s:%lld' was already used, the transaction will rollback.

`ER_GRP_RPL_GTID_ALREADY_USED` was added in 8.0.11.

- Error number: `MY-011444`; Symbol: `ER_GRP_RPL_APPLIER_THD_KILLED`; SQLSTATE: `HY000`

Message: The group replication applier thread was killed.

`ER_GRP_RPL_APPLIER_THD_KILLED` was added in 8.0.11.

- Error number: `MY-011445`; Symbol: `ER_GRP_RPL_EVENT_HANDLING_ERROR`; SQLSTATE: `HY000`

Message: Error at event handling! Got error: %d.

`ER_GRP_RPL_EVENT_HANDLING_ERROR` was added in 8.0.11.

- Error number: `MY-011446`; Symbol: `ER_GRP_RPL_ERROR_GTID_EXECUTION_INFO`; SQLSTATE: `HY000`

Message: Error when extracting group GTID execution information, some recovery operations may face future issues.

`ER_GRP_RPL_ERROR_GTID_EXECUTION_INFO` was added in 8.0.11.

- Error number: `MY-011447`; Symbol: `ER_GRP_RPL_CERTIFICATE_SIZE_ERROR`; SQLSTATE: `HY000`

Message: An error occurred when trying to reduce the Certification information size for transmission.

`ER_GRP_RPL_CERTIFICATE_SIZE_ERROR` was added in 8.0.11.

- Error number: `MY-011448`; Symbol: `ER_GRP_RPL_CREATE_APPLIER_CACHE_ERROR`; SQLSTATE: `HY000`

Message: Failed to create group replication pipeline applier cache!

`ER_GRP_RPL_CREATE_APPLIER_CACHE_ERROR` was added in 8.0.11.

- Error number: `MY-011449`; Symbol: `ER_GRP_RPL_UNBLOCK_WAITING_THD`; SQLSTATE: `HY000`

Message: Unblocking the group replication thread waiting for applier to start, as the start group replication was killed.

`ER_GRP_RPL_UNBLOCK_WAITING_THD` was added in 8.0.11.

- Error number: `MY-011450`; Symbol: `ER_GRP_RPL_APPLIER_PIPELINE_NOT_DISPOSED`; SQLSTATE: `HY000`

Message: The group replication applier pipeline was not properly disposed. Check the error log for further info.

`ER_GRP_RPL_APPLIER_PIPELINE_NOT_DISPOSED` was added in 8.0.11.

- Error number: `MY-011451`; Symbol: `ER_GRP_RPL_APPLIER_THD_EXECUTION_ABORTED`; SQLSTATE: `HY000`

Message: The applier thread execution was aborted. Unable to process more transactions, this member will now leave the group.

`ER_GRP_RPL_APPLIER_THD_EXECUTION_ABORTED` was added in 8.0.11.

- Error number: `MY-011452`; Symbol: `ER_GRP_RPL_APPLIER_EXECUTION_FATAL_ERROR`; SQLSTATE: `HY000`

Message: Fatal error during execution on the Applier process of Group Replication. The server will now leave the group.

`ER_GRP_RPL_APPLIER_EXECUTION_FATAL_ERROR` was added in 8.0.11.

- Error number: `MY-011453`; Symbol: `ER_GRP_RPL_ERROR_STOPPING_CHANNELS`; SQLSTATE: `HY000`

Message: Error stopping all replication channels while server was leaving the group. %s

`ER_GRP_RPL_ERROR_STOPPING_CHANNELS` was added in 8.0.11.

- Error number: `MY-011454`; Symbol: `ER_GRP_RPL_ERROR_SENDING_SINGLE_PRIMARY_MSSG`; SQLSTATE: `HY000`

Message: Error sending single primary message informing that primary did apply relay logs.

`ER_GRP_RPL_ERROR_SENDING_SINGLE_PRIMARY_MSSG` was added in 8.0.11.

- Error number: `MY-011455`; Symbol: `ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_VER_ERROR`; SQLSTATE: `HY000`

Message: Error updating transaction snapshot version after transaction being positively certified.

`ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_VER_ERROR` was added in 8.0.11.

- Error number: `MY-011456`; Symbol: `ER_GRP_RPL_SIDNO_FETCH_ERROR`; SQLSTATE: `HY000`

Message: Error fetching transaction sidno after transaction being positively certified.

`ER_GRP_RPL_SIDNO_FETCH_ERROR` was added in 8.0.11.

- Error number: `MY-011457`; Symbol: `ER_GRP_RPL_BROADCAST_COMMIT_TRANS_MSSG_FAILED`; SQLSTATE: `HY000`

Message: Broadcast of committed transactions message failed.

`ER_GRP_RPL_BROADCAST_COMMIT_TRANS_MSSG_FAILED` was added in 8.0.11.

- Error number: `MY-011458`; Symbol: `ER_GRP_RPL_GROUP_NAME_PARSE_ERROR`; SQLSTATE: `HY000`

Message: Unable to parse the group_replication_group_name during the Certification module initialization.

`ER_GRP_RPL_GROUP_NAME_PARSE_ERROR` was added in 8.0.11.

- Error number: `MY-011459`; Symbol: `ER_GRP_RPL_ADD_GRPSID_TO_GRP GTIDSID_MAP_ERROR`; SQLSTATE: `HY000`

Message: Unable to add the group_sid in the group_gtid_sid_map during the Certification module initialization.

`ER_GRP_RPL_ADD_GRPSID_TO_GRP GTIDSID_MAP_ERROR` was added in 8.0.11.

- Error number: `MY-011460`; Symbol: `ER_GRP_RPL_UPDATE_GRP GTID_EXECUTED_ERROR`; SQLSTATE: `HY000`

Message: Error updating group_gtid_executed GITD set during the Certification module initialization.

`ER_GRP_RPL_UPDATE_GRP GTID_EXECUTED_ERROR` was added in 8.0.11.

- Error number: `MY-011461`; Symbol: `ER_GRP_RPL_DONOR_TRANS_INFO_ERROR`; SQLSTATE: `HY000`

Message: Unable to handle the donor's transaction information when initializing the conflict detection component. Possible out of memory error.

`ER_GRP_RPL_DONOR_TRANS_INFO_ERROR` was added in 8.0.11.

- Error number: `MY-011462`; Symbol: `ER_GRP_RPL_SERVER_CONN_ERROR`; SQLSTATE: `HY000`

Message: Error when establishing a server connection during the Certification module initialization.

`ER_GRP_RPL_SERVER_CONN_ERROR` was added in 8.0.11.

- Error number: `MY-011463`; Symbol: `ER_GRP_RPL_ERROR_FETCHING_GTI D_EXECUTED_SET`; SQLSTATE: `HY000`

Message: Error when extracting this member GTID executed set. Certification module can't be properly initialized.

`ER_GRP_RPL_ERROR_FETCHING_GTI D_EXECUTED_SET` was added in 8.0.11.

- Error number: `MY-011464`; Symbol: `ER_GRP_RPL_ADD_GTI D_TO_GRP GTID_EXECUTED_ERROR`; SQLSTATE: `HY000`

Message: Error while adding the server GTID EXECUTED set to the group_gtid_execute during the Certification module initialization.

`ER_GRP_RPL_ADD_GTI D_TO_GRP GTID_EXECUTED_ERROR` was added in 8.0.11.

- Error number: `MY-011465`; Symbol: `ER_GRP_RPL_ERROR_FETCHING_GTI D_SET`; SQLSTATE: `HY000`

Message: Error when extracting this member retrieved set for its applier. Certification module can't be properly initialized.

`ER_GRP_RPL_ERROR_FETCHING_GTI D_SET` was added in 8.0.11.

- Error number: [MY-011466](#); Symbol: [ER_GRP_RPL_ADD_RETRIEVED_SET_TO_GRP_GTID_EXECUTED_ERROR](#); SQLSTATE: [HY000](#)

Message: Error while adding the member retrieved set to the group_gtid_executed during the Certification module initialization.

[ER_GRP_RPL_ADD_RETRIEVED_SET_TO_GRP_GTID_EXECUTED_ERROR](#) was added in 8.0.11.

- Error number: [MY-011467](#); Symbol: [ER_GRP_RPL_CERTIFICATION_INITIALIZATION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Error during Certification module initialization.

[ER_GRP_RPL_CERTIFICATION_INITIALIZATION_FAILURE](#) was added in 8.0.11.

- Error number: [MY-011468](#); Symbol: [ER_GRP_RPL_UPDATE_LAST_CONFLICT_FREE_TRANS_ERROR](#); SQLSTATE: [HY000](#)

Message: Unable to update last conflict free transaction, this transaction will not be tracked on performance_schema.replication_group_member_stats.last_conflict_free_transaction.

[ER_GRP_RPL_UPDATE_LAST_CONFLICT_FREE_TRANS_ERROR](#) was added in 8.0.11.

- Error number: [MY-011469](#); Symbol: [ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_REF_VER_ERROR](#); SQLSTATE: [HY000](#)

Message: Error updating transaction snapshot version reference for internal storage.

[ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_REF_VER_ERROR](#) was added in 8.0.11.

- Error number: [MY-011470](#); Symbol: [ER_GRP_RPL_FETCH_TRANS_SIDNO_ERROR](#); SQLSTATE: [HY000](#)

Message: Error fetching transaction sidno while adding to the group_gtid_executed set.

[ER_GRP_RPL_FETCH_TRANS_SIDNO_ERROR](#) was added in 8.0.11.

- Error number: [MY-011471](#); Symbol: [ER_GRP_RPL_ERROR_VERIFYING_SIDNO](#); SQLSTATE: [HY000](#)

Message: Error while ensuring the sidno be present in the group_gtid_executed.

[ER_GRP_RPL_ERROR_VERIFYING_SIDNO](#) was added in 8.0.11.

- Error number: [MY-011472](#); Symbol: [ER_GRP_RPL_CANT_GENERATE_GTID](#); SQLSTATE: [HY000](#)

Message: Impossible to generate Global Transaction Identifier: the integer component reached the maximal value. Restart the group with a new group_replication_group_name.

[ER_GRP_RPL_CANT_GENERATE_GTID](#) was added in 8.0.11.

- Error number: [MY-011473](#); Symbol: [ER_GRP_RPL_INVALID_GTID_SET](#); SQLSTATE: [HY000](#)

Message: Invalid stable transactions set.

[ER_GRP_RPL_INVALID_GTID_SET](#) was added in 8.0.11.

- Error number: [MY-011474](#); Symbol: [ER_GRP_RPL_UPDATE_GTID_SET_ERROR](#); SQLSTATE: [HY000](#)

Message: Error updating stable transactions set.

[ER_GRP_RPL_UPDATE_GTID_SET_ERROR](#) was added in 8.0.11.

-
- Error number: [MY-011475](#); Symbol: [ER_GRP_RPL_RECEIVED_SET_MISSING_GTIDS](#); SQLSTATE: [HY000](#)

Message: There was an error when filling the missing GTIDs on the applier channel received set. Despite not critical, on the long run this may cause performance issues.

[ER_GRP_RPL_RECEIVED_SET_MISSING_GTIDS](#) was added in 8.0.11.

- Error number: [MY-011476](#); Symbol: [ER_GRP_RPL_SKIP_COMPUTATION_TRANS_COMMITTED](#); SQLSTATE: [HY000](#)

Message: Skipping the computation of the Transactions_committed_all_members field as an older instance of this computation is still ongoing.

[ER_GRP_RPL_SKIP_COMPUTATION_TRANS_COMMITTED](#) was added in 8.0.11.

- Error number: [MY-011477](#); Symbol: [ER_GRP_RPL_NULL_PACKET](#); SQLSTATE: [HY000](#)

Message: Null packet on certifier's queue.

[ER_GRP_RPL_NULL_PACKET](#) was added in 8.0.11.

- Error number: [MY-011478](#); Symbol: [ER_GRP_RPL_CANT_READ_GTID](#); SQLSTATE: [HY000](#)

Message: Error reading GTIDs from the message.

[ER_GRP_RPL_CANT_READ_GTID](#) was added in 8.0.11.

- Error number: [MY-011479](#); Symbol: [ER_GRP_RPL_PROCESS_GTID_SET_ERROR](#); SQLSTATE: [HY000](#)

Message: Error processing stable transactions set.

[ER_GRP_RPL_PROCESS_GTID_SET_ERROR](#) was added in 8.0.11.

- Error number: [MY-011480](#); Symbol: [ER_GRP_RPL_PROCESS_INTERSECTION_GTID_SET_ERROR](#); SQLSTATE: [HY000](#)

Message: Error processing intersection of stable transactions set.

[ER_GRP_RPL_PROCESS_INTERSECTION_GTID_SET_ERROR](#) was added in 8.0.11.

- Error number: [MY-011481](#); Symbol: [ER_GRP_RPL_SET_STABLE_TRANS_ERROR](#); SQLSTATE: [HY000](#)

Message: Error setting stable transactions set.

[ER_GRP_RPL_SET_STABLE_TRANS_ERROR](#) was added in 8.0.11.

- Error number: [MY-011482](#); Symbol: [ER_GRP_RPL_CANT_READ_GRP_GTID_EXTRACTED](#); SQLSTATE: [HY000](#)

Message: Error reading group_gtid_extracted from the View_change_log_event.

[ER_GRP_RPL_CANT_READ_GRP_GTID_EXTRACTED](#) was added in 8.0.11.

- Error number: [MY-011483](#); Symbol: [ER_GRP_RPL_CANT_READ_WRITE_SET_ITEM](#); SQLSTATE: [HY000](#)

Message: Error reading the write set item '%s' from the View_change_log_event.

[ER_GRP_RPL_CANT_READ_WRITE_SET_ITEM](#) was added in 8.0.11.

- Error number: [MY-011484](#); Symbol: [ER_GRP_RPL_INIT_CERTIFICATION_INFO_FAILURE](#); SQLSTATE: [HY000](#)

Message: Error during certification_info initialization.

[ER_GRP_RPL_INIT_CERTIFICATION_INFO_FAILURE](#) was added in 8.0.11.

- Error number: [MY-011485](#); Symbol: [ER_GRP_RPL_CONFLICT_DETECTION_DISABLED](#); SQLSTATE: [HY000](#)

Message: Primary had applied all relay logs, disabled conflict detection.

[ER_GRP_RPL_CONFLICT_DETECTION_DISABLED](#) was added in 8.0.11.

- Error number: [MY-011486](#); Symbol: [ER_GRP_RPL_MSG_DISCARDED](#); SQLSTATE: [HY000](#)

Message: Message received while the plugin is not ready, message discarded.

[ER_GRP_RPL_MSG_DISCARDED](#) was added in 8.0.11.

- Error number: [MY-011487](#); Symbol: [ER_GRP_RPL_MISSING_GRP_RPL_APPLIER](#); SQLSTATE: [HY000](#)

Message: Message received without a proper group replication applier.

[ER_GRP_RPL_MISSING_GRP_RPL_APPLIER](#) was added in 8.0.11.

- Error number: [MY-011488](#); Symbol: [ER_GRP_RPL_CERTIFIER_MSSG_PROCESS_ERROR](#); SQLSTATE: [HY000](#)

Message: Error processing message in Certifier.

[ER_GRP_RPL_CERTIFIER_MSSG_PROCESS_ERROR](#) was added in 8.0.11.

- Error number: [MY-011489](#); Symbol: [ER_GRP_RPL_SRV_NOT_ONLINE](#); SQLSTATE: [HY000](#)

Message: This server was not declared online since it is on status %s.

[ER_GRP_RPL_SRV_NOT_ONLINE](#) was added in 8.0.11.

- Error number: [MY-011490](#); Symbol: [ER_GRP_RPL_SRV_ONLINE](#); SQLSTATE: [HY000](#)

Message: This server was declared online within the replication group.

[ER_GRP_RPL_SRV_ONLINE](#) was added in 8.0.11.

- Error number: [MY-011491](#); Symbol: [ER_GRP_RPL_DISABLE_SRV_READ_MODE_RESTRICTED](#); SQLSTATE: [HY000](#)

Message: When declaring the plugin online it was not possible to disable the server read mode settings. Try to disable it manually.

[ER_GRP_RPL_DISABLE_SRV_READ_MODE_RESTRICTED](#) was added in 8.0.11.

- Error number: [MY-011492](#); Symbol: [ER_GRP_RPL_MEM_ONLINE](#); SQLSTATE: [HY000](#)

Message: The member with address %s:%u was declared online within the replication group.

[ER_GRP_RPL_MEM_ONLINE](#) was added in 8.0.11.

- Error number: [MY-011493](#); Symbol: [ER_GRP_RPL_MEM_UNREACHABLE](#); SQLSTATE: [HY000](#)

Message: Member with address %s:%u has become unreachable.

`ER_GRP_RPL_MEM_UNREACHABLE` was added in 8.0.11.

- Error number: `MY-011494`; Symbol: `ER_GRP_RPL_MEM_REACHABLE`; SQLSTATE: `HY000`

Message: Member with address %s:%u is reachable again.

`ER_GRP_RPL_MEM_REACHABLE` was added in 8.0.11.

- Error number: `MY-011495`; Symbol: `ER_GRP_RPL_SRV_BLOCKED`; SQLSTATE: `HY000`

Message: This server is not able to reach a majority of members in the group. This server will now block all updates. The server will remain blocked until contact with the majority is restored. It is possible to use `group_replication_force_members` to force a new group membership.

`ER_GRP_RPL_SRV_BLOCKED` was added in 8.0.11.

- Error number: `MY-011496`; Symbol: `ER_GRP_RPL_SRV_BLOCKED_FOR_SECS`; SQLSTATE: `HY000`

Message: This server is not able to reach a majority of members in the group. This server will now block all updates. The server will remain blocked for the next %lu seconds. Unless contact with the majority is restored, after this time the member will error out and leave the group. It is possible to use `group_replication_force_members` to force a new group membership.

`ER_GRP_RPL_SRV_BLOCKED_FOR_SECS` was added in 8.0.11.

- Error number: `MY-011497`; Symbol: `ER_GRP_RPL_CHANGE_GRP_MEM_NOT_PROCESSED`; SQLSTATE: `HY000`

Message: A group membership change was received but the plugin is already leaving due to the configured timeout on `group_replication_unreachable_majority_timeout` option.

`ER_GRP_RPL_CHANGE_GRP_MEM_NOT_PROCESSED` was added in 8.0.11.

- Error number: `MY-011498`; Symbol: `ER_GRP_RPL_MEMBER_CONTACT_RESTORED`; SQLSTATE: `HY000`

Message: The member has resumed contact with a majority of the members in the group. Regular operation is restored and transactions are unblocked.

`ER_GRP_RPL_MEMBER_CONTACT_RESTORED` was added in 8.0.11.

- Error number: `MY-011499`; Symbol: `ER_GRP_RPL_MEMBER_REMOVED`; SQLSTATE: `HY000`

Message: Members removed from the group: %s

`ER_GRP_RPL_MEMBER_REMOVED` was added in 8.0.11.

- Error number: `MY-011500`; Symbol: `ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP`; SQLSTATE: `HY000`

Message: Primary server with address %s left the group. Electing new Primary.

`ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP` was added in 8.0.11.

- Error number: `MY-011501`; Symbol: `ER_GRP_RPL_MEMBER_ADDED`; SQLSTATE: `HY000`

Message: Members joined the group: %s

`ER_GRP_RPL_MEMBER_ADDED` was added in 8.0.11.

- Error number: `MY-011502`; Symbol: `ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR`; SQLSTATE: `HY000`

Message: There was a previous plugin error while the member joined the group. The member will now exit the group.

`ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR` was added in 8.0.11.

- Error number: `MY-011503`; Symbol: `ER_GRP_RPL_MEMBER_CHANGE`; SQLSTATE: `HY000`

Message: Group membership changed to %s on view %s.

`ER_GRP_RPL_MEMBER_CHANGE` was added in 8.0.11.

- Error number: `MY-011504`; Symbol: `ER_GRP_RPL_MEMBER_LEFT_GRP`; SQLSTATE: `HY000`

Message: Group membership changed: This member has left the group.

`ER_GRP_RPL_MEMBER_LEFT_GRP` was added in 8.0.11.

- Error number: `MY-011505`; Symbol: `ER_GRP_RPL_MEMBER_EXPelled`; SQLSTATE: `HY000`

Message: Member was expelled from the group due to network failures, changing member status to ERROR.

`ER_GRP_RPL_MEMBER_EXPelled` was added in 8.0.11.

- Error number: `MY-011506`; Symbol: `ER_GRP_RPL_SESSION_OPEN_FAILED`; SQLSTATE: `HY000`

Message: Unable to open session to (re)set read only mode. Skipping.

`ER_GRP_RPL_SESSION_OPEN_FAILED` was added in 8.0.11.

- Error number: `MY-011507`; Symbol: `ER_GRP_RPL_NEW_PRIMARY_ELECTED`; SQLSTATE: `HY000`

Message: A new primary with address %s:%u was elected. %s

`ER_GRP_RPL_NEW_PRIMARY_ELECTED` was added in 8.0.11.

- Error number: `MY-011508`; Symbol: `ER_GRP_RPL_DISABLE_READ_ONLY_FAILED`; SQLSTATE: `HY000`

Message: Unable to disable super read only flag. Try to disable it manually

`ER_GRP_RPL_DISABLE_READ_ONLY_FAILED` was added in 8.0.11.

- Error number: `MY-011509`; Symbol: `ER_GRP_RPL_ENABLE_READ_ONLY_FAILED`; SQLSTATE: `HY000`

Message: Unable to set super read only flag. Try to set it manually.

`ER_GRP_RPL_ENABLE_READ_ONLY_FAILED` was added in 8.0.11.

- Error number: `MY-011510`; Symbol: `ER_GRP_RPL_SRV_PRIMARY_MEM`; SQLSTATE: `HY000`

Message: This server is working as primary member.

`ER_GRP_RPL_SRV_PRIMARY_MEM` was added in 8.0.11.

- Error number: `MY-011511`; Symbol: `ER_GRP_RPL_SRV_SECONDARY_MEM`; SQLSTATE: `HY000`

Message: This server is working as secondary member with primary member address %s:%u.

`ER_GRP_RPL_SRV_SECONDARY_MEM` was added in 8.0.11.

-
- Error number: [MY-011512](#); Symbol: [ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEM](#); SQLSTATE: [HY000](#)

Message: Unable to set any member as primary. No suitable candidate.

[ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEM](#) was added in 8.0.11.

- Error number: [MY-011513](#); Symbol: [ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERROR](#); SQLSTATE: [HY000](#)

Message: Error when activating super_read_only mode on start. The member will now exit the group.

[ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERROR](#) was added in 8.0.11.

- Error number: [MY-011514](#); Symbol: [ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE](#); SQLSTATE: [HY000](#)

Message: Group contains %lu members which is greater than group_replication_auto_increment_increment value of %lu. This can lead to a higher transactional abort rate.

[ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE](#) was added in 8.0.11.

- Error number: [MY-011515](#); Symbol: [ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM](#); SQLSTATE: [HY000](#)

Message: Member with address '%s:%u' didn't provide any data during the last group change. Group information can be outdated and lead to errors on recovery.

[ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM](#) was added in 8.0.11.

- Error number: [MY-011516](#); Symbol: [ER_GRP_RPL_MEMBER_ALREADY_EXISTS](#); SQLSTATE: [HY000](#)

Message: There is already a member with server_uuid %s. The member will now exit the group.

[ER_GRP_RPL_MEMBER_ALREADY_EXISTS](#) was added in 8.0.11.

- Error number: [MY-011517](#); Symbol: [ER_GRP_RPL_GRP_CHANGE_INFO_EXTRACT_ERROR](#); SQLSTATE: [HY000](#)

Message: Error when extracting information for group change. Operations and checks made to group joiners may be incomplete.

[ER_GRP_RPL_GRP_CHANGE_INFO_EXTRACT_ERROR](#) was added in 8.0.11.

- Error number: [MY-011518](#); Symbol: [ER_GRP_RPL_GTIID_EXECUTED_EXTRACT_ERROR](#); SQLSTATE: [HY000](#)

Message: Error when extracting this member GTID executed set. Operations and checks made to group joiners may be incomplete.

[ER_GRP_RPL_GTIID_EXECUTED_EXTRACT_ERROR](#) was added in 8.0.11.

- Error number: [MY-011519](#); Symbol: [ER_GRP_RPL_GTIID_SET_EXTRACT_ERROR](#); SQLSTATE: [HY000](#)

Message: Error when extracting this member retrieved set for its applier. Operations and checks made to group joiners may be incomplete.

[ER_GRP_RPL_GTIID_SET_EXTRACT_ERROR](#) was added in 8.0.11.

-
- Error number: [MY-011520](#); Symbol: [ER_GRP_RPL_START_FAILED](#); SQLSTATE: [HY000](#)

Message: The START GROUP_REPLICATION command failed since the group already has 9 members.

[ER_GRP_RPL_START_FAILED](#) was added in 8.0.11.

- Error number: [MY-011521](#); Symbol: [ER_GRP_RPL_MEMBER_VER_INCOMPATIBLE](#); SQLSTATE: [HY000](#)

Message: Member version is incompatible with the group.

[ER_GRP_RPL_MEMBER_VER_INCOMPATIBLE](#) was added in 8.0.11.

- Error number: [MY-011522](#); Symbol: [ER_GRP_RPL_TRANS_NOT_PRESENT_IN_GRP](#); SQLSTATE: [HY000](#)

Message: The member contains transactions not present in the group. The member will now exit the group.

[ER_GRP_RPL_TRANS_NOT_PRESENT_IN_GRP](#) was added in 8.0.11.

- Error number: [MY-011523](#); Symbol: [ER_GRP_RPL_TRANS_GREATER_THAN_GRP](#); SQLSTATE: [HY000](#)

Message: It was not possible to assess if the member has more transactions than the group. The member will now exit the group.

[ER_GRP_RPL_TRANS_GREATER_THAN_GRP](#) was added in 8.0.11.

- Error number: [MY-011524](#); Symbol: [ER_GRP_RPL_MEMBER_VERSION_LOWER_THAN_GRP](#); SQLSTATE: [HY000](#)

Message: Member version is lower than some group member, but since option 'group_replication_allow_local_lower_version_join' is enabled, member will be allowed to join.

[ER_GRP_RPL_MEMBER_VERSION_LOWER_THAN_GRP](#) was added in 8.0.11.

- Error number: [MY-011525](#); Symbol: [ER_GRP_RPL_LOCAL_GTID_SETS_PROCESS_ERROR](#); SQLSTATE: [HY000](#)

Message: Error processing local GTID sets when comparing this member transactions against the group.

[ER_GRP_RPL_LOCAL_GTID_SETS_PROCESS_ERROR](#) was added in 8.0.11.

- Error number: [MY-011526](#); Symbol: [ER_GRP_RPL_MEMBER_TRANS_GREATER_THAN_GRP](#); SQLSTATE: [HY000](#)

Message: This member has more executed transactions than those present in the group. Local transactions: %s > Group transactions: %s

[ER_GRP_RPL_MEMBER_TRANS_GREATER_THAN_GRP](#) was added in 8.0.11.

- Error number: [MY-011527](#); Symbol: [ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP](#); SQLSTATE: [HY000](#)

Message: The member is configured with a group_replication_gtid_assignment_block_size option value '%llu' different from the group '%llu'. The member will now exit the group.

[ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP](#) was added in 8.0.11.

-
- Error number: [MY-011528](#); Symbol: [ER_GRP_RPL_TRANS_WRITE_SET_EXTRACT_DIFF_FROM_GRP](#); SQLSTATE: HY000

Message: The member is configured with a transaction-write-set-extraction option value '%s' different from the group '%s'. The member will now exit the group.

[ER_GRP_RPL_TRANS_WRITE_SET_EXTRACT_DIFF_FROM_GRP](#) was added in 8.0.11.

- Error number: [MY-011529](#); Symbol: [ER_GRP_RPL_MEMBER_CFG_INCOMPATIBLE_WITH_GRP_CFG](#); SQLSTATE: HY000

Message: The member configuration is not compatible with the group configuration. Variables such as group_replication_single_primary_mode or group_replication_enforce_update_everywhere_checks must have the same value on every server in the group. (member configuration option: [%s], group configuration option: [%s]).

[ER_GRP_RPL_MEMBER_CFG_INCOMPATIBLE_WITH_GRP_CFG](#) was added in 8.0.11.

- Error number: [MY-011530](#); Symbol: [ER_GRP_RPL_MEMBER_STOP_RPL_CHANNELS_ERROR](#); SQLSTATE: HY000

Message: Error stopping all replication channels while server was leaving the group. %s

[ER_GRP_RPL_MEMBER_STOP_RPL_CHANNELS_ERROR](#) was added in 8.0.11.

- Error number: [MY-011531](#); Symbol: [ER_GRP_RPL_PURGE_APPLIER_LOGS](#); SQLSTATE: HY000

Message: Detected previous RESET MASTER invocation or an issue exists in the group replication applier relay log. Purging existing applier logs.

[ER_GRP_RPL_PURGE_APPLIER_LOGS](#) was added in 8.0.11.

- Error number: [MY-011532](#); Symbol: [ER_GRP_RPL_RESET_APPLIER_MODULE_LOGS_ERROR](#); SQLSTATE: HY000

Message: Unknown error occurred while resetting applier's module logs.

[ER_GRP_RPL_RESET_APPLIER_MODULE_LOGS_ERROR](#) was added in 8.0.11.

- Error number: [MY-011533](#); Symbol: [ER_GRP_RPL_APPLIER_THD_SETUP_ERROR](#); SQLSTATE: HY000

Message: Failed to setup the group replication applier thread.

[ER_GRP_RPL_APPLIER_THD_SETUP_ERROR](#) was added in 8.0.11.

- Error number: [MY-011534](#); Symbol: [ER_GRP_RPL_APPLIER_THD_START_ERROR](#); SQLSTATE: HY000

Message: Error while starting the group replication applier thread

[ER_GRP_RPL_APPLIER_THD_START_ERROR](#) was added in 8.0.11.

- Error number: [MY-011535](#); Symbol: [ER_GRP_RPL_APPLIER_THD_STOP_ERROR](#); SQLSTATE: HY000

Message: Failed to stop the group replication applier thread.

[ER_GRP_RPL_APPLIER_THD_STOP_ERROR](#) was added in 8.0.11.

- Error number: [MY-011536](#); Symbol: [ER_GRP_RPL_FETCH_TRANS_DATA_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to fetch transaction data containing required transaction info for applier

[ER_GRP_RPL_FETCH_TRANS_DATA_FAILED](#) was added in 8.0.11.

- Error number: [MY-011537](#); Symbol: [ER_GRP_RPL_SLAVE_IO_THD_PRIMARY_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: Can't start slave IO THREAD of channel '%s' when group replication is running with single-primary mode and the primary member is not known.

[ER_GRP_RPL_SLAVE_IO_THD_PRIMARY_UNKNOWN](#) was added in 8.0.11.

- Error number: [MY-011538](#); Symbol: [ER_GRP_RPL_SLAVE_IO_THD_ON_SECONDARY_MEMBER](#); SQLSTATE: [HY000](#)

Message: Can't start slave IO THREAD of channel '%s' when group replication is running with single-primary mode on a secondary member.

[ER_GRP_RPL_SLAVE_IO_THD_ON_SECONDARY_MEMBER](#) was added in 8.0.11.

- Error number: [MY-011539](#); Symbol: [ER_GRP_RPL_SLAVE_SQL_THD_PRIMARY_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: Can't start slave SQL THREAD of channel '%s' when group replication is running with single-primary mode and the primary member is not known.

[ER_GRP_RPL_SLAVE_SQL_THD_PRIMARY_UNKNOWN](#) was added in 8.0.11.

- Error number: [MY-011540](#); Symbol: [ER_GRP_RPL_SLAVE_SQL_THD_ON_SECONDARY_MEMBER](#); SQLSTATE: [HY000](#)

Message: Can't start slave SQL THREAD of channel '%s' when group replication is running with single-primary mode on a secondary member.

[ER_GRP_RPL_SLAVE_SQL_THD_ON_SECONDARY_MEMBER](#) was added in 8.0.11.

- Error number: [MY-011541](#); Symbol: [ER_GRP_RPL_NEEDS_INNODB_TABLE](#); SQLSTATE: [HY000](#)

Message: Table %s does not use the InnoDB storage engine. This is not compatible with Group Replication.

[ER_GRP_RPL_NEEDS_INNODB_TABLE](#) was added in 8.0.11.

- Error number: [MY-011542](#); Symbol: [ER_GRP_RPL_PRIMARY_KEY_NOT_DEFINED](#); SQLSTATE: [HY000](#)

Message: Table %s does not have any PRIMARY KEY. This is not compatible with Group Replication.

[ER_GRP_RPL_PRIMARY_KEY_NOT_DEFINED](#) was added in 8.0.11.

- Error number: [MY-011543](#); Symbol: [ER_GRP_RPL_FK_WITH CASCADE_UNSUPPORTED](#); SQLSTATE: [HY000](#)

Message: Table %s has a foreign key with 'CASCADE', 'SET NULL' or 'SET DEFAULT' clause. This is not compatible with Group Replication.

[ER_GRP_RPL_FK_WITH CASCADE_UNSUPPORTED](#) was added in 8.0.11.

- Error number: [MY-011544](#); Symbol: [ER_GRP_RPL_AUTO_INC_RESET](#); SQLSTATE: [HY000](#)

Message: group_replication_auto_increment_increment is reset to %lu

`ER_GRP_RPL_AUTO_INC_RESET` was added in 8.0.11.

- Error number: `MY-011545`; Symbol: `ER_GRP_RPL_AUTO_INC_OFFSET_RESET`; SQLSTATE: `HY000`

Message: auto_increment_offset is reset to %lu

`ER_GRP_RPL_AUTO_INC_OFFSET_RESET` was added in 8.0.11.

- Error number: `MY-011546`; Symbol: `ER_GRP_RPL_AUTO_INC_SET`; SQLSTATE: `HY000`

Message: group_replication_auto_increment_increment is set to %lu

`ER_GRP_RPL_AUTO_INC_SET` was added in 8.0.11.

- Error number: `MY-011547`; Symbol: `ER_GRP_RPL_AUTO_INC_OFFSET_SET`; SQLSTATE: `HY000`

Message: auto_increment_offset is set to %lu

`ER_GRP_RPL_AUTO_INC_OFFSET_SET` was added in 8.0.11.

- Error number: `MY-011548`; Symbol: `ER_GRP_RPL_FETCH_TRANS_CONTEXT_FAILED`; SQLSTATE: `HY000`

Message: Failed to fetch transaction context containing required transaction info for certification

`ER_GRP_RPL_FETCH_TRANS_CONTEXT_FAILED` was added in 8.0.11.

- Error number: `MY-011549`; Symbol: `ER_GRP_RPL_FETCH_FORMAT_DESC_LOG_EVENT_FAILED`; SQLSTATE: `HY000`

Message: Failed to fetch Format_description_log_event containing required server info for applier

`ER_GRP_RPL_FETCH_FORMAT_DESC_LOG_EVENT_FAILED` was added in 8.0.11.

- Error number: `MY-011550`; Symbol:

`ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FAILED`; SQLSTATE: `HY000`

Message: Failed to fetch Transaction_context_log_event containing required transaction info for certification

`ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FAILED` was added in 8.0.11.

- Error number: `MY-011551`; Symbol: `ER_GRP_RPL_FETCH_SNAPSHOT_VERSION_FAILED`; SQLSTATE: `HY000`

Message: Failed to read snapshot version from transaction context event required for certification

`ER_GRP_RPL_FETCH_SNAPSHOT_VERSION_FAILED` was added in 8.0.11.

- Error number: `MY-011552`; Symbol: `ER_GRP_RPL_FETCH_GTID_LOG_EVENT_FAILED`; SQLSTATE: `HY000`

Message: Failed to fetch Gtid_log_event containing required transaction info for certification

`ER_GRP_RPL_FETCH_GTID_LOG_EVENT_FAILED` was added in 8.0.11.

- Error number: `MY-011553`; Symbol: `ER_GRP_RPL_UPDATE_SERV_CERTIFICATE_FAILED`; SQLSTATE: `HY000`

Message: Unable to update certification result on server side, thread_id: %lu

`ER_GRP_RPL_UPDATE_SERV_CERTIFICATE_FAILED` was added in 8.0.11.

- Error number: `MY-011554`; Symbol:

`ER_GRP_RPL_ADD_GTID_INFO_WITH_LOCAL_GTID_FAILED`; SQLSTATE: `HY000`

Message: Unable to add gtid information to the group_gtid_executed set when gtid was provided for local transactions

`ER_GRP_RPL_ADD_GTID_INFO_WITH_LOCAL_GTID_FAILED` was added in 8.0.11.

- Error number: `MY-011555`; Symbol:

`ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_LOCAL_GTID_FAILED`; SQLSTATE: `HY000`

Message: Unable to add gtid information to the group_gtid_executed set when no gtid was provided for local transactions

`ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_LOCAL_GTID_FAILED` was added in 8.0.11.

- Error number: `MY-011556`; Symbol: `ER_GRP_RPL_NOTIFY_CERTIFICATION_OUTCOME_FAILED`; SQLSTATE: `HY000`

Message: Failed to notify certification outcome

`ER_GRP_RPL_NOTIFY_CERTIFICATION_OUTCOME_FAILED` was added in 8.0.11.

- Error number: `MY-011557`; Symbol:

`ER_GRP_RPL_ADD_GTID_INFO_WITH_REMOTE_GTID_FAILED`; SQLSTATE: `HY000`

Message: Unable to add gtid information to the group_gtid_executed set when gtid was provided for remote transactions

`ER_GRP_RPL_ADD_GTID_INFO_WITH_REMOTE_GTID_FAILED` was added in 8.0.11.

- Error number: `MY-011558`; Symbol:

`ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTID_FAILED`; SQLSTATE: `HY000`

Message: Unable to add gtid information to the group_gtid_executed set when gtid was not provided for remote transactions

`ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTID_FAILED` was added in 8.0.11.

- Error number: `MY-011559`; Symbol: `ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_FAILED`; SQLSTATE: `HY000`

Message: Failed to fetch View_change_log_event containing required info for certification

`ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_FAILED` was added in 8.0.11.

- Error number: `MY-011560`; Symbol: `ER_GRP_RPL_CONTACT_WITH_SRV_FAILED`; SQLSTATE: `HY000`

Message: Error when contacting the server to ensure the proper logging of a group change in the binlog

`ER_GRP_RPL_CONTACT_WITH_SRV_FAILED` was added in 8.0.11.

- Error number: `MY-011561`; Symbol: `ER_GRP_RPL_SRV_WAIT_TIME_OUT`; SQLSTATE: `HY000`

Message: Timeout when waiting for the server to execute local transactions in order assure the group change proper logging

`ER_GRP_RPL_SRV_WAIT_TIME_OUT` was added in 8.0.11.

-
- Error number: [MY-011562](#); Symbol: [ER_GRP_RPL_FETCH_LOG_EVENT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to fetch Log_event containing required server info for applier
[ER_GRP_RPL_FETCH_LOG_EVENT_FAILED](#) was added in 8.0.11.
 - Error number: [MY-011563](#); Symbol: [ER_GRP_RPL_START_GRP_RPL_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to start Group Replication. Replication applier infrastructure is not initialized since the server was started with --initialize, --initialize-insecure or --upgrade=MINIMAL on a server upgrade.
[ER_GRP_RPL_START_GRP_RPL_FAILED](#) was added in 8.0.11.
 - Error number: [MY-011564](#); Symbol: [ER_GRP_RPL_CONN_INTERNAL_PLUGIN_FAIL](#); SQLSTATE: [HY000](#)

Message: Failed to establish an internal server connection to execute plugin operations
[ER_GRP_RPL_CONN_INTERNAL_PLUGIN_FAIL](#) was added in 8.0.11.
 - Error number: [MY-011565](#); Symbol: [ER_GRP_RPL_SUPER_READ_ON](#); SQLSTATE: [HY000](#)

Message: Setting super_read_only=ON.
[ER_GRP_RPL_SUPER_READ_ON](#) was added in 8.0.11.
 - Error number: [MY-011566](#); Symbol: [ER_GRP_RPL_SUPER_READ_OFF](#); SQLSTATE: [HY000](#)

Message: Setting super_read_only=OFF.
[ER_GRP_RPL_SUPER_READ_OFF](#) was added in 8.0.11.
 - Error number: [MY-011567](#); Symbol: [ER_GRP_RPL_KILLED_SESSION_ID](#); SQLSTATE: [HY000](#)

Message: killed session id: %d status: %d
[ER_GRP_RPL_KILLED_SESSION_ID](#) was added in 8.0.11.
 - Error number: [MY-011568](#); Symbol: [ER_GRP_RPL_KILLED_FAILED_ID](#); SQLSTATE: [HY000](#)

Message: killed failed id: %d failed: %d
[ER_GRP_RPL_KILLED_FAILED_ID](#) was added in 8.0.11.
 - Error number: [MY-011569](#); Symbol: [ER_GRP_RPL_INTERNAL_QUERY](#); SQLSTATE: [HY000](#)

Message: Internal query: %s result in error. Error number: %ld
[ER_GRP_RPL_INTERNAL_QUERY](#) was added in 8.0.11.
 - Error number: [MY-011570](#); Symbol: [ER_GRP_RPL_COPY_FROM_EMPTY_STRING](#); SQLSTATE: [HY000](#)

Message: Error copying from empty string
[ER_GRP_RPL_COPY_FROM_EMPTY_STRING](#) was added in 8.0.11.
 - Error number: [MY-011571](#); Symbol: [ER_GRP_RPL_QUERY_FAIL](#); SQLSTATE: [HY000](#)

Message: Query execution resulted in failure. errno: %d
[ER_GRP_RPL_QUERY_FAIL](#) was added in 8.0.11.

- Error number: [MY-011572](#); Symbol: [ER_GRP_RPL_CREATE_SESSION_UNABLE](#); SQLSTATE: [HY000](#)

Message: Unable to create a session for executing the queries on the server
[ER_GRP_RPL_CREATE_SESSION_UNABLE](#) was added in 8.0.11.
- Error number: [MY-011573](#); Symbol: [ER_GRP_RPL_MEMBER_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: The member with address %s:%u has unexpectedly disappeared, killing the current group replication recovery connection
[ER_GRP_RPL_MEMBER_NOT_FOUND](#) was added in 8.0.11.
- Error number: [MY-011574](#); Symbol: [ER_GRP_RPL_MAXIMUM_CONNECTION_RETRIES_REACHED](#); SQLSTATE: [HY000](#)

Message: Maximum number of retries when trying to connect to a donor reached. Aborting group replication incremental recovery.
[ER_GRP_RPL_MAXIMUM_CONNECTION_RETRIES_REACHED](#) was added in 8.0.11.
- Error number: [MY-011575](#); Symbol: [ER_GRP_RPL_ALL_DONORS_LEFT_ABORT_RECOVERY](#); SQLSTATE: [HY000](#)

Message: All donors left. Aborting group replication incremental recovery.
[ER_GRP_RPL_ALL_DONORS_LEFT_ABORT_RECOVERY](#) was added in 8.0.11.
- Error number: [MY-011576](#); Symbol: [ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_DONOR](#); SQLSTATE: [HY000](#)

Message: Establishing group recovery connection with a possible donor. Attempt %d/%d
[ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_DONOR](#) was added in 8.0.11.
- Error number: [MY-011577](#); Symbol: [ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHER_DONOR](#); SQLSTATE: [HY000](#)

Message: Retrying group recovery connection with another donor. Attempt %d/%d
[ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHER_DONOR](#) was added in 8.0.11.
- Error number: [MY-011578](#); Symbol: [ER_GRP_RPL_NO_VALID_DONOR](#); SQLSTATE: [HY000](#)

Message: No valid donors exist in the group, retrying
[ER_GRP_RPL_NO_VALID_DONOR](#) was added in 8.0.11.
- Error number: [MY-011579](#); Symbol: [ER_GRP_RPL_CONFIG_RECOVERY](#); SQLSTATE: [HY000](#)

Message: Error when configuring the asynchronous recovery channel connection to the donor.
[ER_GRP_RPL_CONFIG_RECOVERY](#) was added in 8.0.11.
- Error number: [MY-011580](#); Symbol: [ER_GRP_RPL_ESTABLISHING_CONN_GRP_REC_DONOR](#); SQLSTATE: [HY000](#)

Message: Establishing connection to a group replication recovery donor %s at %s port: %d.
[ER_GRP_RPL_ESTABLISHING_CONN_GRP_REC_DONOR](#) was added in 8.0.11.
- Error number: [MY-011581](#); Symbol: [ER_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Error while creating the group replication recovery channel with donor %s at %s port: %d.

[ER_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL](#) was added in 8.0.11.

- Error number: [MY-011582](#); Symbol: [ER_GRP_RPL_DONOR_SERVER_CONN](#); SQLSTATE: [HY000](#)

Message: There was an error when connecting to the donor server. Please check that group_replication_recovery channel credentials and all MEMBER_HOST column values of performance_schema.replication_group_members table are correct and DNS resolvable.

[ER_GRP_RPL_DONOR_SERVER_CONN](#) was added in 8.0.11.

- Error number: [MY-011583](#); Symbol: [ER_GRP_RPL_CHECK_STATUS_TABLE](#); SQLSTATE: [HY000](#)

Message: For details please check performance_schema.replication_connection_status table and error log messages of Slave I/O for channel group_replication_recovery.

[ER_GRP_RPL_CHECK_STATUS_TABLE](#) was added in 8.0.11.

- Error number: [MY-011584](#); Symbol: [ER_GRP_RPL_STARTING_GRP_REC](#); SQLSTATE: [HY000](#)

Message: Error while starting the group replication incremental recovery receiver/appplier threads

[ER_GRP_RPL_STARTING_GRP_REC](#) was added in 8.0.11.

- Error number: [MY-011585](#); Symbol: [ER_GRP_RPL_DONOR_CONN_TERMINATION](#); SQLSTATE: [HY000](#)

Message: Terminating existing group replication donor connection and purging the corresponding logs.

[ER_GRP_RPL_DONOR_CONN_TERMINATION](#) was added in 8.0.11.

- Error number: [MY-011586](#); Symbol: [ER_GRP_RPL_STOPPING_GRP_REC](#); SQLSTATE: [HY000](#)

Message: Error when stopping the group replication incremental recovery's donor connection

[ER_GRP_RPL_STOPPING_GRP_REC](#) was added in 8.0.11.

- Error number: [MY-011587](#); Symbol: [ER_GRP_RPL_PURGE_REC](#); SQLSTATE: [HY000](#)

Message: Error when purging the group replication recovery's relay logs

[ER_GRP_RPL_PURGE_REC](#) was added in 8.0.11.

- Error number: [MY-011588](#); Symbol: [ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_APPLIER](#); SQLSTATE: [HY000](#)

Message: Unable to kill the current group replication recovery donor connection after an applier error. Incremental recovery will shutdown.

[ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_APPLIER](#) was added in 8.0.11.

- Error number: [MY-011589](#); Symbol: [ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_FAILOVER](#); SQLSTATE: [HY000](#)

Message: Unable to kill the current group replication recovery donor connection during failover. Incremental recovery will shutdown.

[ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_FAILOVER](#) was added in 8.0.11.

- Error number: [MY-011590](#); Symbol: [ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_EVENT](#); SQLSTATE: [HY000](#)

Message: Unexpected error when notifying an internal component named %s regarding a group membership event.

`ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_EVENT` was added in 8.0.11.

- Error number: `MY-011591`; Symbol: `ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBERSHIP_NOTIFICATION`; SQLSTATE: `HY000`

Message: An undefined error was found while broadcasting an internal group membership notification! This is likely to happen if your components or plugins are not properly loaded or are malfunctioning!

`ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBERSHIP_NOTIFICATION` was added in 8.0.11.

- Error number: `MY-011592`; Symbol: `ER_GRP_RPL_FAILED_TO_BROADCAST_MEMBER_STATUS_NOTIFICATION`; SQLSTATE: `HY000`

Message: An undefined error was found while broadcasting an internal group member status notification! This is likely to happen if your components or plugins are not properly loaded or are malfunctioning!

`ER_GRP_RPL_FAILED_TO_BROADCAST_MEMBER_STATUS_NOTIFICATION` was added in 8.0.11.

- Error number: `MY-011593`; Symbol: `ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFICATION_HASH`; SQLSTATE: `HY000`

Message: No memory to generate write identification hash

`ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFICATION_HASH` was added in 8.0.11.

- Error number: `MY-011594`; Symbol: `ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODING_FAILED`; SQLSTATE: `HY000`

Message: Base 64 encoding of the write identification hash failed

`ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODING_FAILED` was added in 8.0.11.

- Error number: `MY-011595`; Symbol: `ER_GRP_RPL_INVALID_BINLOG_FORMAT`; SQLSTATE: `HY000`

Message: Binlog format should be ROW for Group Replication

`ER_GRP_RPL_INVALID_BINLOG_FORMAT` was added in 8.0.11.

- Error number: `MY-011596`; Symbol: `ER_GRP_RPL_BINLOG_CHECKSUM_SET`; SQLSTATE: `HY000`

Message: binlog_checksum should be NONE for Group Replication

`ER_GRP_RPL_BINLOG_CHECKSUM_SET` was added in 8.0.11, removed after 8.0.20.

- Error number: `MY-011597`; Symbol: `ER_GRP_RPL_TRANS_WRITE_SET_EXTRACTION_NOT_SET`; SQLSTATE: `HY000`

Message: A transaction_write_set_extraction algorithm should be selected when running Group Replication

`ER_GRP_RPL_TRANS_WRITE_SET_EXTRACTION_NOT_SET` was added in 8.0.11.

-
- Error number: `MY-011598`; Symbol: `ER_GRP_RPL_UNSUPPORTED_TRANS_ISOLATION`; SQLSTATE: `HY000`

Message: Transaction isolation level (tx_isolation) is set to SERIALIZABLE, which is not compatible with Group Replication

`ER_GRP_RPL_UNSUPPORTED_TRANS_ISOLATION` was added in 8.0.11.

- Error number: `MY-011599`; Symbol: `ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPING`; SQLSTATE: `HY000`

Message: Transaction cannot be executed while Group Replication is stopping.

`ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPING` was added in 8.0.11.

- Error number: `MY-011600`; Symbol: `ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_RECOVERING`; SQLSTATE: `HY000`

Message: Transaction cannot be executed while Group Replication is recovering. Try again when the server is ONLINE.

`ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_RECOVERING` was added in 8.0.11.

- Error number: `MY-011601`; Symbol: `ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_ERROR_STATE`; SQLSTATE: `HY000`

Message: Transaction cannot be executed while Group Replication is on ERROR state. Check for errors and restart the plugin

`ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_ERROR_STATE` was added in 8.0.11.

- Error number: `MY-011602`; Symbol: `ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_OFFLINE_MODE`; SQLSTATE: `HY000`

Message: Transaction cannot be executed while Group Replication is OFFLINE. Check for errors and restart the plugin

`ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_OFFLINE_MODE` was added in 8.0.11.

- Error number: `MY-011603`; Symbol: `ER_GRP_RPL_MULTIPLE_CACHE_TYPE_NOT_SUPPORTED_FOR_SESSION`; SQLSTATE: `HY000`

Message: We can only use one cache type at a time on session %u

`ER_GRP_RPL_MULTIPLE_CACHE_TYPE_NOT_SUPPORTED_FOR_SESSION` was added in 8.0.11.

- Error number: `MY-011604`; Symbol: `ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_FOR_READ`; SQLSTATE: `HY000`

Message: Failed to reinit binlog cache log for read on session %u

`ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_FOR_READ` was added in 8.0.11.

- Error number: `MY-011605`; Symbol: `ER_GRP_RPL_FAILED_TO_CREATE_TRANS_CONTEXT`; SQLSTATE: `HY000`

Message: Failed to create the context of the current transaction on session %u

`ER_GRP_RPL_FAILED_TO_CREATE_TRANS_CONTEXT` was added in 8.0.11.

- Error number: [MY-011606](#); Symbol: [ER_GRP_RPL_FAILED_TO_EXTRACT_TRANS_WRITE_SET](#); SQLSTATE: [HY000](#)

Message: Failed to extract the set of items written during the execution of the current transaction on session %u

[ER_GRP_RPL_FAILED_TO_EXTRACT_TRANS_WRITE_SET](#) was added in 8.0.11.

- Error number: [MY-011607](#); Symbol: [ER_GRP_RPL_FAILED_TO_GATHER_TRANS_WRITE_SET](#); SQLSTATE: [HY000](#)

Message: Failed to gather the set of items written during the execution of the current transaction on session %u

[ER_GRP_RPL_FAILED_TO_GATHER_TRANS_WRITE_SET](#) was added in 8.0.11.

- Error number: [MY-011608](#); Symbol: [ER_GRP_RPL_TRANS_SIZE_EXCEEDS_LIMIT](#); SQLSTATE: [HY000](#)

Message: Error on session %u. Transaction of size %lu exceeds specified limit %lu. To increase the limit please adjust group_replication_transaction_size_limit option.

[ER_GRP_RPL_TRANS_SIZE_EXCEEDS_LIMIT](#) was added in 8.0.11.

- Error number: [MY-011609](#); Symbol: [ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_READ_FAILED](#); SQLSTATE: [HY000](#)

Message: Error while re-initializing an internal cache, for read operations, on session %u

[ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_READ_FAILED](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011610](#); Symbol: [ER_GRP_RPL_APPENDING_DATA_TO_INTERNAL_CACHE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error while appending data to an internal cache on session %u

[ER_GRP_RPL_APPENDING_DATA_TO_INTERNAL_CACHE_FAILED](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011611](#); Symbol: [ER_GRP_RPL_WRITE_TO_BINLOG_CACHE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error while writing binary log cache on session %u

[ER_GRP_RPL_WRITE_TO_BINLOG_CACHE_FAILED](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011611](#); Symbol: [ER_GRP_RPL_WRITE_TO_TRANSACTION_MESSAGE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error while writing to transaction message on session %u

[ER_GRP_RPL_WRITE_TO_TRANSACTION_MESSAGE_FAILED](#) was added in 8.0.13.

- Error number: [MY-011612](#); Symbol: [ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME_NOTIFICATION](#); SQLSTATE: [HY000](#)

Message: Unable to register for getting notifications regarding the outcome of the transaction on session %u

[ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME_NOTIFICATION](#) was added in 8.0.11.

- Error number: [MY-011613](#); Symbol: [ER_GRP_RPL_MSG_TOO_LONG_BROADCASTING_TRANS_FAILED](#); SQLSTATE: [HY000](#)

Message: Error broadcasting transaction to the group on session %u. Message is too big.
[ER_GRP_RPL_MSG_TOO_LONG_BROADCASTING_TRANS_FAILED](#) was added in 8.0.11.
- Error number: [MY-011614](#); Symbol: [ER_GRP_RPL_BROADCASTING_TRANS_TO_GRP_FAILED](#); SQLSTATE: [HY000](#)

Message: Error while broadcasting the transaction to the group on session %u
[ER_GRP_RPL_BROADCASTING_TRANS_TO_GRP_FAILED](#) was added in 8.0.11.
- Error number: [MY-011615](#); Symbol: [ER_GRP_RPL_ERROR_WHILE_WAITING_FOR_CONFLICT_DETECTION](#); SQLSTATE: [HY000](#)

Message: Error while waiting for conflict detection procedure to finish on session %u
[ER_GRP_RPL_ERROR_WHILE_WAITING_FOR_CONFLICT_DETECTION](#) was added in 8.0.11.
- Error number: [MY-011616](#); Symbol: [ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_WRITE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error while re-initializing an internal cache, for write operations, on session %u
[ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_WRITE_FAILED](#) was added in 8.0.11, removed after 8.0.12.
- Error number: [MY-011617](#); Symbol: [ER_GRP_RPL_FAILED_TO_CREATE_COMMIT_CACHE](#); SQLSTATE: [HY000](#)

Message: Failed to create group replication commit cache on session %u
[ER_GRP_RPL_FAILED_TO_CREATE_COMMIT_CACHE](#) was added in 8.0.11, removed after 8.0.12.
- Error number: [MY-011618](#); Symbol: [ER_GRP_RPL_REINIT_OF_COMMIT_CACHE_FOR_WRITE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to reinit group replication commit cache for write on session %u
[ER_GRP_RPL_REINIT_OF_COMMIT_CACHE_FOR_WRITE_FAILED](#) was added in 8.0.11, removed after 8.0.12.
- Error number: [MY-011619](#); Symbol: [ER_GRP_RPL_PREV_REC_SESSION_RUNNING](#); SQLSTATE: [HY000](#)

Message: A previous recovery session is still running. Please stop the group replication plugin and wait for it to stop
[ER_GRP_RPL_PREV_REC_SESSION_RUNNING](#) was added in 8.0.11, removed after 8.0.22.
- Error number: [MY-011620](#); Symbol: [ER_GRP_RPL_FATAL_REC_PROCESS](#); SQLSTATE: [HY000](#)

Message: Fatal error during the incremental recovery process of Group Replication. The server will leave the group.
[ER_GRP_RPL_FATAL_REC_PROCESS](#) was added in 8.0.11.
- Error number: [MY-011621](#); Symbol: [ER_GRP_RPL WHILE STOPPING REP CHANNEL](#); SQLSTATE: [HY000](#)

Message: Error stopping all replication channels while server was leaving the group. %s

`ER_GRP_RPL_WHILE_STOPPING_REP_CHANNEL` was added in 8.0.11, removed after 8.0.17.

- Error number: `MY-011622`; Symbol: `ER_GRP_RPL_UNABLE_TO_EVALUATE_APPLIER_STATUS`; SQLSTATE: `HY000`

Message: Unable to evaluate the group replication applier execution status. Group replication recovery will shutdown to avoid data corruption.

`ER_GRP_RPL_UNABLE_TO_EVALUATE_APPLIER_STATUS` was added in 8.0.11.

- Error number: `MY-011623`; Symbol: `ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE`; SQLSTATE: `HY000`

Message: Only one server alive. Declaring this server as online within the replication group

`ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE` was added in 8.0.11.

- Error number: `MY-011624`; Symbol: `ER_GRP_RPL_CERTIFICATION_REC_PROCESS`; SQLSTATE: `HY000`

Message: Error when processing certification information in the incremental recovery process

`ER_GRP_RPL_CERTIFICATION_REC_PROCESS` was added in 8.0.11.

- Error number: `MY-011625`; Symbol: `ER_GRP_RPL_UNABLE_TO_ENSURE_EXECUTION_REC`; SQLSTATE: `HY000`

Message: Unable to ensure the execution of group transactions received during recovery.

`ER_GRP_RPL_UNABLE_TO_ENSURE_EXECUTION_REC` was added in 8.0.11.

- Error number: `MY-011626`; Symbol: `ER_GRP_RPL_WHILE_SENDING_MSG_REC`; SQLSTATE: `HY000`

Message: Error while sending message in the group replication incremental recovery process.

`ER_GRP_RPL_WHILE_SENDING_MSG_REC` was added in 8.0.11.

- Error number: `MY-011627`; Symbol: `ER_GRP_RPL_READ_UNABLE_FOR_SUPER_READ_ONLY`; SQLSTATE: `HY000`

Message: Unable to read the server value for the super_read_only variable.

`ER_GRP_RPL_READ_UNABLE_FOR_SUPER_READ_ONLY` was added in 8.0.11.

- Error number: `MY-011628`; Symbol: `ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY_SUPER_READ_ONLY`; SQLSTATE: `HY000`

Message: Unable to read the server values for the read_only and super_read_only variables.

`ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY_SUPER_READ_ONLY` was added in 8.0.11.

- Error number: `MY-011629`; Symbol: `ER_GRP_RPL_UNABLE_TO_RESET_SERVER_READ_MODE`; SQLSTATE: `HY000`

Message: Unable to reset the server read mode settings. Try to reset them manually.

`ER_GRP_RPL_UNABLE_TO_RESET_SERVER_READ_MODE` was added in 8.0.11.

- Error number: `MY-011630`; Symbol: `ER_GRP_RPL_UNABLE_TO_CERTIFY_PLUGIN_TRANS`; SQLSTATE: `HY000`

Message: Due to a plugin error, some transactions were unable to be certified and will now rollback.

`ER_GRP_RPL_UNABLE_TO_CERTIFY_PLUGIN_TRANS` was added in 8.0.11.

- Error number: `MY-011631`; Symbol: `ER_GRP_RPL_UNBLOCK_CERTIFIED_TRANS`; SQLSTATE: `HY000`

Message: Error when trying to unblock non certified or consistent transactions. Check for consistency errors when restarting the service

`ER_GRP_RPL_UNBLOCK_CERTIFIED_TRANS` was added in 8.0.11.

- Error number: `MY-011632`; Symbol: `ER_GRP_RPL_SERVER_WORKING_AS_SECONDARY`; SQLSTATE: `HY000`

Message: This server is working as secondary member with primary member address %s:%u.

`ER_GRP_RPL_SERVER_WORKING_AS_SECONDARY` was added in 8.0.11, removed after 8.0.20.

- Error number: `MY-011633`; Symbol: `ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER_ID`; SQLSTATE: `HY000`

Message: Unable to start Group Replication. Replication applier infrastructure is not initialized since the server was started with `server_id=0`. Please, restart the server with `server_id` larger than 0.

`ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER_ID` was added in 8.0.11.

- Error number: `MY-011634`; Symbol: `ER_GRP_RPL_FORCE_MEMBERS_MUST_BE_EMPTY`; SQLSTATE: `HY000`

Message: `group_replication_force_members` must be empty on group start. Current value: '%s'

`ER_GRP_RPL_FORCE_MEMBERS_MUST_BE_EMPTY` was added in 8.0.11.

- Error number: `MY-011635`; Symbol: `ER_GRP_RPL_PLUGIN_STRUCT_INIT_NOT_POSSIBLE_ON_SERVER_START`; SQLSTATE: `HY000`

Message: It was not possible to guarantee the initialization of plugin structures on server start

`ER_GRP_RPL_PLUGIN_STRUCT_INIT_NOT_POSSIBLE_ON_SERVER_START` was added in 8.0.11.

- Error number: `MY-011636`; Symbol: `ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY_MODE`; SQLSTATE: `HY000`

Message: Could not enable the server read only mode and guarantee a safe recovery execution

`ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY_MODE` was added in 8.0.11.

- Error number: `MY-011637`; Symbol: `ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGINE`; SQLSTATE: `HY000`

Message: Error on group communication engine initialization

`ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGINE` was added in 8.0.11.

- Error number: `MY-011638`; Symbol: `ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_WITH_ASYNC_CHANNELS`; SQLSTATE: `HY000`

Message: Can't start group replication on secondary member with single-primary mode while asynchronous replication channels are running.

`ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_WITH_ASYNC_CHANNELS` was added in 8.0.11.

- Error number: [MY-011639](#); Symbol: [ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_ENGINE](#); SQLSTATE: [HY000](#)

Message: Error on group communication engine start
[ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_ENGINE](#) was added in 8.0.11.
- Error number: [MY-011640](#); Symbol: [ER_GRP_RPL_TIMEOUT_ON_VIEW_AFTER_JOINING_GRP](#); SQLSTATE: [HY000](#)

Message: Timeout on wait for view after joining group
[ER_GRP_RPL_TIMEOUT_ON_VIEW_AFTER_JOINING_GRP](#) was added in 8.0.11.
- Error number: [MY-011641](#); Symbol: [ER_GRP_RPL_FAILED_TO_CALL_GRP_COMMUNICATION_INTERFACE](#); SQLSTATE: [HY000](#)

Message: Error calling group communication interfaces
[ER_GRP_RPL_FAILED_TO_CALL_GRP_COMMUNICATION_INTERFACE](#) was added in 8.0.11.
- Error number: [MY-011642](#); Symbol: [ER_GRP_RPL_MEMBER_SERVER_UUID_IS_INCOMPATIBLE_WITH_GRP](#); SQLSTATE: [HY000](#)

Message: Member server_uuid is incompatible with the group. Server_uuid %s matches group_replication_group_name %s.
[ER_GRP_RPL_MEMBER_SERVER_UUID_IS_INCOMPATIBLE_WITH_GRP](#) was added in 8.0.11.
- Error number: [MY-011643](#); Symbol: [ER_GRP_RPL_MEMBER_CONF_INFO](#); SQLSTATE: [HY000](#)

Message: Member configuration: member_id: %lu; member_uuid: "%s"; single-primary mode: "%s"; group_replication_auto_increment_increment: %lu; group_replication_view_change_uuid: "%s";
[ER_GRP_RPL_MEMBER_CONF_INFO](#) was added in 8.0.11.
- Error number: [MY-011644](#); Symbol: [ER_GRP_RPL_FAILED_TO_CONFIRM_IF_SERVER_LEFT_GRP](#); SQLSTATE: [HY000](#)

Message: Unable to confirm whether the server has left the group or not. Check performance_schema.replication_group_members to check group membership information.
[ER_GRP_RPL_FAILED_TO_CONFIRM_IF_SERVER_LEFT_GRP](#) was added in 8.0.11.
- Error number: [MY-011645](#); Symbol: [ER_GRP_RPL_SERVER_IS_ALREADY_LEAVEING](#); SQLSTATE: [HY000](#)

Message: Skipping leave operation: concurrent attempt to leave the group is on-going.
[ER_GRP_RPL_SERVER_IS_ALREADY_LEAVEING](#) was added in 8.0.11.
- Error number: [MY-011646](#); Symbol: [ER_GRP_RPL_SERVER_ALREADY_LEFT](#); SQLSTATE: [HY000](#)

Message: Skipping leave operation: member already left the group.
[ER_GRP_RPL_SERVER_ALREADY_LEFT](#) was added in 8.0.11.
- Error number: [MY-011647](#); Symbol: [ER_GRP_RPL_WAITING_FOR_VIEW_UPDATE](#); SQLSTATE: [HY000](#)

Message: Going to wait for view modification
[ER_GRP_RPL_WAITING_FOR_VIEW_UPDATE](#) was added in 8.0.11.

- Error number: [MY-011648](#); Symbol: [ER_GRP_RPL_TIMEOUT RECEIVING VIEW CHANGE ON SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: While leaving the group due to a stop, shutdown or failure there was a timeout receiving a view change. This can lead to a possible inconsistent state. Check the log for more details
[ER_GRP_RPL_TIMEOUT RECEIVING VIEW CHANGE ON SHUTDOWN](#) was added in 8.0.11.
- Error number: [MY-011649](#); Symbol: [ER_GRP_RPL_REQUESTING_NON_MEMBER_SERVER_TO_LEAVE](#); SQLSTATE: [HY000](#)

Message: Requesting to leave the group despite of not being a member
[ER_GRP_RPL_REQUESTING_NON_MEMBER_SERVER_TO_LEAVE](#) was added in 8.0.11.
- Error number: [MY-011650](#); Symbol: [ER_GRP_RPL_IS_STOPPING](#); SQLSTATE: [HY000](#)

Message: Plugin 'group_replication' is stopping.
[ER_GRP_RPL_IS_STOPPING](#) was added in 8.0.11.
- Error number: [MY-011651](#); Symbol: [ER_GRP_RPL_IS_STOPPED](#); SQLSTATE: [HY000](#)

Message: Plugin 'group_replication' has been stopped.
[ER_GRP_RPL_IS_STOPPED](#) was added in 8.0.11.
- Error number: [MY-011652](#); Symbol: [ER_GRP_RPL_FAILED_TO_ENABLE_READ_ONLY_MODE_ON_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: On plugin shutdown it was not possible to enable the server read only mode. Local transactions will be accepted and committed.
[ER_GRP_RPL_FAILED_TO_ENABLE_READ_ONLY_MODE_ON_SHUTDOWN](#) was added in 8.0.11.
- Error number: [MY-011653](#); Symbol: [ER_GRP_RPL_RECOVERY_MODULE_TERMINATION_TIMED_OUT_ON_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: On shutdown there was a timeout on the Group Replication recovery module termination. Check the log for more details
[ER_GRP_RPL_RECOVERY_MODULE_TERMINATION_TIMED_OUT_ON_SHUTDOWN](#) was added in 8.0.11.
- Error number: [MY-011654](#); Symbol: [ER_GRP_RPL_APPLIER_TERMINATION_TIMED_OUT_ON_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: On shutdown there was a timeout on the Group Replication applier termination.
[ER_GRP_RPL_APPLIER_TERMINATION_TIMED_OUT_ON_SHUTDOWN](#) was added in 8.0.11.
- Error number: [MY-011655](#); Symbol: [ER_GRP_RPL_FAILED_TO_SHUTDOWN_REGISTRY_MODULE](#); SQLSTATE: [HY000](#)

Message: Unexpected failure while shutting down registry module!
[ER_GRP_RPL_FAILED_TO_SHUTDOWN_REGISTRY_MODULE](#) was added in 8.0.11.
- Error number: [MY-011656](#); Symbol: [ER_GRP_RPL_FAILED_TO_INIT_HANDLER](#); SQLSTATE: [HY000](#)

Message: Failure during Group Replication handler initialization

`ER_GRP_RPL_FAILED_TO_INIT_HANDLER` was added in 8.0.11.

- Error number: `MY-011657`; Symbol: `ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_OBSERVER`; SQLSTATE: `HY000`

Message: Failure when registering the server state observers

`ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_OBSERVER` was added in 8.0.11.

- Error number: `MY-011658`; Symbol: `ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OBSERVER`; SQLSTATE: `HY000`

Message: Failure when registering the transactions state observers

`ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OBSERVER` was added in 8.0.11.

- Error number: `MY-011659`; Symbol: `ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_OBSERVER`; SQLSTATE: `HY000`

Message: Failure when registering the binlog state observers

`ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_OBSERVER` was added in 8.0.11.

- Error number: `MY-011660`; Symbol: `ER_GRP_RPL_FAILED_TO_START_ON_BOOT`; SQLSTATE: `HY000`

Message: Unable to start Group Replication on boot

`ER_GRP_RPL_FAILED_TO_START_ON_BOOT` was added in 8.0.11.

- Error number: `MY-011661`; Symbol: `ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL`; SQLSTATE: `HY000`

Message: Failure when stopping Group Replication on plugin uninstall

`ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL` was added in 8.0.11.

- Error number: `MY-011662`; Symbol: `ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE_OBSERVER`; SQLSTATE: `HY000`

Message: Failure when unregistering the server state observers

`ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE_OBSERVER` was added in 8.0.11.

- Error number: `MY-011663`; Symbol: `ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE_OBSERVER`; SQLSTATE: `HY000`

Message: Failure when unregistering the transactions state observers

`ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE_OBSERVER` was added in 8.0.11.

- Error number: `MY-011664`; Symbol: `ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE_OBSERVER`; SQLSTATE: `HY000`

Message: Failure when unregistering the binlog state observers

`ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE_OBSERVER` was added in 8.0.11.

- Error number: `MY-011665`; Symbol: `ER_GRP_RPL_ALL_OBSERVERS_UNREGISTERED`; SQLSTATE: `HY000`

Message: All Group Replication server observers have been successfully unregistered

`ER_GRP_RPL_ALL_OBSERVERS_UNREGISTERED` was added in 8.0.11.

- Error number: `MY-011666`; Symbol: `ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME`; SQLSTATE: `HY000`

Message: Unable to parse the group_replication_group_name.

`ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME` was added in 8.0.11.

- Error number: `MY-011667`; Symbol: `ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GRP`; SQLSTATE: `HY000`

Message: Unable to parse the group_replication_group_name.

`ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GRP` was added in 8.0.11.

- Error number: `MY-011668`; Symbol: `ER_GRP_RPL_APPLIER_NOT_STARTED_DUE_TO_RUNNING_PREV_SHUTDOWN`; SQLSTATE: `HY000`

Message: Cannot start the Group Replication applier as a previous shutdown is still running: The thread will stop once its task is complete.

`ER_GRP_RPL_APPLIER_NOT_STARTED_DUE_TO_RUNNING_PREV_SHUTDOWN` was added in 8.0.11.

- Error number: `MY-011669`; Symbol: `ER_GRP_RPL_FAILED_TO_INIT_APPLIER_MODULE`; SQLSTATE: `HY000`

Message: Unable to initialize the Group Replication applier module.

`ER_GRP_RPL_FAILED_TO_INIT_APPLIER_MODULE` was added in 8.0.11.

- Error number: `MY-011670`; Symbol: `ER_GRP_RPL_APPLIER_INITIALIZED`; SQLSTATE: `HY000`

Message: Group Replication applier module successfully initialized!

`ER_GRP_RPL_APPLIER_INITIALIZED` was added in 8.0.11.

- Error number: `MY-011671`; Symbol: `ER_GRP_RPL_COMMUNICATION_SSL_CONF_INFO`; SQLSTATE: `HY000`

Message: Group communication SSL configuration: group_replication_ssl_mode: "%s"; server_key_file: "%s"; server_cert_file: "%s"; client_key_file: "%s"; client_cert_file: "%s"; ca_file: "%s"; ca_path: "%s"; cipher: "%s"; tls_version: "%s"; tls_ciphersuites: "%s"; crl_file: "%s"; crl_path: "%s"; ssl_fips_mode: "%s"

`ER_GRP_RPL_COMMUNICATION_SSL_CONF_INFO` was added in 8.0.11.

- Error number: `MY-011672`; Symbol: `ER_GRP_RPL_ABORTS_AS_SSL_NOT_SUPPORTED_BY_MYSQLD`; SQLSTATE: `HY000`

Message: MySQL server does not have SSL support and group_replication_ssl_mode is "%s", START GROUP_REPLICATION will abort

`ER_GRP_RPL_ABORTS_AS_SSL_NOT_SUPPORTED_BY_MYSQLD` was added in 8.0.11.

- Error number: `MY-011673`; Symbol: `ER_GRP_RPL_SSL_DISABLED`; SQLSTATE: `HY000`

Message: Group communication SSL configuration: group_replication_ssl_mode: "%s"

`ER_GRP_RPL_SSL_DISABLED` was added in 8.0.11.

- Error number: [MY-011674](#); Symbol: [ER_GRP_RPL_UNABLE_TO_INIT_COMMUNICATION_ENGINE](#); SQLSTATE: [HY000](#)

Message: Unable to initialize the group communication engine

[ER_GRP_RPL_UNABLE_TO_INIT_COMMUNICATION_ENGINE](#) was added in 8.0.11.

- Error number: [MY-011675](#); Symbol: [ER_GRP_RPL_BINLOG_DISABLED](#); SQLSTATE: [HY000](#)

Message: Binlog must be enabled for Group Replication

[ER_GRP_RPL_BINLOG_DISABLED](#) was added in 8.0.11.

- Error number: [MY-011676](#); Symbol: [ER_GRP_RPL_GTID_MODE_OFF](#); SQLSTATE: [HY000](#)

Message: Gtid mode should be ON for Group Replication

[ER_GRP_RPL_GTID_MODE_OFF](#) was added in 8.0.11.

- Error number: [MY-011677](#); Symbol: [ER_GRP_RPL_LOG_SLAVE_UPDATES_NOT_SET](#); SQLSTATE: [HY000](#)

Message: LOG_SLAVE_UPDATES should be ON for Group Replication

[ER_GRP_RPL_LOG_SLAVE_UPDATES_NOT_SET](#) was added in 8.0.11, removed after 8.0.25.

- Error number: [MY-011677](#); Symbol: [ER_GRP_RPL_LOG_REPLICA_UPDATES_NOT_SET](#); SQLSTATE: [HY000](#)

Message: LOG_REPLICA_UPDATES should be ON for Group Replication

[ER_GRP_RPL_LOG_REPLICA_UPDATES_NOT_SET](#) was added in 8.0.26.

- Error number: [MY-011678](#); Symbol: [ER_GRP_RPL_INVALID_TRANS_WRITE_SET_EXTRACTION_VALUE](#); SQLSTATE: [HY000](#)

Message: Extraction of transaction write sets requires an hash algorithm configuration. Please, double check that the parameter transaction-write-set-extraction is set to a valid algorithm.

[ER_GRP_RPL_INVALID_TRANS_WRITE_SET_EXTRACTION_VALUE](#) was added in 8.0.11.

- Error number: [MY-011679](#); Symbol: [ER_GRP_RPL_RELAY_LOG_INFO_REPO_MUST_BE_TABLE](#); SQLSTATE: [HY000](#)

Message: Relay log info repository must be set to TABLE

[ER_GRP_RPL_RELAY_LOG_INFO_REPO_MUST_BE_TABLE](#) was added in 8.0.11.

- Error number: [MY-011680](#); Symbol: [ER_GRP_RPL_MASTER_INFO_REPO_MUST_BE_TABLE](#); SQLSTATE: [HY000](#)

Message: Master info repository must be set to TABLE.

[ER_GRP_RPL_MASTER_INFO_REPO_MUST_BE_TABLE](#) was added in 8.0.11.

- Error number: [MY-011681](#); Symbol: [ER_GRP_RPL_INCORRECT_TYPE_SET_FOR_PARALLEL_APPLIER](#); SQLSTATE: [HY000](#)

Message: In order to use parallel applier on Group Replication, parameter replica-parallel-type must be set to 'LOGICAL_CLOCK'.

[ER_GRP_RPL_INCORRECT_TYPE_SET_FOR_PARALLEL_APPLIER](#) was added in 8.0.11.

-
- Error number: [MY-011682](#); Symbol: [ER_GRP_RPL_SLAVE_PRESERVE_COMMIT_ORDER_NOT_SET](#); SQLSTATE: [HY000](#)

Message: Group Replication requires slave-preserve-commit-order to be set to ON when using more than 1 applier threads.

[ER_GRP_RPL_SLAVE_PRESERVE_COMMIT_ORDER_NOT_SET](#) was added in 8.0.11, removed after 8.0.25.

- Error number: [MY-011682](#); Symbol: [ER_GRP_RPL_REPLICA_PRESERVE_COMMIT_ORDER_NOT_SET](#); SQLSTATE: [HY000](#)

Message: Group Replication requires replica-preserve-commit-order to be set to ON when using more than 1 applier threads.

[ER_GRP_RPL_REPLICA_PRESERVE_COMMIT_ORDER_NOT_SET](#) was added in 8.0.26.

- Error number: [MY-011683](#); Symbol: [ER_GRP_RPL_SINGLE_PRIM_MODE_NOT_ALLOWED_WITH_UPDATE_EVERYWHERE](#); SQLSTATE: [HY000](#)

Message: It is not allowed to run single primary mode with 'group_replication_enforce_update_everywhere_checks' enabled.

[ER_GRP_RPL_SINGLE_PRIM_MODE_NOT_ALLOWED_WITH_UPDATE_EVERYWHERE](#) was added in 8.0.11.

- Error number: [MY-011684](#); Symbol: [ER_GRP_RPL_MODULE_TERMINATE_ERROR](#); SQLSTATE: [HY000](#)

Message: error_message: %s

[ER_GRP_RPL_MODULE_TERMINATE_ERROR](#) was added in 8.0.11.

- Error number: [MY-011685](#); Symbol: [ER_GRP_RPL_GRP_NAME_OPTION_MANDATORY](#); SQLSTATE: [HY000](#)

Message: The group_replication_group_name option is mandatory

[ER_GRP_RPL_GRP_NAME_OPTION_MANDATORY](#) was added in 8.0.11.

- Error number: [MY-011686](#); Symbol: [ER_GRP_RPL_GRP_NAME_IS_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: The group_replication_group_name '%s' is not a valid UUID, its length is too big

[ER_GRP_RPL_GRP_NAME_IS_TOO_LONG](#) was added in 8.0.11.

- Error number: [MY-011687](#); Symbol: [ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID](#); SQLSTATE: [HY000](#)

Message: The group_replication_group_name '%s' is not a valid UUID

[ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID](#) was added in 8.0.11.

- Error number: [MY-011688](#); Symbol: [ER_GRP_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_MAX_QUOTA](#); SQLSTATE: [HY000](#)

Message: group_replication_flow_control_min_quota cannot be larger than group_replication_flow_control_max_quota

[ER_GRP_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_MAX_QUOTA](#) was added in 8.0.11.

- Error number: [MY-011689](#); Symbol: [ER_GRP_RPL_FLOW_CTRL_MIN_RECOVERY_QUOTA_GREATER_THAN_MAX_QUOTA](#); SQLSTATE: [HY000](#)

Message: group_replication_flow_control_min_recovery_quota cannot be larger than group_replication_flow_control_max_quota

[ER_GRP_RPL_FLOW_CTRL_MIN_RECOVERY_QUOTA_GREATER_THAN_MAX_QUOTA](#) was added in 8.0.11.
- Error number: [MY-011690](#); Symbol: [ER_GRP_RPL_FLOW_CTRL_MAX_QUOTA_SMALLER_THAN_MIN_QUOTAS](#); SQLSTATE: [HY000](#)

Message: group_replication_flow_control_max_quota cannot be smaller than group_replication_flow_control_min_quota or group_replication_flow_control_min_recovery_quota

[ER_GRP_RPL_FLOW_CTRL_MAX_QUOTA_SMALLER_THAN_MIN_QUOTAS](#) was added in 8.0.11.
- Error number: [MY-011691](#); Symbol: [ER_GRP_RPL_INVALID_SSL_RECOVERY_STRING](#); SQLSTATE: [HY000](#)

Message: The given value for recovery ssl option 'group_replication_%s' is invalid as its length is beyond the limit

[ER_GRP_RPL_INVALID_SSL_RECOVERY_STRING](#) was added in 8.0.11.
- Error number: [MY-011692](#); Symbol: [ER_GRP_RPL_SUPPORTS_ONLY_ONE_FORCE_MEMBERS_SET](#); SQLSTATE: [HY000](#)

Message: There is one group_replication_force_members operation already ongoing

[ER_GRP_RPL_SUPPORTS_ONLY_ONE_FORCE_MEMBERS_SET](#) was added in 8.0.11.
- Error number: [MY-011693](#); Symbol: [ER_GRP_RPL_FORCE_MEMBERS_SET_UPDATE_NOT_ALLOWED](#); SQLSTATE: [HY000](#)

Message: group_replication_force_members can only be updated when Group Replication is running and a majority of the members are unreachable

[ER_GRP_RPL_FORCE_MEMBERS_SET_UPDATE_NOT_ALLOWED](#) was added in 8.0.11.
- Error number: [MY-011694](#); Symbol: [ER_GRP_RPL_GRP_COMMUNICATION_INIT_WITH_CONF](#); SQLSTATE: [HY000](#)

Message: Initialized group communication with configuration: group_replication_group_name: '%s'; group_replication_local_address: '%s'; group_replication_group_seeds: '%s'; group_replication_bootstrap_group: '%s'; group_replication_poll_spin_loops: %lu; group_replication_compression_threshold: %lu; group_replication_ip_allowlist: '%s'; group_replication_communication_debug_options: '%s'; group_replication_member_expire_timeout: '%lu'; group_replication_communication_max_message_size: %lu; group_replication_message_cache_size: '%lu'

[ER_GRP_RPL_GRP_COMMUNICATION_INIT_WITH_CONF](#) was added in 8.0.11.
- Error number: [MY-011695](#); Symbol: [ER_GRP_RPL_UNKNOWN_GRP_RPL_APPLIER_PIPELINE_REQUESTED](#); SQLSTATE: [HY000](#)

Message: Unknown group replication applier pipeline requested

[ER_GRP_RPL_UNKNOWN_GRP_RPL_APPLIER_PIPELINE_REQUESTED](#) was added in 8.0.11.

-
- Error number: [MY-011696](#); Symbol: [ER_GRP_RPL_FAILED_TO_BOOTSTRAP_EVENT_HANDLING_INFRASTRUCTURE](#); SQLSTATE: [HY000](#)

Message: Unable to bootstrap group replication event handling infrastructure. Unknown handler type: %d
[ER_GRP_RPL_FAILED_TO_BOOTSTRAP_EVENT_HANDLING_INFRASTRUCTURE](#) was added in 8.0.11.
 - Error number: [MY-011697](#); Symbol: [ER_GRP_RPL_APPLIER_HANDLER_NOT_INITIALIZED](#); SQLSTATE: [HY000](#)

Message: One of the group replication applier handlers is null due to an initialization error
[ER_GRP_RPL_APPLIER_HANDLER_NOT_INITIALIZED](#) was added in 8.0.11.
 - Error number: [MY-011698](#); Symbol: [ER_GRP_RPL_APPLIER_HANDLER_IS_IN_USE](#); SQLSTATE: [HY000](#)

Message: A group replication applier handler, marked as unique, is already in use.
[ER_GRP_RPL_APPLIER_HANDLER_IS_IN_USE](#) was added in 8.0.11.
 - Error number: [MY-011699](#); Symbol: [ER_GRP_RPL_APPLIER_HANDLER_ROLE_IS_IN_USE](#); SQLSTATE: [HY000](#)

Message: A group replication applier handler role, that was marked as unique, is already in use.
[ER_GRP_RPL_APPLIER_HANDLER_ROLE_IS_IN_USE](#) was added in 8.0.11.
 - Error number: [MY-011700](#); Symbol: [ER_GRP_RPL_FAILED_TO_INIT_APPLIER_HANDLER](#); SQLSTATE: [HY000](#)

Message: Error on group replication applier handler initialization
[ER_GRP_RPL_FAILED_TO_INIT_APPLIER_HANDLER](#) was added in 8.0.11.
 - Error number: [MY-011701](#); Symbol: [ER_GRP_RPL_SQL_SERVICE_FAILED_TO_INIT_SESSION_THREAD](#); SQLSTATE: [HY000](#)

Message: Error when initializing a session thread for internal server connection.
[ER_GRP_RPL_SQL_SERVICE_FAILED_TO_INIT_SESSION_THREAD](#) was added in 8.0.11.
 - Error number: [MY-011702](#); Symbol: [ER_GRP_RPL_SQL_SERVICE_COMM_SESSION_NOT_INITIALIZED](#); SQLSTATE: [HY000](#)

Message: Error running internal SQL query: %s. The internal server communication session is not initialized
[ER_GRP_RPL_SQL_SERVICE_COMM_SESSION_NOT_INITIALIZED](#) was added in 8.0.11.
 - Error number: [MY-011703](#); Symbol: [ER_GRP_RPL_SQL_SERVICE_SERVER_SESSION_KILLED](#); SQLSTATE: [HY000](#)

Message: Error running internal SQL query: %s. The internal server session was killed or server is shutting down.
[ER_GRP_RPL_SQL_SERVICE_SERVER_SESSION_KILLED](#) was added in 8.0.11.
 - Error number: [MY-011704](#); Symbol: [ER_GRP_RPL_SQL_SERVICE_FAILED_TO_RUN_SQL_QUERY](#); SQLSTATE: [HY000](#)

Message: Error running internal SQL query: %s. Got internal SQL error: %s(%d)

`ER_GRP_RPL_SQL_SERVICE_FAILED_TO_RUN_SQL_QUERY` was added in 8.0.11.

- Error number: `MY-011705`; Symbol: `ER_GRP_RPL_SQL_SERVICE_SERVER_INTERNAL_FAILURE`; SQLSTATE: `HY000`

Message: Error running internal SQL query: %s. Internal failure.

`ER_GRP_RPL_SQL_SERVICE_SERVER_INTERNAL_FAILURE` was added in 8.0.11.

- Error number: `MY-011706`; Symbol: `ER_GRP_RPL_SQL_SERVICE_RETRIES_EXCEEDED_ON_SESSION_STATE`; SQLSTATE: `HY000`

Message: Error, maximum number of retries exceeded when waiting for the internal server session state to be operating

`ER_GRP_RPL_SQL_SERVICE_RETRIES_EXCEEDED_ON_SESSION_STATE` was added in 8.0.11.

- Error number: `MY-011707`; Symbol: `ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SECURITY_CTX`; SQLSTATE: `HY000`

Message: Error when trying to fetch security context when contacting the server for internal plugin requests.

`ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SECURITY_CTX` was added in 8.0.11.

- Error number: `MY-011708`; Symbol: `ER_GRP_RPL_SQL_SERVICE_SERVER_ACCESS_DENIED_FOR_USER`; SQLSTATE: `HY000`

Message: There was an error when trying to access the server with user: %s. Make sure the user is present in the server and that the MySQL upgrade procedure was run correctly.

`ER_GRP_RPL_SQL_SERVICE_SERVER_ACCESS_DENIED_FOR_USER` was added in 8.0.11.

- Error number: `MY-011709`; Symbol: `ER_GRP_RPL_SQL_SERVICE_MAX_CONN_ERROR_FROM_SERVER`; SQLSTATE: `HY000`

Message: Failed to establish an internal server connection to execute plugin operations since the server does not have available connections, please increase `@@GLOBAL.MAX_CONNECTIONS`. Server error: %i.

`ER_GRP_RPL_SQL_SERVICE_MAX_CONN_ERROR_FROM_SERVER` was added in 8.0.11.

- Error number: `MY-011710`; Symbol: `ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_CONN`; SQLSTATE: `HY000`

Message: Failed to establish an internal server connection to execute plugin operations. Server error: %i. Server error message: %s

`ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_CONN` was added in 8.0.11.

- Error number: `MY-011711`; Symbol: `ER_GRP_RPL_UNREACHABLE_MAORITY_TIMEOUT_FOR_MEMBER`; SQLSTATE: `HY000`

Message: This member could not reach a majority of the members for more than %ld seconds. The member will now leave the group as instructed by the `group_replication_unreachable_majority_timeout` option.

`ER_GRP_RPL_UNREACHABLE_MAORITY_TIMEOUT_FOR_MEMBER` was added in 8.0.11.

- Error number: [MY-011712](#); Symbol: [ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DUE_TO_ERRORS](#); SQLSTATE: [HY000](#)

Message: The server was automatically set into read only mode after an error was detected.
[ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DUE_TO_ERRORS](#) was added in 8.0.11.
- Error number: [MY-011713](#); Symbol: [ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION](#); SQLSTATE: [HY000](#)

Message: Unable to log notification to table (errno: %lu) (res: %d)! Message: %s
[ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION](#) was added in 8.0.11.
- Error number: [MY-011714](#); Symbol: [ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failure in group communication engine '%s' initialization
[ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILED](#) was added in 8.0.11.
- Error number: [MY-011715](#); Symbol: [ER_GRP_RPL_SET_GRP_COMMUNICATION_ENG_LOGGER_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to set the group communication engine logger
[ER_GRP_RPL_SET_GRP_COMMUNICATION_ENG_LOGGER_FAILED](#) was added in 8.0.11.
- Error number: [MY-011716](#); Symbol: [ER_GRP_RPL_DEBUG_OPTIONS](#); SQLSTATE: [HY000](#)

Message: Current debug options are: '%s'.
[ER_GRP_RPL_DEBUG_OPTIONS](#) was added in 8.0.11.
- Error number: [MY-011717](#); Symbol: [ER_GRP_RPL_INVALID_DEBUG_OPTIONS](#); SQLSTATE: [HY000](#)

Message: Some debug options in '%s' are not valid.
[ER_GRP_RPL_INVALID_DEBUG_OPTIONS](#) was added in 8.0.11.
- Error number: [MY-011718](#); Symbol: [ER_GRP_RPL_EXIT_GRP_GCS_ERROR](#); SQLSTATE: [HY000](#)

Message: Error calling group communication interfaces while trying to leave the group
[ER_GRP_RPL_EXIT_GRP_GCS_ERROR](#) was added in 8.0.11.
- Error number: [MY-011719](#); Symbol: [ER_GRP_RPL_GRP_MEMBER_OFFLINE](#); SQLSTATE: [HY000](#)

Message: Member is not ONLINE, it is not possible to force a new group membership
[ER_GRP_RPL_GRP_MEMBER_OFFLINE](#) was added in 8.0.11.
- Error number: [MY-011720](#); Symbol: [ER_GRP_RPL_GCS_INTERFACE_ERROR](#); SQLSTATE: [HY000](#)

Message: Error calling group communication interfaces
[ER_GRP_RPL_GCS_INTERFACE_ERROR](#) was added in 8.0.11.
- Error number: [MY-011721](#); Symbol: [ER_GRP_RPL_FORCE_MEMBER_VALUE_SET_ERROR](#); SQLSTATE: [HY000](#)

Message: Error setting group_replication_force_members value '%s' on group communication interfaces

`ER_GRP_RPL_FORCE_MEMBER_VALUE_SET_ERROR` was added in 8.0.11.

- Error number: `MY-011722`; Symbol: `ER_GRP_RPL_FORCE_MEMBER_VALUE_SET`; SQLSTATE: `HY000`

Message: The group_replication_force_members value '%s' was set in the group communication interfaces

`ER_GRP_RPL_FORCE_MEMBER_VALUE_SET` was added in 8.0.11.

- Error number: `MY-011723`; Symbol: `ER_GRP_RPL_FORCE_MEMBER_VALUE_TIME_OUT`; SQLSTATE: `HY000`

Message: Timeout on wait for view after setting group_replication_force_members value '%s' into group communication interfaces

`ER_GRP_RPL_FORCE_MEMBER_VALUE_TIME_OUT` was added in 8.0.11.

- Error number: `MY-011724`; Symbol: `ER_GRP_RPL_BROADCAST_COMMIT_MSSG_TOO_BIG`; SQLSTATE: `HY000`

Message: Broadcast of committed transactions message failed. Message is too big.

`ER_GRP_RPL_BROADCAST_COMMIT_MSSG_TOO_BIG` was added in 8.0.11.

- Error number: `MY-011725`; Symbol: `ER_GRP_RPL_SEND_STATS_ERROR`; SQLSTATE: `HY000`

Message: Error while sending stats message

`ER_GRP_RPL_SEND_STATS_ERROR` was added in 8.0.11.

- Error number: `MY-011726`; Symbol: `ER_GRP_RPL_MEMBER_STATS_INFO`; SQLSTATE: `HY000`

Message: Flow control - update member stats: %s stats certifier_queue %d, applier_queue %d certified %ld (%ld), applied %ld (%ld), local %ld (%ld), quota %ld (%ld) mode=%d

`ER_GRP_RPL_MEMBER_STATS_INFO` was added in 8.0.11.

- Error number: `MY-011727`; Symbol: `ER_GRP_RPL_FLOW_CONTROL_STATS`; SQLSTATE: `HY000`

Message: Flow control: throttling to %ld commits per %ld sec, with %d writing and %d non-recovering members, min capacity %lld, lim throttle %lld

`ER_GRP_RPL_FLOW_CONTROL_STATS` was added in 8.0.11.

- Error number: `MY-011728`; Symbol: `ER_GRP_RPL_UNABLE_TO_CONVERT_PACKET_TO_EVENT`; SQLSTATE: `HY000`

Message: Unable to convert a packet into an event on the applier. Error: %s

`ER_GRP_RPL_UNABLE_TO_CONVERT_PACKET_TO_EVENT` was added in 8.0.11.

- Error number: `MY-011729`; Symbol: `ER_GRP_RPL_PIPELINE_CREATE_FAILED`; SQLSTATE: `HY000`

Message: Failed to create group replication pipeline cache.

`ER_GRP_RPL_PIPELINE_CREATE_FAILED` was added in 8.0.11.

- Error number: `MY-011730`; Symbol: `ER_GRP_RPL_PIPELINE_REINIT_FAILED_WRITE`; SQLSTATE: `HY000`

Message: Failed to reinit group replication pipeline cache for write.

`ER_GRP_RPL_PIPELINE_REINIT_FAILED_WRITE` was added in 8.0.11.

- Error number: `MY-011731`; Symbol: `ER_GRP_RPL_UNABLE_TO_CONVERT_EVENT_TO_PACKET`; SQLSTATE: `HY000`

Message: Unable to convert the event into a packet on the applier. Error: %s

`ER_GRP_RPL_UNABLE_TO_CONVERT_EVENT_TO_PACKET` was added in 8.0.11.

- Error number: `MY-011732`; Symbol: `ER_GRP_RPL_PIPELINE_FLUSH_FAIL`; SQLSTATE: `HY000`

Message: Failed to flush group replication pipeline cache.

`ER_GRP_RPL_PIPELINE_FLUSH_FAIL` was added in 8.0.11.

- Error number: `MY-011733`; Symbol: `ER_GRP_RPL_PIPELINE_REINIT_FAILED_READ`; SQLSTATE: `HY000`

Message: Failed to reinit group replication pipeline cache for read.

`ER_GRP_RPL_PIPELINE_REINIT_FAILED_READ` was added in 8.0.11.

- Error number: `MY-011734`; Symbol: `ER_GRP_RPL_STOP_REP_CHANNEL`; SQLSTATE: `HY000`

Message: Error stopping all replication channels while server was leaving the group. Got error: %d. Please check the error log for more details.

`ER_GRP_RPL_STOP_REP_CHANNEL` was added in 8.0.11, removed after 8.0.17.

- Error number: `MY-011735`; Symbol: `ER_GRP_RPL_GCS_GR_ERROR_MSG`; SQLSTATE: `HY000`

Message: %s

`ER_GRP_RPL_GCS_GR_ERROR_MSG` was added in 8.0.11.

- Error number: `MY-011736`; Symbol: `ER_GRP_RPL_SLAVE_IO_THREAD_UNBLOCKED`; SQLSTATE: `HY000`

Message: The slave IO thread of channel '%s' is unblocked as the member is declared ONLINE now.

`ER_GRP_RPL_SLAVE_IO_THREAD_UNBLOCKED` was added in 8.0.11.

- Error number: `MY-011737`; Symbol: `ER_GRP_RPL_SLAVE_IO_THREAD_ERROR_OUT`; SQLSTATE: `HY000`

Message: The slave IO thread of channel '%s' will error out as the member failed to come ONLINE.

`ER_GRP_RPL_SLAVE_IO_THREAD_ERROR_OUT` was added in 8.0.11.

- Error number: `MY-011738`; Symbol: `ER_GRP_RPL_SLAVE_APPLIER_THREAD_UNBLOCKED`; SQLSTATE: `HY000`

Message: The slave applier thread of channel '%s' is unblocked as the member is declared ONLINE now.

`ER_GRP_RPL_SLAVE_APPLIER_THREAD_UNBLOCKED` was added in 8.0.11.

- Error number: `MY-011739`; Symbol: `ER_GRP_RPL_SLAVE_APPLIER_THREAD_ERROR_OUT`; SQLSTATE: `HY000`

Message: The slave applier thread of channel '%s' will error out as the member failed to come ONLINE.

`ER_GRP_RPL_SLAVE_APPLIER_THREAD_ERROR_OUT` was added in 8.0.11.

- Error number: `MY-011740`; Symbol: `ER_LDAP_AUTH_FAILED_TO_CREATE_OR_GET_CONNECTION`; SQLSTATE: `HY000`

Message: LDAP authentication initialize: failed to create/ get connection from the pool.

`ER_LDAP_AUTH_FAILED_TO_CREATE_OR_GET_CONNECTION` was added in 8.0.11.

- Error number: `MY-011741`; Symbol: `ER_LDAP_AUTH_DEINIT_FAILED`; SQLSTATE: `HY000`

Message: LDAP authentication de_initialize Failed

`ER_LDAP_AUTH_DEINIT_FAILED` was added in 8.0.11.

- Error number: `MY-011742`; Symbol: `ER_LDAP_AUTH_SKIPPING_USER_GROUP_SEARCH`; SQLSTATE: `HY000`

Message: Skipping group search, No group attribute mentioned

`ER_LDAP_AUTH_SKIPPING_USER_GROUP_SEARCH` was added in 8.0.11.

- Error number: `MY-011743`; Symbol: `ER_LDAP_AUTH_POOL_DISABLE_MAX_SIZE_ZERO`; SQLSTATE: `HY000`

Message: Pool max size is 0, connection pool is disabled

`ER_LDAP_AUTH_POOL_DISABLE_MAX_SIZE_ZERO` was added in 8.0.11.

- Error number: `MY-011744`; Symbol: `ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT_CREATOR`; SQLSTATE: `HY000`

Message: Connection pool initialization, failed to create LDAP object creator

`ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT_CREATOR` was added in 8.0.11.

- Error number: `MY-011745`; Symbol: `ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT`; SQLSTATE: `HY000`

Message: Connection pool initialization, failed to create LDAP object

`ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT` was added in 8.0.11.

- Error number: `MY-011746`; Symbol: `ER_LDAP_AUTH_TLS_CONF`; SQLSTATE: `HY000`

Message: LDAP TLS configuration

`ER_LDAP_AUTH_TLS_CONF` was added in 8.0.11.

- Error number: `MY-011747`; Symbol: `ER_LDAP_AUTH_TLS_CONNECTION`; SQLSTATE: `HY000`

Message: LDAP TLS connection

`ER_LDAP_AUTH_TLS_CONNECTION` was added in 8.0.11.

- Error number: `MY-011748`; Symbol: `ER_LDAP_AUTH_CONN_POOL_NOT_CREATED`; SQLSTATE: `HY000`

Message: LDAP pool is not created.

`ER_LDAP_AUTH_CONN_POOL_NOT_CREATED` was added in 8.0.11.

-
- Error number: MY-011749; Symbol: `ER_LDAP_AUTH_CONN_POOL_INITIALIZING`; SQLSTATE: HY000
Message: LDAP pool is initializing
`ER_LDAP_AUTH_CONN_POOL_INITIALIZING` was added in 8.0.11.
 - Error number: MY-011750; Symbol: `ER_LDAP_AUTH_CONN_POOL_DEINITIALIZING`; SQLSTATE: HY000
Message: LDAP pool is de-initializing
`ER_LDAP_AUTH_CONN_POOL_DEINITIALIZING` was added in 8.0.11.
 - Error number: MY-011751; Symbol: `ER_LDAP_AUTH_ZERO_MAX_POOL_SIZE_UNCHANGED`; SQLSTATE: HY000
Message: Pool max size old and new values are 0
`ER_LDAP_AUTH_ZERO_MAX_POOL_SIZE_UNCHANGED` was added in 8.0.11.
 - Error number: MY-011752; Symbol: `ER_LDAP_AUTH_POOL_REINITIALIZING`; SQLSTATE: HY000
Message: LDAP pool is re-initializing
`ER_LDAP_AUTH_POOL_REINITIALIZING` was added in 8.0.11.
 - Error number: MY-011753; Symbol: `ER_LDAP_AUTH_FAILED_TO_WRITE_PACKET`; SQLSTATE: HY000
Message: Plug-in has failed to write the packet.
`ER_LDAP_AUTH_FAILED_TO_WRITE_PACKET` was added in 8.0.11.
 - Error number: MY-011754; Symbol: `ER_LDAP_AUTH_SETTING_USERNAME`; SQLSTATE: HY000
Message: Setting LDAP user name as : %s
`ER_LDAP_AUTH_SETTING_USERNAME` was added in 8.0.11.
 - Error number: MY-011755; Symbol: `ER_LDAP_AUTH_USER_AUTH_DATA`; SQLSTATE: HY000
Message: User authentication data: %s size: %lu
`ER_LDAP_AUTH_USER_AUTH_DATA` was added in 8.0.11.
 - Error number: MY-011756; Symbol: `ER_LDAP_AUTH_INFO_FOR_USER`; SQLSTATE: HY000
Message: User is authenticated as: %s external user: %s
`ER_LDAP_AUTH_INFO_FOR_USER` was added in 8.0.11.
 - Error number: MY-011757; Symbol: `ER_LDAP_AUTH_USER_GROUP_SEARCH_INFO`; SQLSTATE: HY000
Message: Group search information base DN: %s scope: %d filter: %s attribute: %s
`ER_LDAP_AUTH_USER_GROUP_SEARCH_INFO` was added in 8.0.11.
 - Error number: MY-011758; Symbol: `ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL`; SQLSTATE: HY000
Message: Special handling for group search, {GA} found

`ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL` was added in 8.0.11.

- Error number: `MY-011759`; Symbol: `ER_LDAP_AUTH_GRP_IS_FULL_DN`; SQLSTATE: `HY000`

Message: Group search special handling, group full DN found.

`ER_LDAP_AUTH_GRP_IS_FULL_DN` was added in 8.0.11.

- Error number: `MY-011760`; Symbol: `ER_LDAP_AUTH_USER_NOT_FOUND_IN_ANY_GRP`; SQLSTATE: `HY000`

Message: User %s is not member of any group.

`ER_LDAP_AUTH_USER_NOT_FOUND_IN_ANY_GRP` was added in 8.0.11.

- Error number: `MY-011761`; Symbol: `ER_LDAP_AUTH_USER_FOUND_IN_MANY_GRPS`; SQLSTATE: `HY000`

Message: User %s is member of more than one group

`ER_LDAP_AUTH_USER_FOUND_IN_MANY_GRPS` was added in 8.0.11.

- Error number: `MY-011762`; Symbol: `ER_LDAP_AUTH_USER_HAS_MULTIPLE_GRP_NAMES`; SQLSTATE: `HY000`

Message: For user %s has multiple user group names. Please check if group attribute name is correct

`ER_LDAP_AUTH_USER_HAS_MULTIPLE_GRP_NAMES` was added in 8.0.11.

- Error number: `MY-011763`; Symbol: `ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME`; SQLSTATE: `HY000`

Message: Searched group name: %s

`ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME` was added in 8.0.11.

- Error number: `MY-011764`; Symbol: `ER_LDAP_AUTH_OBJECT_CREATE_TIMESTAMP`; SQLSTATE: `HY000`

Message: LDAP authentication object creation time_stamp: %s dn: %s

`ER_LDAP_AUTH_OBJECT_CREATE_TIMESTAMP` was added in 8.0.11.

- Error number: `MY-011765`; Symbol: `ER_LDAP_AUTH_CERTIFICATE_NAME`; SQLSTATE: `HY000`

Message: Certificate name: %s

`ER_LDAP_AUTH_CERTIFICATE_NAME` was added in 8.0.11.

- Error number: `MY-011766`; Symbol: `ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT`; SQLSTATE: `HY000`

Message: Failed to pool de-initialized: pool is already reconstructing

`ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT` was added in 8.0.11.

- Error number: `MY-011767`; Symbol: `ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_RECONSTRUCTING`; SQLSTATE: `HY000`

Message: Pool initialization failed: pool is already initialized

`ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_RECONSTRUCTING` was added in 8.0.11.

- Error number: `MY-011768`; Symbol: `ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INIT_STATE`; SQLSTATE: `HY000`

Message: Pool initialization failed: pool is initializing
`ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INIT_STATE` was added in 8.0.11.
- Error number: `MY-011769`; Symbol: `ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DEINIT_STATE`; SQLSTATE: `HY000`

Message: Pool initialization failed: pool is de-initializing
`ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DEINIT_STATE` was added in 8.0.11.
- Error number: `MY-011770`; Symbol: `ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_RECONSTRUCT_STATE`; SQLSTATE: `HY000`

Message: Failed to pool deinitialized: pool is already reconstructing
`ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_RECONSTRUCT_STATE` was added in 8.0.11.
- Error number: `MY-011771`; Symbol: `ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY_POOL`; SQLSTATE: `HY000`

Message: Failed to pool deinitialized : pool is not ready
`ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY_POOL` was added in 8.0.11.
- Error number: `MY-011772`; Symbol: `ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_PLUGIN_NOT_READY`; SQLSTATE: `HY000`

Message: Ldap_connection_pool::get: Failed to return connection as plug-in is not ready/initializing/de-initializing
`ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_PLUGIN_NOT_READY` was added in 8.0.11.
- Error number: `MY-011773`; Symbol: `ER_LDAP_AUTH_CONNECTION_POOL_INIT_FAILED`; SQLSTATE: `HY000`

Message: Connection pool has failed to initialized
`ER_LDAP_AUTH_CONNECTION_POOL_INIT_FAILED` was added in 8.0.11.
- Error number: `MY-011774`; Symbol: `ER_LDAP_AUTH_MAX_ALLOWED_CONNECTION_LIMIT_HIT`; SQLSTATE: `HY000`

Message: Ldap_connnection_pool::get LDAP maximum connection allowed size is reached. Increase the maximum limit.
`ER_LDAP_AUTH_MAX_ALLOWED_CONNECTION_LIMIT_HIT` was added in 8.0.11.
- Error number: `MY-011775`; Symbol: `ER_LDAP_AUTH_MAX_POOL_SIZE_SET_FAILED`; SQLSTATE: `HY000`

Message: Set max pool size failed.
`ER_LDAP_AUTH_MAX_POOL_SIZE_SET_FAILED` was added in 8.0.11.

- Error number: [MY-011776](#); Symbol: [ER_LDAP_AUTH_PLUGIN_FAILED_TO_READ_PACKET](#); SQLSTATE: [HY000](#)

Message: Plug-in has failed to read the packet from client
[ER_LDAP_AUTH_PLUGIN_FAILED_TO_READ_PACKET](#) was added in 8.0.11.
- Error number: [MY-011777](#); Symbol: [ER_LDAP_AUTH_CREATING_LDAP_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Ldap_authentication::initialize: creating new LDAP connection.
[ER_LDAP_AUTH_CREATING_LDAP_CONNECTION](#) was added in 8.0.11.
- Error number: [MY-011778](#); Symbol: [ER_LDAP_AUTH_GETTING_CONNECTION_FROM_POOL](#); SQLSTATE: [HY000](#)

Message: Ldap_authentication::initialize: getting connection from pool.
[ER_LDAP_AUTH_GETTING_CONNECTION_FROM_POOL](#) was added in 8.0.11.
- Error number: [MY-011779](#); Symbol: [ER_LDAP_AUTH_RETURNING_CONNECTION_TO_POOL](#); SQLSTATE: [HY000](#)

Message: Ldap_authentication::de_initialize putting back connection in the pool
[ER_LDAP_AUTH_RETURNING_CONNECTION_TO_POOL](#) was added in 8.0.11.
- Error number: [MY-011780](#); Symbol: [ER_LDAP_AUTH_SEARCH_USER_GROUP_ATTR_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Ldap_authentication::search_user_group no group attribute found
[ER_LDAP_AUTH_SEARCH_USER_GROUP_ATTR_NOT_FOUND](#) was added in 8.0.11.
- Error number: [MY-011781](#); Symbol: [ER_LDAP_AUTH_LDAP_INFO_NULL](#); SQLSTATE: [HY000](#)

Message: Ldap_connection_pool::put ldap info null
[ER_LDAP_AUTH_LDAP_INFO_NULL](#) was added in 8.0.11.
- Error number: [MY-011782](#); Symbol: [ER_LDAP_AUTH_FREEING_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Ldap_connection_pool::put connection is freeing.
[ER_LDAP_AUTH_FREEING_CONNECTION](#) was added in 8.0.11.
- Error number: [MY-011783](#); Symbol: [ER_LDAP_AUTH_CONNECTION_PUSHED_TO_POOL](#); SQLSTATE: [HY000](#)

Message: Ldap_connection_pool::put connection in pushed in the pool
[ER_LDAP_AUTH_CONNECTION_PUSHED_TO_POOL](#) was added in 8.0.11.
- Error number: [MY-011784](#); Symbol: [ER_LDAP_AUTH_CONNECTION_CREATOR_ENTER](#); SQLSTATE: [HY000](#)

Message: Ldap_connection_creator::Ldap_connection_creator
[ER_LDAP_AUTH_CONNECTION_CREATOR_ENTER](#) was added in 8.0.11.
- Error number: [MY-011785](#); Symbol: [ER_LDAP_AUTH_STARTING_TLS](#); SQLSTATE: [HY000](#)

Message: starting TLS

`ER_LDAP_AUTH_STARTING_TLS` was added in 8.0.11.

- Error number: `MY-011786`; Symbol: `ER_LDAP_AUTH_CONNECTION_GET_LDAP_INFO_NULL`; SQLSTATE: `HY000`

Message: Ldap_connection_pool::get: (ldap_info == NULL)|| (*ldap_info)

`ER_LDAP_AUTH_CONNECTION_GET_LDAP_INFO_NULL` was added in 8.0.11.

- Error number: `MY-011787`; Symbol: `ER_LDAP_AUTH_DELETING_CONNECTION_KEY`; SQLSTATE: `HY000`

Message: Ldap_connection_pool::deinit: deleting connection key %s

`ER_LDAP_AUTH_DELETING_CONNECTION_KEY` was added in 8.0.11.

- Error number: `MY-011788`; Symbol: `ER_LDAP_AUTH_POOLED_CONNECTION_KEY`; SQLSTATE: `HY000`

Message: Ldap_connection_pool::get pooled connection key: %s

`ER_LDAP_AUTH_POOLED_CONNECTION_KEY` was added in 8.0.11.

- Error number: `MY-011789`; Symbol: `ER_LDAP_AUTH_CREATE_CONNECTION_KEY`; SQLSTATE: `HY000`

Message: Ldap_connection_pool::get create connection key: %s

`ER_LDAP_AUTH_CREATE_CONNECTION_KEY` was added in 8.0.11.

- Error number: `MY-011790`; Symbol: `ER_LDAP_AUTH_COMMUNICATION_HOST_INFO`; SQLSTATE: `HY000`

Message: LDAP communication host %s port %u

`ER_LDAP_AUTH_COMMUNICATION_HOST_INFO` was added in 8.0.11.

- Error number: `MY-011791`; Symbol: `ER_LDAP_AUTH_METHOD_TO_CLIENT`; SQLSTATE: `HY000`

Message: Sending authentication method to client : %s

`ER_LDAP_AUTH_METHOD_TO_CLIENT` was added in 8.0.11.

- Error number: `MY-011792`; Symbol: `ER_LDAP_AUTH_SASL_REQUEST_FROM_CLIENT`; SQLSTATE: `HY000`

Message: SASL request received from mysql client: %s

`ER_LDAP_AUTH_SASL_REQUEST_FROM_CLIENT` was added in 8.0.11.

- Error number: `MY-011793`; Symbol: `ER_LDAP_AUTH_SASL_PROCESS_SASL`; SQLSTATE: `HY000`

Message: Ldap_sasl_authentication::process_sasl rc: %s

`ER_LDAP_AUTH_SASL_PROCESS_SASL` was added in 8.0.11.

- Error number: `MY-011794`; Symbol: `ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO`; SQLSTATE: `HY000`

Message: Ldap_sasl_authentication::process_sasl sasl bind succeed. dn: %s method: %s server credential: %s

`ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO` was added in 8.0.11.

- Error number: [MY-011795](#); Symbol: [ER_LDAP_AUTH_STARTED_FOR_USER](#); SQLSTATE: [HY000](#)

Message: LDAP authentication started for user name: %s
[ER_LDAP_AUTH_STARTED_FOR_USER](#) was added in 8.0.11.
- Error number: [MY-011796](#); Symbol: [ER_LDAP_AUTH_DISTINGUISHED_NAME](#); SQLSTATE: [HY000](#)

Message: %s
[ER_LDAP_AUTH_DISTINGUISHED_NAME](#) was added in 8.0.11.
- Error number: [MY-011797](#); Symbol: [ER_LDAP_AUTH_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: LDAP authentication initialize is failed with: %s
[ER_LDAP_AUTH_INIT_FAILED](#) was added in 8.0.11.
- Error number: [MY-011798](#); Symbol: [ER_LDAP_AUTH_OR_GROUP_RETRIEVAL_FAILED](#); SQLSTATE: [HY000](#)

Message: LDAP authentication failed or group retrieval failed: %s
[ER_LDAP_AUTH_OR_GROUP_RETRIEVAL_FAILED](#) was added in 8.0.11.
- Error number: [MY-011799](#); Symbol: [ER_LDAP_AUTH_USER_GROUP_SEARCH_FAILED](#); SQLSTATE: [HY000](#)

Message: Search user group has failed: %s
[ER_LDAP_AUTH_USER_GROUP_SEARCH_FAILED](#) was added in 8.0.11.
- Error number: [MY-011800](#); Symbol: [ER_LDAP_AUTH_USER_BIND_FAILED](#); SQLSTATE: [HY000](#)

Message: LDAP user bind has failed: %s
[ER_LDAP_AUTH_USER_BIND_FAILED](#) was added in 8.0.11.
- Error number: [MY-011801](#); Symbol: [ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Connection pool get: Failed to create LDAP connection. %s
[ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION](#) was added in 8.0.11.
- Error number: [MY-011802](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Failed to create new LDAP connection: %s
[ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION](#) was added in 8.0.11.
- Error number: [MY-011803](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Failed to establish TLS connection: %s
[ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION](#) was added in 8.0.11.
- Error number: [MY-011804](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_SEARCH_DN](#); SQLSTATE: [HY000](#)

Message: Failed to search user full dn: %s

`ER_LDAP_AUTH_FAILED_TO_SEARCH_DN` was added in 8.0.11.

- Error number: `MY-011805`; Symbol: `ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTER`; SQLSTATE: `HY000`

Message: Ldap_connection_pool::reinit

`ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTER` was added in 8.0.11.

- Error number: `MY-011806`; Symbol: `ER_SYSTEMD_NOTIFY_PATH_TOO_LONG`; SQLSTATE: `HY000`

Message: The path '%s', from the NOTIFY_SOCKET environment variable, is too long. At %u bytes it exceeds the limit of %u bytes for an AF_UNIX socket.

`ER_SYSTEMD_NOTIFY_PATH_TOO_LONG` was added in 8.0.11.

- Error number: `MY-011807`; Symbol: `ER_SYSTEMD_NOTIFY_CONNECT_FAILED`; SQLSTATE: `HY000`

Message: Failed to connect to systemd notification socket named %s. Error: '%s'

`ER_SYSTEMD_NOTIFY_CONNECT_FAILED` was added in 8.0.11.

- Error number: `MY-011808`; Symbol: `ER_SYSTEMD_NOTIFY_WRITE_FAILED`; SQLSTATE: `HY000`

Message: Failed to write '%s' to systemd notification. Error: '%s'

`ER_SYSTEMD_NOTIFY_WRITE_FAILED` was added in 8.0.11.

- Error number: `MY-011809`; Symbol: `ER_FOUND_MISSING_GTIDS`; SQLSTATE: `HY000`

Message: Cannot replicate to server with server_uuid='%s' because the present server has purged required binary logs. The connecting server needs to replicate the missing transactions from elsewhere, or be replaced by a new server created from a more recent backup. To prevent this error in the future, consider increasing the binary log expiration period on the present server. %s.

`ER_FOUND_MISSING_GTIDS` was added in 8.0.11.

- Error number: `MY-011810`; Symbol: `ER_PID_FILE_PRIV_DIRECTORY_INSECURE`; SQLSTATE: `HY000`

Message: Insecure configuration for --pid-file: Location '%s' in the path is accessible to all OS users. Consider choosing a different directory.

`ER_PID_FILE_PRIV_DIRECTORY_INSECURE` was added in 8.0.11.

- Error number: `MY-011811`; Symbol: `ER_CANT_CHECK_PID_PATH`; SQLSTATE: `HY000`

Message: Can't start server: can't check PID filepath: %s

`ER_CANT_CHECK_PID_PATH` was added in 8.0.11.

- Error number: `MY-011812`; Symbol: `ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED`; SQLSTATE: `HY000`

Message: validate_password status variables registration failed.

`ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED` was added in 8.0.11.

- Error number: `MY-011813`; Symbol: `ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED`; SQLSTATE: `HY000`

Message: validate_password status variables unregistration failed.

`ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED` was added in 8.0.11.

- Error number: `MY-011814`; Symbol: `ER_VALIDATE_PWD_DICT_FILE_OPEN_FAILED`; SQLSTATE: `HY000`

Message: Dictionary file open failed

`ER_VALIDATE_PWD_DICT_FILE_OPEN_FAILED` was added in 8.0.11.

- Error number: `MY-011815`; Symbol: `ER_VALIDATE_PWD_COULD_BE_NULL`; SQLSTATE: `HY000`

Message: given password string could be null

`ER_VALIDATE_PWD_COULD_BE_NULL` was added in 8.0.11.

- Error number: `MY-011816`; Symbol:

`ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED`; SQLSTATE: `HY000`

Message: failed to convert the password string to lower case

`ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED` was added in 8.0.11.

- Error number: `MY-011817`; Symbol: `ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED`; SQLSTATE: `HY000`

Message: failed to convert the password string into a buffer

`ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED` was added in 8.0.11.

- Error number: `MY-011818`; Symbol:

`ER_VALIDATE_PWD_STRING_HANDLER_MEM_ALLOCATION_FAILED`; SQLSTATE: `HY000`

Message: memory allocation failed for string handler

`ER_VALIDATE_PWD_STRING_HANDLER_MEM_ALLOCATION_FAILED` was added in 8.0.11.

- Error number: `MY-011819`; Symbol:

`ER_VALIDATE_PWD_STRONG_POLICY_DICT_FILE_UNSPECIFIED`; SQLSTATE: `HY000`

Message: Since the validate_password_policy is mentioned as Strong, dictionary file must be specified

`ER_VALIDATE_PWD_STRONG_POLICY_DICT_FILE_UNSPECIFIED` was added in 8.0.11.

- Error number: `MY-011820`; Symbol: `ER_VALIDATE_PWD_CONVERT_TO_BUFFER_FAILED`; SQLSTATE: `HY000`

Message: convert_to_buffer service failed

`ER_VALIDATE_PWD_CONVERT_TO_BUFFER_FAILED` was added in 8.0.11.

- Error number: `MY-011821`; Symbol: `ER_VALIDATE_PWD_VARIABLE_REGISTRATION_FAILED`; SQLSTATE: `HY000`

Message: %s variable registration failed.

`ER_VALIDATE_PWD_VARIABLE_REGISTRATION_FAILED` was added in 8.0.11.

- Error number: `MY-011822`; Symbol: `ER_VALIDATE_PWD_VARIABLE_UNREGISTRATION_FAILED`; SQLSTATE: `HY000`

Message: %s variable unregistration failed.

`ER_VALIDATE_PWD_VARIABLE_UNREGISTRATION_FAILED` was added in 8.0.11.

- Error number: `MY-011823`; Symbol: `ER_KEYRING_MIGRATION_EXTRA_OPTIONS`; SQLSTATE: `HY000`

Message: Please specify options specific to keyring migration. Any additional options can be ignored.
NOTE: Although some options are valid, migration tool can still report error example: plugin variables for which plugin is not loaded yet.

`ER_KEYRING_MIGRATION_EXTRA_OPTIONS` was added in 8.0.11.

- Error number: `MY-011825`; Symbol: `ER_IB_MSG_0`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_0` was added in 8.0.11.

- Error number: `MY-011826`; Symbol: `ER_IB_MSG_1`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1` was added in 8.0.11.

- Error number: `MY-011827`; Symbol: `ER_IB_MSG_2`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_2` was added in 8.0.11.

- Error number: `MY-011828`; Symbol: `ER_IB_MSG_3`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_3` was added in 8.0.11.

- Error number: `MY-011829`; Symbol: `ER_IB_MSG_4`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_4` was added in 8.0.11.

- Error number: `MY-011830`; Symbol: `ER_IB_MSG_5`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_5` was added in 8.0.11.

- Error number: `MY-011831`; Symbol: `ER_IB_MSG_6`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_6` was added in 8.0.11.

- Error number: `MY-011832`; Symbol: `ER_IB_MSG_7`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_7` was added in 8.0.11.

-
- Error number: [MY-011833](#); Symbol: [ER_IB_MSG_8](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_8](#) was added in 8.0.11.
 - Error number: [MY-011834](#); Symbol: [ER_IB_MSG_9](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_9](#) was added in 8.0.11.
 - Error number: [MY-011835](#); Symbol: [ER_IB_MSG_10](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_10](#) was added in 8.0.11.
 - Error number: [MY-011836](#); Symbol: [ER_IB_MSG_11](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_11](#) was added in 8.0.11.
 - Error number: [MY-011837](#); Symbol: [ER_IB_MSG_12](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_12](#) was added in 8.0.11.
 - Error number: [MY-011838](#); Symbol: [ER_IB_MSG_13](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_13](#) was added in 8.0.11.
 - Error number: [MY-011839](#); Symbol: [ER_IB_MSG_14](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_14](#) was added in 8.0.11.
 - Error number: [MY-011840](#); Symbol: [ER_IB_MSG_15](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_15](#) was added in 8.0.11.
 - Error number: [MY-011841](#); Symbol: [ER_IB_MSG_16](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_16](#) was added in 8.0.11.
 - Error number: [MY-011842](#); Symbol: [ER_IB_MSG_17](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_17](#) was added in 8.0.11.
 - Error number: [MY-011843](#); Symbol: [ER_IB_MSG_18](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_18](#) was added in 8.0.11.

-
- Error number: [MY-011844](#); Symbol: [ER_IB_MSG_19](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_19](#) was added in 8.0.11.
 - Error number: [MY-011845](#); Symbol: [ER_IB_MSG_20](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_20](#) was added in 8.0.11.
 - Error number: [MY-011846](#); Symbol: [ER_IB_MSG_21](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_21](#) was added in 8.0.11.
 - Error number: [MY-011847](#); Symbol: [ER_IB_MSG_22](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_22](#) was added in 8.0.11.
 - Error number: [MY-011848](#); Symbol: [ER_IB_MSG_23](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_23](#) was added in 8.0.11.
 - Error number: [MY-011849](#); Symbol: [ER_IB_MSG_24](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_24](#) was added in 8.0.11.
 - Error number: [MY-011850](#); Symbol: [ER_IB_MSG_25](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_25](#) was added in 8.0.11.
 - Error number: [MY-011851](#); Symbol: [ER_IB_MSG_26](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_26](#) was added in 8.0.11.
 - Error number: [MY-011852](#); Symbol: [ER_IB_MSG_27](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_27](#) was added in 8.0.11.
 - Error number: [MY-011853](#); Symbol: [ER_IB_MSG_28](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_28](#) was added in 8.0.11.
 - Error number: [MY-011854](#); Symbol: [ER_IB_MSG_29](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_29](#) was added in 8.0.11.

-
- Error number: [MY-011855](#); Symbol: [ER_IB_MSG_30](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_30](#) was added in 8.0.11.
 - Error number: [MY-011856](#); Symbol: [ER_IB_MSG_31](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_31](#) was added in 8.0.11.
 - Error number: [MY-011857](#); Symbol: [ER_IB_MSG_32](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_32](#) was added in 8.0.11.
 - Error number: [MY-011858](#); Symbol: [ER_IB_MSG_33](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_33](#) was added in 8.0.11.
 - Error number: [MY-011859](#); Symbol: [ER_IB_MSG_34](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_34](#) was added in 8.0.11.
 - Error number: [MY-011860](#); Symbol: [ER_IB_MSG_35](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_35](#) was added in 8.0.11.
 - Error number: [MY-011861](#); Symbol: [ER_IB_MSG_36](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_36](#) was added in 8.0.11.
 - Error number: [MY-011862](#); Symbol: [ER_IB_MSG_37](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_37](#) was added in 8.0.11.
 - Error number: [MY-011863](#); Symbol: [ER_IB_MSG_38](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_38](#) was added in 8.0.11.
 - Error number: [MY-011864](#); Symbol: [ER_IB_MSG_39](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_39](#) was added in 8.0.11.
 - Error number: [MY-011865](#); Symbol: [ER_IB_MSG_40](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_40](#) was added in 8.0.11.

-
- Error number: [MY-011866](#); Symbol: [ER_IB_MSG_41](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_41](#) was added in 8.0.11.
 - Error number: [MY-011867](#); Symbol: [ER_IB_MSG_42](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_42](#) was added in 8.0.11.
 - Error number: [MY-011868](#); Symbol: [ER_IB_MSG_43](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_43](#) was added in 8.0.11.
 - Error number: [MY-011869](#); Symbol: [ER_IB_MSG_44](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_44](#) was added in 8.0.11.
 - Error number: [MY-011870](#); Symbol: [ER_IB_MSG_45](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_45](#) was added in 8.0.11.
 - Error number: [MY-011871](#); Symbol: [ER_IB_MSG_46](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_46](#) was added in 8.0.11.
 - Error number: [MY-011872](#); Symbol: [ER_IB_MSG_47](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_47](#) was added in 8.0.11.
 - Error number: [MY-011873](#); Symbol: [ER_IB_MSG_48](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_48](#) was added in 8.0.11.
 - Error number: [MY-011874](#); Symbol: [ER_IB_MSG_49](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_49](#) was added in 8.0.11.
 - Error number: [MY-011875](#); Symbol: [ER_IB_MSG_50](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_50](#) was added in 8.0.11.
 - Error number: [MY-011876](#); Symbol: [ER_IB_MSG_51](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_51](#) was added in 8.0.11.

-
- Error number: [MY-011877](#); Symbol: [ER_IB_MSG_52](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_52](#) was added in 8.0.11.
 - Error number: [MY-011878](#); Symbol: [ER_IB_MSG_53](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_53](#) was added in 8.0.11.
 - Error number: [MY-011879](#); Symbol: [ER_IB_MSG_54](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_54](#) was added in 8.0.11.
 - Error number: [MY-011880](#); Symbol: [ER_IB_MSG_55](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_55](#) was added in 8.0.11.
 - Error number: [MY-011881](#); Symbol: [ER_IB_MSG_56](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_56](#) was added in 8.0.11.
 - Error number: [MY-011882](#); Symbol: [ER_IB_MSG_57](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_57](#) was added in 8.0.11.
 - Error number: [MY-011883](#); Symbol: [ER_IB_MSG_58](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_58](#) was added in 8.0.11.
 - Error number: [MY-011884](#); Symbol: [ER_IB_MSG_59](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_59](#) was added in 8.0.11.
 - Error number: [MY-011885](#); Symbol: [ER_IB_MSG_60](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_60](#) was added in 8.0.11.
 - Error number: [MY-011886](#); Symbol: [ER_IB_MSG_61](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_61](#) was added in 8.0.11.
 - Error number: [MY-011887](#); Symbol: [ER_IB_MSG_62](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_62](#) was added in 8.0.11.

-
- Error number: [MY-011888](#); Symbol: [ER_IB_MSG_63](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_63](#) was added in 8.0.11.
 - Error number: [MY-011889](#); Symbol: [ER_IB_MSG_64](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_64](#) was added in 8.0.11.
 - Error number: [MY-011890](#); Symbol: [ER_IB_MSG_65](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_65](#) was added in 8.0.11.
 - Error number: [MY-011891](#); Symbol: [ER_IB_MSG_66](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_66](#) was added in 8.0.11.
 - Error number: [MY-011892](#); Symbol: [ER_IB_MSG_67](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_67](#) was added in 8.0.11.
 - Error number: [MY-011893](#); Symbol: [ER_IB_MSG_68](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_68](#) was added in 8.0.11.
 - Error number: [MY-011894](#); Symbol: [ER_IB_MSG_69](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_69](#) was added in 8.0.11.
 - Error number: [MY-011895](#); Symbol: [ER_IB_MSG_70](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_70](#) was added in 8.0.11.
 - Error number: [MY-011896](#); Symbol: [ER_IB_MSG_71](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_71](#) was added in 8.0.11.
 - Error number: [MY-011897](#); Symbol: [ER_IB_MSG_72](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_72](#) was added in 8.0.11.
 - Error number: [MY-011898](#); Symbol: [ER_IB_MSG_73](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_73](#) was added in 8.0.11.

-
- Error number: [MY-011899](#); Symbol: [ER_IB_MSG_74](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_74](#) was added in 8.0.11.
 - Error number: [MY-011900](#); Symbol: [ER_IB_MSG_75](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_75](#) was added in 8.0.11.
 - Error number: [MY-011901](#); Symbol: [ER_IB_MSG_76](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_76](#) was added in 8.0.11.
 - Error number: [MY-011902](#); Symbol: [ER_IB_MSG_77](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_77](#) was added in 8.0.11.
 - Error number: [MY-011903](#); Symbol: [ER_IB_MSG_78](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_78](#) was added in 8.0.11.
 - Error number: [MY-011904](#); Symbol: [ER_IB_MSG_79](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_79](#) was added in 8.0.11.
 - Error number: [MY-011905](#); Symbol: [ER_IB_MSG_80](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_80](#) was added in 8.0.11.
 - Error number: [MY-011906](#); Symbol: [ER_IB_MSG_81](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_81](#) was added in 8.0.11.
 - Error number: [MY-011907](#); Symbol: [ER_IB_MSG_82](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_82](#) was added in 8.0.11.
 - Error number: [MY-011908](#); Symbol: [ER_IB_MSG_83](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_83](#) was added in 8.0.11.
 - Error number: [MY-011909](#); Symbol: [ER_IB_MSG_84](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_84](#) was added in 8.0.11.

-
- Error number: [MY-011910](#); Symbol: [ER_IB_MSG_85](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_85](#) was added in 8.0.11.
 - Error number: [MY-011911](#); Symbol: [ER_IB_MSG_86](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_86](#) was added in 8.0.11.
 - Error number: [MY-011912](#); Symbol: [ER_IB_MSG_87](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_87](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-011913](#); Symbol: [ER_IB_MSG_88](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_88](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-011914](#); Symbol: [ER_IB_MSG_89](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_89](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-011915](#); Symbol: [ER_IB_MSG_90](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_90](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-011916](#); Symbol: [ER_IB_MSG_91](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_91](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-011917](#); Symbol: [ER_IB_MSG_92](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_92](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-011918](#); Symbol: [ER_IB_MSG_93](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_93](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-011919](#); Symbol: [ER_IB_MSG_94](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_94](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-011920](#); Symbol: [ER_IB_MSG_95](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_95](#) was added in 8.0.11.

-
- Error number: [MY-011921](#); Symbol: [ER_IB_MSG_96](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_96](#) was added in 8.0.11.
 - Error number: [MY-011922](#); Symbol: [ER_IB_MSG_97](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_97](#) was added in 8.0.11.
 - Error number: [MY-011923](#); Symbol: [ER_IB_MSG_98](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_98](#) was added in 8.0.11.
 - Error number: [MY-011924](#); Symbol: [ER_IB_MSG_99](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_99](#) was added in 8.0.11.
 - Error number: [MY-011925](#); Symbol: [ER_IB_MSG_100](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_100](#) was added in 8.0.11.
 - Error number: [MY-011926](#); Symbol: [ER_IB_MSG_101](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_101](#) was added in 8.0.11.
 - Error number: [MY-011927](#); Symbol: [ER_IB_MSG_102](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_102](#) was added in 8.0.11.
 - Error number: [MY-011928](#); Symbol: [ER_IB_MSG_103](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_103](#) was added in 8.0.11.
 - Error number: [MY-011929](#); Symbol: [ER_IB_MSG_104](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_104](#) was added in 8.0.11.
 - Error number: [MY-011930](#); Symbol: [ER_IB_MSG_105](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_105](#) was added in 8.0.11.
 - Error number: [MY-011931](#); Symbol: [ER_IB_MSG_106](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_106](#) was added in 8.0.11.

-
- Error number: [MY-011932](#); Symbol: [ER_IB_MSG_107](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_107](#) was added in 8.0.11.
 - Error number: [MY-011933](#); Symbol: [ER_IB_MSG_108](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_108](#) was added in 8.0.11.
 - Error number: [MY-011934](#); Symbol: [ER_IB_MSG_109](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_109](#) was added in 8.0.11.
 - Error number: [MY-011935](#); Symbol: [ER_IB_MSG_110](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_110](#) was added in 8.0.11.
 - Error number: [MY-011936](#); Symbol: [ER_IB_MSG_111](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_111](#) was added in 8.0.11.
 - Error number: [MY-011937](#); Symbol: [ER_IB_MSG_112](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_112](#) was added in 8.0.11.
 - Error number: [MY-011938](#); Symbol: [ER_IB_MSG_113](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_113](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-011939](#); Symbol: [ER_IB_MSG_114](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_114](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-011940](#); Symbol: [ER_IB_MSG_115](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_115](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-011941](#); Symbol: [ER_IB_MSG_116](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_116](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-011942](#); Symbol: [ER_IB_MSG_117](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_117](#) was added in 8.0.11, removed after 8.0.13.

- Error number: MY-011943; Symbol: ER_IB_MSG_118; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_118` was added in 8.0.11, removed after 8.0.13.
- Error number: MY-011944; Symbol: ER_IB_MSG_119; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_119` was added in 8.0.11.
- Error number: MY-011945; Symbol: ER_IB_MSG_120; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_120` was added in 8.0.11.
- Error number: MY-011946; Symbol: ER_IB_MSG_121; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_121` was added in 8.0.11.
- Error number: MY-011947; Symbol: ER_IB_MSG_122; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_122` was added in 8.0.11.
- Error number: MY-011948; Symbol: ER_IB_MSG_123; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_123` was added in 8.0.11.
- Error number: MY-011949; Symbol: ER_IB_MSG_124; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_124` was added in 8.0.11.
- Error number: MY-011950; Symbol: ER_IB_MSG_125; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_125` was added in 8.0.11.
- Error number: MY-011951; Symbol: ER_IB_MSG_126; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_126` was added in 8.0.11.
- Error number: MY-011952; Symbol: ER_IB_MSG_127; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_127` was added in 8.0.11.
- Error number: MY-011953; Symbol: ER_IB_MSG_128; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_128` was added in 8.0.11.

-
- Error number: [MY-011954](#); Symbol: [ER_IB_MSG_129](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_129](#) was added in 8.0.11.
 - Error number: [MY-011955](#); Symbol: [ER_IB_MSG_130](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_130](#) was added in 8.0.11.
 - Error number: [MY-011956](#); Symbol: [ER_IB_MSG_131](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_131](#) was added in 8.0.11.
 - Error number: [MY-011957](#); Symbol: [ER_IB_MSG_132](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_132](#) was added in 8.0.11.
 - Error number: [MY-011958](#); Symbol: [ER_IB_MSG_133](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_133](#) was added in 8.0.11.
 - Error number: [MY-011959](#); Symbol: [ER_IB_MSG_134](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_134](#) was added in 8.0.11.
 - Error number: [MY-011960](#); Symbol: [ER_IB_MSG_135](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_135](#) was added in 8.0.11.
 - Error number: [MY-011961](#); Symbol: [ER_IB_MSG_136](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_136](#) was added in 8.0.11.
 - Error number: [MY-011962](#); Symbol: [ER_IB_MSG_137](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_137](#) was added in 8.0.11.
 - Error number: [MY-011963](#); Symbol: [ER_IB_MSG_138](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_138](#) was added in 8.0.11.
 - Error number: [MY-011964](#); Symbol: [ER_IB_MSG_139](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_139](#) was added in 8.0.11.

- Error number: MY-011965; Symbol: ER_IB_MSG_140; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_140` was added in 8.0.11.
- Error number: MY-011966; Symbol: ER_IB_MSG_141; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_141` was added in 8.0.11.
- Error number: MY-011967; Symbol: ER_IB_MSG_142; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_142` was added in 8.0.11.
- Error number: MY-011968; Symbol: ER_IB_MSG_143; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_143` was added in 8.0.11.
- Error number: MY-011969; Symbol: ER_IB_MSG_144; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_144` was added in 8.0.11.
- Error number: MY-011970; Symbol: ER_IB_MSG_145; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_145` was added in 8.0.11.
- Error number: MY-011971; Symbol: ER_IB_MSG_146; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_146` was added in 8.0.11.
- Error number: MY-011972; Symbol: ER_IB_MSG_147; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_147` was added in 8.0.11.
- Error number: MY-011973; Symbol: ER_IB_MSG_148; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_148` was added in 8.0.11.
- Error number: MY-011974; Symbol: ER_IB_MSG_149; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_149` was added in 8.0.11, removed after 8.0.16.
- Error number: MY-011974; Symbol: ER_IB_CLONE_INTERNAL; SQLSTATE: HY000
Message: %s
`ER_IB_CLONE_INTERNAL` was added in 8.0.17.

-
- Error number: [MY-011975](#); Symbol: [ER_IB_MSG_150](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_150](#) was added in 8.0.11, removed after 8.0.16.
 - Error number: [MY-011975](#); Symbol: [ER_IB_CLONE_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_CLONE_TIMEOUT](#) was added in 8.0.17.
 - Error number: [MY-011976](#); Symbol: [ER_IB_MSG_151](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_151](#) was added in 8.0.11, removed after 8.0.16.
 - Error number: [MY-011976](#); Symbol: [ER_IB_CLONE_STATUS_FILE](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_CLONE_STATUS_FILE](#) was added in 8.0.17.
 - Error number: [MY-011977](#); Symbol: [ER_IB_MSG_152](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_152](#) was added in 8.0.11, removed after 8.0.16.
 - Error number: [MY-011977](#); Symbol: [ER_IB_CLONE_SQL](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_CLONE_SQL](#) was added in 8.0.17.
 - Error number: [MY-011978](#); Symbol: [ER_IB_MSG_153](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_153](#) was added in 8.0.11, removed after 8.0.16.
 - Error number: [MY-011978](#); Symbol: [ER_IB_CLONE_VALIDATE](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_CLONE_VALIDATE](#) was added in 8.0.17.
 - Error number: [MY-011979](#); Symbol: [ER_IB_MSG_154](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_154](#) was added in 8.0.11, removed after 8.0.16.
 - Error number: [MY-011979](#); Symbol: [ER_IB_CLONE_PUNCH_HOLE](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_CLONE_PUNCH_HOLE](#) was added in 8.0.17.
 - Error number: [MY-011980](#); Symbol: [ER_IB_MSG_155](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_155](#) was added in 8.0.11, removed after 8.0.16.

- Error number: MY-011980; Symbol: `ER_IB_CLONE_GTID_PERSIST`; SQLSTATE: HY000
Message: %s
`ER_IB_CLONE_GTID_PERSIST` was added in 8.0.17.
- Error number: MY-011981; Symbol: `ER_IB_MSG_156`; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_156` was added in 8.0.11.
- Error number: MY-011982; Symbol: `ER_IB_MSG_157`; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_157` was added in 8.0.11.
- Error number: MY-011983; Symbol: `ER_IB_MSG_158`; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_158` was added in 8.0.11.
- Error number: MY-011984; Symbol: `ER_IB_MSG_159`; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_159` was added in 8.0.11.
- Error number: MY-011985; Symbol: `ER_IB_MSG_160`; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_160` was added in 8.0.11.
- Error number: MY-011986; Symbol: `ER_IB_MSG_161`; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_161` was added in 8.0.11.
- Error number: MY-011987; Symbol: `ER_IB_MSG_162`; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_162` was added in 8.0.11.
- Error number: MY-011988; Symbol: `ER_IB_MSG_163`; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_163` was added in 8.0.11.
- Error number: MY-011989; Symbol: `ER_IB_MSG_164`; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_164` was added in 8.0.11.
- Error number: MY-011990; Symbol: `ER_IB_MSG_165`; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_165` was added in 8.0.11.

-
- Error number: [MY-011991](#); Symbol: [ER_IB_MSG_166](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_166](#) was added in 8.0.11.
 - Error number: [MY-011992](#); Symbol: [ER_IB_MSG_167](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_167](#) was added in 8.0.11.
 - Error number: [MY-011993](#); Symbol: [ER_IB_MSG_168](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_168](#) was added in 8.0.11.
 - Error number: [MY-011994](#); Symbol: [ER_IB_MSG_169](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_169](#) was added in 8.0.11.
 - Error number: [MY-011995](#); Symbol: [ER_IB_MSG_170](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_170](#) was added in 8.0.11.
 - Error number: [MY-011996](#); Symbol: [ER_IB_MSG_171](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_171](#) was added in 8.0.11.
 - Error number: [MY-011997](#); Symbol: [ER_IB_MSG_172](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_172](#) was added in 8.0.11.
 - Error number: [MY-011998](#); Symbol: [ER_IB_MSG_173](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_173](#) was added in 8.0.11.
 - Error number: [MY-011999](#); Symbol: [ER_IB_MSG_174](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_174](#) was added in 8.0.11.
 - Error number: [MY-012000](#); Symbol: [ER_IB_MSG_175](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_175](#) was added in 8.0.11.
 - Error number: [MY-012001](#); Symbol: [ER_IB_MSG_176](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_176](#) was added in 8.0.11.

- Error number: MY-012002; Symbol: ER_IB_MSG_177; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_177` was added in 8.0.11.
- Error number: MY-012003; Symbol: ER_IB_MSG_178; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_178` was added in 8.0.11.
- Error number: MY-012004; Symbol: ER_IB_MSG_179; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_179` was added in 8.0.11.
- Error number: MY-012005; Symbol: ER_IB_MSG_180; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_180` was added in 8.0.11.
- Error number: MY-012006; Symbol: ER_IB_MSG_181; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_181` was added in 8.0.11.
- Error number: MY-012007; Symbol: ER_IB_MSG_182; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_182` was added in 8.0.11.
- Error number: MY-012008; Symbol: ER_IB_MSG_183; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_183` was added in 8.0.11.
- Error number: MY-012009; Symbol: ER_IB_MSG_184; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_184` was added in 8.0.11.
- Error number: MY-012010; Symbol: ER_IB_MSG_185; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_185` was added in 8.0.11.
- Error number: MY-012011; Symbol: ER_IB_MSG_186; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_186` was added in 8.0.11.
- Error number: MY-012012; Symbol: ER_IB_MSG_187; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_187` was added in 8.0.11.

-
- Error number: [MY-012013](#); Symbol: [ER_IB_MSG_188](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_188](#) was added in 8.0.11.
 - Error number: [MY-012014](#); Symbol: [ER_IB_MSG_189](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_189](#) was added in 8.0.11.
 - Error number: [MY-012015](#); Symbol: [ER_IB_MSG_190](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_190](#) was added in 8.0.11.
 - Error number: [MY-012016](#); Symbol: [ER_IB_MSG_191](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_191](#) was added in 8.0.11.
 - Error number: [MY-012017](#); Symbol: [ER_IB_MSG_192](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_192](#) was added in 8.0.11.
 - Error number: [MY-012018](#); Symbol: [ER_IB_MSG_193](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_193](#) was added in 8.0.11.
 - Error number: [MY-012019](#); Symbol: [ER_IB_MSG_194](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_194](#) was added in 8.0.11.
 - Error number: [MY-012020](#); Symbol: [ER_IB_MSG_195](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_195](#) was added in 8.0.11.
 - Error number: [MY-012021](#); Symbol: [ER_IB_MSG_196](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_196](#) was added in 8.0.11.
 - Error number: [MY-012022](#); Symbol: [ER_IB_MSG_197](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_197](#) was added in 8.0.11.
 - Error number: [MY-012023](#); Symbol: [ER_IB_MSG_198](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_198](#) was added in 8.0.11.

- Error number: MY-012024; Symbol: ER_IB_MSG_199; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_199](#) was added in 8.0.11.
- Error number: MY-012025; Symbol: ER_IB_MSG_200; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_200](#) was added in 8.0.11.
- Error number: MY-012026; Symbol: ER_IB_MSG_201; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_201](#) was added in 8.0.11.
- Error number: MY-012027; Symbol: ER_IB_MSG_202; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_202](#) was added in 8.0.11.
- Error number: MY-012028; Symbol: ER_IB_MSG_203; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_203](#) was added in 8.0.11.
- Error number: MY-012029; Symbol: ER_IB_MSG_204; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_204](#) was added in 8.0.11.
- Error number: MY-012030; Symbol: ER_IB_MSG_205; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_205](#) was added in 8.0.11.
- Error number: MY-012031; Symbol: ER_IB_MSG_206; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_206](#) was added in 8.0.11.
- Error number: MY-012032; Symbol: ER_IB_MSG_207; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_207](#) was added in 8.0.11.
- Error number: MY-012033; Symbol: ER_IB_MSG_208; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_208](#) was added in 8.0.11.
- Error number: MY-012034; Symbol: ER_IB_MSG_209; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_209](#) was added in 8.0.11.

-
- Error number: [MY-012035](#); Symbol: [ER_IB_MSG_210](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_210](#) was added in 8.0.11.
 - Error number: [MY-012036](#); Symbol: [ER_IB_MSG_211](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_211](#) was added in 8.0.11.
 - Error number: [MY-012037](#); Symbol: [ER_IB_MSG_212](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_212](#) was added in 8.0.11.
 - Error number: [MY-012038](#); Symbol: [ER_IB_MSG_213](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_213](#) was added in 8.0.11.
 - Error number: [MY-012039](#); Symbol: [ER_IB_MSG_214](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_214](#) was added in 8.0.11.
 - Error number: [MY-012040](#); Symbol: [ER_IB_MSG_215](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_215](#) was added in 8.0.11.
 - Error number: [MY-012041](#); Symbol: [ER_IB_MSG_216](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_216](#) was added in 8.0.11.
 - Error number: [MY-012042](#); Symbol: [ER_IB_MSG_217](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_217](#) was added in 8.0.11.
 - Error number: [MY-012043](#); Symbol: [ER_IB_MSG_218](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_218](#) was added in 8.0.11.
 - Error number: [MY-012044](#); Symbol: [ER_IB_MSG_219](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_219](#) was added in 8.0.11.
 - Error number: [MY-012045](#); Symbol: [ER_IB_MSG_220](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_220](#) was added in 8.0.11.

- Error number: MY-012046; Symbol: ER_IB_MSG_221; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_221` was added in 8.0.11.
- Error number: MY-012047; Symbol: ER_IB_MSG_222; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_222` was added in 8.0.11.
- Error number: MY-012048; Symbol: ER_IB_MSG_223; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_223` was added in 8.0.11.
- Error number: MY-012049; Symbol: ER_IB_MSG_224; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_224` was added in 8.0.11.
- Error number: MY-012050; Symbol: ER_IB_MSG_225; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_225` was added in 8.0.11.
- Error number: MY-012051; Symbol: ER_IB_MSG_226; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_226` was added in 8.0.11.
- Error number: MY-012052; Symbol: ER_IB_MSG_227; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_227` was added in 8.0.11.
- Error number: MY-012053; Symbol: ER_IB_MSG_228; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_228` was added in 8.0.11.
- Error number: MY-012054; Symbol: ER_IB_MSG_229; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_229` was added in 8.0.11.
- Error number: MY-012055; Symbol: ER_IB_MSG_230; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_230` was added in 8.0.11.
- Error number: MY-012056; Symbol: ER_IB_MSG_231; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_231` was added in 8.0.11.

-
- Error number: [MY-012057](#); Symbol: [ER_IB_MSG_232](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_232](#) was added in 8.0.11.
 - Error number: [MY-012058](#); Symbol: [ER_IB_MSG_233](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_233](#) was added in 8.0.11.
 - Error number: [MY-012059](#); Symbol: [ER_IB_MSG_234](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_234](#) was added in 8.0.11.
 - Error number: [MY-012060](#); Symbol: [ER_IB_MSG_235](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_235](#) was added in 8.0.11.
 - Error number: [MY-012061](#); Symbol: [ER_IB_MSG_236](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_236](#) was added in 8.0.11.
 - Error number: [MY-012062](#); Symbol: [ER_IB_MSG_237](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_237](#) was added in 8.0.11.
 - Error number: [MY-012063](#); Symbol: [ER_IB_MSG_238](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_238](#) was added in 8.0.11.
 - Error number: [MY-012064](#); Symbol: [ER_IB_MSG_239](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_239](#) was added in 8.0.11.
 - Error number: [MY-012065](#); Symbol: [ER_IB_MSG_240](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_240](#) was added in 8.0.11.
 - Error number: [MY-012066](#); Symbol: [ER_IB_MSG_241](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_241](#) was added in 8.0.11.
 - Error number: [MY-012067](#); Symbol: [ER_IB_MSG_242](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_242](#) was added in 8.0.11.

- Error number: MY-012068; Symbol: ER_IB_MSG_243; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_243](#) was added in 8.0.11.
- Error number: MY-012069; Symbol: ER_IB_MSG_244; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_244](#) was added in 8.0.11.
- Error number: MY-012070; Symbol: ER_IB_MSG_245; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_245](#) was added in 8.0.11.
- Error number: MY-012071; Symbol: ER_IB_MSG_246; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_246](#) was added in 8.0.11.
- Error number: MY-012072; Symbol: ER_IB_MSG_247; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_247](#) was added in 8.0.11.
- Error number: MY-012073; Symbol: ER_IB_MSG_248; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_248](#) was added in 8.0.11.
- Error number: MY-012074; Symbol: ER_IB_MSG_249; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_249](#) was added in 8.0.11.
- Error number: MY-012075; Symbol: ER_IB_MSG_250; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_250](#) was added in 8.0.11.
- Error number: MY-012076; Symbol: ER_IB_MSG_251; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_251](#) was added in 8.0.11.
- Error number: MY-012077; Symbol: ER_IB_MSG_252; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_252](#) was added in 8.0.11.
- Error number: MY-012078; Symbol: ER_IB_MSG_253; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_253](#) was added in 8.0.11.

-
- Error number: [MY-012079](#); Symbol: [ER_IB_MSG_254](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_254](#) was added in 8.0.11.
 - Error number: [MY-012080](#); Symbol: [ER_IB_MSG_255](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_255](#) was added in 8.0.11.
 - Error number: [MY-012081](#); Symbol: [ER_IB_MSG_256](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_256](#) was added in 8.0.11.
 - Error number: [MY-012082](#); Symbol: [ER_IB_MSG_257](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_257](#) was added in 8.0.11.
 - Error number: [MY-012083](#); Symbol: [ER_IB_MSG_258](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_258](#) was added in 8.0.11.
 - Error number: [MY-012084](#); Symbol: [ER_IB_MSG_259](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_259](#) was added in 8.0.11.
 - Error number: [MY-012085](#); Symbol: [ER_IB_MSG_260](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_260](#) was added in 8.0.11.
 - Error number: [MY-012086](#); Symbol: [ER_IB_MSG_261](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_261](#) was added in 8.0.11.
 - Error number: [MY-012087](#); Symbol: [ER_IB_MSG_262](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_262](#) was added in 8.0.11.
 - Error number: [MY-012088](#); Symbol: [ER_IB_MSG_263](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_263](#) was added in 8.0.11.
 - Error number: [MY-012089](#); Symbol: [ER_IB_MSG_264](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_264](#) was added in 8.0.11.

- Error number: MY-012090; Symbol: ER_IB_MSG_265; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_265` was added in 8.0.11.
- Error number: MY-012091; Symbol: ER_IB_MSG_266; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_266` was added in 8.0.11.
- Error number: MY-012092; Symbol: ER_IB_MSG_267; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_267` was added in 8.0.11.
- Error number: MY-012093; Symbol: ER_IB_MSG_268; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_268` was added in 8.0.11.
- Error number: MY-012094; Symbol: ER_IB_MSG_269; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_269` was added in 8.0.11.
- Error number: MY-012095; Symbol: ER_IB_MSG_270; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_270` was added in 8.0.11.
- Error number: MY-012096; Symbol: ER_IB_MSG_271; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_271` was added in 8.0.11.
- Error number: MY-012097; Symbol: ER_IB_MSG_272; SQLSTATE: HY000
Message: Table flags are 0x%lx in the data dictionary but the flags in file %s are 0x%llx!
`ER_IB_MSG_272` was added in 8.0.11.
- Error number: MY-012098; Symbol: ER_IB_MSG_273; SQLSTATE: HY000
Message: Can't read encryption key from file %s!
`ER_IB_MSG_273` was added in 8.0.11.
- Error number: MY-012099; Symbol: ER_IB_MSG_274; SQLSTATE: HY000
Message: Cannot close file %s, because n_pending_flushes %zu
`ER_IB_MSG_274` was added in 8.0.11.
- Error number: MY-012100; Symbol: ER_IB_MSG_275; SQLSTATE: HY000
Message: Cannot close file %s, because modification count %lld != flush count %lld
`ER_IB_MSG_275` was added in 8.0.11.

-
- Error number: [MY-012101](#); Symbol: [ER_IB_MSG_276](#); SQLSTATE: [HY000](#)

Message: Cannot close file %s, because it is in use
[ER_IB_MSG_276](#) was added in 8.0.11.
 - Error number: [MY-012102](#); Symbol: [ER_IB_MSG_277](#); SQLSTATE: [HY000](#)

Message: Open file list len in shard %zu is %lu
[ER_IB_MSG_277](#) was added in 8.0.11.
 - Error number: [MY-012103](#); Symbol: [ER_IB_MSG_278](#); SQLSTATE: [HY000](#)

Message: Tablespace %s, waiting for IO to stop for %lld seconds
[ER_IB_MSG_278](#) was added in 8.0.11.
 - Error number: [MY-012104](#); Symbol: [ER_IB_MSG_279](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_279](#) was added in 8.0.11.
 - Error number: [MY-012105](#); Symbol: [ER_IB_MSG_280](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_280](#) was added in 8.0.11.
 - Error number: [MY-012106](#); Symbol: [ER_IB_MSG_281](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_281](#) was added in 8.0.11.
 - Error number: [MY-012107](#); Symbol: [ER_IB_MSG_282](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_282](#) was added in 8.0.11.
 - Error number: [MY-012108](#); Symbol: [ER_IB_MSG_283](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_283](#) was added in 8.0.11.
 - Error number: [MY-012109](#); Symbol: [ER_IB_MSG_284](#); SQLSTATE: [HY000](#)

Message: You must raise the value of innodb_open_files in my.cnf! Remember that InnoDB keeps all log files and all system tablespace files open for the whole time mysqld is running, and needs to open also some .ibd files if the file-per-table storage model is used. Current open files %zu, max allowed open files %zu.
[ER_IB_MSG_284](#) was added in 8.0.11.
 - Error number: [MY-012110](#); Symbol: [ER_IB_MSG_285](#); SQLSTATE: [HY000](#)

Message: Max tablespace id is too high, %lu
[ER_IB_MSG_285](#) was added in 8.0.11.
 - Error number: [MY-012111](#); Symbol: [ER_IB_MSG_286](#); SQLSTATE: [HY000](#)

Message: Trying to access missing tablespace %lu

[ER_IB_MSG_286](#) was added in 8.0.11.

- Error number: [MY-012112](#); Symbol: [ER_IB_MSG_287](#); SQLSTATE: [HY000](#)

Message: Trying to close/delete tablespace '%s' but there are %lu pending operations on it.

[ER_IB_MSG_287](#) was added in 8.0.11.

- Error number: [MY-012113](#); Symbol: [ER_IB_MSG_288](#); SQLSTATE: [HY000](#)

Message: Trying to delete/close tablespace '%s' but there are %lu flushes and %zu pending I/O's on it.

[ER_IB_MSG_288](#) was added in 8.0.11.

- Error number: [MY-012114](#); Symbol: [ER_IB_MSG_289](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_289](#) was added in 8.0.11.

- Error number: [MY-012115](#); Symbol: [ER_IB_MSG_290](#); SQLSTATE: [HY000](#)

Message: Cannot delete tablespace %lu because it is not found in the tablespace memory cache.

[ER_IB_MSG_290](#) was added in 8.0.11, removed after 8.0.17.

- Error number: [MY-012116](#); Symbol: [ER_IB_MSG_291](#); SQLSTATE: [HY000](#)

Message: While deleting tablespace %lu in DISCARD TABLESPACE. File rename/delete failed: %s

[ER_IB_MSG_291](#) was added in 8.0.11.

- Error number: [MY-012117](#); Symbol: [ER_IB_MSG_292](#); SQLSTATE: [HY000](#)

Message: Cannot delete tablespace %lu in DISCARD TABLESPACE: %s

[ER_IB_MSG_292](#) was added in 8.0.11.

- Error number: [MY-012118](#); Symbol: [ER_IB_MSG_293](#); SQLSTATE: [HY000](#)

Message: Cannot rename '%s' to '%s' for space ID %lu because the source file does not exist.

[ER_IB_MSG_293](#) was added in 8.0.11.

- Error number: [MY-012119](#); Symbol: [ER_IB_MSG_294](#); SQLSTATE: [HY000](#)

Message: Cannot rename '%s' to '%s' for space ID %lu because the target file exists. Remove the target file and try again.

[ER_IB_MSG_294](#) was added in 8.0.11.

- Error number: [MY-012120](#); Symbol: [ER_IB_MSG_295](#); SQLSTATE: [HY000](#)

Message: Cannot rename file '%s' (space id %lu) retried %llu times. There are either pending IOs or flushes or the file is being extended.

[ER_IB_MSG_295](#) was added in 8.0.11.

-
- Error number: [MY-012121](#); Symbol: [ER_IB_MSG_296](#); SQLSTATE: [HY000](#)

Message: Cannot find space id %lu in the tablespace memory cache, though the file '%s' in a rename operation should have that ID.

[ER_IB_MSG_296](#) was added in 8.0.11.

- Error number: [MY-012122](#); Symbol: [ER_IB_MSG_297](#); SQLSTATE: [HY000](#)

Message: Rename waiting for IO to resume

[ER_IB_MSG_297](#) was added in 8.0.11.

- Error number: [MY-012123](#); Symbol: [ER_IB_MSG_298](#); SQLSTATE: [HY000](#)

Message: Cannot find tablespace for '%s' in the tablespace memory cache

[ER_IB_MSG_298](#) was added in 8.0.11.

- Error number: [MY-012124](#); Symbol: [ER_IB_MSG_299](#); SQLSTATE: [HY000](#)

Message: Cannot find tablespace for '%s' in the tablespace memory cache

[ER_IB_MSG_299](#) was added in 8.0.11.

- Error number: [MY-012125](#); Symbol: [ER_IB_MSG_300](#); SQLSTATE: [HY000](#)

Message: Tablespace '%s' is already in the tablespace memory cache

[ER_IB_MSG_300](#) was added in 8.0.11.

- Error number: [MY-012126](#); Symbol: [ER_IB_MSG_301](#); SQLSTATE: [HY000](#)

Message: Cannot create file '%s'

[ER_IB_MSG_301](#) was added in 8.0.11.

- Error number: [MY-012127](#); Symbol: [ER_IB_MSG_302](#); SQLSTATE: [HY000](#)

Message: The file '%s' already exists though the corresponding table did not exist. Have you moved InnoDB .ibd files around without using the SQL commands DISCARD TABLESPACE and IMPORT TABLESPACE, or did mysqld crash in the middle of CREATE TABLE? You can resolve the problem by removing the file '%s' under the 'datadir' of MySQL.

[ER_IB_MSG_302](#) was added in 8.0.11, removed after 8.0.16.

- Error number: [MY-012127](#); Symbol: [ER_IB_MSG_UNEXPECTED_FILE_EXISTS](#); SQLSTATE: [HY000](#)

Message: The file '%s' already exists though the corresponding table did not exist. Have you moved InnoDB .ibd files around without using the SQL commands DISCARD TABLESPACE and IMPORT TABLESPACE, or did mysqld crash in the middle of CREATE TABLE? You can resolve the problem by removing the file '%s' under the 'datadir' of MySQL.

[ER_IB_MSG_UNEXPECTED_FILE_EXISTS](#) was added in 8.0.17.

- Error number: [MY-012128](#); Symbol: [ER_IB_MSG_303](#); SQLSTATE: [HY000](#)

Message: posix_fallocate(): Failed to preallocate data for file %s, desired size %llu Operating system error number %d - %s. Check that the disk is not full or a disk quota exceeded. Make sure the file

system supports this function. Refer to your operating system documentation for operating system error code information.

[ER_IB_MSG_303](#) was added in 8.0.11.

- Error number: [MY-012129](#); Symbol: [ER_IB_MSG_304](#); SQLSTATE: [HY000](#)

Message: Could not write the first page to tablespace '%s'

[ER_IB_MSG_304](#) was added in 8.0.11.

- Error number: [MY-012130](#); Symbol: [ER_IB_MSG_305](#); SQLSTATE: [HY000](#)

Message: File flush of tablespace '%s' failed

[ER_IB_MSG_305](#) was added in 8.0.11.

- Error number: [MY-012131](#); Symbol: [ER_IB_MSG_306](#); SQLSTATE: [HY000](#)

Message: Could not find a valid tablespace file for `'%s` . %s

[ER_IB_MSG_306](#) was added in 8.0.11.

- Error number: [MY-012132](#); Symbol: [ER_IB_MSG_307](#); SQLSTATE: [HY000](#)

Message: Ignoring data file '%s' with space ID %lu. Another data file called '%s' exists with the same space ID

[ER_IB_MSG_307](#) was added in 8.0.11.

- Error number: [MY-012133](#); Symbol: [ER_IB_MSG_308](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_308](#) was added in 8.0.11.

- Error number: [MY-012134](#); Symbol: [ER_IB_MSG_309](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_309](#) was added in 8.0.11.

- Error number: [MY-012135](#); Symbol: [ER_IB_MSG_310](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_310](#) was added in 8.0.11.

- Error number: [MY-012136](#); Symbol: [ER_IB_MSG_311](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_311](#) was added in 8.0.11.

- Error number: [MY-012137](#); Symbol: [ER_IB_MSG_312](#); SQLSTATE: [HY000](#)

Message: Can't set encryption information for tablespace %s!

[ER_IB_MSG_312](#) was added in 8.0.11.

-
- Error number: [MY-012138](#); Symbol: [ER_IB_MSG_313](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_313](#) was added in 8.0.11.
 - Error number: [MY-012139](#); Symbol: [ER_IB_MSG_314](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_314](#) was added in 8.0.11.
 - Error number: [MY-012140](#); Symbol: [ER_IB_MSG_315](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_315](#) was added in 8.0.11.
 - Error number: [MY-012141](#); Symbol: [ER_IB_MSG_316](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_316](#) was added in 8.0.11.
 - Error number: [MY-012142](#); Symbol: [ER_IB_MSG_317](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_317](#) was added in 8.0.11.
 - Error number: [MY-012143](#); Symbol: [ER_IB_MSG_318](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_318](#) was added in 8.0.11.
 - Error number: [MY-012144](#); Symbol: [ER_IB_MSG_319](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_319](#) was added in 8.0.11.
 - Error number: [MY-012145](#); Symbol: [ER_IB_MSG_320](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_320](#) was added in 8.0.11.
 - Error number: [MY-012146](#); Symbol: [ER_IB_MSG_321](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_321](#) was added in 8.0.11.
 - Error number: [MY-012147](#); Symbol: [ER_IB_MSG_322](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_322](#) was added in 8.0.11.
 - Error number: [MY-012148](#); Symbol: [ER_IB_MSG_323](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_323](#) was added in 8.0.11.

- Error number: MY-012149; Symbol: ER_IB_MSG_324; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_324` was added in 8.0.11.
- Error number: MY-012150; Symbol: ER_IB_MSG_325; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_325` was added in 8.0.11.
- Error number: MY-012151; Symbol: ER_IB_MSG_326; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_326` was added in 8.0.11.
- Error number: MY-012152; Symbol: ER_IB_MSG_327; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_327` was added in 8.0.11.
- Error number: MY-012153; Symbol: ER_IB_MSG_328; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_328` was added in 8.0.11.
- Error number: MY-012154; Symbol: ER_IB_MSG_329; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_329` was added in 8.0.11.
- Error number: MY-012155; Symbol: ER_IB_MSG_330; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_330` was added in 8.0.11.
- Error number: MY-012156; Symbol: ER_IB_MSG_331; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_331` was added in 8.0.11.
- Error number: MY-012157; Symbol: ER_IB_MSG_332; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_332` was added in 8.0.11.
- Error number: MY-012158; Symbol: ER_IB_MSG_333; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_333` was added in 8.0.11.
- Error number: MY-012159; Symbol: ER_IB_MSG_334; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_334` was added in 8.0.11.

-
- Error number: [MY-012160](#); Symbol: [ER_IB_MSG_335](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_335](#) was added in 8.0.11.
 - Error number: [MY-012161](#); Symbol: [ER_IB_MSG_336](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_336](#) was added in 8.0.11.
 - Error number: [MY-012162](#); Symbol: [ER_IB_MSG_337](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_337](#) was added in 8.0.11.
 - Error number: [MY-012163](#); Symbol: [ER_IB_MSG_338](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_338](#) was added in 8.0.11.
 - Error number: [MY-012164](#); Symbol: [ER_IB_MSG_339](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_339](#) was added in 8.0.11.
 - Error number: [MY-012165](#); Symbol: [ER_IB_MSG_340](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_340](#) was added in 8.0.11.
 - Error number: [MY-012166](#); Symbol: [ER_IB_MSG_341](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_341](#) was added in 8.0.11.
 - Error number: [MY-012167](#); Symbol: [ER_IB_MSG_342](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_342](#) was added in 8.0.11.
 - Error number: [MY-012168](#); Symbol: [ER_IB_MSG_343](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_343](#) was added in 8.0.11.
 - Error number: [MY-012169](#); Symbol: [ER_IB_MSG_344](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_344](#) was added in 8.0.11.
 - Error number: [MY-012170](#); Symbol: [ER_IB_MSG_345](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_345](#) was added in 8.0.11.

-
- Error number: [MY-012171](#); Symbol: [ER_IB_MSG_346](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_346](#) was added in 8.0.11.

- Error number: [MY-012172](#); Symbol: [ER_IB_MSG_347](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_347](#) was added in 8.0.11.

- Error number: [MY-012173](#); Symbol: [ER_IB_MSG_348](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_348](#) was added in 8.0.11.

- Error number: [MY-012174](#); Symbol: [ER_IB_MSG_349](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_349](#) was added in 8.0.11.

- Error number: [MY-012175](#); Symbol: [ER_IB_MSG_350](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_350](#) was added in 8.0.11.

- Error number: [MY-012176](#); Symbol: [ER_IB_MSG_351](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_351](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012177](#); Symbol: [ER_IB_MSG_352](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_352](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012177](#); Symbol: [ER_IB_MSG_UNPROTECTED_LOCATION_ALLOWED](#); SQLSTATE: [HY000](#)

Message: The datafile '%s' for tablespace %s is in an unprotected location. This file cannot be recovered after a crash until this location is added to innodb_directories.

[ER_IB_MSG_UNPROTECTED_LOCATION_ALLOWED](#) was added in 8.0.21.

- Error number: [MY-012178](#); Symbol: [ER_IB_MSG_353](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_353](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012179](#); Symbol: [ER_IB_MSG_354](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_354](#) was added in 8.0.11.

-
- Error number: [MY-012180](#); Symbol: [ER_IB_MSG_355](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_355](#) was added in 8.0.11.
 - Error number: [MY-012181](#); Symbol: [ER_IB_MSG_356](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_356](#) was added in 8.0.11.
 - Error number: [MY-012182](#); Symbol: [ER_IB_MSG_357](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_357](#) was added in 8.0.11.
 - Error number: [MY-012183](#); Symbol: [ER_IB_MSG_358](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_358](#) was added in 8.0.11.
 - Error number: [MY-012184](#); Symbol: [ER_IB_MSG_359](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_359](#) was added in 8.0.11.
 - Error number: [MY-012185](#); Symbol: [ER_IB_MSG_360](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_360](#) was added in 8.0.11.
 - Error number: [MY-012186](#); Symbol: [ER_IB_MSG_361](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_361](#) was added in 8.0.11.
 - Error number: [MY-012187](#); Symbol: [ER_IB_MSG_362](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_362](#) was added in 8.0.11.
 - Error number: [MY-012188](#); Symbol: [ER_IB_MSG_363](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_363](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012189](#); Symbol: [ER_IB_MSG_364](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_364](#) was added in 8.0.11.
 - Error number: [MY-012190](#); Symbol: [ER_IB_MSG_365](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_365](#) was added in 8.0.11.

- Error number: [MY-012191](#); Symbol: [ER_IB_MSG_366](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_366](#) was added in 8.0.11, removed after 8.0.18.
- Error number: [MY-012191](#); Symbol: [ER_IB_MSG_IGNORE_SCAN_PATH](#); SQLSTATE: [HY000](#)

Message: Scan path '%s' is ignored because %s
[ER_IB_MSG_IGNORE_SCAN_PATH](#) was added in 8.0.19.
- Error number: [MY-012192](#); Symbol: [ER_IB_MSG_367](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_367](#) was added in 8.0.11.
- Error number: [MY-012193](#); Symbol: [ER_IB_MSG_368](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_368](#) was added in 8.0.11.
- Error number: [MY-012194](#); Symbol: [ER_IB_MSG_369](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_369](#) was added in 8.0.11.
- Error number: [MY-012195](#); Symbol: [ER_IB_MSG_370](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_370](#) was added in 8.0.11.
- Error number: [MY-012196](#); Symbol: [ER_IB_MSG_371](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_371](#) was added in 8.0.11.
- Error number: [MY-012197](#); Symbol: [ER_IB_MSG_372](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_372](#) was added in 8.0.11.
- Error number: [MY-012198](#); Symbol: [ER_IB_MSG_373](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_373](#) was added in 8.0.11.
- Error number: [MY-012199](#); Symbol: [ER_IB_MSG_374](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_374](#) was added in 8.0.11.
- Error number: [MY-012200](#); Symbol: [ER_IB_MSG_375](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_375](#) was added in 8.0.11.

-
- Error number: [MY-012201](#); Symbol: [ER_IB_MSG_376](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_376](#) was added in 8.0.11.
 - Error number: [MY-012202](#); Symbol: [ER_IB_MSG_377](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_377](#) was added in 8.0.11.
 - Error number: [MY-012203](#); Symbol: [ER_IB_MSG_378](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_378](#) was added in 8.0.11.
 - Error number: [MY-012204](#); Symbol: [ER_IB_MSG_379](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_379](#) was added in 8.0.11.
 - Error number: [MY-012205](#); Symbol: [ER_IB_MSG_380](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_380](#) was added in 8.0.11.
 - Error number: [MY-012206](#); Symbol: [ER_IB_MSG_381](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_381](#) was added in 8.0.11.
 - Error number: [MY-012207](#); Symbol: [ER_IB_MSG_382](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_382](#) was added in 8.0.11.
 - Error number: [MY-012208](#); Symbol: [ER_IB_MSG_383](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_383](#) was added in 8.0.11.
 - Error number: [MY-012209](#); Symbol: [ER_IB_MSG_384](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_384](#) was added in 8.0.11.
 - Error number: [MY-012210](#); Symbol: [ER_IB_MSG_385](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_385](#) was added in 8.0.11.
 - Error number: [MY-012211](#); Symbol: [ER_IB_MSG_386](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_386](#) was added in 8.0.11.

-
- Error number: [MY-012212](#); Symbol: [ER_IB_MSG_387](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_387](#) was added in 8.0.11.

- Error number: [MY-012213](#); Symbol: [ER_IB_MSG_388](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_388](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012213](#); Symbol: [ER_IB_MSG_GENERAL_TABLESPACE_UNDER_DATADIR](#); SQLSTATE: [HY000](#)

Message: A general tablespace cannot be located under the datadir. Cannot open file '%s'.

[ER_IB_MSG_GENERAL_TABLESPACE_UNDER_DATADIR](#) was added in 8.0.21.

- Error number: [MY-012214](#); Symbol: [ER_IB_MSG_389](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_389](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012214](#); Symbol: [ER_IB_MSG_IMPLPLICIT_TABLESPACE_IN_DATADIR](#); SQLSTATE: [HY000](#)

Message: A file-per-table tablespace cannot be located in the datadir. Cannot open file '%s'.

[ER_IB_MSG_IMPLPLICIT_TABLESPACE_IN_DATADIR](#) was added in 8.0.21.

- Error number: [MY-012215](#); Symbol: [ER_IB_MSG_390](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_390](#) was added in 8.0.11.

- Error number: [MY-012216](#); Symbol: [ER_IB_MSG_391](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_391](#) was added in 8.0.11.

- Error number: [MY-012217](#); Symbol: [ER_IB_MSG_392](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_392](#) was added in 8.0.11.

- Error number: [MY-012218](#); Symbol: [ER_IB_MSG_393](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_393](#) was added in 8.0.11.

- Error number: [MY-012219](#); Symbol: [ER_IB_MSG_394](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_394](#) was added in 8.0.11.

-
- Error number: [MY-012220](#); Symbol: [ER_IB_MSG_395](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_395](#) was added in 8.0.11.
 - Error number: [MY-012221](#); Symbol: [ER_IB_MSG_396](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_396](#) was added in 8.0.11.
 - Error number: [MY-012222](#); Symbol: [ER_IB_MSG_397](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_397](#) was added in 8.0.11.
 - Error number: [MY-012223](#); Symbol: [ER_IB_MSG_398](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_398](#) was added in 8.0.11.
 - Error number: [MY-012224](#); Symbol: [ER_IB_MSG_399](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_399](#) was added in 8.0.11.
 - Error number: [MY-012225](#); Symbol: [ER_IB_MSG_400](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_400](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012226](#); Symbol: [ER_IB_MSG_401](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_401](#) was added in 8.0.11.
 - Error number: [MY-012227](#); Symbol: [ER_IB_MSG_402](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_402](#) was added in 8.0.11.
 - Error number: [MY-012228](#); Symbol: [ER_IB_MSG_403](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_403](#) was added in 8.0.11.
 - Error number: [MY-012229](#); Symbol: [ER_IB_MSG_404](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_404](#) was added in 8.0.11.
 - Error number: [MY-012230](#); Symbol: [ER_IB_MSG_405](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_405](#) was added in 8.0.11.

-
- Error number: [MY-012231](#); Symbol: [ER_IB_MSG_406](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_406](#) was added in 8.0.11.
 - Error number: [MY-012232](#); Symbol: [ER_IB_MSG_407](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_407](#) was added in 8.0.11.
 - Error number: [MY-012233](#); Symbol: [ER_IB_MSG_408](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_408](#) was added in 8.0.11.
 - Error number: [MY-012234](#); Symbol: [ER_IB_MSG_409](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_409](#) was added in 8.0.11.
 - Error number: [MY-012235](#); Symbol: [ER_IB_MSG_410](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_410](#) was added in 8.0.11.
 - Error number: [MY-012236](#); Symbol: [ER_IB_MSG_411](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_411](#) was added in 8.0.11.
 - Error number: [MY-012237](#); Symbol: [ER_IB_MSG_412](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_412](#) was added in 8.0.11.
 - Error number: [MY-012238](#); Symbol: [ER_IB_MSG_413](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_413](#) was added in 8.0.11.
 - Error number: [MY-012239](#); Symbol: [ER_IB_MSG_414](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_414](#) was added in 8.0.11.
 - Error number: [MY-012240](#); Symbol: [ER_IB_MSG_415](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_415](#) was added in 8.0.11.
 - Error number: [MY-012241](#); Symbol: [ER_IB_MSG_416](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_416](#) was added in 8.0.11.

-
- Error number: [MY-012242](#); Symbol: [ER_IB_MSG_417](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_417](#) was added in 8.0.11.
 - Error number: [MY-012243](#); Symbol: [ER_IB_MSG_418](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_418](#) was added in 8.0.11.
 - Error number: [MY-012244](#); Symbol: [ER_IB_MSG_419](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_419](#) was added in 8.0.11.
 - Error number: [MY-012245](#); Symbol: [ER_IB_MSG_420](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_420](#) was added in 8.0.11.
 - Error number: [MY-012246](#); Symbol: [ER_IB_MSG_421](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_421](#) was added in 8.0.11.
 - Error number: [MY-012247](#); Symbol: [ER_IB_MSG_422](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_422](#) was added in 8.0.11.
 - Error number: [MY-012248](#); Symbol: [ER_IB_MSG_423](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_423](#) was added in 8.0.11.
 - Error number: [MY-012249](#); Symbol: [ER_IB_MSG_424](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_424](#) was added in 8.0.11.
 - Error number: [MY-012250](#); Symbol: [ER_IB_MSG_425](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_425](#) was added in 8.0.11.
 - Error number: [MY-012251](#); Symbol: [ER_IB_MSG_426](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_426](#) was added in 8.0.11.
 - Error number: [MY-012252](#); Symbol: [ER_IB_MSG_427](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_427](#) was added in 8.0.11.

- Error number: MY-012253; Symbol: ER_IB_MSG_428; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_428](#) was added in 8.0.11.
- Error number: MY-012254; Symbol: ER_IB_MSG_429; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_429](#) was added in 8.0.11.
- Error number: MY-012255; Symbol: ER_IB_MSG_430; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_430](#) was added in 8.0.11.
- Error number: MY-012256; Symbol: ER_IB_MSG_431; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_431](#) was added in 8.0.11.
- Error number: MY-012257; Symbol: ER_IB_MSG_432; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_432](#) was added in 8.0.11.
- Error number: MY-012258; Symbol: ER_IB_MSG_433; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_433](#) was added in 8.0.11.
- Error number: MY-012259; Symbol: ER_IB_MSG_434; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_434](#) was added in 8.0.11.
- Error number: MY-012260; Symbol: ER_IB_MSG_435; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_435](#) was added in 8.0.11.
- Error number: MY-012261; Symbol: ER_IB_MSG_436; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_436](#) was added in 8.0.11.
- Error number: MY-012262; Symbol: ER_IB_MSG_437; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_437](#) was added in 8.0.11.
- Error number: MY-012263; Symbol: ER_IB_MSG_438; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_438](#) was added in 8.0.11.

-
- Error number: [MY-012264](#); Symbol: [ER_IB_MSG_439](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_439](#) was added in 8.0.11.
 - Error number: [MY-012265](#); Symbol: [ER_IB_MSG_440](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_440](#) was added in 8.0.11.
 - Error number: [MY-012266](#); Symbol: [ER_IB_MSG_441](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_441](#) was added in 8.0.11.
 - Error number: [MY-012267](#); Symbol: [ER_IB_MSG_442](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_442](#) was added in 8.0.11.
 - Error number: [MY-012268](#); Symbol: [ER_IB_MSG_443](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_443](#) was added in 8.0.11.
 - Error number: [MY-012269](#); Symbol: [ER_IB_MSG_444](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_444](#) was added in 8.0.11.
 - Error number: [MY-012270](#); Symbol: [ER_IB_MSG_445](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_445](#) was added in 8.0.11.
 - Error number: [MY-012271](#); Symbol: [ER_IB_MSG_446](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_446](#) was added in 8.0.11.
 - Error number: [MY-012272](#); Symbol: [ER_IB_MSG_447](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_447](#) was added in 8.0.11.
 - Error number: [MY-012273](#); Symbol: [ER_IB_MSG_448](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_448](#) was added in 8.0.11.
 - Error number: [MY-012274](#); Symbol: [ER_IB_MSG_449](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_449](#) was added in 8.0.11.

- Error number: MY-012275; Symbol: ER_IB_MSG_450; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_450` was added in 8.0.11.
- Error number: MY-012276; Symbol: ER_IB_MSG_451; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_451` was added in 8.0.11.
- Error number: MY-012277; Symbol: ER_IB_MSG_452; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_452` was added in 8.0.11.
- Error number: MY-012278; Symbol: ER_IB_MSG_453; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_453` was added in 8.0.11.
- Error number: MY-012279; Symbol: ER_IB_MSG_454; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_454` was added in 8.0.11.
- Error number: MY-012280; Symbol: ER_IB_MSG_455; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_455` was added in 8.0.11.
- Error number: MY-012281; Symbol: ER_IB_MSG_456; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_456` was added in 8.0.11.
- Error number: MY-012282; Symbol: ER_IB_MSG_457; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_457` was added in 8.0.11.
- Error number: MY-012283; Symbol: ER_IB_MSG_458; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_458` was added in 8.0.11.
- Error number: MY-012284; Symbol: ER_IB_MSG_459; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_459` was added in 8.0.11.
- Error number: MY-012285; Symbol: ER_IB_MSG_460; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_460` was added in 8.0.11.

-
- Error number: [MY-012286](#); Symbol: [ER_IB_MSG_461](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_461](#) was added in 8.0.11.
 - Error number: [MY-012287](#); Symbol: [ER_IB_MSG_462](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_462](#) was added in 8.0.11.
 - Error number: [MY-012288](#); Symbol: [ER_IB_MSG_463](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_463](#) was added in 8.0.11.
 - Error number: [MY-012289](#); Symbol: [ER_IB_MSG_464](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_464](#) was added in 8.0.11.
 - Error number: [MY-012290](#); Symbol: [ER_IB_MSG_465](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_465](#) was added in 8.0.11.
 - Error number: [MY-012291](#); Symbol: [ER_IB_MSG_466](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_466](#) was added in 8.0.11.
 - Error number: [MY-012292](#); Symbol: [ER_IB_MSG_467](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_467](#) was added in 8.0.11.
 - Error number: [MY-012293](#); Symbol: [ER_IB_MSG_468](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_468](#) was added in 8.0.11.
 - Error number: [MY-012294](#); Symbol: [ER_IB_MSG_469](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_469](#) was added in 8.0.11.
 - Error number: [MY-012295](#); Symbol: [ER_IB_MSG_470](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_470](#) was added in 8.0.11.
 - Error number: [MY-012296](#); Symbol: [ER_IB_MSG_471](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_471](#) was added in 8.0.11.

- Error number: [MY-012297](#); Symbol: [ER_IB_MSG_472](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_472](#) was added in 8.0.11.
- Error number: [MY-012298](#); Symbol: [ER_IB_MSG_473](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_473](#) was added in 8.0.11.
- Error number: [MY-012299](#); Symbol: [ER_IB_MSG_474](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_474](#) was added in 8.0.11.
- Error number: [MY-012300](#); Symbol: [ER_IB_MSG_475](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_475](#) was added in 8.0.11.
- Error number: [MY-012301](#); Symbol: [ER_IB_MSG_476](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_476](#) was added in 8.0.11.
- Error number: [MY-012302](#); Symbol: [ER_IB_MSG_477](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_477](#) was added in 8.0.11.
- Error number: [MY-012303](#); Symbol: [ER_IB_MSG_478](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_478](#) was added in 8.0.11.
- Error number: [MY-012304](#); Symbol: [ER_IB_MSG_479](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_479](#) was added in 8.0.11.
- Error number: [MY-012305](#); Symbol: [ER_IB_MSG_480](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_480](#) was added in 8.0.11.
- Error number: [MY-012306](#); Symbol: [ER_IB_MSG_481](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_481](#) was added in 8.0.11.
- Error number: [MY-012307](#); Symbol: [ER_IB_MSG_482](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_482](#) was added in 8.0.11.

-
- Error number: [MY-012308](#); Symbol: [ER_IB_MSG_483](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_483](#) was added in 8.0.11.
 - Error number: [MY-012309](#); Symbol: [ER_IB_MSG_484](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_484](#) was added in 8.0.11.
 - Error number: [MY-012310](#); Symbol: [ER_IB_MSG_485](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_485](#) was added in 8.0.11.
 - Error number: [MY-012311](#); Symbol: [ER_IB_MSG_486](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_486](#) was added in 8.0.11.
 - Error number: [MY-012312](#); Symbol: [ER_IB_MSG_487](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_487](#) was added in 8.0.11.
 - Error number: [MY-012313](#); Symbol: [ER_IB_MSG_488](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_488](#) was added in 8.0.11.
 - Error number: [MY-012314](#); Symbol: [ER_IB_MSG_489](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_489](#) was added in 8.0.11.
 - Error number: [MY-012315](#); Symbol: [ER_IB_MSG_490](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_490](#) was added in 8.0.11.
 - Error number: [MY-012316](#); Symbol: [ER_IB_MSG_491](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_491](#) was added in 8.0.11.
 - Error number: [MY-012317](#); Symbol: [ER_IB_MSG_492](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_492](#) was added in 8.0.11.
 - Error number: [MY-012318](#); Symbol: [ER_IB_MSG_493](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_493](#) was added in 8.0.11.

- Error number: MY-012319; Symbol: ER_IB_MSG_494; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_494` was added in 8.0.11.
- Error number: MY-012320; Symbol: ER_IB_MSG_495; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_495` was added in 8.0.11.
- Error number: MY-012321; Symbol: ER_IB_MSG_496; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_496` was added in 8.0.11.
- Error number: MY-012322; Symbol: ER_IB_MSG_497; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_497` was added in 8.0.11.
- Error number: MY-012323; Symbol: ER_IB_MSG_498; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_498` was added in 8.0.11.
- Error number: MY-012324; Symbol: ER_IB_MSG_499; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_499` was added in 8.0.11.
- Error number: MY-012325; Symbol: ER_IB_MSG_500; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_500` was added in 8.0.11.
- Error number: MY-012326; Symbol: ER_IB_MSG_501; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_501` was added in 8.0.11.
- Error number: MY-012327; Symbol: ER_IB_MSG_502; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_502` was added in 8.0.11.
- Error number: MY-012328; Symbol: ER_IB_MSG_503; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_503` was added in 8.0.11.
- Error number: MY-012329; Symbol: ER_IB_MSG_504; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_504` was added in 8.0.11.

-
- Error number: [MY-012330](#); Symbol: [ER_IB_MSG_505](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_505](#) was added in 8.0.11.
 - Error number: [MY-012331](#); Symbol: [ER_IB_MSG_506](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_506](#) was added in 8.0.11.
 - Error number: [MY-012332](#); Symbol: [ER_IB_MSG_507](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_507](#) was added in 8.0.11.
 - Error number: [MY-012333](#); Symbol: [ER_IB_MSG_508](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_508](#) was added in 8.0.11.
 - Error number: [MY-012334](#); Symbol: [ER_IB_MSG_509](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_509](#) was added in 8.0.11.
 - Error number: [MY-012335](#); Symbol: [ER_IB_MSG_510](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_510](#) was added in 8.0.11.
 - Error number: [MY-012336](#); Symbol: [ER_IB_MSG_511](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_511](#) was added in 8.0.11.
 - Error number: [MY-012337](#); Symbol: [ER_IB_MSG_512](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_512](#) was added in 8.0.11.
 - Error number: [MY-012338](#); Symbol: [ER_IB_MSG_513](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_513](#) was added in 8.0.11.
 - Error number: [MY-012339](#); Symbol: [ER_IB_MSG_514](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_514](#) was added in 8.0.11.
 - Error number: [MY-012340](#); Symbol: [ER_IB_MSG_515](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_515](#) was added in 8.0.11.

-
- Error number: [MY-012341](#); Symbol: [ER_IB_MSG_516](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_516](#) was added in 8.0.11.
 - Error number: [MY-012342](#); Symbol: [ER_IB_MSG_517](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_517](#) was added in 8.0.11.
 - Error number: [MY-012343](#); Symbol: [ER_IB_MSG_518](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_518](#) was added in 8.0.11.
 - Error number: [MY-012344](#); Symbol: [ER_IB_MSG_519](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_519](#) was added in 8.0.11.
 - Error number: [MY-012345](#); Symbol: [ER_IB_MSG_520](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_520](#) was added in 8.0.11.
 - Error number: [MY-012346](#); Symbol: [ER_IB_MSG_521](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_521](#) was added in 8.0.11.
 - Error number: [MY-012347](#); Symbol: [ER_IB_MSG_522](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_522](#) was added in 8.0.11.
 - Error number: [MY-012348](#); Symbol: [ER_IB_MSG_523](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_523](#) was added in 8.0.11.
 - Error number: [MY-012349](#); Symbol: [ER_IB_MSG_524](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_524](#) was added in 8.0.11.
 - Error number: [MY-012350](#); Symbol: [ER_IB_MSG_525](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_525](#) was added in 8.0.11.
 - Error number: [MY-012351](#); Symbol: [ER_IB_MSG_526](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_526](#) was added in 8.0.11.

-
- Error number: [MY-012352](#); Symbol: [ER_IB_MSG_527](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_527](#) was added in 8.0.11.
 - Error number: [MY-012353](#); Symbol: [ER_IB_MSG_528](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_528](#) was added in 8.0.11, removed after 8.0.18.
 - Error number: [MY-012354](#); Symbol: [ER_IB_MSG_529](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_529](#) was added in 8.0.11, removed after 8.0.18.
 - Error number: [MY-012355](#); Symbol: [ER_IB_MSG_530](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_530](#) was added in 8.0.11.
 - Error number: [MY-012356](#); Symbol: [ER_IB_MSG_531](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_531](#) was added in 8.0.11.
 - Error number: [MY-012357](#); Symbol: [ER_IB_MSG_532](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_532](#) was added in 8.0.11.
 - Error number: [MY-012358](#); Symbol: [ER_IB_MSG_533](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_533](#) was added in 8.0.11.
 - Error number: [MY-012359](#); Symbol: [ER_IB_MSG_534](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_534](#) was added in 8.0.11.
 - Error number: [MY-012360](#); Symbol: [ER_IB_MSG_535](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_535](#) was added in 8.0.11.
 - Error number: [MY-012361](#); Symbol: [ER_IB_MSG_536](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_536](#) was added in 8.0.11.
 - Error number: [MY-012362](#); Symbol: [ER_IB_MSG_537](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_537](#) was added in 8.0.11.

-
- Error number: MY-012363; Symbol: ER_IB_MSG_538; SQLSTATE: HY000
Message: %s
ER_IB_MSG_538 was added in 8.0.11.
 - Error number: MY-012364; Symbol: ER_IB_MSG_539; SQLSTATE: HY000
Message: %s
ER_IB_MSG_539 was added in 8.0.11.
 - Error number: MY-012365; Symbol: ER_IB_MSG_540; SQLSTATE: HY000
Message: %s
ER_IB_MSG_540 was added in 8.0.11.
 - Error number: MY-012366; Symbol: ER_IB_MSG_541; SQLSTATE: HY000
Message: %s
ER_IB_MSG_541 was added in 8.0.11.
 - Error number: MY-012367; Symbol: ER_IB_MSG_542; SQLSTATE: HY000
Message: %s
ER_IB_MSG_542 was added in 8.0.11.
 - Error number: MY-012368; Symbol: ER_IB_MSG_543; SQLSTATE: HY000
Message: %s
ER_IB_MSG_543 was added in 8.0.11.
 - Error number: MY-012369; Symbol: ER_IB_MSG_544; SQLSTATE: HY000
Message: %s
ER_IB_MSG_544 was added in 8.0.11.
 - Error number: MY-012370; Symbol: ER_IB_MSG_545; SQLSTATE: HY000
Message: %s
ER_IB_MSG_545 was added in 8.0.11.
 - Error number: MY-012371; Symbol: ER_IB_MSG_546; SQLSTATE: HY000
Message: %s
ER_IB_MSG_546 was added in 8.0.11.
 - Error number: MY-012372; Symbol: ER_IB_MSG_547; SQLSTATE: HY000
Message: %s
ER_IB_MSG_547 was added in 8.0.11.
 - Error number: MY-012373; Symbol: ER_IB_MSG_548; SQLSTATE: HY000
Message: %s
ER_IB_MSG_548 was added in 8.0.11.

-
- Error number: [MY-012374](#); Symbol: [ER_IB_MSG_549](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_549](#) was added in 8.0.11.
 - Error number: [MY-012375](#); Symbol: [ER_IB_MSG_550](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_550](#) was added in 8.0.11.
 - Error number: [MY-012376](#); Symbol: [ER_IB_MSG_551](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_551](#) was added in 8.0.11.
 - Error number: [MY-012377](#); Symbol: [ER_IB_MSG_552](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_552](#) was added in 8.0.11.
 - Error number: [MY-012378](#); Symbol: [ER_IB_MSG_553](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_553](#) was added in 8.0.11.
 - Error number: [MY-012379](#); Symbol: [ER_IB_MSG_554](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_554](#) was added in 8.0.11.
 - Error number: [MY-012380](#); Symbol: [ER_IB_MSG_555](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_555](#) was added in 8.0.11.
 - Error number: [MY-012381](#); Symbol: [ER_IB_MSG_556](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_556](#) was added in 8.0.11.
 - Error number: [MY-012382](#); Symbol: [ER_IB_MSG_557](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_557](#) was added in 8.0.11.
 - Error number: [MY-012383](#); Symbol: [ER_IB_MSG_558](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_558](#) was added in 8.0.11.
 - Error number: [MY-012384](#); Symbol: [ER_IB_MSG_559](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_559](#) was added in 8.0.11.

-
- Error number: MY-012385; Symbol: `ER_IB_MSG_560`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_560` was added in 8.0.11.

- Error number: MY-012386; Symbol: `ER_IB_MSG_561`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_561` was added in 8.0.11.

- Error number: MY-012387; Symbol: `ER_IB_MSG_562`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_562` was added in 8.0.11.

- Error number: MY-012388; Symbol: `ER_IB_MSG_563`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_563` was added in 8.0.11.

- Error number: MY-012389; Symbol: `ER_IB_MSG_564`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_564` was added in 8.0.11.

- Error number: MY-012390; Symbol: `ER_IB_MSG_565`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_565` was added in 8.0.11, removed after 8.0.20.

- Error number: MY-012390; Symbol: `ER_IB_MSG_INVALID_LOCATION_FOR_TABLE`; SQLSTATE: `HY000`

Message: Cannot create a tablespace for table %s because the directory is not a valid location. %s

`ER_IB_MSG_INVALID_LOCATION_FOR_TABLE` was added in 8.0.21.

- Error number: MY-012391; Symbol: `ER_IB_MSG_566`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_566` was added in 8.0.11.

- Error number: MY-012392; Symbol: `ER_IB_MSG_567`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_567` was added in 8.0.11.

- Error number: MY-012393; Symbol: `ER_IB_MSG_568`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_568` was added in 8.0.11.

- Error number: MY-012394; Symbol: `ER_IB_MSG_569`; SQLSTATE: `HY000`

Message: %s

[ER_IB_MSG_569](#) was added in 8.0.11.

- Error number: [MY-012395](#); Symbol: [ER_IB_MSG_570](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_570](#) was added in 8.0.11.

- Error number: [MY-012396](#); Symbol: [ER_IB_MSG_571](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_571](#) was added in 8.0.11.

- Error number: [MY-012397](#); Symbol: [ER_IB_MSG_572](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_572](#) was added in 8.0.11, removed after 8.0.18.

- Error number: [MY-012398](#); Symbol: [ER_IB_MSG_573](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_573](#) was added in 8.0.11.

- Error number: [MY-012399](#); Symbol: [ER_IB_MSG_574](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_574](#) was added in 8.0.11.

- Error number: [MY-012400](#); Symbol: [ER_IB_MSG_575](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_575](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012401](#); Symbol: [ER_IB_MSG_576](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_576](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012402](#); Symbol: [ER_IB_MSG_577](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_577](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012403](#); Symbol: [ER_IB_MSG_578](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_578](#) was added in 8.0.11.

- Error number: [MY-012404](#); Symbol: [ER_IB_MSG_579](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_579](#) was added in 8.0.11.

- Error number: [MY-012405](#); Symbol: [ER_IB_MSG_580](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_580](#) was added in 8.0.11.

- Error number: [MY-012406](#); Symbol: [ER_IB_MSG_581](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_581](#) was added in 8.0.11.

- Error number: [MY-012407](#); Symbol: [ER_IB_MSG_582](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_582](#) was added in 8.0.11.

- Error number: [MY-012408](#); Symbol: [ER_IB_MSG_583](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_583](#) was added in 8.0.11.

- Error number: [MY-012409](#); Symbol: [ER_IB_MSG_584](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_584](#) was added in 8.0.11.

- Error number: [MY-012410](#); Symbol: [ER_IB_MSG_585](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_585](#) was added in 8.0.11.

- Error number: [MY-012411](#); Symbol: [ER_IB_MSG_586](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_586](#) was added in 8.0.11.

- Error number: [MY-012412](#); Symbol: [ER_IB_MSG_587](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_587](#) was added in 8.0.11.

- Error number: [MY-012413](#); Symbol: [ER_IB_MSG_588](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_588](#) was added in 8.0.11.

- Error number: [MY-012414](#); Symbol: [ER_IB_MSG_589](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_589](#) was added in 8.0.11.

- Error number: [MY-012415](#); Symbol: [ER_IB_MSG_590](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_590](#) was added in 8.0.11.

-
- Error number: [MY-012416](#); Symbol: [ER_IB_MSG_591](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_591](#) was added in 8.0.11.
 - Error number: [MY-012417](#); Symbol: [ER_IB_MSG_592](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_592](#) was added in 8.0.11.
 - Error number: [MY-012418](#); Symbol: [ER_IB_MSG_593](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_593](#) was added in 8.0.11.
 - Error number: [MY-012419](#); Symbol: [ER_IB_MSG_594](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_594](#) was added in 8.0.11.
 - Error number: [MY-012420](#); Symbol: [ER_IB_MSG_595](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_595](#) was added in 8.0.11.
 - Error number: [MY-012421](#); Symbol: [ER_IB_MSG_596](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_596](#) was added in 8.0.11.
 - Error number: [MY-012422](#); Symbol: [ER_IB_MSG_597](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_597](#) was added in 8.0.11.
 - Error number: [MY-012423](#); Symbol: [ER_IB_MSG_598](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_598](#) was added in 8.0.11.
 - Error number: [MY-012424](#); Symbol: [ER_IB_MSG_599](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_599](#) was added in 8.0.11.
 - Error number: [MY-012425](#); Symbol: [ER_IB_MSG_600](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_600](#) was added in 8.0.11.
 - Error number: [MY-012426](#); Symbol: [ER_IB_MSG_601](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_601](#) was added in 8.0.11.

- Error number: MY-012427; Symbol: ER_IB_MSG_602; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_602` was added in 8.0.11.
- Error number: MY-012428; Symbol: ER_IB_MSG_603; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_603` was added in 8.0.11.
- Error number: MY-012429; Symbol: ER_IB_MSG_604; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_604` was added in 8.0.11.
- Error number: MY-012430; Symbol: ER_IB_MSG_605; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_605` was added in 8.0.11.
- Error number: MY-012431; Symbol: ER_IB_MSG_606; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_606` was added in 8.0.11.
- Error number: MY-012432; Symbol: ER_IB_MSG_607; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_607` was added in 8.0.11.
- Error number: MY-012433; Symbol: ER_IB_MSG_608; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_608` was added in 8.0.11.
- Error number: MY-012434; Symbol: ER_IB_MSG_609; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_609` was added in 8.0.11.
- Error number: MY-012435; Symbol: ER_IB_MSG_610; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_610` was added in 8.0.11.
- Error number: MY-012436; Symbol: ER_IB_MSG_611; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_611` was added in 8.0.11.
- Error number: MY-012437; Symbol: ER_IB_MSG_612; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_612` was added in 8.0.11.

-
- Error number: [MY-012438](#); Symbol: [ER_IB_MSG_613](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_613](#) was added in 8.0.11.
 - Error number: [MY-012439](#); Symbol: [ER_IB_MSG_614](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_614](#) was added in 8.0.11.
 - Error number: [MY-012440](#); Symbol: [ER_IB_MSG_615](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_615](#) was added in 8.0.11.
 - Error number: [MY-012441](#); Symbol: [ER_IB_MSG_616](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_616](#) was added in 8.0.11.
 - Error number: [MY-012442](#); Symbol: [ER_IB_MSG_617](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_617](#) was added in 8.0.11.
 - Error number: [MY-012443](#); Symbol: [ER_IB_MSG_618](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_618](#) was added in 8.0.11.
 - Error number: [MY-012444](#); Symbol: [ER_IB_MSG_619](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_619](#) was added in 8.0.11.
 - Error number: [MY-012445](#); Symbol: [ER_IB_MSG_620](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_620](#) was added in 8.0.11.
 - Error number: [MY-012446](#); Symbol: [ER_IB_MSG_621](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_621](#) was added in 8.0.11.
 - Error number: [MY-012447](#); Symbol: [ER_IB_MSG_622](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_622](#) was added in 8.0.11.
 - Error number: [MY-012448](#); Symbol: [ER_IB_MSG_623](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_623](#) was added in 8.0.11.

- Error number: MY-012449; Symbol: ER_IB_MSG_624; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_624` was added in 8.0.11.
- Error number: MY-012450; Symbol: ER_IB_MSG_625; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_625` was added in 8.0.11.
- Error number: MY-012451; Symbol: ER_IB_MSG_626; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_626` was added in 8.0.11.
- Error number: MY-012452; Symbol: ER_IB_MSG_627; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_627` was added in 8.0.11.
- Error number: MY-012453; Symbol: ER_IB_MSG_628; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_628` was added in 8.0.11.
- Error number: MY-012454; Symbol: ER_IB_MSG_629; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_629` was added in 8.0.11.
- Error number: MY-012455; Symbol: ER_IB_MSG_630; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_630` was added in 8.0.11.
- Error number: MY-012456; Symbol: ER_IB_MSG_631; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_631` was added in 8.0.11.
- Error number: MY-012457; Symbol: ER_IB_MSG_632; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_632` was added in 8.0.11.
- Error number: MY-012458; Symbol: ER_IB_MSG_633; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_633` was added in 8.0.11.
- Error number: MY-012459; Symbol: ER_IB_MSG_634; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_634` was added in 8.0.11.

-
- Error number: [MY-012460](#); Symbol: [ER_IB_MSG_635](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_635](#) was added in 8.0.11.
 - Error number: [MY-012461](#); Symbol: [ER_IB_MSG_636](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_636](#) was added in 8.0.11.
 - Error number: [MY-012462](#); Symbol: [ER_IB_MSG_637](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_637](#) was added in 8.0.11.
 - Error number: [MY-012463](#); Symbol: [ER_IB_MSG_638](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_638](#) was added in 8.0.11.
 - Error number: [MY-012464](#); Symbol: [ER_IB_MSG_639](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_639](#) was added in 8.0.11.
 - Error number: [MY-012465](#); Symbol: [ER_IB_MSG_640](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_640](#) was added in 8.0.11, removed after 8.0.20.
 - Error number: [MY-012466](#); Symbol: [ER_IB_MSG_641](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_641](#) was added in 8.0.11, removed after 8.0.20.
 - Error number: [MY-012467](#); Symbol: [ER_IB_MSG_642](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_642](#) was added in 8.0.11.
 - Error number: [MY-012468](#); Symbol: [ER_IB_MSG_643](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_643](#) was added in 8.0.11.
 - Error number: [MY-012469](#); Symbol: [ER_IB_MSG_644](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_644](#) was added in 8.0.11.
 - Error number: [MY-012470](#); Symbol: [ER_IB_MSG_645](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_645](#) was added in 8.0.11.

- Error number: [MY-012471](#); Symbol: [ER_IB_MSG_646](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_646](#) was added in 8.0.11.
- Error number: [MY-012472](#); Symbol: [ER_IB_MSG_647](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_647](#) was added in 8.0.11.
- Error number: [MY-012473](#); Symbol: [ER_IB_MSG_648](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_648](#) was added in 8.0.11.
- Error number: [MY-012474](#); Symbol: [ER_IB_MSG_649](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_649](#) was added in 8.0.11.
- Error number: [MY-012475](#); Symbol: [ER_IB_MSG_650](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_650](#) was added in 8.0.11.
- Error number: [MY-012476](#); Symbol: [ER_IB_MSG_651](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_651](#) was added in 8.0.11.
- Error number: [MY-012477](#); Symbol: [ER_IB_MSG_652](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_652](#) was added in 8.0.11.
- Error number: [MY-012478](#); Symbol: [ER_IB_MSG_653](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_653](#) was added in 8.0.11, removed after 8.0.15.
- Error number: [MY-012478](#); Symbol: [ER_IB_MSG_DDL_LOG_DELETE_BY_ID_OK](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_DDL_LOG_DELETE_BY_ID_OK](#) was added in 8.0.16.
- Error number: [MY-012479](#); Symbol: [ER_IB_MSG_654](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_654](#) was added in 8.0.11.
- Error number: [MY-012480](#); Symbol: [ER_IB_MSG_655](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_655](#) was added in 8.0.11.

- Error number: [MY-012481](#); Symbol: [ER_IB_MSG_656](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_656](#) was added in 8.0.11.

- Error number: [MY-012482](#); Symbol: [ER_IB_MSG_657](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_657](#) was added in 8.0.11.

- Error number: [MY-012483](#); Symbol: [ER_IB_MSG_658](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_658](#) was added in 8.0.11.

- Error number: [MY-012484](#); Symbol: [ER_IB_MSG_659](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_659](#) was added in 8.0.11.

- Error number: [MY-012485](#); Symbol: [ER_IB_MSG_660](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_660](#) was added in 8.0.11.

- Error number: [MY-012486](#); Symbol: [ER_IB_MSG_661](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_661](#) was added in 8.0.11.

- Error number: [MY-012487](#); Symbol: [ER_IB_MSG_662](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_662](#) was added in 8.0.11.

- Error number: [MY-012488](#); Symbol: [ER_IB_MSG_663](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_663](#) was added in 8.0.11.

- Error number: [MY-012489](#); Symbol: [ER_IB_MSG_664](#); SQLSTATE: [HY000](#)

Message: The transaction log size is too large for innodb_log_buffer_size (%lu >= %lu / 2). Trying to extend it.

[ER_IB_MSG_664](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012490](#); Symbol: [ER_IB_MSG_665](#); SQLSTATE: [HY000](#)

Message: innodb_log_buffer_size was extended to %lu bytes.

[ER_IB_MSG_665](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012491](#); Symbol: [ER_IB_MSG_666](#); SQLSTATE: [HY000](#)

Message: The transaction log files are too small for the single transaction log (size=%lu). So, the last checkpoint age might exceed the log group capacity %llu.

[ER_IB_MSG_666](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012492](#); Symbol: [ER_IB_MSG_667](#); SQLSTATE: [HY000](#)

Message: The age of the last checkpoint is %llu, which exceeds the log group capacity %llu.

[ER_IB_MSG_667](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012493](#); Symbol: [ER_IB_MSG_668](#); SQLSTATE: [HY000](#)

Message: Cannot continue operation. ib_logfiles are too small for innodb_thread_concurrency %lu. The combined size of ib_logfiles should be bigger than 200 kB * innodb_thread_concurrency. To get mysqld to start up, set innodb_thread_concurrency in my.cnf to a lower value, for example, to 8. After an ERROR-FREE shutdown of mysqld you can adjust the size of ib_logfiles. %s

[ER_IB_MSG_668](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012494](#); Symbol: [ER_IB_MSG_669](#); SQLSTATE: [HY000](#)

Message: Redo log was encrypted, but keyring plugin is not loaded.

[ER_IB_MSG_669](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012495](#); Symbol: [ER_IB_MSG_670](#); SQLSTATE: [HY000](#)

Message: Read redo log encryption metadata successful.

[ER_IB_MSG_670](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012496](#); Symbol: [ER_IB_MSG_671](#); SQLSTATE: [HY000](#)

Message: Can't set redo log tablespace encryption metadata.

[ER_IB_MSG_671](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012497](#); Symbol: [ER_IB_MSG_672](#); SQLSTATE: [HY000](#)

Message: Cannot read the encryption information in log file header, please check if keyring plugin loaded and the key file exists.

[ER_IB_MSG_672](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012498](#); Symbol: [ER_IB_MSG_673](#); SQLSTATE: [HY000](#)

Message: Can't set redo log tablespace to be encrypted in read-only mode.

[ER_IB_MSG_673](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012499](#); Symbol: [ER_IB_MSG_674](#); SQLSTATE: [HY000](#)

Message: Can't set redo log tablespace to be encrypted.

[ER_IB_MSG_674](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012500](#); Symbol: [ER_IB_MSG_675](#); SQLSTATE: [HY000](#)

Message: Can't set redo log tablespace to be encrypted.

[ER_IB_MSG_675](#) was added in 8.0.11, removed after 8.0.13.

-
- Error number: [MY-012501](#); Symbol: [ER_IB_MSG_676](#); SQLSTATE: [HY000](#)
Message: Redo log encryption is enabled.
[ER_IB_MSG_676](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012502](#); Symbol: [ER_IB_MSG_677](#); SQLSTATE: [HY000](#)
Message: Flush Waiting for archiver to catch up lag LSN: %lu
[ER_IB_MSG_677](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012503](#); Symbol: [ER_IB_MSG_678](#); SQLSTATE: [HY000](#)
Message: Flush overwriting data to archive - wait too long (1 minute) lag LSN: %lu
[ER_IB_MSG_678](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012504](#); Symbol: [ER_IB_MSG_679](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_679](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012505](#); Symbol: [ER_IB_MSG_680](#); SQLSTATE: [HY000](#)
Message: Starting shutdown...
[ER_IB_MSG_680](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012506](#); Symbol: [ER_IB_MSG_681](#); SQLSTATE: [HY000](#)
Message: Waiting for %s to exit
[ER_IB_MSG_681](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012507](#); Symbol: [ER_IB_MSG_682](#); SQLSTATE: [HY000](#)
Message: Waiting for %lu active transactions to finish
[ER_IB_MSG_682](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012508](#); Symbol: [ER_IB_MSG_683](#); SQLSTATE: [HY000](#)
Message: Waiting for master thread to be suspended
[ER_IB_MSG_683](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012509](#); Symbol: [ER_IB_MSG_684](#); SQLSTATE: [HY000](#)
Message: Waiting for page_cleaner to finish flushing of buffer pool
[ER_IB_MSG_684](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012510](#); Symbol: [ER_IB_MSG_685](#); SQLSTATE: [HY000](#)
Message: Pending checkpoint_writes: %lu. Pending log flush writes: %lu.
[ER_IB_MSG_685](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012511](#); Symbol: [ER_IB_MSG_686](#); SQLSTATE: [HY000](#)
Message: Waiting for %lu buffer page I/Os to complete
[ER_IB_MSG_686](#) was added in 8.0.11, removed after 8.0.13.

-
- Error number: [MY-012512](#); Symbol: [ER_IB_MSG_687](#); SQLSTATE: [HY000](#)

Message: MySQL has requested a very fast shutdown without flushing the InnoDB buffer pool to data files. At the next mysqld startup InnoDB will do a crash recovery!

[ER_IB_MSG_687](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012513](#); Symbol: [ER_IB_MSG_688](#); SQLSTATE: [HY000](#)

Message: Background thread %s woke up during shutdown

[ER_IB_MSG_688](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012514](#); Symbol: [ER_IB_MSG_689](#); SQLSTATE: [HY000](#)

Message: Waiting for archiver to finish archiving page and log

[ER_IB_MSG_689](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012515](#); Symbol: [ER_IB_MSG_690](#); SQLSTATE: [HY000](#)

Message: Background thread %s woke up during shutdown

[ER_IB_MSG_690](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012516](#); Symbol: [ER_IB_MSG_691](#); SQLSTATE: [HY000](#)

Message: Waiting for dirty buffer pages to be flushed

[ER_IB_MSG_691](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012517](#); Symbol: [ER_IB_MSG_692](#); SQLSTATE: [HY000](#)

Message: Log sequence number at shutdown %llu is lower than at startup %llu!

[ER_IB_MSG_692](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012518](#); Symbol: [ER_IB_MSG_693](#); SQLSTATE: [HY000](#)

Message: Waiting for archiver to finish archiving page and log

[ER_IB_MSG_693](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012519](#); Symbol: [ER_IB_MSG_694](#); SQLSTATE: [HY000](#)

Message: ##### CORRUPT LOG RECORD FOUND #####

[ER_IB_MSG_694](#) was added in 8.0.11.

- Error number: [MY-012520](#); Symbol: [ER_IB_MSG_695](#); SQLSTATE: [HY000](#)

Message: Log record type %d, page %lu:%lu. Log parsing proceeded successfully up to %llu. Previous log record type %d, is multi %llu Recv offset %zd, prev %llu

[ER_IB_MSG_695](#) was added in 8.0.11.

- Error number: [MY-012521](#); Symbol: [ER_IB_MSG_696](#); SQLSTATE: [HY000](#)

Message: Hex dump starting %llu bytes before and ending %llu bytes after the corrupted record:

[ER_IB_MSG_696](#) was added in 8.0.11.

-
- Error number: [MY-012522](#); Symbol: [ER_IB_MSG_697](#); SQLSTATE: [HY000](#)

Message: Set innodb_force_recovery to ignore this error.
[ER_IB_MSG_697](#) was added in 8.0.11.
 - Error number: [MY-012523](#); Symbol: [ER_IB_MSG_698](#); SQLSTATE: [HY000](#)

Message: The log file may have been corrupt and it is possible that the log scan did not proceed far enough in recovery! Please run CHECK TABLE on your InnoDB tables to check that they are ok! If mysqld crashes after this recovery; %s
[ER_IB_MSG_698](#) was added in 8.0.11.
 - Error number: [MY-012524](#); Symbol: [ER_IB_MSG_699](#); SQLSTATE: [HY000](#)

Message: %lu pages with log records were left unprocessed!
[ER_IB_MSG_699](#) was added in 8.0.11.
 - Error number: [MY-012525](#); Symbol: [ER_IB_MSG_700](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_700](#) was added in 8.0.11.
 - Error number: [MY-012526](#); Symbol: [ER_IB_MSG_701](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_701](#) was added in 8.0.11.
 - Error number: [MY-012527](#); Symbol: [ER_IB_MSG_702](#); SQLSTATE: [HY000](#)

Message: Invalid redo log header checksum.
[ER_IB_MSG_702](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012528](#); Symbol: [ER_IB_MSG_703](#); SQLSTATE: [HY000](#)

Message: Unsupported redo log format (%lu). The redo log was created before MySQL 5.7.9
[ER_IB_MSG_703](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012529](#); Symbol: [ER_IB_MSG_704](#); SQLSTATE: [HY000](#)

Message: Redo log format is v%lu. The redo log was created before MySQL 8.0.3.
[ER_IB_MSG_704](#) was added in 8.0.11.
 - Error number: [MY-012530](#); Symbol: [ER_IB_MSG_705](#); SQLSTATE: [HY000](#)

Message: Unknown redo log format (%lu). Please follow the instructions at %s upgrading-downgrading.html.
[ER_IB_MSG_705](#) was added in 8.0.11.
 - Error number: [MY-012531](#); Symbol: [ER_IB_MSG_706](#); SQLSTATE: [HY000](#)

Message: No valid checkpoint found (corrupted redo log). You can try --innodb-force-recovery=6 as a last resort.
[ER_IB_MSG_706](#) was added in 8.0.11.

-
- Error number: [MY-012532](#); Symbol: [ER_IB_MSG_707](#); SQLSTATE: [HY000](#)

Message: Applying a batch of %llu redo log records ...
[ER_IB_MSG_707](#) was added in 8.0.11.
 - Error number: [MY-012533](#); Symbol: [ER_IB_MSG_708](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_708](#) was added in 8.0.11.
 - Error number: [MY-012534](#); Symbol: [ER_IB_MSG_709](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_709](#) was added in 8.0.11.
 - Error number: [MY-012535](#); Symbol: [ER_IB_MSG_710](#); SQLSTATE: [HY000](#)

Message: Apply batch completed!
[ER_IB_MSG_710](#) was added in 8.0.11.
 - Error number: [MY-012536](#); Symbol: [ER_IB_MSG_711](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_711](#) was added in 8.0.11.
 - Error number: [MY-012537](#); Symbol: [ER_IB_MSG_712](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_712](#) was added in 8.0.11.
 - Error number: [MY-012538](#); Symbol: [ER_IB_MSG_713](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_713](#) was added in 8.0.11.
 - Error number: [MY-012539](#); Symbol: [ER_IB_MSG_714](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_714](#) was added in 8.0.11.
 - Error number: [MY-012540](#); Symbol: [ER_IB_MSG_715](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_715](#) was added in 8.0.11.
 - Error number: [MY-012541](#); Symbol: [ER_IB_MSG_716](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_716](#) was added in 8.0.11.
 - Error number: [MY-012542](#); Symbol: [ER_IB_MSG_717](#); SQLSTATE: [HY000](#)

Message: An optimized(without redo logging) DDL operation has been performed. All modified pages may not have been flushed to the disk yet. This offline backup may not be consistent

[ER_IB_MSG_717](#) was added in 8.0.11.

- Error number: [MY-012543](#); Symbol: [ER_IB_MSG_718](#); SQLSTATE: [HY000](#)

Message: Extending tablespace : %lu space name: %s to new size: %lu pages during recovery.

[ER_IB_MSG_718](#) was added in 8.0.11.

- Error number: [MY-012544](#); Symbol: [ER_IB_MSG_719](#); SQLSTATE: [HY000](#)

Message: Could not extend tablespace: %lu space name: %s to new size: %lu pages during recovery.

[ER_IB_MSG_719](#) was added in 8.0.11.

- Error number: [MY-012545](#); Symbol: [ER_IB_MSG_720](#); SQLSTATE: [HY000](#)

Message: Log block %llu at lsn %llu has valid header, but checksum field contains %lu, should be %lu.

[ER_IB_MSG_720](#) was added in 8.0.11.

- Error number: [MY-012546](#); Symbol: [ER_IB_MSG_721](#); SQLSTATE: [HY000](#)

Message: Recovery skipped, --innodb-read-only set!

[ER_IB_MSG_721](#) was added in 8.0.11.

- Error number: [MY-012547](#); Symbol: [ER_IB_MSG_722](#); SQLSTATE: [HY000](#)

Message: Log scan progressed past the checkpoint LSN %llu.

[ER_IB_MSG_722](#) was added in 8.0.11.

- Error number: [MY-012548](#); Symbol: [ER_IB_MSG_723](#); SQLSTATE: [HY000](#)

Message: Log parsing buffer overflow. Recovery may have failed! Please set log_buffer_size to a value higher than %lu.

[ER_IB_MSG_723](#) was added in 8.0.11.

- Error number: [MY-012549](#); Symbol: [ER_IB_MSG_724](#); SQLSTATE: [HY000](#)

Message: Set innodb_force_recovery to ignore this error.

[ER_IB_MSG_724](#) was added in 8.0.11.

- Error number: [MY-012550](#); Symbol: [ER_IB_MSG_725](#); SQLSTATE: [HY000](#)

Message: Doing recovery: scanned up to log sequence number %llu

[ER_IB_MSG_725](#) was added in 8.0.11.

- Error number: [MY-012551](#); Symbol: [ER_IB_MSG_726](#); SQLSTATE: [HY000](#)

Message: Database was not shutdown normally!

[ER_IB_MSG_726](#) was added in 8.0.11.

- Error number: [MY-012552](#); Symbol: [ER_IB_MSG_727](#); SQLSTATE: [HY000](#)

Message: Starting crash recovery.
[ER_IB_MSG_727](#) was added in 8.0.11.
- Error number: [MY-012553](#); Symbol: [ER_IB_MSG_728](#); SQLSTATE: [HY000](#)

Message: The user has set SRV_FORCE_NO_LOG_REDO on, skipping log redo
[ER_IB_MSG_728](#) was added in 8.0.11.
- Error number: [MY-012554](#); Symbol: [ER_IB_MSG_729](#); SQLSTATE: [HY000](#)

Message: Cannot restore from mysqlbackup, InnoDB running in read-only mode!
[ER_IB_MSG_729](#) was added in 8.0.11.
- Error number: [MY-012555](#); Symbol: [ER_IB_MSG_730](#); SQLSTATE: [HY000](#)

Message: The log file was created by mysqlbackup --apply-log at %. The following crash recovery is part of a normal restore.
[ER_IB_MSG_730](#) was added in 8.0.11.
- Error number: [MY-012556](#); Symbol: [ER_IB_MSG_731](#); SQLSTATE: [HY000](#)

Message: Opening cloned database
[ER_IB_MSG_731](#) was added in 8.0.11.
- Error number: [MY-012557](#); Symbol: [ER_IB_MSG_732](#); SQLSTATE: [HY000](#)

Message: Redo log is from an earlier version, v%lu.
[ER_IB_MSG_732](#) was added in 8.0.11.
- Error number: [MY-012558](#); Symbol: [ER_IB_MSG_733](#); SQLSTATE: [HY000](#)

Message: Redo log format v%lu not supported. Current supported format is v%lu.
[ER_IB_MSG_733](#) was added in 8.0.11.
- Error number: [MY-012559](#); Symbol: [ER_IB_MSG_734](#); SQLSTATE: [HY000](#)

Message: Are you sure you are using the right ib_logfiles to start up the database? Log sequence number in the ib_logfiles is %lu, less than the log sequence number in the first system tablespace file header, %lu.
[ER_IB_MSG_734](#) was added in 8.0.11.
- Error number: [MY-012560](#); Symbol: [ER_IB_MSG_735](#); SQLSTATE: [HY000](#)

Message: The log sequence number %lu in the system tablespace does not match the log sequence number %lu in the ib_logfiles!
[ER_IB_MSG_735](#) was added in 8.0.11.
- Error number: [MY-012561](#); Symbol: [ER_IB_MSG_736](#); SQLSTATE: [HY000](#)

Message: Can't initiate database recovery, running in read-only-mode.
[ER_IB_MSG_736](#) was added in 8.0.11.

-
- Error number: [MY-012562](#); Symbol: [ER_IB_MSG_737](#); SQLSTATE: HY000

Message: We scanned the log up to %llu. A checkpoint was at %llu and the maximum LSN on a database page was %llu. It is possible that the database is now corrupt!

[ER_IB_MSG_737](#) was added in 8.0.11.

- Error number: [MY-012563](#); Symbol: [ER_IB_MSG_738](#); SQLSTATE: HY000

Message: Waiting for recv_writer to finish flushing of buffer pool

[ER_IB_MSG_738](#) was added in 8.0.11.

- Error number: [MY-012564](#); Symbol: [ER_IB_MSG_739](#); SQLSTATE: HY000

Message: Recovery parsing buffer extended to %zu.

[ER_IB_MSG_739](#) was added in 8.0.11.

- Error number: [MY-012565](#); Symbol: [ER_IB_MSG_740](#); SQLSTATE: HY000

Message: Out of memory while resizing recovery parsing buffer.

[ER_IB_MSG_740](#) was added in 8.0.11.

- Error number: [MY-012566](#); Symbol: [ER_IB_MSG_741](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_741](#) was added in 8.0.11.

- Error number: [MY-012567](#); Symbol: [ER_IB_MSG_742](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_742](#) was added in 8.0.11.

- Error number: [MY-012568](#); Symbol: [ER_IB_MSG_743](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_743](#) was added in 8.0.11.

- Error number: [MY-012569](#); Symbol: [ER_IB_MSG_744](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_744](#) was added in 8.0.11.

- Error number: [MY-012570](#); Symbol: [ER_IB_MSG_745](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_745](#) was added in 8.0.11.

- Error number: [MY-012571](#); Symbol: [ER_IB_MSG_746](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_746](#) was added in 8.0.11.

- Error number: [MY-012572](#); Symbol: [ER_IB_MSG_747](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_747](#) was added in 8.0.11.

- Error number: [MY-012573](#); Symbol: [ER_IB_MSG_748](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_748](#) was added in 8.0.11.

- Error number: [MY-012574](#); Symbol: [ER_IB_MSG_749](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_749](#) was added in 8.0.11.

- Error number: [MY-012575](#); Symbol: [ER_IB_MSG_750](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_750](#) was added in 8.0.11.

- Error number: [MY-012576](#); Symbol: [ER_IB_MSG_751](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_751](#) was added in 8.0.11.

- Error number: [MY-012577](#); Symbol: [ER_IB_MSG_752](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_752](#) was added in 8.0.11.

- Error number: [MY-012578](#); Symbol: [ER_IB_MSG_753](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_753](#) was added in 8.0.11.

- Error number: [MY-012579](#); Symbol: [ER_IB_MSG_754](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_754](#) was added in 8.0.11.

- Error number: [MY-012580](#); Symbol: [ER_IB_MSG_755](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_755](#) was added in 8.0.11.

- Error number: [MY-012581](#); Symbol: [ER_IB_MSG_756](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_756](#) was added in 8.0.11.

- Error number: [MY-012582](#); Symbol: [ER_IB_MSG_757](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_757](#) was added in 8.0.11.

- Error number: [MY-012583](#); Symbol: [ER_IB_MSG_758](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_758](#) was added in 8.0.11.

- Error number: [MY-012584](#); Symbol: [ER_IB_MSG_759](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_759](#) was added in 8.0.11.

- Error number: [MY-012585](#); Symbol: [ER_IB_MSG_760](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_760](#) was added in 8.0.11.

- Error number: [MY-012586](#); Symbol: [ER_IB_MSG_761](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_761](#) was added in 8.0.11.

- Error number: [MY-012587](#); Symbol: [ER_IB_MSG_762](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_762](#) was added in 8.0.11.

- Error number: [MY-012588](#); Symbol: [ER_IB_MSG_763](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_763](#) was added in 8.0.11.

- Error number: [MY-012589](#); Symbol: [ER_IB_MSG_764](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_764](#) was added in 8.0.11.

- Error number: [MY-012590](#); Symbol: [ER_IB_MSG_765](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_765](#) was added in 8.0.11.

- Error number: [MY-012591](#); Symbol: [ER_IB_MSG_766](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_766](#) was added in 8.0.11.

- Error number: [MY-012592](#); Symbol: [ER_IB_MSG_767](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_767](#) was added in 8.0.11.

- Error number: [MY-012593](#); Symbol: [ER_IB_MSG_768](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_768](#) was added in 8.0.11.

-
- Error number: [MY-012594](#); Symbol: [ER_IB_MSG_769](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_769](#) was added in 8.0.11.
 - Error number: [MY-012595](#); Symbol: [ER_IB_MSG_770](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_770](#) was added in 8.0.11.
 - Error number: [MY-012596](#); Symbol: [ER_IB_MSG_771](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_771](#) was added in 8.0.11.
 - Error number: [MY-012597](#); Symbol: [ER_IB_MSG_772](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_772](#) was added in 8.0.11.
 - Error number: [MY-012598](#); Symbol: [ER_IB_MSG_773](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_773](#) was added in 8.0.11.
 - Error number: [MY-012599](#); Symbol: [ER_IB_MSG_774](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_774](#) was added in 8.0.11.
 - Error number: [MY-012600](#); Symbol: [ER_IB_MSG_775](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_775](#) was added in 8.0.11.
 - Error number: [MY-012601](#); Symbol: [ER_IB_MSG_776](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_776](#) was added in 8.0.11.
 - Error number: [MY-012602](#); Symbol: [ER_IB_MSG_777](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_777](#) was added in 8.0.11.
 - Error number: [MY-012603](#); Symbol: [ER_IB_MSG_778](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_778](#) was added in 8.0.11.
 - Error number: [MY-012604](#); Symbol: [ER_IB_MSG_779](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_779](#) was added in 8.0.11.

-
- Error number: [MY-012605](#); Symbol: [ER_IB_MSG_780](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_780](#) was added in 8.0.11.
 - Error number: [MY-012606](#); Symbol: [ER_IB_MSG_781](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_781](#) was added in 8.0.11.
 - Error number: [MY-012607](#); Symbol: [ER_IB_MSG_782](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_782](#) was added in 8.0.11.
 - Error number: [MY-012608](#); Symbol: [ER_IB_MSG_783](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_783](#) was added in 8.0.11.
 - Error number: [MY-012609](#); Symbol: [ER_IB_MSG_784](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_784](#) was added in 8.0.11.
 - Error number: [MY-012610](#); Symbol: [ER_IB_MSG_785](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_785](#) was added in 8.0.11.
 - Error number: [MY-012611](#); Symbol: [ER_IB_MSG_786](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_786](#) was added in 8.0.11.
 - Error number: [MY-012612](#); Symbol: [ER_IB_MSG_787](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_787](#) was added in 8.0.11.
 - Error number: [MY-012613](#); Symbol: [ER_IB_MSG_788](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_788](#) was added in 8.0.11.
 - Error number: [MY-012614](#); Symbol: [ER_IB_MSG_789](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_789](#) was added in 8.0.11.
 - Error number: [MY-012615](#); Symbol: [ER_IB_MSG_790](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_790](#) was added in 8.0.11.

- Error number: MY-012616; Symbol: ER_IB_MSG_791; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_791` was added in 8.0.11.
- Error number: MY-012617; Symbol: ER_IB_MSG_792; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_792` was added in 8.0.11.
- Error number: MY-012618; Symbol: ER_IB_MSG_793; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_793` was added in 8.0.11.
- Error number: MY-012619; Symbol: ER_IB_MSG_794; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_794` was added in 8.0.11.
- Error number: MY-012620; Symbol: ER_IB_MSG_795; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_795` was added in 8.0.11.
- Error number: MY-012621; Symbol: ER_IB_MSG_796; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_796` was added in 8.0.11.
- Error number: MY-012622; Symbol: ER_IB_MSG_797; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_797` was added in 8.0.11.
- Error number: MY-012623; Symbol: ER_IB_MSG_798; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_798` was added in 8.0.11.
- Error number: MY-012624; Symbol: ER_IB_MSG_799; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_799` was added in 8.0.11.
- Error number: MY-012625; Symbol: ER_IB_MSG_800; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_800` was added in 8.0.11.
- Error number: MY-012626; Symbol: ER_IB_MSG_801; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_801` was added in 8.0.11.

-
- Error number: [MY-012627](#); Symbol: [ER_IB_MSG_802](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_802](#) was added in 8.0.11.
 - Error number: [MY-012628](#); Symbol: [ER_IB_MSG_803](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_803](#) was added in 8.0.11.
 - Error number: [MY-012629](#); Symbol: [ER_IB_MSG_804](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_804](#) was added in 8.0.11.
 - Error number: [MY-012630](#); Symbol: [ER_IB_MSG_805](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_805](#) was added in 8.0.11.
 - Error number: [MY-012631](#); Symbol: [ER_IB_MSG_806](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_806](#) was added in 8.0.11.
 - Error number: [MY-012632](#); Symbol: [ER_IB_MSG_807](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_807](#) was added in 8.0.11.
 - Error number: [MY-012633](#); Symbol: [ER_IB_MSG_808](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_808](#) was added in 8.0.11.
 - Error number: [MY-012634](#); Symbol: [ER_IB_MSG_809](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_809](#) was added in 8.0.11.
 - Error number: [MY-012635](#); Symbol: [ER_IB_MSG_810](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_810](#) was added in 8.0.11.
 - Error number: [MY-012636](#); Symbol: [ER_IB_MSG_811](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_811](#) was added in 8.0.11.
 - Error number: [MY-012637](#); Symbol: [ER_IB_MSG_812](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_812](#) was added in 8.0.11.

- Error number: MY-012638; Symbol: ER_IB_MSG_813; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_813](#) was added in 8.0.11.
- Error number: MY-012639; Symbol: ER_IB_MSG_814; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_814](#) was added in 8.0.11.
- Error number: MY-012640; Symbol: ER_IB_MSG_815; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_815](#) was added in 8.0.11.
- Error number: MY-012641; Symbol: ER_IB_MSG_816; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_816](#) was added in 8.0.11.
- Error number: MY-012642; Symbol: ER_IB_MSG_817; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_817](#) was added in 8.0.11.
- Error number: MY-012643; Symbol: ER_IB_MSG_818; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_818](#) was added in 8.0.11.
- Error number: MY-012644; Symbol: ER_IB_MSG_819; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_819](#) was added in 8.0.11.
- Error number: MY-012645; Symbol: ER_IB_MSG_820; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_820](#) was added in 8.0.11.
- Error number: MY-012646; Symbol: ER_IB_MSG_821; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_821](#) was added in 8.0.11.
- Error number: MY-012647; Symbol: ER_IB_MSG_822; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_822](#) was added in 8.0.11.
- Error number: MY-012648; Symbol: ER_IB_MSG_823; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_823](#) was added in 8.0.11.

-
- Error number: [MY-012649](#); Symbol: [ER_IB_MSG_824](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_824](#) was added in 8.0.11.
 - Error number: [MY-012650](#); Symbol: [ER_IB_MSG_825](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_825](#) was added in 8.0.11.
 - Error number: [MY-012651](#); Symbol: [ER_IB_MSG_826](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_826](#) was added in 8.0.11.
 - Error number: [MY-012652](#); Symbol: [ER_IB_MSG_827](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_827](#) was added in 8.0.11.
 - Error number: [MY-012653](#); Symbol: [ER_IB_MSG_828](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_828](#) was added in 8.0.11.
 - Error number: [MY-012654](#); Symbol: [ER_IB_MSG_829](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_829](#) was added in 8.0.11.
 - Error number: [MY-012655](#); Symbol: [ER_IB_MSG_830](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_830](#) was added in 8.0.11.
 - Error number: [MY-012656](#); Symbol: [ER_IB_MSG_831](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_831](#) was added in 8.0.11.
 - Error number: [MY-012657](#); Symbol: [ER_IB_MSG_832](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_832](#) was added in 8.0.11.
 - Error number: [MY-012658](#); Symbol: [ER_IB_MSG_833](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_833](#) was added in 8.0.11.
 - Error number: [MY-012659](#); Symbol: [ER_IB_MSG_834](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_834](#) was added in 8.0.11.

- Error number: MY-012660; Symbol: ER_IB_MSG_835; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_835](#) was added in 8.0.11.
- Error number: MY-012661; Symbol: ER_IB_MSG_836; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_836](#) was added in 8.0.11.
- Error number: MY-012662; Symbol: ER_IB_MSG_837; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_837](#) was added in 8.0.11.
- Error number: MY-012663; Symbol: ER_IB_MSG_838; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_838](#) was added in 8.0.11.
- Error number: MY-012664; Symbol: ER_IB_MSG_839; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_839](#) was added in 8.0.11.
- Error number: MY-012665; Symbol: ER_IB_MSG_840; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_840](#) was added in 8.0.11.
- Error number: MY-012666; Symbol: ER_IB_MSG_841; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_841](#) was added in 8.0.11.
- Error number: MY-012667; Symbol: ER_IB_MSG_842; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_842](#) was added in 8.0.11.
- Error number: MY-012668; Symbol: ER_IB_MSG_843; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_843](#) was added in 8.0.11.
- Error number: MY-012669; Symbol: ER_IB_MSG_844; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_844](#) was added in 8.0.11.
- Error number: MY-012670; Symbol: ER_IB_MSG_845; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_845](#) was added in 8.0.11.

-
- Error number: [MY-012671](#); Symbol: [ER_IB_MSG_846](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_846](#) was added in 8.0.11.
 - Error number: [MY-012672](#); Symbol: [ER_IB_MSG_847](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_847](#) was added in 8.0.11.
 - Error number: [MY-012673](#); Symbol: [ER_IB_MSG_848](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_848](#) was added in 8.0.11.
 - Error number: [MY-012674](#); Symbol: [ER_IB_MSG_849](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_849](#) was added in 8.0.11.
 - Error number: [MY-012675](#); Symbol: [ER_IB_MSG_850](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_850](#) was added in 8.0.11.
 - Error number: [MY-012676](#); Symbol: [ER_IB_MSG_851](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_851](#) was added in 8.0.11.
 - Error number: [MY-012677](#); Symbol: [ER_IB_MSG_852](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_852](#) was added in 8.0.11.
 - Error number: [MY-012678](#); Symbol: [ER_IB_MSG_853](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_853](#) was added in 8.0.11.
 - Error number: [MY-012679](#); Symbol: [ER_IB_MSG_854](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_854](#) was added in 8.0.11.
 - Error number: [MY-012680](#); Symbol: [ER_IB_MSG_855](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_855](#) was added in 8.0.11.
 - Error number: [MY-012681](#); Symbol: [ER_IB_MSG_856](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_856](#) was added in 8.0.11.

- Error number: [MY-012682](#); Symbol: [ER_IB_MSG_857](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_857](#) was added in 8.0.11.
- Error number: [MY-012683](#); Symbol: [ER_IB_MSG_858](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_858](#) was added in 8.0.11.
- Error number: [MY-012684](#); Symbol: [ER_IB_MSG_859](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_859](#) was added in 8.0.11.
- Error number: [MY-012685](#); Symbol: [ER_IB_MSG_860](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_860](#) was added in 8.0.11.
- Error number: [MY-012686](#); Symbol: [ER_IB_MSG_861](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_861](#) was added in 8.0.11.
- Error number: [MY-012687](#); Symbol: [ER_IB_MSG_862](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_862](#) was added in 8.0.11.
- Error number: [MY-012688](#); Symbol: [ER_IB_MSG_863](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_863](#) was added in 8.0.11.
- Error number: [MY-012689](#); Symbol: [ER_IB_MSG_864](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_864](#) was added in 8.0.11.
- Error number: [MY-012690](#); Symbol: [ER_IB_MSG_865](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_865](#) was added in 8.0.11.
- Error number: [MY-012691](#); Symbol: [ER_IB_MSG_866](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_866](#) was added in 8.0.11.
- Error number: [MY-012692](#); Symbol: [ER_IB_MSG_867](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_867](#) was added in 8.0.11.

-
- Error number: [MY-012693](#); Symbol: [ER_IB_MSG_868](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_868](#) was added in 8.0.11.
 - Error number: [MY-012694](#); Symbol: [ER_IB_MSG_869](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_869](#) was added in 8.0.11.
 - Error number: [MY-012695](#); Symbol: [ER_IB_MSG_870](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_870](#) was added in 8.0.11.
 - Error number: [MY-012696](#); Symbol: [ER_IB_MSG_871](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_871](#) was added in 8.0.11.
 - Error number: [MY-012697](#); Symbol: [ER_IB_MSG_872](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_872](#) was added in 8.0.11.
 - Error number: [MY-012698](#); Symbol: [ER_IB_MSG_873](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_873](#) was added in 8.0.11.
 - Error number: [MY-012699](#); Symbol: [ER_IB_MSG_874](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_874](#) was added in 8.0.11.
 - Error number: [MY-012700](#); Symbol: [ER_IB_MSG_875](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_875](#) was added in 8.0.11.
 - Error number: [MY-012701](#); Symbol: [ER_IB_MSG_876](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_876](#) was added in 8.0.11.
 - Error number: [MY-012702](#); Symbol: [ER_IB_MSG_877](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_877](#) was added in 8.0.11.
 - Error number: [MY-012703](#); Symbol: [ER_IB_MSG_878](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_878](#) was added in 8.0.11.

- Error number: [MY-012704](#); Symbol: [ER_IB_MSG_879](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_879](#) was added in 8.0.11.
- Error number: [MY-012705](#); Symbol: [ER_IB_MSG_880](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_880](#) was added in 8.0.11.
- Error number: [MY-012706](#); Symbol: [ER_IB_MSG_881](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_881](#) was added in 8.0.11.
- Error number: [MY-012707](#); Symbol: [ER_IB_MSG_882](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_882](#) was added in 8.0.11.
- Error number: [MY-012708](#); Symbol: [ER_IB_MSG_883](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_883](#) was added in 8.0.11.
- Error number: [MY-012709](#); Symbol: [ER_IB_MSG_884](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_884](#) was added in 8.0.11.
- Error number: [MY-012710](#); Symbol: [ER_IB_MSG_885](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_885](#) was added in 8.0.11.
- Error number: [MY-012711](#); Symbol: [ER_IB_MSG_886](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_886](#) was added in 8.0.11.
- Error number: [MY-012712](#); Symbol: [ER_IB_MSG_887](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_887](#) was added in 8.0.11.
- Error number: [MY-012713](#); Symbol: [ER_IB_MSG_888](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_888](#) was added in 8.0.11.
- Error number: [MY-012714](#); Symbol: [ER_IB_MSG_889](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_889](#) was added in 8.0.11.

-
- Error number: [MY-012715](#); Symbol: [ER_IB_MSG_890](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_890](#) was added in 8.0.11.
 - Error number: [MY-012716](#); Symbol: [ER_IB_MSG_891](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_891](#) was added in 8.0.11.
 - Error number: [MY-012717](#); Symbol: [ER_IB_MSG_892](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_892](#) was added in 8.0.11.
 - Error number: [MY-012718](#); Symbol: [ER_IB_MSG_893](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_893](#) was added in 8.0.11.
 - Error number: [MY-012719](#); Symbol: [ER_IB_MSG_894](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_894](#) was added in 8.0.11.
 - Error number: [MY-012720](#); Symbol: [ER_IB_MSG_895](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_895](#) was added in 8.0.11.
 - Error number: [MY-012721](#); Symbol: [ER_IB_MSG_896](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_896](#) was added in 8.0.11.
 - Error number: [MY-012722](#); Symbol: [ER_IB_MSG_897](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_897](#) was added in 8.0.11.
 - Error number: [MY-012723](#); Symbol: [ER_IB_MSG_898](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_898](#) was added in 8.0.11.
 - Error number: [MY-012724](#); Symbol: [ER_IB_MSG_899](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_899](#) was added in 8.0.11.
 - Error number: [MY-012725](#); Symbol: [ER_IB_MSG_900](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_900](#) was added in 8.0.11.

-
- Error number: MY-012726; Symbol: ER_IB_MSG_901; SQLSTATE: HY000
Message: %s
ER_IB_MSG_901 was added in 8.0.11.
 - Error number: MY-012727; Symbol: ER_IB_MSG_902; SQLSTATE: HY000
Message: %s
ER_IB_MSG_902 was added in 8.0.11.
 - Error number: MY-012728; Symbol: ER_IB_MSG_903; SQLSTATE: HY000
Message: %s
ER_IB_MSG_903 was added in 8.0.11.
 - Error number: MY-012729; Symbol: ER_IB_MSG_904; SQLSTATE: HY000
Message: %s
ER_IB_MSG_904 was added in 8.0.11.
 - Error number: MY-012730; Symbol: ER_IB_MSG_905; SQLSTATE: HY000
Message: %s
ER_IB_MSG_905 was added in 8.0.11.
 - Error number: MY-012731; Symbol: ER_IB_MSG_906; SQLSTATE: HY000
Message: %s
ER_IB_MSG_906 was added in 8.0.11.
 - Error number: MY-012732; Symbol: ER_IB_MSG_907; SQLSTATE: HY000
Message: %s
ER_IB_MSG_907 was added in 8.0.11.
 - Error number: MY-012733; Symbol: ER_IB_MSG_908; SQLSTATE: HY000
Message: %s
ER_IB_MSG_908 was added in 8.0.11.
 - Error number: MY-012734; Symbol: ER_IB_MSG_909; SQLSTATE: HY000
Message: %s
ER_IB_MSG_909 was added in 8.0.11.
 - Error number: MY-012735; Symbol: ER_IB_MSG_910; SQLSTATE: HY000
Message: %s
ER_IB_MSG_910 was added in 8.0.11.
 - Error number: MY-012736; Symbol: ER_IB_MSG_911; SQLSTATE: HY000
Message: %s
ER_IB_MSG_911 was added in 8.0.11.

-
- Error number: [MY-012737](#); Symbol: [ER_IB_MSG_912](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_912](#) was added in 8.0.11.
 - Error number: [MY-012738](#); Symbol: [ER_IB_MSG_913](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_913](#) was added in 8.0.11.
 - Error number: [MY-012739](#); Symbol: [ER_IB_MSG_914](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_914](#) was added in 8.0.11.
 - Error number: [MY-012740](#); Symbol: [ER_IB_MSG_915](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_915](#) was added in 8.0.11.
 - Error number: [MY-012741](#); Symbol: [ER_IB_MSG_916](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_916](#) was added in 8.0.11.
 - Error number: [MY-012742](#); Symbol: [ER_IB_MSG_917](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_917](#) was added in 8.0.11.
 - Error number: [MY-012743](#); Symbol: [ER_IB_MSG_918](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_918](#) was added in 8.0.11.
 - Error number: [MY-012744](#); Symbol: [ER_IB_MSG_919](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_919](#) was added in 8.0.11.
 - Error number: [MY-012745](#); Symbol: [ER_IB_MSG_920](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_920](#) was added in 8.0.11.
 - Error number: [MY-012746](#); Symbol: [ER_IB_MSG_921](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_921](#) was added in 8.0.11.
 - Error number: [MY-012747](#); Symbol: [ER_IB_MSG_922](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_922](#) was added in 8.0.11.

- Error number: MY-012748; Symbol: ER_IB_MSG_923; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_923](#) was added in 8.0.11.
- Error number: MY-012749; Symbol: ER_IB_MSG_924; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_924](#) was added in 8.0.11.
- Error number: MY-012750; Symbol: ER_IB_MSG_925; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_925](#) was added in 8.0.11.
- Error number: MY-012751; Symbol: ER_IB_MSG_926; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_926](#) was added in 8.0.11.
- Error number: MY-012752; Symbol: ER_IB_MSG_927; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_927](#) was added in 8.0.11.
- Error number: MY-012753; Symbol: ER_IB_MSG_928; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_928](#) was added in 8.0.11.
- Error number: MY-012754; Symbol: ER_IB_MSG_929; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_929](#) was added in 8.0.11.
- Error number: MY-012755; Symbol: ER_IB_MSG_930; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_930](#) was added in 8.0.11.
- Error number: MY-012756; Symbol: ER_IB_MSG_931; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_931](#) was added in 8.0.11.
- Error number: MY-012757; Symbol: ER_IB_MSG_932; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_932](#) was added in 8.0.11.
- Error number: MY-012758; Symbol: ER_IB_MSG_933; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_933](#) was added in 8.0.11.

-
- Error number: [MY-012759](#); Symbol: [ER_IB_MSG_934](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_934](#) was added in 8.0.11.
 - Error number: [MY-012760](#); Symbol: [ER_IB_MSG_935](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_935](#) was added in 8.0.11.
 - Error number: [MY-012761](#); Symbol: [ER_IB_MSG_936](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_936](#) was added in 8.0.11.
 - Error number: [MY-012762](#); Symbol: [ER_IB_MSG_937](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_937](#) was added in 8.0.11.
 - Error number: [MY-012763](#); Symbol: [ER_IB_MSG_938](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_938](#) was added in 8.0.11.
 - Error number: [MY-012764](#); Symbol: [ER_IB_MSG_939](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_939](#) was added in 8.0.11.
 - Error number: [MY-012765](#); Symbol: [ER_IB_MSG_940](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_940](#) was added in 8.0.11.
 - Error number: [MY-012766](#); Symbol: [ER_IB_MSG_941](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_941](#) was added in 8.0.11.
 - Error number: [MY-012767](#); Symbol: [ER_IB_MSG_942](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_942](#) was added in 8.0.11.
 - Error number: [MY-012768](#); Symbol: [ER_IB_MSG_943](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_943](#) was added in 8.0.11.
 - Error number: [MY-012769](#); Symbol: [ER_IB_MSG_944](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_944](#) was added in 8.0.11.

- Error number: MY-012770; Symbol: ER_IB_MSG_945; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_945](#) was added in 8.0.11.
- Error number: MY-012771; Symbol: ER_IB_MSG_946; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_946](#) was added in 8.0.11.
- Error number: MY-012772; Symbol: ER_IB_MSG_947; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_947](#) was added in 8.0.11.
- Error number: MY-012773; Symbol: ER_IB_MSG_948; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_948](#) was added in 8.0.11.
- Error number: MY-012774; Symbol: ER_IB_MSG_949; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_949](#) was added in 8.0.11.
- Error number: MY-012775; Symbol: ER_IB_MSG_950; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_950](#) was added in 8.0.11.
- Error number: MY-012776; Symbol: ER_IB_MSG_951; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_951](#) was added in 8.0.11.
- Error number: MY-012777; Symbol: ER_IB_MSG_952; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_952](#) was added in 8.0.11.
- Error number: MY-012778; Symbol: ER_IB_MSG_953; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_953](#) was added in 8.0.11.
- Error number: MY-012779; Symbol: ER_IB_MSG_954; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_954](#) was added in 8.0.11.
- Error number: MY-012780; Symbol: ER_IB_MSG_955; SQLSTATE: HY000
Message: %s
[ER_IB_MSG_955](#) was added in 8.0.11.

-
- Error number: [MY-012781](#); Symbol: [ER_IB_MSG_956](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_956](#) was added in 8.0.11.
 - Error number: [MY-012782](#); Symbol: [ER_IB_MSG_957](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_957](#) was added in 8.0.11.
 - Error number: [MY-012783](#); Symbol: [ER_IB_MSG_958](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_958](#) was added in 8.0.11.
 - Error number: [MY-012784](#); Symbol: [ER_IB_MSG_959](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_959](#) was added in 8.0.11.
 - Error number: [MY-012785](#); Symbol: [ER_IB_MSG_960](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_960](#) was added in 8.0.11.
 - Error number: [MY-012786](#); Symbol: [ER_IB_MSG_961](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_961](#) was added in 8.0.11.
 - Error number: [MY-012787](#); Symbol: [ER_IB_MSG_962](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_962](#) was added in 8.0.11.
 - Error number: [MY-012788](#); Symbol: [ER_IB_MSG_963](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_963](#) was added in 8.0.11.
 - Error number: [MY-012789](#); Symbol: [ER_IB_MSG_964](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_964](#) was added in 8.0.11.
 - Error number: [MY-012790](#); Symbol: [ER_IB_MSG_965](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_965](#) was added in 8.0.11.
 - Error number: [MY-012791](#); Symbol: [ER_IB_MSG_966](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_966](#) was added in 8.0.11.

- Error number: MY-012792; Symbol: ER_IB_MSG_967; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_967` was added in 8.0.11.
- Error number: MY-012793; Symbol: ER_IB_MSG_968; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_968` was added in 8.0.11.
- Error number: MY-012794; Symbol: ER_IB_MSG_969; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_969` was added in 8.0.11.
- Error number: MY-012795; Symbol: ER_IB_MSG_970; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_970` was added in 8.0.11.
- Error number: MY-012796; Symbol: ER_IB_MSG_971; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_971` was added in 8.0.11.
- Error number: MY-012797; Symbol: ER_IB_MSG_972; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_972` was added in 8.0.11.
- Error number: MY-012798; Symbol: ER_IB_MSG_973; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_973` was added in 8.0.11.
- Error number: MY-012799; Symbol: ER_IB_MSG_974; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_974` was added in 8.0.11.
- Error number: MY-012800; Symbol: ER_IB_MSG_975; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_975` was added in 8.0.11.
- Error number: MY-012801; Symbol: ER_IB_MSG_976; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_976` was added in 8.0.11.
- Error number: MY-012802; Symbol: ER_IB_MSG_977; SQLSTATE: HY000
Message: %s
`ER_IB_MSG_977` was added in 8.0.11.

-
- Error number: [MY-012803](#); Symbol: [ER_IB_MSG_978](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_978](#) was added in 8.0.11.
 - Error number: [MY-012804](#); Symbol: [ER_IB_MSG_979](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_979](#) was added in 8.0.11.
 - Error number: [MY-012805](#); Symbol: [ER_IB_MSG_980](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_980](#) was added in 8.0.11.
 - Error number: [MY-012806](#); Symbol: [ER_IB_MSG_981](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_981](#) was added in 8.0.11.
 - Error number: [MY-012807](#); Symbol: [ER_IB_MSG_982](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_982](#) was added in 8.0.11.
 - Error number: [MY-012808](#); Symbol: [ER_IB_MSG_983](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_983](#) was added in 8.0.11.
 - Error number: [MY-012809](#); Symbol: [ER_IB_MSG_984](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_984](#) was added in 8.0.11.
 - Error number: [MY-012810](#); Symbol: [ER_IB_MSG_985](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_985](#) was added in 8.0.11.
 - Error number: [MY-012811](#); Symbol: [ER_IB_MSG_986](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_986](#) was added in 8.0.11.
 - Error number: [MY-012812](#); Symbol: [ER_IB_MSG_987](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_987](#) was added in 8.0.11.
 - Error number: [MY-012813](#); Symbol: [ER_IB_MSG_988](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_988](#) was added in 8.0.11.

- Error number: [MY-012814](#); Symbol: [ER_IB_MSG_989](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_989](#) was added in 8.0.11.
- Error number: [MY-012815](#); Symbol: [ER_IB_MSG_990](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_990](#) was added in 8.0.11.
- Error number: [MY-012816](#); Symbol: [ER_IB_MSG_991](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_991](#) was added in 8.0.11.
- Error number: [MY-012817](#); Symbol: [ER_IB_MSG_992](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_992](#) was added in 8.0.11.
- Error number: [MY-012818](#); Symbol: [ER_IB_MSG_993](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_993](#) was added in 8.0.11.
- Error number: [MY-012819](#); Symbol: [ER_IB_MSG_994](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_994](#) was added in 8.0.11.
- Error number: [MY-012820](#); Symbol: [ER_IB_MSG_995](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_995](#) was added in 8.0.11.
- Error number: [MY-012821](#); Symbol: [ER_IB_MSG_996](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_996](#) was added in 8.0.11.
- Error number: [MY-012822](#); Symbol: [ER_IB_MSG_997](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_997](#) was added in 8.0.11.
- Error number: [MY-012823](#); Symbol: [ER_IB_MSG_998](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_998](#) was added in 8.0.11.
- Error number: [MY-012824](#); Symbol: [ER_IB_MSG_999](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_999](#) was added in 8.0.11.

-
- Error number: [MY-012825](#); Symbol: [ER_IB_MSG_1000](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1000](#) was added in 8.0.11.
 - Error number: [MY-012826](#); Symbol: [ER_IB_MSG_1001](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1001](#) was added in 8.0.11.
 - Error number: [MY-012827](#); Symbol: [ER_IB_MSG_1002](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1002](#) was added in 8.0.11.
 - Error number: [MY-012828](#); Symbol: [ER_IB_MSG_1003](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1003](#) was added in 8.0.11.
 - Error number: [MY-012829](#); Symbol: [ER_IB_MSG_1004](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1004](#) was added in 8.0.11.
 - Error number: [MY-012830](#); Symbol: [ER_IB_MSG_1005](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1005](#) was added in 8.0.11.
 - Error number: [MY-012831](#); Symbol: [ER_IB_MSG_1006](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1006](#) was added in 8.0.11.
 - Error number: [MY-012832](#); Symbol: [ER_IB_MSG_1007](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1007](#) was added in 8.0.11.
 - Error number: [MY-012833](#); Symbol: [ER_IB_MSG_1008](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1008](#) was added in 8.0.11.
 - Error number: [MY-012834](#); Symbol: [ER_IB_MSG_1009](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1009](#) was added in 8.0.11.
 - Error number: [MY-012835](#); Symbol: [ER_IB_MSG_1010](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1010](#) was added in 8.0.11.

-
- Error number: MY-012836; Symbol: [ER_IB_MSG_1011](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1011](#) was added in 8.0.11.
 - Error number: MY-012837; Symbol: [ER_IB_MSG_1012](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1012](#) was added in 8.0.11.
 - Error number: MY-012838; Symbol: [ER_IB_MSG_1013](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1013](#) was added in 8.0.11.
 - Error number: MY-012839; Symbol: [ER_IB_MSG_1014](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1014](#) was added in 8.0.11.
 - Error number: MY-012840; Symbol: [ER_IB_MSG_1015](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1015](#) was added in 8.0.11.
 - Error number: MY-012841; Symbol: [ER_IB_MSG_1016](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1016](#) was added in 8.0.11.
 - Error number: MY-012842; Symbol: [ER_IB_MSG_1017](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1017](#) was added in 8.0.11.
 - Error number: MY-012843; Symbol: [ER_IB_MSG_1018](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1018](#) was added in 8.0.11.
 - Error number: MY-012844; Symbol: [ER_IB_MSG_1019](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1019](#) was added in 8.0.11.
 - Error number: MY-012845; Symbol: [ER_IB_MSG_1020](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1020](#) was added in 8.0.11.
 - Error number: MY-012846; Symbol: [ER_IB_MSG_1021](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1021](#) was added in 8.0.11.

-
- Error number: [MY-012847](#); Symbol: [ER_IB_MSG_1022](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1022](#) was added in 8.0.11.
 - Error number: [MY-012848](#); Symbol: [ER_IB_MSG_1023](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1023](#) was added in 8.0.11.
 - Error number: [MY-012849](#); Symbol: [ER_IB_MSG_1024](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1024](#) was added in 8.0.11.
 - Error number: [MY-012850](#); Symbol: [ER_IB_MSG_1025](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1025](#) was added in 8.0.11.
 - Error number: [MY-012851](#); Symbol: [ER_IB_MSG_1026](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1026](#) was added in 8.0.11.
 - Error number: [MY-012852](#); Symbol: [ER_IB_MSG_1027](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1027](#) was added in 8.0.11.
 - Error number: [MY-012853](#); Symbol: [ER_IB_MSG_1028](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1028](#) was added in 8.0.11.
 - Error number: [MY-012854](#); Symbol: [ER_IB_MSG_1029](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1029](#) was added in 8.0.11.
 - Error number: [MY-012855](#); Symbol: [ER_IB_MSG_1030](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1030](#) was added in 8.0.11.
 - Error number: [MY-012856](#); Symbol: [ER_IB_MSG_1031](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1031](#) was added in 8.0.11.
 - Error number: [MY-012857](#); Symbol: [ER_IB_MSG_1032](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1032](#) was added in 8.0.11.

-
- Error number: MY-012858; Symbol: `ER_IB_MSG_1033`; SQLSTATE: `HY000`

Message: %s
`ER_IB_MSG_1033` was added in 8.0.11.
 - Error number: MY-012859; Symbol: `ER_IB_MSG_1034`; SQLSTATE: `HY000`

Message: %s
`ER_IB_MSG_1034` was added in 8.0.11.
 - Error number: MY-012860; Symbol: `ER_IB_MSG_1035`; SQLSTATE: `HY000`

Message: %s
`ER_IB_MSG_1035` was added in 8.0.11.
 - Error number: MY-012861; Symbol: `ER_IB_MSG_1036`; SQLSTATE: `HY000`

Message: %s
`ER_IB_MSG_1036` was added in 8.0.11.
 - Error number: MY-012862; Symbol: `ER_IB_MSG_1037`; SQLSTATE: `HY000`

Message: %s
`ER_IB_MSG_1037` was added in 8.0.11.
 - Error number: MY-012863; Symbol: `ER_IB_MSG_1038`; SQLSTATE: `HY000`

Message: %s
`ER_IB_MSG_1038` was added in 8.0.11.
 - Error number: MY-012864; Symbol: `ER_IB_MSG_1039`; SQLSTATE: `HY000`

Message: %s
`ER_IB_MSG_1039` was added in 8.0.11.
 - Error number: MY-012865; Symbol: `ER_IB_MSG_1040`; SQLSTATE: `HY000`

Message: %s
`ER_IB_MSG_1040` was added in 8.0.11.
 - Error number: MY-012866; Symbol: `ER_IB_MSG_1041`; SQLSTATE: `HY000`

Message: %s
`ER_IB_MSG_1041` was added in 8.0.11.
 - Error number: MY-012867; Symbol: `ER_IB_MSG_1042`; SQLSTATE: `HY000`

Message: %s
`ER_IB_MSG_1042` was added in 8.0.11.
 - Error number: MY-012868; Symbol: `ER_IB_MSG_1043`; SQLSTATE: `HY000`

Message: %s
`ER_IB_MSG_1043` was added in 8.0.11.

-
- Error number: [MY-012869](#); Symbol: [ER_IB_MSG_1044](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1044](#) was added in 8.0.11.
 - Error number: [MY-012870](#); Symbol: [ER_IB_MSG_1045](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1045](#) was added in 8.0.11.
 - Error number: [MY-012871](#); Symbol: [ER_IB_MSG_1046](#); SQLSTATE: HY000
Message: Old log sequence number %llu was greater than the new log sequence number %llu.
Please submit a bug report to <http://bugs.mysql.com>
[ER_IB_MSG_1046](#) was added in 8.0.11.
 - Error number: [MY-012872](#); Symbol: [ER_IB_MSG_1047](#); SQLSTATE: HY000
Message: Semaphore wait has lasted > %llu seconds. We intentionally crash the server because it appears to be hung.
[ER_IB_MSG_1047](#) was added in 8.0.11.
 - Error number: [MY-012873](#); Symbol: [ER_IB_MSG_1048](#); SQLSTATE: HY000
Message: Waiting for %llu table(s) to be dropped
[ER_IB_MSG_1048](#) was added in 8.0.11.
 - Error number: [MY-012874](#); Symbol: [ER_IB_MSG_1049](#); SQLSTATE: HY000
Message: Waiting for change buffer merge to complete number of bytes of change buffer just merged: %llu
[ER_IB_MSG_1049](#) was added in 8.0.11.
 - Error number: [MY-012875](#); Symbol: [ER_IB_MSG_1050](#); SQLSTATE: HY000
Message: Can't set undo tablespace(s) to be encrypted since --innodb_undo_tablespaces=0.
[ER_IB_MSG_1050](#) was added in 8.0.11, removed after 8.0.15.
 - Error number: [MY-012876](#); Symbol: [ER_IB_MSG_1051](#); SQLSTATE: HY000
Message: Can't set undo tablespace(s) to be encrypted in read-only-mode.
[ER_IB_MSG_1051](#) was added in 8.0.11.
 - Error number: [MY-012877](#); Symbol: [ER_IB_MSG_1052](#); SQLSTATE: HY000
Message: Can't set undo tablespace '%s' to be encrypted.
[ER_IB_MSG_1052](#) was added in 8.0.11.
 - Error number: [MY-012878](#); Symbol: [ER_IB_MSG_1053](#); SQLSTATE: HY000
Message: Can't set undo tablespace '%s' to be encrypted. Failed to write header page.
[ER_IB_MSG_1053](#) was added in 8.0.11.
 - Error number: [MY-012879](#); Symbol: [ER_IB_MSG_1054](#); SQLSTATE: HY000

Message: Can't set undo tablespace '%s' to be encrypted. Error %d - %s

[ER_IB_MSG_1054](#) was added in 8.0.11.

- Error number: [MY-012880](#); Symbol: [ER_IB_MSG_1055](#); SQLSTATE: [HY000](#)

Message: Encryption is enabled for undo tablespace '%s'.

[ER_IB_MSG_1055](#) was added in 8.0.11.

- Error number: [MY-012881](#); Symbol: [ER_IB_MSG_1056](#); SQLSTATE: [HY000](#)

Message: Can't rotate encryption on undo tablespace '%s'.

[ER_IB_MSG_1056](#) was added in 8.0.11.

- Error number: [MY-012882](#); Symbol: [ER_IB_MSG_1057](#); SQLSTATE: [HY000](#)

Message: Encryption is enabled for undo tablespace '%s'.

[ER_IB_MSG_1057](#) was added in 8.0.11.

- Error number: [MY-012883](#); Symbol: [ER_IB_MSG_1058](#); SQLSTATE: [HY000](#)

Message: os_file_get_status() failed on '%s'. Can't determine file permissions.

[ER_IB_MSG_1058](#) was added in 8.0.11.

- Error number: [MY-012884](#); Symbol: [ER_IB_MSG_1059](#); SQLSTATE: [HY000](#)

Message: %s can't be opened in %s mode.

[ER_IB_MSG_1059](#) was added in 8.0.11.

- Error number: [MY-012885](#); Symbol: [ER_IB_MSG_1060](#); SQLSTATE: [HY000](#)

Message: '%s' not a regular file.

[ER_IB_MSG_1060](#) was added in 8.0.11.

- Error number: [MY-012886](#); Symbol: [ER_IB_MSG_1061](#); SQLSTATE: [HY000](#)

Message: Cannot create %s

[ER_IB_MSG_1061](#) was added in 8.0.11.

- Error number: [MY-012887](#); Symbol: [ER_IB_MSG_1062](#); SQLSTATE: [HY000](#)

Message: Setting log file %s size to %llu MB. Progress : %u%%

[ER_IB_MSG_1062](#) was added in 8.0.11.

- Error number: [MY-012888](#); Symbol: [ER_IB_MSG_1063](#); SQLSTATE: [HY000](#)

Message: Cannot set log file %s to size %llu MB

[ER_IB_MSG_1063](#) was added in 8.0.11.

- Error number: [MY-012889](#); Symbol: [ER_IB_MSG_1064](#); SQLSTATE: [HY000](#)

Message: Cannot create log files in read-only mode

[ER_IB_MSG_1064](#) was added in 8.0.11.

-
- Error number: [MY-012890](#); Symbol: [ER_IB_MSG_1065](#); SQLSTATE: [HY000](#)
Message: Redo log encryption is enabled, but the keyring is not loaded.
[ER_IB_MSG_1065](#) was added in 8.0.11.
 - Error number: [MY-012891](#); Symbol: [ER_IB_MSG_1066](#); SQLSTATE: [HY000](#)
Message: Cannot create file for log file %s.
[ER_IB_MSG_1066](#) was added in 8.0.11.
 - Error number: [MY-012892](#); Symbol: [ER_IB_MSG_1067](#); SQLSTATE: [HY000](#)
Message: Renaming log file %s to %s
[ER_IB_MSG_1067](#) was added in 8.0.11.
 - Error number: [MY-012893](#); Symbol: [ER_IB_MSG_1068](#); SQLSTATE: [HY000](#)
Message: New log files created, LSN=%lu
[ER_IB_MSG_1068](#) was added in 8.0.11.
 - Error number: [MY-012894](#); Symbol: [ER_IB_MSG_1069](#); SQLSTATE: [HY000](#)
Message: Unable to open '%s'.
[ER_IB_MSG_1069](#) was added in 8.0.11.
 - Error number: [MY-012895](#); Symbol: [ER_IB_MSG_1070](#); SQLSTATE: [HY000](#)
Message: Cannot create construction log file '%s' for undo tablespace '%s'.
[ER_IB_MSG_1070](#) was added in 8.0.11.
 - Error number: [MY-012896](#); Symbol: [ER_IB_MSG_1071](#); SQLSTATE: [HY000](#)
Message: Creating UNDO Tablespace %s
[ER_IB_MSG_1071](#) was added in 8.0.11.
 - Error number: [MY-012897](#); Symbol: [ER_IB_MSG_1072](#); SQLSTATE: [HY000](#)
Message: Setting file %s size to %lu MB
[ER_IB_MSG_1072](#) was added in 8.0.11.
 - Error number: [MY-012898](#); Symbol: [ER_IB_MSG_1073](#); SQLSTATE: [HY000](#)
Message: Physically writing the file full
[ER_IB_MSG_1073](#) was added in 8.0.11.
 - Error number: [MY-012899](#); Symbol: [ER_IB_MSG_1074](#); SQLSTATE: [HY000](#)
Message: Error in creating %s: probably out of disk space
[ER_IB_MSG_1074](#) was added in 8.0.11.
 - Error number: [MY-012900](#); Symbol: [ER_IB_MSG_1075](#); SQLSTATE: [HY000](#)
Message: Can't set encryption metadata for space %s
[ER_IB_MSG_1075](#) was added in 8.0.11.

- Error number: [MY-012901](#); Symbol: [ER_IB_MSG_1076](#); SQLSTATE: [HY000](#)

Message: Cannot read first page of '%s' - %s
[ER_IB_MSG_1076](#) was added in 8.0.11.
- Error number: [MY-012902](#); Symbol: [ER_IB_MSG_1077](#); SQLSTATE: [HY000](#)

Message: Undo tablespace number %lu was being truncated when mysqld quit.
[ER_IB_MSG_1077](#) was added in 8.0.11.
- Error number: [MY-012903](#); Symbol: [ER_IB_MSG_1078](#); SQLSTATE: [HY000](#)

Message: Cannot recover a truncated undo tablespace in read-only mode
[ER_IB_MSG_1078](#) was added in 8.0.11.
- Error number: [MY-012904](#); Symbol: [ER_IB_MSG_1079](#); SQLSTATE: [HY000](#)

Message: Reconstructing undo tablespace number %lu.
[ER_IB_MSG_1079](#) was added in 8.0.11.
- Error number: [MY-012905](#); Symbol: [ER_IB_MSG_1080](#); SQLSTATE: [HY000](#)

Message: Cannot create %s because %s already uses Space ID=%lu! Did you change innodb_undo_directory?
[ER_IB_MSG_1080](#) was added in 8.0.11.
- Error number: [MY-012906](#); Symbol: [ER_IB_MSG_1081](#); SQLSTATE: [HY000](#)

Message: UNDO tablespace %s must be %s
[ER_IB_MSG_1081](#) was added in 8.0.11.
- Error number: [MY-012907](#); Symbol: [ER_IB_MSG_1082](#); SQLSTATE: [HY000](#)

Message: Error creating file for %s
[ER_IB_MSG_1082](#) was added in 8.0.11.
- Error number: [MY-012908](#); Symbol: [ER_IB_MSG_1083](#); SQLSTATE: [HY000](#)

Message: Error reading encryption for %s
[ER_IB_MSG_1083](#) was added in 8.0.11.
- Error number: [MY-012909](#); Symbol: [ER_IB_MSG_1084](#); SQLSTATE: [HY000](#)

Message: Unable to open undo tablespace number %lu
[ER_IB_MSG_1084](#) was added in 8.0.11, removed after 8.0.20.
- Error number: [MY-012909](#); Symbol: [ER_IB_MSG_CANNOT_OPEN_57_UNDO](#); SQLSTATE: [HY000](#)

Message: Unable to open undo tablespace number %lu
[ER_IB_MSG_CANNOT_OPEN_57_UNDO](#) was added in 8.0.21.
- Error number: [MY-012910](#); Symbol: [ER_IB_MSG_1085](#); SQLSTATE: [HY000](#)

Message: Opened %llu existing undo tablespaces.

[ER_IB_MSG_1085](#) was added in 8.0.11.

- Error number: [MY-012911](#); Symbol: [ER_IB_MSG_1086](#); SQLSTATE: [HY000](#)

Message: Cannot create undo tablespaces since innodb_%s has been set. Using %llu existing undo tablespaces.

[ER_IB_MSG_1086](#) was added in 8.0.11.

- Error number: [MY-012912](#); Symbol: [ER_IB_MSG_1087](#); SQLSTATE: [HY000](#)

Message: Cannot continue InnoDB startup in '%s' mode because there are no existing undo tablespaces found.

[ER_IB_MSG_1087](#) was added in 8.0.11.

- Error number: [MY-012913](#); Symbol: [ER_IB_MSG_1088](#); SQLSTATE: [HY000](#)

Message: Could not create undo tablespace '%s'.

[ER_IB_MSG_1088](#) was added in 8.0.11.

- Error number: [MY-012914](#); Symbol: [ER_IB_MSG_1089](#); SQLSTATE: [HY000](#)

Message: Error %d - %s - opening newly created undo tablespace '%s'.

[ER_IB_MSG_1089](#) was added in 8.0.11.

- Error number: [MY-012915](#); Symbol: [ER_IB_MSG_1090](#); SQLSTATE: [HY000](#)

Message: Created %llu undo tablespaces.

[ER_IB_MSG_1090](#) was added in 8.0.11.

- Error number: [MY-012916](#); Symbol: [ER_IB_MSG_1091](#); SQLSTATE: [HY000](#)

Message: Unable to create encrypted undo tablespace number %lu. please check if the keyring is initialized correctly

[ER_IB_MSG_1091](#) was added in 8.0.11.

- Error number: [MY-012917](#); Symbol: [ER_IB_MSG_1092](#); SQLSTATE: [HY000](#)

Message: Encryption is enabled for undo tablespace number %lu.

[ER_IB_MSG_1092](#) was added in 8.0.11.

- Error number: [MY-012918](#); Symbol: [ER_IB_MSG_1093](#); SQLSTATE: [HY000](#)

Message: Unable to initialize the header page in undo tablespace number %lu.

[ER_IB_MSG_1093](#) was added in 8.0.11.

- Error number: [MY-012919](#); Symbol: [ER_IB_MSG_1094](#); SQLSTATE: [HY000](#)

Message: Cannot delete old undo tablespaces because they contain undo logs for XA PREPARED transactions.

[ER_IB_MSG_1094](#) was added in 8.0.11.

-
- Error number: [MY-012920](#); Symbol: [ER_IB_MSG_1095](#); SQLSTATE: [HY000](#)

Message: Upgrading %zu existing undo tablespaces that were tracked in the system tablespace to %lu new independent undo tablespaces.

[ER_IB_MSG_1095](#) was added in 8.0.11.

- Error number: [MY-012921](#); Symbol: [ER_IB_MSG_1096](#); SQLSTATE: [HY000](#)

Message: Deleting %lu new independent undo tablespaces that we just created.

[ER_IB_MSG_1096](#) was added in 8.0.11.

- Error number: [MY-012922](#); Symbol: [ER_IB_MSG_1097](#); SQLSTATE: [HY000](#)

Message: Waiting for purge to start

[ER_IB_MSG_1097](#) was added in 8.0.11.

- Error number: [MY-012923](#); Symbol: [ER_IB_MSG_1098](#); SQLSTATE: [HY000](#)

Message: Creating shared tablespace for temporary tables

[ER_IB_MSG_1098](#) was added in 8.0.11.

- Error number: [MY-012924](#); Symbol: [ER_IB_MSG_1099](#); SQLSTATE: [HY000](#)

Message: The %s data file must be writable!

[ER_IB_MSG_1099](#) was added in 8.0.11.

- Error number: [MY-012925](#); Symbol: [ER_IB_MSG_1100](#); SQLSTATE: [HY000](#)

Message: Could not create the shared %s.

[ER_IB_MSG_1100](#) was added in 8.0.11.

- Error number: [MY-012926](#); Symbol: [ER_IB_MSG_1101](#); SQLSTATE: [HY000](#)

Message: Unable to create the shared %s.

[ER_IB_MSG_1101](#) was added in 8.0.11.

- Error number: [MY-012927](#); Symbol: [ER_IB_MSG_1102](#); SQLSTATE: [HY000](#)

Message: The %s data file cannot be re-opened after check_file_spec() succeeded!

[ER_IB_MSG_1102](#) was added in 8.0.11.

- Error number: [MY-012928](#); Symbol: [ER_IB_MSG_1103](#); SQLSTATE: [HY000](#)

Message: %d threads created by InnoDB had not exited at shutdown!

[ER_IB_MSG_1103](#) was added in 8.0.11.

- Error number: [MY-012929](#); Symbol: [ER_IB_MSG_1104](#); SQLSTATE: [HY000](#)

Message: InnoDB Database creation was aborted %s with error %s. You may need to delete the ibdata1 file before trying to start up again.

[ER_IB_MSG_1104](#) was added in 8.0.11.

-
- Error number: [MY-012930](#); Symbol: [ER_IB_MSG_1105](#); SQLSTATE: [HY000](#)
Message: Plugin initialization aborted %s with error %s.
[ER_IB_MSG_1105](#) was added in 8.0.11.
 - Error number: [MY-012931](#); Symbol: [ER_IB_MSG_1106](#); SQLSTATE: [HY000](#)
Message: Waiting for %llu buffer page I/Os to complete
[ER_IB_MSG_1106](#) was added in 8.0.11.
 - Error number: [MY-012932](#); Symbol: [ER_IB_MSG_1107](#); SQLSTATE: [HY000](#)
Message: PUNCH HOLE support available
[ER_IB_MSG_1107](#) was added in 8.0.11.
 - Error number: [MY-012933](#); Symbol: [ER_IB_MSG_1108](#); SQLSTATE: [HY000](#)
Message: PUNCH HOLE support not available
[ER_IB_MSG_1108](#) was added in 8.0.11.
 - Error number: [MY-012934](#); Symbol: [ER_IB_MSG_1109](#); SQLSTATE: [HY000](#)
Message: Size of InnoDB's uint is %zu but size of void* is %zu. The sizes should be the same so that on a 64-bit platforms you can allocate more than 4 GB of memory.
[ER_IB_MSG_1109](#) was added in 8.0.11.
 - Error number: [MY-012935](#); Symbol: [ER_IB_MSG_1110](#); SQLSTATE: [HY000](#)
Message: Database upgrade cannot be accomplished in read-only mode.
[ER_IB_MSG_1110](#) was added in 8.0.11.
 - Error number: [MY-012936](#); Symbol: [ER_IB_MSG_1111](#); SQLSTATE: [HY000](#)
Message: Database upgrade cannot be accomplished with innodb_force_recovery > 0
[ER_IB_MSG_1111](#) was added in 8.0.11.
 - Error number: [MY-012937](#); Symbol: [ER_IB_MSG_1112](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1112](#) was added in 8.0.11.
 - Error number: [MY-012938](#); Symbol: [ER_IB_MSG_1113](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1113](#) was added in 8.0.11.
 - Error number: [MY-012939](#); Symbol: [ER_IB_MSG_1114](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1114](#) was added in 8.0.11.
 - Error number: [MY-012940](#); Symbol: [ER_IB_MSG_1115](#); SQLSTATE: [HY000](#)
Message: %s

[ER_IB_MSG_1115](#) was added in 8.0.11.

- Error number: [MY-012941](#); Symbol: [ER_IB_MSG_1116](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1116](#) was added in 8.0.11.

- Error number: [MY-012942](#); Symbol: [ER_IB_MSG_1117](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1117](#) was added in 8.0.11.

- Error number: [MY-012943](#); Symbol: [ER_IB_MSG_1118](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1118](#) was added in 8.0.11, removed after 8.0.22.

- Error number: [MY-012944](#); Symbol: [ER_IB_MSG_1119](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1119](#) was added in 8.0.11.

- Error number: [MY-012945](#); Symbol: [ER_IB_MSG_1120](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1120](#) was added in 8.0.11.

- Error number: [MY-012946](#); Symbol: [ER_IB_MSG_1121](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1121](#) was added in 8.0.11.

- Error number: [MY-012947](#); Symbol: [ER_IB_MSG_1122](#); SQLSTATE: [HY000](#)

Message: MySQL was built without a memory barrier capability on this architecture, which might allow a mutex/rw_lock violation under high thread concurrency. This may cause a hang.

[ER_IB_MSG_1122](#) was added in 8.0.11.

- Error number: [MY-012948](#); Symbol: [ER_IB_MSG_1123](#); SQLSTATE: [HY000](#)

Message: Compressed tables use zlib %s

[ER_IB_MSG_1123](#) was added in 8.0.11.

- Error number: [MY-012949](#); Symbol: [ER_IB_MSG_1124](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1124](#) was added in 8.0.11.

- Error number: [MY-012950](#); Symbol: [ER_IB_MSG_1125](#); SQLSTATE: [HY000](#)

Message: Startup called second time during the process lifetime. In the MySQL Embedded Server Library you cannot call server_init() more than once during the process lifetime.

[ER_IB_MSG_1125](#) was added in 8.0.11.

-
- Error number: [MY-012951](#); Symbol: [ER_IB_MSG_1126](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1126](#) was added in 8.0.11.
 - Error number: [MY-012952](#); Symbol: [ER_IB_MSG_1127](#); SQLSTATE: HY000
Message: Unable to create monitor file %s: %s
[ER_IB_MSG_1127](#) was added in 8.0.11.
 - Error number: [MY-012953](#); Symbol: [ER_IB_MSG_1128](#); SQLSTATE: HY000
Message: Disabling background log and ibuf IO write threads.
[ER_IB_MSG_1128](#) was added in 8.0.11.
 - Error number: [MY-012954](#); Symbol: [ER_IB_MSG_1129](#); SQLSTATE: HY000
Message: Cannot initialize AIO sub-system
[ER_IB_MSG_1129](#) was added in 8.0.11.
 - Error number: [MY-012955](#); Symbol: [ER_IB_MSG_1130](#); SQLSTATE: HY000
Message: Initializing buffer pool, total size = %lf%c, instances = %lu, chunk size =%lf%c
[ER_IB_MSG_1130](#) was added in 8.0.11.
 - Error number: [MY-012956](#); Symbol: [ER_IB_MSG_1131](#); SQLSTATE: HY000
Message: Cannot allocate memory for the buffer pool
[ER_IB_MSG_1131](#) was added in 8.0.11.
 - Error number: [MY-012957](#); Symbol: [ER_IB_MSG_1132](#); SQLSTATE: HY000
Message: Completed initialization of buffer pool
[ER_IB_MSG_1132](#) was added in 8.0.11.
 - Error number: [MY-012958](#); Symbol: [ER_IB_MSG_1133](#); SQLSTATE: HY000
Message: Small buffer pool size (%lluM), the flst_validate() debug function can cause a deadlock if the buffer pool fills up.
[ER_IB_MSG_1133](#) was added in 8.0.11.
 - Error number: [MY-012959](#); Symbol: [ER_IB_MSG_1134](#); SQLSTATE: HY000
Message: Could not open or create the system tablespace. If you tried to add new data files to the system tablespace, and it failed here, you should now edit innodb_data_file_path in my.cnf back to what it was, and remove the new ibdata files InnoDB created in this failed attempt. InnoDB only wrote those files full of zeros, but did not yet use them in any way. But be careful: do not remove old data files which contain your precious data!
[ER_IB_MSG_1134](#) was added in 8.0.11.
 - Error number: [MY-012960](#); Symbol: [ER_IB_MSG_1135](#); SQLSTATE: HY000
Message: Cannot create log files because data files are corrupt or the database was not shut down cleanly after creating the data files.

[ER_IB_MSG_1135](#) was added in 8.0.11.

- Error number: [MY-012961](#); Symbol: [ER_IB_MSG_1136](#); SQLSTATE: [HY000](#)

Message: Only one log file found

[ER_IB_MSG_1136](#) was added in 8.0.11.

- Error number: [MY-012962](#); Symbol: [ER_IB_MSG_1137](#); SQLSTATE: [HY000](#)

Message: Log file %s size %llu is not a multiple of innodb_page_size

[ER_IB_MSG_1137](#) was added in 8.0.11.

- Error number: [MY-012963](#); Symbol: [ER_IB_MSG_1138](#); SQLSTATE: [HY000](#)

Message: Log file %s is of different size %llu bytes than other log files %llu bytes!

[ER_IB_MSG_1138](#) was added in 8.0.11.

- Error number: [MY-012964](#); Symbol: [ER_IB_MSG_1139](#); SQLSTATE: [HY000](#)

Message: Use --innodb-directories to find the tablespace files. If that fails then use --innodb-force-recovery=1 to ignore this and to permanently lose all changes to the missing tablespace(s)

[ER_IB_MSG_1139](#) was added in 8.0.11.

- Error number: [MY-012965](#); Symbol: [ER_IB_MSG_1140](#); SQLSTATE: [HY000](#)

Message: The log file may have been corrupt and it is possible that the log scan or parsing did not proceed far enough in recovery. Please run CHECK TABLE on your InnoDB tables to check that they are ok! It may be safest to recover your InnoDB database from a backup!

[ER_IB_MSG_1140](#) was added in 8.0.11.

- Error number: [MY-012966](#); Symbol: [ER_IB_MSG_1141](#); SQLSTATE: [HY000](#)

Message: Cannot resize log files in read-only mode.

[ER_IB_MSG_1141](#) was added in 8.0.11.

- Error number: [MY-012967](#); Symbol: [ER_IB_MSG_1142](#); SQLSTATE: [HY000](#)

Message: Cannot open DD tablespace.

[ER_IB_MSG_1142](#) was added in 8.0.11.

- Error number: [MY-012968](#); Symbol: [ER_IB_MSG_1143](#); SQLSTATE: [HY000](#)

Message: Starting to delete and rewrite log files.

[ER_IB_MSG_1143](#) was added in 8.0.11.

- Error number: [MY-012969](#); Symbol: [ER_IB_MSG_1144](#); SQLSTATE: [HY000](#)

Message: Undo from 5.7 found. It will be purged

[ER_IB_MSG_1144](#) was added in 8.0.11.

-
- Error number: [MY-012970](#); Symbol: [ER_IB_MSG_1145](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1145](#) was added in 8.0.11.
 - Error number: [MY-012971](#); Symbol: [ER_IB_MSG_1146](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1146](#) was added in 8.0.11.
 - Error number: [MY-012972](#); Symbol: [ER_IB_MSG_1147](#); SQLSTATE: HY000
Message: Tablespace size stored in header is %lu pages, but the sum of data file sizes is %lu pages
[ER_IB_MSG_1147](#) was added in 8.0.11.
 - Error number: [MY-012973](#); Symbol: [ER_IB_MSG_1148](#); SQLSTATE: HY000
Message: Cannot start InnoDB. The tail of the system tablespace is missing. Have you edited innodb_data_file_path in my.cnf in an inappropriate way, removing ibdata files from there? You can set innodb_force_recovery=1 in my.cnf to force a startup if you are trying to recover a badly corrupt database.
[ER_IB_MSG_1148](#) was added in 8.0.11.
 - Error number: [MY-012974](#); Symbol: [ER_IB_MSG_1149](#); SQLSTATE: HY000
Message: Tablespace size stored in header is %lu pages, but the sum of data file sizes is only %lu pages
[ER_IB_MSG_1149](#) was added in 8.0.11.
 - Error number: [MY-012975](#); Symbol: [ER_IB_MSG_1150](#); SQLSTATE: HY000
Message: Cannot start InnoDB. The tail of the system tablespace is missing. Have you edited innodb_data_file_path in my.cnf in an InnoDB: inappropriate way, removing ibdata files from there? You can set innodb_force_recovery=1 in my.cnf to force InnoDB: a startup if you are trying to recover a badly corrupt database.
[ER_IB_MSG_1150](#) was added in 8.0.11.
 - Error number: [MY-012976](#); Symbol: [ER_IB_MSG_1151](#); SQLSTATE: HY000
Message: %s started; log sequence number %llu
[ER_IB_MSG_1151](#) was added in 8.0.11.
 - Error number: [MY-012977](#); Symbol: [ER_IB_MSG_1152](#); SQLSTATE: HY000
Message: Waiting for purge to complete
[ER_IB_MSG_1152](#) was added in 8.0.11.
 - Error number: [MY-012978](#); Symbol: [ER_IB_MSG_1153](#); SQLSTATE: HY000
Message: Waiting for dict_stats_thread to exit
[ER_IB_MSG_1153](#) was added in 8.0.11, removed after 8.0.20.
 - Error number: [MY-012979](#); Symbol: [ER_IB_MSG_1154](#); SQLSTATE: HY000
Message: Query counter shows %lld queries still inside InnoDB at shutdown

[ER_IB_MSG_1154](#) was added in 8.0.11.

- Error number: [MY-012980](#); Symbol: [ER_IB_MSG_1155](#); SQLSTATE: [HY000](#)

Message: Shutdown completed; log sequence number %llu

[ER_IB_MSG_1155](#) was added in 8.0.11.

- Error number: [MY-012981](#); Symbol: [ER_IB_MSG_1156](#); SQLSTATE: [HY000](#)

Message: Cannot continue operation.

[ER_IB_MSG_1156](#) was added in 8.0.11.

- Error number: [MY-012982](#); Symbol: [ER_IB_MSG_1157](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1157](#) was added in 8.0.11.

- Error number: [MY-012983](#); Symbol: [ER_IB_MSG_1158](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1158](#) was added in 8.0.11.

- Error number: [MY-012984](#); Symbol: [ER_IB_MSG_1159](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1159](#) was added in 8.0.11.

- Error number: [MY-012985](#); Symbol: [ER_IB_MSG_1160](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1160](#) was added in 8.0.11.

- Error number: [MY-012986](#); Symbol: [ER_IB_MSG_1161](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1161](#) was added in 8.0.11.

- Error number: [MY-012987](#); Symbol: [ER_IB_MSG_1162](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1162](#) was added in 8.0.11.

- Error number: [MY-012988](#); Symbol: [ER_IB_MSG_1163](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1163](#) was added in 8.0.11.

- Error number: [MY-012989](#); Symbol: [ER_IB_MSG_1164](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1164](#) was added in 8.0.11.

- Error number: [MY-012990](#); Symbol: [ER_IB_MSG_1165](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1165](#) was added in 8.0.11.

- Error number: [MY-012991](#); Symbol: [ER_IB_MSG_1166](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1166](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012991](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_FAIL_TO_READ_LOG_FILE](#); SQLSTATE: [HY000](#)

Message: Unable to read the existing undo truncate log file '%s'. The error is %s

[ER_IB_MSG_UNDO_TRUNCATE_FAIL_TO_READ_LOG_FILE](#) was added in 8.0.21.

- Error number: [MY-012992](#); Symbol: [ER_IB_MSG_1167](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1167](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012992](#); Symbol: [ER_IB_MSG_UNDO_MARKED_FOR_TRUNCATE](#); SQLSTATE: [HY000](#)

Message: Undo tablespace %s is marked for truncate

[ER_IB_MSG_UNDO_MARKED_FOR_TRUNCATE](#) was added in 8.0.21.

- Error number: [MY-012993](#); Symbol: [ER_IB_MSG_1168](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1168](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012994](#); Symbol: [ER_IB_MSG_1169](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1169](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012994](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_START](#); SQLSTATE: [HY000](#)

Message: Truncating UNDO tablespace %s

[ER_IB_MSG_UNDO_TRUNCATE_START](#) was added in 8.0.21.

- Error number: [MY-012995](#); Symbol: [ER_IB_MSG_1170](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1170](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012996](#); Symbol: [ER_IB_MSG_1171](#); SQLSTATE: [HY000](#)

Message: Cannot create truncate log for undo tablespace '%s'.

[ER_IB_MSG_1171](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012996](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_LOG_CREATE](#); SQLSTATE: [HY000](#)

Message: Cannot create truncate log for undo tablespace '%s'.

[ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_LOG_CREATE](#) was added in 8.0.21.

- Error number: [MY-012997](#); Symbol: [ER_IB_MSG_1172](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1172](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012998](#); Symbol: [ER_IB_MSG_1173](#); SQLSTATE: [HY000](#)

Message: Failed to truncate undo tablespace '%s'.

[ER_IB_MSG_1173](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012998](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_FAILURE](#); SQLSTATE: [HY000](#)

Message: Failed to truncate undo tablespace '%s'.

[ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_FAILURE](#) was added in 8.0.21.

- Error number: [MY-012999](#); Symbol: [ER_IB_MSG_1174](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1174](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-013000](#); Symbol: [ER_IB_MSG_1175](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1175](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-013000](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_COMPLETE](#); SQLSTATE: [HY000](#)

Message: Completed truncate of undo tablespace %s.

[ER_IB_MSG_UNDO_TRUNCATE_COMPLETE](#) was added in 8.0.21.

- Error number: [MY-013001](#); Symbol: [ER_IB_MSG_1176](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1176](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-013002](#); Symbol: [ER_IB_MSG_1177](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1177](#) was added in 8.0.11.

- Error number: [MY-013003](#); Symbol: [ER_IB_MSG_1178](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1178](#) was added in 8.0.11.

- Error number: [MY-013004](#); Symbol: [ER_IB_MSG_1179](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1179](#) was added in 8.0.11.

- Error number: [MY-013005](#); Symbol: [ER_IB_MSG_1180](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1180](#) was added in 8.0.11.

- Error number: [MY-013006](#); Symbol: [ER_IB_MSG_1181](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1181](#) was added in 8.0.11.

- Error number: [MY-013007](#); Symbol: [ER_IB_MSG_1182](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1182](#) was added in 8.0.11.

- Error number: [MY-013008](#); Symbol: [ER_IB_MSG_1183](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1183](#) was added in 8.0.11.

- Error number: [MY-013009](#); Symbol: [ER_IB_MSG_1184](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1184](#) was added in 8.0.11.

- Error number: [MY-013010](#); Symbol: [ER_IB_MSG_1185](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1185](#) was added in 8.0.11.

- Error number: [MY-013011](#); Symbol: [ER_IB_MSG_1186](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1186](#) was added in 8.0.11.

- Error number: [MY-013012](#); Symbol: [ER_IB_MSG_1187](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1187](#) was added in 8.0.11.

- Error number: [MY-013013](#); Symbol: [ER_IB_MSG_1188](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1188](#) was added in 8.0.11.

- Error number: [MY-013014](#); Symbol: [ER_IB_MSG_1189](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1189](#) was added in 8.0.11.

- Error number: [MY-013015](#); Symbol: [ER_IB_MSG_1190](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_1190](#) was added in 8.0.11, removed after 8.0.20.
- Error number: [MY-013015](#); Symbol: [ER_IB_MSG_TRX_RECOVERY_ROLLBACK_COMPLETED](#); SQLSTATE: [HY000](#)

Message: Rollback of non-prepared transactions completed
[ER_IB_MSG_TRX_RECOVERY_ROLLBACK_COMPLETED](#) was added in 8.0.21.
- Error number: [MY-013016](#); Symbol: [ER_IB_MSG_1191](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_1191](#) was added in 8.0.11.
- Error number: [MY-013017](#); Symbol: [ER_IB_MSG_1192](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_1192](#) was added in 8.0.11.
- Error number: [MY-013018](#); Symbol: [ER_IB_MSG_1193](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_1193](#) was added in 8.0.11.
- Error number: [MY-013019](#); Symbol: [ER_IB_MSG_1194](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_1194](#) was added in 8.0.11.
- Error number: [MY-013020](#); Symbol: [ER_IB_MSG_1195](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_1195](#) was added in 8.0.11.
- Error number: [MY-013021](#); Symbol: [ER_IB_MSG_1196](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_1196](#) was added in 8.0.11.
- Error number: [MY-013022](#); Symbol: [ER_IB_MSG_1197](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_1197](#) was added in 8.0.11.
- Error number: [MY-013023](#); Symbol: [ER_IB_MSG_1198](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_1198](#) was added in 8.0.11.
- Error number: [MY-013024](#); Symbol: [ER_IB_MSG_1199](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1199](#) was added in 8.0.11.

- Error number: [MY-013025](#); Symbol: [ER_IB_MSG_1200](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_1200](#) was added in 8.0.11.

- Error number: [MY-013026](#); Symbol: [ER_IB_MSG_1201](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_1201](#) was added in 8.0.11.

- Error number: [MY-013027](#); Symbol: [ER_IB_MSG_1202](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_1202](#) was added in 8.0.11.

- Error number: [MY-013028](#); Symbol: [ER_IB_MSG_1203](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_1203](#) was added in 8.0.11.

- Error number: [MY-013029](#); Symbol: [ER_IB_MSG_1204](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_1204](#) was added in 8.0.11.

- Error number: [MY-013030](#); Symbol: [ER_IB_MSG_1205](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_1205](#) was added in 8.0.11.

- Error number: [MY-013031](#); Symbol: [ER_IB_MSG_1206](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_1206](#) was added in 8.0.11.

- Error number: [MY-013032](#); Symbol: [ER_IB_MSG_1207](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_1207](#) was added in 8.0.11.

- Error number: [MY-013033](#); Symbol: [ER_IB_MSG_1208](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_1208](#) was added in 8.0.11.

- Error number: [MY-013034](#); Symbol: [ER_IB_MSG_1209](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_1209](#) was added in 8.0.11.

- Error number: [MY-013035](#); Symbol: [ER_IB_MSG_1210](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_1210](#) was added in 8.0.11.

- Error number: [MY-013036](#); Symbol: [ER_IB_MSG_1211](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1211](#) was added in 8.0.11.

- Error number: [MY-013037](#); Symbol: [ER_IB_MSG_1212](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1212](#) was added in 8.0.11.

- Error number: [MY-013038](#); Symbol: [ER_IB_MSG_1213](#); SQLSTATE: [HY000](#)

Message: gettimeofday() failed: %s

[ER_IB_MSG_1213](#) was added in 8.0.11.

- Error number: [MY-013039](#); Symbol: [ER_IB_MSG_1214](#); SQLSTATE: [HY000](#)

Message: Can't create UNDO tablespace %s %s

[ER_IB_MSG_1214](#) was added in 8.0.11.

- Error number: [MY-013040](#); Symbol: [ER_IB_MSG_1215](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1215](#) was added in 8.0.11.

- Error number: [MY-013041](#); Symbol: [ER_IB_MSG_1216](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1216](#) was added in 8.0.11.

- Error number: [MY-013042](#); Symbol: [ER_IB_MSG_1217](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1217](#) was added in 8.0.11.

- Error number: [MY-013043](#); Symbol: [ER_IB_MSG_1218](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1218](#) was added in 8.0.11.

- Error number: [MY-013044](#); Symbol: [ER_IB_MSG_1219](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1219](#) was added in 8.0.11.

- Error number: [MY-013045](#); Symbol: [ER_IB_MSG_1220](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1220](#) was added in 8.0.11.

-
- Error number: [MY-013046](#); Symbol: [ER_IB_MSG_1221](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1221](#) was added in 8.0.11.
 - Error number: [MY-013047](#); Symbol: [ER_IB_MSG_1222](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1222](#) was added in 8.0.11.
 - Error number: [MY-013048](#); Symbol: [ER_IB_MSG_1223](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1223](#) was added in 8.0.11.
 - Error number: [MY-013049](#); Symbol: [ER_IB_MSG_1224](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1224](#) was added in 8.0.11.
 - Error number: [MY-013050](#); Symbol: [ER_IB_MSG_1225](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1225](#) was added in 8.0.11.
 - Error number: [MY-013051](#); Symbol: [ER_IB_MSG_1226](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1226](#) was added in 8.0.11.
 - Error number: [MY-013052](#); Symbol: [ER_IB_MSG_1227](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1227](#) was added in 8.0.11.
 - Error number: [MY-013053](#); Symbol: [ER_IB_MSG_1228](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1228](#) was added in 8.0.11.
 - Error number: [MY-013054](#); Symbol: [ER_IB_MSG_1229](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1229](#) was added in 8.0.11.
 - Error number: [MY-013055](#); Symbol: [ER_IB_MSG_1230](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1230](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-013056](#); Symbol: [ER_IB_MSG_1231](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_1231](#) was added in 8.0.11.

-
- Error number: [MY-013057](#); Symbol: [ER_IB_MSG_1232](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_1232](#) was added in 8.0.11.
 - Error number: [MY-013058](#); Symbol: [ER_IB_MSG_1233](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_1233](#) was added in 8.0.11.
 - Error number: [MY-013059](#); Symbol: [ER_IB_MSG_1234](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_1234](#) was added in 8.0.11.
 - Error number: [MY-013060](#); Symbol: [ER_IB_MSG_1235](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_1235](#) was added in 8.0.11.
 - Error number: [MY-013061](#); Symbol: [ER_IB_MSG_1236](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_1236](#) was added in 8.0.11.
 - Error number: [MY-013062](#); Symbol: [ER_IB_MSG_1237](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_1237](#) was added in 8.0.11.
 - Error number: [MY-013063](#); Symbol: [ER_IB_MSG_1238](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_1238](#) was added in 8.0.11.
 - Error number: [MY-013064](#); Symbol: [ER_IB_MSG_1239](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_1239](#) was added in 8.0.11.
 - Error number: [MY-013065](#); Symbol: [ER_IB_MSG_1240](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_1240](#) was added in 8.0.11.
 - Error number: [MY-013066](#); Symbol: [ER_IB_MSG_1241](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_1241](#) was added in 8.0.11.
 - Error number: [MY-013067](#); Symbol: [ER_IB_MSG_1242](#); SQLSTATE: [HY000](#)

Message: Can't set redo log tablespace to be encrypted in read-only mode.
[ER_IB_MSG_1242](#) was added in 8.0.11.

-
- Error number: [MY-013068](#); Symbol: [ER_IB_MSG_1243](#); SQLSTATE: HY000
Message: Can't set redo log tablespace to be encrypted.
[ER_IB_MSG_1243](#) was added in 8.0.11.
 - Error number: [MY-013069](#); Symbol: [ER_IB_MSG_1244](#); SQLSTATE: HY000
Message: Can't set redo log tablespace to be encrypted.
[ER_IB_MSG_1244](#) was added in 8.0.11.
 - Error number: [MY-013070](#); Symbol: [ER_IB_MSG_1245](#); SQLSTATE: HY000
Message: Redo log encryption is enabled.
[ER_IB_MSG_1245](#) was added in 8.0.11.
 - Error number: [MY-013071](#); Symbol: [ER_IB_MSG_1246](#); SQLSTATE: HY000
Message: Waiting for archiver to finish archiving page and log
[ER_IB_MSG_1246](#) was added in 8.0.11.
 - Error number: [MY-013072](#); Symbol: [ER_IB_MSG_1247](#); SQLSTATE: HY000
Message: Starting shutdown...
[ER_IB_MSG_1247](#) was added in 8.0.11.
 - Error number: [MY-013073](#); Symbol: [ER_IB_MSG_1248](#); SQLSTATE: HY000
Message: Waiting for %s to exit.
[ER_IB_MSG_1248](#) was added in 8.0.11.
 - Error number: [MY-013074](#); Symbol: [ER_IB_MSG_1249](#); SQLSTATE: HY000
Message: Waiting for rollback of %zu recovered transactions, before shutdown.
[ER_IB_MSG_1249](#) was added in 8.0.11.
 - Error number: [MY-013075](#); Symbol: [ER_IB_MSG_1250](#); SQLSTATE: HY000
Message: Waiting for master thread to be suspended.
[ER_IB_MSG_1250](#) was added in 8.0.11.
 - Error number: [MY-013076](#); Symbol: [ER_IB_MSG_1251](#); SQLSTATE: HY000
Message: Waiting for page_cleaner to finish flushing of buffer pool.
[ER_IB_MSG_1251](#) was added in 8.0.11.
 - Error number: [MY-013077](#); Symbol: [ER_IB_MSG_1252](#); SQLSTATE: HY000
Message: Waiting for %lu buffer page I/Os to complete.
[ER_IB_MSG_1252](#) was added in 8.0.11.
 - Error number: [MY-013078](#); Symbol: [ER_IB_MSG_1253](#); SQLSTATE: HY000
Message: MySQL has requested a very fast shutdown without flushing the InnoDB buffer pool to data files. At the next mysqld startup InnoDB will do a crash recovery!

`ER_IB_MSG_1253` was added in 8.0.11.

- Error number: `MY-013079`; Symbol: `ER_IB_MSG_1254`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1254` was added in 8.0.11, removed after 8.0.13.

- Error number: `MY-013080`; Symbol: `ER_IB_MSG_1255`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1255` was added in 8.0.11.

- Error number: `MY-013081`; Symbol: `ER_IB_MSG_1256`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1256` was added in 8.0.11.

- Error number: `MY-013082`; Symbol: `ER_IB_MSG_1257`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1257` was added in 8.0.11.

- Error number: `MY-013083`; Symbol: `ER_IB_MSG_1258`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1258` was added in 8.0.11.

- Error number: `MY-013084`; Symbol: `ER_IB_MSG_1259`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1259` was added in 8.0.11.

- Error number: `MY-013085`; Symbol: `ER_IB_MSG_1260`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1260` was added in 8.0.11.

- Error number: `MY-013086`; Symbol: `ER_IB_MSG_1261`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1261` was added in 8.0.11.

- Error number: `MY-013087`; Symbol: `ER_IB_MSG_1262`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1262` was added in 8.0.11.

- Error number: `MY-013088`; Symbol: `ER_IB_MSG_1263`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1263` was added in 8.0.11.

- Error number: `MY-013089`; Symbol: `ER_IB_MSG_1264`; SQLSTATE: `HY000`

Message: %s

[ER_IB_MSG_1264](#) was added in 8.0.11.

- Error number: [MY-013090](#); Symbol: [ER_IB_MSG_1265](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_1265](#) was added in 8.0.11.

- Error number: [MY-013091](#); Symbol: [ER_IB_MSG_1266](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_1266](#) was added in 8.0.11.

- Error number: [MY-013092](#); Symbol: [ER_IB_MSG_1267](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_1267](#) was added in 8.0.11.

- Error number: [MY-013093](#); Symbol: [ER_IB_MSG_1268](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_1268](#) was added in 8.0.11.

- Error number: [MY-013094](#); Symbol: [ER_IB_MSG_1269](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_1269](#) was added in 8.0.11.

- Error number: [MY-013095](#); Symbol: [ER_IB_MSG_1270](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_1270](#) was added in 8.0.11.

- Error number: [MY-013096](#); Symbol: [ER_RPL_SLAVE_SQL_THREAD_STOP_CMD_EXEC_TIMEOUT](#); SQLSTATE: HY000

Message: STOP SLAVE command execution is incomplete: Slave SQL thread got the stop signal, thread is busy, SQL thread will stop once the current task is complete.

[ER_RPL_SLAVE_SQL_THREAD_STOP_CMD_EXEC_TIMEOUT](#) was added in 8.0.11.

- Error number: [MY-013097](#); Symbol: [ER_RPL_SLAVE_IO_THREAD_STOP_CMD_EXEC_TIMEOUT](#); SQLSTATE: HY000

Message: STOP SLAVE command execution is incomplete: Slave IO thread got the stop signal, thread is busy, IO thread will stop once the current task is complete.

[ER_RPL_SLAVE_IO_THREAD_STOP_CMD_EXEC_TIMEOUT](#) was added in 8.0.11.

- Error number: [MY-013098](#); Symbol: [ER_RPL_GTID_UNSAFE_STMT_ON_NON_TRANS_TABLE](#); SQLSTATE: HY000

Message: Statement violates GTID consistency: Updates to non-transactional tables can only be done in either autocommitted statements or single-statement transactions, and never in the same statement as updates to transactional tables.

`ER_RPL_GTID_UNSAFE_STMT_ON_NON_TRANS_TABLE` was added in 8.0.11.

- Error number: `MY-013099`; Symbol: `ER_RPL_GTID_UNSAFE_STMT_CREATE_SELECT`; SQLSTATE: `HY000`

Message: Statement violates GTID consistency: CREATE TABLE ... SELECT.

`ER_RPL_GTID_UNSAFE_STMT_CREATE_SELECT` was added in 8.0.11.

- Error number: `MY-013100`; Symbol: `ER_RPL_GTID_UNSAFE_STMT_ON_TEMPORARY_TABLE`; SQLSTATE: `HY000`

Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE can only be executed outside transactional context. These statements are also not allowed in a function or trigger because functions and triggers are also considered to be multi-statement transactions.

`ER_RPL_GTID_UNSAFE_STMT_ON_TEMPORARY_TABLE` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-013101`; Symbol: `ER_BINLOG_ROW_VALUE_OPTION_IGNORED`; SQLSTATE: `HY000`

Message: When %s, the option binlog_row_value_options=%s will be ignored and updates will be written in full format to binary log.

`ER_BINLOG_ROW_VALUE_OPTION_IGNORED` was added in 8.0.11.

- Error number: `MY-013102`; Symbol: `ER_BINLOG_USE_V1_ROW_EVENTS_IGNORED`; SQLSTATE: `HY000`

Message: When %s, the option log_bin_use_v1_row_events=1 will be ignored and row events will be written in new format to binary log.

`ER_BINLOG_USE_V1_ROW_EVENTS_IGNORED` was added in 8.0.11.

- Error number: `MY-013103`; Symbol: `ER_BINLOG_ROW_VALUE_OPTION_USED_ONLY_FOR_AFTER_IMAGES`; SQLSTATE: `HY000`

Message: When %s, the option binlog_row_value_options=%s will be used only for the after-image. Full values will be written in the before-image, so the saving in disk space due to binlog_row_value_options is limited to less than 50%.

`ER_BINLOG_ROW_VALUE_OPTION_USED_ONLY_FOR_AFTER_IMAGES` was added in 8.0.11.

- Error number: `MY-013104`; Symbol: `ER_CONNECTION_ABORTED`; SQLSTATE: `HY000`

Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s).

`ER_CONNECTION_ABORTED` was added in 8.0.11.

- Error number: `MY-013105`; Symbol: `ER_NORMAL_SERVER_SHUTDOWN`; SQLSTATE: `HY000`

Message: %s: Normal shutdown.

`ER_NORMAL_SERVER_SHUTDOWN` was added in 8.0.11.

- Error number: `MY-013106`; Symbol: `ER_KEYRING_MIGRATE_FAILED`; SQLSTATE: `HY000`

Message: Can not perform keyring migration : %s.

`ER_KEYRING_MIGRATE_FAILED` was added in 8.0.11.

-
- Error number: [MY-013107](#); Symbol: [ER_GRP_RPL_LOWER_CASE_TABLE_NAMES_DIFF_FROM_GRP](#); SQLSTATE: [HY000](#)

Message: The member is configured with a lower_case_table_names option value '%u' different from the group '%u'. The member will now exit the group. If there is existing data on member, it may be incompatible with group if it was created with a lower_case_table_names value different from the group.

[ER_GRP_RPL_LOWER_CASE_TABLE_NAMES_DIFF_FROM_GRP](#) was added in 8.0.11.
 - Error number: [MY-013108](#); Symbol: [ER_OOM_SAVE_GTIDS](#); SQLSTATE: [HY000](#)

Message: An out-of-memory error occurred while saving the set of GTIDs from the last binary log into the mysql.gtid_executed table

[ER_OOM_SAVE_GTIDS](#) was added in 8.0.11.
 - Error number: [MY-013109](#); Symbol: [ER_LCTN_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: The lower_case_table_names setting for the data dictionary was not found. Starting the server using lower_case_table_names = '%u'.

[ER_LCTN_NOT_FOUND](#) was added in 8.0.11.
 - Error number: [MY-013111](#); Symbol: [ER_COMPONENT_FILTER_WRONG_VALUE](#); SQLSTATE: [HY000](#)

Message: Variable '%s' can't be set to the value of '%s'

[ER_COMPONENT_FILTER_WRONG_VALUE](#) was added in 8.0.11.
 - Error number: [MY-013112](#); Symbol: [ER_XPLUGIN_FAILED_TO_STOP_SERVICES](#); SQLSTATE: [HY000](#)

Message: Stopping services failed with error "%s"

[ER_XPLUGIN_FAILED_TO_STOP_SERVICES](#) was added in 8.0.11.
 - Error number: [MY-013113](#); Symbol: [ER_INCONSISTENT_ERROR](#); SQLSTATE: [HY000](#)

Message: Query caused different errors on master and slave. Error on master: message (format)='%s' error code=%d; Error on slave:actual message='%s', error code=%d. Default database:'%s'. Query:'%s'
 - Error number: [MY-013114](#); Symbol: [ER_SERVER_MASTER_FATAL_ERROR_READING_BINLOG](#); SQLSTATE: [HY000](#)

Message: Got fatal error %d from master when reading data from binary log: '%s'

[ER_SERVER_MASTER_FATAL_ERROR_READING_BINLOG](#) was added in 8.0.11.
 - Error number: [MY-013115](#); Symbol: [ER_NETWORK_READ_EVENT_CHECKSUM_FAILURE](#); SQLSTATE: [HY000](#)

Message: Replication event checksum verification failed while reading from network.
 - Error number: [MY-013116](#); Symbol: [ER_SLAVE_CREATE_EVENT_FAILURE](#); SQLSTATE: [HY000](#)

Message: Failed to create %s
 - Error number: [MY-013117](#); Symbol: [ER_SLAVE_FATAL_ERROR](#); SQLSTATE: [HY000](#)

Message: Fatal error: %s
 - Error number: [MY-013118](#); Symbol: [ER_SLAVE_HEARTBEAT_FAILURE](#); SQLSTATE: [HY000](#)

Message: Unexpected master's heartbeat data: %s

- Error number: MY-013119; Symbol: ER_SLAVE INCIDENT; SQLSTATE: HY000

Message: The incident %s occurred on the master. Message: %s

- Error number: MY-013120; Symbol: ER_SLAVE_MASTER_COM_FAILURE; SQLSTATE: HY000

Message: Master command %s failed: %s

- Error number: MY-013121; Symbol: ER_SLAVE_RELAY_LOG_READ_FAILURE; SQLSTATE: HY000

Message: Relay log read failure: %s

- Error number: MY-013122; Symbol: ER_SLAVE_RELAY_LOG_WRITE_FAILURE; SQLSTATE: HY000

Message: Relay log write failure: %s

- Error number: MY-013123; Symbol: ER_SERVER_SLAVE_MI_INIT_REPOSITORY; SQLSTATE: HY000

Message: Slave failed to initialize master info structure from the repository

ER_SERVER_SLAVE_MI_INIT_REPOSITORY was added in 8.0.11.

- Error number: MY-013124; Symbol: ER_SERVER_SLAVE_RLI_INIT_REPOSITORY; SQLSTATE: HY000

Message: Slave failed to initialize relay log info structure from the repository

ER_SERVER_SLAVE_RLI_INIT_REPOSITORY was added in 8.0.11.

- Error number: MY-013125; Symbol: ER_SERVER_NET_PACKET_TOO_LARGE; SQLSTATE: HY000

Message: Got a packet bigger than 'max_allowed_packet' bytes

ER_SERVER_NET_PACKET_TOO_LARGE was added in 8.0.11.

- Error number: MY-013126; Symbol: ER_SERVER_NO_SYSTEM_TABLE_ACCESS; SQLSTATE: HY000

Message: Access to %s '%s.%s' is rejected.

ER_SERVER_NO_SYSTEM_TABLE_ACCESS was added in 8.0.11.

- Error number: MY-013127; Symbol: ER_SERVER_UNKNOWN_ERROR; SQLSTATE: HY000

Message: Unknown error

ER_SERVER_UNKNOWN_ERROR was added in 8.0.11.

- Error number: MY-013128; Symbol: ER_SERVER_UNKNOWN_SYSTEM_VARIABLE; SQLSTATE: HY000

Message: Unknown system variable '%s'

ER_SERVER_UNKNOWN_SYSTEM_VARIABLE was added in 8.0.11.

- Error number: MY-013129; Symbol: ER_SERVER_NO_SESSION_TO_SEND_TO; SQLSTATE: HY000

Message: A message intended for a client cannot be sent there as no client-session is attached.
Therefore, we're sending the information to the error-log instead: MY-%06d - %s

`ER_SERVER_NO_SESSION_TO_SEND_TO` was added in 8.0.11.

- Error number: `MY-013130`; Symbol: `ER_SERVER_NEW_ABORTING_CONNECTION`; SQLSTATE: `08S01`

Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s; diagnostics area: MY-%06d - %s)

`ER_SERVER_NEW_ABORTING_CONNECTION` was added in 8.0.11.

- Error number: `MY-013131`; Symbol: `ER_SERVER_OUT_OF_SORTMEMORY`; SQLSTATE: `HY000`

Message: Out of sort memory, consider increasing server sort buffer size!

`ER_SERVER_OUT_OF_SORTMEMORY` was added in 8.0.11.

- Error number: `MY-013132`; Symbol: `ER_SERVER_RECORD_FILE_FULL`; SQLSTATE: `HY000`

Message: The table '%s' is full!

`ER_SERVER_RECORD_FILE_FULL` was added in 8.0.11.

- Error number: `MY-013133`; Symbol: `ER_SERVER_DISK_FULL_NOWAIT`; SQLSTATE: `HY000`

Message: Create table/tablespace '%s' failed, as disk is full.

`ER_SERVER_DISK_FULL_NOWAIT` was added in 8.0.11.

- Error number: `MY-013134`; Symbol: `ER_SERVER_HANDLER_ERROR`; SQLSTATE: `HY000`

Message: Handler reported error %d - %s

`ER_SERVER_HANDLER_ERROR` was added in 8.0.11.

- Error number: `MY-013135`; Symbol: `ER_SERVER_NOT_FORM_FILE`; SQLSTATE: `HY000`

Message: Incorrect information in file: '%s'

`ER_SERVER_NOT_FORM_FILE` was added in 8.0.11.

- Error number: `MY-013136`; Symbol: `ER_SERVER_CANT_OPEN_FILE`; SQLSTATE: `HY000`

Message: Can't open file: '%s' (OS errno: %d - %s)

`ER_SERVER_CANT_OPEN_FILE` was added in 8.0.11.

- Error number: `MY-013137`; Symbol: `ER_SERVER_FILE_NOT_FOUND`; SQLSTATE: `HY000`

Message: Can't find file: '%s' (OS errno: %d - %s)

`ER_SERVER_FILE_NOT_FOUND` was added in 8.0.11.

- Error number: `MY-013138`; Symbol: `ER_SERVER_FILE_USED`; SQLSTATE: `HY000`

Message: '%s' is locked against change (OS errno: %d - %s)

`ER_SERVER_FILE_USED` was added in 8.0.11.

- Error number: [MY-013139](#); Symbol: [ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2](#); SQLSTATE: [HY000](#)

Message: Cannot load from %s.%s. The table is probably corrupted!
[ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2](#) was added in 8.0.11.
- Error number: [MY-013140](#); Symbol: [ER_ERROR_INFO_FROM_DA](#); SQLSTATE: [HY000](#)

Message: Error in diagnostics area: MY-%06d - %s
[ER_ERROR_INFO_FROM_DA](#) was added in 8.0.11.
- Error number: [MY-013141](#); Symbol: [ER_SERVER_TABLE_CHECK_FAILED](#); SQLSTATE: [HY000](#)

Message: Incorrect definition of table %s.%s: expected column '%s' at position %d, found '%s'.
[ER_SERVER_TABLE_CHECK_FAILED](#) was added in 8.0.11.
- Error number: [MY-013142](#); Symbol: [ER_SERVER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2](#); SQLSTATE: [HY000](#)

Message: The column count of %s.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please perform the MySQL upgrade procedure.
[ER_SERVER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2](#) was added in 8.0.11.
- Error number: [MY-013143](#); Symbol: [ER_SERVER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2](#); SQLSTATE: [HY000](#)

Message: Column count of %s.%s is wrong. Expected %d, found %d. The table is probably corrupted
[ER_SERVER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2](#) was added in 8.0.11.
- Error number: [MY-013144](#); Symbol: [ER_SERVER_ACL_TABLE_ERROR](#); SQLSTATE: [HY000](#)

Message:
[ER_SERVER_ACL_TABLE_ERROR](#) was added in 8.0.11.
- Error number: [MY-013145](#); Symbol: [ER_SERVER_SLAVE_INIT_QUERY_FAILED](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread aborted. Can't execute init_replica query, MY-%06d - '%s'
[ER_SERVER_SLAVE_INIT_QUERY_FAILED](#) was added in 8.0.11.
- Error number: [MY-013146](#); Symbol: [ER_SERVER_SLAVE_CONVERSION_FAILED](#); SQLSTATE: [HY000](#)

Message: Column %d of table '%s.%s' cannot be converted from type '%s' to type '%s'
[ER_SERVER_SLAVE_CONVERSION_FAILED](#) was added in 8.0.11.
- Error number: [MY-013147](#); Symbol: [ER_SERVER_SLAVE_IGNORED_TABLE](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread ignored the query because of replicate-*-table rules
[ER_SERVER_SLAVE_IGNORED_TABLE](#) was added in 8.0.11.
- Error number: [MY-013148](#); Symbol: [ER_CANT_REPLICATE_ANONYMOUS_WITH_AUTO_POSITION](#); SQLSTATE: [HY000](#)

Message: Cannot replicate anonymous transaction when AUTO_POSITION = 1, at file %s, position %lld.

- Error number: [MY-013149](#); Symbol: [ER_CANT_REPLICATE_ANONYMOUS_WITH_GTID_MODE_ON](#); SQLSTATE: [HY000](#)

Message: Cannot replicate anonymous transaction when @@GLOBAL.GTID_MODE = ON, at file %s, position %lld.

- Error number: [MY-013150](#); Symbol: [ER_CANT_REPLICATE_GTID_WITH_GTID_MODE_OFF](#); SQLSTATE: [HY000](#)

Message: Cannot replicate GTID-transaction when @@GLOBAL.GTID_MODE = OFF, at file %s, position %lld.

- Error number: [MY-013151](#); Symbol: [ER_SERVER_TEST_MESSAGE](#); SQLSTATE: [HY000](#)

Message: Simulated error

[ER_SERVER_TEST_MESSAGE](#) was added in 8.0.11.

- Error number: [MY-013152](#); Symbol: [ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

[ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR](#) was added in 8.0.11.

- Error number: [MY-013153](#); Symbol: [ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED](#); SQLSTATE: [HY000](#)

Message: Audit Log filtering has not been installed.

[ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED](#) was added in 8.0.11.

- Error number: [MY-013154](#); Symbol: [ER_PLUGIN_FAILED_TO_OPEN_TABLES](#); SQLSTATE: [HY000](#)

Message: Failed to open the %s filter tables.

[ER_PLUGIN_FAILED_TO_OPEN_TABLES](#) was added in 8.0.11.

- Error number: [MY-013155](#); Symbol: [ER_PLUGIN_FAILED_TO_OPEN_TABLE](#); SQLSTATE: [HY000](#)

Message: Failed to open '%s.%s' %s table.

[ER_PLUGIN_FAILED_TO_OPEN_TABLE](#) was added in 8.0.11.

- Error number: [MY-013156](#); Symbol: [ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE_EMPTY](#); SQLSTATE: [HY000](#)

Message: Filter name cannot be empty.

[ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE_EMPTY](#) was added in 8.0.11.

- Error number: [MY-013157](#); Symbol: [ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER](#); SQLSTATE: [HY000](#)

Message: Invalid character in the user name.

[ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER](#) was added in 8.0.11.

- Error number: [MY-013158](#); Symbol: [ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE](#); SQLSTATE: [HY000](#)

Message: Request ignored for '%s'@'%s'. SUPER or AUDIT_ADMIN needed to perform operation
`ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE` was added in 8.0.11.

- Error number: `MY-013159`; Symbol: `ER_AUDIT_LOG_NO_KEYRING_PLUGIN_INSTALLED`; SQLSTATE: `HY000`

Message: No keyring installed.

`ER_AUDIT_LOG_NO_KEYRING_PLUGIN_INSTALLED` was added in 8.0.11.

- Error number: `MY-013160`; Symbol: `ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER`; SQLSTATE: `HY000`

Message: Invalid character in the host name.

`ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER` was added in 8.0.11.

- Error number: `MY-013161`; Symbol: `ER_AUDIT_LOG_ENCRYPTION_PASSWORD_HAS_NOT_BEEN_SET`; SQLSTATE: `HY000`

Message: Audit log encryption password has not been set; it will be generated automatically. Use `audit_log_encryption_password_get` to obtain the password or `audit_log_encryption_password_set` to set a new one.

`ER_AUDIT_LOG_ENCRYPTION_PASSWORD_HAS_NOT_BEEN_SET` was added in 8.0.11.

- Error number: `MY-013162`; Symbol: `ER_AUDIT_LOG_COULD_NOT_CREATE_AES_KEY`; SQLSTATE: `HY000`

Message: Could not create AES key. OpenSSL's EVP_BytesToKey function failed.

`ER_AUDIT_LOG_COULD_NOT_CREATE_AES_KEY` was added in 8.0.11.

- Error number: `MY-013163`; Symbol: `ER_AUDIT_LOG_ENCRYPTION_PASSWORD_CANNOT_BE_FETCHED`; SQLSTATE: `HY000`

Message: Audit log encryption password cannot be fetched from the keyring. Password used so far is used for encryption.

`ER_AUDIT_LOG_ENCRYPTION_PASSWORD_CANNOT_BE_FETCHED` was added in 8.0.11.

- Error number: `MY-013164`; Symbol: `ER_COULD_NOT_REINITIALIZE_AUDIT_LOG_FILTERS`; SQLSTATE: `HY000`

Message: Could not reinitialize audit log filters.

`ER_COULD_NOT_REINITIALIZE_AUDIT_LOG_FILTERS` was added in 8.0.11.

- Error number: `MY-013165`; Symbol: `ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY`; SQLSTATE: `HY000`

Message: User cannot be empty.

`ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY` was added in 8.0.11.

- Error number: `MY-013166`; Symbol: `ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALPHANUMERIC`; SQLSTATE: `HY000`

Message: First character of the user name must be alphanumeric.

`ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALPHANUMERIC` was added in 8.0.11.

-
- Error number: [MY-013167](#); Symbol: [ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXIST](#); SQLSTATE: [HY000](#)

Message: Specified filter has not been found.
[ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXIST](#) was added in 8.0.11.
 - Error number: [MY-013168](#); Symbol: [ER_IB_MSG_1271](#); SQLSTATE: [HY000](#)

Message: Cannot upgrade server earlier than 5.7 to 8.0
[ER_IB_MSG_1271](#) was added in 8.0.11.
 - Error number: [MY-013169](#); Symbol: [ER_STARTING_INIT](#); SQLSTATE: [HY000](#)

Message: %s (mysqld %s) initializing of server in progress as process %lu
[ER_STARTING_INIT](#) was added in 8.0.11.
 - Error number: [MY-013170](#); Symbol: [ER_ENDING_INIT](#); SQLSTATE: [HY000](#)

Message: %s (mysqld %s) initializing of server has completed
[ER_ENDING_INIT](#) was added in 8.0.11.
 - Error number: [MY-013171](#); Symbol: [ER_IB_MSG_1272](#); SQLSTATE: [HY000](#)

Message: Cannot boot server version %lu on data directory built by version %llu. Downgrade is not supported
[ER_IB_MSG_1272](#) was added in 8.0.11.
 - Error number: [MY-013172](#); Symbol: [ER_SERVER_SHUTDOWN_INFO](#); SQLSTATE: [HY000](#)

Message: Received SHUTDOWN from user %. Shutting down mysqld (Version: %s).
[ER_SERVER_SHUTDOWN_INFO](#) was added in 8.0.12.
 - Error number: [MY-013173](#); Symbol: [ER_GRP_RPL_PLUGIN_ABORT](#); SQLSTATE: [HY000](#)

Message: The plugin encountered a critical error and will abort: %s
[ER_GRP_RPL_PLUGIN_ABORT](#) was added in 8.0.12.
 - Error number: [MY-013177](#); Symbol: [ER_AUDIT_LOG_TABLE_DEFINITION_NOT_UPDATED](#); SQLSTATE: [HY000](#)

Message: '%s.%s' table definition has not been upgraded; Please perform the MySQL upgrade procedure.
[ER_AUDIT_LOG_TABLE_DEFINITION_NOT_UPDATED](#) was added in 8.0.12.
 - Error number: [MY-013178](#); Symbol: [ER_DD_INITIALIZE_SQL_ERROR](#); SQLSTATE: [HY000](#)

Message: Execution of server-side SQL statement '%s' failed with error code = %d, error message = '%s'.
[ER_DD_INITIALIZE_SQL_ERROR](#) was added in 8.0.12.
 - Error number: [MY-013179](#); Symbol: [ER_NO_PATH_FOR_SHARED_LIBRARY](#); SQLSTATE: [HY000](#)

Message: No paths allowed for shared library.
[ER_NO_PATH_FOR_SHARED_LIBRARY](#) was added in 8.0.13.

- Error number: [MY-013180](#); Symbol: [ER_UDF_ALREADY_EXISTS](#); SQLSTATE: [HY000](#)

Message: Function '%s' already exists.
[ER_UDF_ALREADY_EXISTS](#) was added in 8.0.13.
- Error number: [MY-013181](#); Symbol: [ER_SET_EVENT_FAILED](#); SQLSTATE: [HY000](#)

Message: Got Error: %d from SetEvent.
[ER_SET_EVENT_FAILED](#) was added in 8.0.13.
- Error number: [MY-013182](#); Symbol: [ER_FAILED_TO_ALLOCATE_SSL_BIO](#); SQLSTATE: [HY000](#)

Message: Error allocating SSL BIO.
[ER_FAILED_TO_ALLOCATE_SSL_BIO](#) was added in 8.0.13.
- Error number: [MY-013183](#); Symbol: [ER_IB_MSG_1273](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_MSG_1273](#) was added in 8.0.13.
- Error number: [MY-013184](#); Symbol: [ER_PID_FILEPATH_LOCATIONS_INACCESSIBLE](#); SQLSTATE: [HY000](#)

Message: One or several locations were inaccessible while checking PID filepath.
[ER_PID_FILEPATH_LOCATIONS_INACCESSIBLE](#) was added in 8.0.13.
- Error number: [MY-013185](#); Symbol: [ER_UNKNOWN_VARIABLE_IN_PERSISTED_CONFIG_FILE](#); SQLSTATE: [HY000](#)

Message: Currently unknown variable '%s' was read from the persisted config file.
[ER_UNKNOWN_VARIABLE_IN_PERSISTED_CONFIG_FILE](#) was added in 8.0.13.
- Error number: [MY-013186](#); Symbol: [ER_FAILED_TO_HANDLE_DEFAULTS_FILE](#); SQLSTATE: [HY000](#)

Message: Fatal error in defaults handling. Program aborted!
[ER_FAILED_TO_HANDLE_DEFAULTS_FILE](#) was added in 8.0.13.
- Error number: [MY-013187](#); Symbol: [ER_DUPLICATE_SYS_VAR](#); SQLSTATE: [HY000](#)

Message: Duplicate variable name '%s'.
[ER_DUPLICATE_SYS_VAR](#) was added in 8.0.13.
- Error number: [MY-013188](#); Symbol: [ER_FAILED_TO_INIT_SYS_VAR](#); SQLSTATE: [HY000](#)

Message: Failed to initialize system variables.
[ER_FAILED_TO_INIT_SYS_VAR](#) was added in 8.0.13.
- Error number: [MY-013189](#); Symbol: [ER_SYS_VAR_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Variable name '%s' not found.
[ER_SYS_VAR_NOT_FOUND](#) was added in 8.0.13.
- Error number: [MY-013190](#); Symbol: [ER_IB_MSG_1274](#); SQLSTATE: [HY000](#)

Message: Some (%d) threads are still active

`ER_IB_MSG_1274` was added in 8.0.13.

- Error number: `MY-013191`; Symbol: `ER_IB_MSG_1275`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1275` was added in 8.0.13.

- Error number: `MY-013192`; Symbol: `ER_TARGET_TS_UNENCRYPTED`; SQLSTATE: `HY000`

Message: Source tablespace is encrypted but target tablespace is not.

`ER_TARGET_TS_UNENCRYPTED` was added in 8.0.13, removed after 8.0.15.

- Error number: `MY-013193`; Symbol: `ER_IB_MSG_1276`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1276` was added in 8.0.13, removed after 8.0.13.

- Error number: `MY-013193`; Symbol: `ER_IB_MSG_WAIT_FOR_ENCRYPT_THREAD`; SQLSTATE: `HY000`

Message: Waiting for tablespace_alter_encrypt_thread to exit

`ER_IB_MSG_WAIT_FOR_ENCRYPT_THREAD` was added in 8.0.14.

- Error number: `MY-013194`; Symbol: `ER_IB_MSG_1277`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1277` was added in 8.0.13.

- Error number: `MY-013195`; Symbol: `ER_IB_MSG_1278`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1278` was added in 8.0.13, removed after 8.0.13.

- Error number: `MY-013195`; Symbol: `ER_IB_MSG_NO_ENCRYPT_PROGRESS_FOUND`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_NO_ENCRYPT_PROGRESS_FOUND` was added in 8.0.14.

- Error number: `MY-013196`; Symbol: `ER_IB_MSG_1279`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1279` was added in 8.0.13, removed after 8.0.13.

- Error number: `MY-013196`; Symbol: `ER_IB_MSG_RESUME_OP_FOR_SPACE`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_RESUME_OP_FOR_SPACE` was added in 8.0.14.

- Error number: `MY-013197`; Symbol: `ER_IB_MSG_1280`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1280` was added in 8.0.13.

- Error number: `MY-013198`; Symbol: `ER_IB_MSG_1281`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1281` was added in 8.0.13.

- Error number: `MY-013199`; Symbol: `ER_IB_MSG_1282`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1282` was added in 8.0.13.

- Error number: `MY-013200`; Symbol: `ER_IB_MSG_1283`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1283` was added in 8.0.13.

- Error number: `MY-013201`; Symbol: `ER_IB_MSG_1284`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1284` was added in 8.0.13.

- Error number: `MY-013202`; Symbol: `ER_CANT_SET_ERROR_SUPPRESSION_LIST_FROM_COMMAND_LINE`; SQLSTATE: `HY000`

Message: %s: Could not add suppression rule for code "%s". Rule-set may be full, or code may not correspond to an error-log message.

`ER_CANT_SET_ERROR_SUPPRESSION_LIST_FROM_COMMAND_LINE` was added in 8.0.13.

- Error number: `MY-013203`; Symbol: `ER_INVALID_VALUE_OF_BIND_ADDRESSES`; SQLSTATE: `HY000`

Message: Invalid value for command line option bind-addresses: '%s'

`ER_INVALID_VALUE_OF_BIND_ADDRESSES` was added in 8.0.13.

- Error number: `MY-013204`; Symbol: `ER_RELAY_LOG_SPACE_LIMIT_DISABLED`; SQLSTATE: `HY000`

Message: Ignoring the @@global.relay_log_space_limit option because @@global.relay_log_purge is disabled.

`ER_RELAY_LOG_SPACE_LIMIT_DISABLED` was added in 8.0.13.

- Error number: `MY-013205`; Symbol: `ER_GRP_RPL_ERROR_GTIID_SET_EXTRACTION`; SQLSTATE: `HY000`

Message: Error when extracting GTID execution information: %s

`ER_GRP_RPL_ERROR_GTIID_SET_EXTRACTION` was added in 8.0.13.

- Error number: `MY-013206`; Symbol: `ER_GRP_RPL_MISSING_GRP_RPL_ACTION_COORDINATOR`; SQLSTATE: `HY000`

Message: Message received without a proper group coordinator module.

`ER_GRP_RPL_MISSING_GRP_RPL_ACTION_COORDINATOR` was added in 8.0.13.

-
- Error number: [MY-013207](#); Symbol: [ER_GRP_RPL_JOIN_WHEN_GROUP_ACTION_RUNNING](#); SQLSTATE: [HY000](#)

Message: A member cannot join the group while a group configuration operation is running.

[ER_GRP_RPL_JOIN_WHEN_GROUP_ACTION_RUNNING](#) was added in 8.0.13.

- Error number: [MY-013208](#); Symbol: [ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION_RUNNING](#); SQLSTATE: [HY000](#)

Message: A member is joining the group while a group configuration operation is occurring. The member will now leave the group

[ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION_RUNNING](#) was added in 8.0.13.

- Error number: [MY-013209](#); Symbol: [ER_GRP_RPL_CHANNEL_THREAD_WHEN_GROUP_ACTION_RUNNING](#); SQLSTATE: [HY000](#)

Message: Can't start slave %s when group replication is running a group configuration operation.

[ER_GRP_RPL_CHANNEL_THREAD_WHEN_GROUP_ACTION_RUNNING](#) was added in 8.0.13.

- Error number: [MY-013210](#); Symbol: [ER_GRP_RPL_APPOINTED_PRIMARY_NOT_PRESENT](#); SQLSTATE: [HY000](#)

Message: A primary election was invoked but the requested primary member is not in the group. Request ignored.

[ER_GRP_RPL_APPOINTED_PRIMARY_NOT_PRESENT](#) was added in 8.0.13.

- Error number: [MY-013211](#); Symbol: [ER_GRP_RPL_ERROR_ON_MESSAGE_SENDING](#); SQLSTATE: [HY000](#)

Message: Error while sending message. Context: %s

[ER_GRP_RPL_ERROR_ON_MESSAGE_SENDING](#) was added in 8.0.13.

- Error number: [MY-013212](#); Symbol: [ER_GRP_RPL_CONFIGURATION_ACTION_ERROR](#); SQLSTATE: [HY000](#)

Message: Error while executing a group configuration operation: %s

[ER_GRP_RPL_CONFIGURATION_ACTION_ERROR](#) was added in 8.0.13.

- Error number: [MY-013213](#); Symbol: [ER_GRP_RPL_CONFIGURATION_ACTION_LOCAL_TERMINATION](#); SQLSTATE: [HY000](#)

Message: Configuration operation '%s' terminated. %s

[ER_GRP_RPL_CONFIGURATION_ACTION_LOCAL_TERMINATION](#) was added in 8.0.13.

- Error number: [MY-013214](#); Symbol: [ER_GRP_RPL_CONFIGURATION_ACTION_START](#); SQLSTATE: [HY000](#)

Message: Starting group operation local execution: %s

[ER_GRP_RPL_CONFIGURATION_ACTION_START](#) was added in 8.0.13.

-
- Error number: [MY-013215](#); Symbol: [ER_GRP_RPL_CONFIGURATION_ACTION_END](#); SQLSTATE: [HY000](#)

Message: Termination of group operation local execution: %s

[ER_GRP_RPL_CONFIGURATION_ACTION_END](#) was added in 8.0.13.

- Error number: [MY-013216](#); Symbol: [ER_GRP_RPL_CONFIGURATION_ACTION_KILLED_ERROR](#); SQLSTATE: [HY000](#)

Message: A configuration change was killed in this member. The member will now leave the group as its configuration may have diverged.

[ER_GRP_RPL_CONFIGURATION_ACTION_KILLED_ERROR](#) was added in 8.0.13.

- Error number: [MY-013217](#); Symbol: [ER_GRP_RPL_PRIMARY_ELECTION_PROCESS_ERROR](#); SQLSTATE: [HY000](#)

Message: There was an issue on the primary election process: %s The member will now leave the group.

[ER_GRP_RPL_PRIMARY_ELECTION_PROCESS_ERROR](#) was added in 8.0.13.

- Error number: [MY-013218](#); Symbol: [ER_GRP_RPL_PRIMARY_ELECTION_STOP_ERROR](#); SQLSTATE: [HY000](#)

Message: There was an issue when stopping a previous election process: %s

[ER_GRP_RPL_PRIMARY_ELECTION_STOP_ERROR](#) was added in 8.0.13.

- Error number: [MY-013219](#); Symbol: [ER_GRP_RPL_NO_STAGE_SERVICE](#); SQLSTATE: [HY000](#)

Message: It was not possible to initialize stage logging for this task. The operation will still run without stage tracking.

[ER_GRP_RPL_NO_STAGE_SERVICE](#) was added in 8.0.13.

- Error number: [MY-013220](#); Symbol: [ER_GRP_RPL_UDF_REGISTER_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not execute the installation of Group Replication UDF function: %. Check if the function is already present, if so, try to remove it

[ER_GRP_RPL_UDF_REGISTER_ERROR](#) was added in 8.0.13.

- Error number: [MY-013221](#); Symbol: [ER_GRP_RPL_UDF_UNREGISTER_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not uninstall Group Replication UDF functions. Try to remove them manually if present.

[ER_GRP_RPL_UDF_UNREGISTER_ERROR](#) was added in 8.0.13.

- Error number: [MY-013222](#); Symbol: [ER_GRP_RPL_UDF_REGISTER_SERVICE_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not execute the installation of Group Replication UDF functions. Check for other errors in the log and try to reinstall the plugin

[ER_GRP_RPL_UDF_REGISTER_SERVICE_ERROR](#) was added in 8.0.13.

- Error number: [MY-013223](#); Symbol: [ER_GRP_RPL_SERVER_UDF_ERROR](#); SQLSTATE: [HY000](#)

Message: The function '%s' failed. %s
[ER_GRP_RPL_SERVER_UDF_ERROR](#) was added in 8.0.17.
- Error number: [MY-013227](#); Symbol: [ER_SERVER_WRONG_VALUE_FOR_VAR](#); SQLSTATE: [HY000](#)

Message: Variable '%s' can't be set to the value of '%s'
[ER_SERVER_WRONG_VALUE_FOR_VAR](#) was added in 8.0.13.
- Error number: [MY-013228](#); Symbol: [ER_COULD_NOT_CREATE_WINDOWS_REGISTRY_KEY](#); SQLSTATE: [HY000](#)

Message: %s was unable to create a new Windows registry key %s for %s; continuing to use the previous ident.
[ER_COULD_NOT_CREATE_WINDOWS_REGISTRY_KEY](#) was added in 8.0.13.
- Error number: [MY-013229](#); Symbol: [ER_SERVER_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_TRX_IN_SBR](#); SQLSTATE: [HY000](#)

Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE are not allowed inside a transaction or inside a procedure in a transactional context when @@session.binlog_format=STATEMENT.
[ER_SERVER_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_TRX_IN_SBR](#) was added in 8.0.13.
- Error number: [MY-013233](#); Symbol: [ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX](#); SQLSTATE: [HY000](#)

Message: Unable to switch security context to user: %s
[ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX](#) was added in 8.0.13.
- Error number: [MY-013234](#); Symbol: [ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION](#); SQLSTATE: [HY000](#)

Message: Statement violates GTID consistency: ALTER TABLE ... ADD COLUMN .. with expression as DEFAULT.
[ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION](#) was added in 8.0.13.
- Error number: [MY-013235](#); Symbol: [ER_UPGRADE_PARSE_ERROR](#); SQLSTATE: [HY000](#)

Message: Error in parsing %s '%s'.'%s' during upgrade. %s
[ER_UPGRADE_PARSE_ERROR](#) was added in 8.0.13.
- Error number: [MY-013236](#); Symbol: [ER_DATA_DIRECTORY_UNUSABLE](#); SQLSTATE: [HY000](#)

Message: The designated data directory %s is unusable. You can remove all files that the server added to it.
[ER_DATA_DIRECTORY_UNUSABLE](#) was added in 8.0.13.
- Error number: [MY-013237](#); Symbol: [ER_LDAP_AUTH_USER_GROUP_SEARCH_ROOT_BIND](#); SQLSTATE: [HY000](#)

Message: Group search rebinding via root DN: %s
[ER_LDAP_AUTH_USER_GROUP_SEARCH_ROOT_BIND](#) was added in 8.0.13.

- Error number: [MY-013238](#); Symbol: [ER_PLUGIN_INSTALL_ERROR](#); SQLSTATE: [HY000](#)

Message: Error installing plugin '%s': %s
[ER_PLUGIN_INSTALL_ERROR](#) was added in 8.0.13.
- Error number: [MY-013239](#); Symbol: [ER_PLUGIN_UNINSTALL_ERROR](#); SQLSTATE: [HY000](#)

Message: Error uninstalling plugin '%s': %s
[ER_PLUGIN_UNINSTALL_ERROR](#) was added in 8.0.13.
- Error number: [MY-013240](#); Symbol: [ER_SHARED_TABLESPACE_USED_BY_PARTITIONED_TABLE](#); SQLSTATE: [HY000](#)

Message: Partitioned table '%s' is not allowed to use shared tablespace '%s'. Please move all partitions to file-per-table tablespaces before upgrade.
[ER_SHARED_TABLESPACE_USED_BY_PARTITIONED_TABLE](#) was added in 8.0.13.
- Error number: [MY-013241](#); Symbol: [ER_UNKNOWN_TABLESPACE_TYPE](#); SQLSTATE: [HY000](#)

Message: Cannot determine the type of the tablespace named '%s'.
[ER_UNKNOWN_TABLESPACE_TYPE](#) was added in 8.0.13.
- Error number: [MY-013242](#); Symbol: [ER_WARN_DEPRECATED_UTF8_ALIAS_OPTION](#); SQLSTATE: [HY000](#)

Message: %s: 'utf8' is currently an alias for the character set UTF8MB3, but will be an alias for UTF8MB4 in a future release. Please consider using UTF8MB4 in order to be unambiguous.
[ER_WARN_DEPRECATED_UTF8_ALIAS_OPTION](#) was added in 8.0.13.
- Error number: [MY-013243](#); Symbol: [ER_WARN_DEPRECATED_UTF8MB3_CHARSET_OPTION](#); SQLSTATE: [HY000](#)

Message: %s: The character set UTF8MB3 is deprecated and will be removed in a future release. Please consider using UTF8MB4 instead.
[ER_WARN_DEPRECATED_UTF8MB3_CHARSET_OPTION](#) was added in 8.0.13.
- Error number: [MY-013244](#); Symbol: [ER_WARN_DEPRECATED_UTF8MB3_COLLATION_OPTION](#); SQLSTATE: [HY000](#)

Message: %s: '%s' is a collation of the deprecated character set UTF8MB3. Please consider using UTF8MB4 with an appropriate collation instead.
[ER_WARN_DEPRECATED_UTF8MB3_COLLATION_OPTION](#) was added in 8.0.13.
- Error number: [MY-013245](#); Symbol: [ER_SSL_MEMORY_INSTRUMENTATION_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: The SSL library function %s failed. This is typically caused by the SSL library already being used. As a result the SSL memory allocation will not be instrumented.
[ER_SSL_MEMORY_INSTRUMENTATION_INIT_FAILED](#) was added in 8.0.13.
- Error number: [MY-013246](#); Symbol: [ER_IB_MSG_MADV_DONTDUMP_UNSUPPORTED](#); SQLSTATE: [HY000](#)

Message: Disabling @@core_file because @@innodb_buffer_pool_in_core_file is disabled, yet MADV_DONTDUMP is not supported on this platform

`ER_IB_MSG_MADV_DONTDUMP_UNSUPPORTED` was added in 8.0.14.

- Error number: `MY-013247`; Symbol: `ER_IB_MSG_MADVISE_FAILED`; SQLSTATE: `HY000`

Message: Disabling @@core_file because @@innodb_buffer_pool_in_core_file is disabled, yet madvise(%p,%zu,%s) failed with %s

`ER_IB_MSG_MADVISE_FAILED` was added in 8.0.14.

- Error number: `MY-013249`; Symbol: `ER_WARN_REMOVED_SQL_MODE`; SQLSTATE: `HY000`

Message: sql_mode=0x%08x has been removed and will be ignored

`ER_WARN_REMOVED_SQL_MODE` was added in 8.0.14.

- Error number: `MY-013250`; Symbol: `ER_IB_MSG_FAILED_TO_ALLOCATE_WAIT`; SQLSTATE: `HY000`

Message: Failed to allocate memory for a pool of size %zu bytes. Will wait for %zu seconds for a thread to free a resource.

`ER_IB_MSG_FAILED_TO_ALLOCATE_WAIT` was added in 8.0.14.

- Error number: `MY-013251`; Symbol: `ER_IB_MSG_NUM_POOLS`; SQLSTATE: `HY000`

Message: Number of pools: %zu

`ER_IB_MSG_NUM_POOLS` was added in 8.0.14.

- Error number: `MY-013252`; Symbol: `ER_IB_MSG_USING_UNDO_SPACE`; SQLSTATE: `HY000`

Message: Using undo tablespace '%s'.

`ER_IB_MSG_USING_UNDO_SPACE` was added in 8.0.14.

- Error number: `MY-013253`; Symbol: `ER_IB_MSG_FAIL_TO_SAVE_SPACE_STATE`; SQLSTATE: `HY000`

Message: %s Unable to save the current state of tablespace '%s' to the data dictionary

`ER_IB_MSG_FAIL_TO_SAVE_SPACE_STATE` was added in 8.0.14.

- Error number: `MY-013254`; Symbol: `ER_IB_MSG_MAX_UNDO_SPACES_REACHED`; SQLSTATE: `HY000`

Message: Cannot create undo tablespace %s at %s because %d undo tablespaces already exist.

`ER_IB_MSG_MAX_UNDO_SPACES_REACHED` was added in 8.0.14.

- Error number: `MY-013255`; Symbol: `ER_IB_MSG_ERROR_OPENING_NEW_UNDO_SPACE`; SQLSTATE: `HY000`

Message: Error %d opening newly created undo tablespace %s.

`ER_IB_MSG_ERROR_OPENING_NEW_UNDO_SPACE` was added in 8.0.14.

- Error number: `MY-013256`; Symbol: `ER_IB_MSG_FAILED_SDI_Z_BUF_ERROR`; SQLSTATE: `HY000`

Message: SDI Compression failed, Z_BUF_ERROR

`ER_IB_MSG_FAILED_SDI_Z_BUF_ERROR` was added in 8.0.14.

- Error number: [MY-013257](#); Symbol: [ER_IB_MSG_FAILED_SDI_Z_MEM_ERROR](#); SQLSTATE: [HY000](#)

Message: SDI Compression failed, Z_MEM_ERROR

[ER_IB_MSG_FAILED_SDI_Z_MEM_ERROR](#) was added in 8.0.14.

- Error number: [MY-013258](#); Symbol: [ER_IB_MSG_SDI_Z_STREAM_ERROR](#); SQLSTATE: [HY000](#)

Message: SDI Compression failed, Z_STREAM_ERROR

[ER_IB_MSG_SDI_Z_STREAM_ERROR](#) was added in 8.0.14.

- Error number: [MY-013259](#); Symbol: [ER_IB_MSG_SDI_Z_UNKNOWN_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_SDI_Z_UNKNOWN_ERROR](#) was added in 8.0.14.

- Error number: [MY-013260](#); Symbol: [ER_IB_MSG_FOUND_WRONG_UNDO_SPACE](#); SQLSTATE: [HY000](#)

Message: Expected to find undo tablespace '%s' for Space ID=%lu, but found '%s' instead! Did you change innodb_undo_directory?

[ER_IB_MSG_FOUND_WRONG_UNDO_SPACE](#) was added in 8.0.14.

- Error number: [MY-013261](#); Symbol: [ER_IB_MSG_NOT_END_WITH_IBU](#); SQLSTATE: [HY000](#)

Message: Cannot use %s as an undo tablespace because it does not end with '.ibu'.

[ER_IB_MSG_NOT_END_WITH_IBU](#) was added in 8.0.14.

- Error number: [MY-013262](#); Symbol: [ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE](#); SQLSTATE: [HY000](#)

Message: ib_undo_trunc_empty_file

[ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE](#) was added in 8.0.14, removed after 8.0.20.

- Error number: [MY-013263](#); Symbol: [ER_IB_MSG_UNDO_TRUNC_BEFOR_DD_UPDATE](#); SQLSTATE: [HY000](#)

Message: ib_undo_trunc_before_dd_update

[ER_IB_MSG_UNDO_TRUNC_BEFOR_DD_UPDATE](#) was added in 8.0.14, removed after 8.0.20.

- Error number: [MY-013264](#); Symbol: [ER_IB_MSG_UNDO_TRUNC_BEFORE_UNDO_LOGGING](#); SQLSTATE: [HY000](#)

Message: ib_undo_trunc_before_done_logging

[ER_IB_MSG_UNDO_TRUNC_BEFORE_UNDO_LOGGING](#) was added in 8.0.14, removed after 8.0.20.

- Error number: [MY-013265](#); Symbol: [ER_IB_MSG_UNDO_TRUNK_BEFORE_RSEG](#); SQLSTATE: [HY000](#)

Message: ib_undo_trunc_before_rsegs

[ER_IB_MSG_UNDO_TRUNK_BEFORE_RSEG](#) was added in 8.0.14, removed after 8.0.20.

- Error number: [MY-013266](#); Symbol: [ER_IB_MSG_FAILED_TO_FINISH_TRUNCATE](#); SQLSTATE: [HY000](#)

Message: %s Failed to finish truncating Undo Tablespace '%s'

`ER_IB_MSG_FAILED_TO_FINISH_TRUNCATE` was added in 8.0.14.

- Error number: `MY-013267`; Symbol: `ER_IB_MSG_DEPRECATED_INNODB_UNDO_TABLESPACES`; SQLSTATE: `HY000`

Message: The setting INNODB_UNDO_TABLESPACES is deprecated and is no longer used. InnoDB always creates 2 undo tablespaces to start with. If you need more, please use CREATE UNDO TABLESPACE.

`ER_IB_MSG_DEPRECATED_INNODB_UNDO_TABLESPACES` was added in 8.0.14.

- Error number: `MY-013268`; Symbol: `ER_IB_MSG_DIR_DOES_NOT_EXIST`; SQLSTATE: `HY000`

Message: The directory '%s' does not exist.

`ER_IB_MSG_DIR_DOES_NOT_EXIST` was added in 8.0.14, removed after 8.0.20.

- Error number: `MY-013268`; Symbol: `ER_IB_MSG_WRONG_TABLESPACE_DIR`; SQLSTATE: `HY000`

Message: The directory for tablespace %s does not exist or is incorrect.

`ER_IB_MSG_WRONG_TABLESPACE_DIR` was added in 8.0.21.

- Error number: `MY-013269`; Symbol: `ER_IB_MSG_LOCK_FREE_HASH_USAGE_STATS`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_LOCK_FREE_HASH_USAGE_STATS` was added in 8.0.14.

- Error number: `MY-013270`; Symbol: `ER_CLONE_REMOTE_ERROR`; SQLSTATE: `HY000`

Message: Clone Remote Error: %s.

`ER_CLONE_REMOTE_ERROR` was added in 8.0.14, removed after 8.0.16.

- Error number: `MY-013270`; Symbol: `ER_CLONE_DONOR_TRACE`; SQLSTATE: `HY000`

Message: Clone donor reported : %s.

`ER_CLONE_DONOR_TRACE` was added in 8.0.17.

- Error number: `MY-013271`; Symbol: `ER_CLONE_PROTOCOL_ERROR`; SQLSTATE: `HY000`

Message: Clone Protocol Error: %s.

`ER_CLONE_PROTOCOL_ERROR` was added in 8.0.14, removed after 8.0.16.

- Error number: `MY-013271`; Symbol: `ER_CLONE_PROTOCOL_TRACE`; SQLSTATE: `HY000`

Message: Clone received unexpected response from donor : %s.

`ER_CLONE_PROTOCOL_TRACE` was added in 8.0.17.

- Error number: `MY-013272`; Symbol: `ER_CLONE_INFO_CLIENT`; SQLSTATE: `HY000`

Message: Client: %s.

`ER_CLONE_INFO_CLIENT` was added in 8.0.14, removed after 8.0.16.

- Error number: `MY-013272`; Symbol: `ER_CLONE_CLIENT_TRACE`; SQLSTATE: `HY000`

Message: Client: %s.

`ER_CLONE_CLIENT_TRACE` was added in 8.0.17.

- Error number: `MY-013273`; Symbol: `ER_CLONE_INFO_SERVER`; SQLSTATE: `HY000`

Message: Server: %s.

`ER_CLONE_INFO_SERVER` was added in 8.0.14, removed after 8.0.16.

- Error number: `MY-013273`; Symbol: `ER_CLONE_SERVER_TRACE`; SQLSTATE: `HY000`

Message: Server: %s.

`ER_CLONE_SERVER_TRACE` was added in 8.0.17.

- Error number: `MY-013274`; Symbol: `ER_THREAD_POOL_PFS_TABLES_INIT_FAILED`; SQLSTATE: `HY000`

Message: Failed to initialize the performance schema tables service.

`ER_THREAD_POOL_PFS_TABLES_INIT_FAILED` was added in 8.0.14.

- Error number: `MY-013275`; Symbol: `ER_THREAD_POOL_PFS_TABLES_ADD_FAILED`; SQLSTATE: `HY000`

Message: Failed to add thread pool performance schema tables.

`ER_THREAD_POOL_PFS_TABLES_ADD_FAILED` was added in 8.0.14.

- Error number: `MY-013276`; Symbol: `ER_CANT_SET_DATA_DIR`; SQLSTATE: `HY000`

Message: Failed to set datadir to '\%s\' (OS errno: %d - %s)

`ER_CANT_SET_DATA_DIR` was added in 8.0.14.

- Error number: `MY-013277`; Symbol:

`ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY_LOCATION`; SQLSTATE: `HY000`

Message: The innodb_undo_directory is not allowed to be an ancestor of the datadir.

`ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY_LOCATION` was added in 8.0.14.

- Error number: `MY-013278`; Symbol: `ER_SERVER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY`; SQLSTATE: `HY000`

Message: Failed to fetch key from keyring, please check if keyring is loaded.

`ER_SERVER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY` was added in 8.0.14.

- Error number: `MY-013279`; Symbol: `ER_SERVER_RPL_ENCRYPTION_KEY_NOT_FOUND`; SQLSTATE: `HY000`

Message: Can't find key from keyring, please check in the server log if a keyring is loaded and initialized successfully.

`ER_SERVER_RPL_ENCRYPTION_KEY_NOT_FOUND` was added in 8.0.14.

- Error number: `MY-013280`; Symbol: `ER_SERVER_RPL_ENCRYPTION_KEYRING_INVALID_KEY`; SQLSTATE: `HY000`

Message: Fetched an invalid key from keyring.

`ER_SERVER_RPL_ENCRYPTION_KEYRING_INVALID_KEY` was added in 8.0.14.

-
- Error number: [MY-013281](#); Symbol: [ER_SERVER_RPL_ENCRYPTION_HEADER_ERROR](#); SQLSTATE: [HY000](#)

Message: Error reading a replication log encryption header: %s.

[ER_SERVER_RPL_ENCRYPTION_HEADER_ERROR](#) was added in 8.0.14.

- Error number: [MY-013282](#); Symbol: [ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS](#); SQLSTATE: [HY000](#)

Message: Failed to rotate some logs after changing binlog encryption settings. Please fix the problem and rotate the logs manually.

[ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS](#) was added in 8.0.14.

- Error number: [MY-013283](#); Symbol: [ER_SERVER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED](#); SQLSTATE: [HY000](#)

Message: Key %s exists unexpected.

[ER_SERVER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED](#) was added in 8.0.14.

- Error number: [MY-013284](#); Symbol: [ER_SERVER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY](#); SQLSTATE: [HY000](#)

Message: Failed to generate key, please check if keyring is loaded.

[ER_SERVER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY](#) was added in 8.0.14.

- Error number: [MY-013285](#); Symbol: [ER_SERVER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY](#); SQLSTATE: [HY000](#)

Message: Failed to store key, please check if keyring is loaded.

[ER_SERVER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY](#) was added in 8.0.14.

- Error number: [MY-013286](#); Symbol: [ER_SERVER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY](#); SQLSTATE: [HY000](#)

Message: Failed to remove key, please check if keyring is loaded.

[ER_SERVER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY](#) was added in 8.0.14.

- Error number: [MY-013287](#); Symbol: [ER_SERVER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to recover binlog encryption master key, please check if keyring is loaded.

[ER_SERVER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED](#) was added in 8.0.14.

- Error number: [MY-013288](#); Symbol: [ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_INITIALIZE](#); SQLSTATE: [HY000](#)

Message: Failed to initialize binlog encryption, please check if keyring is loaded.

[ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_INITIALIZE](#) was added in 8.0.14.

- Error number: [MY-013289](#); Symbol: [ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_ROTATE_MASTER_KEY_AT_STARTUP](#); SQLSTATE: [HY000](#)

Message: Failed to rotate binlog encryption master key at startup, please check if keyring is loaded.

[ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_ROTATE_MASTER_KEY_AT_STARTUP](#) was added in 8.0.14.

- Error number: [MY-013290](#); Symbol: [ER_SERVER_RPL_ENCRYPTION_IGNORE_ROTATE_MASTER_KEY_AT_STARTUP](#); SQLSTATE: [HY000](#)

Message: Ignoring binlog_rotate_encryption_master_key_at_startup because binlog_encryption option is disabled.

[ER_SERVER_RPL_ENCRYPTION_IGNORE_ROTATE_MASTER_KEY_AT_STARTUP](#) was added in 8.0.14.

- Error number: [MY-013291](#); Symbol: [ER_INVALID_ADMIN_ADDRESS](#); SQLSTATE: [HY000](#)

Message: Invalid value for command line option admin-address: '%s'

[ER_INVALID_ADMIN_ADDRESS](#) was added in 8.0.14.

- Error number: [MY-013292](#); Symbol: [ER_SERVER_STARTUP_ADMIN_INTERFACE](#); SQLSTATE: [HY000](#)

Message: Admin interface ready for connections, address: '%s' port: %d

[ER_SERVER_STARTUP_ADMIN_INTERFACE](#) was added in 8.0.14.

- Error number: [MY-013293](#); Symbol: [ER_CANT_CREATE_ADMIN_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create thread to handle admin connections (errno= %d)

[ER_CANT_CREATE_ADMIN_THREAD](#) was added in 8.0.14.

- Error number: [MY-013294](#); Symbol: [ER_WARNING_RETAIN_CURRENT_PASSWORD_CLAUSE_VOID](#); SQLSTATE: [HY000](#)

Message: RETAIN CURRENT PASSWORD ignored for user '%s'@'%s' as its authentication plugin %s does not support multiple passwords.

[ER_WARNING_RETAIN_CURRENT_PASSWORD_CLAUSE_VOID](#) was added in 8.0.14.

- Error number: [MY-013295](#); Symbol: [ER_WARNING_DISCARD_OLD_PASSWORD_CLAUSE_VOID](#); SQLSTATE: [HY000](#)

Message: DISCARD OLD PASSWORD ignored for user '%s'@'%s' as its authentication plugin %s does not support multiple passwords.

[ER_WARNING_DISCARD_OLD_PASSWORD_CLAUSE_VOID](#) was added in 8.0.14.

- Error number: [MY-013299](#); Symbol: [ER_WARNING_AUTHCACHE_INVALID_USER_ATTRIBUTES](#); SQLSTATE: [HY000](#)

Message: Can not read and process value of User_attributes column from mysql.user table for user: '%s@%s'; Ignoring user.

[ER_WARNING_AUTHCACHE_INVALID_USER_ATTRIBUTES](#) was added in 8.0.14.

- Error number: [MY-013300](#); Symbol: [ER_MYSQL_NATIVE_PASSWORD_SECOND_PASSWORD_USED_INFORMATION](#); SQLSTATE: [HY000](#)

Message: Second password was used for login by user: '%s'@'%s'.
[ER_MYSQL_NATIVE_PASSWORD_SECOND_PASSWORD_USED_INFORMATION](#) was added in 8.0.14.
- Error number: [MY-013301](#); Symbol: [ER_SHA256_PASSWORD_SECOND_PASSWORD_USED_INFORMATION](#); SQLSTATE: [HY000](#)

Message: Second password was used for login by user: '%s'@'%s'.
[ER_SHA256_PASSWORD_SECOND_PASSWORD_USED_INFORMATION](#) was added in 8.0.14.
- Error number: [MY-013302](#); Symbol: [ER_CACHING_SHA2_PASSWORD_SECOND_PASSWORD_USED_INFORMATION](#); SQLSTATE: [HY000](#)

Message: Second password was used for login by user: '%s'@'%s'.
[ER_CACHING_SHA2_PASSWORD_SECOND_PASSWORD_USED_INFORMATION](#) was added in 8.0.14.
- Error number: [MY-013303](#); Symbol: [ER_GRP_RPL_SEND_TRX_PREPARED_MESSAGE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error sending transaction '%d:%lld' prepared message from session '%u'.
[ER_GRP_RPL_SEND_TRX_PREPARED_MESSAGE_FAILED](#) was added in 8.0.14.
- Error number: [MY-013304](#); Symbol: [ER_GRP_RPL_RELEASE_COMMIT_AFTER_GROUP_PREPARE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error releasing transaction '%d:%lld' for commit on session '%u' after being prepared on all group members.
[ER_GRP_RPL_RELEASE_COMMIT_AFTER_GROUP_PREPARE_FAILED](#) was added in 8.0.14.
- Error number: [MY-013305](#); Symbol: [ER_GRP_RPL_TRX_ALREADY_EXISTS_ON_TCM_ON_AFTER_CERTIFICATION](#); SQLSTATE: [HY000](#)

Message: Transaction '%d:%lld' already exists on Group Replication consistency manager while being registered after conflict detection.
[ER_GRP_RPL_TRX_ALREADY_EXISTS_ON_TCM_ON_AFTER_CERTIFICATION](#) was added in 8.0.14.
- Error number: [MY-013306](#); Symbol: [ER_GRP_RPL_FAILED_TO_INSERT_TRX_ON_TCM_ON_AFTER_CERTIFICATION](#); SQLSTATE: [HY000](#)

Message: Error registering transaction '%d:%lld' on Group Replication consistency manager after conflict detection.
[ER_GRP_RPL_FAILED_TO_INSERT_TRX_ON_TCM_ON_AFTER_CERTIFICATION](#) was added in 8.0.14.
- Error number: [MY-013307](#); Symbol: [ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_GROUP_PREPARE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error registering transaction '%d:%lld' from session '%u' to wait for being prepared on all group members.
[ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_GROUP_PREPARE_FAILED](#) was added in 8.0.14.

- Error number: [MY-013308](#); Symbol: [ER_GRP_RPL_TRX_WAIT_FOR_GROUP_PREPARE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error on transaction '%d:%lld' from session '%u' while waiting for being prepared on all group members.

[ER_GRP_RPL_TRX_WAIT_FOR_GROUP_PREPARE_FAILED](#) was added in 8.0.14.

- Error number: [MY-013309](#); Symbol: [ER_GRP_RPL_TRX_DOES_NOT_EXIST_ON_TCM_ON_HANDLE_REMOTE_PREPARE](#); SQLSTATE: [HY000](#)

Message: Transaction '%d:%lld' does not exist on Group Replication consistency manager while receiving remote transaction prepare.

[ER_GRP_RPL_TRX_DOES_NOT_EXIST_ON_TCM_ON_HANDLE_REMOTE_PREPARE](#) was added in 8.0.14.

- Error number: [MY-013310](#); Symbol: [ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_DEPENDENCIES_COMMIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Error releasing transaction '%d:%lld' for execution on session '%u' after its dependencies did complete commit.

[ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_DEPENDENCIES_COMMIT_FAILED](#) was added in 8.0.14.

- Error number: [MY-013311](#); Symbol: [ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_DEPENDENCIES_FAILED](#); SQLSTATE: [HY000](#)

Message: Error registering transaction from session '%u' to wait for its dependencies to complete commit.

[ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_DEPENDENCIES_FAILED](#) was added in 8.0.14.

- Error number: [MY-013312](#); Symbol: [ER_GRP_RPL_WAIT_FOR_DEPENDENCIES_FAILED](#); SQLSTATE: [HY000](#)

Message: Error on session '%u' while waiting for its dependencies to complete commit.

[ER_GRP_RPL_WAIT_FOR_DEPENDENCIES_FAILED](#) was added in 8.0.14.

- Error number: [MY-013313](#); Symbol: [ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_SYNC_BEFORE_EXECUTION_FAILED](#); SQLSTATE: [HY000](#)

Message: Error registering transaction from session '%u' to wait for sync before execution.

[ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_SYNC_BEFORE_EXECUTION_FAILED](#) was added in 8.0.14.

- Error number: [MY-013314](#); Symbol: [ER_GRP_RPL_SEND_TRX_SYNC_BEFORE_EXECUTION_FAILED](#); SQLSTATE: [HY000](#)

Message: Error sending sync before execution message from session '%u'.

[ER_GRP_RPL_SEND_TRX_SYNC_BEFORE_EXECUTION_FAILED](#) was added in 8.0.14.

- Error number: [MY-013315](#); Symbol: [ER_GRP_RPL_TRX_WAIT_FOR_SYNC_BEFORE_EXECUTION_FAILED](#); SQLSTATE: [HY000](#)

Message: Error on transaction from session '%u' while waiting for sync before execution.
[ER_GRP_RPL_TRX_WAIT_FOR_SYNC_BEFORE_EXECUTION_FAILED](#) was added in 8.0.14.
- Error number: [MY-013316](#); Symbol: [ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_WAIT_FOR_SYNC_BEFORE_EXEC](#); SQLSTATE: [HY000](#)

Message: Error releasing transaction for execution on session '%u' after wait for sync before execution.
[ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_WAIT_FOR_SYNC_BEFORE_EXEC](#) was added in 8.0.14.
- Error number: [MY-013317](#); Symbol: [ER_GRP_RPL_TRX_WAIT_FOR_GROUP_GTID_EXECUTED](#); SQLSTATE: [HY000](#)

Message: Error waiting for group executed transactions commit on session '%u'.
[ER_GRP_RPL_TRX_WAIT_FOR_GROUP_GTID_EXECUTED](#) was added in 8.0.14.
- Error number: [MY-013320](#); Symbol: [ER_WARN_PROPERTY_STRING_PARSE_FAILED](#); SQLSTATE: [HY000](#)

Message: Could not parse key-value pairs in property string '%s'
[ER_WARN_PROPERTY_STRING_PARSE_FAILED](#) was added in 8.0.14.
- Error number: [MY-013321](#); Symbol: [ER_INVALID_PROPERTY_KEY](#); SQLSTATE: [HY000](#)

Message: Property key '%s' is invalid.
[ER_INVALID_PROPERTY_KEY](#) was added in 8.0.14.
- Error number: [MY-013322](#); Symbol: [ER_GRP_RPL_GTID_SET_EXTRACT_ERROR_DURING_RECOVERY](#); SQLSTATE: [HY000](#)

Message: Error when extracting the group_replication_applier channel received transactions set. Unable to ensure the execution of group transactions received during recovery.
[ER_GRP_RPL_GTID_SET_EXTRACT_ERROR_DURING_RECOVERY](#) was added in 8.0.14.
- Error number: [MY-013323](#); Symbol: [ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT](#); SQLSTATE: [HY000](#)

Message: Failed to encrypt content to write into binlog file: %s.
[ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT](#) was added in 8.0.14.
- Error number: [MY-013324](#); Symbol: [ER_CANNOT_GET_SERVER_VERSION_FROM_TABLESPACE_HEADER](#); SQLSTATE: [HY000](#)

Message: Cannot get the server version number from the dictionary tablespace header.
[ER_CANNOT_GET_SERVER_VERSION_FROM_TABLESPACE_HEADER](#) was added in 8.0.14.
- Error number: [MY-013325](#); Symbol: [ER_CANNOT_SET_SERVER_VERSION_IN_TABLESPACE_HEADER](#); SQLSTATE: [HY000](#)

Message: Cannot set the server version number in the dictionary tablespace header.

`ER_CANNOT_SET_SERVER_VERSION_IN_TABLESPACE_HEADER` was added in 8.0.14.

- Error number: `MY-013326`; Symbol: `ER_SERVER_UPGRADE_VERSION_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Upgrading the server from server version '%u' is not supported.

`ER_SERVER_UPGRADE_VERSION_NOT_SUPPORTED` was added in 8.0.14.

- Error number: `MY-013327`; Symbol: `ER_SERVER_UPGRADE_FROM_VERSION`; SQLSTATE: `HY000`

Message: MySQL server upgrading from version '%u' to '%u'.

`ER_SERVER_UPGRADE_FROM_VERSION` was added in 8.0.14.

- Error number: `MY-013328`; Symbol: `ER_GRP_RPL_ERROR_ON_CERT_DB_INSTALL`; SQLSTATE: `HY000`

Message: The certification information could not be set in this server: '%s'

`ER_GRP_RPL_ERROR_ON_CERT_DB_INSTALL` was added in 8.0.14.

- Error number: `MY-013329`; Symbol: `ER_GRP_RPL_FORCE_MEMBERS_WHEN_LEAVEING`; SQLSTATE: `HY000`

Message: A request to force a new group membership was issued when the member is leaving the group.

`ER_GRP_RPL_FORCE_MEMBERS_WHEN_LEAVEING` was added in 8.0.14.

- Error number: `MY-013330`; Symbol: `ER_TRG_WRONG_ORDER`; SQLSTATE: `HY000`

Message: Trigger %s.%s for table %s.%s is listed in wrong order. Please drop and recreate all triggers for the table.

`ER_TRG_WRONG_ORDER` was added in 8.0.14.

- Error number: `MY-013332`; Symbol: `ER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL`; SQLSTATE: `HY000`

Message: Special handling for group search, {GA} not found

`ER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL` was added in 8.0.14.

- Error number: `MY-013333`; Symbol: `ER_LDAP_AUTH_GRP_USER_OBJECT_HAS_GROUP_INFO`; SQLSTATE: `HY000`

Message: User group retrieval: User object has group information

`ER_LDAP_AUTH_GRP_USER_OBJECT_HAS_GROUP_INFO` was added in 8.0.14.

- Error number: `MY-013334`; Symbol: `ER_LDAP_AUTH_GRP_INFO_FOUND_IN_MANY_OBJECTS`; SQLSTATE: `HY000`

Message: Group information found in multiple user objects. Search filter configuration is incorrect.

`ER_LDAP_AUTH_GRP_INFO_FOUND_IN_MANY_OBJECTS` was added in 8.0.14.

- Error number: `MY-013335`; Symbol: `ER_LDAP_AUTH_GRP_INCORRECT_ATTRIBUTE`; SQLSTATE: `HY000`

Message: User group retrieval: no group attribute found. Incorrect group search attribute.

`ER_LDAP_AUTH_GRP_INCORRECT_ATTRIBUTE` was added in 8.0.14.

- Error number: `MY-013336`; Symbol: `ER_LDAP_AUTH_GRP_NULL_ATTRIBUTE_VALUE`; SQLSTATE: `HY000`

Message: User group retrieval: Group attribute values is NULL.

`ER_LDAP_AUTH_GRP_NULL_ATTRIBUTE_VALUE` was added in 8.0.14.

- Error number: `MY-013337`; Symbol: `ER_LDAP_AUTH_GRP_DN_PARSING_FAILED`; SQLSTATE: `HY000`

Message: User group retrieval: parsing DN failed.

`ER_LDAP_AUTH_GRP_DN_PARSING_FAILED` was added in 8.0.14.

- Error number: `MY-013338`; Symbol: `ER_LDAP_AUTH_GRP_OBJECT_HAS_USER_INFO`; SQLSTATE: `HY000`

Message: User group retrieval: Group object has user information

`ER_LDAP_AUTH_GRP_OBJECT_HAS_USER_INFO` was added in 8.0.14.

- Error number: `MY-013339`; Symbol: `ER_LDAP_AUTH_LDAPS`; SQLSTATE: `HY000`

Message: Reserved port for ldaps using ldaps

`ER_LDAP_AUTH_LDAPS` was added in 8.0.14.

- Error number: `MY-013340`; Symbol: `ER_LDAP_MAPPING_GET_USER_PROXY`; SQLSTATE: `HY000`

Message: Get user proxy

`ER_LDAP_MAPPING_GET_USER_PROXY` was added in 8.0.14.

- Error number: `MY-013341`; Symbol: `ER_LDAP_MAPPING_USER_DONT_BELONG_GROUP`; SQLSTATE: `HY000`

Message: Get user proxy: User doesn't belongs to any group, user name will be treated as authenticated user.

`ER_LDAP_MAPPING_USER_DONT_BELONG_GROUP` was added in 8.0.14.

- Error number: `MY-013342`; Symbol: `ER_LDAP_MAPPING_INFO`; SQLSTATE: `HY000`

Message: Get user proxy: configured mapping info: %s

`ER_LDAP_MAPPING_INFO` was added in 8.0.14.

- Error number: `MY-013343`; Symbol: `ER_LDAP_MAPPING_EMPTY_MAPPING`; SQLSTATE: `HY000`

Message: Get user proxy: User doesn't have group mapping information, First LDAP group will be treated as authenticated user.

`ER_LDAP_MAPPING_EMPTY_MAPPING` was added in 8.0.14.

- Error number: `MY-013344`; Symbol: `ER_LDAP_MAPPING_PROCESS_MAPPING`; SQLSTATE: `HY000`

Message: Process group proxy mapping

`ER_LDAP_MAPPING_PROCESS_MAPPING` was added in 8.0.14.

- Error number: MY-013345; Symbol: `ER_LDAP_MAPPING_CHECK_DELIMI_QUOTE`; SQLSTATE: HY000

Message: Check delimiter after quote

`ER_LDAP_MAPPING_CHECK_DELIMI_QUOTE` was added in 8.0.14.

- Error number: MY-013346; Symbol: `ER_LDAP_MAPPING_PROCESS_DELIMITER`; SQLSTATE: HY000

Message: Processing delimiter

`ER_LDAP_MAPPING_PROCESS_DELIMITER` was added in 8.0.14.

- Error number: MY-013347; Symbol: `ER_LDAP_MAPPING_PROCESS_DELIMITER_EQUAL_NOT_FOUND`; SQLSTATE: HY000

Message: Processing delimiter, separator = not found, resetting position

`ER_LDAP_MAPPING_PROCESS_DELIMITER_EQUAL_NOT_FOUND` was added in 8.0.14.

- Error number: MY-013348; Symbol: `ER_LDAP_MAPPING_PROCESS_DELIMITER_TRY_COMMA`; SQLSTATE: HY000

Message: "Processing delimiter, failed to get data for = separator try for separator ,."

`ER_LDAP_MAPPING_PROCESS_DELIMITER_TRY_COMMA` was added in 8.0.14.

- Error number: MY-013349; Symbol: `ER_LDAP_MAPPING_PROCESS_DELIMITER_COMMA_NOT_FOUND`; SQLSTATE: HY000

Message: Processing delimiter, separator , not found, resetting position

`ER_LDAP_MAPPING_PROCESS_DELIMITER_COMMA_NOT_FOUND` was added in 8.0.14.

- Error number: MY-013350; Symbol: `ER_LDAP_MAPPING_NO_SEPEARATOR_END_OF_GROUP`; SQLSTATE: HY000

Message: Processing delimiter: No mapping separator is found, end of group information

`ER_LDAP_MAPPING_NO_SEPEARATOR_END_OF_GROUP` was added in 8.0.14.

- Error number: MY-013351; Symbol: `ER_LDAP_MAPPING_GETTING_NEXT_MAPPING`; SQLSTATE: HY000

Message: Getting next mapping information

`ER_LDAP_MAPPING_GETTING_NEXT_MAPPING` was added in 8.0.14.

- Error number: MY-013352; Symbol: `ER_LDAP_MAPPING_PARSING_CURRENT_STATE`; SQLSTATE: HY000

Message: Parsing mapping, current state: %d delimiter char: %c

`ER_LDAP_MAPPING_PARSING_CURRENT_STATE` was added in 8.0.14.

- Error number: MY-013353; Symbol: `ER_LDAP_MAPPING_PARSING_MAPPING_INFO`; SQLSTATE: HY000

Message: Parsing mapping info, LDAP group: %s MySQL proxy: %s

`ER_LDAP_MAPPING_PARSING_MAPPING_INFO` was added in 8.0.14.

- Error number: MY-013354; Symbol: `ER_LDAP_MAPPING_PARSING_ERROR`; SQLSTATE: HY000

Message: Mapping parsing error

`ER_LDAP_MAPPING_PARSING_ERROR` was added in 8.0.14.

- Error number: `MY-013355`; Symbol: `ER_LDAP_MAPPING_TRIMMING_SPACES`; SQLSTATE: `HY000`

Message: Trimming left spaces

`ER_LDAP_MAPPING_TRIMMING_SPACES` was added in 8.0.14.

- Error number: `MY-013356`; Symbol: `ER_LDAP_MAPPING_IS_QUOTE`; SQLSTATE: `HY000`

Message: Checking if current characters is quote

`ER_LDAP_MAPPING_IS_QUOTE` was added in 8.0.14.

- Error number: `MY-013357`; Symbol: `ER_LDAP_MAPPING_NON_DESIRED_STATE`; SQLSTATE: `HY000`

Message: Not desired state or un-defined states.

`ER_LDAP_MAPPING_NON_DESIRED_STATE` was added in 8.0.14.

- Error number: `MY-013358`; Symbol: `ER_INVALID_NAMED_PIPE_FULL_ACCESS_GROUP`; SQLSTATE: `HY000`

Message: Invalid value for named_pipe_full_access_group.

`ER_INVALID_NAMED_PIPE_FULL_ACCESS_GROUP` was added in 8.0.14.

- Error number: `MY-013359`; Symbol: `ER_PREPARE_FOR_SECONDARY_ENGINE`; SQLSTATE: `HY000`

Message: Retry the statement using a secondary storage engine.

`ER_PREPARE_FOR_SECONDARY_ENGINE` was added in 8.0.16.

- Error number: `MY-013360`; Symbol: `ER_SERVER_WARN_DEPRECATED`; SQLSTATE: `HY000`

Message: '%s' is deprecated and will be removed in a future release. Please use %s instead

`ER_SERVER_WARN_DEPRECATED` was added in 8.0.16.

- Error number: `MY-013361`; Symbol:

`ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES`; SQLSTATE: `HY000`

Message: Cannot set mandatory_roles: AuthId `'%s`@`'%s` has '%s' privilege.

`ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES` was added in 8.0.16.

- Error number: `MY-013362`; Symbol:

`ER_SERVER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION`; SQLSTATE: `HY000`

Message: Unable to recover binary log master key, the combination of new_master_key_seqno=%u, master_key_seqno=%u and old_master_key_seqno=%u are wrong.

`ER_SERVER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION` was added in 8.0.16.

- Error number: `MY-013363`; Symbol:

`ER_SERVER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_AUX_KEY`; SQLSTATE: `HY000`

Message: Failed to remove auxiliary binary log encryption key from keyring, please check if keyring is loaded. The cleanup of the binary log master key rotation process did not finish as expected

and the cleanup will take place upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.

`ER_SERVER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_AUX_KEY` was added in 8.0.16.

- Error number: `MY-013368`; Symbol: `ER_TURNING_ON_PARTIAL_REVOKES`; SQLSTATE: `HY000`

Message: At least one partial revoke exists on a database. Turning ON the system variable '@@partial_revokes'.

`ER_TURNING_ON_PARTIAL_REVOKES` was added in 8.0.16.

- Error number: `MY-013369`; Symbol: `ER_WARN_PARTIAL_REVOKES_AND_DB_GRANT`; SQLSTATE: `HY000`

Message: For user '%s'@'%s', one or more privileges granted through mysql.db for database '%s', conflict with partial revoke. It could mean 'mysql' schema is corrupted.

`ER_WARN_PARTIAL_REVOKES_AND_DB_GRANT` was added in 8.0.16.

- Error number: `MY-013370`; Symbol: `ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTIONS`; SQLSTATE: `HY000`

Message: For user %s, ignored restrictions for privilege(s) '%s' for database '%s' as these are not valid database privileges.

`ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTIONS` was added in 8.0.16.

- Error number: `MY-013371`; Symbol: `ER_WARN_INVALID_DB_RESTRICTIONS`; SQLSTATE: `HY000`

Message: For user %s, ignored restrictions for privilege(s) '%s' for database '%s' as corresponding global privilege(s) are not granted.

`ER_WARN_INVALID_DB_RESTRICTIONS` was added in 8.0.16.

- Error number: `MY-013372`; Symbol: `ER_GRP_RPL_INVALID_COMMUNICATION_PROTOCOL`; SQLSTATE: `HY000`

Message: '%s' is an invalid value for group_replication_communication_protocol_join, please use a MySQL version between 5.7.14 and this server's version

`ER_GRP_RPL_INVALID_COMMUNICATION_PROTOCOL` was added in 8.0.16.

- Error number: `MY-013373`; Symbol: `ER_GRP_RPL_STARTED_AUTO_REJOIN`; SQLSTATE: `HY000`

Message: Started auto-rejoin procedure attempt %lu of %lu

`ER_GRP_RPL_STARTED_AUTO_REJOIN` was added in 8.0.16.

- Error number: `MY-013374`; Symbol: `ER_GRP_RPL_TIMEOUT_RECEIVED_VC_ON_REJOIN`; SQLSTATE: `HY000`

Message: Timeout while waiting for a view change event during the auto-rejoin procedure

`ER_GRP_RPL_TIMEOUT_RECEIVED_VC_ON_REJOIN` was added in 8.0.16.

- Error number: `MY-013375`; Symbol: `ER_GRP_RPL_FINISHED_AUTO_REJOIN`; SQLSTATE: `HY000`

Message: Auto-rejoin procedure attempt %lu of %lu finished. Member was %s able to join the group.

`ER_GRP_RPL_FINISHED_AUTO_REJOIN` was added in 8.0.16.

-
- Error number: [MY-013376](#); Symbol: [ER_GRP_RPL_DEFAULT_TABLE_ENCRYPTION_DIFF_FROM_GRP](#); SQLSTATE: [HY000](#)

Message: The member is configured with a default_table_encryption option value '%d' different from the group '%d'. The member will now exit the group.

[ER_GRP_RPL_DEFAULT_TABLE_ENCRYPTION_DIFF_FROM_GRP](#) was added in 8.0.16.
 - Error number: [MY-013377](#); Symbol: [ER_SERVER_UPGRADE_OFF](#); SQLSTATE: [HY000](#)

Message: Server shutting down because upgrade is required, yet prohibited by the command line option '--upgrade=NONE'.

[ER_SERVER_UPGRADE_OFF](#) was added in 8.0.16.
 - Error number: [MY-013378](#); Symbol: [ER_SERVER_UPGRADE_SKIP](#); SQLSTATE: [HY000](#)

Message: Server upgrade is required, but skipped by command line option '--upgrade=MINIMAL'.

[ER_SERVER_UPGRADE_SKIP](#) was added in 8.0.16.
 - Error number: [MY-013379](#); Symbol: [ER_SERVER_UPGRADE_PENDING](#); SQLSTATE: [HY000](#)

Message: Server upgrade started with version %d, but server upgrade of version %d is still pending.

[ER_SERVER_UPGRADE_PENDING](#) was added in 8.0.16.
 - Error number: [MY-013380](#); Symbol: [ER_SERVER_UPGRADE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to upgrade server.

[ER_SERVER_UPGRADE_FAILED](#) was added in 8.0.16.
 - Error number: [MY-013381](#); Symbol: [ER_SERVER_UPGRADE_STATUS](#); SQLSTATE: [HY000](#)

Message: Server upgrade from '%d' to '%d' %s.

[ER_SERVER_UPGRADE_STATUS](#) was added in 8.0.16.
 - Error number: [MY-013382](#); Symbol: [ER_SERVER_UPGRADE_REPAIR_REQUIRED](#); SQLSTATE: [HY000](#)

Message: Table '%s' requires repair.

[ER_SERVER_UPGRADE_REPAIR_REQUIRED](#) was added in 8.0.16.
 - Error number: [MY-013383](#); Symbol: [ER_SERVER_UPGRADE_REPAIR_STATUS](#); SQLSTATE: [HY000](#)

Message: Table '%s' repair %s.

[ER_SERVER_UPGRADE_REPAIR_STATUS](#) was added in 8.0.16.
 - Error number: [MY-013384](#); Symbol: [ER_SERVER_UPGRADE_INFO_FILE](#); SQLSTATE: [HY000](#)

Message: Could not open server upgrade info file '%s' for writing. Please make sure the file is writable.

[ER_SERVER_UPGRADE_INFO_FILE](#) was added in 8.0.16.
 - Error number: [MY-013385](#); Symbol: [ER_SERVER_UPGRADE_SYS_SCHEMA](#); SQLSTATE: [HY000](#)

Message: Upgrading the sys schema.

[ER_SERVER_UPGRADE_SYS_SCHEMA](#) was added in 8.0.16.

- Error number: [MY-013386](#); Symbol: [ER_SERVER_UPGRADE_MYSQL_TABLES](#); SQLSTATE: [HY000](#)

Message: Running queries to upgrade MySQL server.

[ER_SERVER_UPGRADE_MYSQL_TABLES](#) was added in 8.0.16.

- Error number: [MY-013387](#); Symbol: [ER_SERVER_UPGRADE_SYSTEM_TABLES](#); SQLSTATE: [HY000](#)

Message: Upgrading system table data.

[ER_SERVER_UPGRADE_SYSTEM_TABLES](#) was added in 8.0.16.

- Error number: [MY-013388](#); Symbol: [ER_SERVER_UPGRADE_EMPTY_SYS](#); SQLSTATE: [HY000](#)

Message: Found empty sys database. Installing the sys schema.

[ER_SERVER_UPGRADE_EMPTY_SYS](#) was added in 8.0.16.

- Error number: [MY-013389](#); Symbol: [ER_SERVER_UPGRADE_NO_SYS_VERSION](#); SQLSTATE: [HY000](#)

Message: A sys schema exists with no sys.version view. If you have a user created sys schema, this must be renamed for the upgrade to succeed.

[ER_SERVER_UPGRADE_NO_SYS_VERSION](#) was added in 8.0.16.

- Error number: [MY-013390](#); Symbol: [ER_SERVER_UPGRADE_SYS_VERSION_EMPTY](#); SQLSTATE: [HY000](#)

Message: A sys schema exists with a sys.version view, but it returns no results.

[ER_SERVER_UPGRADE_SYS_VERSION_EMPTY](#) was added in 8.0.16.

- Error number: [MY-013391](#); Symbol: [ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED](#); SQLSTATE: [HY000](#)

Message: Found outdated sys schema version %s.

[ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED](#) was added in 8.0.16.

- Error number: [MY-013392](#); Symbol: [ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE](#); SQLSTATE: [HY000](#)

Message: The sys schema is already up to date (version %s).

[ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE](#) was added in 8.0.16.

- Error number: [MY-013393](#); Symbol: [ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNT](#); SQLSTATE: [HY000](#)

Message: Found %d sys %s, but expected %d. Re-installing the sys schema.

[ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNT](#) was added in 8.0.16.

- Error number: [MY-013394](#); Symbol: [ER_SERVER_UPGRADE_CHECKING_DB](#); SQLSTATE: [HY000](#)

Message: Checking '%s' schema.

[ER_SERVER_UPGRADE_CHECKING_DB](#) was added in 8.0.16.

-
- Error number: [MY-013395](#); Symbol: [ER_IB_MSG_DDL_LOG_DELETE_BY_ID_TMCT](#); SQLSTATE: [HY000](#)

Message: Too many concurrent transactions while clearing the DDL Log. Please increase the number of Rollback Segments.

[ER_IB_MSG_DDL_LOG_DELETE_BY_ID_TMCT](#) was added in 8.0.16.

- Error number: [MY-013396](#); Symbol: [ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER](#); SQLSTATE: [HY000](#)

Message: Error in DDL Log recovery during Post-Recovery processing.

[ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER](#) was added in 8.0.16.

- Error number: [MY-013397](#); Symbol: [ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT](#); SQLSTATE: [HY000](#)

Message: Error in Post-Tablespace-Encryption during Post-Recovery processing.

[ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT](#) was added in 8.0.16.

- Error number: [MY-013398](#); Symbol: [ER_IB_MSG_DDL_LOG_FAIL_POST_DDL](#); SQLSTATE: [HY000](#)

Message: Error in DLL Log cleanup during Post-DDL processing.

[ER_IB_MSG_DDL_LOG_FAIL_POST_DDL](#) was added in 8.0.16.

- Error number: [MY-013399](#); Symbol: [ER_SERVER_BINLOG_UNSAFE_SYSTEM_FUNCTION](#); SQLSTATE: [HY000](#)

Message: '%s' statement is unsafe because it uses a system function that may return a different value on the slave.

[ER_SERVER_BINLOG_UNSAFE_SYSTEM_FUNCTION](#) was added in 8.0.16.

- Error number: [MY-013400](#); Symbol: [ER_SERVER_UPGRADE_HELP_TABLE_STATUS](#); SQLSTATE: [HY000](#)

Message: Upgrade of help tables %s.

[ER_SERVER_UPGRADE_HELP_TABLE_STATUS](#) was added in 8.0.16.

- Error number: [MY-013401](#); Symbol: [ER_GRP_RPL_SRV_GTID_WAIT_ERROR](#); SQLSTATE: [HY000](#)

Message: Error when waiting for the server to execute local transactions in order assure the group change proper logging

[ER_GRP_RPL_SRV_GTID_WAIT_ERROR](#) was added in 8.0.16.

- Error number: [MY-013402](#); Symbol: [ER_GRP_DELAYED_VCLE_LOGGING](#); SQLSTATE: [HY000](#)

Message: Unable to log the group change View log event in its exaction position in the log. This will not however affect the group replication recovery process or the overall plugin process.

[ER_GRP_DELAYED_VCLE_LOGGING](#) was added in 8.0.16.

- Error number: [MY-013404](#); Symbol: [ER_BINLOG_UNABLE_TO_ROTATE_GTID_TABLE_READONLY](#); SQLSTATE: [HY000](#)

Message: Unable to create a new binlog file: Table `mysql.gtid_executed` couldn't be opened. %s

[ER_BINLOG_UNABLE_TO_ROTATE_GTID_TABLE_READONLY](#) was added in 8.0.16.

- Error number: [MY-013405](#); Symbol: [ER_NETWORK_NAMESPACES_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Network Namespaces is not supported on this platform
[ER_NETWORK_NAMESPACES_NOT_SUPPORTED](#) was added in 8.0.16.
- Error number: [MY-013406](#); Symbol: [ER_UNKNOWN_NETWORK_NAMESPACE](#); SQLSTATE: [HY000](#)

Message: Unknown network namespace '%s'
[ER_UNKNOWN_NETWORK_NAMESPACE](#) was added in 8.0.16.
- Error number: [MY-013407](#); Symbol: [ER_NETWORK_NAMESPACE_NOT_ALLOWED_FOR_WILDCARD_ADDRESS](#); SQLSTATE: [HY000](#)

Message: Network namespace not allowed for wildcard interface address
[ER_NETWORK_NAMESPACE_NOT_ALLOWED_FOR_WILDCARD_ADDRESS](#) was added in 8.0.16.
- Error number: [MY-013408](#); Symbol: [ER_SETNS_FAILED](#); SQLSTATE: [HY000](#)

Message: setns() failed with error '%s'
[ER_SETNS_FAILED](#) was added in 8.0.16.
- Error number: [MY-013409](#); Symbol: [ER_WILDCARD_NOT_ALLOWED_FOR_MULTIADDRESS_BIND](#); SQLSTATE: [HY000](#)

Message: Wildcard address value not allowed for multivalued bind address
[ER_WILDCARD_NOT_ALLOWED_FOR_MULTIADDRESS_BIND](#) was added in 8.0.16.
- Error number: [MY-013410](#); Symbol: [ER_NETWORK_NAMESPACE_FILE_PATH_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: The path to a special network namespace file is too long. (got %u > max %u)
[ER_NETWORK_NAMESPACE_FILE_PATH_TOO_LONG](#) was added in 8.0.16.
- Error number: [MY-013411](#); Symbol: [ER_IB_MSG_TOO_LONG_PATH](#); SQLSTATE: [HY000](#)

Message: Cannot create tablespace '%s'. The filepath is too long for this OS.
[ER_IB_MSG_TOO_LONG_PATH](#) was added in 8.0.16.
- Error number: [MY-013412](#); Symbol: [ER_IB_RECV_FIRST_REC_GROUP_INVALID](#); SQLSTATE: [HY000](#)

Message: The last block of redo had corrupted first_rec_group and became fixed (%u -> %u).
[ER_IB_RECV_FIRST_REC_GROUP_INVALID](#) was added in 8.0.16.
- Error number: [MY-013413](#); Symbol: [ER_DD_UPGRADE_COMPLETED](#); SQLSTATE: [HY000](#)

Message: Data dictionary upgrade from version '%u' to '%u' completed.
[ER_DD_UPGRADE_COMPLETED](#) was added in 8.0.16.
- Error number: [MY-013414](#); Symbol: [ER_SSL_SERVER_CERT_VERIFY_FAILED](#); SQLSTATE: [HY000](#)

Message: Server SSL certificate doesn't verify: %s

`ER_SSL_SERVER_CERT_VERIFY_FAILED` was added in 8.0.16.

- Error number: `MY-013415`; Symbol: `ER_PERSIST_OPTION_USER_TRUNCATED`; SQLSTATE: `HY000`

Message: Truncated a user name for %s that was too long while reading the persisted variables file
`ER_PERSIST_OPTION_USER_TRUNCATED` was added in 8.0.16.

- Error number: `MY-013416`; Symbol: `ER_PERSIST_OPTION_HOST_TRUNCATED`; SQLSTATE: `HY000`

Message: Truncated a host name for %s that was too long while reading the persisted variables file
`ER_PERSIST_OPTION_HOST_TRUNCATED` was added in 8.0.16.

- Error number: `MY-013417`; Symbol: `ER_NET_WAIT_ERROR`; SQLSTATE: `HY000`

Message: The wait_timeout period was exceeded, the idle time since last command was too long.
`ER_NET_WAIT_ERROR` was added in 8.0.16.

- Error number: `MY-013418`; Symbol: `ER_IB_MSG_1285`; SQLSTATE: `HY000`

Message: '%s' found not encrypted while '%s' is ON. Trying to encrypt it now.
`ER_IB_MSG_1285` was added in 8.0.16.

- Error number: `MY-013419`; Symbol: `ER_IB_MSG_CLOCK_MONOTONIC_UNSUPPORTED`; SQLSTATE: `HY000`

Message: CLOCK_MONOTONIC is unsupported, so do not change the system time when MySQL is running !

`ER_IB_MSG_CLOCK_MONOTONIC_UNSUPPORTED` was added in 8.0.16.

- Error number: `MY-013420`; Symbol: `ER_IB_MSG_CLOCK_GETTIME_FAILED`; SQLSTATE: `HY000`

Message: clock_gettime() failed: %s

`ER_IB_MSG_CLOCK_GETTIME_FAILED` was added in 8.0.16.

- Error number: `MY-013421`; Symbol: `ER_PLUGIN_NOT_EARLY_DUP`; SQLSTATE: `HY000`

Message: Plugin '%s' is not to be used as an "early" plugin. Don't add it to --early-plugin-load, keyring migration etc.

`ER_PLUGIN_NOT_EARLY_DUP` was added in 8.0.16.

- Error number: `MY-013422`; Symbol: `ER_PLUGIN_NO_INSTALL_DUP`; SQLSTATE: `HY000`

Message: Plugin '%s' is marked as not dynamically installable. You have to stop the server to install it.

`ER_PLUGIN_NO_INSTALL_DUP` was added in 8.0.16.

- Error number: `MY-013425`; Symbol:

`ER_BINLOG_UNSAFE_DEFAULT_EXPRESSION_IN_SUBSTATEMENT`; SQLSTATE: `HY000`

Message: The statement is unsafe because it invokes a trigger or a stored function that modifies a table that has a column with a DEFAULT expression that may return a different value on the slave.

`ER_BINLOG_UNSAFE_DEFAULT_EXPRESSION_IN_SUBSTATEMENT` was added in 8.0.16.

- Error number: [MY-013426](#); Symbol: [ER_GRP_RPL_MEMBER_VER_READ_COMPATIBLE](#); SQLSTATE: [HY000](#)

Message: Member version is read compatible with the group.
[ER_GRP_RPL_MEMBER_VER_READ_COMPATIBLE](#) was added in 8.0.16.
- Error number: [MY-013427](#); Symbol: [ER_LOCK_ORDER_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Lock order disabled (reason: init failed).
[ER_LOCK_ORDER_INIT_FAILED](#) was added in 8.0.16.
- Error number: [MY-013428](#); Symbol: [ER_AUDIT_LOG_KEYRING_ID_TIMESTAMP_VALUE_IS_INVALID](#); SQLSTATE: [HY000](#)

Message: Keyring ID timestamp value is invalid: '%s'
[ER_AUDIT_LOG_KEYRING_ID_TIMESTAMP_VALUE_IS_INVALID](#) was added in 8.0.16.
- Error number: [MY-013429](#); Symbol: [ER_AUDIT_LOG_FILE_NAME_TIMESTAMP_VALUE_IS_MISSING_OR_INVALID](#); SQLSTATE: [HY000](#)

Message: Cannot process audit log file. File name timestamp value is missing or invalid: '%s'
[ER_AUDIT_LOG_FILE_NAME_TIMESTAMP_VALUE_IS_MISSING_OR_INVALID](#) was added in 8.0.16.
- Error number: [MY-013430](#); Symbol: [ER_AUDIT_LOG_FILE_NAME_DOES_NOT_HAVE_REQUIRED_FORMAT](#); SQLSTATE: [HY000](#)

Message: Cannot process audit log file. File name does not have required format: '%s'
[ER_AUDIT_LOG_FILE_NAME_DOES_NOT_HAVE_REQUIRED_FORMAT](#) was added in 8.0.16.
- Error number: [MY-013431](#); Symbol: [ER_AUDIT_LOG_FILE_NAME_KEYRING_ID_VALUE_IS_MISSING](#); SQLSTATE: [HY000](#)

Message: Cannot process audit log file. File name keyring ID value is missing: '%s'
[ER_AUDIT_LOG_FILE_NAME_KEYRING_ID_VALUE_IS_MISSING](#) was added in 8.0.16.
- Error number: [MY-013432](#); Symbol: [ER_AUDIT_LOG_FILE_HAS_BEEN_SUCCESSFULLY_PROCESSED](#); SQLSTATE: [HY000](#)

Message: Audit log file has been successfully processed: '%s'
[ER_AUDIT_LOG_FILE_HAS_BEEN_SUCCESSFULLY_PROCESSED](#) was added in 8.0.16.
- Error number: [MY-013433](#); Symbol: [ER_AUDIT_LOG_COULD_NOT_OPEN_FILE_FOR_READING](#); SQLSTATE: [HY000](#)

Message: Could not open audit log file for reading: '%s'
[ER_AUDIT_LOG_COULD_NOT_OPEN_FILE_FOR_READING](#) was added in 8.0.16.
- Error number: [MY-013434](#); Symbol: [ER_AUDIT_LOG_INVALID_FILE_CONTENT](#); SQLSTATE: [HY000](#)

Message: Invalid audit log file content: '%s'
[ER_AUDIT_LOG_INVALID_FILE_CONTENT](#) was added in 8.0.16.

-
- Error number: [MY-013435](#); Symbol: [ER_AUDIT_LOG_CANNOT_READ_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Cannot read password: '%s'.

[ER_AUDIT_LOG_CANNOT_READ_PASSWORD](#) was added in 8.0.16.
 - Error number: [MY-013436](#); Symbol: [ER_AUDIT_LOG_CANNOT_STORE_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Cannot store password: '%s'.

[ER_AUDIT_LOG_CANNOT_STORE_PASSWORD](#) was added in 8.0.16.
 - Error number: [MY-013437](#); Symbol: [ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Cannot remove password: '%s'.

[ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD](#) was added in 8.0.16.
 - Error number: [MY-013438](#); Symbol: [ER_AUDIT_LOG_PASSWORD_HAS_BEEN_COPIED](#); SQLSTATE: [HY000](#)

Message: 'audit_log' password has been copied into '%s' and will be removed with first purged password.

[ER_AUDIT_LOG_PASSWORD_HAS_BEEN_COPIED](#) was added in 8.0.16.
 - Error number: [MY-013447](#); Symbol: [ER_LDAP_EMPTY_USERDN_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Empty user dn or password is not allowed, not attempting LDAP bind.

[ER_LDAP_EMPTY_USERDN_PASSWORD](#) was added in 8.0.16.
 - Error number: [MY-013449](#); Symbol: [ER_ACL_WRONG_OR_MISSING_ACL_TABLES_LOG](#); SQLSTATE: [HY000](#)

Message: The current layout of the ACL tables does not conform to the server's expected layout. They're either altered, missing or not upgraded from a previous version. However a best effort attempt to read data from these tables will still be made.

[ER_ACL_WRONG_OR_MISSING_ACL_TABLES_LOG](#) was added in 8.0.17.
 - Error number: [MY-013450](#); Symbol: [ER_LOCK_ORDER_FAILED_WRITE_FILE](#); SQLSTATE: [HY000](#)

Message: LOCK_ORDER: Failed to write to file <%s>.

[ER_LOCK_ORDER_FAILED_WRITE_FILE](#) was added in 8.0.17.
 - Error number: [MY-013451](#); Symbol: [ER_LOCK_ORDER_FAILED_READ_FILE](#); SQLSTATE: [HY000](#)

Message: LOCK_ORDER: Failed to read from file <%s>.

[ER_LOCK_ORDER_FAILED_READ_FILE](#) was added in 8.0.17.
 - Error number: [MY-013452](#); Symbol: [ER_LOCK_ORDER_MESSAGE](#); SQLSTATE: [HY000](#)

Message: LOCK_ORDER message: %s

[ER_LOCK_ORDER_MESSAGE](#) was added in 8.0.17.
 - Error number: [MY-013453](#); Symbol: [ER_LOCK_ORDER_DEPENDENCIES_SYNTAX](#); SQLSTATE: [HY000](#)

Message: Lock order dependencies file <%s> (%d:%d) - (%d:%d) : %s

`ER_LOCK_ORDER_DEPENDENCIES_SYNTAX` was added in 8.0.17.

- Error number: `MY-013454`; Symbol: `ER_LOCK_ORDER_SCANNER_SYNTAX`; SQLSTATE: `HY000`

Message: Lock order scanner: (%d:%d) - (%d:%d) : %s

`ER_LOCK_ORDER_SCANNER_SYNTAX` was added in 8.0.17.

- Error number: `MY-013455`; Symbol: `ER_DATA_DIRECTORY_UNUSABLE_DELETEABLE`; SQLSTATE: `HY000`

Message: The newly created data directory %s by --initialize is unusable. You can remove it.

`ER_DATA_DIRECTORY_UNUSABLE_DELETEABLE` was added in 8.0.17.

- Error number: `MY-013456`; Symbol: `ER_IB_MSG_BTREE_LEVEL_LIMIT_EXCEEDED`; SQLSTATE: `HY000`

Message: No. of B-tree level created for index %s has crossed the permissible limit. If debug option `innodb_limit_optimistic_insert_debug` is being used try tweaking it to include more records in a page.

`ER_IB_MSG_BTREE_LEVEL_LIMIT_EXCEEDED` was added in 8.0.17.

- Error number: `MY-013457`; Symbol: `ER_IB_CLONE_START_STOP`; SQLSTATE: `HY000`

Message: %s

`ER_IB_CLONE_START_STOP` was added in 8.0.17.

- Error number: `MY-013458`; Symbol: `ER_IB_CLONE_OPERATION`; SQLSTATE: `HY000`

Message: %s

`ER_IB_CLONE_OPERATION` was added in 8.0.17.

- Error number: `MY-013459`; Symbol: `ER_IB_CLONE_RESTART`; SQLSTATE: `HY000`

Message: %s

`ER_IB_CLONE_RESTART` was added in 8.0.17.

- Error number: `MY-013460`; Symbol: `ER_IB_CLONE_USER_DATA`; SQLSTATE: `HY000`

Message: Clone removing all user data for provisioning: %s

`ER_IB_CLONE_USER_DATA` was added in 8.0.17.

- Error number: `MY-013461`; Symbol: `ER_IB_CLONE_NON_INNODB_TABLE`; SQLSTATE: `HY000`

Message: Non innodb table: %s.%s is not cloned and is empty.

`ER_IB_CLONE_NON_INNODB_TABLE` was added in 8.0.17.

- Error number: `MY-013462`; Symbol: `ER_CLONE_SHUTDOWN_TRACE`; SQLSTATE: `HY000`

Message: Clone shutting down server as RESTART failed. Please start server to complete clone operation.

`ER_CLONE_SHUTDOWN_TRACE` was added in 8.0.17.

-
- Error number: [MY-013463](#); Symbol: [ER_GRP_RPL_GTID_PURGED_EXTRACT_ERROR](#); SQLSTATE: [HY000](#)

Message: Error when extracting this member GTID purged set. Operations and checks made to group joiners may be incomplete.

[ER_GRP_RPL_GTID_PURGED_EXTRACT_ERROR](#) was added in 8.0.17.

- Error number: [MY-013464](#); Symbol: [ER_GRP_RPL_CLONE_PROCESS_PREPARE_ERROR](#); SQLSTATE: [HY000](#)

Message: There was an issue when configuring the remote cloning process: %s

[ER_GRP_RPL_CLONE_PROCESS_PREPARE_ERROR](#) was added in 8.0.17.

- Error number: [MY-013465](#); Symbol: [ER_GRP_RPL_CLONE_PROCESS_EXEC_ERROR](#); SQLSTATE: [HY000](#)

Message: There was an issue when cloning from another server: %s

[ER_GRP_RPL_CLONE_PROCESS_EXEC_ERROR](#) was added in 8.0.17.

- Error number: [MY-013466](#); Symbol: [ER_GRP_RPL_RECOVERY_EVAL_ERROR](#); SQLSTATE: [HY000](#)

Message: There was an issue when trying to evaluate the best distributed recovery strategy while joining.%s

[ER_GRP_RPL_RECOVERY_EVAL_ERROR](#) was added in 8.0.17.

- Error number: [MY-013467](#); Symbol: [ER_GRP_RPL_NO_POSSIBLE_RECOVERY](#); SQLSTATE: [HY000](#)

Message: No valid or ONLINE members exist to get the missing data from the group. For cloning check if donors of the same version and with clone plugin installed exist. For incremental recovery check if you have donors where the required data was not purged from the binary logs.

[ER_GRP_RPL_NO_POSSIBLE_RECOVERY](#) was added in 8.0.17.

- Error number: [MY-013468](#); Symbol: [ER_GRP_RPL_CANT_KILL_THREAD](#); SQLSTATE: [HY000](#)

Message: The group replication plugin could not kill the plugin routine for %s. %s

[ER_GRP_RPL_CANT_KILL_THREAD](#) was added in 8.0.17.

- Error number: [MY-013469](#); Symbol: [ER_GRP_RPL_RECOVERY_STRAT_CLONE_THRESHOLD](#); SQLSTATE: [HY000](#)

Message: This member will start distributed recovery using clone. It is due to the number of missing transactions being higher than the configured threshold of %llu.

[ER_GRP_RPL_RECOVERY_STRAT_CLONE_THRESHOLD](#) was added in 8.0.17.

- Error number: [MY-013470](#); Symbol: [ER_GRP_RPL_RECOVERY_STRAT_CLONE_PURGED](#); SQLSTATE: [HY000](#)

Message: This member will start distributed recovery using clone. It is due to no ONLINE member has the missing data for recovering in its binary logs.

[ER_GRP_RPL_RECOVERY_STRAT_CLONE_PURGED](#) was added in 8.0.17.

- Error number: [MY-013471](#); Symbol: [ER_GRP_RPL_RECOVERY_STRAT_CHOICE](#); SQLSTATE: [HY000](#)

Message: Distributed recovery will transfer data using: %s

`ER_GRP_RPL_RECOVERY_STRAT_CHOICE` was added in 8.0.17.

- Error number: `MY-013472`; Symbol: `ER_GRP_RPL_RECOVERY_STRAT_FALLBACK`; SQLSTATE: `HY000`

Message: Due to some issue on the previous step distributed recovery is now executing: %s

`ER_GRP_RPL_RECOVERY_STRAT_FALLBACK` was added in 8.0.17.

- Error number: `MY-013473`; Symbol: `ER_GRP_RPL_RECOVERY_STRAT_NO_FALLBACK`; SQLSTATE: `HY000`

Message: Due to a critical cloning error or lack of donors, distributed recovery cannot be executed. The member will now leave the group.

`ER_GRP_RPL_RECOVERY_STRAT_NO_FALLBACK` was added in 8.0.17.

- Error number: `MY-013474`; Symbol: `ER_GRP_RPL_SLAVE_THREAD_ERROR_ON_CLONE`; SQLSTATE: `HY000`

Message: The '%s' thread of channel '%s' will error out as the server will attempt to clone another server

`ER_GRP_RPL_SLAVE_THREAD_ERROR_ON_CLONE` was added in 8.0.17.

- Error number: `MY-013475`; Symbol: `ER_UNKNOWN_TABLE_IN_UPGRADE`; SQLSTATE: `HY000`

Message: Unknown table '%s'

`ER_UNKNOWN_TABLE_IN_UPGRADE` was added in 8.0.17.

- Error number: `MY-013476`; Symbol: `ER_IDENT_CAUSES_TOO_LONG_PATH_IN_UPGRADE`; SQLSTATE: `HY000`

Message: Long database name and identifier for object resulted in path length exceeding %d characters. Path: '%s'.

`ER_IDENT_CAUSES_TOO_LONG_PATH_IN_UPGRADE` was added in 8.0.17.

- Error number: `MY-013477`; Symbol: `ER_XA_CANT_CREATE_MDL_BACKUP`; SQLSTATE: `HY000`

Message: XA: Failed to take MDL Lock backup of PREPARED XA transaction during client disconnect.

`ER_XA_CANT_CREATE_MDL_BACKUP` was added in 8.0.13.

- Error number: `MY-013478`; Symbol: `ER_AUDIT_LOG_SUPER_PRIVILEGE_REQUIRED`; SQLSTATE: `HY000`

Message: SUPER privilege or AUDIT_ADMIN role required for '%s'@'%s' user.

`ER_AUDIT_LOG_SUPER_PRIVILEGE_REQUIRED` was added in 8.0.11.

- Error number: `MY-013479`; Symbol: `ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_TYPE`; SQLSTATE: `HY000`

Message: Invalid argument type

`ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_TYPE` was added in 8.0.11.

- Error number: `MY-013480`; Symbol: `ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_COUNT`; SQLSTATE: `HY000`

Message: Invalid argument count

`ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_COUNT` was added in 8.0.11.

- Error number: `MY-013481`; Symbol: `ER_AUDIT_LOG_HAS_NOT_BEEN_INSTALLED`; SQLSTATE: `HY000`

Message: audit_log plugin has not been installed using INSTALL PLUGIN syntax.

`ER_AUDIT_LOG_HAS_NOT_BEEN_INSTALLED` was added in 8.0.11.

- Error number: `MY-013482`; Symbol: `ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH_ARG_TYPE`; SQLSTATE: `HY000`

Message: Invalid "max_array_length" argument type.

`ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH_ARG_TYPE` was added in 8.0.11.

- Error number: `MY-013483`; Symbol: `ER_LOG_CANNOT_WRITE_EXTENDED`; SQLSTATE: `HY000`

Message: Failed to write to %s: %s (%s)

`ER_LOG_CANNOT_WRITE_EXTENDED` was added in 8.0.17.

- Error number: `MY-013484`; Symbol: `ER_UPGRADE_WITH_PARTITIONED_TABLES_REJECTED`; SQLSTATE: `HY000`

Message: Upgrading from server version %d with partitioned tables and lower_case_table_names == 1 on a case sensitive file system may cause issues, and is therefore prohibited. To upgrade anyway, restart the new server version with the command line option 'upgrade=FORCE'. When upgrade is completed, please execute 'RENAME TABLE <part_table_name> TO <new_table_name>; RENAME TABLE <new_table_name> TO <part_table_name>;' for each of the partitioned tables. Please see the documentation for further information.

`ER_UPGRADE_WITH_PARTITIONED_TABLES_REJECTED` was added in 8.0.17, removed after 8.0.18.

- Error number: `MY-013485`; Symbol: `ER_KEYRING_AWS_INCORRECT_PROXY`; SQLSTATE: `HY000`

Message: Incorrect environment variable %s, invalid port: %s

`ER_KEYRING_AWS_INCORRECT_PROXY` was added in 8.0.18.

- Error number: `MY-013486`; Symbol: `ER_GRP_RPL_SERVER_SET_TO_OFFLINE_MODE_DUE_TO_ERRORS`; SQLSTATE: `HY000`

Message: The server was automatically set into offline mode after an error was detected.

`ER_GRP_RPL_SERVER_SET_TO_OFFLINE_MODE_DUE_TO_ERRORS` was added in 8.0.18.

- Error number: `MY-013487`; Symbol: `ER_GRP_RPL_MESSAGE_SERVICE_FATAL_ERROR`; SQLSTATE: `HY000`

Message: A message sent through the Group Replication message deliver service was not delivered successfully. The server will now leave the group. Try to add the server back to the group and check if the problem persists, or check previous messages in the log for hints of what could be the problem.

`ER_GRP_RPL_MESSAGE_SERVICE_FATAL_ERROR` was added in 8.0.18.

-
- Error number: [MY-013488](#); Symbol: [ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOG](#); SQLSTATE: [HY000](#)

Message: Invalid MASTER_COMPRESSION_ALGORITHMS '%s' found in repository for channel '%s'. Resetting to 'uncompressed' (no compression).

[ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOG](#) was added in 8.0.18.

- Error number: [MY-013489](#); Symbol: [ER_WARN_WRONG_COMPRESSION_LEVEL_LOG](#); SQLSTATE: [HY000](#)

Message: Invalid MASTER_ZSTD_COMPRESSION_LEVEL found in repository for channel '%s'. Resetting to %u.

[ER_WARN_WRONG_COMPRESSION_LEVEL_LOG](#) was added in 8.0.18.

- Error number: [MY-013490](#); Symbol: [ER_PROTOCOL_COMPRESSION_RESET_LOG](#); SQLSTATE: [HY000](#)

Message: Option --protocol-compression-algorithms is reset to default value.

[ER_PROTOCOL_COMPRESSION_RESET_LOG](#) was added in 8.0.18.

- Error number: [MY-013491](#); Symbol: [ER_XPLUGIN_COMPRESSION_ERROR](#); SQLSTATE: [HY000](#)

Message: Fatal error while compressing outgoing data - %s

[ER_XPLUGIN_COMPRESSION_ERROR](#) was added in 8.0.18.

- Error number: [MY-013492](#); Symbol: [ER_MYSQLBACKUP_MSG](#); SQLSTATE: [HY000](#)

Message: %s

[ER_MYSQLBACKUP_MSG](#) was added in 8.0.18.

- Error number: [MY-013493](#); Symbol: [ER_WARN_UNKNOWN_KEYRING_AWS_REGION](#); SQLSTATE: [HY000](#)

Message: Unknown keyring_aws_region '%s'. Connection to AWS KMS may fail.

[ER_WARN_UNKNOWN_KEYRING_AWS_REGION](#) was added in 8.0.18.

- Error number: [MY-013494](#); Symbol: [ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST](#); SQLSTATE: [HY000](#)

Message: PRIVILEGE_CHECKS_USER for replication channel '%s' was set to `'%s`@`%s`', but this is not an existing user. Correct this before starting replication threads.

[ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST](#) was added in 8.0.18.

- Error number: [MY-013495](#); Symbol: [ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPT](#); SQLSTATE: [HY000](#)

Message: Invalid, corrupted PRIVILEGE_CHECKS_USER was found in the replication configuration repository for channel '%s'. Use CHANGE MASTER TO PRIVILEGE_CHECKS_USER to correct the configuration.

[ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPT](#) was added in 8.0.18.

-
- Error number: [MY-013496](#); Symbol: [ER_WARN_LOG_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPLIER_PRIV](#); SQLSTATE: [HY000](#)

Message: PRIVILEGE_CHECKS_USER for replication channel '%s' was set to `'%s`@`%s`, but this user does not have REPLICATION_APPLIER privilege. Correct this before starting the replication threads.

[ER_WARN_LOG_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPLIER_PRIV](#) was added in 8.0.18.
 - Error number: [MY-013497](#); Symbol: [ER_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS](#); SQLSTATE: [HY000](#)

Message: The PRIVILEGE_CHECKS_USER for channel '%s' would need FILE privilege to execute a LOAD DATA INFILE statement replicated in statement format. Consider using binlog_format=ROW on master. If the replicated events are trusted, recover from the failure by temporarily granting FILE to the PRIVILEGE_CHECKS_USER.

[ER_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS](#) was added in 8.0.18.
 - Error number: [MY-013498](#); Symbol: [ER_RPL_SLAVE_SQL_THREAD_STARTING_WITH_PRIVILEGE_CHECKS](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread%s initialized, starting replication in log '%s' at position %s, relay log '%s' position: %s, user: '%s'@'%s', roles: %s

[ER_RPL_SLAVE_SQL_THREAD_STARTING_WITH_PRIVILEGE_CHECKS](#) was added in 8.0.18.
 - Error number: [MY-013499](#); Symbol: [ER_AUDIT_LOG_CANNOT_GENERATE_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Cannot generate password: '%s'

[ER_AUDIT_LOG_CANNOT_GENERATE_PASSWORD](#) was added in 8.0.18.
 - Error number: [MY-013500](#); Symbol: [ER_INIT_FAILED_TO_GENERATE_ROOT_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Failed to generate a random password for root. Probabably not enough entropy.

[ER_INIT_FAILED_TO_GENERATE_ROOT_PASSWORD](#) was added in 8.0.18.
 - Error number: [MY-013501](#); Symbol: [ER_PLUGIN_LOAD_OPTIONS_IGNORED](#); SQLSTATE: [HY000](#)

Message: Ignoring --plugin-load[_add] list as the server is running with --initialize(-insecure).

[ER_PLUGIN_LOAD_OPTIONS_IGNORED](#) was added in 8.0.18.
 - Error number: [MY-013502](#); Symbol: [ER_WARN_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES](#); SQLSTATE: [HY000](#)

Message: Cannot set mandatory_roles: AuthId `'%s`@`%s` has '%s' privilege. AuthId(s) set in the mandatory_roles are ignored.

[ER_WARN_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES](#) was added in 8.0.18.
 - Error number: [MY-013503](#); Symbol: [ER_IB_MSG_SKIP_HIDDEN_DIR](#); SQLSTATE: [HY000](#)

Message: Directory '%s' will not be scanned because it is a hidden directory.

[ER_IB_MSG_SKIP_HIDDEN_DIR](#) was added in 8.0.18.
 - Error number: [MY-013504](#); Symbol: [ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_MASTER_EOF](#); SQLSTATE: [HY000](#)

Message: Server was not able to find a rotate event from master server to initialize relay log recovery for channel '%s'. Skipping relay log recovery for the channel.

`ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_MASTER_EOF` was added in 8.0.19.

- Error number: `MY-013505`; Symbol: `ER_IB_LOB_ROLLBACK_INDEX_LEN`; SQLSTATE: `HY000`

Message: Rolling back LOB for transaction %llu undo number %llu : current index length %llu.
(iteration %llu)

`ER_IB_LOB_ROLLBACK_INDEX_LEN` was added in 8.0.19.

- Error number: `MY-013506`; Symbol:
`ER_CANT_PROCESS_EXPRESSION_FOR_GENERATED_COLUMN_TO_DD`; SQLSTATE: `HY000`

Message: Error in processing (possibly deprecated) expression or function '%s' for generated column %s.%s.%s

`ER_CANT_PROCESS_EXPRESSION_FOR_GENERATED_COLUMN_TO_DD` was added in 8.0.19.

- Error number: `MY-013507`; Symbol:
`ER_RPL_SLAVE_QUEUE_EVENT_FAILED_INVALID_NON_ROW_FORMAT`; SQLSTATE: `HY000`

Message: The queue event failed for channel '%s' as an invalid event according to
REQUIRE_ROW_FORMAT was found.

`ER_RPL_SLAVE_QUEUE_EVENT_FAILED_INVALID_NON_ROW_FORMAT` was added in 8.0.19.

- Error number: `MY-013508`; Symbol:
`ER_RPL_SLAVE_APPLY_LOG_EVENT_FAILED_INVALID_NON_ROW_FORMAT`; SQLSTATE: `HY000`

Message: The application of relay events failed for channel '%s' as an invalid event according to
REQUIRE_ROW_FORMAT was found.

`ER_RPL_SLAVE_APPLY_LOG_EVENT_FAILED_INVALID_NON_ROW_FORMAT` was added in 8.0.19.

- Error number: `MY-013509`; Symbol: `ER_LOG_PRIV_CHECKS_REQUIRE_ROW_FORMAT_NOT_SET`;
SQLSTATE: `HY000`

Message: PRIVILEGE_CHECKS_USER for replication channel '%s' can't be set to `'%s`@`%s`
unless REQUIRE_ROW_FORMAT is also set to %d.

`ER_LOG_PRIV_CHECKS_REQUIRE_ROW_FORMAT_NOT_SET` was added in 8.0.19.

- Error number: `MY-013510`; Symbol:
`ER_RPL_SLAVE_SQL_THREAD_DETECTED_UNEXPECTED_EVENT_SEQUENCE`; SQLSTATE: `HY000`

Message: An unexpected event sequence was detected by the SQL thread while applying an event.

`ER_RPL_SLAVE_SQL_THREAD_DETECTED_UNEXPECTED_EVENT_SEQUENCE` was added in 8.0.19.

- Error number: `MY-013511`; Symbol: `ER_IB_MSG_UPGRADE_PARTITION_FILE`; SQLSTATE:
`HY000`

Message: Updating partition file name '%s' to '%s' and all other partition files during upgrade

`ER_IB_MSG_UPGRADE_PARTITION_FILE` was added in 8.0.19.

- Error number: `MY-013512`; Symbol: `ER_IB_MSG_DOWNGRADE_PARTITION_FILE`; SQLSTATE:
`HY000`

Message: Updating partition file name '%s' to '%s' and all other partition files during downgrade

`ER_IB_MSG_DOWNGRADE_PARTITION_FILE` was added in 8.0.19.

- Error number: `MY-013513`; Symbol: `ER_IB_MSG_UPGRADE_PARTITION_FILE_IMPORT`; SQLSTATE: `HY000`

Message: Updating partition file name '%s' to '%s' for import

`ER_IB_MSG_UPGRADE_PARTITION_FILE_IMPORT` was added in 8.0.19.

- Error number: `MY-013514`; Symbol: `ER_IB_WARN_OPEN_PARTITION_FILE`; SQLSTATE: `HY000`

Message: Unable to open partition file with new name '%s'. Please check if innodb_directories is set to include all external file paths

`ER_IB_WARN_OPEN_PARTITION_FILE` was added in 8.0.19.

- Error number: `MY-013515`; Symbol: `ER_IB_MSG_FIL_STATE_MOVED_CORRECTED`; SQLSTATE: `HY000`

Message: %s DD ID: %lu - Partition tablespace %u, name '%s' is corrected to '%s'

`ER_IB_MSG_FIL_STATE_MOVED_CORRECTED` was added in 8.0.19.

- Error number: `MY-013516`; Symbol: `ER_IB_MSG_FIL_STATE_MOVED_CHANGED_PATH`; SQLSTATE: `HY000`

Message: %s DD ID: %lu - Tablespace %u, name '%s', '%s' is moved to '%s'

`ER_IB_MSG_FIL_STATE_MOVED_CHANGED_PATH` was added in 8.0.19.

- Error number: `MY-013517`; Symbol: `ER_IB_MSG_FIL_STATE_MOVED_CHANGED_NAME`; SQLSTATE: `HY000`

Message: %s DD ID: %lu - Partition tablespace %u, name '%s', '%s' is updated to '%s'

`ER_IB_MSG_FIL_STATE_MOVED_CHANGED_NAME` was added in 8.0.19.

- Error number: `MY-013518`; Symbol: `ER_IB_MSG_FIL_STATE_MOVED_TOO_MANY`; SQLSTATE: `HY000`

Message: %s Too many files have been moved, disabling logging of detailed messages

`ER_IB_MSG_FIL_STATE_MOVED_TOO_MANY` was added in 8.0.19.

- Error number: `MY-013519`; Symbol: `ER_GR_ELECTED_PRIMARY_GTID_INFORMATION`; SQLSTATE: `HY000`

Message: Elected primary member %s: %s

`ER_GR_ELECTED_PRIMARY_GTID_INFORMATION` was added in 8.0.19.

- Error number: `MY-013520`; Symbol: `ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED`; SQLSTATE: `HY000`

Message: Schema name '%s' containing upper case characters is not allowed with lower_case_table_names = 1.

`ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED` was added in 8.0.19.

- Error number: [MY-013521](#); Symbol: [ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED](#); SQLSTATE: [HY000](#)

Message: Table name '%s.%s' containing upper case characters is not allowed with lower_case_table_names = 1.

[ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED](#) was added in 8.0.19.

- Error number: [MY-013522](#); Symbol: [ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_FK](#); SQLSTATE: [HY000](#)

Message: Schema name '%s' containing upper case characters, used by foreign key '%s' in table '%s.%s', is not allowed with lower_case_table_names = 1.

[ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_FK](#) was added in 8.0.19.

- Error number: [MY-013523](#); Symbol: [ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_FK](#); SQLSTATE: [HY000](#)

Message: Table name '%s.%s' containing upper case characters, used by foreign key '%s' in table '%s.%s', is not allowed with lower_case_table_names = 1.

[ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_FK](#) was added in 8.0.19.

- Error number: [MY-013524](#); Symbol: [ER_IB_MSG_DICT_PARTITION_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Table Partition: %s is not found in InnoDB dictionary

[ER_IB_MSG_DICT_PARTITION_NOT_FOUND](#) was added in 8.0.19.

- Error number: [MY-013525](#); Symbol: [ER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY_PASSWORD_LOCK](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s'. Account is blocked for %s day(s) (%s day(s) remaining) due to %u consecutive failed logins. Use FLUSH PRIVILEGES or ALTER USER to reset.

[ER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY_PASSWORD_LOCK](#) was added in 8.0.19.

- Error number: [MY-013526](#); Symbol: [ER_INNODB_OUT_OF_RESOURCES](#); SQLSTATE: [HY000](#)

Message: %s

[ER_INNODB_OUT_OF_RESOURCES](#) was added in 8.0.19.

- Error number: [MY-013527](#); Symbol: [ER_DD_UPGRADE_FOUND_PREPARED_XA_TRANSACTION](#); SQLSTATE: [HY000](#)

Message: Upgrade cannot proceed due to an existing prepared XA transaction.

[ER_DD_UPGRADE_FOUND_PREPARED_XA_TRANSACTION](#) was added in 8.0.19.

- Error number: [MY-013528](#); Symbol: [ER_MIGRATE_TABLE_TO_DD_OOM](#); SQLSTATE: [HY000](#)

Message: Could not allocate memory for key_info when migrating table %s.%s

[ER_MIGRATE_TABLE_TO_DD_OOM](#) was added in 8.0.19.

-
- Error number: [MY-013529](#); Symbol: [ER_RPL_RELAY_LOG_RECOVERY_INFO_AFTER_CLONE](#); SQLSTATE: [HY000](#)

Message: Relay log information for channel '%s' was found after a clone operation. Relay log recovery will be executed to adjust positions and file information for this new server. Should that automatic procedure fail please adjust the positions through 'CHANGE MASTER TO'

[ER_RPL_RELAY_LOG_RECOVERY_INFO_AFTER_CLONE](#) was added in 8.0.19.
 - Error number: [MY-013530](#); Symbol: [ER_IB_MSG_57_UNDO_SPACE_DELETE_FAIL](#); SQLSTATE: [HY000](#)

Message: Failed to delete 5.7 undo tablespace: %s during upgrade

[ER_IB_MSG_57_UNDO_SPACE_DELETE_FAIL](#) was added in 8.0.19.
 - Error number: [MY-013531](#); Symbol: [ER_IB_MSG_DBWR_1285](#); SQLSTATE: [HY000](#)

Message: Empty doublewrite file: %s

[ER_IB_MSG_DBWR_1285](#) was added in 8.0.20.
 - Error number: [MY-013532](#); Symbol: [ER_IB_MSG_DBWR_1286](#); SQLSTATE: [HY000](#)

Message: Using '%s' for doublewrite

[ER_IB_MSG_DBWR_1286](#) was added in 8.0.20.
 - Error number: [MY-013533](#); Symbol: [ER_IB_MSG_DBWR_1287](#); SQLSTATE: [HY000](#)

Message: Error reading doublewrite buffer from the system tablespace

[ER_IB_MSG_DBWR_1287](#) was added in 8.0.20.
 - Error number: [MY-013534](#); Symbol: [ER_IB_MSG_DBWR_1288](#); SQLSTATE: [HY000](#)

Message: Cannot create doublewrite buffer: you must increase your buffer pool size. Cannot continue operation.

[ER_IB_MSG_DBWR_1288](#) was added in 8.0.20.
 - Error number: [MY-013535](#); Symbol: [ER_IB_MSG_DBWR_1290](#); SQLSTATE: [HY000](#)

Message: The page in the doublewrite file is corrupt. Cannot continue operation. You can try to recover the database with innodb_force_recovery=6

[ER_IB_MSG_DBWR_1290](#) was added in 8.0.20.
 - Error number: [MY-013536](#); Symbol: [ER_IB_MSG_DBWR_1291](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_DBWR_1291](#) was added in 8.0.20, removed after 8.0.20.
 - Error number: [MY-013536](#); Symbol: [ER_IB_MSG_BAD_DBWR_FILE_NAME](#); SQLSTATE: [HY000](#)

Message: The doublewrite filename '%s' is incorrect.

[ER_IB_MSG_BAD_DBWR_FILE_NAME](#) was added in 8.0.21.
 - Error number: [MY-013537](#); Symbol: [ER_IB_MSG_DBWR_1292](#); SQLSTATE: [HY000](#)

Message: %s

`ER_IB_MSG_DBWR_1292` was added in 8.0.20, removed after 8.0.20.

- Error number: `MY-013538`; Symbol: `ER_IB_MSG_DBWR_1293`; SQLSTATE: `HY000`

Message: Doublewrite file create failed: %s

`ER_IB_MSG_DBWR_1293` was added in 8.0.20.

- Error number: `MY-013539`; Symbol: `ER_IB_MSG_DBWR_1294`; SQLSTATE: `HY000`

Message: DBLWRThread: pthread_setaffinity() failed!

`ER_IB_MSG_DBWR_1294` was added in 8.0.20.

- Error number: `MY-013540`; Symbol: `ER_IB_MSG_DBWR_1295`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_DBWR_1295` was added in 8.0.20.

- Error number: `MY-013541`; Symbol: `ER_IB_MSG_DBWR_1296`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_DBWR_1296` was added in 8.0.20.

- Error number: `MY-013542`; Symbol: `ER_IB_MSG_DBWR_1297`; SQLSTATE: `HY000`

Message: Doublewrite file read failed: %s

`ER_IB_MSG_DBWR_1297` was added in 8.0.20.

- Error number: `MY-013543`; Symbol: `ER_IB_MSG_DBWR_1298`; SQLSTATE: `HY000`

Message: Dump of the data file page:

`ER_IB_MSG_DBWR_1298` was added in 8.0.20.

- Error number: `MY-013544`; Symbol: `ER_IB_MSG_DBWR_1300`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_DBWR_1300` was added in 8.0.20.

- Error number: `MY-013545`; Symbol: `ER_IB_MSG_DBWR_1301`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_DBWR_1301` was added in 8.0.20.

- Error number: `MY-013546`; Symbol: `ER_IB_MSG_DBWR_1304`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_DBWR_1304` was added in 8.0.20.

- Error number: `MY-013547`; Symbol: `ER_IB_MSG_DBWR_1305`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_DBWR_1305` was added in 8.0.20.

- Error number: `MY-013548`; Symbol: `ER_IB_MSG_DBWR_1306`; SQLSTATE: `HY000`

Message: %s

[ER_IB_MSG_DBWR_1306](#) was added in 8.0.20.

- Error number: [MY-013549](#); Symbol: [ER_IB_MSG_DBWR_1307](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_DBWR_1307](#) was added in 8.0.20.

- Error number: [MY-013550](#); Symbol: [ER_IB_MSG_DBWR_1308](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_DBWR_1308](#) was added in 8.0.20.

- Error number: [MY-013551](#); Symbol: [ER_IB_MSG_DBWR_1309](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_DBWR_1309](#) was added in 8.0.20.

- Error number: [MY-013552](#); Symbol: [ER_IB_MSG_DBWR_1310](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_DBWR_1310](#) was added in 8.0.20.

- Error number: [MY-013553](#); Symbol: [ER_IB_MSG_DBWR_1311](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_DBWR_1311](#) was added in 8.0.20.

- Error number: [MY-013554](#); Symbol: [ER_IB_MSG_DBWR_1312](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_DBWR_1312](#) was added in 8.0.20.

- Error number: [MY-013555](#); Symbol: [ER_IB_MSG_DBWR_1313](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_DBWR_1313](#) was added in 8.0.20.

- Error number: [MY-013556](#); Symbol: [ER_IB_MSG_DBWR_1314](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_DBWR_1314](#) was added in 8.0.20.

- Error number: [MY-013557](#); Symbol: [ER_IB_MSG_DBWR_1315](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_DBWR_1315](#) was added in 8.0.20.

- Error number: [MY-013558](#); Symbol: [ER_IB_MSG_DBWR_1316](#); SQLSTATE: HY000

Message: %s

[ER_IB_MSG_DBWR_1316](#) was added in 8.0.20.

- Error number: MY-013559; Symbol: `ER_IB_MSG_DBWR_1317`; SQLSTATE: `HY000`

Message: %s
`ER_IB_MSG_DBWR_1317` was added in 8.0.20.
- Error number: MY-013560; Symbol: `ER_IB_MSG_DBWR_1318`; SQLSTATE: `HY000`

Message: %s
`ER_IB_MSG_DBWR_1318` was added in 8.0.20.
- Error number: MY-013561; Symbol: `ER_IB_MSG_DBWR_1319`; SQLSTATE: `HY000`

Message: Doublewrite load file %s size %lu is not a multiple of the configured page size %lu"
`ER_IB_MSG_DBWR_1319` was added in 8.0.20.
- Error number: MY-013562; Symbol: `ER_IB_MSG_DBWR_1320`; SQLSTATE: `HY000`

Message: Doublewrite file %s truncate failed
`ER_IB_MSG_DBWR_1320` was added in 8.0.20.
- Error number: MY-013563; Symbol: `ER_IB_MSG_DBWR_1321`; SQLSTATE: `HY000`

Message: Doublewrite file %s failed to writ zeros
`ER_IB_MSG_DBWR_1321` was added in 8.0.20.
- Error number: MY-013564; Symbol: `ER_IB_MSG_DBWR_1322`; SQLSTATE: `HY000`

Message: Doublewrite create file %s size %lu is not a multiple of the configured page size %lu"
`ER_IB_MSG_DBWR_1322` was added in 8.0.20.
- Error number: MY-013565; Symbol: `ER_IB_MSG_DBWR_1323`; SQLSTATE: `HY000`

Message: %s
`ER_IB_MSG_DBWR_1323` was added in 8.0.20.
- Error number: MY-013566; Symbol: `ER_IB_MSG_DBWR_1324`; SQLSTATE: `HY000`

Message: %s
`ER_IB_MSG_DBWR_1324` was added in 8.0.20.
- Error number: MY-013567; Symbol: `ER_IB_MSG_DBWR_1325`; SQLSTATE: `HY000`

Message: %s
`ER_IB_MSG_DBWR_1325` was added in 8.0.20.
- Error number: MY-013568; Symbol: `ER_IB_MSG_DBWR_1326`; SQLSTATE: `HY000`

Message: %s
`ER_IB_MSG_DBWR_1326` was added in 8.0.20.
- Error number: MY-013569; Symbol: `ER_IB_MSG_DBWR_1327`; SQLSTATE: `HY000`

Message: %s
`ER_IB_MSG_DBWR_1327` was added in 8.0.20.

- Error number: [MY-013570](#); Symbol: [ER_IB_MSG_GTID_FLUSH_AT_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: Could not flush all GTIDs during slow shutdown. Will recover GTIDs when server restarts.
[ER_IB_MSG_GTID_FLUSH_AT_SHUTDOWN](#) was added in 8.0.20.
- Error number: [MY-013571](#); Symbol: [ER_IB_MSG_57_STAT_SPACE_DELETE_FAIL](#); SQLSTATE: [HY000](#)

Message: Failed to delete 5.7 stat tablespace: %s during upgrade
[ER_IB_MSG_57_STAT_SPACE_DELETE_FAIL](#) was added in 8.0.20.
- Error number: [MY-013572](#); Symbol: [ER_NDBINFO_UPGRADING_SCHEMA](#); SQLSTATE: [HY000](#)

Message: Installing ndbinfo schema version %s
[ER_NDBINFO_UPGRADING_SCHEMA](#) was added in 8.0.20.
- Error number: [MY-013573](#); Symbol: [ER_NDBINFO_NOT_UPGRADING_SCHEMA](#); SQLSTATE: [HY000](#)

Message: Installed ndbinfo schema is current. Not upgrading.
[ER_NDBINFO_NOT_UPGRADING_SCHEMA](#) was added in 8.0.20.
- Error number: [MY-013574](#); Symbol: [ER_NDBINFO_UPGRADING_SCHEMA_FAIL](#); SQLSTATE: [HY000](#)

Message: Failed to upgrade ndbinfo schema.
[ER_NDBINFO_UPGRADING_SCHEMA_FAIL](#) was added in 8.0.20.
- Error number: [MY-013575](#); Symbol: [ER_IB_MSG_CREATE_LOG_FILE](#); SQLSTATE: [HY000](#)

Message: Creating log file %s
[ER_IB_MSG_CREATE_LOG_FILE](#) was added in 8.0.20.
- Error number: [MY-013576](#); Symbol: [ER_IB_MSG_INNODB_START_INITIALIZE](#); SQLSTATE: [HY000](#)

Message: InnoDB initialization has started.
[ER_IB_MSG_INNODB_START_INITIALIZE](#) was added in 8.0.20.
- Error number: [MY-013577](#); Symbol: [ER_IB_MSG_INNODB_END_INITIALIZE](#); SQLSTATE: [HY000](#)

Message: InnoDB initialization has ended.
[ER_IB_MSG_INNODB_END_INITIALIZE](#) was added in 8.0.20.
- Error number: [MY-013578](#); Symbol: [ER_IB_MSG_PAGE_ARCH_NO_RESET_POINTS](#); SQLSTATE: [HY000](#)

Message: Could not find appropriate reset points.
[ER_IB_MSG_PAGE_ARCH_NO_RESET_POINTS](#) was added in 8.0.20.
- Error number: [MY-013579](#); Symbol: [ER_IB_WRN_PAGE_ARCH_FLUSH_DATA](#); SQLSTATE: [HY000](#)

Message: Unable to flush. Page archiving data may be corrupt in case of a crash.
[ER_IB_WRN_PAGE_ARCH_FLUSH_DATA](#) was added in 8.0.20.

-
- Error number: [MY-013580](#); Symbol: [ER_IB_ERR_PAGE_ARCH_INVALID_DOUBLE_WRITE_BUF](#); SQLSTATE: [HY000](#)

Message: Page archiver's doublewrite buffer for %ld is not valid.

[ER_IB_ERR_PAGE_ARCH_INVALID_DOUBLE_WRITE_BUF](#) was added in 8.0.20.

- Error number: [MY-013581](#); Symbol: [ER_IB_ERR_PAGE_ARCH_RECOVERY_FAILED](#); SQLSTATE: [HY000](#)

Message: Page archiver system's recovery failed.

[ER_IB_ERR_PAGE_ARCH_RECOVERY_FAILED](#) was added in 8.0.20.

- Error number: [MY-013582](#); Symbol: [ER_IB_ERR_PAGE_ARCH_INVALID_FORMAT](#); SQLSTATE: [HY000](#)

Message: Invalid archived file name format. The archived file is supposed to have the format %s + [0-9]*.

[ER_IB_ERR_PAGE_ARCH_INVALID_FORMAT](#) was added in 8.0.20.

- Error number: [MY-013583](#); Symbol: [ER_INVALID_XPLUGIN_SOCKET_SAME_AS_SERVER](#); SQLSTATE: [HY000](#)

Message: X Plugins UNIX socket must use different file than MySQL server. X Plugin won't be accessible through UNIX socket

[ER_INVALID_XPLUGIN_SOCKET_SAME_AS_SERVER](#) was added in 8.0.20.

- Error number: [MY-013584](#); Symbol: [ER_INNODB_UNABLE_TO_ACQUIRE_DD_OBJECT](#); SQLSTATE: [HY000](#)

Message: %s

[ER_INNODB_UNABLE_TO_ACQUIRE_DD_OBJECT](#) was added in 8.0.20.

- Error number: [MY-013585](#); Symbol: [ER_WARN_LOG_DEPRECATED_PARTITION_PREFIX_KEY](#); SQLSTATE: [HY000](#)

Message: Column '%s.%s.%s' having prefix key part '%s(%u)' is ignored by the partitioning function. Use of prefixed columns in the PARTITION BY KEY() clause is deprecated and will be removed in a future release.

[ER_WARN_LOG_DEPRECATED_PARTITION_PREFIX_KEY](#) was added in 8.0.21.

- Error number: [MY-013586](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_TOO_OFTEN](#); SQLSTATE: [HY000](#)

Message: Undo Truncation is occurring too often. Consider increasing --innodb-max-undo-log-size.

[ER_IB_MSG_UNDO_TRUNCATE_TOO_OFTEN](#) was added in 8.0.21.

- Error number: [MY-013587](#); Symbol: [ER_GRP_RPL_IS_STARTING](#); SQLSTATE: [HY000](#)

Message: Plugin 'group_replication' is starting.

[ER_GRP_RPL_IS_STARTING](#) was added in 8.0.21.

- Error number: [MY-013588](#); Symbol: [ER_IB_MSG_INVALID_LOCATION_FOR_TABLESPACE](#); SQLSTATE: [HY000](#)

Message: Cannot create tablespace %s because the directory is not a valid location. %s

`ER_IB_MSG_INVALID_LOCATION_FOR_TABLESPACE` was added in 8.0.21.

- Error number: `MY-013589`; Symbol: `ER_IB_MSG_INVALID_LOCATION_WRONG_DB`; SQLSTATE: `HY000`

Message: Scanned file '%s' for tablespace %s cannot be opened because it is not in a sub-directory named for the schema.

`ER_IB_MSG_INVALID_LOCATION_WRONG_DB` was added in 8.0.21.

- Error number: `MY-013590`; Symbol: `ER_IB_MSG_CANNOT_FIND_DD_UNDO_SPACE`; SQLSTATE: `HY000`

Message: Cannot find undo tablespace %s with filename '%s' as indicated by the Data Dictionary. Did you move or delete this tablespace? Any undo logs in it cannot be used.

`ER_IB_MSG_CANNOT_FIND_DD_UNDO_SPACE` was added in 8.0.21.

- Error number: `MY-013591`; Symbol: `ER_GRP_RPL_RECOVERY_ENDPOINT_FORMAT`; SQLSTATE: `HY000`

Message: Invalid input value for recovery socket endpoints '%s'. Please, provide a valid, comma separated, list of endpoints (IP:port)

`ER_GRP_RPL_RECOVERY_ENDPOINT_FORMAT` was added in 8.0.21.

- Error number: `MY-013592`; Symbol: `ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID`; SQLSTATE: `HY000`

Message: The server is not listening on endpoint '%s'. Only endpoints that the server is listening on are valid recovery endpoints.

`ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID` was added in 8.0.21.

- Error number: `MY-013593`; Symbol: `ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID_DONOR_ENDPOINT`; SQLSTATE: `HY000`

Message: Received invalid recovery endpoints configuration from donor. This member is not a valid donor for recovery, so it will be skipped.

`ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID_DONOR_ENDPOINT` was added in 8.0.21.

- Error number: `MY-013594`; Symbol: `ER_GRP_RPL_RECOVERY_ENDPOINT_INTERFACES_IPS`; SQLSTATE: `HY000`

Message: Failed to retrieve IP addresses from enabled host network interfaces.

`ER_GRP_RPL_RECOVERY_ENDPOINT_INTERFACES_IPS` was added in 8.0.21.

- Error number: `MY-013595`; Symbol: `ER_WARN_TLS_CHANNEL_INITIALIZATION_ERROR`; SQLSTATE: `HY000`

Message: Failed to initialize TLS for channel: %s. See below for the description of exact issue.

`ER_WARN_TLS_CHANNEL_INITIALIZATION_ERROR` was added in 8.0.21.

- Error number: `MY-013596`; Symbol: `ER_XPLUGIN_FAILED_TO_VALIDATE_ADDRESS`; SQLSTATE: `HY000`

Message: Validation of value '%s' set to `Mysqli_bind_address` failed: %s. Skipping this value.

`ER_XPLUGIN_FAILED_TO_VALIDATE_ADDRESS` was added in 8.0.21.

-
- Error number: [MY-013597](#); Symbol: [ER_XPLUGIN_FAILED_TO_BIND_INTERFACE_ADDRESS](#); SQLSTATE: [HY000](#)

Message: Value '%s' set to `Mysqli_bind_address`, X Plugin can't bind to it. Skipping this value.

[ER_XPLUGIN_FAILED_TO_BIND_INTERFACE_ADDRESS](#) was added in 8.0.21.

- Error number: [MY-013598](#); Symbol: [ER_IB_ERR_RECOVERY_REDO_DISABLED](#); SQLSTATE: [HY000](#)

Message: Server was killed when InnoDB redo logging was disabled. Data files could be corrupt. You can try to restart the database with innodb_force_recovery=6

[ER_IB_ERR_RECOVERY_REDO_DISABLED](#) was added in 8.0.21.

- Error number: [MY-013599](#); Symbol: [ER_IB_WRN_FAST_SHUTDOWN_REDO_DISABLED](#); SQLSTATE: [HY000](#)

Message: InnoDB cannot do cold shutdown 'innodb_fast_shutdown = 2' and is forcing 'innodb_fast_shutdown = 1' as redo logging is disabled. InnoDB would flush all dirty pages to ensure physical data consistency.

[ER_IB_WRN_FAST_SHUTDOWN_REDO_DISABLED](#) was added in 8.0.21.

- Error number: [MY-013600](#); Symbol: [ER_IB_WRN_REDO_DISABLED](#); SQLSTATE: [HY000](#)

Message: InnoDB redo logging is disabled. All data could be lost in case of a server crash.

[ER_IB_WRN_REDO_DISABLED](#) was added in 8.0.21.

- Error number: [MY-013601](#); Symbol: [ER_IB_WRN_REDO_ENABLED](#); SQLSTATE: [HY000](#)

Message: InnoDB redo logging is enabled. Data is now safe and can be recovered in case of a server crash.

[ER_IB_WRN_REDO_ENABLED](#) was added in 8.0.21.

- Error number: [MY-013602](#); Symbol: [ER_TLS_CONFIGURED_FOR_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Channel %s configured to support TLS. Encrypted connections are now supported for this channel.

[ER_TLS_CONFIGURED_FOR_CHANNEL](#) was added in 8.0.21.

- Error number: [MY-013603](#); Symbol: [ER_TLS_CONFIGURATION_REUSE](#); SQLSTATE: [HY000](#)

Message: No TLS configuration was given for channel %s; re-using TLS configuration of channel %s.

[ER_TLS_CONFIGURATION_REUSE](#) was added in 8.0.21.

- Error number: [MY-013604](#); Symbol: [ER_IB_TABLESPACE_PATH_VALIDATION_SKIPPED](#); SQLSTATE: [HY000](#)

Message: Skipping InnoDB tablespace path validation. Manually moved tablespace files will not be detected!

[ER_IB_TABLESPACE_PATH_VALIDATION_SKIPPED](#) was added in 8.0.21.

- Error number: [MY-013605](#); Symbol: [ER_IB_CANNOT_UPGRADE_WITH_DISCARDED_TABLESPACES](#); SQLSTATE: [HY000](#)

Message: Upgrade failed because database contains discarded tablespaces.

`ER_IB_CANNOT_UPGRADE_WITH_DISCARDED_TABLESPACES` was added in 8.0.21.

- Error number: `MY-013606`; Symbol: `ER_USERNAME_TRUNCATED`; SQLSTATE: `HY000`

Message: The user name '%s' exceeds the maximum number of allowed characters %d and is truncated.

`ER_USERNAME_TRUNCATED` was added in 8.0.21.

- Error number: `MY-013607`; Symbol: `ER_HOSTNAME_TRUNCATED`; SQLSTATE: `HY000`

Message: The host name '%s' exceeds the maximum number of allowed characters %d and is truncated.

`ER_HOSTNAME_TRUNCATED` was added in 8.0.21.

- Error number: `MY-013608`; Symbol: `ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETED`; SQLSTATE: `HY000`

Message: Rollback of non-prepared transactions not completed, due to fast shutdown

`ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETED` was added in 8.0.21.

- Error number: `MY-013609`; Symbol: `ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME`; SQLSTATE: `HY000`

Message: Found an entry in the 'role_edges' table with empty authorization ID; Skipped

`ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME` was added in 8.0.21.

- Error number: `MY-013610`; Symbol: `ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATION_ID`; SQLSTATE: `HY000`

Message: Found an entry in the 'role_edges' table with unknown authorization ID '%s'; Skipped

`ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATION_ID` was added in 8.0.21.

- Error number: `MY-013611`; Symbol: `ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAME`; SQLSTATE: `HY000`

Message: Found an entry in the 'default_roles' table with empty authorization ID; Skipped

`ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAME` was added in 8.0.21.

- Error number: `MY-013612`; Symbol: `ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHORIZATION_ID`; SQLSTATE: `HY000`

Message: Found an entry in the 'default_roles' table with unknown authorization ID '%s'; Skipped

`ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHORIZATION_ID` was added in 8.0.21.

- Error number: `MY-013613`; Symbol: `ER_IB_ERR_DDL_LOG_INSERT_FAILURE`; SQLSTATE: `HY000`

Message: Couldn't insert entry in ddl log for ddl.

`ER_IB_ERR_DDL_LOG_INSERT_FAILURE` was added in 8.0.21.

- Error number: `MY-013614`; Symbol: `ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION`; SQLSTATE: `HY000`

Message: %s

`ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION` was added in 8.0.21.

- Error number: `MY-013615`; Symbol: `ER_IB_RELLOCK_LATCH_ORDER_VIOLATION`; SQLSTATE: `HY000`

Message: %s

`ER_IB_RELLOCK_LATCH_ORDER_VIOLATION` was added in 8.0.21.

- Error number: `MY-013621`; Symbol: `ER_IB_MSG_1357`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1357` was added in 8.0.21.

- Error number: `MY-013622`; Symbol: `ER_IB_MSG_1358`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1358` was added in 8.0.21.

- Error number: `MY-013623`; Symbol: `ER_IB_MSG_1359`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1359` was added in 8.0.21.

- Error number: `MY-013624`; Symbol: `ER_IB_FAILED_TO_DELETE_TABLESPACE_FILE`; SQLSTATE: `HY000`

Message: %s

`ER_IB_FAILED_TO_DELETE_TABLESPACE_FILE` was added in 8.0.21.

- Error number: `MY-013625`; Symbol: `ER_IB_UNABLE_TO_EXPAND_TEMPORARY_TABLESPACE_POOL`; SQLSTATE: `HY000`

Message: %s

`ER_IB_UNABLE_TO_EXPAND_TEMPORARY_TABLESPACE_POOL` was added in 8.0.21.

- Error number: `MY-013626`; Symbol: `ER_IB_TMP_TABLESPACE_CANNOT_CREATE_DIRECTORY`; SQLSTATE: `HY000`

Message: %s

`ER_IB_TMP_TABLESPACE_CANNOT_CREATE_DIRECTORY` was added in 8.0.21.

- Error number: `MY-013627`; Symbol: `ER_IB_MSG_SCANNING_TEMP_TABLESPACE_DIR`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_SCANNING_TEMP_TABLESPACE_DIR` was added in 8.0.21.

- Error number: `MY-013628`; Symbol: `ER_IB_ERR_TEMP_TABLESPACE_DIR_DOESNT_EXIST`; SQLSTATE: `HY000`

Message: %s

`ER_IB_ERR_TEMP_TABLESPACE_DIR_DOESNT_EXIST` was added in 8.0.21.

-
- Error number: [MY-013629](#); Symbol: [ER_IB_ERR_TEMP_TABLESPACE_DIR_EMPTY](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_TEMP_TABLESPACE_DIR_EMPTY](#) was added in 8.0.21.

- Error number: [MY-013630](#); Symbol: [ER_IB_ERR_TEMP_TABLESPACE_DIR_CONTAINS_SEMICOLON](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_TEMP_TABLESPACE_DIR_CONTAINS_SEMICOLON](#) was added in 8.0.21.

- Error number: [MY-013631](#); Symbol: [ER_IB_ERR_TEMP_TABLESPACE_DIR_SUBDIR_OF_DATADIR](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_TEMP_TABLESPACE_DIR_SUBDIR_OF_DATADIR](#) was added in 8.0.21.

- Error number: [MY-013632](#); Symbol: [ER_IB_ERR_SCHED_SETAFFNINITY_FAILED](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_SCHED_SETAFFNINITY_FAILED](#) was added in 8.0.21.

- Error number: [MY-013633](#); Symbol: [ER_IB_ERR_UNKNOWN_PAGE_FETCH_MODE](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_UNKNOWN_PAGE_FETCH_MODE](#) was added in 8.0.21.

- Error number: [MY-013634](#); Symbol: [ER_IB_ERR_LOG_PARSING_BUFFER_OVERFLOW](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_LOG_PARSING_BUFFER_OVERFLOW](#) was added in 8.0.21.

- Error number: [MY-013635](#); Symbol: [ER_IB_ERR_NOT_ENOUGH_MEMORY_FOR_PARSE_BUFFER](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_NOT_ENOUGH_MEMORY_FOR_PARSE_BUFFER](#) was added in 8.0.21.

- Error number: [MY-013636](#); Symbol: [ER_IB_MSG_1372](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1372](#) was added in 8.0.21.

- Error number: [MY-013637](#); Symbol: [ER_IB_MSG_1373](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1373](#) was added in 8.0.21.

- Error number: [MY-013638](#); Symbol: [ER_IB_MSG_1374](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1374](#) was added in 8.0.21.

- Error number: [MY-013639](#); Symbol: [ER_IB_MSG_1375](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1375](#) was added in 8.0.21.

- Error number: [MY-013640](#); Symbol: [ER_IB_ERR_ZLIB_UNCOMPRESS_FAILED](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_ZLIB_UNCOMPRESS_FAILED](#) was added in 8.0.21.

- Error number: [MY-013641](#); Symbol: [ER_IB_ERR_ZLIB_BUF_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_ZLIB_BUF_ERROR](#) was added in 8.0.21.

- Error number: [MY-013642](#); Symbol: [ER_IB_ERR_ZLIB_MEM_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_ZLIB_MEM_ERROR](#) was added in 8.0.21.

- Error number: [MY-013643](#); Symbol: [ER_IB_ERR_ZLIB_DATA_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_ZLIB_DATA_ERROR](#) was added in 8.0.21.

- Error number: [MY-013644](#); Symbol: [ER_IB_ERR_ZLIB_UNKNOWN_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_ZLIB_UNKNOWN_ERROR](#) was added in 8.0.21.

- Error number: [MY-013645](#); Symbol: [ER_IB_MSG_1381](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1381](#) was added in 8.0.21.

- Error number: [MY-013646](#); Symbol: [ER_IB_ERR_INDEX_RECORDS_WRONG_ORDER](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_INDEX_RECORDS_WRONG_ORDER](#) was added in 8.0.21.

- Error number: [MY-013647](#); Symbol: [ER_IB_ERR_INDEX_DUPLICATE_KEY](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_INDEX_DUPLICATE_KEY](#) was added in 8.0.21.

- Error number: [MY-013648](#); Symbol: [ER_IB_ERR_FOUND_N_DUPLICATE_KEYS](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_ERR_FOUND_N_DUPLICATE_KEYS](#) was added in 8.0.21.
- Error number: [MY-013649](#); Symbol: [ER_IB_ERR_FOUND_N_RECORDS_WRONG_ORDER](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_ERR_FOUND_N_RECORDS_WRONG_ORDER](#) was added in 8.0.21.
- Error number: [MY-013650](#); Symbol: [ER_IB_ERR_PARALLEL_READ_OOM](#); SQLSTATE: [HY000](#)

Message: %s
[ER_IB_ERR_PARALLEL_READ_OOM](#) was added in 8.0.21.
- Error number: [MY-013651](#); Symbol: [ER_IB_MSG_UNDO_MARKED_ACTIVE](#); SQLSTATE: [HY000](#)

Message: The state of undo tablespace %s is set to active implicitly.
[ER_IB_MSG_UNDO_MARKED_ACTIVE](#) was added in 8.0.21.
- Error number: [MY-013652](#); Symbol: [ER_IB_MSG_UNDO_ALTERED_ACTIVE](#); SQLSTATE: [HY000](#)

Message: The state of undo tablespace %s is set to 'active' by ALTER TABLESPACE.
[ER_IB_MSG_UNDO_ALTERED_ACTIVE](#) was added in 8.0.21.
- Error number: [MY-013653](#); Symbol: [ER_IB_MSG_UNDO_ALTERED_INACTIVE](#); SQLSTATE: [HY000](#)

Message: The state of undo tablespace %s is set to 'inactive' by ALTER TABLESPACE.
[ER_IB_MSG_UNDO_ALTERED_INACTIVE](#) was added in 8.0.21.
- Error number: [MY-013654](#); Symbol: [ER_IB_MSG_UNDO_MARKED_EMPTY](#); SQLSTATE: [HY000](#)

Message: The state of undo tablespace %s is set to 'empty'.
[ER_IB_MSG_UNDO_MARKED_EMPTY](#) was added in 8.0.21.
- Error number: [MY-013655](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_CLONE](#); SQLSTATE: [HY000](#)

Message: Delaying truncate of undo tablespace %s due to clone activity.
[ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_CLONE](#) was added in 8.0.21.
- Error number: [MY-013656](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_MDL](#); SQLSTATE: [HY000](#)

Message: Delaying truncate of undo tablespace %s due to a metadata lock.
[ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_MDL](#) was added in 8.0.21.
- Error number: [MY-013657](#); Symbol: [ER_IB_MSG_UNDO_INJECT_CRASH](#); SQLSTATE: [HY000](#)

Message: Injected debug crash point: %s
[ER_IB_MSG_UNDO_INJECT_CRASH](#) was added in 8.0.21, removed after 8.0.21.

- Error number: [MY-013657](#); Symbol: [ER_IB_MSG_INJECT_CRASH](#); SQLSTATE: [HY000](#)

Message: Injected debug crash point: %s
[ER_IB_MSG_INJECT_CRASH](#) was added in 8.0.22.
- Error number: [MY-013658](#); Symbol: [ER_IB_MSG_UNDO_INJECT_FAILURE](#); SQLSTATE: [HY000](#)

Message: Injected debug failure point: %s
[ER_IB_MSG_UNDO_INJECT_FAILURE](#) was added in 8.0.21, removed after 8.0.21.
- Error number: [MY-013658](#); Symbol: [ER_IB_MSG_INJECT_FAILURE](#); SQLSTATE: [HY000](#)

Message: Injected debug failure point: %s
[ER_IB_MSG_INJECT_FAILURE](#) was added in 8.0.22.
- Error number: [MY-013659](#); Symbol: [ER_GRP_RPL_TIMEOUT_RECEIVED_VC_LEAVE_ON_REJOIN](#); SQLSTATE: [HY000](#)

Message: Timeout while waiting for a view change event during the leave step before a auto-rejoin attempt.
[ER_GRP_RPL_TIMEOUT_RECEIVED_VC_LEAVE_ON_REJOIN](#) was added in 8.0.22.
- Error number: [MY-013660](#); Symbol: [ER_RPL_ASYNC_RECONNECT_FAIL_NO_SOURCE](#); SQLSTATE: [HY000](#)

Message: Failed to automatically re-connect to a different source, for channel '%s', because %s. To fix this %s.
[ER_RPL_ASYNC_RECONNECT_FAIL_NO_SOURCE](#) was added in 8.0.22.
- Error number: [MY-013661](#); Symbol: [ER_UDF_REGISTER_SERVICE_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not execute the installation of UDF functions. Check for other errors in the log
[ER_UDF_REGISTER_SERVICE_ERROR](#) was added in 8.0.22.
- Error number: [MY-013662](#); Symbol: [ER_UDF_REGISTER_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not execute the installation of UDF function: %s. Check if the function is already present, if so, try to remove it.
[ER_UDF_REGISTER_ERROR](#) was added in 8.0.22.
- Error number: [MY-013663](#); Symbol: [ER_UDF_UNREGISTER_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not uninstall UDF functions. Try to remove them manually if present.
[ER_UDF_UNREGISTER_ERROR](#) was added in 8.0.22.
- Error number: [MY-013664](#); Symbol: [ER_EMPTY_PRIVILEGE_NAME_IGNORED](#); SQLSTATE: [HY000](#)

Message: An empty or illegal privilege identifier was ignored when global privileges were read from disk.
[ER_EMPTY_PRIVILEGE_NAME_IGNORED](#) was added in 8.0.22.
- Error number: [MY-013665](#); Symbol: [ER_IB_MSG_INCORRECT_SIZE](#); SQLSTATE: [HY000](#)

Message: %s

`ER_IB_MSG_INCORRECT_SIZE` was added in 8.0.22.

- Error number: `MY-013666`; Symbol: `ER_TMPDIR_PATH_TOO_LONG`; SQLSTATE: `HY000`

Message: A tmpdir temporary path "%s" is too long (> %zu) for this OS. This would not leave enough space for a temporary filename of length %zu within it.

`ER_TMPDIR_PATH_TOO_LONG` was added in 8.0.22.

- Error number: `MY-013667`; Symbol: `ER_ERROR_LOG_DESTINATION_NOT_A_FILE`; SQLSTATE: `HY000`

Message: Error-log destination "%s" is not a file. Can not restore error log messages from previous run.

`ER_ERROR_LOG_DESTINATION_NOT_A_FILE` was added in 8.0.22.

- Error number: `MY-013668`; Symbol: `ER_NO_ERROR_LOG_PARSER_CONFIGURED`; SQLSTATE: `HY000`

Message: None of the log-sinks selected with --log-error-services=... provides a log-parser. The server will not be able to make the previous runs' error-logs available in performance_schema.error_log.

`ER_NO_ERROR_LOG_PARSER_CONFIGURED` was added in 8.0.22.

- Error number: `MY-013669`; Symbol: `ER_UPGRADE_NONEXISTENT_SCHEMA`; SQLSTATE: `HY000`

Message: The schema "%s" referenced by %s "%s" does not exist. Please clean up any orphan %s before upgrading.

`ER_UPGRADE_NONEXISTENT_SCHEMA` was added in 8.0.22.

- Error number: `MY-013670`; Symbol: `ER_IB_MSG_CREATED_UNDO_SPACE`; SQLSTATE: `HY000`

Message: Created undo tablespace '%s'.

`ER_IB_MSG_CREATED_UNDO_SPACE` was added in 8.0.22.

- Error number: `MY-013671`; Symbol: `ER_IB_MSG_DROPPED_UNDO_SPACE`; SQLSTATE: `HY000`

Message: Dropped undo tablespace '%s'.

`ER_IB_MSG_DROPPED_UNDO_SPACE` was added in 8.0.22.

- Error number: `MY-013672`; Symbol: `ER_IB_MSG_MASTER_KEY_ROTATED`; SQLSTATE: `HY000`

Message: The InnoDB Encryption Master Key has been rotated in %d tablespaces.

`ER_IB_MSG_MASTER_KEY_ROTATED` was added in 8.0.22.

- Error number: `MY-013673`; Symbol: `ER_IB_DBWR_DECOMPRESS_FAILED`; SQLSTATE: `HY000`

Message: Failed to decompress a DBLWR page (err=%d). The original size is %d. Reporting the dblwr page as corrupted.

`ER_IB_DBWR_DECOMPRESS_FAILED` was added in 8.0.23.

- Error number: `MY-013674`; Symbol: `ER_IB_DBWR_DECRYPT_FAILED`; SQLSTATE: `HY000`

Message: Decrypting a page in doublewrite file failed: %s.

`ER_IB_DBWR_DECRYPT_FAILED` was added in 8.0.23.

- Error number: [MY-013675](#); Symbol: [ER_IB_DBWR_KEY_MISSING](#); SQLSTATE: [HY000](#)

Message: Encryption key missing: %s.
[ER_IB_DBWR_KEY_MISSING](#) was added in 8.0.23.
- Error number: [MY-013676](#); Symbol: [ER_INNODB_IO_WRITE_ERROR_RETRYING](#); SQLSTATE: [HY000](#)

Message: I/O error while writing to file: %s. Retrying ...
[ER_INNODB_IO_WRITE_ERROR_RETRYING](#) was added in 8.0.23.
- Error number: [MY-013677](#); Symbol: [ER_INNODB_IO_WRITE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to write data to file: %s
[ER_INNODB_IO_WRITE_FAILED](#) was added in 8.0.23.
- Error number: [MY-013678](#); Symbol: [ER_LOG_COMPONENT_CANNOT_INIT](#); SQLSTATE: [HY000](#)

Message: Log component %s failed to initialize.
[ER_LOG_COMPONENT_CANNOT_INIT](#) was added in 8.0.23.
- Error number: [MY-013679](#); Symbol: [ER_RPL_ASYNC_CHANNEL_CANT_CONNECT](#); SQLSTATE: [HY000](#)

Message: The Monitor IO thread failed to connect to the source (host:%s port:%u network_namespace:%s) for channel '%s', thence it will try to connect to another source.
[ER_RPL_ASYNC_CHANNEL_CANT_CONNECT](#) was added in 8.0.23.
- Error number: [MY-013680](#); Symbol: [ER_RPL_ASYNC_SENDER_ADDED](#); SQLSTATE: [HY000](#)

Message: The source (host:%s port:%u network_namespace:%s) for channel '%s' has joined the group (group_name: %s), and so added its entry into replication_asynchronous_connection_failover table.
[ER_RPL_ASYNC_SENDER_ADDED](#) was added in 8.0.23.
- Error number: [MY-013681](#); Symbol: [ER_RPL_ASYNC_SENDER_REMOVED](#); SQLSTATE: [HY000](#)

Message: The source (host:%s port:%u network_namespace:%s) for channel '%s' has left the group (group_name: %s), and so removed its entry from replication_asynchronous_connection_failover table.
[ER_RPL_ASYNC_SENDER_REMOVED](#) was added in 8.0.23.
- Error number: [MY-013682](#); Symbol: [ER_RPL_ASYNC_CHANNEL_STOPPED_QUORUM_LOST](#); SQLSTATE: [HY000](#)

Message: The Monitor IO thread detected that the source (host:%s port:%u network_namespace: %s) does not belong to the group majority, thence the channel '%s' will try to connect to another source.
[ER_RPL_ASYNC_CHANNEL_STOPPED_QUORUM_LOST](#) was added in 8.0.23.
- Error number: [MY-013683](#); Symbol: [ER_RPL_ASYNC_CHANNEL_CANT_CONNECT_NO_QUORUM](#); SQLSTATE: [HY000](#)

Message: The IO thread detected that the source (host:%s port:%u network_namespace:%s) does not belong to the group majority, thence the channel '%s' will try to connect to another source.

`ER_RPL_ASYNC_CHANNEL_CANT_CONNECT_NO_QUORUM` was added in 8.0.23.

- Error number: `MY-013684`; Symbol: `ER_RPL_ASYNC_EXECUTING_QUERY`; SQLSTATE: `HY000`

Message: %s on the source (host:%s port:%u network_namespace:%s) for channel '%s'.

`ER_RPL_ASYNC_EXECUTING_QUERY` was added in 8.0.23.

- Error number: `MY-013685`; Symbol: `ER_RPL_REPLICA_MONITOR_IO_THREAD_EXITING`; SQLSTATE: `HY000`

Message: Replica Monitor IO thread exiting.

`ER_RPL_REPLICA_MONITOR_IO_THREAD_EXITING` was added in 8.0.23.

- Error number: `MY-013686`; Symbol: `ER_RPL_ASYNC_MANAGED_NAME_REMOVED`; SQLSTATE: `HY000`

Message: The group (group_name: %s) for the channel '%s' has been removed, and so removed its entry from replication_asynchronous_connection_failover_managed and all the group members from replication_asynchronous_connection_failover table.

`ER_RPL_ASYNC_MANAGED_NAME_REMOVED` was added in 8.0.23.

- Error number: `MY-013687`; Symbol: `ER_RPL_ASYNC_MANAGED_NAME_ADDED`; SQLSTATE: `HY000`

Message: The group (group_name: %s) for the channel '%s' has been added, and so added its entry in replication_asynchronous_connection_failover_managed and source to replication_asynchronous_connection_failover table.

`ER_RPL_ASYNC_MANAGED_NAME_ADDED` was added in 8.0.23.

- Error number: `MY-013688`; Symbol: `ER_RPL_ASYNC_READ_FAILOVER_TABLE`; SQLSTATE: `HY000`

Message: Error reading failover sources for channel '%s' from replication_asynchronous_connection_failover table.

`ER_RPL_ASYNC_READ_FAILOVER_TABLE` was added in 8.0.23.

- Error number: `MY-013689`; Symbol: `ER_RPL_REPLICA_MONITOR_IO_THREAD_RECONNECT_CHANNEL`; SQLSTATE: `HY000`

Message: Error %s the channel '%s', the operation will be automatically retried.

`ER_RPL_REPLICA_MONITOR_IO_THREAD_RECONNECT_CHANNEL` was added in 8.0.23.

- Error number: `MY-013690`; Symbol: `ER_SLAVE_ANONYMOUS_TO_GTID_IS_LOCAL_OR_UUID_AND_GTID_MODE_NOT_ON`; SQLSTATE: `HY000`

Message: Replication channel '%s' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS=%s`, which is invalid when `GTID_MODE <> ON`. If you intend to use `GTID_MODE = ON` everywhere, change to `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = OFF` and use the procedure for enabling GTIDs online (see the documentation). If you intend to use GTIDs on this replica and cannot enable GTIDs on the source, enable `GTID_MODE = ON` and leave `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL`.

<UUID>. If you intend to not use GTIDs at all in the replication topology, change to ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS=OFF and leave GTID_MODE = '%s'.

`ER_SLAVE_ANONYMOUS_TO_GTID_IS_LOCAL_OR_UUID_AND_GTID_MODE_NOT_ON` was added in 8.0.23.

- Error number: `MY-013691`; Symbol:

`ER_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME`; SQLSTATE: `HY000`

Message: Replication channel '%s' is configured with
ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%' which is equal to
group_replication_group_name. To fix this issue, either change the group_replication_group_name
or use a different value for ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS.

`ER_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME` was added in 8.0.23.

- Error number: `MY-013692`; Symbol:

`ER_GRP_RPL_GRP_NAME_IS_SAME_AS_ANONYMOUS_TO_GTID_UUID`; SQLSTATE: `HY000`

Message: The group_replication_group_name '%s' is the same as the UUID value for
ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS in a server channel

`ER_GRP_RPL_GRP_NAME_IS_SAME_AS_ANONYMOUS_TO_GTID_UUID` was added in 8.0.23.

- Error number: `MY-013693`; Symbol: `ER_WARN_GTID_THRESHOLD_BREACH`; SQLSTATE: `HY000`

Message: The integer component of the GTID number is high. Suggest restarting the server with
a new server_uuid to prevent it from reaching the maximum number $2^{63}-1$, which will make it
impossible to write the binary log and invoke the behavior specified by binlog_error_action.

`ER_WARN_GTID_THRESHOLD_BREACH` was added in 8.0.23.

- Error number: `MY-013694`; Symbol: `ER_HEALTH_INFO`; SQLSTATE: `HY000`

Message: %s

`ER_HEALTH_INFO` was added in 8.0.23.

- Error number: `MY-013695`; Symbol: `ER_HEALTH_WARNING`; SQLSTATE: `HY000`

Message: %s

`ER_HEALTH_WARNING` was added in 8.0.23.

- Error number: `MY-013696`; Symbol: `ER_HEALTH_ERROR`; SQLSTATE: `HY000`

Message: %s

`ER_HEALTH_ERROR` was added in 8.0.23.

- Error number: `MY-013697`; Symbol: `ER_HEALTH_WARNING_DISK_USAGE_LEVEL_1`; SQLSTATE: `HY000`

Message: Disk usage on '%s' is %.2f%. Warning level 1 (%d%) exceeded.

`ER_HEALTH_WARNING_DISK_USAGE_LEVEL_1` was added in 8.0.23.

- Error number: `MY-013698`; Symbol: `ER_HEALTH_WARNING_DISK_USAGE_LEVEL_2`; SQLSTATE: `HY000`

Message: Disk usage on '%s' is %.2f%. Warning level 2 (%d%) exceeded.

`ER_HEALTH_WARNING_DISK_USAGE_LEVEL_2` was added in 8.0.23.

-
- Error number: [MY-013699](#); Symbol: [ER_HEALTH_WARNING_DISK_USAGE_LEVEL_3](#); SQLSTATE: [HY000](#)

Message: Disk usage on '%s' is %.2f%. Warning level 3 (%d%%) exceeded.

[ER_HEALTH_WARNING_DISK_USAGE_LEVEL_3](#) was added in 8.0.23.

- Error number: [MY-013700](#); Symbol: [ER_IB_INNODB_TBSP_OUT_OF_SPACE](#); SQLSTATE: [HY000](#)

Message: InnoDB: Size of tablespace %s is more than the maximum size allowed.

[ER_IB_INNODB_TBSP_OUT_OF_SPACE](#) was added in 8.0.23.

- Error number: [MY-013701](#); Symbol: [ER_GRP_RPL_APPLIER_CHANNEL_STILL_RUNNING](#); SQLSTATE: [HY000](#)

Message: The group_replication_applier channel is still running, most likely it is waiting for a database/table lock, which is preventing the channel from stopping. Please check database/table locks, including the ones created by backup tools.

[ER_GRP_RPL_APPLIER_CHANNEL_STILL_RUNNING](#) was added in 8.0.23.

- Error number: [MY-013702](#); Symbol: [ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Detected misconfiguration: replication channel '\%s' was configured with SOURCE_CONNECTION_AUTO_FAILOVER = 1, but the server was started with a value other then --gtid-mode = ON. Either reconfigure replication using CHANGE MASTER TO SOURCE_CONNECTION_AUTO_FAILOVER = 0 FOR CHANNEL '\%s', or change GTID_MODE to value ON, before starting the replica receiver thread.

[ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF_CHANNEL](#) was added in 8.0.23.

- Error number: [MY-013703](#); Symbol: [ER_FIREWALL_SERVICES_NOT_ACQUIRED](#); SQLSTATE: [HY000](#)

Message: Could not acquire required component services.

[ER_FIREWALL_SERVICES_NOT_ACQUIRED](#) was added in 8.0.23.

- Error number: [MY-013704](#); Symbol: [ER_FIREWALL_UDF_REGISTER_FAILED](#); SQLSTATE: [HY000](#)

Message: Automatic registration of function(s) failed.

[ER_FIREWALL_UDF_REGISTER_FAILED](#) was added in 8.0.23.

- Error number: [MY-013705](#); Symbol: [ER_FIREWALL_PFS_TABLE_REGISTER_FAILED](#); SQLSTATE: [HY000](#)

Message: Automatic registration of Performance schema table(s) failed.

[ER_FIREWALL_PFS_TABLE_REGISTER_FAILED](#) was added in 8.0.23.

- Error number: [MY-013706](#); Symbol: [ER_IB_MSG_STATS_SAMPLING_TOO_LARGE](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_STATS_SAMPLING_TOO_LARGE](#) was added in 8.0.23.

- Error number: [MY-013707](#); Symbol: [ER_AUDIT_LOG_FILE_PRUNE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to auto-prune file '%s', Error (%d): %s

`ER_AUDIT_LOG_FILE_PRUNE_FAILED` was added in 8.0.24.

- Error number: `MY-013708`; Symbol: `ER_AUDIT_LOG_FILE_AUTO_PRUNED`; SQLSTATE: `HY000`

Message: File '%s' auto-pruned

`ER_AUDIT_LOG_FILE_AUTO_PRUNED` was added in 8.0.24.

- Error number: `MY-013709`; Symbol: `ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_INIT`; SQLSTATE: `HY000`

Message: Received an error while processing components from manifest file: %s

`ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_INIT` was added in 8.0.24.

- Error number: `MY-013710`; Symbol: `ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_DEINIT`; SQLSTATE: `HY000`

Message: Received an error while unloading components read from manifest file: %s

`ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_DEINIT` was added in 8.0.24.

- Error number: `MY-013711`; Symbol: `ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_NOT_RO`; SQLSTATE: `HY000`

Message: Manifest file '%s' is not read-only. For better security, please make sure that the file is read-only.

`ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_NOT_RO` was added in 8.0.24.

- Error number: `MY-013712`; Symbol: `ER_WARN_NO_KEYRING_COMPONENT_SERVICE_FOUND`; SQLSTATE: `HY000`

Message: No suitable '%s' service implementation found to fulfill the request.

`ER_WARN_NO_KEYRING_COMPONENT_SERVICE_FOUND` was added in 8.0.24.

- Error number: `MY-013713`; Symbol: `ER_NOTE_KEYRING_COMPONENT_INITIALIZED`; SQLSTATE: `HY000`

Message: Keyring component initialized successfully.

`ER_NOTE_KEYRING_COMPONENT_INITIALIZED` was added in 8.0.24.

- Error number: `MY-013714`; Symbol: `ER_KEYRING_COMPONENT_NOT_INITIALIZED`; SQLSTATE: `HY000`

Message: The component is not initialized properly. Make sure that configuration is proper and use ALTER INSTANCE RELOAD KEYRING to reinitialize the component.

`ER_KEYRING_COMPONENT_NOT_INITIALIZED` was added in 8.0.24.

- Error number: `MY-013715`; Symbol: `ER_KEYRING_COMPONENT_EXCEPTION`; SQLSTATE: `HY000`

Message: Keyring component encountered an exception while executing : '%s' API of service: '%s'

`ER_KEYRING_COMPONENT_EXCEPTION` was added in 8.0.24.

- Error number: `MY-013716`; Symbol: `ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR`; SQLSTATE: `HY000`

Message: Failed to allocated memory for '%s' while executing: '%s' API of service: '%s'

`ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR` was added in 8.0.24.

- Error number: `MY-013717`; Symbol: `ER_NOTE_KEYRING_COMPONENT_AES_INVALID_MODE_BLOCK_SIZE`; SQLSTATE: `HY000`

Message: Empty or 0 values for AES encryption mode and/or block size are not permitted.

`ER_NOTE_KEYRING_COMPONENT_AES_INVALID_MODE_BLOCK_SIZE` was added in 8.0.24.

- Error number: `MY-013718`; Symbol: `ER_NOTE_KEYRING_COMPONENT_AES_DATA_IDENTIFIER_EMPTY`; SQLSTATE: `HY000`

Message: A valid data identifier is required in order to fetch the key required for the AES operation.

`ER_NOTE_KEYRING_COMPONENT_AES_DATA_IDENTIFIER_EMPTY` was added in 8.0.24.

- Error number: `MY-013719`; Symbol: `ER_NOTE_KEYRING_COMPONENT_AES_INVALID_KEY`; SQLSTATE: `HY000`

Message: Key identified by Data ID: '%s' and Auth ID: '%s' is not of type AES.

`ER_NOTE_KEYRING_COMPONENT_AES_INVALID_KEY` was added in 8.0.24.

- Error number: `MY-013720`; Symbol: `ER_NOTE_KEYRING_COMPONENT_AES_OPERATION_ERROR`; SQLSTATE: `HY000`

Message: Encountered error: '%s' while executing '%s' API of keyring_aes service. Key details are Data ID: '%s' and Auth ID: '%s'.

`ER_NOTE_KEYRING_COMPONENT_AES_OPERATION_ERROR` was added in 8.0.24.

- Error number: `MY-013721`; Symbol: `ER_NOTE_KEYRING_COMPONENT_READ_DATA_NOT_FOUND`; SQLSTATE: `HY000`

Message: Could not find the data corresponding to Data ID: '%s', Auth ID: '%s'.

`ER_NOTE_KEYRING_COMPONENT_READ_DATA_NOT_FOUND` was added in 8.0.24.

- Error number: `MY-013722`; Symbol: `ER_NOTE_KEYRING_COMPONENT_WRITE_MAXIMUM_DATA_LENGTH`; SQLSTATE: `HY000`

Message: Maximum permissible size of data is '%zu' bits

`ER_NOTE_KEYRING_COMPONENT_WRITE_MAXIMUM_DATA_LENGTH` was added in 8.0.24.

- Error number: `MY-013723`; Symbol: `ER_NOTE_KEYRING_COMPONENT_STORE_FAILED`; SQLSTATE: `HY000`

Message: Error writing data for Data ID: '%s', Auth ID: '%s'. Either data already exists with same identifier or keyring backend encountered an error.

`ER_NOTE_KEYRING_COMPONENT_STORE_FAILED` was added in 8.0.24.

- Error number: `MY-013724`; Symbol: `ER_NOTE_KEYRING_COMPONENT_REMOVE_FAILED`; SQLSTATE: `HY000`

Message: Error removing data for Data ID: '%s', Auth ID: '%s'. Either data already exists with same identifier or keyring backend encountered an error.

`ER_NOTE_KEYRING_COMPONENT_REMOVE_FAILED` was added in 8.0.24.

- Error number: MY-013725; Symbol: ER_NOTE_KEYRING_COMPONENT_GENERATE_FAILED; SQLSTATE: HY000

Message: Error generating data for Data ID: '%s', Auth ID: '%s'. Either data already exists with same identifier or keyring backend encountered an error.

ER_NOTE_KEYRING_COMPONENT_GENERATE_FAILED was added in 8.0.24.

- Error number: MY-013726; Symbol: ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATOR_FETCH_FAILED; SQLSTATE: HY000

Message: Failed to get metadata from current keys metadata iterator position.

ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATOR_FETCH_FAILED was added in 8.0.24.

- Error number: MY-013727; Symbol: ER_NOTE_KEYRING_COMPONENT_METADATA_ITERATOR_INVALID_OUT_PARAM; SQLSTATE: HY000

Message: Key and value length parameters must not be null.

ER_NOTE_KEYRING_COMPONENT_METADATA_ITERATOR_INVALID_OUT_PARAM was added in 8.0.24.

- Error number: MY-013728; Symbol: ER_IB_WRN_FAILED_TO_ACQUIRE_SERVICE; SQLSTATE: HY000

Message: Innodb could not acquire service : %s

ER_IB_WRN_FAILED_TO_ACQUIRE_SERVICE was added in 8.0.24.

- Error number: MY-013729; Symbol: ER_IB_WRN_OLD_GEOMETRY_TYPE; SQLSTATE: HY000

Message: Column %s of type GEOMETRY is in old (5.6) format which could be deprecated in the future. To change the format to latest, please consider rebuilding the table after the upgrade.

ER_IB_WRN_OLD_GEOMETRY_TYPE was added in 8.0.24.

- Error number: MY-013730; Symbol: ER_NET_WAIT_ERROR2; SQLSTATE: HY000

Message: 'wait_timeout' period of %s seconds was exceeded for %s. The idle time since last command was too long.

ER_NET_WAIT_ERROR2 was added in 8.0.26.

- Error number: MY-013731; Symbol: ER_GRP_RPL_MEMBER_ACTION_TRIGGERED; SQLSTATE: HY000

Message: The member action "%s" for event "%s" with priority "%u" will be run.

ER_GRP_RPL_MEMBER_ACTION_TRIGGERED was added in 8.0.26.

- Error number: MY-013732; Symbol: ER_GRP_RPL_MEMBER_ACTION_FAILURE_IGNORE; SQLSTATE: HY000

Message: The member action "%s" for event "%s" with priority "%u" failed, this error is ignored as instructed. Please check previous messages in the error log for hints about what could have caused this failure.

ER_GRP_RPL_MEMBER_ACTION_FAILURE_IGNORE was added in 8.0.26.

-
- Error number: [MY-013733](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_FAILURE](#); SQLSTATE: [HY000](#)

Message: The member action "%s" for event "%s" with priority "%u" failed. Please check previous messages in the error log for hints about what could have caused this failure.

[ER_GRP_RPL_MEMBER_ACTION_FAILURE](#) was added in 8.0.26.

- Error number: [MY-013734](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_RECEIVE](#); SQLSTATE: [HY000](#)

Message: Unable to parse the member actions configuration sent by the primary.

[ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_RECEIVE](#) was added in 8.0.26.

- Error number: [MY-013735](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS](#); SQLSTATE: [HY000](#)

Message: Unable to update the member actions configuration with the one sent by the primary. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication_group_configuration_version'.

[ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS](#) was added in 8.0.26.

- Error number: [MY-013736](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_GET_EXCHANGEABLE_DATA](#); SQLSTATE: [HY000](#)

Message: Unable to read the member actions configuration during group membership change. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication_group_configuration_version'.

[ER_GRP_RPL_MEMBER_ACTION_GET_EXCHANGEABLE_DATA](#) was added in 8.0.26.

- Error number: [MY-013737](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_DEFAULT_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: This member joined a group on which all members do not support member actions, as such it did reset its member configuration to the default one.

[ER_GRP_RPL_MEMBER_ACTION_DEFAULT_CONFIGURATION](#) was added in 8.0.26.

- Error number: [MY-013738](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_UNABLE_TO_SET_DEFAULT_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Unable to reset to member actions default configuration on member join. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication_group_configuration_version'.

[ER_GRP_RPL_MEMBER_ACTION_UNABLE_TO_SET_DEFAULT_CONFIGURATION](#) was added in 8.0.26.

- Error number: [MY-013739](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_MEMBER_JOIN](#); SQLSTATE: [HY000](#)

Message: Unable to parse the member actions configuration sent by the group on member join.

[ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_MEMBER_JOIN](#) was added in 8.0.26.

- Error number: [MY-013740](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS_ON_MEMBER_JOIN](#); SQLSTATE: [HY000](#)

Message: Unable to update the member actions configuration on member join. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication_group_configuration_version'.

[ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS_ON_MEMBER_JOIN](#) was added in 8.0.26.

- Error number: [MY-013741](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_INVALID_ACTIONS_ON_MEMBER_JOIN](#); SQLSTATE: [HY000](#)

Message: The group members were unable to send their member actions configuration. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication_group_configuration_version' on all members.

[ER_GRP_RPL_MEMBER_ACTION_INVALID_ACTIONS_ON_MEMBER_JOIN](#) was added in 8.0.26.

- Error number: [MY-013742](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_ENABLED](#); SQLSTATE: [HY000](#)

Message: Member action enabled: "%s", type: "%s", event: "%s", priority: "%u", error_handling: "%s".

[ER_GRP_RPL_MEMBER_ACTION_ENABLED](#) was added in 8.0.26.

- Error number: [MY-013743](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_DISABLED](#); SQLSTATE: [HY000](#)

Message: Member action disabled: "%s", type: "%s", event: "%s", priority: "%u", error_handling: "%s".

[ER_GRP_RPL_MEMBER_ACTION_DISABLED](#) was added in 8.0.26.

- Error number: [MY-013744](#); Symbol: [ER_GRP_RPL_MEMBER_ACTIONS_RESET](#); SQLSTATE: [HY000](#)

Message: Member actions configuration was reset.

[ER_GRP_RPL_MEMBER_ACTIONS_RESET](#) was added in 8.0.26.

- Error number: [MY-013745](#); Symbol: [ER_DEPRECATED_TLS_VERSION_SESSION](#); SQLSTATE: [HY000](#)

Message: Accepted a connection with deprecated protocol '%s' for account `'%s` @`%s` from host `'%s`. Client supplied username `'%s'

[ER_DEPRECATED_TLS_VERSION_SESSION](#) was added in 8.0.26.

- Error number: [MY-013746](#); Symbol: [ER_WARN_DEPRECATED_TLS_VERSION_FOR_CHANNEL](#); SQLSTATE: [HY000](#)

Message: A deprecated TLS version %s is enabled for channel %s

[ER_WARN_DEPRECATED_TLS_VERSION_FOR_CHANNEL](#) was added in 8.0.26.

- Error number: [MY-013747](#); Symbol: [ER_FIREWALL_DEPRECATED_USER_PROFILE](#); SQLSTATE: [HY000](#)

Message: User profile '\%s\' loaded. Firewall user profiles are deprecated, consider migrating to group profiles.

[ER_FIREWALL_DEPRECATED_USER_PROFILE](#) was added in 8.0.26.

-
- Error number: [MY-013748](#); Symbol: [ER_GRP_RPL_VIEW_CHANGE_UUID_INVALID](#); SQLSTATE: [HY000](#)

Message: Invalid input value for group_replication_view_change_uuid '%s'. Please, provide a valid UUID.

[ER_GRP_RPL_VIEW_CHANGE_UUID_INVALID](#) was added in 8.0.26.

- Error number: [MY-013749](#); Symbol: [ER_GRP_RPL_VIEW_CHANGE_UUID_SAME_AS_GROUP_NAME](#); SQLSTATE: [HY000](#)

Message: Variable 'group_replication_view_change_uuid' cannot be set to the value of '%s'. If you want to use the UUID of 'group_replication_group_name' for the UUID of View_change_log_events, please set 'group_replication_view_change_uuid' to AUTOMATIC.

[ER_GRP_RPL_VIEW_CHANGE_UUID_SAME_AS_GROUP_NAME](#) was added in 8.0.26.

- Error number: [MY-013750](#); Symbol: [ER_GRP_RPL_GROUP_NAME_SAME_AS_VIEW_CHANGE_UUID](#); SQLSTATE: [HY000](#)

Message: group_replication_group_name '%s', which is the same as group_replication_view_change_uuid. Please change group_replication_view_change_uuid to AUTOMATIC

[ER_GRP_RPL_GROUP_NAME_SAME_AS_VIEW_CHANGE_UUID](#) was added in 8.0.26.

- Error number: [MY-013751](#); Symbol: [ER_GRP_RPL_VIEW_CHANGE_UUID_IS_SAME_AS_ANONYMOUS_TO_GTID_UUID](#); SQLSTATE: [HY000](#)

Message: The group_replication_view_change_uuid '%s' is the same as the UUID value for ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS in a server channel

[ER_GRP_RPL_VIEW_CHANGE_UUID_IS_SAME_AS_ANONYMOUS_TO_GTID_UUID](#) was added in 8.0.26.

- Error number: [MY-013752](#); Symbol: [ER_GRP_RPL_GRP_VIEW_CHANGE_UUID_IS_INCOMPATIBLE_WITH_SERVER_UUID](#); SQLSTATE: [HY000](#)

Message: group_replication_view_change_uuid is incompatible with group. group_replication_view_change_uuid %s matches server_uuid %s.

[ER_GRP_RPL_GRP_VIEW_CHANGE_UUID_IS_INCOMPATIBLE_WITH_SERVER_UUID](#) was added in 8.0.26.

- Error number: [MY-013753](#); Symbol: [ER_GRP_RPL_VIEW_CHANGE_UUID_DIFF_FROM_GRP](#); SQLSTATE: [HY000](#)

Message: The member is configured with a group_replication_view_change_uuid option value '%s' different from the group '%s'. The member will now exit the group.

[ER_GRP_RPL_VIEW_CHANGE_UUID_DIFF_FROM_GRP](#) was added in 8.0.26.

- Error number: [MY-013754](#); Symbol: [ER_WARN_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW_CHANGE_UUID](#); SQLSTATE: [HY000](#)

Message: Replication channel '%s' is configured with ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%' which is equal to group_replication_view_change_uuid. To fix this issue, either

change the group_replication_view_change_uuid or use a different value for ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS.

`ER_WARN_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW_CHANGE_UUID` was added in 8.0.26.

- Error number: `MY-013755`; Symbol:

`ER_GRP_RPL_FAILED_TO_PARSE_THE_VIEW_CHANGE_UUID`; SQLSTATE: `HY000`

Message: Unable to parse the group_replication_view_change_uuid.

`ER_GRP_RPL_FAILED_TO_PARSE_THE_VIEW_CHANGE_UUID` was added in 8.0.26.

- Error number: `MY-013756`; Symbol:

`ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_VIEW_CHANGE_UUID`; SQLSTATE: `HY000`

Message: Unable to generate sidno for group_replication_view_change_uuid.

`ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_VIEW_CHANGE_UUID` was added in 8.0.26.

- Error number: `MY-013757`; Symbol: `ER_GRP_RPL_VIEW_CHANGE_UUID_PARSE_ERROR`; SQLSTATE: `HY000`

Message: Unable to parse the group_replication_view_change_uuid during the Certification module initialization.

`ER_GRP_RPL_VIEW_CHANGE_UUID_PARSE_ERROR` was added in 8.0.26.

- Error number: `MY-013758`; Symbol:

`ER_GRP_RPL_UPDATE_GRP_GTID_VIEW_CHANGE_UUID_EXECUTED_ERROR`; SQLSTATE: `HY000`

Message: Error updating group_gtid_executed GTID set with view change uuid during the Certification module initialization.

`ER_GRP_RPL_UPDATE_GRP_GTID_VIEW_CHANGE_UUID_EXECUTED_ERROR` was added in 8.0.26.

- Error number: `MY-013759`; Symbol:

`ER_GRP_RPL_ADD_VIEW_CHANGE_UUID_TO_GRP_SID_MAP_ERROR`; SQLSTATE: `HY000`

Message: Unable to add the group_replication_view_change_uuid sidno in the group_gtid_sid_map during the Certification module initialization.

`ER_GRP_RPL_ADD_VIEW_CHANGE_UUID_TO_GRP_SID_MAP_ERROR` was added in 8.0.26.

- Error number: `MY-013760`; Symbol:

`ER_GRP_RPL_DONOR_VIEW_CHANGE_UUID_TRANS_INFO_ERROR`; SQLSTATE: `HY000`

Message: Unable to handle the donor's view change uuid transaction information when initializing the conflict detection component. Possible out of memory error.

`ER_GRP_RPL_DONOR_VIEW_CHANGE_UUID_TRANS_INFO_ERROR` was added in 8.0.26.

- Error number: `MY-013761`; Symbol:

`ER_WARN_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE`; SQLSTATE: `HY000`

Message: Unable to retrieve group_replication_view_change_uuid during server checks on replication operations.

`ER_WARN_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE` was added in 8.0.26.

- Error number: `MY-013762`; Symbol:

`ER_WARN_AUDIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS_LOG`; SQLSTATE: `HY000`

Message: Both audit_log_max_size and audit_log_prune_seconds are set to non-zero.
audit_log_max_size takes precedence and audit_log_prune_seconds is ignored

`ER_WARN_AUDIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS_LOG` was added in 8.0.26.

- Error number: `MY-013763`; Symbol:

`ER_WARN_AUDIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE_ON_SIZE_LOG`; SQLSTATE: `HY000`

Message: audit_log_rotate_on_size is not granular enough for the value of audit_log_max_size supplied. Should be at least %d times smaller.

`ER_WARN_AUDIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE_ON_SIZE_LOG` was added in 8.0.26.

- Error number: `MY-013764`; Symbol: `ER_PLUGIN_INVALID_TABLE_DEFINITION`; SQLSTATE: `HY000`

Message: Invalid table definition for '%s.%s'.

`ER_PLUGIN_INVALID_TABLE_DEFINITION` was added in 8.0.26.

- Error number: `MY-013765`; Symbol: `ER_AUTH_KERBEROS_LOGGER_GENERIC_MSG`; SQLSTATE: `HY000`

Message: %s

`ER_AUTH_KERBEROS_LOGGER_GENERIC_MSG` was added in 8.0.26.

- Error number: `MY-013766`; Symbol: `ER_INSTALL_PLUGIN_CONFLICT_LOG`; SQLSTATE: `HY000`

Message: Cannot install the %s plugin when the %s plugin is installed.

`ER_INSTALL_PLUGIN_CONFLICT_LOG` was added in 8.0.26.

- Error number: `MY-013767`; Symbol: `ER_DEPRECATED_PERSISTED_VARIABLE_WITH_ALIAS`; SQLSTATE: `HY000`

Message: The variable %s has been renamed to %s, and the old name deprecated. Only the old name was found in the persisted variable file. Next time the file is saved, both names will be stored. Issue any SET PERSIST command to save the file, get rid of this warning, and prepare the persisted configuration for when the variable is removed in a future version.

`ER_DEPRECATED_PERSISTED_VARIABLE_WITH_ALIAS` was added in 8.0.26.

- Error number: `MY-013768`; Symbol: `ER_LOG_COMPONENT_FLUSH_FAILED`; SQLSTATE: `HY000`

Message: %d error logging component(s) failed to flush. For file-based logs this can happen when the path or permissions of the log-file have changed. Failure to flush file-based logs may affect log-rotation.

`ER_LOG_COMPONENT_FLUSH_FAILED` was added in 8.0.26.

- Error number: `MY-013769`; Symbol: `ER_DDL_MSG_1`; SQLSTATE: `HY000`

Message: DDL failed to create a thread to load an index, fall back to single thread

`ER_DDL_MSG_1` was added in 8.0.27.

- Error number: `MY-013770`; Symbol: `ER_MTR_MSG_1`; SQLSTATE: `HY000`

Message: Debug_check_no_latching failed, slot->type=%d

`ER_MTR_MSG_1` was added in 8.0.27.

Chapter 3 Client Error Message Reference

Client error messages originate from within the MySQL client library. Here is an example client error message, as displayed by the `mysql` client:

```
shell> mysql -h no-such-host
ERROR 2005 (HY000): Unknown MySQL server host 'no-such-host' (0)
```

Each client error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#). For client errors, the SQLSTATE value is always '`HY000`' (general error), so it is not meaningful for distinguishing one client error from another.

The client library also makes available to host client programs any errors that originate on the server side and are received by the client from the server. For a list of server-side errors, see [Chapter 2, Server Error Message Reference](#).

In addition to the errors in the following list, the client library can also produce error messages that have error codes in the range from 1 to 999. See [Chapter 4, Global Error Message Reference](#)

- Error number: `2000`; Symbol: `CR_UNKNOWN_ERROR`;
Message: Unknown MySQL error
- Error number: `2001`; Symbol: `CR_SOCKET_CREATE_ERROR`;
Message: Can't create UNIX socket (%d)
- Error number: `2002`; Symbol: `CR_CONNECTION_ERROR`;
Message: Can't connect to local MySQL server through socket '%s' (%d)
- Error number: `2003`; Symbol: `CR_CONN_HOST_ERROR`;
Message: Can't connect to MySQL server on '%s:%u' (%d)
- Error number: `2004`; Symbol: `CR_IPSOCK_ERROR`;
Message: Can't create TCP/IP socket (%d)
- Error number: `2005`; Symbol: `CR_UNKNOWN_HOST`;
Message: Unknown MySQL server host '%s' (%d)
- Error number: `2006`; Symbol: `CR_SERVER_GONE_ERROR`;
Message: MySQL server has gone away
- Error number: `2007`; Symbol: `CR_VERSION_ERROR`;
Message: Protocol mismatch; server version = %d, client version = %d
- Error number: `2008`; Symbol: `CR_OUT_OF_MEMORY`;
Message: MySQL client ran out of memory
- Error number: `2009`; Symbol: `CR_WRONG_HOST_INFO`;
Message: Wrong host info
- Error number: `2010`; Symbol: `CR_LOCALHOST_CONNECTION`;
Message: Localhost via UNIX socket

- Error number: 2011; Symbol: `CR_TCP_CONNECTION`;
Message: %s via TCP/IP
- Error number: 2012; Symbol: `CR_SERVER_HANDSHAKE_ERR`;
Message: Error in server handshake
- Error number: 2013; Symbol: `CR_SERVER_LOST`;
Message: Lost connection to MySQL server during query
- Error number: 2014; Symbol: `CR_COMMANDS_OUT_OF_SYNC`;
Message: Commands out of sync; you can't run this command now

Commands were executed in an improper order. This error occurs when a function is called that is not appropriate for the current state of the connection. For example, if `mysql_stmt_fetch()` is not called enough times to read an entire result set (that is, enough times to return `MYSQL_NO_DATA`), this error may occur for the following C API call.
- Error number: 2015; Symbol: `CR_NAMEDPIPE_CONNECTION`;
Message: Named pipe: %s
- Error number: 2016; Symbol: `CR_NAMEDPIPEWAIT_ERROR`;
Message: Can't wait for named pipe to host: %s pipe: %s (%lu)
- Error number: 2017; Symbol: `CR_NAMEDPIPEOPEN_ERROR`;
Message: Can't open named pipe to host: %s pipe: %s (%lu)
- Error number: 2018; Symbol: `CR_NAMEDPIPESETSTATE_ERROR`;
Message: Can't set state of named pipe to host: %s pipe: %s (%lu)
- Error number: 2019; Symbol: `CR_CANT_READ_CHARSET`;
Message: Can't initialize character set %s (path: %s)
- Error number: 2020; Symbol: `CR_NET_PACKET_TOO_LARGE`;
Message: Got packet bigger than 'max_allowed_packet' bytes
- Error number: 2021; Symbol: `CR_EMBEDDED_CONNECTION`;
Message: Embedded server
- Error number: 2022; Symbol: `CR_PROBE_SLAVE_STATUS`;
Message: Error on SHOW SLAVE STATUS:
- Error number: 2023; Symbol: `CR_PROBE_SLAVE_HOSTS`;
Message: Error on SHOW SLAVE HOSTS:
- Error number: 2024; Symbol: `CR_PROBE_SLAVE_CONNECT`;
Message: Error connecting to slave:
- Error number: 2025; Symbol: `CR_PROBE_MASTER_CONNECT`;
Message: Error connecting to master:

-
- Error number: 2026; Symbol: `CR_SSL_CONNECTION_ERROR`;
Message: SSL connection error: %s
 - Error number: 2027; Symbol: `CR_MALFORMED_PACKET`;
Message: Malformed packet
 - Error number: 2028; Symbol: `CR_WRONG_LICENSE`;
Message: This client library is licensed only for use with MySQL servers having '%s' license
 - Error number: 2029; Symbol: `CR_NULL_POINTER`;
Message: Invalid use of null pointer
 - Error number: 2030; Symbol: `CR_NO_PREPARE_STMT`;
Message: Statement not prepared
 - Error number: 2031; Symbol: `CR_PARAMS_NOT_BOUND`;
Message: No data supplied for parameters in prepared statement
 - Error number: 2032; Symbol: `CR_DATA_TRUNCATED`;
Message: Data truncated
 - Error number: 2033; Symbol: `CR_NO_PARAMETERS_EXISTS`;
Message: No parameters exist in the statement
 - Error number: 2034; Symbol: `CR_INVALID_PARAMETER_NO`;
Message: Invalid parameter number

The column number for `mysql_stmt_fetch_column()` was invalid.

The parameter number for `mysql_stmt_send_long_data()` was invalid.

A key name was empty or the amount of connection attribute data for `mysql_options4()` exceeds the 64KB limit.
 - Error number: 2035; Symbol: `CR_INVALID_BUFFER_USE`;
Message: Can't send long data for non-string/non-binary data types (parameter: %d)
 - Error number: 2036; Symbol: `CR_UNSUPPORTED_PARAM_TYPE`;
Message: Using unsupported buffer type: %d (parameter: %d)
 - Error number: 2037; Symbol: `CR_SHARED_MEMORY_CONNECTION`;
Message: Shared memory: %s
 - Error number: 2038; Symbol: `CR_SHARED_MEMORY_CONNECT_REQUEST_ERROR`;
Message: Can't open shared memory; client could not create request event (%lu)
 - Error number: 2039; Symbol: `CR_SHARED_MEMORY_CONNECT_ANSWER_ERROR`;
Message: Can't open shared memory; no answer event received from server (%lu)
 - Error number: 2040; Symbol: `CR_SHARED_MEMORY_CONNECT_FILE_MAP_ERROR`;

Message: Can't open shared memory; server could not allocate file mapping (%lu)

- Error number: 2041; Symbol: [CR_SHARED_MEMORY_CONNECT_MAP_ERROR](#);

Message: Can't open shared memory; server could not get pointer to file mapping (%lu)

- Error number: 2042; Symbol: [CR_SHARED_MEMORY_FILE_MAP_ERROR](#);

Message: Can't open shared memory; client could not allocate file mapping (%lu)

- Error number: 2043; Symbol: [CR_SHARED_MEMORY_MAP_ERROR](#);

Message: Can't open shared memory; client could not get pointer to file mapping (%lu)

- Error number: 2044; Symbol: [CR_SHARED_MEMORY_EVENT_ERROR](#);

Message: Can't open shared memory; client could not create %s event (%lu)

- Error number: 2045; Symbol: [CR_SHARED_MEMORY_CONNECT_ABANDONED_ERROR](#);

Message: Can't open shared memory; no answer from server (%lu)

- Error number: 2046; Symbol: [CR_SHARED_MEMORY_CONNECT_SET_ERROR](#);

Message: Can't open shared memory; cannot send request event to server (%lu)

- Error number: 2047; Symbol: [CR_CONN_UNKNOW_PROTOCOL](#);

Message: Wrong or unknown protocol

- Error number: 2048; Symbol: [CR_INVALID_CONN_HANDLE](#);

Message: Invalid connection handle

- Error number: 2049; Symbol: [CR_UNUSED_1](#);

Message: Connection using old (pre-4.1.1) authentication protocol refused (client option 'secure_auth' enabled)

- Error number: 2050; Symbol: [CR_FETCH_CANCELED](#);

Message: Row retrieval was canceled by mysql_stmt_close() call

- Error number: 2051; Symbol: [CR_NO_DATA](#);

Message: Attempt to read column without prior row fetch

- Error number: 2052; Symbol: [CR_NO_STMT_METADATA](#);

Message: Prepared statement contains no metadata

- Error number: 2053; Symbol: [CR_NO_RESULT_SET](#);

Message: Attempt to read a row while there is no result set associated with the statement

- Error number: 2054; Symbol: [CR_NOT_IMPLEMENTED](#);

Message: This feature is not implemented yet

- Error number: 2055; Symbol: [CR_SERVER_LOST_EXTENDED](#);

Message: Lost connection to MySQL server at '%s', system error: %d

- Error number: 2056; Symbol: [CR_STMT_CLOSED](#);

Message: Statement closed indirectly because of a preceding %s() call

- Error number: 2057; Symbol: CR_NEW_STMT_METADATA;

Message: The number of columns in the result set differs from the number of bound buffers. You must reset the statement, rebind the result set columns, and execute the statement again

- Error number: 2058; Symbol: CR_ALREADY_CONNECTED;

Message: This handle is already connected. Use a separate handle for each connection.

- Error number: 2059; Symbol: CR_AUTH_PLUGIN_CANNOT_LOAD;

Message: Authentication plugin '%s' cannot be loaded: %s

- Error number: 2060; Symbol: CR_DUPLICATE_CONNECTION_ATTR;

Message: There is an attribute with the same name already

A duplicate connection attribute name was specified for mysql_options4().

- Error number: 2061; Symbol: CR_AUTH_PLUGIN_ERR;

Message: Authentication plugin '%s' reported error: %s

- Error number: 2062; Symbol: CR_INSECURE_API_ERR;

Message: Insecure API function call: '%s' Use instead: '%s'

An insecure function call was detected. Modify the application to use the suggested alternative function instead.

- Error number: 2063; Symbol: CR_FILE_NAME_TOO_LONG;

Message: File name is too long

CR_FILE_NAME_TOO_LONG was added in 8.0.1.

- Error number: 2064; Symbol: CR_SSL_FIPS_MODE_ERR;

Message: Set FIPS mode ON/STRICT failed

CR_SSL_FIPS_MODE_ERR was added in 8.0.11.

- Error number: 2065; Symbol: CR_COMPRESSION_NOT_SUPPORTED;

Message: Compression protocol not supported with asynchronous protocol

CR_COMPRESSION_NOT_SUPPORTED was added in 8.0.16, removed after 8.0.20.

- Error number: 2065; Symbol: CR_DEPRECATED_COMPRESSION_NOT_SUPPORTED;

Message: Compression protocol not supported with asynchronous protocol

CR_DEPRECATED_COMPRESSION_NOT_SUPPORTED was added in 8.0.21.

- Error number: 2066; Symbol: CR_COMPRESSION_WRONGLY_CONFIGURED;

Message: Connection failed due to wrongly configured compression algorithm

CR_COMPRESSION_WRONGLY_CONFIGURED was added in 8.0.18.

- Error number: 2067; Symbol: CR_KERBEROS_USER_NOT_FOUND;

Message: SSO user not found, Please perform SSO authentication using kerberos.

`CR_KERBEROS_USER_NOT_FOUND` was added in 8.0.20.

- Error number: [2068](#); Symbol: `CR_LOAD_DATA_LOCAL_INFILE_REJECTED`;

Message: LOAD DATA LOCAL INFILE file request rejected due to restrictions on access.

`CR_LOAD_DATA_LOCAL_INFILE_REJECTED` was added in 8.0.21.

- Error number: [2069](#); Symbol: `CR_LOAD_DATA_LOCAL_INFILE_REALPATH_FAIL`;

Message: Determining the real path for '%s' failed with error (%d): %s

`CR_LOAD_DATA_LOCAL_INFILE_REALPATH_FAIL` was added in 8.0.21.

- Error number: [2070](#); Symbol: `CR_DNS_SRV_LOOKUP_FAILED`;

Message: DNS SRV lookup failed with error : %d

`CR_DNS_SRV_LOOKUP_FAILED` was added in 8.0.22.

Chapter 4 Global Error Message Reference

This document lists “global” error messages that are shared in the sense that they can be produced by the MySQL server or by MySQL client programs. These errors have error codes in the range from 1 to 999.

Each global error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#). For global errors, the SQLSTATE value is always '`HY000`' (general error), so it is not meaningful for distinguishing one client error from another.

If the server writes a message to the error log that has a global error code, it pads the error code with leading zeros to six digits and adds a prefix of `MY-` (example: `MY-000022`). The following list displays error codes in that format.

If a client returns a message with a global error code, it adds no zero-padding or prefix to the error code.

- Error number: `1`; Symbol: `EE_CANTCREATEFILE`;

Message: Can't create/write to file '%s' (OS errno %d - %s)

- Error number: `2`; Symbol: `EE_READ`;

Message: Error reading file '%s' (OS errno %d - %s)

- Error number: `3`; Symbol: `EE_WRITE`;

Message: Error writing file '%s' (OS errno %d - %s)

- Error number: `4`; Symbol: `EE_BADCLOSE`;

Message: Error on close of '%s' (OS errno %d - %s)

- Error number: `5`; Symbol: `EE_OUTOFMEMORY`;

Message: Out of memory (Needed %u bytes)

- Error number: `6`; Symbol: `EE_DELETE`;

Message: Error on delete of '%s' (OS errno %d - %s)

- Error number: `7`; Symbol: `EE_LINK`;

Message: Error on rename of '%s' to '%s' (OS errno %d - %s)

- Error number: `9`; Symbol: `EE_EOFERR`;

Message: Unexpected EOF found when reading file '%s' (OS errno %d - %s)

- Error number: `10`; Symbol: `EE_CANTLOCK`;

Message: Can't lock file (OS errno %d - %s)

- Error number: `11`; Symbol: `EE_CANTUNLOCK`;

Message: Can't unlock file (OS errno %d - %s)

- Error number: `12`; Symbol: `EE_DIR`;

Message: Can't read dir of '%s' (OS errno %d - %s)

- Error number: `13`; Symbol: `EE_STAT`;

Message: Can't get stat of '%s' (OS errno %d - %s)

- Error number: [14](#); Symbol: [EE_CANT_CHSIZE](#);

Message: Can't change size of file (OS errno %d - %s)

- Error number: [15](#); Symbol: [EE_CANT_OPEN_STREAM](#);

Message: Can't open stream from handle (OS errno %d - %s)

- Error number: [16](#); Symbol: [EE_GETWD](#);

Message: Can't get working directory (OS errno %d - %s)

- Error number: [17](#); Symbol: [EE_SETWD](#);

Message: Can't change dir to '%s' (OS errno %d - %s)

- Error number: [18](#); Symbol: [EE_LINK_WARNING](#);

Message: Warning: '%s' had %d links

- Error number: [19](#); Symbol: [EE_OPEN_WARNING](#);

Message: Warning: %d files and %d streams are left open

- Error number: [20](#); Symbol: [EE_DISK_FULL](#);

Message: Disk is full writing '%s' (OS errno %d - %s). Waiting for someone to free space...

- Error number: [21](#); Symbol: [EE_CANT_MKDIR](#);

Message: Can't create directory '%s' (OS errno %d - %s)

- Error number: [22](#); Symbol: [EE_UNKNOWN_CHARSET](#);

Message: Character set '%s' is not a compiled character set and is not specified in the '%s' file

- Error number: [23](#); Symbol: [EE_OUT_OF_FILERESOURCES](#);

Message: Out of resources when opening file '%s' (OS errno %d - %s)

- Error number: [24](#); Symbol: [EE_CANT_READLINK](#);

Message: Can't read value for symlink '%s' (Error %d - %s)

- Error number: [25](#); Symbol: [EE_CANT_SYMLINK](#);

Message: Can't create symlink '%s' pointing at '%s' (Error %d - %s)

- Error number: [26](#); Symbol: [EE_REALPATH](#);

Message: Error on realpath() on '%s' (Error %d - %s)

- Error number: [27](#); Symbol: [EE_SYNC](#);

Message: Can't sync file '%s' to disk (OS errno %d - %s)

- Error number: [28](#); Symbol: [EE_UNKNOWN_COLLATION](#);

Message: Collation '%s' is not a compiled collation and is not specified in the '%s' file

- Error number: [29](#); Symbol: [EE_FILENOFOUND](#);

Message: File '%s' not found (OS errno %d - %s)

- Error number: 30; Symbol: `EE_FILE_NOT_CLOSED`;

Message: File '%s' (fileno: %d) was not closed

- Error number: 31; Symbol: `EE_CHANGE_OWNERSHIP`;

Message: Cannot change ownership of the file '%s' (OS errno %d - %s)

- Error number: 32; Symbol: `EE_CHANGE_PERMISSIONS`;

Message: Cannot change permissions of the file '%s' (OS errno %d - %s)

- Error number: 33; Symbol: `EE_CANT_SEEK`;

Message: Cannot seek in file '%s' (OS errno %d - %s)

- Error number: 34; Symbol: `EE_CAPACITY_EXCEEDED`;

Message: Memory capacity exceeded (capacity %llu bytes)

- Error number: 35; Symbol: `EE_DISK_FULL_WITH_RETRY_MSG`;

Message: Disk is full writing '%s' (OS errno %d - %s). Waiting for someone to free space... Retry in %d secs. Message reprinted in %d secs.

`EE_DISK_FULL_WITH_RETRY_MSG` was added in 8.0.13.

- Error number: 36; Symbol: `EE_FAILED_TO_CREATE_TIMER`;

Message: Failed to create timer (OS errno %d).

`EE_FAILED_TO_CREATE_TIMER` was added in 8.0.13.

- Error number: 37; Symbol: `EE_FAILED_TO_DELETE_TIMER`;

Message: Failed to delete timer (OS errno %d).

`EE_FAILED_TO_DELETE_TIMER` was added in 8.0.13.

- Error number: 38; Symbol: `EE_FAILED_TO_CREATE_TIMER_QUEUE`;

Message: Failed to create timer queue (OS errno %d).

`EE_FAILED_TO_CREATE_TIMER_QUEUE` was added in 8.0.13.

- Error number: 39; Symbol: `EE_FAILED_TO_START_TIMER_NOTIFY_THREAD`;

Message: Failed to start timer notify thread.

`EE_FAILED_TO_START_TIMER_NOTIFY_THREAD` was added in 8.0.13.

- Error number: 40; Symbol:

`EE_FAILED_TO_CREATE_TIMER_NOTIFY_THREAD_INTERRUPT_EVENT`;

Message: Failed to create event to interrupt timer notifier thread (OS errno %d).

`EE_FAILED_TO_CREATE_TIMER_NOTIFY_THREAD_INTERRUPT_EVENT` was added in 8.0.13.

- Error number: 41; Symbol: `EE_EXITING_TIMER_NOTIFY_THREAD`;

Message: Failed to register timer event with queue (OS errno %d), exiting timer notifier thread.

`EE_EXITING_TIMER_NOTIFY_THREAD` was added in 8.0.13.

- Error number: [42](#); Symbol: `EE_WIN_LIBRARY_LOAD_FAILED`;

Message: LoadLibrary("kernel32.dll") failed: GetLastError returns %lu.

`EE_WIN_LIBRARY_LOAD_FAILED` was added in 8.0.13.

- Error number: [43](#); Symbol: `EE_WIN_RUN_TIME_ERROR_CHECK`;

Message: %s.

`EE_WIN_RUN_TIME_ERROR_CHECK` was added in 8.0.13.

- Error number: [44](#); Symbol: `EE_FAILED_TO_DETERMINE_LARGE_PAGE_SIZE`;

Message: Failed to determine large page size.

`EE_FAILED_TO_DETERMINE_LARGE_PAGE_SIZE` was added in 8.0.13.

- Error number: [45](#); Symbol: `EE_FAILED_TO_KILL_ALL_THREADS`;

Message: Error in my_thread_global_end(): %d thread(s) did not exit.

`EE_FAILED_TO_KILL_ALL_THREADS` was added in 8.0.13.

- Error number: [46](#); Symbol: `EE_FAILED_TO_CREATE_IO_COMPLETION_PORT`;

Message: Failed to create IO completion port (OS error %d).

`EE_FAILED_TO_CREATE_IO_COMPLETION_PORT` was added in 8.0.13.

- Error number: [47](#); Symbol: `EE_FAILED_TO_OPEN_DEFAULTS_FILE`;

Message: Failed to open required defaults file: %s

`EE_FAILED_TO_OPEN_DEFAULTS_FILE` was added in 8.0.13.

- Error number: [48](#); Symbol: `EE_FAILED_TO_HANDLE_DEFAULTS_FILE`;

Message: Fatal error in defaults handling. Program aborted!

`EE_FAILED_TO_HANDLE_DEFAULTS_FILE` was added in 8.0.13.

- Error number: [49](#); Symbol: `EE_WRONG_DIRECTIVE_IN_CONFIG_FILE`;

Message: Wrong '!%s' directive in config file %s at line %d.

`EE_WRONG_DIRECTIVE_IN_CONFIG_FILE` was added in 8.0.13.

- Error number: [50](#); Symbol: `EE_SKIPPING_DIRECTIVE_DUE_TO_MAX_INCLUDE_RECURSION`;

Message: Skipping '%s' directive as maximum include recursion level was reached in file %s at line %d.

`EE_SKIPPING_DIRECTIVE_DUE_TO_MAX_INCLUDE_RECURSION` was added in 8.0.13.

- Error number: [51](#); Symbol: `EE_INCORRECT_GRP_DEFINITION_IN_CONFIG_FILE`;

Message: Wrong group definition in config file %s at line %d.

`EE_INCORRECT_GRP_DEFINITION_IN_CONFIG_FILE` was added in 8.0.13.

- Error number: [52](#); Symbol: `EE_OPTION_WITHOUT_GRP_IN_CONFIG_FILE`;

Message: Found option without preceding group in config file %s at line %d.

`EE_OPTION_WITHOUT_GRP_IN_CONFIG_FILE` was added in 8.0.13.

- Error number: 53; Symbol: `EE_CONFIG_FILE_PERMISSION_ERROR`;

Message: %s should be readable/writable only by current user.

`EE_CONFIG_FILE_PERMISSION_ERROR` was added in 8.0.13.

- Error number: 54; Symbol: `EE_IGNORE_WORLD_WRITABLE_CONFIG_FILE`;

Message: World-writable config file '%s' is ignored.

`EE_IGNORE_WORLD_WRITABLE_CONFIG_FILE` was added in 8.0.13.

- Error number: 55; Symbol: `EE_USING_DISABLED_OPTION`;

Message: %s: Option '%s' was used, but is disabled.

`EE_USING_DISABLED_OPTION` was added in 8.0.13.

- Error number: 56; Symbol: `EE_USING_DISABLED_SHORT_OPTION`;

Message: %s: Option '-%c' was used, but is disabled.

`EE_USING_DISABLED_SHORT_OPTION` was added in 8.0.13.

- Error number: 57; Symbol: `EE_USING_PASSWORD_ON_CLI_IS_INSECURE`;

Message: Using a password on the command line interface can be insecure.

`EE_USING_PASSWORD_ON_CLI_IS_INSECURE` was added in 8.0.13.

- Error number: 58; Symbol: `EE_UNKNOWN_SUFFIX_FOR_VARIABLE`;

Message: Unknown suffix '%c' used for variable '%s' (value '%s').

`EE_UNKNOWN_SUFFIX_FOR_VARIABLE` was added in 8.0.13.

- Error number: 59; Symbol: `EE_SSL_ERROR_FROM_FILE`;

Message: SSL error: %s from '%s'.

`EE_SSL_ERROR_FROM_FILE` was added in 8.0.13.

- Error number: 60; Symbol: `EE_SSL_ERROR`;

Message: SSL error: %s.

`EE_SSL_ERROR` was added in 8.0.13.

- Error number: 61; Symbol: `EE_NET_SEND_ERROR_IN_BOOTSTRAP`;

Message: %d %s.

`EE_NET_SEND_ERROR_IN_BOOTSTRAP` was added in 8.0.13.

- Error number: 62; Symbol: `EE_PACKETS_OUT_OF_ORDER`;

Message: Packets out of order (found %u, expected %u).

`EE_PACKETS_OUT_OF_ORDER` was added in 8.0.13.

- Error number: 63; Symbol: `EE_UNKNOWN_PROTOCOL_OPTION`;
Message: Unknown option to protocol: %s.
`EE_UNKNOWN_PROTOCOL_OPTION` was added in 8.0.13.
- Error number: 64; Symbol: `EE_FAILED_TO_LOCATE_SERVER_PUBLIC_KEY`;
Message: Failed to locate server public key '%s'.
`EE_FAILED_TO_LOCATE_SERVER_PUBLIC_KEY` was added in 8.0.13.
- Error number: 65; Symbol: `EE_PUBLIC_KEY_NOT_IN_PEM_FORMAT`;
Message: Public key is not in Privacy Enhanced Mail format: '%s'.
`EE_PUBLIC_KEY_NOT_IN_PEM_FORMAT` was added in 8.0.13.
- Error number: 66; Symbol: `EE_DEBUG_INFO`;
Message: %s.
`EE_DEBUG_INFO` was added in 8.0.13.
- Error number: 67; Symbol: `EE_UNKNOWN_VARIABLE`;
Message: unknown variable '%s'.
`EE_UNKNOWN_VARIABLE` was added in 8.0.13.
- Error number: 68; Symbol: `EE_UNKNOWN_OPTION`;
Message: unknown option '--%s'.
`EE_UNKNOWN_OPTION` was added in 8.0.13.
- Error number: 69; Symbol: `EE_UNKNOWN_SHORT_OPTION`;
Message: %s: unknown option '-%c'.
`EE_UNKNOWN_SHORT_OPTION` was added in 8.0.13.
- Error number: 70; Symbol: `EE_OPTION_WITHOUT_ARGUMENT`;
Message: %s: option '--%s' cannot take an argument.
`EE_OPTION_WITHOUT_ARGUMENT` was added in 8.0.13.
- Error number: 71; Symbol: `EE_OPTIONQUIRES_ARGUMENT`;
Message: %s: option '--%s' requires an argument.
`EE_OPTIONQUIRES_ARGUMENT` was added in 8.0.13.
- Error number: 72; Symbol: `EE_SHORTOPTIONQUIRES_ARGUMENT`;
Message: %s: option '-%c' requires an argument.
`EE_SHORTOPTIONQUIRES_ARGUMENT` was added in 8.0.13.
- Error number: 73; Symbol: `EE_OPTION_IGNORED_DUE_TO_INVALID_VALUE`;
Message: %s: ignoring option '--%s' due to invalid value '%s'.
`EE_OPTION_IGNORED_DUE_TO_INVALID_VALUE` was added in 8.0.13.

-
- Error number: 74; Symbol: `EE_OPTION_WITH_EMPTY_VALUE`;
Message: %s: Empty value for '%s' specified.
`EE_OPTION_WITH_EMPTY_VALUE` was added in 8.0.13.
 - Error number: 75; Symbol: `EE_FAILED_TO_ASSIGN_MAX_VALUE_TO_OPTION`;
Message: %s: Maximum value of '%s' cannot be set.
`EE_FAILED_TO_ASSIGN_MAX_VALUE_TO_OPTION` was added in 8.0.13.
 - Error number: 76; Symbol: `EE_INCORRECT_BOOLEAN_VALUE_FOR_OPTION`;
Message: option '%s': boolean value '%s' was not recognized. Set to OFF.
`EE_INCORRECT_BOOLEAN_VALUE_FOR_OPTION` was added in 8.0.13.
 - Error number: 77; Symbol: `EE_FAILED_TO_SET_OPTION_VALUE`;
Message: %s: Error while setting value '%s' to '%s'.
`EE_FAILED_TO_SET_OPTION_VALUE` was added in 8.0.13.
 - Error number: 78; Symbol: `EE_INCORRECT_INT_VALUE_FOR_OPTION`;
Message: Incorrect integer value: '%s'.
`EE_INCORRECT_INT_VALUE_FOR_OPTION` was added in 8.0.13.
 - Error number: 79; Symbol: `EE_INCORRECT_UINT_VALUE_FOR_OPTION`;
Message: Incorrect unsigned integer value: '%s'.
`EE_INCORRECT_UINT_VALUE_FOR_OPTION` was added in 8.0.13.
 - Error number: 80; Symbol: `EE_ADJUSTED_SIGNED_VALUE_FOR_OPTION`;
Message: option '%s': signed value %s adjusted to %s.
`EE_ADJUSTED_SIGNED_VALUE_FOR_OPTION` was added in 8.0.13.
 - Error number: 81; Symbol: `EE_ADJUSTED_UNSIGNED_VALUE_FOR_OPTION`;
Message: option '%s': unsigned value %s adjusted to %s.
`EE_ADJUSTED_UNSIGNED_VALUE_FOR_OPTION` was added in 8.0.13.
 - Error number: 82; Symbol: `EE_ADJUSTED_ULONGLONG_VALUE_FOR_OPTION`;
Message: option '%s': value %s adjusted to %s.
`EE_ADJUSTED_ULONGLONG_VALUE_FOR_OPTION` was added in 8.0.13.
 - Error number: 83; Symbol: `EE_ADJUSTED_DOUBLE_VALUE_FOR_OPTION`;
Message: option '%s': value %g adjusted to %g.
`EE_ADJUSTED_DOUBLE_VALUE_FOR_OPTION` was added in 8.0.13.
 - Error number: 84; Symbol: `EE_INVALID_DECIMAL_VALUE_FOR_OPTION`;
Message: Invalid decimal value for option '%s'.
`EE_INVALID_DECIMAL_VALUE_FOR_OPTION` was added in 8.0.13.

-
- Error number: 85; Symbol: `EE_COLLATION_PARSER_ERROR`;
Message: %s.

`EE_COLLATION_PARSER_ERROR` was added in 8.0.13.
 - Error number: 86; Symbol: `EE_FAILED_TO_RESET_BEFORE_PRIMARY_IGNORABLE_CHAR`;
Message: Failed to reset before a primary ignorable character %s.

`EE_FAILED_TO_RESET_BEFORE_PRIMARY_IGNORABLE_CHAR` was added in 8.0.13.
 - Error number: 87; Symbol: `EE_FAILED_TO_RESET_BEFORE_TERTIARY_IGNORABLE_CHAR`;
Message: Failed to reset before a tertiary ignorable character %s.

`EE_FAILED_TO_RESET_BEFORE_TERTIARY_IGNORABLE_CHAR` was added in 8.0.13.
 - Error number: 88; Symbol: `EE_SHIFT_CHAR_OUT_OF_RANGE`;
Message: Shift character out of range: %s.

`EE_SHIFT_CHAR_OUT_OF_RANGE` was added in 8.0.13.
 - Error number: 89; Symbol: `EE_RESET_CHAR_OUT_OF_RANGE`;
Message: Reset character out of range: %s.

`EE_RESET_CHAR_OUT_OF_RANGE` was added in 8.0.13.
 - Error number: 90; Symbol: `EE_UNKNOWN_LDML_TAG`;
Message: Unknown LDML tag: '%.*s'.

`EE_UNKNOWN_LDML_TAG` was added in 8.0.13.
 - Error number: 91; Symbol: `EE_FAILED_TO_RESET_BEFORE_SECONDARY_IGNORABLE_CHAR`;
Message: Failed to reset before a secondary ignorable character %s.

`EE_FAILED_TO_RESET_BEFORE_SECONDARY_IGNORABLE_CHAR` was added in 8.0.16.

Index

C

CR_ALREADY_CONNECTED error code, 531
CR_AUTH_PLUGIN_CANNOT_LOAD error code, 531
CR_AUTH_PLUGIN_ERR error code, 531
CR_CANT_READ_CHARSET error code, 528
CR_COMMANDS_OUT_OF_SYNC error code, 528
CR_COMPRESSION_NOT_SUPPORTED error code, 531
CR_COMPRESSION_WRONGLY_CONFIGURED error code, 531
CR_CONNECTION_ERROR error code, 527
CR_CONN_HOST_ERROR error code, 527
CR_CONN_UNKNOW_PROTOCOL error code, 530
CR_DATA_TRUNCATED error code, 529
CR_DEPRECATED_COMPRESSION_NOT_SUPPORTED error code, 531
CR_DNS_SRV_LOOKUP_FAILED error code, 532
CR_DUPLICATE_CONNECTION_ATTR error code, 531
CR_EMBEDDED_CONNECTION error code, 528
CR_FETCH_CANCELED error code, 530
CR_FILE_NAME_TOO_LONG error code, 531
CR_INSECURE_API_ERR error code, 531
CR_INVALID_BUFFER_USE error code, 529
CR_INVALID_CONN_HANDLE error code, 530
CR_INVALID_PARAMETER_NO error code, 529
CR_IPSOCK_ERROR error code, 527
CR_KERBEROS_USER_NOT_FOUND error code, 532
CR_LOAD_DATA_LOCAL_INFILE_REALPATH_FAIL error code, 532
CR_LOAD_DATA_LOCAL_INFILE_REJECTED error code, 532
CR_LOCALHOST_CONNECTION error code, 527
CR_MALFORMED_PACKET error code, 529
CR_NAMEDPIPEOPEN_ERROR error code, 528
CR_NAMEDPIPESETSTATE_ERROR error code, 528
CR_NAMEDPIPEWAIT_ERROR error code, 528
CR_NAMEDPIPE_CONNECTION error code, 528
CR_NET_PACKET_TOO_LARGE error code, 528
CR_NEW_STMT_METADATA error code, 531
CR_NOT_IMPLEMENTED error code, 530
CR_NO_DATA error code, 530
CR_NO_PARAMETERS_EXISTS error code, 529
CR_NO_PREPARE_STMT error code, 529
CR_NO_RESULT_SET error code, 530
CR_NO_STMT_METADATA error code, 530
CR_NULL_POINTER error code, 529
CR_OUT_OF_MEMORY error code, 527
CR_PARAMS_NOT_BOUND error code, 529
CR_PROBE_MASTER_CONNECT error code, 528
CR_PROBE_SLAVE_CONNECT error code, 528
CR_PROBE_SLAVE_HOSTS error code, 528
CR_PROBE_SLAVE_STATUS error code, 528
CR_SERVER_GONE_ERROR error code, 527

CR_SERVER_HANDSHAKE_ERR error code, 528
CR_SERVER_LOST error code, 528
CR_SERVER_LOST_EXTENDED error code, 530
CR_SHARED_MEMORY_CONNECTION error code, 529
CR_SHARED_MEMORY_CONNECT_ABANDONED_ERROR error code, 530
CR_SHARED_MEMORY_CONNECT_ANSWER_ERROR error code, 529
CR_SHARED_MEMORY_CONNECT_FILE_MAP_ERROR error code, 530
CR_SHARED_MEMORY_CONNECT_MAP_ERROR error code, 530
CR_SHARED_MEMORY_CONNECT_REQUEST_ERROR error code, 529
CR_SHARED_MEMORY_CONNECT_SET_ERROR error code, 530
CR_SHARED_MEMORY_EVENT_ERROR error code, 530
CR_SHARED_MEMORY_FILE_MAP_ERROR error code, 530
CR_SHARED_MEMORY_MAP_ERROR error code, 530
CR_SOCKET_CREATE_ERROR error code, 527
CR_SSL_CONNECTION_ERROR error code, 529
CR_SSL_FIPS_MODE_ERR error code, 531
CR_STMT_CLOSED error code, 531
CR_TCP_CONNECTION error code, 528
CR_UNKNOWN_ERROR error code, 527
CR_UNKNOWN_HOST error code, 527
CR_UNSUPPORTED_PARAM_TYPE error code, 529
CR_UNUSED_1 error code, 530
CR_VERSION_ERROR error code, 527
CR_WRONG_HOST_INFO error code, 527
CR_WRONG_LICENSE error code, 529

E

EE_ADJUSTED_DOUBLE_VALUE_FOR_OPTION error code, 539
EE_ADJUSTED_SIGNED_VALUE_FOR_OPTION error code, 539
EE_ADJUSTED_ULONGLONG_VALUE_FOR_OPTION error code, 539
EE_ADJUSTED_UNSIGNED_VALUE_FOR_OPTION error code, 539
EE_BADCLOSE error code, 533
EE_CANTCREATEFILE error code, 533
EE_CANTLOCK error code, 533
EE_CANTUNLOCK error code, 533
EE_CANT_CHSIZE error code, 534
EE_CANT_MKDIR error code, 534
EE_CANT_OPEN_STREAM error code, 534
EE_CANT_READLINK error code, 534
EE_CANT_SEEK error code, 535
EE_CANT_SYMLINK error code, 534
EE_CAPACITY_EXCEEDED error code, 535
EE_CHANGE_OWNERSHIP error code, 535
EE_CHANGE_PERMISSIONS error code, 535

EE_COLLATION_PARSER_ERROR error code, 540
EE_CONFIG_FILE_PERMISSION_ERROR error code, 537
EE_DEBUG_INFO error code, 538
EE_DELETE error code, 533
EE_DIR error code, 533
EE_DISK_FULL error code, 534
EE_DISK_FULL_WITH_RETRY_MSG error code, 535
EE_EOFERR error code, 533
EE_EXITING_TIMER_NOTIFY_THREAD error code, 536
EE_FAILED_TO_ASSIGN_MAX_VALUE_TO_OPTION error code, 539
EE_FAILED_TO_CREATE_IO_COMPLETION_PORT error code, 536
EE_FAILED_TO_CREATE_TIMER error code, 535
EE_FAILED_TO_CREATE_TIMER_NOTIFY_THREAD_INTERRUPT_EVENT error code, 535
EE_FAILED_TO_CREATE_TIMER_QUEUE error code, 535
EE_FAILED_TO_DELETE_TIMER error code, 535
EE_FAILED_TO_DETERMINE_LARGE_PAGE_SIZE error code, 536
EE_FAILED_TO_HANDLE_DEFAULTS_FILE error code, 536
EE_FAILED_TO_KILL_ALL_THREADS error code, 536
EE_FAILED_TO_LOCATE_SERVER_PUBLIC_KEY error code, 538
EE_FAILED_TO_OPEN_DEFAULTS_FILE error code, 536
EE_FAILED_TO_RESET_BEFORE_PRIMARY_IGNOREABLE error code, 540
EE_FAILED_TO_RESET_BEFORE_SECONDARY_IGNOREABLE error code, 540
EE_FAILED_TO_RESET_BEFORE_TERTIARY_IGNOREABLE error code, 540
EE_FAILED_TO_SET_OPTION_VALUE error code, 539
EE_FAILED_TO_START_TIMER_NOTIFY_THREAD error code, 535
EE_FILENOFOUND error code, 535
EE_FILE_NOT_CLOSED error code, 535
EE_GETWD error code, 534
EE_IGNORE_WORLD_WRITABLE_CONFIG_FILE error code, 537
EE_INCORRECT_BOOLEAN_VALUE_FOR_OPTION error code, 539
EE_INCORRECT_GRP_DEFINITION_IN_CONFIG_FILE error code, 536
EE_INCORRECT_INT_VALUE_FOR_OPTION error code, 539
EE_INCORRECT_UINT_VALUE_FOR_OPTION error code, 539
EE_INVALID_DECIMAL_VALUE_FOR_OPTION error code, 539
EE_LINK error code, 533
EE_LINK_WARNING error code, 534
EE_NET_SEND_ERROR_IN_BOOTSTRAP error code, 537
EE_OPEN_WARNING error code, 534
EE_OPTION_IGNORED_DUE_TO_INVALID_VALUE error code, 538
EE_OPTION_REQUIRES_ARGUMENT error code, 538
EE_OPTION_WITHOUT_ARGUMENT error code, 538
EE_OPTION_WITHOUT_GRP_IN_CONFIG_FILE error code, 537
EE_OPTION_WITH_EMPTY_VALUE error code, 539
EE_OUTOOMEMORY error code, 533
EE_OUT_OF_FILERESOURCES error code, 534
EE_PACKETS_OUT_OF_ORDER error code, 537
EE_PUBLIC_KEY_NOT_IN_PEM_FORMAT error code, 538
EE_REALPATH error code, 534
EE_RESET_CHAR_OUT_OF_RANGE error code, 540
EE_SETWD error code, 534
EE_SHIFT_CHAR_OUT_OF_RANGE error code, 540
EE_SHORT_OPTION_REQUIRES_ARGUMENT error code, 538
EE_SKIPPING_DIRECTIVE_DUE_TO_MAX_INCLUDE_RECURSION error code, 536
EE_SSL_ERROR error code, 537
EE_SSL_ERROR_FROM_FILE error code, 537
EE_STAT error code, 534
EE_SYNC error code, 534
EE_UNKNOWN_CHARSET error code, 534
EE_UNKNOWN_COLLATION error code, 534
EE_UNKNOWN_LDML_TAG error code, 540
EE_UNKNOWN_OPTION error code, 538
EE_UNKNOWN_PROTOCOL_OPTION error code, 538
EE_UNKOWN_SHORT_OPTION error code, 538
EE_UNKOWN_SUFFIX_FOR_VARIABLE error code, 537
EE_UNKNOWN_VARIABLE error code, 538
EE_USING_DISABLED_OPTION error code, 537
EE_USING_DISABLED_SHORT_OPTION error code, 537
EE_USING_PASSWORD_ON_CLI_IS_INSECURE error code, 537
EE_WIN_LIBRARY_LOAD_FAILED error code, 536
EE_WIN_RUN_TIME_ERROR_CHECK error code, 536
EE_WRITE error code, 533
EE_WRONG_DIRECTIVE_IN_CONFIG_FILE error code, 536
error code
 CR_ALREADY_CONNECTED, 531
 CR_AUTH_PLUGIN_CANNOT_LOAD, 531
 CR_AUTH_PLUGIN_ERR, 531
 CR_CANT_READ_CHARSET, 528
 CR_COMMANDS_OUT_OF_SYNC, 528
 CR_COMPRESSION_NOT_SUPPORTED, 531

CR_COMPRESSION_WRONGLTY_CONFIGURED, 531
CR_CONNECTION_ERROR, 527
CR_CONN_HOST_ERROR, 527
CR_CONN_UNKNOW_PROTOCOL, 530
CR_DATA_TRUNCATED, 529
CR_DEPRECATED_COMPRESSION_NOT_SUPPORTED, 531
CR_DNS_SRV_LOOKUP_FAILED, 532
CR_DUPLICATE_CONNECTION_ATTR, 531
CR_EMBEDDED_CONNECTION, 528
CR_FETCH_CANCELED, 530
CR_FILE_NAME_TOO_LONG, 531
CR_INSECURE_API_ERR, 531
CR_INVALID_BUFFER_USE, 529
CR_INVALID_CONN_HANDLE, 530
CR_INVALID_PARAMETER_NO, 529
CR_IPSOCK_ERROR, 527
CR_KERBEROS_USER_NOT_FOUND, 532
CR_LOAD_DATA_LOCAL_INFILE_REALPATH_FAIL, 532
CR_LOAD_DATA_LOCAL_INFILE_REJECTED, 532
CR_LOCALHOST_CONNECTION, 527
CR_MALFORMED_PACKET, 529
CR_NAMEDPIPEOPEN_ERROR, 528
CR_NAMEDPIPESETSTATE_ERROR, 528
CR_NAMEDPIPEWAIT_ERROR, 528
CR_NAMEDPIPE_CONNECTION, 528
CR_NET_PACKET_TOO_LARGE, 528
CR_NEW_STMT_METADATA, 531
CR_NOT_IMPLEMENTED, 530
CR_NO_DATA, 530
CR_NO_PARAMETERS_EXISTS, 529
CR_NO_PREPARE_STMT, 529
CR_NO_RESULT_SET, 530
CR_NO_STMT_METADATA, 530
CR_NULL_POINTER, 529
CR_OUT_OF_MEMORY, 527
CR_PARAMS_NOT_BOUND, 529
CR_PROBE_MASTER_CONNECT, 528
CR_PROBE_SLAVE_CONNECT, 528
CR_PROBE_SLAVE_HOSTS, 528
CR_PROBE_SLAVE_STATUS, 528
CR_SERVER_GONE_ERROR, 527
CR_SERVER_HANDSHAKE_ERR, 528
CR_SERVER_LOST, 528
CR_SERVER_LOST_EXTENDED, 530
CR_SHARED_MEMORY_CONNECTION, 529
CR_SHARED_MEMORY_CONNECT_ABANDONED_ERROR, 530
CR_SHARED_MEMORY_CONNECT_ANSWER_ERROR, 529
CR_SHARED_MEMORY_CONNECT_FILE_MAP_ERROR, 530
CR_SHARED_MEMORY_CONNECT_MAP_ERROR, 530
CR_SHARED_MEMORY_CONNECT_REQUEST_ERROR, 529
CR_SHARED_MEMORY_CONNECT_SET_ERROR, 530
CR_SHARED_MEMORY_EVENT_ERROR, 530
CR_SHARED_MEMORY_FILE_MAP_ERROR, 530
CR_SHARED_MEMORY_MAP_ERROR, 530
CR_SOCKET_CREATE_ERROR, 527
CR_SSL_CONNECTION_ERROR, 529
CR_SSL_FIPS_MODE_ERR, 531
CR_STMT_CLOSED, 531
CR_TCP_CONNECTION, 528
CR_UNKNOWN_ERROR, 527
CR_UNKNOWN_HOST, 527
CR_UNSUPPORTED_PARAM_TYPE, 529
CR_UNUSED_1, 530
CR_VERSION_ERROR, 527
CR_WRONG_HOST_INFO, 527
CR_WRONG_LICENSE, 529
EE_ADJUSTED_DOUBLE_VALUE_FOR_OPTION, 539
EE_ADJUSTED_SIGNED_VALUE_FOR_OPTION, 539
EE_ADJUSTED_ULONGLONG_VALUE_FOR_OPTION, 539
EE_ADJUSTED_UNSIGNED_VALUE_FOR_OPTION, 539
EE_BADCLOSE, 533
EE_CANTCREATEFILE, 533
EE_CANTLOCK, 533
EE_CANTUNLOCK, 533
EE_CANT_CHSIZE, 534
EE_CANT_MKDIR, 534
EE_CANT_OPEN_STREAM, 534
EE_CANT_READLINK, 534
EE_CANT_SEEK, 535
EE_CANT_SYMLINK, 534
EE_CAPACITY_EXCEEDED, 535
EE_CHANGE_OWNERSHIP, 535
EE_CHANGE_PERMISSIONS, 535
EE_COLLATION_PARSER_ERROR, 540
EE_CONFIG_FILE_PERMISSION_ERROR, 537
EE_DEBUG_INFO, 538
EE_DELETE, 533
EE_DIR, 533
EE_DISK_FULL, 534
EE_DISK_FULL_WITH_RETRY_MSG, 535
EE_EOFERR, 533
EE_EXITING_TIMER_NOTIFY_THREAD, 536
EE_FAILED_TO_ASSIGN_MAX_VALUE_TO_OPTION, 539
EE_FAILED_TO_CREATE_IO_COMPLETION_PORT, 536
EE_FAILED_TO_CREATE_TIMER, 535
EE_FAILED_TO_CREATE_TIMER_NOTIFY_THREAD_INTERRUPT, 535
EE_FAILED_TO_CREATE_TIMER_QUEUE, 535
EE_FAILED_TO_DELETE_TIMER, 535

EE_FAILED_TO_DETERMINE_LARGE_PAGE_SIZE, 536
EE_FAILED_TO_HANDLE_DEFAULTS_FILE, 536
EE_FAILED_TO_KILL_ALL_THREADS, 536
EE_FAILED_TO_LOCATE_SERVER_PUBLIC_KEY, 538
EE_FAILED_TO_OPEN_DEFAULTS_FILE, 536
EE_FAILED_TO_RESET_BEFORE_PRIMARY_IGNORED_CHAR, 540
EE_FAILED_TO_RESET_BEFORE_SECONDARY_IGNORED_CHAR, 540
EE_FAILED_TO_RESET_BEFORE_TERTIARY_IGNORED_CHAR, 540
EE_FAILED_TO_SET_OPTION_VALUE, 539
EE_FAILED_TO_START_TIMER_NOTIFY_THREAD, 535
EE_FILENOFOUND, 535
EE_FILE_NOT_CLOSED, 535
EE_GETWD, 534
EE_IGNORE_WORLD_WRITABLE_CONFIG_FILE, 537
EE_INCORRECT_BOOLEAN_VALUE_FOR_OPTION, 539
EE_INCORRECT_GRP_DEFINITION_IN_CONFIG_FILE, 536
EE_INCORRECT_INT_VALUE_FOR_OPTION, 539
EE_INCORRECT_UINT_VALUE_FOR_OPTION, 539
EE_INVALID_DECIMAL_VALUE_FOR_OPTION, 539
EE_LINK, 533
EE_LINK_WARNING, 534
EE_NET_SEND_ERROR_IN_BOOTSTRAP, 537
EE_OPEN_WARNING, 534
EE_OPTION_IGNORED_DUE_TO_INVALID_VALUE, 538
EE_OPTION_REQUIRES_ARGUMENT, 538
EE_OPTION_WITHOUT_ARGUMENT, 538
EE_OPTION_WITHOUT_GRP_IN_CONFIG_FILE, 537
EE_OPTION_WITH_EMPTY_VALUE, 539
EE_OUTOFMEMORY, 533
EE_OUT_OF_FILERESOURCES, 534
EE_PACKETS_OUT_OF_ORDER, 537
EE_PUBLIC_KEY_NOT_IN_PEM_FORMAT, 538
EE_READ, 533
EE_REALPATH, 534
EE_RESET_CHAR_OUT_OF_RANGE, 540
EE_SETWD, 534
EE_SHIFT_CHAR_OUT_OF_RANGE, 540
EE_SHORT_OPTION_REQUIRES_ARGUMENT, 538
EE_SKIPPING_DIRECTIVE_DUE_TO_MAX_INCLUDE_RECUSION, 536
EE_SSL_ERROR, 537
EE_SSL_ERROR_FROM_FILE, 537
EE_STAT, 534
EE_SYNC, 534
EE_UNKNOWN_CHARSET, 534
EE_UNKNOWN_COLLATION, 534
EE_UNKNOWN_LDML_TAG, 540
EE_UNKNOWN_OPTION, 538
EE_UNKNOWN_PROTOCOL_OPTION, 538
EE_UNKNOWN_SHORT_OPTION, 538
EE_UNKNOWN_SUFFIX_FOR_VARIABLE, 537
EE_UNKNOWN_VARIABLE, 538
EE_USING_DISABLED_OPTION, 537
EE_USING_DISABLED_SHORT_OPTION, 537
EE_USING_PASSWORD_ON_CLI_IS_INSECURE, 537
EE_WRITE, 533
EE_WRONG_DIRECTIVE_IN_CONFIG_FILE, 536
ER_ABORTING, 143
ER_ABORTING_CONNECTION, 13
ER_ABORTING_USER_CONNECTION, 231
ER_ACCESS_DENIED_CHANGE_USER_ERROR, 58
ER_ACCESS_DENIED_ERROR, 6
ER_ACCESS_DENIED_ERROR_WITHOUT_PASSWORD, 232
ER_ACCESS_DENIED_ERROR_WITH_PASSWORD, 232
ER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY, 498
ER_ACCESS_DENIED_FOR_USER_ACCOUNT_LOCKED, 232
ER_ACCESS_DENIED_NO_PASSWORD_ERROR, 45
ER_ACCOUNT_HAS_BEEN_LOCKED, 68
ER_ACL_OPERATION_FAILED, 74
ER_ACL_WRONG_OR_MISSING_ACL_TABLES_LOG, 489
ER_ADD_ADDRESSES_FOR_HOSTNAME_HEADER, 137
ER_ADDRESSES_FOR_HOSTNAME_LIST_ITEM, 137
ER_ADD_PARTITION_NO_NEW_PARTITION, 34
ER_ADD_PARTITION_SUBPART_ERROR, 34
ER_ADMIN_WRONG_MRGR_TABLE, 32
ER_AES_INVALID_IV, 58
ER_AGGREGATE_IN_ORDER_NOT_SELECT, 64
ER_AGGREGATE_ORDER_FOR_UNION, 61
ER_AGGREGATE_ORDER_NON_QUEST, 61
ER_ALTER_CONSTRAINT_ENFORCEMENT_NOT_SUPPORTED, 119
ER_ALTER_FILEGROUP_FAILED, 36
ER_ALTER_INFO, 9
ER_ALTER_OPERATION_NOT_SUPPORTED, 56
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON, 56
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_AUTO, 56

ER.Alter.Operation.NotSupportedReason.CannotChangeEncryptionPassword 460
56
ER.Alter.Operation.NotSupportedReason.CannotChangeAuditLogFile 460
56
ER.Alter.Operation.NotSupportedReason.CannotPruneAuditLogFileAutoPruned 518
56
ER.Alter.Operation.NotSupportedReason.CannotAuditLogFileHasBeenSuccessfullyProcessed 518
56
ER.Alter.Operation.NotSupportedReason.Check 488
56
ER.Alter.Operation.NotSupportedReason.Rename 488
56
ER.Alter.Operation.NotSupportedReason.Timestamp 488
56
ER.Alter.Operation.NotSupportedReason.Keyring 488
63
ER.Alter.Operation.NotSupportedReason.PruneFailed 518
56
ER.Alter.Operation.NotSupportedReason.CloseTableAfterFilteringFailed 265
56
ER.Alter.Operation.NotSupportedReason.DeleteFromTableAfterFilteringFailed 265
56
ER.Alter.Operation.NotSupportedReason.InitTableForAuditLogFilterFailed 265
57
ER.Alter.Operation.NotSupportedReason.InsertIntoTableAuditLogFilterFailed 265
56
ER.AmbiguousFieldTerm 32
ER.AnonymousAuthIdNotAllowedInMandatoryRoles 205
237
ER.AnonymousToGtidUuidSameAsGroup 261
128
ER.AnonymousToGtidUuidSameAsView 264
131
ER.ApplierLogEventValidation 265
86
ER.AssignGtidsToAnonymousTransactions 264
127
ER.AttributeIgnored 89
ER.AuditApiAbort 71
ER.AuditCantAbortCommand 229
ER.AuditCantAbortEvent 229
ER.AuditLogCannotGeneratePassword 495
ER.AuditLogCannotReadPassword 489
ER.AuditLogCannotRemovePassword 489
ER.AuditLogCannotSetLogPolicyWith 262
ER.AuditLogCannotStorePassword 489
ER.AuditLogCouldNotCreateAesKey 460
ER.AuditLogCouldNotOpenFileForReading 488
ER.AuditLogEcWriterFailedToCreateFile 263
ER.AuditLogEcWriterFailedToInitCompression 459
ER.AuditLogEcWriterFailedToInitEncryption 263
ER.AuditLogEcWriterFailedToInitLogJsonReaderBufTooSmall 264

ER_AUDIT_LOG_JSON_READER_FAILED_TO_OPEN_FILE, AUTHCACHE_DB_IGNORED_EMPTY_NAME,
264 164
ER_AUDIT_LOG_JSON_READER_FAILED_TO_PARSE, ER_AUTHCACHE_DB_SKIPPED_NEEDS_RESOLVE,
264 164
ER_AUDIT_LOG_JSON_READER_FILE_PARSING_ERROR, AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAME
264 507
ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY, AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHORIZA
460 507
ER_AUDIT_LOG_KEYRING_ID_TIMESTAMP_VALUE_IS_EXPIRED, CACHE_EXPIRED_PASSWORD_UNSUPPORTED,
488 164
ER_AUDIT_LOG_NO_KEYRING_PLUGIN_INSTALLED, ER_AUTHCACHE_PLUGIN_CONFIG, 163
460 ER_AUTHCACHE_PLUGIN_MISSING, 163
ER_AUDIT_LOG_ONLY_INCLUDE_LIST_USED, ER_AUTHCACHE_PROCS_PRIV_ENTRY_IGNORED_BAD_RO
262 165
ER_AUDIT_LOG_PASSWORD_HAS_BEEN_COPIED, ER_AUTHCACHE_PROCS_PRIV_SKIPPED_NEEDS_RESOLV
489 165
ER_AUDIT_LOG_RENAME_LOG_FILE_BEFORE_FLUSHER, AUTHCACHE_PROXYES_PRIV_SKIPPED_NEEDS_RESOL
263 163
ER_AUDIT_LOG_SUPER_PRIVILEGE_REQUIRED, ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME,
492 507
ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST, ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATIO
262 507
ER_AUDIT_LOG_TABLE_DEFINITION_NOT_UPDATED, ER_AUTHCACHE_ROLE_TABLES_DODGY, 163
461 ER_AUTHCACHE_TABLES_PRIV_SKIPPED_NEEDS_RESOLVE, 163
ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE, 165
460 ER_AUTHCACHE_TABLE_PROXYES_PRIV_MISSING, 165
ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_COUNT, 164
493 ER_AUTHCACHE_USER_IGNORED_DEPRECATED_PASSWORD, 164
ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_TYPE, 163
492 ER_AUTHCACHE_USER_IGNORED_INVALID_PASSWORD, 163
ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH_ARG_TYPE, 163
493 ER_AUTHCACHE_USER_IGNORED_NEEDS_PLUGIN, 163
ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH_ARG_VALUE, 163
74 ER_AUTHCACHE_USER_SKIPPED_NEEDS_RESOLVE, 163
ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALPHANUMERIC,
460 ER_AUTHCACHE_USER_TABLE_DODGY, 163
ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER, ER_AUTH_CANT_ACTIVATE_ROLE, 161
459 ER_AUTH_CANT_CREATE_RSA_PAIR, 162
ER_AUDIT_LOG_WRITER_DEST_FILE_ALREADY_EXISTS, ER_AUTH_CANT_SET_DEFAULT_PLUGIN, 149
263 ER_AUTH_CANT_WRITE_PRIVKEY, 162
ER_AUDIT_LOG_WRITER_FAILED_TO_WRITE_TO_FILER, ER_AUTH_CANT_WRITE_PUBKEY, 162
263 ER_AUTH_CERTS_SAVED_TO_DATADIR, 162
ER_AUDIT_LOG_WRITER_INCOMPLETE_FILE_RENAME, ER_AUTH_CERT_GENERATION_DISABLED, 162
263 ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY, 162
ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED, 481
263 ER_AUTH_KERBEROS_LOGGER_GENERIC_MSG, 162
ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED_REMOVE_FILE_MANUALLY,
263 ER_AUTH_KEYS_SAVED_TO_DATADIR, 162
ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT_AUTH_AVAILKEY_GENERATION_DISABLED, 163
167 ER_AUTH_KEY_GENERATION_SKIPPED_PAIR_PRESENT, 163
ER_AUDIT_PLUGIN_HAS_INVALID_DATA, 168 162
ER_AUDIT_WARNING, 229 ER_AUTH_LDAP_ERROR_LOGGER_ERROR_MSG, 162
ER_AUTHCACHE_CANT_INIT_GRANT_SUBSYSTEM, 268
165 ER_AUTH_RSA_CANT_FIND, 160
ER_AUTHCACHE_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLE, RSA_CANT_PARSE, 160
164 ER_AUTH_RSA_CANT_READ, 160
ER_AUTHCACHE_DB_ENTRY_LOWERCASED_REVOKER, RSA_CONF_PREVENTS_KEY_GENERATION,
164 162

ER_AUTH_RSA_FILES_NOT_FOUND, 160
ER_AUTH_SSL_CONF_PREVENTS_CERT_GENERATION, 162
ER_AUTH_USING_EXISTING_CERTS, 162
ER_AUTOINC_READ_FAILED, 32
ER_AUTO_CONVERT, 19
ER_AUTO_INCREMENT_CONFLICT, 57
ER_AUTO_OPTIONS_FAILED, 150
ER_AUTO_POSITION_REQUIRES_GTID_MODE_NOT_SUPPORTED, 51
ER_BACK_IN_TIME, 143
ER_BAD_DB_ERROR, 6
ER_BAD_FIELD_ERROR, 7
ER_BAD_FT_COLUMN, 21
ER_BAD_HOST_ERROR, 5
ER_BAD_LOG_STATEMENT, 38
ER_BAD_NULL_ERROR, 6
ER_BAD_NULL_ERROR_NOT_IGNORED, 90
ER_BAD_SLAVE, 16
ER_BAD_SLAVE_AUTO_POSITION, 50
ER_BAD_SLAVE_UNTIL_COND, 20
ER_BAD_TABLE_ERROR, 6
ER_BASE64_DECODE_ERROR, 38
ER_BASEDIR_SET_TO, 235
ER_BEFORE_DML_VALIDATION_ERROR, 66
ER_BEG_INITFILE, 145
ER_BINLOG_ATTACHING_THREAD_MEMORY_FINALLY_FAILED, 219
ER_BINLOG_CACHE_SIZE_GREATER_THAN_MAX, 48
ER_BINLOG_CACHE_SIZE_TOO_LARGE, 230
ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX, 222
ER_BINLOG_CANT_CLEAR_IN_USE_FLAG_FOR_CRASHED_BINLOG, 225
ER_BINLOG_CANT_CLOSE_TMP_INDEX, 223
ER_BINLOG_CANT_COPY_INDEX_TO_TMP, 223
ER_BINLOG_CANT_CREATE_CACHE_FOR_LOG, 220
ER_BINLOG_CANT_DELETE_FILE, 222
ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG, 224
ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX_EXISTS, 224
ER_BINLOG_CANT_FIND_LOG_IN_INDEX, 224
ER_BINLOG_CANT_GENERATE_NEW_FILE_NAME, 221
ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAYLOG_FILES, 222
ER_BINLOG_CANT_MOVE_TMP_TO_INDEX, 223
ER_BINLOG_CANT_OPEN_CRASHED_BINLOG, 225
ER_BINLOG_CANT_OPEN_FOR_LOGGING, 220
ER_BINLOG_CANT_OPEN_LOG, 220
ER_BINLOG_CANT_OPEN_TMP_INDEX, 222
ER_BINLOG_CANT_RESIZE_CACHE, 219
ER_BINLOG_CANT_SET_TMP_INDEX_NAME, 222
ER_BINLOG_CANT_TRIM_CRASHED_BINLOG, 225
ER_BINLOG_CANNOT_USE_FOR_LOGGING, 221
ER_BINLOG_CRASHED_BINLOG_TRIMMED, 225
ER_BINLOG_CRASH_RECOVERY_FAILED, 226
ER_BINLOG_CREATE_ROUTINE_NEED_SUPER, 29
ER_BINLOG_END, 143
ER_BINLOG_ERROR_GETTING_NEXT_LOG_FROM_INDEX, 222
ER_BINLOG_ERROR_READING_GTIDS_FROM_BINARY_LOG, 221
ER_BINLOG_ERROR_READING_GTIDS_FROM_RELAY_LOG, 220
ER_BINLOG_EVENTS_READ_FROM_BINLOG_INFO, 221
ER_BINLOG_EVENTS_READ_FROM_RELAY_LOG_INFO, 221
ER_BINLOG_EVENT_WRITE_TO_STMT_CACHE_FAILED, 236
ER_BINLOG_EXPIRAY_LOG_DAYS_AND_SECS_USED_TO_CLOSE, 249
ER_BINLOG_EXPIRE_LOG_DAYS_AND_SECS_USED_TO_CLOSE, 91
ER_BINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE_FLUSHING, 221
ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_FLUSHING, 221
ER_BINLOG_FAILED_TO_DELETE_LOG_FILE, 224
ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_RESETTING, 222
ER_BINLOG_FAILED_TO_OPEN_REGISTER_FILE, 221
ER_BINLOG_FAILED_TO_OPEN_TEMPORARY_INDEX_FILE, 222
ER_BINLOG_FAILED_TO_READ_REGISTER_FILE, 224
ER_BINLOG_FAILED_TO_REINIT_REGISTER_FILE, 224
ER_BINLOG_FAILED_TO_RUN_AFTER_FLUSH_HOOK, 225
ER_BINLOG_FAILED_TO_RUN_AFTER_SYNC_HOOK, 225
ER_BINLOG_FAILED_TO_SET_PURGE_INDEX_FILE_NAME, 224
ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE, 220
ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE_IN_OPEN, 221
ER_BINLOG_FAILED_TO_WRITE_DROP_FOR_TEMP_TABLE, 210
ER_BINLOG_FATAL_ERROR, 39
ER_BINLOG_FILE_BEING_READ_NOT_PURGED, 219

ER_BINLOG_FILE_EXTENSION_NUMBER_EXHAUSTED	ER_BINLOG_ROW_VALUE_OPTION_IGNORED,
220	454
ER_BINLOG_FILE_EXTENSION_NUMBER_RUNNING_LBN	ER_BINLOG_ROW_VALUE_OPTION_USED_ONLY_FOR_AFT
220	454
ER_BINLOG_FILE_NAME_TOO_LONG	ER_BINLOG_STMT_CACHE_SIZE_GREATER_THAN_MAX,
220	48
ER_BINLOG_FILE_OPEN_FAILED	ER_BINLOG_STMT_CACHE_SIZE_TOO_LARGE,
236	230
ER_BINLOG_IO_ERROR_READING_HEADER,	ER_BINLOG_STMT_MODE_AND_NO_REPL_TABLES,
219	56
ER_BINLOG_LOGGING_IMPOSSIBLE	ER_BINLOG_STMT_MODE_AND_ROW_ENGINE,
39	43
ER_BINLOG_LOGGING INCIDENT_TO_STOP_SLAVES	ER_BINLOG_UNABLE_TO_ROTATE_GTID_TABLE_READONLY
224	ERBINLOGKEYSAFE_AUTOINC_COLUMNS, 43
ERBINLOGKEYNOT_POSSIBLE	ERBINLOGUNSAFE_AUTOINC_NOT_FIRST, 47
ERBINLOGLOGICAL_CORRUPTION	ERBINLOGUNSAFE_CREATE_IGNORE_SELECT,
57	46
ERBINLOGMALFORMED_OR_OLD_RELAY_LOG	ERBINLOGUNSAFE_CREATE_REPLACE_SELECT,
249	47
ERBINLOGMASTER_KEY_RECOVERY_OUT_OF_COMBINATION	ERBINLOGUNSAFE_DEFAULT_EXPRESSION_IN_SUBSTA
105	487
ERBINLOGMASTER_KEY_ROTATION_FAIL_TO_CLEARBINLOGKEYSAFE_AUTOINC_COLUMNS	ERBINLOGUNSAFE_CREATE_SELECT_AUTOINC,
105	47
ERBINLOGMASTER_KEY_ROTATION_FAIL_TO_CLEARBINLOGKEYSAFE_CREATE_IGNORE_SELECT	ERBINLOGUNSAFE_CREATE_SELECT_AUTOINC,
105	46
ERBINLOGMASTER_KEY_ROTATION_FAIL_TO_OPERATBINLOGUNSAFE_CREATE_REPLACE_SELECT	ERBINLOGUNSAFE_CREATE_SELECT_AUTOINC,
105	47
ERBINLOGMASTER_KEY_ROTATION_FAIL_TO_RESETBINLOGUNSAFE_CREATE_SELECT_AUTOINC	ERBINLOGUNSAFE_CREATE_SELECT_AUTOINC,
105	47
ERBINLOGMASTER_KEY_ROTATION_FAIL_TO_ROTATEBINLOGUNSAFE_DEFAULT_EXPRESSION_IN_SUBSTA	ERBINLOGUNSAFE_INSERT_IGNORE_SELECT,
105	487
ERBINLOGMULTIPLE_ENGINES_AND_SELF_LOGGING	ERBINLOGUNSAFE_FULLTEXT_PLUGIN, 59
43	ERBINLOGUNSAFE_INSERT_IGNORE_SELECT,
ERBINLOGNEEDS_SERVERID	46
148	46
ERBINLOGOOM_WRITING_DELETE WHILE_OPENINERBINLOGUNSAFE_INSERT_SELECT_UPDATE	ERBINLOGUNSAFE_INSERT_SELECT_UPDATE,
210	46
ERBINLOGPURGE_EMFILE	ERBINLOGUNSAFE_INSERT_TWO_KEYS, 47
38	ERBINLOGUNSAFE_LIMIT, 43
ERBINLOGPURGE_FATAL_ERR	ERBINLOGUNSAFE_MESSAGE_AND_STATEMENT,
26	230
ERBINLOGPURGE_LOGS_CALLED_WITH_FILE_NOTE	ERBINLOGUNSAFE_NONTRANS_AFTER_TRANS,
223	43
ERBINLOGPURGE_LOGS_CANT_COPY_TO_REGISTERBINLOGUNSAFE_MIXED_STATEMENT	ERBINLOGUNSAFE_NOWAIT, 80
223	45
ERBINLOGPURGE_LOGS_CANT_FLUSH_REGISTERFILE	ERBINLOGUNSAFE_MULTIPLE_ENGINES_AND_SELF_LOG
223	45
ERBINLOGPURGE_LOGS_CANT_SYNC_INDEX_FILE	ERBINLOGUNSAFE_ROUTINE, 29
223	43
ERBINLOGPURGE_LOGS_CANT_UPDATE_INDEX_FIE	ERBINLOGUNSAFE_SKIP_LOCKED, 79
223	ERBINLOGUNSAFE_STATEMENT, 39
ERBINLOGPURGE_PROHIBITED	ERBINLOGUNSAFE_SYSTEM_FUNCTION, 43
26	ERBINLOGUNSAFE_SYSTEM_TABLE, 43
ERBINLOGRECOVERING_AFTER_CRASH_USING	ERBINLOGUNSAFE_SYSTEM_VARIABLE, 43
225	ERBINLOGUNSAFE_UDF, 43
ERBINLOGROW_ENGINE_AND_STMT_ENGINE	ERBINLOGUNSAFE_UPDATE_IGNORE, 47
42	ERBINLOGUNSAFE_WRITE_AUTOINC_SELECT,
43	47
ERBINLOGROW_INJECTION_AND_STMT_ENGINE	ERBINLOGUNSAFE_XA, 74
43	ERBINLOGUSE_V1_ROW_EVENTS_IGNORED,
43	454
ERBINLOGROW_LOGGING_FAILED	ERBINLOGWARNING_SUPPRESSED, 226
36	ER_BLOBS_AND_NO_TERMINATED, 8
ERBINLOGROW_MODE_AND_STMT_ENGINE	
42	

ER_BLOB_CANT_HAVE_DEFAULT, 10	ER_CANNOT_USER_REFERENCED_AS_DEFINER, 126
ER_BLOB_FIELD_IN_PART_FUNC_ERROR, 34	ER_CANNOT_USE_AUTOEXTEND_SIZE_CLAUSE, 129
ER_BLOB_KEY_WITHOUT_LENGTH, 14	ER_CANNOT_USE_ENCRYPTION_CLAUSE, 108
ER_BLOB_USED_AS_KEY, 8	ER_CANT_ACCESS_CAPATH, 150
ER_BOOST_GEOMETRY_CENTROID_EXCEPTION, 62	ER_CANT_ACCESS_2COLLATIONS, 20
ER_BOOST_GEOMETRY_EMPTY_INPUT_EXCEPTION, 62	ER_CANT_ACCESS_3COLLATIONS, 20
ER_BOOST_GEOMETRY_INCONSISTENT_TURNS_EXCEPTION, 68	ER_CANT_CHANGE_TX_CHARACTERISTICS, 37
ER_BOOST_GEOMETRY_OVERLAY_INVALID_INPUT_EXCEPTION, 62	ER_CANT_CHECK_PID_PATH, 331
ER_BOOST_GEOMETRY_SELF_INTERSECTION_POINT_EXCEPTION, 62	ER_CANT_COMBINE_ANONYMOUS_TO_GTID_AND_AUTO_COMMIT, 149
ER_BOOST_GEOMETRY_TURN_INFO_EXCEPTION, 62	ER_CANT_CREATE_ADMIN_THREAD, 474
ER_BOOST_GEOMETRY_UNKNOWN_EXCEPTION, 62	ER_CANT_CREATE_CACHE_FOR_DB_OPT, 215
ER_BOOTSTRAP_CANT_THREAD, 132	ER_CANT_CREATE_DB, 3
ER_BUFPOLL_RESIZE_INPROGRESS, 71	ER_CANT_CREATE_FILE, 3
ER_CACHING_SHA2_PASSWORD_SECOND_PASSWORD, 475	ER_CANT_CREATE_GEOMETRY_OBJECT, 28
ER_CALL_ME_LOCALHOST, 144	ER_CANT_CREATE_HANDLER_FILE, 34
ER_CANNOT_ADD_FOREIGN, 17	ER_CANT_CREATE_HANDLER_OBJECT_FOR_TABLE, 214
ER_CANNOT_ADD_FOREIGN_BASE_COL_STORED, 73	ER_CANT_CREATE_HANDLE_MGR_THREAD, 135
ER_CANNOT_ADD_FOREIGN_BASE_COL_VIRTUAL, 72	ER_CANT_CREATE_INTERRUPT_THREAD, 142
ER_CANNOT_ALTER_SRID_DUE_TO_INDEX, 87	ER_CANT_CREATE_NAMED_PIPES_THREAD, 142
ER_CANNOT_CHANGE_TO_ROOT_DIR, 234	ER_CANT_CREATE_PID_FILE, 141
ER_CANNOT_CONVERT_STRING, 110	ER_CANT_CREATE_SCHEDULER_THREAD, 136
ER_CANNOT_CREATE_VIRTUAL_INDEX_CONSTRAINT, 72	ER_CANT_CREATE_SHM_THREAD, 142
ER_CANNOT_DISCARD_TEMPORARY_TABLE, 60	ER_CANT_CREATE_SHUTDOWN_THREAD, 141
ER_CANNOT_DROP_COLUMN_FUNCTIONAL_INDEX, 99	ER_CANT_CREATE_TABLE, 3
ER_CANNOT_FIND_KEY_IN_KEYRING, 73	ER_CANT_CREATE_TABLE_SHARE_FROM_FRM, 213
ER_CANNOT_GET_SERVER_VERSION_FROM_TABLE, 477	ER_CANT_CREATE_TCPIP_THREAD, 142
ER_CANNOT_GRANT_ROLES_TO_ANONYMOUS_USER, 112	ER_CANT_CREATE_TEST_FILE, 140
ER_CANNOT_GRANT_SYSTEM_PRIV_TO_MANDATOR, 114	ER_CANT_CREATE_THREAD, 12
ER_CANNOT_LOAD_FROM_TABLE_V2, 47	ER_CANT_DETACH_SESSION_LEFT_BY_PLUGIN, 181
ER_CANNOT_LOCK_USER_MANAGEMENT_CACHES, 77	ER_CANT_DETACH_USER_WITH_GRANT, 28
ER_CANNOT_LOG_PARTIAL_DROP_DATABASE_WITHOUT_TRANSACTION, 65	ER_CANT_CREATE_UUID, 139
ER_CANNOT_SET_DATABASE_ENCRYPTION, 107	ER_CANT_DETACH_SESSION_LEFT_BY_PLUGIN, 181
ER_CANNOT_SET_LOG_ERROR_SERVICES, 235	ER_CANT_DO_IMPLICIT_COMMIT_IN_TRX_WHEN_GTID_IS_CANCELED, 51
ER_CANNOT_SET_SERVER_VERSION_IN_TABLESPACE, 478	ER_CANT_EXECUTE_IN_READ_ONLY_TRANSACTION, 52
ER_CANNOT_SET_TABLESPACE_ENCRYPTION, 107	ER_CANT_FIND_DL_ENTRY, 11
ER_CANNOT_SET_TABLE_ENCRYPTION, 107	ER_CANT_FIND_SYSTEM_REC, 4
ER_CANNOT_USER, 27	ER_CANT_FIND_UDF, 11
	ER_CANT_GET_STAT, 4
	ER_CANT_HASH_DO_AND_IGNORE_RULES, 149
	ER_CANT_IDENTIFY_CHARSET_USING_DEFAULT, 215

ER_CANT_INCREASE_MAX_OPEN_FILES, 145
ER_CANT_INITIALIZE_BUILTIN_PLUGINS, 148
ER_CANT_INITIALIZE_DYNAMIC_PLUGINS, 148
ER_CANT_INITIALIZE_EARLY_PLUGINS, 148
ER_CANT_INITIALIZE_GTID, 148
ER_CANT_INITIALIZE_UDF, 11
ER_CANT_INIT_DBs, 146
ER_CANT_INIT_SCHEDULER_THREAD, 136
ER_CANT_INIT_TC_LOG, 136
ER_CANT_INIT_TIMER, 150
ER_CANT_JOIN_SHUTDOWN_THREAD, 149
ER_CANT_LOCK, 4
ER_CANT_LOCK_LOG_TABLE, 36
ER_CANT_LOCK_TABLE, 214
ER_CANT_LOCK_TABLESPACE, 214
ER_CANT MODIFY_SRID_0, 95
ER_CANT MODIFY_SRS_USED_BY_COLUMN, 95
ER_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES, 167
ER_CANT_OPEN_CA, 150
ER_CANT_OPEN_DATADIR_AFTER_UPGRADE_FAILURE, 216
ER_CANT_OPEN_DB_OPT_USING_DEFAULT_CHARSET, 215
ER_CANT_OPEN_DIR, 216
ER_CANT_OPEN_ERROR_LOG, 150
ER_CANT_OPEN_FILE, 4
ER_CANT_OPEN_FRM_FILE, 167
ER_CANT_OPEN_LIBRARY, 11
ER_CANT_OPEN_TABLE_MYSQL_PROC, 216
ER_CANT_PARSE_STORED_ROUTINE_BODY, 216
ER_CANT_PROCESS_EXPRESSION_FOR_GENERATE, 496
ER_CANT_READ_DIR, 4
ER_CANT_READ_ERRMSGS, 146
ER_CANT_READ_FRM_FILE, 167
ER_CANT_READ_TABLE_MYSQL_PROC, 216
ER_CANT_REMOVE_ALL_FIELDS, 9
ER_CANT_REMOVE_PID_FILE, 141
ER_CANT_RENAME_LOG_TABLE, 38
ER_CANT_REOPEN_TABLE, 12
ER_CANT_REPLICATE_ANONYMOUS_WITH_AUTO_POSITION, 459
ER_CANT_REPLICATE_ANONYMOUS_WITH_GTID_MODE, 459
ER_CANT_RESET_MASTER, 73
ER_CANT_SAVE_GTIDS, 149
ER_CANT_SET_ANONYMOUS_TO_GTID_AND_WAIT_UNTIL_CASCADE, 128
ER_CANT_SET_DATADIR, 149
ER_CANT_SET_DATA_DIR, 472
ER_CANT_SET_ERROR_LOG_SERVICE, 93
ER_CANT_SET_ERROR_SUPPRESSION_LIST, 97
ER_CANT_SET_ERROR_SUPPRESSION_LIST_FROM_COMM, 464
ER_CANT_SET_GTID_MODE, 67
ER_CANT_SET_GTID_NEXT_LIST_TO_NON_NULL_WHEN_GTID, 51
ER_CANT_SET_GTID_NEXT_TO_ANONYMOUS_WHEN_GTID, 51
ER_CANT_SET_GTID_NEXT_TO_GTID_WHEN_GTID_MODE, 51
ER_CANT_SET_GTID_NEXT_WHEN_OWNING_GTID, 52
ER_CANT_SET_GTID_PURGED_DUE_SETS_CONSTRAINTS, 77
ER_CANT_SET_GTID_PURGED_WHEN_GTID_EXECUTED_IS, 55
ER_CANT_SET_GTID_PURGED_WHEN_OWNED_GTIDS_IS, 55
ER_CANT_SET_HANDLER_REFERENCE_FOR_TABLE, 214
ER_CANT_SET_PATH_FOR, 216
ER_CANT_SET_PERSISTED, 153
ER_CANT_SET_SQL_AFTER_OR_BEFORE_GTIDS_WITH_AN, 128
ER_CANT_SET_UP_PERSISTED_VALUES, 149
ER_CANT_SET_VARIABLE_WHEN_OWNING_GTID, 69
ER_CANT_START_ERROR_LOG_SERVICE, 233
ER_CANT_STAT_DATADIR, 149
ER_CANT_STAT_FILE, 224
ER_CANT_UPDATE_TABLE_IN_CREATE_TABLE_SELECT, 48
ER_CANT_UPDATE_USED_TABLE_IN_SF_OR_TRG, 30
ER_CANT_UPDATE_USED_TABLE_IN_SF_OR_TRG, 17
ER_CANT_UPGRADE_GENERATED_COLUMNS_TO_DD, 214
ER_CANT_USE_ANONYMOUS_TO_GTID_WITH_GTID_MODE, 127
ER_CANT_USE_AUTO_POSITION_WITH_GTID_MODE_OFF, 67
ER_CANT_USE_OPTION_HERE, 18
ER_CANT_USE_SAME_UUID_AS_GROUP_NAME, 128
ER_CANT_USE_SAME_UUID_AS_VIEW_CHANGE_UUID, 130
ER_CANT_WAIT_FOR_EXECUTED_GTID_SET_WHILE_OWNIN, 72
ER_CANT_WAIT_FOR_EXECUTED_GTID_SET_WHILE_OWNIN, 130
ER_CAPACITY_EXCEEDED, 72
ER_CAPACITY_EXCEEDED_IN_PARSER, 73
ER_CAPACITY_EXCEEDED_IN_RANGE_OPTIMIZER, 72
ER_CHANGED_ENFORCE_GTID_CONSISTENCY, 135
ER_CHANGED_GTID_MODE, 135
ER_CHANGED_MAX_CONNECTIONS, 146
ER_CHANGED_MAX_OPEN_FILES, 145
ER_CHANGED_TABLE_OPEN_CACHE, 146

ER_CHANGE_MASTER_PASSWORD_LENGTH,	ER_CLONE_CREATE_HANDLER_FAIL_TRACE,
63	245
ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM,	ER_CLONE_CLIENT_IN_PROGRESS, 86
116	ER_CLONE_DISALLOWED, 112
ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM,	ER_CLONE_ISOLIGENCE, 112
117	ER_CLONE_DONOR, 111
ER_CHANGE_MASTER_WRONG_COMPRESSION_LEVEL,	ER_CLONE_DONOR_TRACE, 471
116	ER_CLONE_DONOR_VERSION, 111
ER_CHANGE_RPL_INFO_REPOSITORY_FAILURE,	ER_CLONE_ENCRYPTION, 112
49	ER_CLONE_HANDLER_EXISTS, 244
ER_CHANGE_RPL_SRC_WRONG_COMPRESSION_ALGORITHM,	ER_CLONE_HANDLER_EXIST_TRACE, 244
130	ER_CLONE_INFO_CLIENT, 471
ER_CHARACTER_SET_MISMATCH, 125	ER_CLONE_INFO_SERVER, 472
ER_CHECKING_TABLE, 213	ER_CLONE_IN_PROGRESS, 112
ER_CHECKREAD, 4	ER_CLONE_LOOPBACK, 112
ER_CHECK_CONSTRAINT_CLAUSE_USING_FK_REFERENCES,	ER_CLONE_NETWORK_PACKET, 120
107	ER_CLONE_OS, 111
ER_CHECK_CONSTRAINT_DUP_NAME, 107	ER_CLONE_PLATFORM, 111
ER_CHECK_CONSTRAINT_FUNCTION_IS_NOT_ALLOWED,	ER_CLONE_PLUGIN_MATCH, 111
106	ER_CLONE_PLUGIN_NOT_LOADED, 244
ER_CHECK_CONSTRAINT_NAMED_FUNCTION_IS_NOT_DEFINED,	ER_CLONE_PLUGIN_NOT_LOADED_TRACE, 244
106	ER_CLONE_PROTOCOL, 111
ER_CHECK_CONSTRAINT_NOT_FOUND, 107	ER_CLONE_PROTOCOL_ERROR, 471
ER_CHECK_CONSTRAINT_REFERES_AUTO_INCREMENT,	ER_CLONE_PROTOCOL_TRACE, 471
106	ER_CLONE_REMOTE_ERROR, 471
ER_CHECK_CONSTRAINT_REFERES_UNKNOWN_COLUMN,	ER_CLONE_SERVER_TRACE, 472
106	ER_CLONE_SHUTDOWN_TRACE, 490
ER_CHECK_CONSTRAINT_ROW_VALUE, 106	ER_CLONE_SYS_CONFIG, 111
ER_CHECK_CONSTRAINT_VARIABLES, 106	ER_CLONE_TOO_MANY_CONCURRENT_CLONES, 86
ER_CHECK_CONSTRAINT_VIOLATED, 106	ER_CMD_NEED_SUPER, 86
ER_CHECK_NOT_IMPLEMENTED, 15	ER_COALESCE_ONLY_ON_HASH_PARTITION, 34
ER_CHECK_NO SUCH_TABLE, 14	ER_COL_CANT_BE_ANONYMOUS,
ER_CLIENT_DOES_NOT_SUPPORT, 87	ER_COMMIT_NOT_ALLOWED_IN_SF_OR_TRG,
ER_CLIENT_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE,	ER_COMPONENTS_CANT_ACQUIRE_SERVICE_IMPLEMENTATION_NO_PARTITION, 35
98	ER_COLLATION_CHARSET_MISMATCH, 19
ER_CLIENT_INTERACTION_TIMEOUT, 130	ER_COLUMNACCESS_DENIED_ERROR, 13
ER_CLIENT_KEYRING_UDF_KEY_INVALID, 117	ER_COLUMN_CHANGE_SIZE, 113
ER_CLIENT_KEYRING_UDF_KEY_TOO_LONG,	ER_COLUMN_CHECK_CONSTRAINT_REFERENCES_OTHER, 106
118	ER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2, 53
ER_CLIENT_KEYRING_UDF_KEY_TYPE_INVALID,	ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V, 37
118	ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V, 37
ER_CLIENT_LOCAL_FILES_DISABLED, 119	ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V, 37
ER_CLIENT_PRIVILEGE_CHECKS_USER_CANNOT_BE,	ER_COMPONENTS_CANT_LOAD, 76
117	ER_COMMIT_NOT_ALLOWED_IN_SF_OR_TRG,
ER_CLIENT_PRIVILEGE_CHECKS_USER_CORRUPT,	ER_COMPONENTS_CANT_RELEASE_SERVICE, 77
117	ER_COMPONENTS_CANT_RELEASE_SERVICE, 77
ER_CLIENT_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST,	ER_COMPONENTS_CANT_SATISFY_DEPENDENCY, 76
117	ER_COMPONENTS_CANT_UNLOAD, 77
ER_CLIENT_PRIVILEGE_CHECKS_USER_NEEDS_RPL,	ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION, 249
117	ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION, 249
ER_CLIENT_QUERY_FAILURE_INVALID_NON_ROW_FORMAT,	ER_COMPONENTS_CANT_SATISFY_DEPENDENCY, 76
119	ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION, 249
ER_CLONE_CHARSET, 111	ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION, 249
ER_CLONE_CLIENT_TRACE, 472	ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION, 249
ER_CLONE_CONFIG, 111	ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION, 249

ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP, ER_CONN_PIP_CANT_CREATE_PIPE, 156
138
ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_DEINIT,
518
ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_INIT, ER_CONN_SHM_LISTENER, 156
518
ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN, ER_CONN_SOCKET_SELECT_FAILED, 160
138
ER_COMPONENTS_LOAD_CANT_INITIALIZE, 77
ER_COMPONENTS_LOAD_CANT_REGISTER_SERVICE, ER_COMPONENT_REGISTRATION_RETRY, 158
77
ER_COMPONENTS_NO_SCHEME, 76
ER_COMPONENTS_NO_SCHEME_SERVICE, 76
ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP, ER_CONN_TCP_CREATED, 157
138
ER_COMPONENTS_UNLOAD_CANT_DEINITIALIZE, 77
ER_COMPONENTS_UNLOAD_CANT_UNREGISTER_SERVICE, ER_CONN_TCP_IP_NOT_LOGGED, 158
77
ER_COMPONENTS_UNLOAD_DUPLICATE_IN_GROUP, 157
77
ER_COMPONENTS_UNLOAD_NOT_LOADED, 77
ER_COMPONENT_FILTER_CONFUSED, 269
ER_COMPONENT_FILTER_DIAGNOSTICS, 93
ER_COMPONENT_FILTER_FLABBERGASTED, 85
ER_COMPONENT_FILTER_WRONG_VALUE, 455
ER_COMPONENT_MANIPULATE_ROW_FAILED, 77
ER_COMPONENT_TABLE_INCORRECT, 77
ER_COND_ITEM_TOO_LONG, 42
ER_CONFIG_OPTION_WITHOUT_GROUP, 153
ER_CONFIRMING_THE_FUTURE, 143
ER_CONFLICTING_DECLARATIONS, 22
ER_CONFLICT_FN_PARSE_ERROR, 40
ER_CONNECTION_ABORTED, 454
ER_CONNECTION_HANDLING_OOM, 140
ER_CONNECT_TO_FOREIGN_DATA_SOURCE, 29
ER_CONNECT_TO_MASTER, 17
ER_CONN_ATTR_TRUNCATED, 160
ER_CONN_CONTROL_DELAY_ACTION_INIT_FAILED, 271
ER_CONN_CONTROL_ERROR_MSG, 268
ER_CONN_CONTROL_EVENT_COORDINATOR_INIT_FAILED, ER_CONN_UNIX_PATH_TOO_LONG, 158
270
ER_CONN_CONTROL_FAILED_TO_SET_CONN_DELAY, 58
271
ER_CONN_CONTROL_INVALID_CONN_DELAY_TYPE, ER_CORE_VALUES, 142
270
ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED, ER_CONN_UPGRADE_DB, 19
270
ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED, ER_CONN_ADDITIVE_CREATE_WINDOWS_REGISTRY_KEY, 467
270
ER_CONN_INIT_CONNECT_IGNORED, 270
ER_CONN_PER_THREAD_NO_THREAD, 157
ER_CONN_PIP_CANT_CREATE_EVENT, 156
ER_CONN_SHM_CANT_CREATE_CONNECTION, 158
ER_CONN_SHM_CANT_CREATE_SERVICE, 156
ER_CONN_SOCKET_ACCEPT_FAILED, 160
ER_CONN_TCP_ADDRESS, 157
ER_CONN_TCP_BIND_FAIL, 158
ER_CONN_TCP_CANT_RESET_V6ONLY, 158
ER_CONN_TCP_CANT_RESOLVE_HOSTNAME, 157
ER_CONN_TCP_ERROR_WITH_STRERROR, 157
ER_CONN_TCP_IPV6_AVAILABLE, 157
ER_CONN_TCP_IPV6_UNAVAILABLE, 157
ER_CONN_TCP_IS THERE_ANOTHER_USING_PORT, 157
ER_CONN_TCP_LISTEN_FAIL, 158
ER_CONN_TCP_NO_SOCKET, 157
ER_CONN_TCP_RESOLVE_INFO, 158
ER_CONN_TCP_START_FAIL, 158
ER_CONN_TPC_BIND_FAIL, 158
ER_CONN_UNIX_IS THERE_ANOTHER_USING_SOCKET, 157
ER_CONN_UNIX_LISTEN_FAILED, 159
ER_CONN_UNIX_LOCK_FILE_CANT_CLOSE, 160
ER_CONN_UNIX_LOCK_FILE_CANT_CREATE, 159
ER_CONN_UNIX_LOCK_FILE_CANT_DELETE, 160
ER_CONN_UNIX_LOCK_FILE_CANT_OPEN, 159
ER_CONN_UNIX_LOCK_FILE_CANT_READ, 159
ER_CONN_UNIX_LOCK_FILE_CANT_SYNC, 160
ER_CONN_UNIX_LOCK_FILE_CANT_WRITE, 159
ER_CONN_UNIX_LOCK_FILE_EMPTY, 159
ER_CONN_UNIX_LOCK_FILE_FAIL, 158
ER_CONN_UNIX_LOCK_FILE_GIVING_UP, 159
ER_CONN_UNIX_LOCK_FILE_PIDLESS, 159
ER_CONN_UNIX_NO_BIND_NO_START, 159
ER_CONN_UNIX_NO_FD, 159
ER_CON_COUNT_ERROR, 5
ER_CONSECUTIVE_REORG_PARTITIONS, 35
ER_CONN_CONTROL_FAILED_TO_UPDATE_CONN_DELAY_CONSTRAINT_NOT_FOUND, 119
271
ER_CONN_CONTROL_INVALID_CONN_DELAY_TYPE, ER_CORE_VALUES, 142
270
ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED, ER_CONN_UPGRADE_DB, 19
270
ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED, ER_CONN_ADDITIVE_CREATE_WINDOWS_REGISTRY_KEY, 467
270
ER_COULD_NOT_APPLY_JSON_DIFF, 88
ER_COULD_NOT_REINITIALIZE_AUDIT_LOG_FILTERS, 460
ER_CRASHED_ON_REPAIR, 15

ER_CRASHED_ON_USAGE, 15
ER_CREATED_SYSTEM_WITH_VERSION, 242
ER_CREATE_FILEGROUP_FAILED, 35
ER_CREATING_NEW_UUID, 139
ER_CREATING_NEW_UUID_FIRST_START, 234
ER_CREDENTIALLESS_AUTO_USER_BAD, 140
ER_CREDENTIALS_CONTRADICT_TO_HISTORY, 87
ER_CTE_MAX_RECUSION_DEPTH, 87
ER_CTE_RECURSIVE_FORBIDDEN_JOIN_ORDER, 80
ER_CTE_RECURSIVE_FORBIDS_AGGREGATION, 80
ER_CTE_RECURSIVEQUIRES_NONRECUSIVEFIRSTDB_DROP_RMDIR2, 84
ER_CTE_RECURSIVE_SINGLE_REFERENCE~~E5~~
ER_CTE_RECURSIVE_UNION, 80
ER_CURRENT_PASSWORD_CANNOT_BE_RETAINED, 114
ER_CURRENT_PASSWORD_NOT_REQUIRED, 114
ER_CUT_VALUE_GROUP_CONCAT, 19
ER_CYCLE_TIMER_IS_NOT_AVAILABLE, 245
ER_DATABASE_NAME, 40
ER_DATA_DIRECTORY_UNUSABLE, 467
ER_DATA_DIRECTORY_UNUSABLE_DELETEABLE, 490
ER_DATA_OUT_OF_RANGE, 45
ER_DATA_TOO_LONG, 28
ER_DATETIME_FUNCTION_OVERFLOW, 30
ER_DA_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MA~~NDBDIRYRROEKS~~TS_FOR_TABLE, 166
ER_DA_CANT_OPEN_ERROR_LOG, 126
ER_DA_ERROR_LOG_COMPONENT_FLUSH_FAILED, 131
ER_DA_ERROR_LOG_MULTIPLE_FILTERS, 126
ER_DA_ERROR_LOG_TABLE_DISABLED, 126
ER_DA_GRP_RPL_RECOVERY_ENDPOINT_FORMAT, 122
ER_DA_GRP_RPL_RECOVERY_ENDPOINT_INVALID, 123
ER_DA_GRP_RPL_STARTED_AUTO_REJOIN, 116
ER_DA_INVALID_CONDITION_NUMBER, 49
ER_DA_NO_ERROR_LOG_PARSER_CONFIGURED, 126
ER_DA_OOM, 120
ER_DA_PLUGIN_INSTALL_ERROR, 113
ER_DA_RPL_GTID_TABLE_CANNOT_OPEN, 113
ER_DA_SSL_LIBRARY_ERROR, 113
ER_DA_UDF_INVALID_ARGUMENT_TO_SET_CHARSET~~E5~~
ER_DA_UDF_INVALID_CHARSET, 118
ER_DA_UDF_INVALID_CHARSET_SPECIFIED, 118
ER_DA_UDF_INVALID_COLLATION, 118
ER_DA_UDF_INVALID_EXTENSION_ARGUMENT_TYPE, 118
ER_DA_UDF_INVALID_RETURN_TYPE_TO_SET_CHARSET~~E5~~
ER_DA_UNKNOWN_ERROR_NUMBER, 113
ER_DBACCESS_DENIED_ERROR, 6
ER_DBBUG_CHECK_SHARES_DROPPED, 186
ER_DBBUG_CHECK_SHARES_INFO, 186
ER_DBBUG_CHECK_SHARES_OPEN, 186
ER_DB_ACCESS_DENIED, 112
ER_DB_CREATE_EXISTS, 4
ER_DB_DROP_EXISTS, 4
ER_DB_DROP_RMDIR, 4
ER_DB_OPT_NOT_FOUND_USING_DEFAULT_CHARSET,
ER_DDL_IN_PROGRESS, 86
ER_DDL_LOG_ERROR, 37
ER_DDL_MSG_1, 525
ER_DD_ABORTING_PARTIAL_UPGRADE, 165
ER_DD_CACHE_NOT_EMPTY_AT_SHUTDOWN, 134
ER_DD_CANT_CREATE_OBJECT_KEY, 134
ER_DD_CANT_CREATE_SP, 214
ER_DD_CANT_FETCH_TABLE_DATA, 214
ER_DD_CANT_FIX_SE_DATA, 214
ER_DD_CANT_GET_OBJECT_KEY, 134
ER_DD_CANT_RESOLVE_VIEW, 152
ER_DD_CREATED_FOR_UPGRADE, 166
ER_DD_ERROR_CREATING_ENTRY, 214
ER_DD_FAILSAFE, 132
ER_DD_INITIALIZE, 250
ER_DD_INITIALIZE_SQL_ERROR, 461
ER_DD_INIT_FAILED, 133
ER_DD_INIT_UPGRADE_FAILED, 133
ER_DD_METADATA_NOT_FOUND, 134
ER_DD_MINOR_DOWNGRADE, 251
ER_DD_MINOR_DOWNGRADE_VERSION_NOT_SUPPORT~~E5~~
ER_DD_NO_VERSION_FOUND, 251
ER_DD_NO_WRITES_NO_REPOPULATION, 132
ER_DD_OBJECT_RELEASEER_REMAINS, 134
ER_DD_OBJECT_REMAINS, 134
ER_DD_OBJECT_REMAINS_IN_RELEASEER, 134
ER_DD_POPULATING_TABLES_FAILED, 134
ER_DD_RESTART, 250
ER_DD_SCHEMA_NOT_FOUND, 165
ER_DD_SE_INIT_FAILED, 165
ER_DD_TABLESPACE_NOT_FOUND, 151
ER_DD_TABLE_NOT_FOUND, 165
ER_DD_TRG_CANT_ADD, 151
ER_DD_TRG_CONNECTION_COLLATION_MISSING, 151
ER_DD_TRG_DB_COLLATION_MISSING, 151
ER_DD_TRG_DEFINER_OOM, 151
ER_DD_TRG_FILE_UNREADABLE, 151
ER_DD_UPDATING_PLUGIN_MD_FAILED, 134

ER_DD_UPGRADE, 250
ER_DD_UPGRADE_COMPLETED, 486
ER_DD_UPGRADE_DD_OPEN_FAILED, 240
ER_DD_UPGRADE_DD_POPULATED, 241
ER_DD_UPGRADE_FAILED_FIND_VALID_DATA_DIR, 242
ER_DD_UPGRADE_FAILED_INIT_DD_SE, 242
ER_DD_UPGRADE_FAILED_TO_ACQUIRE_TABLESPACE, 240
ER_DD_UPGRADE_FAILED_TO_CREATE_INDEX_STAT, 241
ER_DD_UPGRADE_FAILED_TO_CREATE_TABLE_STAT, 241
ER_DD_UPGRADE_FAILED_TO_FETCH_TABLES, 241
ER_DD_UPGRADE_FAILED_TO_FETCH_TABLESPACES, 240
ER_DD_UPGRADE_FAILED_TO_RESOLVE_TABLESPACE, 240
ER_DD_UPGRADE_FAILED_TO_UPDATE_VER_NO_INDEPENDENT_BY_CHECK_CONSTRAINT, 250
ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_ABORT, 242
ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DEPENDENT_BY_GENERATED_COLUMN, 242
ER_DD_UPGRADE_FOUND_PREPARED_XA_TRANSACTION, 498
ER_DD_UPGRADE_INDEX_STATS_MIGRATE_COMPLETE, 241
ER_DD_UPGRADE_INFO_FILE_CLOSE_FAILED, 241
ER_DD_UPGRADE_INFO_FILE_OPEN_FAILED, 241
ER_DD_UPGRADE_OFF, 251
ER_DD_UPGRADE_RENAME_IDX_STATS_FILE_FAILED, 240
ER_DD_UPGRADE_SCHEMA_UNAVAILABLE, 251
ER_DD_UPGRADE_SDI_INFO_UPDATE_FAILED, 242
ER_DD_UPGRADE_SE_LOGS_FAILED, 242
ER_DD_UPGRADE_START, 242
ER_DD_UPGRADE_TABLESPACE_MIGRATION_FAILED, 241
ER_DD_UPGRADE_TABLE_INTACT_ERROR, 247
ER_DD_UPGRADE_TABLE_STATS_MIGRATE_COMPLETE, 241
ER_DD_UPGRADE_VERSION_NOT_SUPPORTED, 251
ER_DD_UPGRADE_VIEW_COLUMN_NAME_TOO_LONG, 250
ER_DD_VERSION_FOUND, 132
ER_DD_VERSION_INSTALLED, 132
ER_DD_VERSION_UNSUPPORTED, 132
ER_DD_VIEW_CANT_ALLOC_CHARSET, 133
ER_DD_VIEW_CANT_CREATE, 134
ER_DD_VIEW_WITHOUT_DEFINER, 152
ER_DEBUG_SYNC_EXECUTED, 135
ER_DEBUG_SYNC_HIT, 135
ER_DEBUG_SYNC_HIT_LIMIT, 41
ER_DEBUG_SYNC_OOM, 136
ER_DEBUG_SYNC_THREAD_MAX, 135
ER_DEBUG_SYNC_TIMEOUT, 41
ER_DEFAULT_AS_VAL_GENERATED, 101
ER_DEFAULT_SE_UNAVAILABLE, 150
ER_DEFAULT_VAL_GENERATED_FUNCTION_IS_NOT_ALLO, 101
ER_DEFAULT_VAL_GENERATED_NAMED_FUNCTION_IS_NC, 101
ER_DEFAULT_VAL_GENERATED_NON_PRIOR, 100
ER_DEFAULT_VAL_GENERATED_REF_AUTO_INC, 100
ER_DEFAULT_VAL_GENERATED_ROW_VALUE, 100
ER_DEFAULT_VAL_GENERATED_VARIABLES, 100
ER_DEPENDENT_BY_ENGINE, 138
ER_DEPENDENT_BY_DEFAULT_GENERATED_VALUE, 121
ER_DEPENDENT_BY_FUNCTIONAL_INDEX, 108
ER_DEPENDENT_BY_GENERATED_COLUMN, 67
ER_DEPENDENT_BY_PARTITION_FUNC, 110
ER_DEPRECATED_NATIONAL, 95
ER_DEPRECATED_PERSISTED_VARIABLE_WITH_ALIAS, 525D
ER_DEPRECATED_SYNTAX_NO_REPLACEMENT, 248
ER_DEPRECATED_SYNTAX_WITH_REPLACEMENT, 248
ER_DEPRECATED_TIMESTAMP_IMPLICIT_DEFAULTS, 140
ER_DEPRECATED_TLS_VERSION_SESSION, 522
ER_DEPRECATED_UTF8_ALIAS, 95
ER_DEPRECATED_MSG_NO_REPLACE, 248
ER_DEPRECATED_MSG_WITH_REPLACE, 232
ER_DERIVED_MUST_HAVE_ALIAS, 19
ER_DES_FILE_WRONG_KEY, 153
ER_DETACHED_SESSIONS_LEFT_BY_PLUGIN, 181
ER_DETACHING_SESSION_LEFT_BY_PLUGIN, 180D
ER_DIMENSION_UNSUPPORTED, 64
ER_DISABLED_STORAGE_ENGINE, 71
ER_DISABLED_STORAGE_ENGINE_AS_DEFAULT, 71
ER_DISABLE_AUTO_POSITIONQUIRES_ASYNC_RECON, 125
ER_DISABLE_GTI_MODE_REQUIREASYNC_RECONNECT, 125
ER_DISALLOWED_OPERATION, 89
ER_DISCARD_FK_CHECKS_RUNNING, 53
ER_DISCONNECTING_REMAINING_CLIENTS, 143
ER_DISK_FULL_NOWAIT, 90

ER_DIVISION_BY_ZERO, 26
ER_DONT_SUPPORT_REPLICA_PRESERVE_COMMIT, 61
ER_DONT_SUPPORT_SLAVE_PRESERVE_COMMIT, 61
ER_DROP_DATABASE_FAILED_RMDIR_MANUALLY, 249
ER_DROP_FILEGROUP_FAILED, 35
ER_DROP_INDEX_FK, 36
ER_DROP_LAST_PARTITION, 34
ER_DROP_PARTITION_NON_EXISTENT, 34
ER_DUPLICATED_VALUE_IN_TYPE, 21
ER_DUPLICATE_OPTION_KEY, 79
ER_DUPLICATE_SYS_VAR, 462
ER_DUPLICATE_TABLE_LOCK, 79
ER_DUP_ARGUMENT, 17
ER_DUP_ENTRY, 7
ER_DUP_ENTRY_AUTOINCREMENT_CASE, 37
ER_DUP_ENTRY_WITH_KEY_NAME, 38
ER_DUP_FD_OPEN_FAILED, 234
ER_DUP_FIELDNAME, 7
ER_DUP_INDEX, 55
ER_DUP_KEY, 4
ER_DUP_KEYNAME, 7
ER_DUP_LIST_ENTRY, 61
ER_DUP_SIGNAL_SET, 41
ER_DUP_UNIQUE, 14
ER_DUP_UNKNOWN_IN_INDEX, 57
ER_EMPTY_PIPELINE_FOR_ERROR_LOG_SERVICE, 93
ER_EMPTY_PRIVILEGE_NAME_IGNORED, 512
ER_EMPTY_QUERY, 7
ER_ENDING_INIT, 461
ER_END_INITFILE, 145
ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONESHOT_ENGINES_BEFORE_EXECUTE, 68
ER_ENGINE_ATTRIBUTE_NOT_SUPPORTED, 123
ER_ENGINE_CANT_DROP_MISSING_TABLE, 83
ER_ENGINE_CANT_DROP_TABLE, 83
ER_ENGINE_COST_FAILED_TO_READ, 177
ER_ENGINE_COST_INVALID_CONST_CONSTANT_FOR_DEVICE, 177
ER_ENGINE_COST_INVALID_DEVICE_TYPE_FOR_SE, 178
ER_ENGINE_COST_INVALID_DEVICE_TYPE_FOR_SE, 177
ER_ENGINE_COST_UNKNOWN_COST_CONSTANT, 177
ER_ENGINE_COST_UNKNOWN_STORAGE_ENGINE, 177
ER_ENGINE_OUT_OF_MEMORY, 60
ER_ERRMSG_CANT_FIND_FILE, 166
ER_ERRMSG_CANT_READ, 166
ER_ERRMSG_LOADING_55_STYLE, 166
ER_ERRMSG_MISSING_IN_FILE, 166
ER_ERRMSG_OOM, 166
ER_ERRMSG_REPLACEMENTS_FAILED, 228
ER_ERRMSG_REPLACEMENT_DODGY, 228
ER_ERROR_DURING_COMMIT, 15
ER_ERROR_DURING_FLUSH_LOG_COMMIT_PHASE, 249
ER_ERROR_DURING_OPTIMIZE_TABLE, 213
ER_ERROR_DURING_ROLLBACK, 15
ER_ERROR_ENABLING_KEYS, 213
ER_ERROR_INFO_FROM_DA, 458
ER_ERROR_IN_TRIGGER_BODY, 46
ER_ERROR_IN_UNKNOWN_TRIGGER_BODY, 46
ER_ERROR_LOG_DESTINATION_NOT_A_FILE, 513
ER_ERROR_ON_MASTER, 59
ER_ERROR_ON MODIFYING_GTIID_EXECUTED_TABLE, 72
ER_ERROR_ON_READ, 4
ER_ERROR_ON_RENAME, 4
ER_ERROR_ON_WRITE, 4
ER_ERROR_WHEN_EXECUTING_COMMAND, 17
ER_EVENT_ALREADY_EXISTS, 36
ER_EVENT_CANNOT_ALTER_IN_THE_PAST, 38
ER_EVENT_CANNOT_CREATE_IN_THE_PAST, 38
ER_EVENT_CANT_FIND_TIMEZONE, 215
ER_EVENT_CANT_GET_CHARSET, 215
ER_EVENT_CANT_GET_COLLATION, 215
ER_EVENT_CANT_GET_LOCK_FOR_DROPPING_EVENT, 219
ER_EVENT_CANT_GET_TIMEZONE_FROM_FIELD, 215
ER_EVENT_CANT_INIT_QUEUE, 136
ER_EVENT_CANT_OPEN_TABLE_MYSQL_EVENT, 216
ER_EVENT_DOES_NOT_EXIST, 36
ER_EVENT_DROPPING, 179
ER_EVENT_ENGINES_BEFORE_EXECUTE_STARTS, 36
ER_EVENT_ERROR_CREATING_QUERY_TO_WRITE_TO, 218
ER_EVENT_ERROR_DURING_COMPILATION, 178
ER_EVENT_EXECUTION_FAILED, 136
ER_EVENT_EXECUTION_FAILED_CANT_AUTHENTICATE, 178
ER_EVENT_EXECUTION_FAILED_USER_LOST_EVEN_PPP, 178
ER_EVENT_EXEC_TIME_IN_THE_PAST, 36
ER_EVENT_INTERVAL_NOT_POSITIVE_OR_TOO_BIG, 36
ER_EVENT_INVALID_CREATION_CTX, 39
ER_EVENT_LAST_EXECUTION, 136
ER_EVENT_MESSAGE_STACK, 136
ER_EVENT_PURGING_QUEUE, 136
ER_EVENT_RECURRENCE_FORBIDDEN, 38
ER_EVENT_SAME_NAME, 36
ER_EVENT_SCHEDULER_ERROR_GETTING_EVENT_OBJECT, 219
ER_EVENT_SCHEDULER_ERROR_LOADING_FROM_DB, 219

ER_EVENT_SCHEDULER_GOT_BAD_DATA_FROM_TABLE_FAILED_TO_GET_ABSOLUTE_PATH, 234
219
ER_EVENT_SET_VAR_ERROR, 37
ER_EVENT_UNABLE_TO_DROP_EVENT, 219
ER_EXCEEDED_MV_KEYS_NUM, 115
ER_EXCEEDED_MV_KEYS_SPACE, 115
ER_EXCEPTIONS_WRITE_ERROR, 40
ER_EXCESS_ARGUMENTS, 146
ER_EXPIRE_LOGS_DAYS_IGNORED, 249
ER_EXPLAIN_NOT_SUPPORTED, 60
ER_FAILED_DEFAULT_ROLES, 76
ER_FAILED_READ_FROM_PAR_FILE, 45
ER_FAILED_REVOKE_ROLE, 76
ER_FAILED_ROLE_GRANT, 76
ER_FAILED_START_MYSQLD_DAEMON, 234
ER_FAILED_TO_ACQUIRE_LOCK_ON_RESOURCE_GROUP_FAILED_TO_REPAIR_TABLE, 210
238
ER_FAILED_TO_ADD_RESOURCE_GROUP_TO_MAP, ER_FAILED_TO_START_SLAVE_THREAD, 243
238
ER_FAILED_TO_ADD_RPL_FILTER, 244
ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP_FAILED_TO_UPDATE_RESOURCE_GROUP, 238
238
ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP_FAILED_TO_WRITE_TO_FILE, 230
238
ER_FAILED_TO_ALLOCATE_SSL_BIO, 462
ER_FAILED_TO_APPLY_RESOURCE_GROUP_CONTROLLER_FAILED_SETREGID, 144
238
ER_FAILED_TO_BINLOG_DROP_EVENT, 243
ER_FAILED_TO_BUILD_DO_AND_IGNORE_TABLE_HAS_FEATURE_DISABLED, 21
244
ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE_ER_FEATURE_NOT_AVAILABLE, 67
171
ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE_ER_FIELD_IN_GROUPING_NOT_GROUP_BY, 83
171
ER_FAILED_TO_CONSTRUCT_DROP_EVENT_QUERY_ER_FIELD_NOT_FOUND_PART_ERROR, 33
243
ER_FAILED_TO_CREATE_CLONE_HANDLER, ER_FIELD_SPECIFIED_TWICE, 10
244
ER_FAILED_TO_CREATE_GTID_TABLE_COMPRESSION_ER_THREADS_GROUP_OPTION_ONLY_ONCE, 35
171
ER_FAILED_TO_CREATE_SDI_FOR_TABLESPACE, ER_FILE_CORRUPT, 59
240
ER_FAILED_TO_DECREMENT_NUMBER_OF_THREADS_ER_FILE_EXISTS_ERROR, 9
181
ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE_ER_FILE_NOT_FOUND, 4
171
ER_FAILED_TO_DESERIALIZE_RESOURCE_GROUP, ER_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS, 495
237
ER_FAILED_TO_DETERMINE_IF_ROLE_IS_MANDATORY_ER_FILE_USED, 5
119
ER_FAILED_TO_FETCH_MANDATORY_ROLE_LIST, ER_FILSORT_ABORT, 5
119
ER_FAILED_TO_FIND_COLLATION_NAME, 233
ER_FAILED_TO_FIND_DL_ENTRY, 230
ER_FAILED_TO_FIND_LOCALE_NAME, 233
ER_FAILED_TO_FIND_MYSQLD_STATUS, 248
ER_FAILED_TO_GENERATE_UNIQUE_LOGFILE, ER_FIREWALL_ACCESS_DENIED, 261
230
ER_FAILED_TO_HANDLE_DEFAULTS_FILE, 462
ER_FAILED_TO_INIT_SYS_VAR, 462
ER_FAILED_TO_INIT_THREAD_ATTR_FOR_GTID_TABLE_CO
171
ER_FAILED_TO_JOIN_GTID_TABLE_COMPRESSION_THREA
171
ER_FAILED_TO_LOCK_MEM, 145
ER_FAILED_TO_OPEN_COST_CONSTANT_TABLES, 177
ER_FAILED_TO_OPEN_SHARED_LIBRARY, 230
ER_FAILED_TO_PERSIST_RESOURCE_GROUP_METADATA, 237
ER_FAILED_TO_READ_FILE, 230
ER_FAILED_TO_REMOVE_TEMP_TABLE, 210
ER_FAILED_TO_SET_PERSISTED_OPTIONS, 248
ER_FAILED_TO_STORE_SDI_FOR_TABLESPACE, 241
ER_FAILED_TO_WRITE_TO_FILE, 230
ER_FAIL_CHROOT, 144
ER_FAIL_SETGID, 144
ER_FAIL_SETREUID, 144
ER_FAIL_SETUID, 144
ER_FEATURE_DISABLED_SEE_DOC, 71
ER_FEATURE_NOT_AVAILABLE, 67
ER_FEATURE_UNSUPPORTED, 89
ER_FIELD_IN_ORDER_NOT_SELECT, 64
ER_FIELD_NOT_FOUND_PART_ERROR, 33
ER_FIELD_SPECIFIED_TWICE, 10
ER_FIELD_TYPE_NOT_ALLOWED_AS_PARTITION_FIELD, 42
ER_FILE_SORT_TERMINATED, 233
ER_FILE_EXISTS_UPGRADE, 216
ER_FILE_EXISTS_ERROR, 9
ER_FILE_HAS_OLD_FORMAT, 232
ER_FILE_NOT_FOUND, 4
ER_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS, 495
ER_FILE_TYPE_UNKNOWN, 167
ER_FILE_USED, 5
ER_FILSORT_ABORT, 5
ER_FIREWALL_DEPRECATED_USER_PROFILE, 522
ER_FIREWALL_FAILED_TO_READ_FIREWALL_TABLES, 261
ER_FIREWALL_FAILED_TO_REG_DYNAMIC_PRIVILEGES, 261

ER_FIREWALL_PFS_TABLE_REGISTER_FAILED,	ER_FPARSER_TOO_BIG_FILE, 24
517	ER_FSEEK_FAIL, 26
ER_FIREWALL_RECORDING_STMT_WAS_TRUNCATED,	ER_FT_BOOL_SYNTAX_INVALID, 140
261	ER_FT_MATCHING_KEY_NOT_FOUND, 15
ER_FIREWALL_RECORDING_STMT_WITHOUT_TEXT,	ER_FULLTEXT_FUNCTIONAL_INDEX, 100
261	ER_FULLTEXT_NOT_SUPPORTED_WITH_PARTITIONING
ER_FIREWALL_RELOADING_CACHE, 262	49
ER_FIREWALL_RESET_FOR_USER, 262	ER_FUNCTIONAL_INDEX_DATA_IS_TOO_LONG,
ER_FIREWALL_SERVICES_NOT_ACQUIRED, 517	115
ER_FIREWALL_SKIPPED_UNKNOWN_USER_MODE,	ER_FUNCTIONAL_INDEX_FUNCTION_IS_NOT_ALLOWED
261	99
ER_FIREWALL_STATUS_FLUSHED, 262	ER_FUNCTIONAL_INDEX_ON_FIELD, 100
ER_FIREWALL_SUSPICIOUS_STMT, 261	ER_FUNCTIONAL_INDEX_ON_JSON_OR_GEOMETRY_FU
ER_FIREWALL_UDF_REGISTER_FAILED, 517	99
ER_FIXING_CLIENT_CHARSET, 145	ER_FUNCTIONAL_INDEX_ON_LOB, 99
ER_FK_CANNOT_CHANGE_ENGINE, 101	ER_FUNCTIONAL_INDEX_PRIMARY_KEY, 99
ER_FK_CANNOT_DROP_PARENT, 96	ER_FUNCTIONAL_INDEX_REF_AUTO_INCREMENT,
ER_FK_CANNOT_OPEN_PARENT, 54	99
ER_FK_CANNOT_USE_VIRTUAL_COLUMN, 97	ER_FUNCTIONAL_INDEX_ROW_VALUE_IS_NOT_ALLOW
ER_FK_COLUMN_CANNOT_CHANGE, 55	104
ER_FK_COLUMN_CANNOT_CHANGE_CHILD, 55	ER_FUNCTION_DOES_NOT_SUPPORT_CHARACTER_SE
ER_FK_COLUMN_CANNOT_DROP, 54	124
ER_FK_COLUMN_CANNOT_DROP_CHILD, 54	ER_FUNCTION_NOT_DEFINED, 12
ER_FK_COLUMN_NOT_NULL, 54	ER_FUNC_INEXISTENT_NAME_COLLISION, 40
ER_FK_DEPTH_EXCEEDED, 60	ER_FUTURE_DATE, 143
ER_FK_DUP_NAME, 54	ER_GENERATED_COLUMN_FUNCTION_IS_NOT_ALLOW
ER_FK_FAIL_ADD_SYSTEM, 54	66
ER_FK_INCOMPATIBLE_COLUMNS, 102	ER_GENERATED_COLUMN_NAMED_FUNCTION_IS_NOT
ER_FK_INCORRECT_OPTION, 54	100
ER_FK_NO_COLUMN_PARENT, 97	ER_GENERATED_COLUMN_NON_PRIOR, 67
ER_FK_NO_INDEX_CHILD, 54	ER_GENERATED_COLUMN_REF_AUTO_INC, 67
ER_FK_NO_INDEX_PARENT, 54	ER_GENERATED_COLUMN_ROW_VALUE, 100
ER_FORBID_SCHEMA_CHANGE, 31	ER_GENERATED_COLUMN_VARIABLES, 100
ER_FORCE_CLOSE_THREAD, 231	ER_GEOMETRY_IN_UNKNOWN_LENGTH_UNIT,
ER_FORCING_CLOSE, 8	113
ER_FOREIGN_DATA_SOURCE_DOESNT_EXIST,	ER_GEOMETRY_PARAM_LATITUDE_OUT_OF_RANGE,
29	96
ER_FOREIGN_DATA_STRING_INVALID, 30	ER_GEOMETRY_PARAM_LONGITUDE_OUT_OF_RANGE,
ER_FOREIGN_DATA_STRING_INVALID_CANT_CREAT	96
29	ER_GET_ERRMSG, 22
ER_FOREIGN_DUPLICATE_KEY_OLD_UNUSED,	ER_GET_ERRNO, 5
36	ER_GET_ERRNO_FROM_STORAGE_ENGINE,
ER_FOREIGN_DUPLICATE_KEY_WITHOUT_CHILD_INF	202
50	ER_GET_STACKED_DA_WITHOUT_ACTIVE_HANDLER,
ER_FOREIGN_DUPLICATE_KEY_WITH_CHILD_INFO,	59
50	ER_GET_TEMPORARY_ERRMSG, 22
ER_FOREIGN_KEY_ON_PARTITIONED, 34	ER_GIS_DATA_WRONG_ENDIANESS, 63
ER_FOREIGN_KEY_WITH_ATOMIC_CREATE_SELECT,	ER_GIS_DIFFERENT_SRIDS, 62
123	ER_GIS_DIFFERENT_SRIDS_AGGREGATION,
ER_FOREIGN_SERVER_DOESNT_EXIST, 32	130
ER_FOREIGN_SERVER_EXISTS, 32	ER_GIS_INVALID_DATA, 62
ER_FOUND_MISSING_GTIDS, 331	ER_GIS_MAX_POINTS_IN_GEOMETRY_OVERFLOWED,
ER_FOUND_ROWS_WHILE_REPAIRING, 213	69
ER_FPARSER_BAD_HEADER, 24	ER_GIS_UNKNOWN_ERROR, 62
ER_FPARSER_EOF_IN_COMMENT, 24	ER_GIS_UNKNOWN_EXCEPTION, 62
ER_FPARSER_EOF_IN_UNKNOWN_PARAMETER,	ER_GIS_UNSUPPORTED_ARGUMENT, 62
25	ER_GLOBAL_VARIABLE, 18
ER_FPARSER_ERROR_IN_PARAMETER, 25	ER_GLOBSTAT_CHANGE_DURING_QUERY, 116

ER_GNO_EXHAUSTED, 50
ER_GRANT_WRONG_HOST_OR_USER, 13
ER_GROUPING_ON_TIMESTAMP_IN_DST, 116
ER_GROUP_REPLICATION_APPLIER_INIT_ERROR,
66
ER_GROUP_REPLICATION_COMMAND_FAILURE,
89
ER_GROUP_REPLICATION_COMMUNICATION_LAYERER~~ER_GRP_RPL_APPLIER_PIPELINE_NOT_DISPOSED~~,
66
ER_GROUP_REPLICATION_COMMUNICATION_LAYERE~~ER_GRP_RPL_APPLIER_TERMINATION_TIMED_OUT_ON_SH~~
66
ER_GROUP_REPLICATION_CONFIGURATION, 66
ER_GROUP_REPLICATION_MAX_GROUP_SIZE,
73
ER_GROUP_REPLICATION_PASSWORD_LENGTH,
122
ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLEDER_GRP_RPL_APPLIER_THD_START_ERROR,
170
ER_GROUP_REPLICATION_RUNNING, 66
ER_GROUP_REPLICATION_STOP_APPLIER_THREAD~~TIMEOUT~~,
66
ER_GROUP_REPLICATION_USER_EMPTY_MSG,
122
ER_GROUP_REPLICATION_USER_MANDATORY_MSGER_GRP_RPL_AUTO_INC_OFFSET_SET, 301
122
ER_GRP_DELAYED_VCLE_LOGGING, 485
ER_GRP_OPERATION_NOT_ALLOWED_GR_MUST_STOPER_GRP_RPL_BINLOG_CHECKSUM_SET, 306
121
ER_GRP_RPL_ABORTS_AS_SSL_NOT_SUPPORTED~~ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP~~,
315
ER_GRP_RPL_ADD_GRPSID_TO_GRP_TIDSID_MAP~~ERRGRP_RPL_BROADCASTING_TRANS_TO_GRP_FAILED~~,
291
309
ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_LOCAL_GTIDE~~ERRRPL_BROADCAST_COMMIT_MSSG_TOO_BIG~~,
302
322
ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTIDE~~ERRRPL_BROADCAST_COMMIT_TRANS_MSSG_FAILE~~,
302
290
ER_GRP_RPL_ADD_GTID_INFO_WITH_LOCAL_GTID_FEARL~~RPL_CANNOT_EXECUTE_TRANS_IN_ERROR_STA~~,
302
307
ER_GRP_RPL_ADD_GTID_INFO_WITH_REMOTE_GTIDE~~RACERPL_CANNOT_EXECUTE_TRANS_IN_OFFLINE_M~~,
302
307
ER_GRP_RPL_ADD_GTID_TO_GRP_TID_EXECUTED_ER~~RRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_REC~~,
291
307
ER_GRP_RPL_ADD_RETRIEVED_SET_TO_GRP_GTID~~ERRRPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPI~~,
292
307
ER_GRP_RPL_ADD_VIEW_CHANGE_UUID_TO_GRP_SE~~RRP_RPL_CANT_GENERATE_GTID~~, 292
524
ER_GRP_RPL_ALL_DONORS_LEFT_ABORT_RECOVER~~ERRRPL_CANT_KILL_THREAD~~, 491
304
ER_GRP_RPL_ALL_OBSERVERS_UNREGISTERED, ER~~RRP_RPL_CANT_READ_GRP_GTID_EXTRACTED~~,
315
293
ER_GRP_RPL_APPENDING_DATA_TO_INTERNAL_CAC~~RRP_FAILED~~,
308
ER_GRP_RPL_APPLIER_CHANNEL_STILL_RUNNING, ER~~RRP_RPL_CERTIFICATION_INITIALIZATION_FAILURE~~,
517
292
ER_GRP_RPL_APPLIER_EXECUTION_FATAL_ERROR, ER~~RRP_RPL_CERTIFICATION_REC_PROCESS~~,
290
310
ER_GRP_RPL_APPLIER_HANDLER_IS_IN_USE,
319
ER_GRP_RPL_APPLIER_HANDLER_NOT_INITIALIZED,
319
ER_GRP_RPL_APPLIER_HANDLER_ROLE_IS_IN_USE,
319
ER_GRP_RPL_APPLIER_INITIALIZED, 315
ER_GRP_RPL_APPLIER_NOT_STARTED_DUE_TO_RUNNING
315
ER_GRP_RPL_APPLIER_PIPELINE_NOT_DISPOSED,
290
ER_GRP_RPL_APPLIER_TERMINATION_TIMED_OUT_ON_SH
313
ER_GRP_RPL_APPLIER_THD_EXECUTION_ABORTED,
290
ER_GRP_RPL_APPLIER_THD_KILLED, 289
ER_GRP_RPL_APPLIER_THD_SETUP_ERROR,
299
ER_GRP_RPL_APPOINTED_PRIMARY_NOT_PRESENT,
465
ER_GRP_RPL_AUTO_INC_OFFSET_RESET, 301
ER_GRP_RPL_AUTO_INC_RESET, 301
ER_GRP_RPL_AUTO_INC_SET, 301
ER_GRP_RPL_BINLOG_DISABLED, 316
ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP,
298
ER_GRP_RPL_BROADCAST_COMMIT_MSSG_TOO_BIG,
322
ER_GRP_RPL_BROADCAST_COMMIT_TRANS_MSSG_FAILE,
307
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_ERROR_STA,
307
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_OFFLINE_M,
307
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_REC,
307
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPI,
307
ER_GRP_RPL_CANT_KILL_THREAD, 491
ER_GRP_RPL_CANT_READ_GRP_GTID_EXTRACTED,
293
ER_GRP_RPL_CANT_READ_GTID, 293
ER_GRP_RPL_CANT_READ_WRITE_SET_ITEM,
293
ER_GRP_RPL_CERTIFICATE_SIZE_ERROR, 289
ER_GRP_RPL_CERTIFICATION_INITIALIZATION_FAILURE,
292
ER_GRP_RPL_CERTIFICATION_REC_PROCESS,
310
ER_GRP_RPL_CERTIFIER_MSSG_PROCESS_ERROR,
294

ER_GRP_RPL_CHANGE_GRP_MEM_NOT_PROCESSED, 295
ER_GRP_RPL_ERROR_GTID_EXECUTION_INFO, 289
ER_GRP_RPL_CHANNEL_THREAD_WHEN_GROUP_ACTIVE, 465
ER_GRP_RPL_ERROR_GTID_SET_EXTRACTION, 464
ER_GRP_RPL_CHECK_STATUS_TABLE, 305 ER_GRP_RPL_ERROR_MSG, 268
ER_GRP_RPL_CLONE_PROCESS_EXEC_ERROR, 491 ER_GRP_RPL_ERROR_ON_CERT_DB_INSTALL, 478
ER_GRP_RPL_CLONE_PROCESS_PREPARE_ERROR, 491 ER_GRP_RPL_ERROR_ON_MESSAGE_SENDING, 465
ER_GRP_RPL_COMMUNICATION_SSL_CONF_INFO, 315 ER_GRP_RPL_ERROR_SENDING_SINGLE_PRIMARY_MS
ER_GRP_RPL_CONFIGURATION_ACTION_END, 466 ER_GRP_RPL_ERROR_STOPPING_CHANNELS, 290
ER_GRP_RPL_CONFIGURATION_ACTION_ERROR, 465 ER_GRP_RPL_ERROR_VERIFYING_SIDNO, 292
ER_GRP_RPL_CONFIGURATION_ACTION_KILLED_ERRO, 466 ER_GRP_RPL_ERROR WHILE_WAITING_FOR_CONFLICT
ER_GRP_RPL_CONFIGURATION_ACTION_LOCAL_TERMINATION, 465 ER_GRP_RPL_ESTABLISHING_CONN_GRP_REC_DONOR
ER_GRP_RPL_CONFIGURATION_ACTION_START, 465 ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHERF
ER_GRP_RPL_CONFIG_RECOVERY, 304 304
ER_GRP_RPL_CONFLICT_DETECTION_DISABLED, 294 ER_GRP_RPL_EVENT_HANDLING_ERROR, 289
ER_GRP_RPL_CONN_INTERNAL_PLUGIN_FAIL, 303 ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE, 297
ER_GRP_RPL_CONTACT_WITH_SRV_FAILED, 302 ER_GRP_RPL_EXIT_GRP_GCS_ERROR, 321
ER_GRP_RPL_COPY_FROM_EMPTY_STRING, 303 ER_GRP_RPL FAILED TO_BOOTSTRAP_EVENT_HANDLE
ER_GRP_RPL_CREATE_APPLIER_CACHE_ERROR, 289 319
ER_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL, 305 ER_GRP_RPL FAILED TO_BROADCAST_GRP_MEMBER
ER_GRP_RPL_CREATE_SESSION_UNABLE, 304 306
ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM, 297 ER_GRP_RPL FAILED TO_BROADCAST_MEMBER_STA
ER_GRP_RPL_DEBUG_OPTIONS, 321 312
ER_GRP_RPL_DEFAULT_TABLE_ENCRYPTION_DIFF_ERRO, 483
ER_GRP_RPL_FAILED_TO_CREATE_TRANS_CONTEXT, 307
ER_GRP_RPL_DISABLE_READ_ONLY_FAILED, 296 ER_GRP_RPL FAILED TO_ENABLE_READ_ONLY_MODE
ER_GRP_RPL_DISABLE_SRV_READ_MODE_RESTRICTI, 294 313
ER_GRP_RPL_DONOR_CONN_TERMINATION, 305 ER_GRP_RPL FAILED TO_ENABLE_SUPER_READ_ONL
ER_GRP_RPL_DONOR_SERVER_CONN, 305 311
ER_GRP_RPL_DONOR_TRANS_INFO_ERROR, 291 ER_GRP_RPL FAILED TO_EXTRACT_TRANS_WRITE_SE
ER_GRP_RPL_DONOR_VIEW_CHANGE_UUID_TRANS3INFO_ERROR, 524
ER_GRP_RPL_FAILED_TO_GATHER_TRANS_WRITE_SE, 308
ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GR, 308
ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_VIE, 524
ER_GRP_RPL_ENABLE_READ_ONLY_FAILED, 296 ER_GRP_RPL FAILED TO_INIT_APPLIER_HANDLER,
ER_GRP_RPL_ERROR_FETCHING_GTID_EXECUTED_319, 291
ER_GRP_RPL_ERROR_FETCHING_GTID_SET, 291 ER_GRP_RPL FAILED TO_INIT_APPLIER_MODULE, 315
ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENG, 311

ER_GRP_RPL_FAILED_TO_INIT_HANDLER, 314 ER_GRP_RPL_FLOW_CONTROL_STATS, 322
ER_GRP_RPL_FAILED_TO_INSERT_TRX_ON_TCM_ONE_FINGER_BETWEEN_CTRL_MAX_QUOTA_SMALLER_THAN_475 318
ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_ERROR_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_306 317
ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME, ER_GRP_RPL_FLOW_CTRL_MIN_RECOVERY_QUOTA_GREATER_THAN_315 318
ER_GRP_RPL_FAILED_TO_PARSE_THE_VIEW_CHANGE_ERROR_GRP_FORCE_MEMBERS_MUST_BE_EMPTY, 524 311
ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_ERROR_OBSERVER_RPL_FORCE_MEMBERS_SET_UPDATE_NOT_ALLOCATED_314 318
ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_ERROR_OBSERVER_FORCE_MEMBERS_WHEN_LEAVEING, 314 478
ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME_ERROR_REGISTRATION_FORCE_MEMBER_VALUE_SET, 308 322
ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_ERROR_OBSERVER_FORCE_MEMBER_VALUE_SET_ERROR, 314 322
ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_ERROR_GRP_RPL_FORCE_MEMBER_VALUE_TIME_OUT, 307 322
ER_GRP_RPL_FAILED_TO_SHUTDOWN_REGISTRY_MEMBER_ERROR_RPL_GCS_GR_ERROR_MSG, 323
313 ER_GRP_RPL_GCS_INTERFACE_ERROR, 321
ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_ENGINE_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION, 312 321
ER_GRP_RPL_FAILED_TO_START_ON_BOOT, ER_GRP_RPL_GROUP_NAME_PARSE_ERROR, 314 291
ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_ERROR_SYNC_GROUPNAME_SAME_SAME_AS_VIEW_CHANGE_311 523
ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER_ERROR_GRP_RPL_GRP_CHANGE_INFO_EXTRACT_ERROR, 311 297
ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL_ERROR_RPL_GRP_RPL_COMMUNICATION_ENG_INIT_FAILED, 314 321
ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE_ERROR_GRP_RPL_COMMUNICATION_INIT_WITH_CONF, 314 318
ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_START_ERROR_GRP_SERVER_GRP_MEMBER_OFFLINE, 314 321
ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STANDBY_OBSERVER, ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID, 314 321
ER_GRP_RPL_FATAL_REC_PROCESS, 309 516
ER_GRP_RPL_FETCH_FORMAT_DESC_LOG_EVENT_ERROR_GRP_RPL_GRP_NAME_IS_TOO_LONG, 301 317
ER_GRP_RPL_FETCH_GTID_LOG_EVENT_FAILED, ER_GRP_RPL_GRP_NAME_OPTION_MANDATORY, 301 317
ER_GRP_RPL_FETCH_LOG_EVENT_FAILED, 303 523
ER_GRP_RPL_FETCH_SNAPSHOT_VERSION_FAILED, ER_GRP_RPL_GTID_ALREADY_USED, 301 289
ER_GRP_RPL_FETCH_TRANS_CONTEXT_FAILED, ER_GRP_RPL_GTID_EXECUTED_EXTRACT_ERROR, 301 297
ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_ERROR_GRP_RPL_GTID_MODE_OFF, 301 316
ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_ERROR_GRP_RPL_GTID_PURGED_EXTRACT_ERROR, 301 491
ER_GRP_RPL_FETCH_TRANS_DATA_FAILED, ER_GRP_RPL_GTID_SET_EXTRACT_ERROR, 300 297
ER_GRP_RPL_FETCH_TRANS_SIDNO_ERROR, ER_GRP_RPL_GTID_SET_EXTRACT_ERROR_DURING_RECO, 292 477
ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_ERROR_GRP_RPL_INCORRECT_TYPE_SET_FOR_PARALLEL_APP, 302 316
ER_GRP_RPL_FINISHED_AUTO_REJOIN, 482 ER_GRP_RPL_INIT_CERTIFICATION_INFO_FAILURE, ER_GRP_RPL_FK_WITH CASCADE_UNSUPPORTED, 294
300 ER_GRP_RPL_INTERNAL_QUERY, 303

ER_GRP_RPL_INVALID_BINLOG_FORMAT, 306
ER_GRP_RPL_INVALID_COMMUNICATION_PROTOCOL, 299
482
ER_GRP_RPL_INVALID_DEBUG_OPTIONS, 321
ER_GRP_RPL_INVALID_GTID_SET, 292
ER_GRP_RPL_INVALID_SSL_RECOVERY_STRING, 295
318
ER_GRP_RPL_INVALID_TRANS_WRITE_SET_EXTRACT, 290
316
ER_GRP_RPL_IS_STARTING, 504
ER_GRP_RPL_IS_STOPPED, 313
ER_GRP_RPL_IS_STOPPING, 313
ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION, 312
465
ER_GRP_RPL_JOIN_WHEN_GROUP_ACTION_RUNNING, 322
465
ER_GRP_RPL_KILLED_FAILED_ID, 303
299
ER_GRP_RPL_KILLED_SESSION_ID, 303
ER_GRP_RPL_LOCAL_GTID_SETS_PROCESS_ERROR, 298
298
ER_GRP_RPL_LOG_REPLICA_UPDATES_NOT_SET, 298
316
ER_GRP_RPL_LOG_SLAVE_UPDATES_NOT_SET, 298
316
ER_GRP_RPL_LOWER_CASE_TABLE_NAMES_DIFF, 298
455
ER_GRP_RPL_MASTER_INFO_REPO_MUST_BE_TABLE, 295
316
ER_GRP_RPL_MAXIMUM_CONNECTION_RETRIES, 493
304
ER_GRP_RPL_MEMBER_ACTIONS_RESET, 522
ER_GRP_RPL_MEMBER_ACTION_DEFAULT_CONFIGURATION, 521
521
ER_GRP_RPL_MEMBER_ACTION_DISABLED, 464
522
ER_GRP_RPL_MEMBER_ACTION_ENABLED, 522
ER_GRP_RPL_MEMBER_ACTION_FAILURE, 521
ER_GRP_RPL_MEMBER_ACTION_FAILURE_IGNORE, 317
520
ER_GRP_RPL_MEMBER_ACTION_GET_EXCHANGEABLE, 309
521
ER_GRP_RPL_MEMBER_ACTION_INVALID_ACTIONS, 307
522
ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_MEMBER, 300
521
ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_RECEIVER, 296
521
ER_GRP_RPL_MEMBER_ACTION_TRIGGERED, 302
520
ER_GRP_RPL_MEMBER_ACTION_UNABLE_TO_SET, 491
521
ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS, 304
521
ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS, 293
522
ER_GRP_RPL_MEMBER_ADDED, 295
ER_GRP_RPL_MEMBER_ALREADY_EXISTS, 297
ER_GRP_RPL_MEMBER_CHANGE, 296
ER_GRP_RPL_MEMBER_CONF_INFO, 312
ER_GRP_RPL_MEMBER_CONTACT_RESTORED, 295
ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR, 290
ER_GRP_RPL_MEMBER_EXPelled, 296
ER_GRP_RPL_MEMBER_LEFT_GRP, 296
ER_GRP_RPL_MEMBER_NOT_FOUND, 304
ER_GRP_RPL_MEMBER_REMOVED, 295
ER_GRP_RPL_MEMBER_SERVER_UUID_IS_INCOMPATIBLE, 312
ER_GRP_RPL_MEMBER_STATS_INFO, 322
ER_GRP_RPL_MEMBER_STOP_RPL_CHANNELS_ERROR, 299
ER_GRP_RPL_MEMBER_TRANS_GREATER_THAN_GRP, 298
ER_GRP_RPL_MEMBER_VERSION_LOWER_THAN_GRP, 298
ER_GRP_RPL_MEMBER_VER_INCOMPATIBLE, 298
ER_GRP_RPL_MEMBER_VER_READ_COMPATIBLE, 298
ER_GRP_RPL_MEM_ONLINE, 294
ER_GRP_RPL_MEM_REACHABLE, 295
ER_GRP_RPL_MEM_UNREACHABLE, 295
ER_GRP_RPL_MESSAGE_SERVICE_FATAL_ERROR, 493
ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE, 295
ER_GRP_RPL_MESSAGE_SERVICE_INITIALIZATION, 295
ER_GRP_RPL_MISSING_GRP_RPL_ACTION_COORDINATOR, 294
ER_GRP_RPL_MISSING_GRP_RPL_APPLIER, 294
ER_GRP_RPL_MODULE_TERMINATE_ERROR, 294
ER_GRP_RPL_MSG_DISCARDED, 294
ER_GRP_RPL_MSG_TOO_LONG_BROADCASTING_TRANSACTION, 309
ER_GRP_RPL_MULTIPLE_CACHE_TYPE_NOT_SUPPORTED, 307
ER_GRP_RPL_NEEDS_INNODB_TABLE, 300
ER_GRP_RPL_NEW_PRIMARY_ELECTED, 296
ER_GRP_RPL_NOTIFY_CERTIFICATION_OUTCOME_FAILURE, 302
ER_GRP_RPL_NO_POSSIBLE_RECOVERY, 491
ER_GRP_RPL_NO_STAGE_SERVICE, 466
ER_GRP_RPL_PRIMARY_MEMBERSHIP_TABLE_PRIMARY_MEM, 297
ER_GRP_RPL_NO_VALID_DONOR, 304
ER_GRP_RPL_NULL_PACKET, 293
ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE, 310
ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFIERS, 306
ER_GRP_RPL_PIPELINE_CREATE_FAILED, 322
ER_GRP_RPL_PIPELINE_FLUSH_FAIL, 323

ER_GRP_RPL_PIPELINE_REINIT_FAILED_READ,
323
ER_GRP_RPL_PIPELINE_REINIT_FAILED_WRITE,
323
ER_GRP_RPL_PLUGIN_ABORT, 461
ER_GRP_RPL_PLUGIN_STRUCT_INIT_NOT_POSSIBLE
311
ER_GRP_RPL_PREV_REC_SESSION_RUNNING,
309
ER_GRP_RPL_PRIMARY_ELECTION_PROCESS_ERROR
466
ER_GRP_RPL_PRIMARY_ELECTION_STOP_ERROR,
466
ER_GRP_RPL_PRIMARY_KEY_NOT_DEFINED,
300
ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP,
295
ER_GRP_RPL_PROCESS_GTID_SET_ERROR,
293
ER_GRP_RPL_PROCESS_INTERSECTION_GTID_SET
293
ER_GRP_RPL_PURGE_APPLIER_LOGS, 299
ER_GRP_RPL_PURGE_REC, 305
ER_GRP_RPL_QUERY_FAIL, 303
ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY_SUPER
310
ER_GRP_RPL_READ_UNABLE_FOR_SUPER_READ_ONLY
310
ER_GRP_RPL_RECEIVED_SET_MISSING_GTIDS,
293
ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING
129
ER_GRP_RPL_RECOVERY_ENDPOINT_FORMAT,
505
ER_GRP_RPL_RECOVERY_ENDPOINT_INTERFACES
505
ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID,
505
ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID_DONOR
ER_GRP_RPL_SESSION_OPEN_FAILED, 296
ER_GRP_RPL_RECOVERY_EVAL_ERROR, 491
ER_GRP_RPL_RECOVERY_MODULE_TERMINATION
313
ER_GRP_RPL_RECOVERY_STRAT_CHOICE, 492
ER_GRP_RPL_RECOVERY_STRAT_CLONE_PURGED, ER_GRP_RPL_SINGLE_PRIM_MODE_NOT_ALLOWED_WITH
491
ER_GRP_RPL_RECOVERY_STRAT_CLONE_THRESHOLD
491
ER_GRP_RPL_RECOVERY_STRAT_FALLBACK,
492
ER_GRP_RPL_RECOVERY_STRAT_NO_FALLBACK,
492
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_DEPENDENCIES
476
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_GROUP_PARALLEL_FAILURE
475
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_SYNC_BEFORE_EXECUTE_SLAVE_OF_THREAD
476
ER_GRP_RPL_REINIT_OF_COMMIT_CACHE_FOR_WRITE_F
309
ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_READ_F
308
ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_WRITE_
309
ER_GRP_RPL_RELAY_LOG_INFO_REPO_MUST_BE_TABLE,
316
ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_DEPENDENC
476
ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_WAIT_FOR_S
477
ER_GRP_RPL_RELEASE_COMMIT_AFTER_GROUP_PREPAR
475
ER_GRP_RPL_REPLICA_PRESERVE_COMMIT_ORDER_NOT
317
ER_GRP_RPL_REQUESTING_NON_MEMBER_SERVER_TO_L
313
ER_GRP_RPL_RESET_APPLIER_MODULE_LOGS_ERROR,
299
ER_GRP_RPL_SALVE_IO_THD_ON_SECONDARY_MEMBER,
300
ER_GRP_RPL_SEND_STATS_ERROR, 322
ER_GRP_RPL_SEND_TRX_PREPARED_MESSAGE_FAILED,
322
ER_GRP_RPL_SEND_TRX_SYNC_BEFORE_EXECUTION_FA
312
ER_GRP_RPL_SERVER_CONN_ERROR, 291
ER_GRP_RPL_SERVER_IS_ALREADY_LEAVE,
312
ER_GRP_RPL_SERVER_SET_TO_OFFLINE_MODE_DUE_TO
493
ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DUE_TO_ER
323
ER_GRP_RPL_SERVER_UDF_ERROR, 467
ER_GRP_RPL_SERVER_WORKING_AS_SECONDARY,
311
ER_GRP_RPL_SET_GRP_COMMUNICATION_ENG_LOGGER
321
ER_GRP_RPL_SET_GRP_RESPONSE_STABILIT
293
ER_GRP_RPL_SIDNO_FETCH_ERROR, 290
ER_GRP_RPL_SINGLE_PRIM_MODE_NOT_ALLOWED_WITH
317
ER_GRP_RPL_SKIP_COMPUTATION_TRANS_COMMITTED,
293
ER_GRP_RPL_SLAVE_APPLIER_THREAD_ERROR_OUT,
323
ER_GRP_RPL_SLAVE_APPLIER_THREAD_UNBLOCKED,
323
ER_GRP_RPL_SLAVE_IO_THD_PRIMARY_UNKNOWN,
300
ER_GRP_RPL_THREAD_ERROR_OUT,
323
ER_GRP_RPL_THREAD_UNBLOCKED,
323

ER_GRP_RPL_SLAVE_PRESERVE_COMMIT_ORDER_ER_GRP_RPL_TRANS_GREATER_THAN_GRP,
317 298

ER_GRP_RPL_SLAVE_SQL_THD_ON_SECONDARY_MEMBER_ER_GRP_RPL_TRANS_NOT_PRESENT_IN_GRP,
300 298

ER_GRP_RPL_SLAVE_SQL_THD_PRIMARY_UNKNOWNR_GRP_RPL_TRANS_SIZE_EXCEEDS_LIMIT,
300 308

ER_GRP_RPL_SLAVE_THREAD_ERROR_ON_CLONE, ER_GRP_RPL_TRANS_WRITE_SET_EXTRACTION_NOT_492 306

ER_GRP_RPL_SQL_SERVICE_COMM_SESSION_NOT_ER_GRP_RPL_TRANS_WRITE_SET_EXTRACT_DIFF_FRC
319 299

ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SEEER_GRP_RPL_TRX_ALREADY_EXISTS_ON_TCM_ON_AFF
320 475

ER_GRP_RPL_SQL_SERVICE_FAILED_TO_INIT_SESSION_ER_GRP_RPL_TRX_DOES_NOT_EXIST_ON_TCM_ON_HA
319 476

ER_GRP_RPL_SQL_SERVICE_FAILED_TO_RUN_SQL_ER_GRP_RPL_TRX_WAIT_FOR_GROUP_GTID_EXECUTE
320 477

ER_GRP_RPL_SQL_SERVICE_MAX_CONN_ERROR_FREOM_GRP_RPL_TRX_WAIT_FOR_GROUP_PREPARE_FAIL
320 476

ER_GRP_RPL_SQL_SERVICE_RETRIES_EXCEEDED_GER_SESSION_STRAEWAIT_FOR_SYNC_BEFORE_EXECUT
320 477

ER_GRP_RPL_SQL_SERVICE_SERVER_ACCESS_DENIED_ER_GRP_RPL_UDF_ERROR, 115
320 ER_GRP_RPL_UDF_REGISTER_ERROR, 466

ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_ER_GRP_RPL_UDF_REGISTER_SERVICE_ERROR,
320 466

ER_GRP_RPL_SQL_SERVICE_SERVER_INTERNAL_FAER_GRP_RPL_UDF_UNREGISTER_ERROR, 466
320 ER_GRP_RPL_UNABLE_TO_CERTIFY_PLUGIN_TRANS,

ER_GRP_RPL_SQL_SERVICE_SERVER_SESSION_KILLED,
319 ER_GRP_RPL_UNABLE_TO_CONVERT_EVENT_TO_PAC
323

ER_GRP_RPL_SRV_BLOCKED, 295 ER_GRP_RPL_UNABLE_TO_CONVERT_PACKET_TO_EV
323

ER_GRP_RPL_SRV_BLOCKED_FOR_SECS, 295

ER_GRP_RPL_SRV_GTIW_ERROR, 485

ER_GRP_RPL_SRV_NOT_ONLINE, 294

ER_GRP_RPL_SRV_ONLINE, 294

ER_GRP_RPL_SRV_PRIMARY_MEM, 296

ER_GRP_RPL_SRV_SECONDARY_MEM, 296

ER_GRP_RPL_SRV_WAIT_TIME_OUT, 302

ER_GRP_RPL_SSL_DISABLED, 315

ER_GRP_RPL_STARTED_AUTO_REJOIN, 482

ER_GRP_RPL_STARTING_GRP_REC, 305

ER_GRP_RPL_START_FAILED, 298

ER_GRP_RPL_START_GRP_RPL_FAILED, 303

ER_GRP_RPL_STOPPING_GRP_REC, 305

ER_GRP_RPL_STOP_REP_CHANNEL, 323

ER_GRP_RPL_SUPER_READ_OFF, 303

ER_GRP_RPL_SUPER_READ_ON, 303

ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERRORERR_GRP_RPL_UNBLOCK_WAITING THD, 290
297 ER_GRP_RPL_UNKNOWN_GRP_RPL_APPLIER_PIPELINE

ER_GRP_RPL_SUPPORTS_ONLY_ONE_FORCE_MEMBERS_SET,
318 ER_GRP_RPL_UNREACHABLE_MAORITY_TIMEOUT_FC

ER_GRP_RPL_TIMEOUT_ON_VIEW_AFTER_JOINING_GRP,
312 ER_GRP_RPL_UNSUPPORTED_TRANS_ISOLATION,

ER_GRP_RPL_TIMEOUT_RECEIVED_VC_LEAVE_ON_REJOIN,
512 ER_GRP_RPL_UPDATE_GRP_GTIW_EXECUTED_ERROR,

ER_GRP_RPL_TIMEOUT_RECEIVED_VC_ON_REJOIN, 291

482 ER_GRP_RPL_UPDATE_GRP_GTIW_VIEW_CHANGE_UUID

ER_GRP_RPL_TIMEOUT RECEIVING VIEW CHANGE_50AN SHUTDOWN,
313 ER_GRP_RPL_UPDATE_GTID_SET_ERROR, 292

ER_GRP_RPL_UPDATE_LAST_CONFLICT_FREE_TRANSACTION_PURGED_WAS_UPDATED, 231
292 ER_GTIID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION
ER_GRP_RPL_UPDATE_SERV_CERTIFICATE_FAILED, 101
302 ER_GTIID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND
ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_REF_VERSION_ERROR,
292 ER_GTIID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND
ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_VERSION_ERROR,
290 ER_GTIID_UNSAFE_CREATE_DROP_TEMPORARY_TABLE_IM
ER_GRP_RPL_VIEW_CHANGE_UUID_DIFF_FROM_GRP1
523 ER_GTIID_UNSAFE_CREATE_SELECT, 51
ER_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE_ER_GTIID_UNSAFE_NON_TRANSACTIONAL_TABLE,
131 51
ER_GRP_RPL_VIEW_CHANGE_UUID_INVALID, ER_HANDLERTON_OOM, 156
523 ER_HANDSHAKE_ERROR, 5
ER_GRP_RPL_VIEW_CHANGE_UUID_IS_SAME_AS_ANOTHER_ID_ER_GTIID_UNSAFE_NON_TRANSACTIONAL_TABLE,
523 ER_HEALTH_INFO, 516
ER_GRP_RPL_VIEW_CHANGE_UUID_PARSE_ERROR, ER_HEALTH_WARNING, 516
524 ER_HEALTH_WARNING_DISK_USAGE_LEVEL_1,
ER_GRP_RPL_VIEW_CHANGE_UUID_SAME_AS_GROUPNAME,
523 ER_HEALTH_WARNING_DISK_USAGE_LEVEL_2,
ER_GRP_RPL_WAITING_FOR_VIEW_UPDATE, 516
312 ER_HEALTH_WARNING_DISK_USAGE_LEVEL_3,
ER_GRP_RPL_WAIT_FOR_DEPENDENCIES_FAILED, 517
476 ER_HOSTNAME, 32
ER_GRP_RPL_WHILE_SENDING_MSG_REC, 310 ER_HOSTNAME_DOESNT_RESOLVE_TO, 137
ER_GRP_RPL_WHILE_STOPPING_REP_CHANNEL, 310 ER_HOSTNAME_RESEMBLES_IPV4, 137
ER_HOSTNAME_TOO_LONG, 122
ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODING_HOSTNAME_TRUNCATED, 507
306 ER_HOST_IS_BLOCKED, 12
ER_GRP_RPL_WRITE_TO_BINLOG_CACHE_FAILED, ER_HOST_NOT_PRIVILEGED, 12
308 ER_HYPERGRAPH_NOT_SUPPORTED_YET, 125
ER_GRP_RPL_WRITE_TO_TRANSACTION_MESSAGE_FAILED_CANNOT_UPGRADE_WITH_DISCARDED_TABLESPACE
308 507
ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN_IB_CLONE_GTID_PERSIST, 348
104 ER_IB_CLONE_INTERNAL, 346
ER_GRP_TRX_CONSISTENCY_BEFORE, 104 ER_IB_CLONE_NON_INNODB_TABLE, 490
ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED_ER_IB_CLONE_OPERATION, 490
104 ER_IB_CLONE_PUNCH_HOLE, 347
ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED, ER_IB_CLONE_RESTART, 490
104 ER_IB_CLONE_SQL, 347
ER_GR_ELECTED_PRIMARY_GTID_INFORMATION, ER_IB_CLONE_START_STOP, 490
497 ER_IB_CLONE_STATUS_FILE, 347
ER_IB_CLONE_TIMEOUT, 347
ER_GR_HOLD_KILLED, 102 ER_IB_CLONE_USER_DATA, 490
ER_GR_HOLD_MEMBER_STATUS_ERROR, 102 ER_IB_CLONE_VALIDATE, 347
ER_GR_HOLD_WAIT_TIMEOUT, 102 ER_IB_DBLWR_DECOMPRESS_FAILED, 513
ER_GTIID_ALREADY_ADDED_BY_USER, 171 ER_IB_DBLWR_DECRYPT_FAILED, 513
ER_GTIID_EXECUTED_WAS_CHANGED, 55 ER_IB_DBLWR_KEY_MISSING, 514
ER_GTIID_EXECUTED_WAS_UPDATED, 231 ER_IB_ERR_DDL_LOG_INSERT_FAILURE, 507
ER_GTIID_MODE_CAN_ONLY_CHANGE_ONE_STEP_AT_A_TIME_IB_ERR_DDL_LOG_INSERT_FAILURE, 507
52 ER_IB_ERR_FOUND_N_DUPLICATE_KEYS, 511
ER_GTIID_MODE_OFF, 64 ER_IB_ERR_FOUND_N_RECORDS_WRONG_ORDER,
ER_GTIID_MODE_ON_REQUIRE_ENFORCE_GTID_CONSISTENCY_ON,
51 ER_IB_ERR_INDEX_DUPLICATE_KEY, 510
ER_GTIID_NEXT_CANT_BE_AUTOMATIC_IF_GTID_NEXT_LISTENER_NON_EMURECORDS_WRONG_ORDER,
50 510
ER_GTIID_NEXT_TYPE_UNDEFINED_GROUP, 55 ER_IB_ERR_LOG_PARSING_BUFFER_OVERFLOW,
ER_GTIID_NEXT_TYPE_UNDEFINED_GTID, 55 509
ER_GTIID_PURGED_WAS_CHANGED, 55

ER_IB_ERR_NOT_ENOUGH_MEMORY_FOR_PARSE_BERIBRMSG_102, 342
509 ER_IB_MSG_1020, 428
ER_IB_ERR_PAGE_ARCH_INVALID_DOUBLE_WRITE_BERIBJMSG_1021, 428
504 ER_IB_MSG_1022, 429
ER_IB_ERR_PAGE_ARCH_INVALID_FORMAT, ER_IB_MSG_1023, 429
504 ER_IB_MSG_1024, 429
ER_IB_ERR_PAGE_ARCH_RECOVERY_FAILED, ER_IB_MSG_1025, 429
504 ER_IB_MSG_1026, 429
ER_IB_ERR_PARALLEL_READ_OOM, 511 ER_IB_MSG_1027, 429
ER_IB_ERR_RECOVERY_REDO_DISABLED, 506 ER_IB_MSG_1028, 429
ER_IB_ERR_SCHED_SETAFFNINITY_FAILED, ER_IB_MSG_1029, 429
509 ER_IB_MSG_103, 342
ER_IB_ERR_TEMP_TABLESPACE_DIR_CONTAINS_SEERCBLMSG_1030, 429
509 ER_IB_MSG_1031, 429
ER_IB_ERR_TEMP_TABLESPACE_DIR_DOESNT_EXISTER_IB_MSG_1032, 429
508 ER_IB_MSG_1033, 430
ER_IB_ERR_TEMP_TABLESPACE_DIR_EMPTY, ER_IB_MSG_1034, 430
509 ER_IB_MSG_1035, 430
ER_IB_ERR_TEMP_TABLESPACE_DIR_SUBDIR_OF_DERRADBMSG_1036, 430
509 ER_IB_MSG_1037, 430
ER_IB_ERR_UNKNOWN_PAGE_FETCH_MODE, ER_IB_MSG_1038, 430
509 ER_IB_MSG_1039, 430
ER_IB_ERR_ZLIB_BUF_ERROR, 510 ER_IB_MSG_104, 342
ER_IB_ERR_ZLIB_DATA_ERROR, 510 ER_IB_MSG_1040, 430
ER_IB_ERR_ZLIB_MEM_ERROR, 510 ER_IB_MSG_1041, 430
ER_IB_ERR_ZLIB_UNCOMPRESS_FAILED, 510 ER_IB_MSG_1042, 430
ER_IB_ERR_ZLIB_UNKNOWN_ERROR, 510 ER_IB_MSG_1043, 430
ER_IB_FAILED_TO_DELETE_TABLESPACE_FILE, ER_IB_MSG_1044, 431
508 ER_IB_MSG_1045, 431
ER_IB_INNODB_TBSP_OUT_OF_SPACE, 517 ER_IB_MSG_1046, 431
ER_IB_LOB_ROLLBACK_INDEX_LEN, 496 ER_IB_MSG_1047, 431
ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION, ER_IB_MSG_1048, 431
507 ER_IB_MSG_1049, 431
ER_IB_MSG_0, 333 ER_IB_MSG_105, 342
ER_IB_MSG_1, 333 ER_IB_MSG_1050, 431
ER_IB_MSG_10, 334 ER_IB_MSG_1051, 431
ER_IB_MSG_100, 342 ER_IB_MSG_1052, 431
ER_IB_MSG_1000, 427 ER_IB_MSG_1053, 431
ER_IB_MSG_1001, 427 ER_IB_MSG_1054, 432
ER_IB_MSG_1002, 427 ER_IB_MSG_1055, 432
ER_IB_MSG_1003, 427 ER_IB_MSG_1056, 432
ER_IB_MSG_1004, 427 ER_IB_MSG_1057, 432
ER_IB_MSG_1005, 427 ER_IB_MSG_1058, 432
ER_IB_MSG_1006, 427 ER_IB_MSG_1059, 432
ER_IB_MSG_1007, 427 ER_IB_MSG_106, 342
ER_IB_MSG_1008, 427 ER_IB_MSG_1060, 432
ER_IB_MSG_1009, 427 ER_IB_MSG_1061, 432
ER_IB_MSG_101, 342 ER_IB_MSG_1062, 432
ER_IB_MSG_1010, 427 ER_IB_MSG_1063, 432
ER_IB_MSG_1011, 428 ER_IB_MSG_1064, 432
ER_IB_MSG_1012, 428 ER_IB_MSG_1065, 433
ER_IB_MSG_1013, 428 ER_IB_MSG_1066, 433
ER_IB_MSG_1014, 428 ER_IB_MSG_1067, 433
ER_IB_MSG_1015, 428 ER_IB_MSG_1068, 433
ER_IB_MSG_1016, 428 ER_IB_MSG_1069, 433
ER_IB_MSG_1017, 428 ER_IB_MSG_107, 343
ER_IB_MSG_1018, 428 ER_IB_MSG_1070, 433
ER_IB_MSG_1019, 428 ER_IB_MSG_1071, 433

ER_IB_MSG_1072, 433
ER_IB_MSG_1073, 433
ER_IB_MSG_1074, 433
ER_IB_MSG_1075, 433
ER_IB_MSG_1076, 434
ER_IB_MSG_1077, 434
ER_IB_MSG_1078, 434
ER_IB_MSG_1079, 434
ER_IB_MSG_108, 343
ER_IB_MSG_1080, 434
ER_IB_MSG_1081, 434
ER_IB_MSG_1082, 434
ER_IB_MSG_1083, 434
ER_IB_MSG_1084, 434
ER_IB_MSG_1085, 434
ER_IB_MSG_1086, 435
ER_IB_MSG_1087, 435
ER_IB_MSG_1088, 435
ER_IB_MSG_1089, 435
ER_IB_MSG_109, 343
ER_IB_MSG_1090, 435
ER_IB_MSG_1091, 435
ER_IB_MSG_1092, 435
ER_IB_MSG_1093, 435
ER_IB_MSG_1094, 435
ER_IB_MSG_1095, 436
ER_IB_MSG_1096, 436
ER_IB_MSG_1097, 436
ER_IB_MSG_1098, 436
ER_IB_MSG_1099, 436
ER_IB_MSG_11, 334
ER_IB_MSG_110, 343
ER_IB_MSG_1100, 436
ER_IB_MSG_1101, 436
ER_IB_MSG_1102, 436
ER_IB_MSG_1103, 436
ER_IB_MSG_1104, 436
ER_IB_MSG_1105, 437
ER_IB_MSG_1106, 437
ER_IB_MSG_1107, 437
ER_IB_MSG_1108, 437
ER_IB_MSG_1109, 437
ER_IB_MSG_111, 343
ER_IB_MSG_1110, 437
ER_IB_MSG_1111, 437
ER_IB_MSG_1112, 437
ER_IB_MSG_1113, 437
ER_IB_MSG_1114, 437
ER_IB_MSG_1115, 438
ER_IB_MSG_1116, 438
ER_IB_MSG_1117, 438
ER_IB_MSG_1118, 438
ER_IB_MSG_1119, 438
ER_IB_MSG_112, 343
ER_IB_MSG_1120, 438
ER_IB_MSG_1121, 438
ER_IB_MSG_1122, 438
ER_IB_MSG_1123, 438
ER_IB_MSG_1124, 438
ER_IB_MSG_1125, 438
ER_IB_MSG_1126, 439
ER_IB_MSG_1127, 439
ER_IB_MSG_1128, 439
ER_IB_MSG_1129, 439
ER_IB_MSG_113, 343
ER_IB_MSG_1130, 439
ER_IB_MSG_1131, 439
ER_IB_MSG_1132, 439
ER_IB_MSG_1133, 439
ER_IB_MSG_1134, 439
ER_IB_MSG_1135, 439
ER_IB_MSG_1136, 440
ER_IB_MSG_1137, 440
ER_IB_MSG_1138, 440
ER_IB_MSG_1139, 440
ER_IB_MSG_114, 343
ER_IB_MSG_1140, 440
ER_IB_MSG_1141, 440
ER_IB_MSG_1142, 440
ER_IB_MSG_1143, 440
ER_IB_MSG_1144, 440
ER_IB_MSG_1145, 441
ER_IB_MSG_1146, 441
ER_IB_MSG_1147, 441
ER_IB_MSG_1148, 441
ER_IB_MSG_1149, 441
ER_IB_MSG_115, 343
ER_IB_MSG_1150, 441
ER_IB_MSG_1151, 441
ER_IB_MSG_1152, 441
ER_IB_MSG_1153, 441
ER_IB_MSG_1154, 442
ER_IB_MSG_1155, 442
ER_IB_MSG_1156, 442
ER_IB_MSG_1157, 442
ER_IB_MSG_1158, 442
ER_IB_MSG_1159, 442
ER_IB_MSG_116, 343
ER_IB_MSG_1160, 442
ER_IB_MSG_1161, 442
ER_IB_MSG_1162, 442
ER_IB_MSG_1163, 442
ER_IB_MSG_1164, 442
ER_IB_MSG_1165, 443
ER_IB_MSG_1166, 443
ER_IB_MSG_1167, 443
ER_IB_MSG_1168, 443
ER_IB_MSG_1169, 443
ER_IB_MSG_117, 343
ER_IB_MSG_1170, 443
ER_IB_MSG_1171, 443
ER_IB_MSG_1172, 444
ER_IB_MSG_1173, 444
ER_IB_MSG_1174, 444
ER_IB_MSG_1175, 444
ER_IB_MSG_1176, 444

ER_IB_MSG_1177, 444
ER_IB_MSG_1178, 444
ER_IB_MSG_1179, 445
ER_IB_MSG_118, 344
ER_IB_MSG_1180, 445
ER_IB_MSG_1181, 445
ER_IB_MSG_1182, 445
ER_IB_MSG_1183, 445
ER_IB_MSG_1184, 445
ER_IB_MSG_1185, 445
ER_IB_MSG_1186, 445
ER_IB_MSG_1187, 445
ER_IB_MSG_1188, 445
ER_IB_MSG_1189, 445
ER_IB_MSG_119, 344
ER_IB_MSG_1190, 446
ER_IB_MSG_1191, 446
ER_IB_MSG_1192, 446
ER_IB_MSG_1193, 446
ER_IB_MSG_1194, 446
ER_IB_MSG_1195, 446
ER_IB_MSG_1196, 446
ER_IB_MSG_1197, 446
ER_IB_MSG_1198, 446
ER_IB_MSG_1199, 447
ER_IB_MSG_12, 334
ER_IB_MSG_120, 344
ER_IB_MSG_1200, 447
ER_IB_MSG_1201, 447
ER_IB_MSG_1202, 447
ER_IB_MSG_1203, 447
ER_IB_MSG_1204, 447
ER_IB_MSG_1205, 447
ER_IB_MSG_1206, 447
ER_IB_MSG_1207, 447
ER_IB_MSG_1208, 447
ER_IB_MSG_1209, 447
ER_IB_MSG_121, 344
ER_IB_MSG_1210, 448
ER_IB_MSG_1211, 448
ER_IB_MSG_1212, 448
ER_IB_MSG_1213, 448
ER_IB_MSG_1214, 448
ER_IB_MSG_1215, 448
ER_IB_MSG_1216, 448
ER_IB_MSG_1217, 448
ER_IB_MSG_1218, 448
ER_IB_MSG_1219, 448
ER_IB_MSG_122, 344
ER_IB_MSG_1220, 448
ER_IB_MSG_1221, 449
ER_IB_MSG_1222, 449
ER_IB_MSG_1223, 449
ER_IB_MSG_1224, 449
ER_IB_MSG_1225, 449
ER_IB_MSG_1226, 449
ER_IB_MSG_1227, 449
ER_IB_MSG_1228, 449
ER_IB_MSG_1229, 449
ER_IB_MSG_123, 344
ER_IB_MSG_1230, 449
ER_IB_MSG_1231, 449
ER_IB_MSG_1232, 450
ER_IB_MSG_1233, 450
ER_IB_MSG_1234, 450
ER_IB_MSG_1235, 450
ER_IB_MSG_1236, 450
ER_IB_MSG_1237, 450
ER_IB_MSG_1238, 450
ER_IB_MSG_1239, 450
ER_IB_MSG_124, 344
ER_IB_MSG_1240, 450
ER_IB_MSG_1241, 450
ER_IB_MSG_1242, 450
ER_IB_MSG_1243, 451
ER_IB_MSG_1244, 451
ER_IB_MSG_1245, 451
ER_IB_MSG_1246, 451
ER_IB_MSG_1247, 451
ER_IB_MSG_1248, 451
ER_IB_MSG_1249, 451
ER_IB_MSG_125, 344
ER_IB_MSG_1250, 451
ER_IB_MSG_1251, 451
ER_IB_MSG_1252, 451
ER_IB_MSG_1253, 452
ER_IB_MSG_1254, 452
ER_IB_MSG_1255, 452
ER_IB_MSG_1256, 452
ER_IB_MSG_1257, 452
ER_IB_MSG_1258, 452
ER_IB_MSG_1259, 452
ER_IB_MSG_126, 344
ER_IB_MSG_1260, 452
ER_IB_MSG_1261, 452
ER_IB_MSG_1262, 452
ER_IB_MSG_1263, 452
ER_IB_MSG_1264, 453
ER_IB_MSG_1265, 453
ER_IB_MSG_1266, 453
ER_IB_MSG_1267, 453
ER_IB_MSG_1268, 453
ER_IB_MSG_1269, 453
ER_IB_MSG_127, 344
ER_IB_MSG_1270, 453
ER_IB_MSG_1271, 461
ER_IB_MSG_1272, 461
ER_IB_MSG_1273, 462
ER_IB_MSG_1274, 463
ER_IB_MSG_1275, 463
ER_IB_MSG_1276, 463
ER_IB_MSG_1277, 463
ER_IB_MSG_1278, 463
ER_IB_MSG_1279, 463
ER_IB_MSG_128, 344
ER_IB_MSG_1280, 464

ER_IB_MSG_1281, 464
ER_IB_MSG_1282, 464
ER_IB_MSG_1283, 464
ER_IB_MSG_1284, 464
ER_IB_MSG_1285, 487
ER_IB_MSG_129, 345
ER_IB_MSG_13, 334
ER_IB_MSG_130, 345
ER_IB_MSG_131, 345
ER_IB_MSG_132, 345
ER_IB_MSG_133, 345
ER_IB_MSG_134, 345
ER_IB_MSG_135, 345
ER_IB_MSG_1357, 508
ER_IB_MSG_1358, 508
ER_IB_MSG_1359, 508
ER_IB_MSG_136, 345
ER_IB_MSG_137, 345
ER_IB_MSG_1372, 509
ER_IB_MSG_1373, 509
ER_IB_MSG_1374, 509
ER_IB_MSG_1375, 510
ER_IB_MSG_138, 345
ER_IB_MSG_1381, 510
ER_IB_MSG_139, 345
ER_IB_MSG_14, 334
ER_IB_MSG_140, 346
ER_IB_MSG_141, 346
ER_IB_MSG_142, 346
ER_IB_MSG_143, 346
ER_IB_MSG_144, 346
ER_IB_MSG_145, 346
ER_IB_MSG_146, 346
ER_IB_MSG_147, 346
ER_IB_MSG_148, 346
ER_IB_MSG_149, 346
ER_IB_MSG_15, 334
ER_IB_MSG_150, 347
ER_IB_MSG_151, 347
ER_IB_MSG_152, 347
ER_IB_MSG_153, 347
ER_IB_MSG_154, 347
ER_IB_MSG_155, 347
ER_IB_MSG_156, 348
ER_IB_MSG_157, 348
ER_IB_MSG_158, 348
ER_IB_MSG_159, 348
ER_IB_MSG_16, 334
ER_IB_MSG_160, 348
ER_IB_MSG_161, 348
ER_IB_MSG_162, 348
ER_IB_MSG_163, 348
ER_IB_MSG_164, 348
ER_IB_MSG_165, 348
ER_IB_MSG_166, 349
ER_IB_MSG_167, 349
ER_IB_MSG_168, 349
ER_IB_MSG_169, 349
ER_IB_MSG_17, 334
ER_IB_MSG_170, 349
ER_IB_MSG_171, 349
ER_IB_MSG_172, 349
ER_IB_MSG_173, 349
ER_IB_MSG_174, 349
ER_IB_MSG_175, 349
ER_IB_MSG_176, 349
ER_IB_MSG_177, 350
ER_IB_MSG_178, 350
ER_IB_MSG_179, 350
ER_IB_MSG_18, 334
ER_IB_MSG_180, 350
ER_IB_MSG_181, 350
ER_IB_MSG_182, 350
ER_IB_MSG_183, 350
ER_IB_MSG_184, 350
ER_IB_MSG_185, 350
ER_IB_MSG_186, 350
ER_IB_MSG_187, 350
ER_IB_MSG_188, 351
ER_IB_MSG_189, 351
ER_IB_MSG_19, 335
ER_IB_MSG_190, 351
ER_IB_MSG_191, 351
ER_IB_MSG_192, 351
ER_IB_MSG_193, 351
ER_IB_MSG_194, 351
ER_IB_MSG_195, 351
ER_IB_MSG_196, 351
ER_IB_MSG_197, 351
ER_IB_MSG_198, 351
ER_IB_MSG_199, 352
ER_IB_MSG_2, 333
ER_IB_MSG_20, 335
ER_IB_MSG_200, 352
ER_IB_MSG_201, 352
ER_IB_MSG_202, 352
ER_IB_MSG_203, 352
ER_IB_MSG_204, 352
ER_IB_MSG_205, 352
ER_IB_MSG_206, 352
ER_IB_MSG_207, 352
ER_IB_MSG_208, 352
ER_IB_MSG_209, 352
ER_IB_MSG_21, 335
ER_IB_MSG_210, 353
ER_IB_MSG_211, 353
ER_IB_MSG_212, 353
ER_IB_MSG_213, 353
ER_IB_MSG_214, 353
ER_IB_MSG_215, 353
ER_IB_MSG_216, 353
ER_IB_MSG_217, 353
ER_IB_MSG_218, 353
ER_IB_MSG_219, 353
ER_IB_MSG_22, 335
ER_IB_MSG_220, 353

ER_IB_MSG_221, 354
ER_IB_MSG_222, 354
ER_IB_MSG_223, 354
ER_IB_MSG_224, 354
ER_IB_MSG_225, 354
ER_IB_MSG_226, 354
ER_IB_MSG_227, 354
ER_IB_MSG_228, 354
ER_IB_MSG_229, 354
ER_IB_MSG_23, 335
ER_IB_MSG_230, 354
ER_IB_MSG_231, 354
ER_IB_MSG_232, 355
ER_IB_MSG_233, 355
ER_IB_MSG_234, 355
ER_IB_MSG_235, 355
ER_IB_MSG_236, 355
ER_IB_MSG_237, 355
ER_IB_MSG_238, 355
ER_IB_MSG_239, 355
ER_IB_MSG_24, 335
ER_IB_MSG_240, 355
ER_IB_MSG_241, 355
ER_IB_MSG_242, 355
ER_IB_MSG_243, 356
ER_IB_MSG_244, 356
ER_IB_MSG_245, 356
ER_IB_MSG_246, 356
ER_IB_MSG_247, 356
ER_IB_MSG_248, 356
ER_IB_MSG_249, 356
ER_IB_MSG_25, 335
ER_IB_MSG_250, 356
ER_IB_MSG_251, 356
ER_IB_MSG_252, 356
ER_IB_MSG_253, 356
ER_IB_MSG_254, 357
ER_IB_MSG_255, 357
ER_IB_MSG_256, 357
ER_IB_MSG_257, 357
ER_IB_MSG_258, 357
ER_IB_MSG_259, 357
ER_IB_MSG_26, 335
ER_IB_MSG_260, 357
ER_IB_MSG_261, 357
ER_IB_MSG_262, 357
ER_IB_MSG_263, 357
ER_IB_MSG_264, 357
ER_IB_MSG_265, 358
ER_IB_MSG_266, 358
ER_IB_MSG_267, 358
ER_IB_MSG_268, 358
ER_IB_MSG_269, 358
ER_IB_MSG_27, 335
ER_IB_MSG_270, 358
ER_IB_MSG_271, 358
ER_IB_MSG_272, 358
ER_IB_MSG_273, 358
ER_IB_MSG_274, 358
ER_IB_MSG_275, 358
ER_IB_MSG_276, 359
ER_IB_MSG_277, 359
ER_IB_MSG_278, 359
ER_IB_MSG_279, 359
ER_IB_MSG_28, 335
ER_IB_MSG_280, 359
ER_IB_MSG_281, 359
ER_IB_MSG_282, 359
ER_IB_MSG_283, 359
ER_IB_MSG_284, 359
ER_IB_MSG_285, 359
ER_IB_MSG_286, 360
ER_IB_MSG_287, 360
ER_IB_MSG_288, 360
ER_IB_MSG_289, 360
ER_IB_MSG_29, 335
ER_IB_MSG_290, 360
ER_IB_MSG_291, 360
ER_IB_MSG_292, 360
ER_IB_MSG_293, 360
ER_IB_MSG_294, 360
ER_IB_MSG_295, 360
ER_IB_MSG_296, 361
ER_IB_MSG_297, 361
ER_IB_MSG_298, 361
ER_IB_MSG_299, 361
ER_IB_MSG_3, 333
ER_IB_MSG_30, 336
ER_IB_MSG_300, 361
ER_IB_MSG_301, 361
ER_IB_MSG_302, 361
ER_IB_MSG_303, 362
ER_IB_MSG_304, 362
ER_IB_MSG_305, 362
ER_IB_MSG_306, 362
ER_IB_MSG_307, 362
ER_IB_MSG_308, 362
ER_IB_MSG_309, 362
ER_IB_MSG_31, 336
ER_IB_MSG_310, 362
ER_IB_MSG_311, 362
ER_IB_MSG_312, 362
ER_IB_MSG_313, 363
ER_IB_MSG_314, 363
ER_IB_MSG_315, 363
ER_IB_MSG_316, 363
ER_IB_MSG_317, 363
ER_IB_MSG_318, 363
ER_IB_MSG_319, 363
ER_IB_MSG_32, 336
ER_IB_MSG_320, 363
ER_IB_MSG_321, 363
ER_IB_MSG_322, 363
ER_IB_MSG_323, 363
ER_IB_MSG_324, 364
ER_IB_MSG_325, 364

ER_IB_MSG_326, 364
ER_IB_MSG_327, 364
ER_IB_MSG_328, 364
ER_IB_MSG_329, 364
ER_IB_MSG_33, 336
ER_IB_MSG_330, 364
ER_IB_MSG_331, 364
ER_IB_MSG_332, 364
ER_IB_MSG_333, 364
ER_IB_MSG_334, 364
ER_IB_MSG_335, 365
ER_IB_MSG_336, 365
ER_IB_MSG_337, 365
ER_IB_MSG_338, 365
ER_IB_MSG_339, 365
ER_IB_MSG_34, 336
ER_IB_MSG_340, 365
ER_IB_MSG_341, 365
ER_IB_MSG_342, 365
ER_IB_MSG_343, 365
ER_IB_MSG_344, 365
ER_IB_MSG_345, 365
ER_IB_MSG_346, 366
ER_IB_MSG_347, 366
ER_IB_MSG_348, 366
ER_IB_MSG_349, 366
ER_IB_MSG_35, 336
ER_IB_MSG_350, 366
ER_IB_MSG_351, 366
ER_IB_MSG_352, 366
ER_IB_MSG_353, 366
ER_IB_MSG_354, 366
ER_IB_MSG_355, 367
ER_IB_MSG_356, 367
ER_IB_MSG_357, 367
ER_IB_MSG_358, 367
ER_IB_MSG_359, 367
ER_IB_MSG_36, 336
ER_IB_MSG_360, 367
ER_IB_MSG_361, 367
ER_IB_MSG_362, 367
ER_IB_MSG_363, 367
ER_IB_MSG_364, 367
ER_IB_MSG_365, 367
ER_IB_MSG_366, 368
ER_IB_MSG_367, 368
ER_IB_MSG_368, 368
ER_IB_MSG_369, 368
ER_IB_MSG_37, 336
ER_IB_MSG_370, 368
ER_IB_MSG_371, 368
ER_IB_MSG_372, 368
ER_IB_MSG_373, 368
ER_IB_MSG_374, 368
ER_IB_MSG_375, 368
ER_IB_MSG_376, 369
ER_IB_MSG_377, 369
ER_IB_MSG_378, 369
ER_IB_MSG_379, 369
ER_IB_MSG_38, 336
ER_IB_MSG_380, 369
ER_IB_MSG_381, 369
ER_IB_MSG_382, 369
ER_IB_MSG_383, 369
ER_IB_MSG_384, 369
ER_IB_MSG_385, 369
ER_IB_MSG_386, 369
ER_IB_MSG_387, 370
ER_IB_MSG_388, 370
ER_IB_MSG_389, 370
ER_IB_MSG_39, 336
ER_IB_MSG_390, 370
ER_IB_MSG_391, 370
ER_IB_MSG_392, 370
ER_IB_MSG_393, 370
ER_IB_MSG_394, 370
ER_IB_MSG_395, 371
ER_IB_MSG_396, 371
ER_IB_MSG_397, 371
ER_IB_MSG_398, 371
ER_IB_MSG_399, 371
ER_IB_MSG_4, 333
ER_IB_MSG_40, 336
ER_IB_MSG_400, 371
ER_IB_MSG_401, 371
ER_IB_MSG_402, 371
ER_IB_MSG_403, 371
ER_IB_MSG_404, 371
ER_IB_MSG_405, 371
ER_IB_MSG_406, 372
ER_IB_MSG_407, 372
ER_IB_MSG_408, 372
ER_IB_MSG_409, 372
ER_IB_MSG_41, 337
ER_IB_MSG_410, 372
ER_IB_MSG_411, 372
ER_IB_MSG_412, 372
ER_IB_MSG_413, 372
ER_IB_MSG_414, 372
ER_IB_MSG_415, 372
ER_IB_MSG_416, 372
ER_IB_MSG_417, 373
ER_IB_MSG_418, 373
ER_IB_MSG_419, 373
ER_IB_MSG_42, 337
ER_IB_MSG_420, 373
ER_IB_MSG_421, 373
ER_IB_MSG_422, 373
ER_IB_MSG_423, 373
ER_IB_MSG_424, 373
ER_IB_MSG_425, 373
ER_IB_MSG_426, 373
ER_IB_MSG_427, 373
ER_IB_MSG_428, 374
ER_IB_MSG_429, 374
ER_IB_MSG_43, 337

ER_IB_MSG_430, 374
ER_IB_MSG_431, 374
ER_IB_MSG_432, 374
ER_IB_MSG_433, 374
ER_IB_MSG_434, 374
ER_IB_MSG_435, 374
ER_IB_MSG_436, 374
ER_IB_MSG_437, 374
ER_IB_MSG_438, 374
ER_IB_MSG_439, 375
ER_IB_MSG_44, 337
ER_IB_MSG_440, 375
ER_IB_MSG_441, 375
ER_IB_MSG_442, 375
ER_IB_MSG_443, 375
ER_IB_MSG_444, 375
ER_IB_MSG_445, 375
ER_IB_MSG_446, 375
ER_IB_MSG_447, 375
ER_IB_MSG_448, 375
ER_IB_MSG_449, 375
ER_IB_MSG_45, 337
ER_IB_MSG_450, 376
ER_IB_MSG_451, 376
ER_IB_MSG_452, 376
ER_IB_MSG_453, 376
ER_IB_MSG_454, 376
ER_IB_MSG_455, 376
ER_IB_MSG_456, 376
ER_IB_MSG_457, 376
ER_IB_MSG_458, 376
ER_IB_MSG_459, 376
ER_IB_MSG_46, 337
ER_IB_MSG_460, 376
ER_IB_MSG_461, 377
ER_IB_MSG_462, 377
ER_IB_MSG_463, 377
ER_IB_MSG_464, 377
ER_IB_MSG_465, 377
ER_IB_MSG_466, 377
ER_IB_MSG_467, 377
ER_IB_MSG_468, 377
ER_IB_MSG_469, 377
ER_IB_MSG_47, 337
ER_IB_MSG_470, 377
ER_IB_MSG_471, 377
ER_IB_MSG_472, 378
ER_IB_MSG_473, 378
ER_IB_MSG_474, 378
ER_IB_MSG_475, 378
ER_IB_MSG_476, 378
ER_IB_MSG_477, 378
ER_IB_MSG_478, 378
ER_IB_MSG_479, 378
ER_IB_MSG_48, 337
ER_IB_MSG_480, 378
ER_IB_MSG_481, 378
ER_IB_MSG_482, 378
ER_IB_MSG_483, 379
ER_IB_MSG_484, 379
ER_IB_MSG_485, 379
ER_IB_MSG_486, 379
ER_IB_MSG_487, 379
ER_IB_MSG_488, 379
ER_IB_MSG_489, 379
ER_IB_MSG_49, 337
ER_IB_MSG_490, 379
ER_IB_MSG_491, 379
ER_IB_MSG_492, 379
ER_IB_MSG_493, 379
ER_IB_MSG_494, 380
ER_IB_MSG_495, 380
ER_IB_MSG_496, 380
ER_IB_MSG_497, 380
ER_IB_MSG_498, 380
ER_IB_MSG_499, 380
ER_IB_MSG_5, 333
ER_IB_MSG_50, 337
ER_IB_MSG_500, 380
ER_IB_MSG_501, 380
ER_IB_MSG_502, 380
ER_IB_MSG_503, 380
ER_IB_MSG_504, 380
ER_IB_MSG_505, 381
ER_IB_MSG_506, 381
ER_IB_MSG_507, 381
ER_IB_MSG_508, 381
ER_IB_MSG_509, 381
ER_IB_MSG_51, 337
ER_IB_MSG_510, 381
ER_IB_MSG_511, 381
ER_IB_MSG_512, 381
ER_IB_MSG_513, 381
ER_IB_MSG_514, 381
ER_IB_MSG_515, 381
ER_IB_MSG_516, 382
ER_IB_MSG_517, 382
ER_IB_MSG_518, 382
ER_IB_MSG_519, 382
ER_IB_MSG_52, 338
ER_IB_MSG_520, 382
ER_IB_MSG_521, 382
ER_IB_MSG_522, 382
ER_IB_MSG_523, 382
ER_IB_MSG_524, 382
ER_IB_MSG_525, 382
ER_IB_MSG_526, 382
ER_IB_MSG_527, 383
ER_IB_MSG_528, 383
ER_IB_MSG_529, 383
ER_IB_MSG_53, 338
ER_IB_MSG_530, 383
ER_IB_MSG_531, 383
ER_IB_MSG_532, 383
ER_IB_MSG_533, 383
ER_IB_MSG_534, 383

ER_IB_MSG_535, 383
ER_IB_MSG_536, 383
ER_IB_MSG_537, 383
ER_IB_MSG_538, 384
ER_IB_MSG_539, 384
ER_IB_MSG_54, 338
ER_IB_MSG_540, 384
ER_IB_MSG_541, 384
ER_IB_MSG_542, 384
ER_IB_MSG_543, 384
ER_IB_MSG_544, 384
ER_IB_MSG_545, 384
ER_IB_MSG_546, 384
ER_IB_MSG_547, 384
ER_IB_MSG_548, 384
ER_IB_MSG_549, 385
ER_IB_MSG_55, 338
ER_IB_MSG_550, 385
ER_IB_MSG_551, 385
ER_IB_MSG_552, 385
ER_IB_MSG_553, 385
ER_IB_MSG_554, 385
ER_IB_MSG_555, 385
ER_IB_MSG_556, 385
ER_IB_MSG_557, 385
ER_IB_MSG_558, 385
ER_IB_MSG_559, 385
ER_IB_MSG_56, 338
ER_IB_MSG_560, 386
ER_IB_MSG_561, 386
ER_IB_MSG_562, 386
ER_IB_MSG_563, 386
ER_IB_MSG_564, 386
ER_IB_MSG_565, 386
ER_IB_MSG_566, 386
ER_IB_MSG_567, 386
ER_IB_MSG_568, 386
ER_IB_MSG_569, 387
ER_IB_MSG_57, 338
ER_IB_MSG_570, 387
ER_IB_MSG_571, 387
ER_IB_MSG_572, 387
ER_IB_MSG_573, 387
ER_IB_MSG_574, 387
ER_IB_MSG_575, 387
ER_IB_MSG_576, 387
ER_IB_MSG_577, 387
ER_IB_MSG_578, 387
ER_IB_MSG_579, 387
ER_IB_MSG_57_STAT_SPACE_DELETE_FAIL,
503
ER_IB_MSG_57_UNDO_SPACE_DELETE_FAIL,
499
ER_IB_MSG_58, 338
ER_IB_MSG_580, 388
ER_IB_MSG_581, 388
ER_IB_MSG_582, 388
ER_IB_MSG_583, 388
ER_IB_MSG_584, 388
ER_IB_MSG_585, 388
ER_IB_MSG_586, 388
ER_IB_MSG_587, 388
ER_IB_MSG_588, 388
ER_IB_MSG_589, 388
ER_IB_MSG_59, 338
ER_IB_MSG_590, 388
ER_IB_MSG_591, 389
ER_IB_MSG_592, 389
ER_IB_MSG_593, 389
ER_IB_MSG_594, 389
ER_IB_MSG_595, 389
ER_IB_MSG_596, 389
ER_IB_MSG_597, 389
ER_IB_MSG_598, 389
ER_IB_MSG_599, 389
ER_IB_MSG_6, 333
ER_IB_MSG_60, 338
ER_IB_MSG_600, 389
ER_IB_MSG_601, 389
ER_IB_MSG_602, 390
ER_IB_MSG_603, 390
ER_IB_MSG_604, 390
ER_IB_MSG_605, 390
ER_IB_MSG_606, 390
ER_IB_MSG_607, 390
ER_IB_MSG_608, 390
ER_IB_MSG_609, 390
ER_IB_MSG_61, 338
ER_IB_MSG_610, 390
ER_IB_MSG_611, 390
ER_IB_MSG_612, 390
ER_IB_MSG_613, 391
ER_IB_MSG_614, 391
ER_IB_MSG_615, 391
ER_IB_MSG_616, 391
ER_IB_MSG_617, 391
ER_IB_MSG_618, 391
ER_IB_MSG_619, 391
ER_IB_MSG_62, 338
ER_IB_MSG_620, 391
ER_IB_MSG_621, 391
ER_IB_MSG_622, 391
ER_IB_MSG_623, 391
ER_IB_MSG_624, 392
ER_IB_MSG_625, 392
ER_IB_MSG_626, 392
ER_IB_MSG_627, 392
ER_IB_MSG_628, 392
ER_IB_MSG_629, 392
ER_IB_MSG_63, 339
ER_IB_MSG_630, 392
ER_IB_MSG_631, 392
ER_IB_MSG_632, 392
ER_IB_MSG_633, 392
ER_IB_MSG_634, 392
ER_IB_MSG_635, 393

ER_IB_MSG_636, 393
ER_IB_MSG_637, 393
ER_IB_MSG_638, 393
ER_IB_MSG_639, 393
ER_IB_MSG_64, 393
ER_IB_MSG_640, 393
ER_IB_MSG_641, 393
ER_IB_MSG_642, 393
ER_IB_MSG_643, 393
ER_IB_MSG_644, 393
ER_IB_MSG_645, 393
ER_IB_MSG_646, 394
ER_IB_MSG_647, 394
ER_IB_MSG_648, 394
ER_IB_MSG_649, 394
ER_IB_MSG_65, 393
ER_IB_MSG_650, 394
ER_IB_MSG_651, 394
ER_IB_MSG_652, 394
ER_IB_MSG_653, 394
ER_IB_MSG_654, 394
ER_IB_MSG_655, 395
ER_IB_MSG_656, 395
ER_IB_MSG_657, 395
ER_IB_MSG_658, 395
ER_IB_MSG_659, 395
ER_IB_MSG_66, 339
ER_IB_MSG_660, 395
ER_IB_MSG_661, 395
ER_IB_MSG_662, 395
ER_IB_MSG_663, 395
ER_IB_MSG_664, 395
ER_IB_MSG_665, 395
ER_IB_MSG_666, 396
ER_IB_MSG_667, 396
ER_IB_MSG_668, 396
ER_IB_MSG_669, 396
ER_IB_MSG_67, 339
ER_IB_MSG_670, 396
ER_IB_MSG_671, 396
ER_IB_MSG_672, 396
ER_IB_MSG_673, 396
ER_IB_MSG_674, 396
ER_IB_MSG_675, 396
ER_IB_MSG_676, 397
ER_IB_MSG_677, 397
ER_IB_MSG_678, 397
ER_IB_MSG_679, 397
ER_IB_MSG_68, 339
ER_IB_MSG_680, 397
ER_IB_MSG_681, 397
ER_IB_MSG_682, 397
ER_IB_MSG_683, 397
ER_IB_MSG_684, 397
ER_IB_MSG_685, 397
ER_IB_MSG_686, 397
ER_IB_MSG_687, 398
ER_IB_MSG_688, 398
ER_IB_MSG_689, 398
ER_IB_MSG_69, 339
ER_IB_MSG_690, 398
ER_IB_MSG_691, 398
ER_IB_MSG_692, 398
ER_IB_MSG_693, 398
ER_IB_MSG_694, 398
ER_IB_MSG_695, 398
ER_IB_MSG_696, 398
ER_IB_MSG_697, 399
ER_IB_MSG_698, 399
ER_IB_MSG_699, 399
ER_IB_MSG_7, 333
ER_IB_MSG_70, 339
ER_IB_MSG_700, 399
ER_IB_MSG_701, 399
ER_IB_MSG_702, 399
ER_IB_MSG_703, 399
ER_IB_MSG_704, 399
ER_IB_MSG_705, 399
ER_IB_MSG_706, 399
ER_IB_MSG_707, 400
ER_IB_MSG_708, 400
ER_IB_MSG_709, 400
ER_IB_MSG_71, 339
ER_IB_MSG_710, 400
ER_IB_MSG_711, 400
ER_IB_MSG_712, 400
ER_IB_MSG_713, 400
ER_IB_MSG_714, 400
ER_IB_MSG_715, 400
ER_IB_MSG_716, 400
ER_IB_MSG_717, 400
ER_IB_MSG_718, 401
ER_IB_MSG_719, 401
ER_IB_MSG_72, 339
ER_IB_MSG_720, 401
ER_IB_MSG_721, 401
ER_IB_MSG_722, 401
ER_IB_MSG_723, 401
ER_IB_MSG_724, 401
ER_IB_MSG_725, 401
ER_IB_MSG_726, 401
ER_IB_MSG_727, 402
ER_IB_MSG_728, 402
ER_IB_MSG_729, 402
ER_IB_MSG_73, 339
ER_IB_MSG_730, 402
ER_IB_MSG_731, 402
ER_IB_MSG_732, 402
ER_IB_MSG_733, 402
ER_IB_MSG_734, 402
ER_IB_MSG_735, 402
ER_IB_MSG_736, 402
ER_IB_MSG_737, 403
ER_IB_MSG_738, 403
ER_IB_MSG_739, 403
ER_IB_MSG_74, 340

ER_IB_MSG_740, 403
ER_IB_MSG_741, 403
ER_IB_MSG_742, 403
ER_IB_MSG_743, 403
ER_IB_MSG_744, 403
ER_IB_MSG_745, 403
ER_IB_MSG_746, 403
ER_IB_MSG_747, 404
ER_IB_MSG_748, 404
ER_IB_MSG_749, 404
ER_IB_MSG_75, 340
ER_IB_MSG_750, 404
ER_IB_MSG_751, 404
ER_IB_MSG_752, 404
ER_IB_MSG_753, 404
ER_IB_MSG_754, 404
ER_IB_MSG_755, 404
ER_IB_MSG_756, 404
ER_IB_MSG_757, 404
ER_IB_MSG_758, 405
ER_IB_MSG_759, 405
ER_IB_MSG_76, 340
ER_IB_MSG_760, 405
ER_IB_MSG_761, 405
ER_IB_MSG_762, 405
ER_IB_MSG_763, 405
ER_IB_MSG_764, 405
ER_IB_MSG_765, 405
ER_IB_MSG_766, 405
ER_IB_MSG_767, 405
ER_IB_MSG_768, 405
ER_IB_MSG_769, 406
ER_IB_MSG_77, 340
ER_IB_MSG_770, 406
ER_IB_MSG_771, 406
ER_IB_MSG_772, 406
ER_IB_MSG_773, 406
ER_IB_MSG_774, 406
ER_IB_MSG_775, 406
ER_IB_MSG_776, 406
ER_IB_MSG_777, 406
ER_IB_MSG_778, 406
ER_IB_MSG_779, 406
ER_IB_MSG_78, 340
ER_IB_MSG_780, 407
ER_IB_MSG_781, 407
ER_IB_MSG_782, 407
ER_IB_MSG_783, 407
ER_IB_MSG_784, 407
ER_IB_MSG_785, 407
ER_IB_MSG_786, 407
ER_IB_MSG_787, 407
ER_IB_MSG_788, 407
ER_IB_MSG_789, 407
ER_IB_MSG_79, 340
ER_IB_MSG_790, 407
ER_IB_MSG_791, 408
ER_IB_MSG_792, 408
ER_IB_MSG_793, 408
ER_IB_MSG_794, 408
ER_IB_MSG_795, 408
ER_IB_MSG_796, 408
ER_IB_MSG_797, 408
ER_IB_MSG_798, 408
ER_IB_MSG_799, 408
ER_IB_MSG_8, 334
ER_IB_MSG_80, 340
ER_IB_MSG_800, 408
ER_IB_MSG_801, 408
ER_IB_MSG_802, 409
ER_IB_MSG_803, 409
ER_IB_MSG_804, 409
ER_IB_MSG_805, 409
ER_IB_MSG_806, 409
ER_IB_MSG_807, 409
ER_IB_MSG_808, 409
ER_IB_MSG_809, 409
ER_IB_MSG_81, 340
ER_IB_MSG_810, 409
ER_IB_MSG_811, 409
ER_IB_MSG_812, 409
ER_IB_MSG_813, 410
ER_IB_MSG_814, 410
ER_IB_MSG_815, 410
ER_IB_MSG_816, 410
ER_IB_MSG_817, 410
ER_IB_MSG_818, 410
ER_IB_MSG_819, 410
ER_IB_MSG_82, 340
ER_IB_MSG_820, 410
ER_IB_MSG_821, 410
ER_IB_MSG_822, 410
ER_IB_MSG_823, 410
ER_IB_MSG_824, 411
ER_IB_MSG_825, 411
ER_IB_MSG_826, 411
ER_IB_MSG_827, 411
ER_IB_MSG_828, 411
ER_IB_MSG_829, 411
ER_IB_MSG_83, 340
ER_IB_MSG_830, 411
ER_IB_MSG_831, 411
ER_IB_MSG_832, 411
ER_IB_MSG_833, 411
ER_IB_MSG_834, 411
ER_IB_MSG_835, 412
ER_IB_MSG_836, 412
ER_IB_MSG_837, 412
ER_IB_MSG_838, 412
ER_IB_MSG_839, 412
ER_IB_MSG_84, 340
ER_IB_MSG_840, 412
ER_IB_MSG_841, 412
ER_IB_MSG_842, 412
ER_IB_MSG_843, 412
ER_IB_MSG_844, 412

ER_IB_MSG_845, 412
ER_IB_MSG_846, 413
ER_IB_MSG_847, 413
ER_IB_MSG_848, 413
ER_IB_MSG_849, 413
ER_IB_MSG_85, 341
ER_IB_MSG_850, 413
ER_IB_MSG_851, 413
ER_IB_MSG_852, 413
ER_IB_MSG_853, 413
ER_IB_MSG_854, 413
ER_IB_MSG_855, 413
ER_IB_MSG_856, 413
ER_IB_MSG_857, 414
ER_IB_MSG_858, 414
ER_IB_MSG_859, 414
ER_IB_MSG_86, 341
ER_IB_MSG_860, 414
ER_IB_MSG_861, 414
ER_IB_MSG_862, 414
ER_IB_MSG_863, 414
ER_IB_MSG_864, 414
ER_IB_MSG_865, 414
ER_IB_MSG_866, 414
ER_IB_MSG_867, 414
ER_IB_MSG_868, 415
ER_IB_MSG_869, 415
ER_IB_MSG_87, 341
ER_IB_MSG_870, 415
ER_IB_MSG_871, 415
ER_IB_MSG_872, 415
ER_IB_MSG_873, 415
ER_IB_MSG_874, 415
ER_IB_MSG_875, 415
ER_IB_MSG_876, 415
ER_IB_MSG_877, 415
ER_IB_MSG_878, 415
ER_IB_MSG_879, 416
ER_IB_MSG_88, 341
ER_IB_MSG_880, 416
ER_IB_MSG_881, 416
ER_IB_MSG_882, 416
ER_IB_MSG_883, 416
ER_IB_MSG_884, 416
ER_IB_MSG_885, 416
ER_IB_MSG_886, 416
ER_IB_MSG_887, 416
ER_IB_MSG_888, 416
ER_IB_MSG_889, 416
ER_IB_MSG_89, 341
ER_IB_MSG_890, 417
ER_IB_MSG_891, 417
ER_IB_MSG_892, 417
ER_IB_MSG_893, 417
ER_IB_MSG_894, 417
ER_IB_MSG_895, 417
ER_IB_MSG_896, 417
ER_IB_MSG_897, 417
ER_IB_MSG_898, 417
ER_IB_MSG_899, 417
ER_IB_MSG_9, 334
ER_IB_MSG_90, 341
ER_IB_MSG_900, 417
ER_IB_MSG_901, 418
ER_IB_MSG_902, 418
ER_IB_MSG_903, 418
ER_IB_MSG_904, 418
ER_IB_MSG_905, 418
ER_IB_MSG_906, 418
ER_IB_MSG_907, 418
ER_IB_MSG_908, 418
ER_IB_MSG_909, 418
ER_IB_MSG_91, 341
ER_IB_MSG_910, 418
ER_IB_MSG_911, 418
ER_IB_MSG_912, 419
ER_IB_MSG_913, 419
ER_IB_MSG_914, 419
ER_IB_MSG_915, 419
ER_IB_MSG_916, 419
ER_IB_MSG_917, 419
ER_IB_MSG_918, 419
ER_IB_MSG_919, 419
ER_IB_MSG_92, 341
ER_IB_MSG_920, 419
ER_IB_MSG_921, 419
ER_IB_MSG_922, 419
ER_IB_MSG_923, 420
ER_IB_MSG_924, 420
ER_IB_MSG_925, 420
ER_IB_MSG_926, 420
ER_IB_MSG_927, 420
ER_IB_MSG_928, 420
ER_IB_MSG_929, 420
ER_IB_MSG_93, 341
ER_IB_MSG_930, 420
ER_IB_MSG_931, 420
ER_IB_MSG_932, 420
ER_IB_MSG_933, 420
ER_IB_MSG_934, 421
ER_IB_MSG_935, 421
ER_IB_MSG_936, 421
ER_IB_MSG_937, 421
ER_IB_MSG_938, 421
ER_IB_MSG_939, 421
ER_IB_MSG_94, 341
ER_IB_MSG_940, 421
ER_IB_MSG_941, 421
ER_IB_MSG_942, 421
ER_IB_MSG_943, 421
ER_IB_MSG_944, 421
ER_IB_MSG_945, 422
ER_IB_MSG_946, 422
ER_IB_MSG_947, 422
ER_IB_MSG_948, 422
ER_IB_MSG_949, 422

ER_IB_MSG_95, 341	ER_IB_MSG_CANNOT_FIND_DD_UNDO_SPACE, 505
ER_IB_MSG_950, 422	ER_IB_MSG_CANNOT_OPEN_57_UNDO, 434
ER_IB_MSG_951, 422	ER_IB_MSG_CLOCK_GETTIME_FAILED, 487
ER_IB_MSG_952, 422	ER_IB_MSG_CLOCK_MONOTONIC_UNSUPPORTED, 487
ER_IB_MSG_953, 422	ER_IB_MSG_CREATED_UNDO_SPACE, 513
ER_IB_MSG_954, 422	ER_IB_MSG_CREATE_LOG_FILE, 503
ER_IB_MSG_955, 422	ER_IB_MSG_DBLWR_1285, 499
ER_IB_MSG_956, 423	ER_IB_MSG_DBLWR_1286, 499
ER_IB_MSG_957, 423	ER_IB_MSG_DBLWR_1287, 499
ER_IB_MSG_958, 423	ER_IB_MSG_DBLWR_1288, 499
ER_IB_MSG_959, 423	ER_IB_MSG_DBLWR_1290, 499
ER_IB_MSG_96, 342	ER_IB_MSG_DBLWR_1291, 499
ER_IB_MSG_960, 423	ER_IB_MSG_DBLWR_1292, 500
ER_IB_MSG_961, 423	ER_IB_MSG_DBLWR_1293, 500
ER_IB_MSG_962, 423	ER_IB_MSG_DBLWR_1294, 500
ER_IB_MSG_963, 423	ER_IB_MSG_DBLWR_1295, 500
ER_IB_MSG_964, 423	ER_IB_MSG_DBLWR_1296, 500
ER_IB_MSG_965, 423	ER_IB_MSG_DBLWR_1297, 500
ER_IB_MSG_966, 423	ER_IB_MSG_DBLWR_1298, 500
ER_IB_MSG_967, 424	ER_IB_MSG_DBLWR_1300, 500
ER_IB_MSG_968, 424	ER_IB_MSG_DBLWR_1301, 500
ER_IB_MSG_969, 424	ER_IB_MSG_DBLWR_1304, 500
ER_IB_MSG_97, 342	ER_IB_MSG_DBLWR_1305, 500
ER_IB_MSG_970, 424	ER_IB_MSG_DBLWR_1306, 501
ER_IB_MSG_971, 424	ER_IB_MSG_DBLWR_1307, 501
ER_IB_MSG_972, 424	ER_IB_MSG_DBLWR_1308, 501
ER_IB_MSG_973, 424	ER_IB_MSG_DBLWR_1309, 501
ER_IB_MSG_974, 424	ER_IB_MSG_DBLWR_1310, 501
ER_IB_MSG_975, 424	ER_IB_MSG_DBLWR_1311, 501
ER_IB_MSG_976, 424	ER_IB_MSG_DBLWR_1312, 501
ER_IB_MSG_977, 424	ER_IB_MSG_DBLWR_1313, 501
ER_IB_MSG_978, 425	ER_IB_MSG_DBLWR_1314, 501
ER_IB_MSG_979, 425	ER_IB_MSG_DBLWR_1315, 501
ER_IB_MSG_98, 342	ER_IB_MSG_DBLWR_1316, 501
ER_IB_MSG_980, 425	ER_IB_MSG_DBLWR_1317, 502
ER_IB_MSG_981, 425	ER_IB_MSG_DBLWR_1318, 502
ER_IB_MSG_982, 425	ER_IB_MSG_DBLWR_1319, 502
ER_IB_MSG_983, 425	ER_IB_MSG_DBLWR_1320, 502
ER_IB_MSG_984, 425	ER_IB_MSG_DBLWR_1321, 502
ER_IB_MSG_985, 425	ER_IB_MSG_DBLWR_1322, 502
ER_IB_MSG_986, 425	ER_IB_MSG_DBLWR_1323, 502
ER_IB_MSG_987, 425	ER_IB_MSG_DBLWR_1324, 502
ER_IB_MSG_988, 425	ER_IB_MSG_DBLWR_1325, 502
ER_IB_MSG_989, 426	ER_IB_MSG_DBLWR_1326, 502
ER_IB_MSG_99, 342	ER_IB_MSG_DBLWR_1327, 502
ER_IB_MSG_990, 426	ER_IB_MSG_DDL_LOG_DELETE_BY_ID_OK, 394
ER_IB_MSG_991, 426	ER_IB_MSG_DDL_LOG_DELETE_BY_ID_TMCT, 485
ER_IB_MSG_992, 426	ER_IB_MSG_DDL_LOG_FAIL_POST_DDL, 485
ER_IB_MSG_993, 426	ER_IB_MSG_DEPRECATED_INNODB_UNDO_TABLESPACES, 471
ER_IB_MSG_994, 426	ER_IB_MSG_DICT_PARTITION_NOT_FOUND, 498
ER_IB_MSG_995, 426	ER_IB_MSG_DIR_DOES_NOT_EXIST, 471
ER_IB_MSG_996, 426	ER_IB_MSG_DOWNGRADE_PARTITION_FILE, 496
ER_IB_MSG_997, 426	
ER_IB_MSG_998, 426	
ER_IB_MSG_999, 426	
ER_IB_MSG_BAD_DBLWR_FILE_NAME, 499	
ER_IB_MSG_BTREE_LEVEL_LIMIT_EXCEEDED, 490	

ER_IB_MSG_DROPPED_UNDO_SPACE, 513
ER_IB_MSG_ERROR_OPENING_NEW_UNDO_SPACE, 469
ER_IB_MSG_FAILED_SDI_Z_BUF_ERROR, 469
ER_IB_MSG_FAILED_SDI_Z_MEM_ERROR, 470
ER_IB_MSG_FAILED_TO_ALLOCATE_WAIT, 469
ER_IB_MSG_FAILED_TO_FINISH_TRUNCATE, 471
ER_IB_MSG_FAIL_TO_SAVE_SPACE_STATE, 469
ER_IB_MSG_FIL_STATE_MOVED_CHANGED_NAME, 497
ER_IB_MSG_FIL_STATE_MOVED_CHANGED_PATH, 497
ER_IB_MSG_FIL_STATE_MOVED_CORRECTED, 497
ER_IB_MSG_FIL_STATE_MOVED_TOO_MANY, 497
ER_IB_MSG_FOUND_WRONG_UNDO_SPACE, 470
ER_IB_MSG_GENERAL_TABLESPACE_UNDER_DATA, 370
ER_IB_MSG_GTID_FLUSH_AT_SHUTDOWN, 503
ER_IB_MSG_IGNORE_SCAN_PATH, 368
ER_IB_MSG_IMPLICIT_TABLESPACE_IN_DATADIR, 370
ER_IB_MSG_INCORRECT_SIZE, 513
ER_IB_MSG_INJECT_CRASH, 512
ER_IB_MSG_INJECT_FAILURE, 512
ER_IB_MSG_INNODB_END_INITIALIZE, 503
ER_IB_MSG_INNODB_START_INITIALIZE, 503
ER_IB_MSG_INVALID_LOCATION_FOR_TABLE, 386
ER_IB_MSG_INVALID_LOCATION_FOR_TABLESPACE, 505
ER_IB_MSG_INVALID_LOCATION_WRONG_DB, 505
ER_IB_MSG_LOCK_FREE_HASH_USAGE_STATS, 471
ER_IB_MSG_MADV FAILED, 469
ER_IB_MSG_MADV_DONTDUMP_UNSUPPORTED, 469
ER_IB_MSG_MASTER_KEY_ROTATED, 513
ER_IB_MSG_MAX_UNDO_SPACES_REACHED, 469
ER_IB_MSG_NOT_END_WITH_IBU, 470
ER_IB_MSG_NO_ENCRYPT_PROGRESS_FOUND, 463
ER_IB_MSG_NUM_POOLS, 469
ER_IB_MSG_PAGE_ARCH_NO_RESET_POINTS, 503
ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER, 485
ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT, 485
ER_IB_MSG_RESUME_OP_FOR_SPACE, 463
ER_IB_MSG_SCANNING_TEMP_TABLESPACE_DIR, 508
ER_IB_MSG_SDI_Z_STREAM_ERROR, 470
ER_IB_MSG_SDI_Z_UNKNOWN_ERROR, 470
ER_IB_MSG_SKIP_HIDDEN_DIR, 495
ER_IB_MSG_STATS_SAMPLING_TOO_LARGE, 517
ER_IB_MSG_TOO_LONG_PATH, 486
ER_IB_MSG_TRX_RECOVERY_ROLLBACK_COMPLETED, 446
ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPL, 507
ER_IB_MSG_UNDO_ALTERED_ACTIVE, 511
ER_IB_MSG_UNDO_ALTERED_INACTIVE, 511
ER_IB_MSG_UNDO_INJECT_CRASH, 511
ER_IB_MSG_UNDO_INJECT_FAILURE, 512
ER_IB_MSG_UNDO_MARKED_ACTIVE, 511
ER_IB_MSG_UNDO_MARKED_EMPTY, 511
ER_IB_MSG_UNDO_MARKED_FOR_TRUNCATE, 443
ER_IB_MSG_UNDO_TRUNCATE_COMPLETE, 444
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_CLONE, 511
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_FAILURE, 444
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_LOG_CREA, 444
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_MDL, 511
ER_IB_MSG_UNDO_TRUNCATE_FAIL_TO_READ_LOG_F, 443
ER_IB_MSG_UNDO_TRUNCATE_START, 443
ER_IB_MSG_UNDO_TRUNCATE_TOO_OFTEN, 504
ER_IB_MSG_UNDO_TRUNC BEFORE UNDO LOGGING, 470
ER_IB_MSG_UNDO_TRUNC_BEFOR_DD_UPDATE, 470
ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE, 470
ER_IB_MSG_UNDO_TRUNC_BEFORE_RSEG, 470
ER_IB_MSG_UNEXPECTED_FILE_EXISTS, 361
ER_IB_MSG_UNPROTECTED_LOCATION_ALLOWED, 366
ER_IB_MSG_UPGRADE_PARTITION_FILE, 496
ER_IB_MSG_UPGRADE_PARTITION_FILE_IMPORT, 497
ER_IB_MSG_USING_UNDO_SPACE, 469
ER_IB_MSG_WAIT_FOR_ENCRYPT_THREAD, 463
ER_IB_MSG_WRONG_TABLESPACE_DIR, 471
ER_IB_RECV_FIRST_REC_GROUP_INVALID, 486
ER_IB_RELLOCK_LATCH_ORDER_VIOLATION, 508
ER_IB_TABLESPACE_PATH_VALIDATION_SKIPPED, 506
ER_IB_TMP_TABLESPACE_CANNOT_CREATE_DIRECTO, 508

ER_IB_UNABLE_TO_EXPAND_TEMPORARY_TABLESPACE	ER_INNODB_ACTIVE_INDEX_CHANGE_FAILED,
508	246
ER_IB_WARN_OPEN_PARTITION_FILE, 497	ER_INNODB_AUTOEXTEND_SIZE_OUT_OF_RANGE,
ER_IB_WRN_FAILED_TO_ACQUIRE_SERVICE,	129
520	ER_INNODB_CANNOT_BE_IGNORED, 93
ER_IB_WRN_FAST_SHUTDOWN_REDO_DISABLED,	ER_INNODB_CANNOT_CREATE_TABLE, 246
506	ER_INNODB_CANT_BUILD_INDEX_XLATION_TABLE_FOR,
ER_IB_WRN_OLD_GEOMETRY_TYPE, 520	228
ER_IB_WRN_PAGE_ARCH_FLUSH_DATA, 503	ER_INNODB_CANT_FIND_INDEX_IN_INNODB_DD,
ER_IB_WRN_REDO_DISABLED, 506	227
ER_IB_WRN_REDO_ENABLED, 506	ER_INNODB_CANT_OPEN_TABLE, 227
ER_IDENT_CAUSES_TOO_LONG_PATH, 57	ER_INNODB_CLOSING_CONNECTION_ROLLS_BACK,
ER_IDENT_CAUSES_TOO_LONG_PATH_IN_UPGRADE	227
492	ER_INNODB_CLUSTERED_INDEX_PRIVATE, 228
ER_ILLEGAL_GRANT_FOR_TABLE, 13	ER_INNODB_COMPRESSION_FAILURE, 129
ER_ILLEGAL_HA, 5	ER_INNODB_DIFF_IN_REF_LEN, 246
ER_ILLEGAL_HA_CREATE_OPTION, 32	ER_INNODB_DIRTY_WATER_MARK_NOT_LOW,
ER_ILLEGAL_PRIVILEGE_LEVEL, 85	227
ER_ILLEGAL_REFERENCE, 19	ER_INNODB_ERROR_LOGGER_FATAL_MSG,
ER_ILLEGAL_USER_VAR, 63	248
ER_ILLEGAL_VALUE_FOR_TYPE, 26	ER_INNODB_ERROR_LOGGER_MSG, 248
ER_IMPLICIT_COMPARISON_FOR_JSON, 124	ER_INNODB_FAILED_TO_FIND_IDX, 245
ER_IMPOSSIBLE_STRING_CONVERSION, 124	ER_INNODB_FAILED_TO_FIND_IDX_FROM_DICT_CACHE,
ER_IMP_INCOMPATIBLE_CFG_VERSION, 120	245
ER_IMP_INCOMPATIBLE_DD_VERSION, 84	ER_INNODB_FAILED_TO_FIND_IDX_WITH_KEY_NO,
ER_IMP_INCOMPATIBLE_MYSQLD_VERSION, 84	245
ER_IMP_INCOMPATIBLE_SDI_VERSION, 84	ER_INNODB_FILES_SAME, 227
ER_IMP_NO_FILES_MATCHED, 84	ER_INNODB_FORCED_RECOVERY, 58
ER_IMP_SCHEMA_DOES_NOT_EXIST, 84	ER_INNODB_FT_AUX_NOT_HEX_ID, 58
ER_IMP_TABLE_ALREADY_EXISTS, 84	ER_INNODB_FT_LIMIT, 52
ER_INCONSISTENT_ERROR, 455	ER_INNODB_FT_WRONG_DOCID_COLUMN, 52
ER_INCONSISTENT_PARTITION_INFO_ERROR,	ER_INNODB_FT_WRONG_DOCID_INDEX, 52
33	ER_INNODB_IDX_CNT_FEWER_THAN_DEFINED_IN_MYSQL,
ER_INCONSISTENT_TYPE_OF_FUNCTIONS_ERROR,	246
33	ER_INNODB_IDX_CNT_MORE_THAN_DEFINED_IN_MYSQL,
ER_INCORRECT_CURRENT_PASSWORD, 113	246
ER_INCORRECT_GLOBAL_LOCAL_VAR, 18	ER_INNODB_IDX_COLUMN_CNT_DIFF, 246
ER_INCORRECT_TYPE, 64	ER_INNODB_ILLEGAL_COLON_IN_POOL, 226
ER_INDEX_COLUMN_TOO_LONG, 46	ER_INNODB_IMPORT_ERROR, 54
ER_INDEX_CORRUPT, 46	ER_INNODB_INCOMPATIBLE_WITH_TABLESPACE,
ER_INDEX_TYPE_NOT_SUPPORTED_FOR_SPATIAL_INDEX,	227
96	ER_INNODB_INDEX_COLUMN_INFO_UNLIKE_MYSQLS,
ER_INIT_BOOTSTRAP_COMPLETE, 179	227
ER_INIT_CANT_OPEN_BOOTSTRAP_FILE, 179	ER_INNODB_INDEX_CORRUPT, 54
ER_INIT_CREATING_DD, 180	ER_INNODB_INTERNAL_INDEX, 246
ER_INIT_DATADIR_EXISTS_AND_NOT_WRITABLE_WONT_INITIALIZE,	227
180	ER_INNODB_INVALID_AUTOEXTEND_SIZE_VALUE,
	129
ER_INIT_DATADIR_EXISTS_AND_PATH_TOO_LONG_WONT_INITIALIZE,	ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY,
180	226
ER_INIT_DATADIR_EXISTS_WONT_INITIALIZE,	ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY_LOCATION,
179	472
ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE,	ER_INNODB_INVALID_LOG_GROUP_HOME_DIR,
179	226
ER_INIT_FAILED_TO_GENERATE_ROOT_PASSWORD	ER_INNODB_INVALID_MONITOR_COUNTER_NAME,
495	247
ER_INIT_GENERATING_TEMP_PASSWORD_FOR_ROOT,	ER_INNODB_INVALID_PAGE_SIZE, 227
179	ER_INNODB_IO_CAPACITY_EXCEEDS_MAX, 227
ER_INIT_ROOT_WITHOUT_PASSWORD, 179	ER_INNODB_IO_WRITE_ERROR_RETRYING, 514

ER_INNODB_IO_WRITE_FAILED, 514
ER_INNODB_MANDATORY, 140
ER_INNODB_MONITOR_DEFAULT_VALUE_NOT_DEFINED, 247
ER_INNODB_MONITOR_IS_ENABLED, 247
ER_INNODB_NO_FT_TEMP_TABLE, 52
ER_INNODB_ONLINE_LOG_TOO_BIG, 52
ER_INNODB_OUT_OF_RESOURCES, 498
ER_INNODB_PARTITION_TABLE_LOWERCASED, 228
ER_INNODB_PK_NOT_IN_MYSQL, 228
ER_INNODB_PK_ONLY_IN_MYSQL, 228
ER_INNODB_READ_ONLY, 58
ER_INNODB_REDO_ARCHIVING_ENABLED, 124
ER_INNODB_REDO_DISABLED, 123
ER_INNODB_REDO_LOG_ARCHIVE_ACTIVE, 109
ER_INNODB_REDO_LOG_ARCHIVE_DIRS_INVALID, 109
ER_INNODB_REDO_LOG_ARCHIVE_DIR_CLASH, 109
ER_INNODB_REDO_LOG_ARCHIVE_DIR_EMPTY, 109
ER_INNODB_REDO_LOG_ARCHIVE_DIR_PERMISSIONS, 109
ER_INNODB_REDO_LOG_ARCHIVE FAILED, 109
ER_INNODB_REDO_LOG_ARCHIVE_FILE_CREATE, 109
ER_INNODB_REDO_LOG_ARCHIVE_INACTIVE, 109
ER_INNODB_REDO_LOG_ARCHIVE_LABEL_NOT_FOUND, 109
ER_INNODB_REDO_LOG_ARCHIVE_NO SUCH_DIR, 109
ER_INNODB_REDO_LOG_ARCHIVE_SESSION, 110
ER_INNODB_REDO_LOG_ARCHIVE_START_SUBDIR, 108
ER_INNODB_REDO_LOG_ARCHIVE_START_TIMEOUT, 108
ER_INNODB_TRX_XLATION_TABLE_OOM, 227
ER_INNODB_UNABLE_TO_ACQUIRE_DD_OBJECT, 504
ER_INNODB_UNDO_LOG_FULL, 60
ER_INNODB_UNKNOWN_COLLATION, 226
ER_INNODB_UNREGISTERED_TRX_ACTIVE, 227
ER_INNODB_USE_MONITOR_GROUP_NAME, 246
ER_INSECURE_CHANGE_MASTER, 49
ER_INSECURE_PLAIN_TEXT, 49
ER_INSERT_INFO, 9
ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_DIRECT, 44
ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_INFORMATION_UPDATE, 44
ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_SQLERRORS, 45
ER_INSTALL_PLUGIN_CONFLICT_CLIENT, 131
ER_INSTALL_PLUGIN_CONFLICT_LOG, 525
ER_INTERNAL_ERROR, 53
ER_INVALID_ADMIN_ADDRESS, 474
ER_INVALID_ARGUMENT_FOR_LOGARITHM, 60
ER_INVALID_BITWISE_AGGREGATE_OPERANDS_SIZE, 75
ER_INVALID_BITWISE_OPERANDS_SIZE, 75
ER_INVALID_CAST, 125
ER_INVALID_CAST_POLYGON_RING_DIRECTION, 130
ER_INVALID_CAST_TO_GEOMETRY, 130
ER_INVALID_CAST_TO_JSON, 70
ER_INVALID_CHARACTER_STRING, 22
ER_INVALID_CHARSET_AND_DEFAULT_IS_MB, 167
ER_INVALID_COLLATION_FOR_CHARSET, 233
ER_INVALID_DD_OBJECT, 75
ER_INVALID_DD_OBJECT_ID, 75
ER_INVALID_DD_OBJECT_NAME, 75
ER_INVALID_DEFAULT, 7
ER_INVALID_DEFAULT_UTF8MB4_COLLATION, 95
ER_INVALID_ENCRYPTION_OPTION, 73
ER_INVALID_ENCRYPTION_REQUEST, 107
ER_INVALID_ERROR_LOG_NAME, 150
ER_INVALID_FIELD_SIZE, 60
ER_INVALID_GEOJSON_CRS_NOT_TOP_LEVEL, 90
ER_INVALID_GEOJSON_MISSING_MEMBER, 64
ER_INVALID_GEOJSON_UNSPECIFIED, 64
ER_INVALID_GEOJSON_WRONG_TYPE, 64
ER_INVALID_GROUP_FUNC_USE, 10
ER_INVALID_INFO_IN_FRM, 167
ER_INVALID_INSTRUMENT, 139
ER_INVALID_JSON_ATTRIBUTE, 123
ER_INVALID_JSON_BINARY_DATA, 70
ER_INVALID_JSON_CHARSET, 70
ER_INVALID_JSON_CHARSET_IN_FUNCTION, 70
ER_INVALID_JSON_DATA, 64
ER_INVALID_JSON_PATH, 70
ER_INVALID_JSON_PATH_ARRAY_CELL, 71
ER_INVALID_JSON_PATH_CHARSET, 70
ER_INVALID_JSON_PATH_WILDCARD, 70
ER_INVALID_JSON_TEXT, 70
ER_INVALID_JSON_TEXT_IN_PARAM, 70
ER_INVALID_JSON_TYPE, 110
ER_INVALID_JSON_VALUE_FOR_CAST, 71
ER_INVALID_JSON_VALUE_FOR_FUNC_INDEX, 115
ER_INVALID_MULTIPLE_CLAUSES, 108
ER_INVALID_NAMED_PIPE_FULL_ACCESS_GROUP, 40
ER_INVALID_NO_OF_ARGS, 83
ER_INVALID_OPTION_CHARACTERS, 79
ER_INVALID_OPTION_END_CHARACTER, 79
ER_INVALID_OPTION_KEY, 78
ER_INVALID_OPTION_KEY_VALUE_PAIR, 78
ER_INVALID_OPTION_START_CHARACTER, 79

ER_INVALID_OPTION_VALUE, 78	ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS, 288
ER_INVALID_OR_OLD_TABLE_OR_DB_NAME, 186	ER_KEYRING_AWS_FAILED_TO_DECRYPT_KEY, 289
ER_INVALID_PARAMETER_USE, 125	ER_KEYRING_AWS_FAILED_TO_ENCRYPT_KEY, 288
ER_INVALID_PROPERTY_KEY, 477	ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_FILE, 288
ER_INVALID_REPLICATION_TIMESTAMPS, 236	ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUE_TO, 288
ER_INVALID_RPL_WILD_TABLE_FILTER_PATTERN, 64	ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEY, 288
ER_INVALID_THREAD_ID, 89	ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIAL_FF, 287
ER_INVALID_THREAD_PRIORITY, 88	ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_E, 287
ER_INVALID_TIME_ZONE_INTERVAL, 125	ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_IN, 287
ER_INVALID_TYPE_FOR_JSON, 70	ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE, 286
ER_INVALID_USER_ATTRIBUTE_JSON, 123	ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP, 288
ER_INVALID_USE_OF_FORCE_OPTION, 89	ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID, 285
ER_INVALID_USE_OF_NULL, 12	ER_KEYRING_AWS_FAILED_TO_SET_REGION, 286
ER_INVALID_VALUE_FOR_ENFORCE_GTID_CONSISTENCY, 135	ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_FILE, 288
ER_INVALID_VALUE_OF_BIND_ADDRESSES, 464	ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK, 289
ER_INVALID_VCPU_ID, 88	ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID, 285
ER_INVALID_VCPU_RANGE, 88	ER_KEYRING_AWS_FAILED_TO_SET_REGION, 286
ER_INVALID_XPLUGIN_SOCKET_SAME_AS_SERVER, 504	ER_KEYRING_AWS_INCORRECT_FILE, 288
ER_INVALID_YEAR_COLUMN_LENGTH, 54	ER_KEYRING_AWS_INCORRECT_PROXY, 493
ER_IO_ERR_LOG_INDEX_READ, 26	ER_KEYRING_AWS_INCORRECT_REGION, 288
ER_IO_READ_ERROR, 53	ER_KEYRING_AWS_INIT_FAILURE, 287
ER_IO_WRITE_ERROR, 53	ER_KEYRING_AWS_INVALID_CONF_FILE_PATH, 286
ER_IPSOCK_ERROR, 8	ER_KEYRING_AWS_INVALID_DATA_FILE_PATH, 286
ER_IS_QUERY_INVALID_CLAUSE, 78	ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER, 287
ER_IS_SKIPPED_TABLESPACE, 87	ER_KEYRING_AWS_UDF_AWS_KMS_ERROR, 73
ER_JSON_BAD_ONE_OR_ALL_ARG, 70	ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_EMPTY_KEY, 279
ER_JSON_DOCUMENT_NULL_KEY, 71	ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_INVALID_KEY, 279
ER_JSON_DOCUMENT_TOO_DEEP, 71	ER_KEYRING_COMPONENT_EXCEPTION, 518
ER_JSON_KEY_TOO_BIG, 70	ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR, 518
ER_JSON_PARSE_ERROR, 153	ER_KEYRING_COMPONENT_NOT_INITIALIZED, 518
ER_JSON_SCHEMA_VALIDATION_ERROR_WITH_DETAIL, 118	ER_KEYRING_FAILED_TO_ACCESS_ENCRYPTED_FILE_DECRIPTION_FAILED, 284
ER_JSON_USED_AS_KEY, 70	ER_KEYRING_FAILED_TO_CREATE_ENCRYPTED_FILE_ENCRYPTION_FAILED, 284
ER_JSON_VACUOUS_PATH, 70	ER_KEYRING_FAILED_TO_CREATE_KEYRING_GDANARIFIED_FILE_FAILED_TO_CREATE_KEY, 285
ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX, 115	
ER_JSON_VALUE_TOO_BIG, 70	
ER_JT_MAX_NESTED_PATH, 90	
ER_JT_VALUE_OUT_OF_RANGE, 90	
ER_KERBEROS_CREATE_USER, 131	
ER_KEYCACHE_OOM, 143	
ER_KEYRING_ACCESS_DENIED_ERROR, 74	
ER_KEYRING_AWS_CMK_ID_NOT_SET, 287	
ER_KEYRING_AWS_FAILED_TO_ACCESS_DATAFILE, 287	
ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY, 286	
ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID, 286	
ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATEKEYRING_GDANARIFIED_FILE_ENCRYPTION_FAILED, 287	
ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATEKEYRING_GDANARIFIED_FILE_FAILED_TO_CREATE_KEY, 286	

ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_FLUSH_ER_KEYRING_MIGRATION_SUCCESSFUL, 250
284 ER_KEYRING_OKV_CONNECTION_TO_SERVER_FAILED
ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_RESTORE_ER_KEYRING,
284 ER_KEYRING_OKV_FAILED_TO_ACTIVATE_KEYS,
ER_KEYRING_ENCRYPTED_FILE_FOUND_MALFORMED_ER_BACKUP_FILE,
284 ER_KEYRING_OKV_FAILED_TO_ADD_ATTRIBUTE,
ER_KEYRING_ENCRYPTED_FILE_GEN_KEY_FAILED_ER_TO_INTERNAL_ERROR,
285 ER_KEYRING_OKV_FAILED_TO_FETCH_KEY,
ER_KEYRING_ENCRYPTED_FILE_INCORRECT_KEYRING_ER_FILE,
284 ER_KEYRING_OKV_FAILED_TO_FIND_SERVER_ENTRY,
ER_KEYRING_ENCRYPTED_FILE_INIT_FAILED_DUE_TO_INTERNAL_ERROR,
285 ER_KEYRING_OKV_FAILED_TO_FIND_STANDBY_SERVER,
ER_KEYRING_ENCRYPTED_FILE_INIT_FAILURE, 282
285 ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY,
ER_KEYRING_ENCRYPTED_FILE_INVALID_KEYRING_ER,
285 ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR,
ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_INVALID_ER,
285 ER_KEYRING_OKV_FAILED_TO_INIT_CLIENT,
ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_TOO_LONG,
285 ER_KEYRING_OKV_FAILED_TO_INIT_SSL_LAYER,
ER_KEYRING_FAILED_TO_CREATE_KEYRING_DIR, 282
278 ER_KEYRING_OKV_FAILED_TO_LOAD_KEY_UID,
ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE_ER
279 ER_KEYRING_OKV_FAILED_TO_LOAD_SSL_TRUST_STORE,
ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING_ER
280 ER_KEYRING_OKV_FAILED_TO_PARSE_CONF_FILE,
ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING_ER_BACKUP,
280 ER_KEYRING_OKV_FAILED_TO_REMOVE_KEY,
ER_KEYRING_FAILED_TO_GENERATE_KEY, 279 282
ER_KEYRING_FAILED_TO_GET_FILE_STAT, 280 ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY,
ER_KEYRING_FAILED_TO_LOAD_KEYRING_CONTENT_ER
280 ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY_SIGNAL,
ER_KEYRING_FAILED_TO_REMOVE_FILE, 280 283
ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_ER_KEYRING_ER
281 ER_KEYRING_OKV_FAILED_TO_SET_CERTIFICATE_FILE,
ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP_ER_KEYRING_ER
279 ER_KEYRING_OKV_FAILED_TO_SET_KEY_FILE,
ER_KEYRING_FAILED_TO_SET_KEYRING_FILE_DATA_ER_KEYRING_ER
280 ER_KEYRING_OKV_FAILED_TO_STORE_KEY,
ER_KEYRING_FAILED_TO_TRUNCATE_FILE, 280 ER_KEYRING_OKV_FAILED_TO_STORE_OR_GENERATE,
ER_KEYRING_FILE_INIT_FAILED, 278 283
ER_KEYRING_FILE_IO_ERROR, 280 ER_KEYRING_OKV_INCORRECT_KEY_VAULT_CONFIGURE,
ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE, 281
279 ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INCORRECT_ER
ER_KEYRING_INCORRECT_FILE, 279 281
ER_KEYRING_INTERNAL_EXCEPTION_FAILED_FILE_ER_KEYRING_ER
279 ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INTERNAL_ER
ER_KEYRING_INVALID_KEY_LENGTH, 278 ER_KEYRING_OKV_INVALID_KEY_LENGTH_FOR_CIPHE
ER_KEYRING_INVALID_KEY_TYPE, 278 281
ER_KEYRING_KEY_FETCH_FAILED_DUE_TO_EMPTY_ER_KEYRING_ER
281 ER_KEYRING_OKV_INVALID_KEY_TYPE, 281
ER_KEYRING_LOGGER_ERROR_MSG, 262 ER_KEYRING_OKV_KEY_MISMATCH, 284
ER_KEYRING_MIGRATE_FAILED, 454 ER_KEYRING_OPERATION_FAILED_DUE_TO_INTERNAL_ER
ER_KEYRING_MIGRATION_EXTRA_OPTIONS, 279
333 ER_KEYRING_UDF_KEYRING_SERVICE_ERROR,
ER_KEYRING_MIGRATION_FAILED, 250 ER_KEYRING_UNKNOWN_ERROR, 280
ER_KEYRING_MIGRATION_FAILURE, 74 ER_KEY_COLUMN_DOES_NOT_EXISTS, 8
ER_KEYRING_MIGRATION_STATUS, 74 ER_KEY_DOES_NOT_EXISTS, 14

ER_KEY_NOT_FOUND, 5
ER_KEY_PART_0, 27
ER_KEY_REF_DO_NOT_MATCH_TABLE_REF, 18
ER_KILLED_THREADS_OF_PLUGIN, 181
ER_KILLING_THREAD, 180
ER_KILL_DENIED_ERROR, 9
ER_LATITUDE_OUT_OF_RANGE, 85
ER_LCTN_CHANGED, 250
ER_LCTN_NOT_FOUND, 455
ER_LDAP_AUTH_CERTIFICATE_NAME, 326
ER_LDAP_AUTH_COMMUNICATION_HOST_INFO, 329
ER_LDAP_AUTH_CONNECTION_CREATOR_ENTER, 328
ER_LDAP_AUTH_CONNECTION_GET_LDAP_INFO_NUEIR_LDAP_AUTH_GRP_NULL_ATTRIBUTE_VALUE, 329
ER_LDAP_AUTH_CONNECTION_POOL_INIT_FAILED, ER_LDAP_AUTH_GRP_OBJECT_HAS_USER_INFO, 327
ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTERER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL, 331
ER_LDAP_AUTH_CONNECTION_PUSHED_TO_POOL, ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL, 328
ER_LDAP_AUTH_CONN_POOL_DEINITIALIZING, 325
ER_LDAP_AUTH_CONN_POOL_INITIALIZING, 325
ER_LDAP_AUTH_CONN_POOL_NOT_CREATED, 324
ER_LDAP_AUTH_CREATE_CONNECTION_KEY, 329
ER_LDAP_AUTH_CREATING_LDAP_CONNECTION, 328
ER_LDAP_AUTH_DEINIT_FAILED, 324
ER_LDAP_AUTH_DELETING_CONNECTION_KEY, 329
ER_LDAP_AUTH_DISTINGUISHED_NAME, 330
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION, 330
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT328
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT329
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT329
ER_LDAP_AUTH_FAILED_TO_CREATE_OR_GET_CONNECTION, 324
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY_POOL, 327
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_FRECONSTRUCT_ISSEARNING_CONNECTION_TO_POOL, 327
ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION329
ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_ER_PLUGINNOTREADY_PROCESS_SASL, 329
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_D320T_STATE, 327
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INIT326STATE, 327
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_REL328NSTRACTING, 326
ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT, 326
ER_LDAP_AUTH_FAILED_TO_SEARCH_DN, 331
ER_LDAP_AUTH_FAILED_TO_WRITE_PACKET, 325
ER_LDAP_AUTH_FREEING_CONNECTION, 328
ER_LDAP_AUTH_GETTING_CONNECTION_FROM_POOL, 328
ER_LDAP_AUTH_GRP_DN_PARSING_FAILED, 479
ER_LDAP_AUTH_GRP_INCORRECT_ATTRIBUTE, 478
ER_LDAP_AUTH_GRP_INFO_FOUND_IN_MANY_OBJECTS, 478
ER_LDAP_AUTH_GRP_IS_FULL_DN, 326
ER_LDAP_AUTH_GRP_NULL_ATTRIBUTE_VALUE, 479
ER_LDAP_AUTH_GRP_OBJECT_HAS_USER_INFO, 479
ER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL, 478
ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL, 326
ER_LDAP_AUTH_GRP_USER_OBJECT_HAS_GROUP_INFO, 478
ER_LDAP_AUTH_INFO_FOR_USER, 325
ER_LDAP_AUTH_INIT_FAILED, 330
ER_LDAP_AUTH_LDAPS, 479
ER_LDAP_AUTH_LDAP_INFO_NULL, 328
ER_LDAP_AUTH_MAX_ALLOWED_CONNECTION_LIMIT_HIT, 327
ER_LDAP_AUTH_MAX_POOL_SIZE_SET_FAILED, 327
ER_LDAP_AUTH_METHOD_TO_CLIENT, 329
ER_LDAP_AUTH_OBJECT_CREATE_TIMESTAMP, 326
ER_LDAP_AUTH_OR_GROUP_RETRIEVAL_FAILED, 330
ER_LDAP_AUTH_PLUGIN_FAILED_TO_READ_PACKET, 328
ER_LDAP_AUTH_POOLED_CONNECTION_KEY, 329
ER_LDAP_AUTH_POOL_DISABLE_MAX_SIZE_ZERO, 327
ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION, 327
ER_LDAP_AUTH_POOL_REINITIALIZING, 325
ER_LDAP_AUTH_POOL_SEAURNING_CONNECTION_TO_POOL, 328
ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO, 329
ER_LDAP_AUTH_SASL_REQUEST_FROM_CLIENT, 329
ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME, 327
ER_LDAP_AUTH_SEARCH_USER_GROUP_ATTR_NOT_FOUN, 326
ER_LDAP_AUTH_SETTING_USERNAME, 325

ER_LDAP_AUTH_SKIPPING_USER_GROUP_SEARCH, ER_LOCKING_SERVICE_DEADLOCK, 69
324
ER_LDAP_AUTH_STARTED_FOR_USER, 330
ER_LDAP_AUTH_STARTING_TLS, 329
ER_LDAP_AUTH_TLS_CONF, 324
ER_LDAP_AUTH_TLS_CONNECTION, 324
ER_LDAP_AUTH_USER_AUTH_DATA, 325
ER_LDAP_AUTH_USER_BIND_FAILED, 330
ER_LDAP_AUTH_USER_FOUND_IN_MANY_GRPS,
326
ER_LDAP_AUTH_USER_GROUP_SEARCH_FAILED,
330
ER_LDAP_AUTH_USER_GROUP_SEARCH_INFO,
325
ER_LDAP_AUTH_USER_GROUP_SEARCH_ROOT_BIN
467
ER_LDAP_AUTH_USER_HAS_MULTIPLE_GRP_NAMES
326
ER_LDAP_AUTH_USER_NOT_FOUND_IN_ANY_GRP,
326
ER_LDAP_AUTH_ZERO_MAX_POOL_SIZE_UNCHANGED
325
ER_LDAP_EMPTY_USERDN_PASSWORD, 489
ER_LDAP_MAPPING_CHECK_DELIMI_QUOTE,
480
ER_LDAP_MAPPING_EMPTY_MAPPING, 479
ER_LDAP_MAPPING_GETTING_NEXT_MAPPING,
480
ER_LDAP_MAPPING_GET_USER_PROXY, 479
ER_LDAP_MAPPING_INFO, 479
ER_LDAP_MAPPING_IS_QUOTE, 481
ER_LDAP_MAPPING_NON_DESIRED_STATE,
481
ER_LDAP_MAPPING_NO_SEPEARATOR_END_OF_GRP
480
ER_LDAP_MAPPING_PARSING_CURRENT_STATE,
480
ER_LDAP_MAPPING_PARSING_ERROR, 481
ER_LDAP_MAPPING_PARSING_MAPPING_INFO,
480
ER_LDAP_MAPPING_PROCESS_DELIMITER, 480
ER_LDAP_MAPPING_PROCESS_DELIMITER_COMMA_
480
ER_LDAP_MAPPING_PROCESS_DELIMITER_EQUAL_
480
ER_LDAP_MAPPING_PROCESS_MAPPING, 479
ER_LDAP_MAPPING_TRIMMING_SPACES, 481
ER_LDAP_MAPPING_USER_DONT_BELONG_GROUP,
479
ER_LIMITED_PART_RANGE, 35
ER_LOAD_DATA_INFILE_FAILED_IN_UNEXPECTED_WAY,
153
ER_LOAD_FROM_FIXED_SIZE_ROWS_TO_VAR,
28
ER_LOAD_INFO, 9
ER_LOCAL_VARIABLE, 18
ER_LOCKING_SERVICE_TIMEOUT, 69
ER_LOCKING_SERVICE_WRONG_NAME, 69
ER_LOCK_ABORTED, 44
ER_LOCK_DEADLOCK, 16
ER_LOCK_NOWAIT, 80
ER_LOCK_ORDER_DEPENDENCIES_SYNTAX,
490
ER_LOCK_ORDER_FAILED_READ_FILE, 489
ER_LOCK_ORDER_FAILED_WRITE_FILE, 489
ER_LOCK_ORDER_INIT_FAILED, 488
ER_LOCK_ORDER_MESSAGE, 489
ER_LOCK_ORDER_SCANNER_SYNTAX, 490
ER_LOCK_OR_ACTIVE_TRANSACTION, 15
ER_LOCK_REFUSED_BY_ENGINE, 72
ER_LOCK_TABLE_FULL, 16
ER_LOCK_WAIT_TIMEOUT, 16
ER_LOG_BIN_BETTER_WITH_NAME, 148
ER_LOG_CANNOT_WRITE, 133
ER_LOG_CANNOT_WRITE_EXTENDED, 493
ER_LOG_COMPONENT_CANNOT_INIT, 514
ER_LOG_COMPONENT_FLUSH_FAILED, 525
ER_LOG_FILES_GIVEN_LOG_OUTPUT_IS_TABLE,
147
ER_LOG_FILE_CANNOT_OPEN, 269
ER_LOG_FILE_INVALID, 147
ER_LOG_GENERAL_CANNOT_OPEN, 133
ER_LOG_IN_USE, 27
ER_LOG_OUTPUT_CONTRADICTORY, 146
ER_LOG_PRINTF_MSG, 248
ER_LOG_PRIV_CHECKS_REQUIRE_ROW_FORMAT_NOT
496
ER_LOG_PURGE_NO_FILE, 39
ER_LOG_PURGE_UNKNOWN_ERR, 27
ER_LOG_SLOW_CANNOT_OPEN, 133
ER_LOG_SYSLOG_CANNOT_OPEN, 132
ER_LOG_SYSLOGFacility_FAIL, 132
ER_LONGITUDE_OUT_OF_RANGE, 84
ER_LOWER_CASE_TABLE_NAMES_CS_DD_ON_CI_FS_L
147
ER_LOWER_CASE_TABLE_NAMES_USING_0,
NOT_FOUND,
ER_LOWER_CASE_TABLE_NAMES_USING_2,
NOT_FOUND,
ER_MALFORMED_GTID_SET_ENCODING, 50
ER_MALFORMED_GTID_SET_SPECIFICATION,
50
ER_MALFORMED_GTID_SPECIFICATION, 50
ER_MALFORMED_PACKET, 55
ER_MANDATORY_ROLE, 86
ER_MASTER, 15
ER_MASTER_DELAY_VALUE_OUT_OF_RANGE,
18
ER_MASTER_FATAL_ERROR_READING_BINLOG,
18
ER_MASTER_HAS_PURGED_REQUIRED_GTIDS,
52
ER_MASTER_INFO, 16

ER_MASTER_KEY_ROTATION_BINLOG_FAILED, 72
ER_MASTER_KEY_ROTATION_NOT_SUPPORTED_BY_ESI, 72
ER_MASTER_KEY_ROTATION_SE_UNAVAILABLE, 72
ER_MASTER_NET_READ, 15
ER_MASTER_NET_WRITE, 15
ER_MAXVALUE_IN_VALUES_IN, 42
ER_MAX_PREPARED_STMT_COUNT_REACHED, 31
ER_MDL_OUT_OF_RESOURCES, 124
ER_ME CAB_CHARSET_LOADED, 254
ER_ME CAB_CREATE_LATTICE_FAILED, 254
ER_ME CAB_CREATING_MODEL, 253
ER_ME CAB_FAILED_TO_CREATE_MODEL, 254
ER_ME CAB_FAILED_TO_CREATE_TRIGGER, 254
ER_ME CAB_NOT_SUPPORTED, 253
ER_ME CAB_NOT_VERIFIED, 253
ER_ME CAB_OOM_WHILE_PARSING_TEXT, 254
ER_ME CAB_PARSE_FAILED, 254
ER_ME CAB_UNSUPPORTED_CHARSET, 254
ER_MESSAGE_AND_STATEMENT, 44
ER_MICROSECOND_TIMER_IS_NOT_AVAILABLE, 245
ER_MIGRATE_TABLE_TO_DD_OOM, 498
ER_MISPLACED_INTO, 120
ER_MISSING_ACL_SYSTEM_TABLE, 237
ER_MISSING_CURRENT_PASSWORD, 114
ER_MISSING_GRANT_SYSTEM_TABLE, 237
ER_MISSING_HA_CREATE_OPTION, 60
ER_MISSING_JSON_TABLE_VALUE, 89
ER_MISSING_JSON_VALUE, 121
ER_MISSING_KEY, 59
ER_MISSING_SKIP_SLAVE, 20
ER_MISSING_TABLESPACE_FILE, 86
ER_MIXING_NOT_ALLOWED, 17
ER_MIX_HANDLER_ERROR, 33
ER_MIX_OF_GROUP_FUNC_AND_FIELDS, 12
ER_MIX_OF_GROUP_FUNC_AND_FIELDS_V2, 65
ER_MTR_MSG_1, 525
ER_MTS_CANT_PARALLEL, 49
ER_MTS_CHANGE_MASTER_CANT_RUN_WITH_GAPS, 53
ER_MTS_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX, 57
ER_MTS_FEATURE_IS_NOT_SUPPORTED, 49
ER_MTS_INCONSISTENT_DATA, 49
ER_MTS_RECOVERY_FAILURE, 53
ER_MTS_RESET_WORKERS, 53
ER_MTS_UPDATED_DBs_GREATER_MAX, 49
ER_MULTIPLE_CONSTRAINTS_WITH_SAME_NAME, 118
ER_MULTIPLE_DEF_CONST_IN_LIST_PART_ERROR, 33
ER_MULTIPLE_INTO_CLAUSES, 120
ER_MULTIPLE_JSON_VALUES, 122
ER_MULTIPLE_PRI_KEY, 7
ER_MULTI_UPDATE_KEY_CONFLICT, 46
ER_MUST_CHANGE_EXPIRED_PASSWORD, 233
ER_MUST_CHANGE_PASSWORD, 54
ER_MUST_CHANGE_PASSWORD_LOGIN, 57
ER_MYINIT_FAILED, 145
ER_MYISAM_CHECK_METHOD_ERROR, 247
ER_MYISAM_CRASHED_ERROR, 247
ER_MYISAM_CRASHED_ERROR_IN, 156
ER_MYISAM_CRASHED_ERROR_IN_THREAD, 156
ER_MYSQLBACKUP_MSG, 494
ER_MYSQL_NATIVE_PASSWORD_SECOND_PASSWORD_US, 475
ER_MY_NET_WRITE_FAILED_FALLING_BACK_ON_STDERR, 213
ER_M_BIGGER_THAN_D, 29
ER_NAME_BECOMES_EMPTY, 32
ER_NANOSECOND_TIMER_IS_NOT_AVAILABLE, 245
ER_NATIVE_FCT_NAME_COLLISION, 38
ER_NDBINFO_NOT_UPGRADING_SCHEMA, 503
ER_NDBINFO_UPGRADING_SCHEMA, 503
ER_NDBINFO_UPGRADING_SCHEMA_FAIL, 503
ER_NDB_BINLOG_BLOBQUIRES_PK, 204
ER_NDB_BINLOG_CANT_COMMIT_TO_NDB_BINLOG_INDEX, 202
ER_NDB_BINLOG_CANT_CREATE_BLOB, 205
ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB, 204
ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB_AND_CAN, 204
ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB_DROPPED, 205
ER_NDB_BINLOG_CANT_CREATE_PURGE_THD, 226
ER_NDB_BINLOG_CANT_DISCOVER_TABLE_FROM_SCHEMA, 199
ER_NDB_BINLOG_CANT_DROP_EVENT_FROM_DB, 205
ER_NDB_BINLOG_CANT_INJECT_APPLY_STATUS_WRITE_R, 207
ER_NDB_BINLOG_CANT_LOCK_NDB_BINLOG_INDEX, 202
ER_NDB_BINLOG_CANT_RELEASE_SLOCK, 200
ER_NDB_BINLOG_CANT_REOPEN_SHADOW_TABLE, 201
ER_NDB_BINLOG_CANT_WRITE_TO_NDB_BINLOG_INDEX, 202
ER_NDB_BINLOG_CLEANING_UP_SETUP_LEFTOVERS, 198
ER_NDB_BINLOG_CLUSTER_FAILURE, 206
ER_NDB_BINLOG_CLUSTER_HAS_RECONNECTED, 207
ER_NDB_BINLOG_CLUSTER_RESTARTED_RESET_MASTER, 206
ER_NDB_BINLOG_CREATE_TABLE_EVENT, 183
ER_NDB_BINLOG_CREATE_TABLE_EVENT_FAILED, 204

ER_NDB_BINLOG_CREATE_TABLE_EVENT_INFO, ER_NDB_BINLOG_REPLY_TO, 200
204 ER_NDB_BINLOG_SERVER_SHUTDOWN_DURING_NDB_
ER_NDB_BINLOG_CREATING_NDBEVENTOPERATION_FAILED,
205 ER_NDB_BINLOG_SHUTDOWN_DETECTED, 207
ER_NDB_BINLOG_DISCOVER_REUSE_OLD_EVENT_ER_NDB_BINLOG_SIGNALLING_UNKNOWN_VALUE,
205 200
ER_NDB_BINLOG_DISCOVER_TABLE_EVENT_INFO, ER_NDB_BINLOG_SKIPPING_DROP_OF_DB_CONTAININ
204 201
ER_NDB_BINLOG_ERROR_DURING_GCI_COMMIT, ER_NDB_BINLOG_SKIPPING_DROP_OF_LOCAL_TABLE,
208 201
ER_NDB_BINLOG_ERROR_DURING_GCI_ROLLBACK, ER_NDB_BINLOG_SKIPPING_LOCAL_TABLE, 200
208 ER_NDB_BINLOG_SKIPPING_OLD_SCHEMA_OPERATION
ER_NDB_BINLOG_ERROR_HANDLING_SCHEMA_EVENT_ER_NDB_BINLOG_SKIPPING_RENAME_OF_LOCAL_TABLE
207 201
ER_NDB_BINLOG_ERROR_INFO_FROM_DA, 183 201
ER_NDB_BINLOG_FAILED_CREATE_EVENT_OPERATION_ER_NDB_BINLOG_STARTING_LOG_AT_EPOCH,
184 207
ER_NDB_BINLOG_FAILED_CREATE_TABLE_EVENT_OPERATION_ER_NDB_BINLOG_UNHANDLED_ERROR_FOR_TABLE,
183 206
ER_NDB_BINLOG_FAILED_TO_GET_TABLE, 204 ER_NDB_BINLOG_UNKNOWN_NON_DATA_EVENT,
ER_NDB_BINLOG_FORMAT_CHANGED_FROM_STMT_ER_NDB_BINLOG_WRITE_TO_NDB_BINLOG_INDEX_FAII
184 206
ER_NDB_BINLOG_GENERIC_MESSAGE, 203 203
ER_NDB_BINLOG_GOT_DIST_PRIV_EVENT_FLUSHING_ER_NDB_BINLOG_WRITE_TO_NDB_BINLOG_INDEX_FAII
201 203
ER_NDB_BINLOG_GOT_SCHEMA_EVENT, 201 ER_NDB_BINLOG_WRITING_TO_NDB_BINLOG_INDEX,
ER_NDB_BINLOG_INJECTING_RANDOM_WRITE_FAIL_ER_NDB_CANT_ALLOC_GLOBAL_NDB_CLUSTER_CONN
202 202
ER_NDB_BINLOG_INJECTOR_DISCARDING_ROW_EVENT_ER_NDB_CANT_ALLOC_GLOBAL_NDB_OBJECT,
206 206
ER_NDB_BINLOG_LATEST_TRX_IN_EPOCH_NOT_IN_BINLOG, ER_NDB_CANT_ALLOC_NDB_CLUSTER_CONNECTION,
208 ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_CONTINUE,
ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_CONTINUE, ER_NDB_CANT_FIND_TABLE, 200
207 ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_WAIT_ER_NDB_CANT_PARSE_NDB_CLUSTER_CONNECTION_
207 217
ER_NDB_BINLOG_NDBEVENT_EXECUTE_FAILED, ER_NDB_CANT_START_CONNECT_THREAD,
205 218
ER_NDB_BINLOG_NDB_LOG_APPLY_STATUS_FORCE_ER_NDB_CLUSTER_CLEAN_TABLES, 197
203 ER_NDB_CLEAR_SLOCK_INFO, 200
ER_NDB_BINLOG_NDB_LOG_TRANSACTION_ID_REQUIRE_ER_NDB_CROSS_SERVER_EVENTS, 201
203 ER_NDB_CLUSTER_FIND_ALL_DBS_FAIL, 198
ER_NDB_BINLOG_NDB_TABLES_INITIALLY_READ_ONER_NDB_CLUSTER_FIND_ALL_DBS_RETRY, 198
185 ER_NDB_CLUSTER_FREE_SHARE_INFO, 185
ER_NDB_BINLOG_NDB_TABLES_WRITABLE, 207 ER_NDB_CLUSTER_GENERIC_MESSAGE, 173
ER_NDB_BINLOG_NOT_LOGGING, 204 ER_NDB_CLUSTER_GET_SHARE_INFO, 185
ER_NDB_BINLOG_ONLINE_ALTER_RENAME, ER_NDB_CLUSTER_MARK_SHARE_DROPPED_DESTROY
200 185
ER_NDB_BINLOG_ONLINE_ALTER_RENAME_COMPLETE_ER_NDB_CLUSTER_MARK_SHARE_DROPPED_INFO,
201 185
ER_NDB_BINLOG_OPENING_INDEX, 202 ER_NDB_CLUSTER_OOM_THD_NDB, 185
ER_NDB_BINLOG_RELEASE_EXTRA_SHARE_REFERRER_NDB_CLUSTER_REAL_FREE_SHARE_DROP_FAILED
208 185
ER_NDB_BINLOG_REMAINING_OPEN_TABLES, ER_NDB_CLUSTER_REAL_FREE_SHARE_INFO,
208 185
ER_NDB_BINLOG_REMAINING_OPEN_TABLE_INFO, ER_NDB_CLUSTER_SCHEMA_INFO, 173
208 ER_NDB_CLUSTER_WRONG_NUMBER_OF_FUNCTION_/
ER_NDB_BINLOG_RENAME_EVENT, 184 173

ER_NDB_COLUMN_DEFAULTS_DIFFER, 182	ER_NDB_NODE_ID_AND_MANAGEMENT_SERVER_INFO, 181
ER_NDB_COLUMN_INFO, 182	ER_NDB_NODE_INFO, 218
ER_NDB_COLUMN_SHOULD_NOT_HAVE_NATIVE_DEFINITIONS, 182	ER_NDB_NOT_WAITING_FOR_DISTRIBUTING, 199
ER_NDB_CONFLICT_FN_PARSE_ERROR, 204	ER_NDB_NUMBER_OF_CHANNELS, 229
ER_NDB_CONFLICT_FN_SETUP_ERROR, 204	ER_NDB_OOM_GET_NDB_BLOBS_VALUE, 197
ER_NDB_CONFLICT_GENERIC_MESSAGE, 203	ER_NDB_OOM_IN_FIX_UNIQUE_INDEX_ATTR_ORDER, 182
ER_NDB_COULD_NOT_GET_APPLY_STATUS_SHARE, 206	ER_NDB_POOL_SIZE_MUST_MATCH_NDB_CLUSTER_CONN, 217
ER_NDB_CPU_MASK_TOO_SHORT, 218	ER_NDB_QUERY_FAILED, 180
ER_NDB_CREATE_EVENT_OPS_LOGGING_INFO, 205	ER_NDB_REMAINING_OPEN_TABLES, 206
ER_NDB_CREATING_SHARE_IN_OPEN, 184	ER_NDB_REMAINING_OPEN_TABLE_INFO, 206
ER_NDB_CREATING_TABLE, 197	ER_NDB_REPLICATION_SCHEMA_ERROR, 40
ER_NDB_DISCARDING_EVENT_ID_VERSION_MISMATCH, 200	ER_NDB_SCHEMA_DISTRIBUTION_FAILED, 199
ER_NDB_DISCARDING_EVENT_NO_OBJ, 200	ER_NDB_SCHEMA_DISTRIBUTION_REPORTS_SUBSCRIBE, 199
ER_NDB_DISCONNECT_INFO, 181	ER_NDB_SCHEMA_DISTRIBUTION_REPORTS_UNSUBSCRIBE, 199
ER_NDB_DISCOVERED_MISSING_DB, 197	ER_NDB_SCHEMA_GENERIC_MESSAGE, 179
ER_NDB_DISCOVERED_REMAINING_DB, 198	ER_NDB_SERVER_ID_RESERVED_OR_TOO_LARGE, 203
ER_NDB DISTRIBUTED_INFO, 199	ER_NDB_DUPLICATE_NODEID_IN_NDB_CLUSTER_CONNECTION_ID_ALREADY_EXISTS, 185
ER_NDB DISTRIBUTING_ERR, 229	ER_NDB_SKIPPING_SETUP_TABLE, 198
ER_NDB DISTRIBUTION_COMPLETE, 199	ER_NDB_EMPTY_NODEID_IN_NDB_CLUSTER_CONNECTION_ID_ALREADY_EXISTS, 183
ER_NDB_DUPLICATE_NODEID_IN_NDB_CLUSTER_CONNECTION_ID_ALREADY_EXISTS, 185	ER_NDB_SLAVE_CANT_ALLOCATE_TABLE_SHARE, 183
ER_NDB_EMPTY_NODEID_IN_NDB_CLUSTER_CONNECTION_ID_ALREADY_EXISTS, 183	ER_NDB_SLAVE_CONFLICT_DETECTIONQUIRES_TRANSACTION, 182
ER_NDB_ERROR_IN_GET_AUTO_INCREMENT, 184	ER_NDB_SLAVE_CONFLICT_FUNCTIONQUIRES_ROLE, 182
ER_NDB_ERROR_IN_READAUTOINCREMENTVALUE, 183	ER_NDB_SLAVE_ERROR_IN_UPDATE_CREATE_INFO, 183
ER_NDB FAILED_TO_SET_UP_TABLE, 198	ER_NDB_SLAVE_LOGGING_EXCEPTIONS_TO, 172
ER_NDB_FIELD_INFO, 182	ER_NDB_SLAVE_LOW_EPOCH_RESOLUTION, 172
ER_NDB_FLUSHING_TABLE_INFO, 197	ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_SET_TO, 181
ER_NDB_FOUND_UNCOMMITTED_AUTOCOMMIT, 183	ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_UNKNOWN, 181
ER_NDB_GENERIC_ERROR, 218	ER_NDB_SLAVE_MISSING_DATA_FOR_TIMESTAMP_COLUMN, 172
ER_NDB_HANDLE_TRAILING_SHARE_INFO, 185	ER_NDB_SLAVE_PARALLEL_WORKERS, 229
ER_NDB IGNORING UNKNOWN_EVENT, 202	ER_NDB_SLAVE_SAW_ALREADY_COMMITTED_EPOCH, 172
ER_NDB ILLEGAL_VALUE_FOR_NDB_RECV_THREAD, 186	ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS, 172
ER_NDB_INFO_FAILED_TO_CREATE_NDBINFO, 173	ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS, 172
ER_NDB_INFO_FAILED_TO_INIT_NDBINFO, 173	ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS, 172
ER_NDB_INFO_FOUND_UNEXPECTED_FIELD_TYPE, 173	ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS, 172
ER_NDB_INITIALIZE_GIVEN_CLUSTER_PLUGIN_DISABLED, 184	ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS, 172
ER_NDB_INVALID_NODEID_IN_NDB_CLUSTER_CONNECTION_ID_ALREADY_EXISTS, 217	ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS, 172
ER_NDB_LOG_ENTRY, 226	ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS, 172
ER_NDB_LOG_ENTRY_WITH_PREFIX, 226	ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS, 172
ER_NDB_MISMATCH_IN_FRM_DISCOVERING, 198	ER_NDB_SLAVE_TOO_MANY_RETRIES, 183
ER_NDB MISSING_FRM_DISCOVERING, 198	ER_NDB_STARTING_CONNECT_THREAD, 218
ER_NDB_NODEID_NOT_FIRST_IN_NDB_CLUSTER_CONNECTION_POOL_NODEIDS, 217	

ER_NDB_TABLES_INITIALLY_READ_ONLY_ON_RECON	ER_NON_UNIQ_ERROR, 6
202	ER_NON_UPDATABLE_TABLE, 21
ER_NDB_TABLES_NOT_READY, 151	ER_NORMAL_SERVER_SHUTDOWN, 454
ER_NDB_TABLE_IS_NOT_DISTRIBUTED, 197	ER_NORMAL_SHUTDOWN, 8
ER_NDB_TABLE_OPENED_READ_ONLY, 184	ER_NOTE_KEYRING_COMPONENT_AES_DATA_IDENTIFI
ER_NDB_THREAD_TIMED_OUT, 197	519
ER_NDB_TIMED_OUT_IN_DROP_TABLE, 205	ER_NOTE_KEYRING_COMPONENT_AES_INVALID_KEY,
ER_NDB_TIMEOUT_WHILE_DISTRIBUTING, 199	519
ER_NDB_TOO_MANY_CBUS_IN_NDB_RECV_THREADS	CPNOTASKEYRING_COMPONENT_AES_INVALID_MODE
186	519
ER_NDB_TRAILING_SHARE_RELEASED_BY_CLOSE_	CPNOTASKEYRING_COMPONENT_AES_OPERATION_E
184	519
ER_NDB_TRANS_DEPENDENCY_TRACKER_ERROR,	ER_NOTE_KEYRING_COMPONENT_GENERATE_FAILED,
203	520
ER_NDB_UNEXPECTED_RENAME_TYPE, 184	ER_NOTE_KEYRING_COMPONENT_INITIALIZED,
ER_NDB_USING_NODEID, 217	518
ER_NDB_USING_NODEID_LIST, 218	ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_IT
ER_NDB_UTIL_THREAD_OOM, 186	520
ER_NDB_WAITING_INFO, 198	ER_NOTE_KEYRING_COMPONENT_METADATA_ITERAT
ER_NDB_WAITING_INFO_WITH_MAP, 198	520
ER_NEED_FILE_INSTEAD_OF_DIR, 148	ER_NOTE_KEYRING_COMPONENT_READ_DATA_NOT_F
ER_NEED_LOG_BIN, 148	519
ER_NEED_REPREPARE, 40	ER_NOTE_KEYRING_COMPONENT_REMOVE_FAILED,
ER_NETWORK_NAMESPACES_NOT_SUPPORTED,	519
486	ER_NOTE_KEYRING_COMPONENT_STORE_FAILED,
ER_NETWORK_NAMESPACE_FILE_PATH_TOO_LONG	519
486	ER_NOTE_KEYRING_COMPONENT_WRITE_MAXIMUM_D
ER_NETWORK_NAMESPACE_NOT_ALLOWED_FOR_WILDCARD_ADDRESS,	
486	ER_NOT_ALLOWED_COMMAND, 13
ER_NETWORK_READ_EVENT_CHECKSUM_FAILURE,	ER_NOT_ALLOWED_WITH_START_TRANSACTION,
455	123
ER_NET_ERROR_ON_WRITE, 13	ER_NOT_FORM_FILE, 5
ER_NET_FCNTL_ERROR, 13	ER_NOT_HINT_UPDATABLE_VARIABLE, 87
ER_NET_OK_PACKET_TOO_LARGE, 64	ER_NOT_IMPLEMENTED_FOR_CARTESIAN_SRS,
ER_NET_PACKETS_OUT_OF_ORDER, 13	94
ER_NET_PACKET_TOO_LARGE, 13	ER_NOT_IMPLEMENTED_FOR_GEOGRAPHIC_SRS,
ER_NET_READ_ERROR, 13	85
ER_NET_READ_ERROR_FROM_PIPE, 13	ER_NOT_IMPLEMENTED_FOR_PROJECTED_SRS,
ER_NET_READ_INTERRUPTED, 13	94
ER_NET_UNCOMPRESS_ERROR, 13	ER_NOT_IMPLEMENTED_GET_TABLESPACE_STATISTI
ER_NET_WAIT_ERROR, 487	269
ER_NET_WAIT_ERROR2, 520	ER_NOT_KEYFILE, 5
ER_NET_WRITE_INTERRUPTED, 14	ER_NOT_RIGHT_NOW, 145
ER_NEW_ABORTING_CONNECTION, 15	ER_NOT_SUPPORTED_AUTH_MODE, 19
ER_NO, 3	ER_NOT_SUPPORTED_YET, 18
ER_NONEXISTING_GRANT, 12	ER_NOT_VALID_PASSWORD, 54
ER_NONEXISTING_PROC_GRANT, 28	ER_NO_ACCESS_TO_NATIVE_FCT, 79
ER_NONEXISTING_TABLE_GRANT, 13	ER_NO_BINARY_LOGGING, 27
ER_NONPOSITIVE_RADIUS, 94	ER_NO_BINLOG_ERROR, 35
ER_NONUNIQ_TABLE, 7	ER_NO_CSV_NO_LOG_TABLES, 147
ER_NONUPDATEABLE_COLUMN, 25	ER_NO_DB_ERROR, 6
ER_NON_BOOLEAN_EXPR_FOR_CHECK_CONSTRAINT	ER_NO_DEFAULT, 18
106	ER_NO_DEFAULT_FOR_FIELD, 26
ER_NON_DEFAULT_VALUE_FOR_GENERATED_COLUMN	ER_NO_DEFAULT_FOR_VIEW_FIELD, 29
67	ER_NO_ERROR_LOG_PARSER_CONFIGURED,
ER_NON_GROUPING_FIELD_USED, 31	513
ER_NON_INSERTABLE_TABLE, 32	ER_NO_FORMAT_DESCRIPTION_EVENT_BEFORE_BINL
ER_NON_RO_SELECT_DISABLE_TIMER, 61	39

ER_NO_FT_MATERIALIZED_SUBQUERY, 60
ER_NO_PARTITION_FOR_GIVEN_VALUE, 35
ER_NO_PARTITION_FOR_GIVEN_VALUE_SILENT, 38
ER_NO_PARTS_ERROR, 34
ER_NO_PATH_FOR_SHARED_LIBRARY, 461
ER_NO_PERMISSION_TO_CREATE_USER, 16
ER_NO_REFERENCED_ROW, 17
ER_NO_REFERENCED_ROW_2, 31
ER_NO_SECURE_TRANSPORTS_CONFIGURED, 71
ER_NO_SESSION_TEMP, 113
ER_NO SUCH_DB, 74
ER_NO SUCH_INDEX, 8
ER_NO SUCH_TABLE, 13
ER_NO SUCH_THREAD, 9
ER_NO SUCH_USER, 30
ER_NO SUPER WITHOUT_USER_PLUGIN, 164
ER_NO_SYSTEM_SCHEMA_ACCESS, 78
ER_NO_SYSTEM_TABLESPACE_ACCESS, 78
ER_NO_SYSTEM_TABLE_ACCESS, 78
ER_NO_SYSTEM_TABLE_ACCESS_FOR_DICTIONARY, 78
ER_NO_SYSTEM_TABLE_ACCESS_FOR_SYSTEM_TABLE, 78
ER_NO_SYSTEM_TABLE_ACCESS_FOR_TABLE, 78
ER_NO_SYSTEM_VIEW_ACCESS, 85
ER_NO_TABLES_USED, 9
ER_NO_THD_NO_UUID, 138
ER_NO_TRIGGERSON_SYSTEM_SCHEMA, 32
ER_NO_UNIQUE_LOGFILE, 9
ER_NPIPE_CANT_CREATE, 228
ER_NPIPE_FAILED_TO_INIT_SECURITY_DESCRIPTOR, 171
ER_NPIPE_FAILED_TO_SET_SECURITY_DESCRIPTOR, 171
ER_NPIPE_PIPE_ALREADY_IN_USE, 172
ER_NULL_COLUMN_IN_INDEX, 11
ER_NULL_IN_VALUES_LESS_THAN, 37
ER_NUMERIC_JSON_VALUE_OUT_OF_RANGE, 70
ER_OLD_FILE_FORMAT, 31
ER_OLD_KEYFILE, 5
ER_OLD_PASSWORDS_NO_MIDDLE_GROUND, 140
ER_OLD_TEMPORALS_UPGRADED, 58
ER_ONLY_FD_AND_RBR_EVENTS_ALLOWED_IN_BINLOG, 48
ER_ONLY_IMPLEMENTED_FOR_SRID_0_AND_4326, 91
ER_ONLY_INTEGERS_ALLOWED, 38
ER_ONLY_ON_RANGE_LIST_PARTITION, 34
ER_OOM, 145
ER_OOM_SAVE_GTIDS, 455
ER_OPEN_AS_READONLY, 5
ER_OPEN_ROLE_TABLES, 76
ER_OPERAND_COLUMNS, 18
ER_OPTION_PREVENTS_STATEMENT, 21
ER_OPT_WRONG_TREE, 132
ER_OUTOFMEMORY, 5
ER_OUT_OF_RESOURCES, 5
ER_OUT_OF_SORTMEMORY, 5
ER_PAGE_TRACKING_CANNOT_PURGE, 104
ER_PAGE_TRACKING_NOT_STARTED, 104
ER_PAGE_TRACKING_RANGE_NOT_TRACKED, 104
ER_PARSER_TRACE, 132
ER_PARSE_ERROR, 7
ER_PARSE_ERROR_IN_DIGEST_FN, 91
ER_PARSING_VIEW, 138
ER_PARTIAL_REVOKES_EXIST, 114
ER_PARTIAL_REVOKE_AND_DB_GRANT_BOTH_EXISTS, 115
ER_PARTITIONS_MUST_BE_DEFINED_ERROR, 33
ER_PARTITION_CLAUSE_ON_NONPARTITIONED, 49
ER_PARTITION_COLUMN_LIST_ERROR, 42
ER_PARTITION_CONST_DOMAIN_ERROR, 37
ER_PARTITION_ENTRY_ERROR, 33
ER_PARTITION_EXCHANGE_DIFFERENT_OPTION, 48
ER_PARTITION_EXCHANGE_FOREIGN_KEY, 48
ER_PARTITION_EXCHANGE_PART_TABLE, 48
ER_PARTITION_EXCHANGE_TEMP_TABLE, 48
ER_PARTITION_FIELDS_TOO_LONG, 42
ER_PARTITION_FUNCTION_FAILURE, 35
ER_PARTITION_FUNCTION_IS_NOT_ALLOWED, 37
ER_PARTITION_FUNC_NOT_ALLOWED_ERROR, 33
ER_PARTITION_HANDLER_ADMIN_MSG, 247
ER_PARTITION_INSTEAD_OF_SUBPARTITION, 48
ER_PARTITION_MAXVALUE_ERROR, 33
ER_PARTITION_MERGE_ERROR, 37
ER_PARTITION_MGMT_ON_NONPARTITIONED, 34
ER_PARTITION_MOVE_CREATED_DUPLICATE_ROW_PLEASE, 229
ER_PARTITION_NAME, 41
ER_PARTITION_NOT_DEFINED_ERROR, 33
ER_PARTITION_NO_TEMPORARY, 37
ER_PARTITIONQUIRES_VALUES_ERROR, 32
ER_PARTITION_WRONG_NO_PART_ERROR, 33
ER_PARTITION_WRONG_NO_SUBPART_ERROR, 33
ER_PARTITION_WRONG_VALUES_ERROR, 32
ER_PART_EXPR_TOO_LONG, 85
ER_PASSWORD_ANONYMOUS_USER, 12
ER_PASSWORD_CANNOT_BE_RETAINED_ON_PLUGIN_CHANNEL, 114
ER_PASSWORD_EXPIRATION_NOT_SUPPORTED_BY_AUTHENTICATION, 90

ER_PASSWORD_EXPIRE_ANONYMOUS_USER, 60
ER_PASSWORD_FORMAT, 54
ER_PASSWORD_NOT_ALLOWED, 12
ER_PASSWORD_NO_MATCH, 12
ER_PATH_IN_DATADIR, 86
ER_PATH_LENGTH, 44
ER_PERFSHEMA_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP_NOT_EARLY, 108
234
ER_PERFSHEMA_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP_NO_INSTALL, 47
234
ER_PERFSHEMA_INIT_FAILED, 149
ER_PERFSHEMA_TABLES_INIT_FAILED, 235
ER_PERSISTENT_PRIVILEGES_BOOTSTRAP, 235
ER_PERSIST_ONLY_ACCESS_DENIED_ERROR, 86
ER_PERSIST_OPTION_HOST_TRUNCATED, 487
ER_PERSIST_OPTION_STATUS, 269
ER_PERSIST_OPTION_USER_TRUNCATED, 487
ER_PER_CHANNEL_RPL_FILTER_CONF_FOR_GRP_RPL2
244
ER_PFS_MALLOC_ARRAY_OOM, 245
ER_PFS_MALLOC_ARRAY_OVERFLOW, 245
ER_PFS_NOTIFICATION_FUNCTION_REGISTER_FAILED
238
ER_PID_FILEPATH_LOCATIONS_INACCESSIBLE, 462
ER_PID_FILE_PRIV_DIRECTORY_INSECURE, 331
ER_PK_INDEX_CANT_BE_INVISIBLE, 76
ER_PLUGGABLE_PROTOCOL_COMMAND_NOT_SUPPORTED
69
ER_PLUGIN_BAD_OPTIONS, 212
ER_PLUGIN_CANNOT_BE_UNINSTALLED, 58
ER_PLUGIN_CANT_LOAD, 211
ER_PLUGIN_CANT_OPEN_PLUGIN_TABLE, 211
ER_PLUGIN_CANT_SET_PERSISTENT_OPTIONS, 213
ER_PLUGIN_COMMON_FAILED_TO_OPEN_FILTER_TABLE
268
ER_PLUGIN_COMMON_FAILED_TO_OPEN_TABLE, 268
ER_PLUGIN_DELETE_BUILTIN, 40
ER_PLUGIN_DID_NOT_DEINITIALIZE_THREADS, 181
ER_PLUGIN_DISABLED, 212
ER_PLUGIN_FAILED_DEINITIALIZATION, 211
ER_PLUGIN_FAILED_TO_OPEN_TABLE, 459
ER_PLUGIN_FAILED_TO_OPEN_TABLES, 459
ER_PLUGIN_FORCING_SHUTDOWN, 211
ER_PLUGIN_HAS_CONFLICTING_SYSTEM_VARIABLES
212
ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_DEINITIALIZATION, 92
211
ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_SHUTDOWN,
211
ER_PLUGIN_INIT_FAILED, 152
ER_PLUGIN_INSTALL_ERROR, 468
ER_PLUGIN_INVALID_TABLE_DEFINITION, 525
ER_PLUGIN_IS_NOT_LOADED, 35
ER_PLUGIN_IS_PERMANENT, 45
ER_PLUGIN_LOAD_OPTIONS_IGNORED, 495
ER_PLUGIN_LOAD_PARAMETER_TOO_LONG, 211
ER_PLUGIN_NO_INSTALL_DUP, 487
ER_PLUGIN_NO_UNINSTALL, 47
ER_PLUGIN_NO_OOM, 212
ER_PLUGIN_PARSING_OPTIONS_FAILED, 212
ER_PLUGIN_REGISTRATION_FAILED, 211
ER_PLUGIN_SHUTTING_DOWN_PLUGIN, 211
ER_PLUGIN_UNINSTALL_ERROR, 468
ER_PLUGIN_UNKNOWN_VARIABLE_TYPE, 212
ER_PLUGIN_VARIABLE_MISSING_NAME, 212
ER_PLUGIN_VARIABLE_NOT_ALLOCATED_THREAD_LO
212
ER_PLUGIN_VARIABLE_SET_READ_ONLY, 212
ER_POINTLESS_WITHOUT_SLOWLOG, 140
ER_POLYGON_TOO_LARGE, 96
ER_PREPARE_FOR_SECONDARY_ENGINE, 481
ER_PREVENTS_VARIABLE_WITHOUT_RBR, 66
ER_PRIMARY_CANT_HAVE_NULL, 14
ER_PRIVILEGE_SYSTEM_INIT_FAILED, 235
ER_PROCACCESS_DENIED_ERROR, 26
ER_PROC_AUTO_GRANT_FAIL, 28
ER_PROC_AUTO_REVOKED, 28
ER_PROTOCOL_COMPRESSION_RESET_LOG, 494
ER_PS_MANY_PARAM, 27
ER_PS_NO_RECURSION, 30
ER_QUERY_CACHE_DISABLED, 42
ER_QUERY_INTERRUPTED, 23
ER_QUERY_ON_FOREIGN_DATA_SOURCE, 29
ER_QUERY_TIMEOUT, 61
ER_RANGE_NOT_INCREASING_ERROR, 33
ER_READING_TABLE_FAILED, 153
ER_READY, 8
ER_READ_LOG_EVENT_FAILED, 243
ER_READ_ONLY_MODE, 55
ER_READ_ONLY_TRANSACTION, 16
ER REALLY_RUN_AS_ROOT, 144
ER_RECORD_FILE_FULL, 10
ER_RECOVERING_TABLE, 213
ER_REFERENCED_TRG_DOES_NOT_EXIST, 60
ER_REGEXP_BAD_ESCAPE_SEQUENCE, 92
ER_REGEXP_BAD_INTERVAL, 92
ER_REGEXP_BUFFER_OVERFLOW, 92
ER_REGEXP_ERROR, 12
ER_REGEXP_INDEX_OUTOFGBOUNDS_ERROR,
92
ER_REGEXP_INTERNAL_ERROR, 92
ER_REGEXP_INVALID_BACK_REF, 92

ER_REGEXP_INVALID_CAPTURE_GROUP_NAME,	ER_RES_GRP_FAILED_TO_GET_THREAD_HANDLE,
113	239
ER_REGEXP_INVALID_FLAG, 114	ER_RES_GRP_FEATURE_NOT_AVAILABLE, 239
ER_REGEXP_INVALID_RANGE, 93	ER_RES_GRP_GET_THREAD_PRIO_NOT_SUPPORTED,
ER_REGEXP_LOOK_BEHIND_LIMIT, 93	239
ER_REGEXP_MAX_LT_MIN, 92	ER_RES_GRP_INVALID_THREAD_PRIORITY, 239
ER_REGEXP_MISMATCHED_PAREN, 92	ER_RES_GRP_INVALID_VCPU_ID, 249
ER_REGEXP_MISSING_CLOSE_BRACKET, 93	ER_RES_GRP_INVALID_VCPU_RANGE, 249
ER_REGEXP_PATTERN_TOO_BIG, 93	ER_RES_GRP_SET_THREAD_PRIORITY_FAILED,
ER_REGEXP_RULE_SYNTAX, 92	239
ER_REGEXP_STACK_OVERFLOW, 93	ER_RES_GRP_SET_THR_AFFINITY_FAILED, 238
ER_REGEXP_STRING_NOT_TERMINATED, 91	ER_RES_GRP_SET_THR_AFFINITY_TO_CPUS_FAILED,
ER_REGEXP_TIME_OUT, 93	239
ER_REGEXP_UNIMPLEMENTED, 92	ER_RES_GRP_SOLARIS_PROCESSOR_AFFINITY_FAILED,
ER_REGEX_NUMBER_TOO_BIG, 126	240
ER_RELAY_LOG_FAIL, 26	ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_CPUID_FA
ER_RELAY_LOG_INIT, 27	240
ER_RELAY_LOG_SPACE_LIMIT_DISABLED, 464	ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_THREAD_F
ER_RELOAD_KEYRING_FAILURE, 130	240
ER_REMOVED_SPACES, 32	ER_RES_GRP_THD_UNBIND_FROM_CPU_FAILED,
ER_RENAMED_NAME, 41	239
ER_RENAME_ROLE, 76	ER_RETRYING_REPAIR_WITHOUT_QUICK, 213
ER_REORG_HASH_ONLY_ON_SAME_NO, 34	ER_RETRYING_REPAIR_WITH_KEYCACHE, 213
ER_REORG_NO_PARAM_ERROR, 34	ER_REVOKER_GRANTS, 20
ER_REORG_OUTSIDE_RANGE, 35	ER_REWRITER_LOAD_FAILED, 270
ER_REORG_PARTITION_NOT_EXIST, 35	ER_REWRITER_OOM, 270
ER_REPLACE_INACCESSIBLE_ROWS, 63	ER_REWRITER_QUERY_ERROR_MSG, 266
ER_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_RESOURCE_NAME	ER_REWRITER_QUERY_FAILED, 266
516	ER_REWRITER_READ_FAILED, 270
ER_REQUIRE_PRIMARY_KEY, 14	ER_REWRITER_TABLE_MALFORMED_ERROR, 270
ER_REQUIRE_ROW_FORMAT_INVALID_VALUE,	ER_ROLE_GRANTED_TO_ITSELF, 129
119	ER_ROLE_NOT_GRANTED, 76
ER_RESERVED_SYNTAX, 27	ER_ROW_DATA_TOO_BIG_TO_WRITE_IN_BINLOG,
ER_RESERVED_TABLESPACE_NAME, 95	243
ER_RESET_MASTER_TO_VALUE_OUT_OF_RANGE,	ER_ROW_DOES_NOT_MATCH_GIVEN_PARTITION_SET,
79	49
ER_RESIGNAL_WITHOUT_ACTIVE_HANDLER, 41	ER_ROW_DOES_NOT_MATCH_PARTITION, 48
ER_RESOURCE_GROUP_BIND_FAILED, 89	ER_ROW_IN_WRONG_PARTITION, 57
ER_RESOURCE_GROUP_BUSY, 89	ER_ROW_IN_WRONG_PARTITION_PLEASE_REPAIR,
ER_RESOURCE_GROUP_DISABLED, 89	155
ER_RESOURCE_GROUP_EXISTS, 88	ER_ROW_IS_REFERENCED, 17
ER_RESOURCE_GROUP_IS_DISABLED, 238	ER_ROW_IS_REFERENCED_2, 31
ER_RESOURCE_GROUP_METADATA_UPDATE_SKIPPED	ER_ROW_SINGLE_PARTITION_FIELD_ERROR,
237	42
ER_RESOURCE_GROUP_NOT_EXISTS, 88	ER_RPL_ASYNC_CHANNEL_CANT_CONNECT,
ER_RESOURCE_GROUP_POST_INIT_FAILED,	514
234	ER_RPL_ASYNC_CHANNEL_CANT_CONNECT_NO_QUORUM,
ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED,	514
234	ER_RPL_ASYNC_CHANNEL_STOPPED_QUORUM_LOST,
ER_RESOURCE_GROUP_VALIDATION_FAILED,	514
238	ER_RPL_ASYNC_EXECUTING_QUERY, 515
ER_RESTART_RECEIVED_INFO, 250	ER_RPL_ASYNC_MANAGED_NAME_ADDED, 515
ER_RESTART_SERVER_FAILED, 94	ER_RPL_ASYNC_MANAGED_NAME_REMOVED,
ER_RES_GRP_FAILED_DETERMINE_CPU_COUNT,	515
239	ER_RPL_ASYNC_READ_FAILOVER_TABLE, 515
ER_RES_GRP_FAILED_TO_DETERMINE_NICE_CAPABILITIES	ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFF,
239	124

ER_RPL_ASYNC_RECONNECT_FAIL_NO_SOURCE,	ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY,
512	103
ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF,	ER_RPL_ENCRYPTION_HEADER_ERROR, 103
124	ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY,
ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF_CHANNEL,	
517	ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED, 103
ER_RPL_ASYNC_SENDER_ADDED, 514	ER_RPL_ENCRYPTION_KEY_NOT_FOUND, 102
ER_RPL_ASYNC_SENDER_REMOVED, 514	ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED
ER_RPL_BINLOG_FILTERS_OOM, 142	
ER_RPL_BINLOG_MASTER_SENDS_HEARTBEAT,	103
180	ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTION,
ER_RPL_BINLOG_MASTERUSES_CHECKSUM_AND_SLAVE_CANT,	
180	ER_RPL_ERROR_CHANGING_MASTER_INFO_REPO_TYPE
ER_RPL_BINLOG_RELAY_DELEGATES_INIT FAILED,	175
152	ER_RPL_ERROR_CHANGING_RELAY_LOG_INFO_REPO
ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEATINFO,	
180	ER_RPL_ERROR_CHECKING_REPOSITORY, 175
ER_RPL_BINLOG_STARTING_DUMP, 180	ER_RPL_ERROR_CREATING_MASTER_INFO,
ER_RPL_BINLOG_STORAGE_DELEGATES_INIT FAILED	174
152	ER_RPL_ERROR_CREATING_RELAY_LOG_INFO,
ER_RPL_BINLOG_TRANSMIT_DELEGATES_INIT FAILED	175
152	ER_RPL_ERROR_LOOKING_FOR_LOG, 193
ER_RPL_CANT_ADD_DO_TABLE, 146	ER_RPL_ERROR_READING_MASTER_CONFIGURATION,
ER_RPL_CANT_ADD_IGNORE_TABLE, 146	210
ER_RPL_CANT_CREATE_SLAVE_THREAD, 189	ER_RPL_ERROR_READING_SLAVE_WORKER_CONFIGURATION
ER_RPL_CANT_FIND_FOLLOWUP_FILE, 193	209
ER_RPL_CANT_HAVE_SAME_BASENAME, 231	ER_RPL_ERROR_WRITING_MASTER_CONFIGURATION,
ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_RLI_INIT_INFO,	
196	ER_RPL_ERROR_WRITING_RELAY_LOG_CONFIGURATION
ER_RPL_CANT_MAKE_PATHS, 148	197
ER_RPL_CANT_OPEN_INFO_TABLE, 173	ER_RPL_ERROR_WRITING_SLAVE_WORKER_CONFIGURATION
ER_RPL_CANT_OPEN_LOG_IN_RLI_INIT_INFO,	209
197	ER_RPL_FAILED_TO_CREATE_CACHE_FOR_INFO_FILE,
ER_RPL_CANT_SCAN_INFO_TABLE, 173	176
ER_RPL_CANT_STOP_SLAVE_WHILE_LOCKED_BACKLOG	ER_RPL_FAILED_TO_CREATE_NEW_INFO_FILE,
110	176
ER_RPL_CHANGING_RELAY_LOG_INFO_REPO_TYPE	ER_RPL_FAILED_TO_CREATE_SLAVE_WORKERS
175	175
ER_RPL_CHANNELS_REQUIRE_NON_ZERO_SERVERPORT	ER_RPL_FAILED_TO_OPEN_INFO_FILE, 176
174	ER_RPL_FAILED_TO_OPEN_RELAY_LOG, 209
ER_RPL_CHANNELS_REQUIRE_TABLES_AS_INFO_REPO	ER_RPL_FAILED_TO_RESET_STATE_IN_SLAVE_INFO_REPO
174	175
ER_RPL_CORRUPTED_INFO_TABLE, 173	ER_RPL_FAILED_TO_STAT_LOG_IN_INDEX, 196
ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE,	ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL,
174	244
ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MASTER_KEY	ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED,
104	235
ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT,	ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED,
104	235
ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY,	ER_RPL_GTID_LOG_EVENT_IN_STREAM, 178
102	ER_RPL_GTID_MEMORY_FINALLY_AVAILABLE,
ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY,	176
103	ER_RPL_GTID_MODEQUIRES_ENFORCE_GTID_COM
ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY,	231
103	ER_RPL_GTID_TABLE_CANNOT_OPEN, 133
ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS,	ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT
103	467

ER_RPL_GTID_UNSAFE_STMT_CREATE_SELECT, 454
ER_RPL_GTID_UNSAFE_STMT_ON_NON_TRANS_TABLE, 453
ER_RPL_GTID_UNSAFE_STMT_ON_TEMPORARY_TABLE, 454
ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR, 179
ER_RPL_INCONSISTENT_SEQUENCE_NO_IN_TRX, 174
ER_RPL_INCONSISTENT_TIMESTAMPS_IN_TRX, 174
ER_RPL_INFINITY_DENIED, 150
ER_RPL_INFINITY_IGNORED, 151
ER_RPL_INFO_DATA_TOO_LONG, 48
ER_RPL_IO_THREAD_KILLED, 243
ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOWABLE, 192
ER_RPL_LOG_ENTRY_EXCEEDS_SLAVE_MAX_ALLOWABLE, 192
ER_RPL_LOG_NOT_FOUND_WHILE_COUNTING_RELAYLOG, 196
ER_RPL_MTS_AUTOMATIC_RECOVERY_FAILED, 189
ER_RPL_MTS_CHECKPOINT_PERIOD_DIFFERS_FROM_MASTER, 193
ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO, 193
ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO_CANT_FLUSH_MASTER_INFO_FILE, 192
ER_RPL_MTS_RECOVERY_CANT_OPEN_RELAY_LOG, 189
ER_RPL_MTS_RECOVERY_COMPLETE, 191
ER_RPL_MTS_RECOVERY_FAILED_TO_START_COORDINATOR, 189
ER_RPL_MTS_RECOVERY_STARTING_COORDINATOR, 189
ER_RPL_MTS_RECOVERY_SUCCESSFUL, 189
ER_RPL_MTS_SLAVE_COORDINATOR_HAS_WAITED, 210
ER_RPL_MTS_STATISTICS, 191
ER_RPL_MULTISOURCEQUIRES_TABLE_TYPE_RESPONSES, 176
ER_RPL_OPEN_INDEX_FILE_FAILED, 196
ER_RPL_PLEASE_USE_OPTION_RELAY_LOG, 196
ER_RPL_PLUGIN_FUNCTION_FAILED, 152
ER_RPL_RECOVERY_ERROR, 188
ER_RPL_RECOVERY_ERROR_FREEING_IO_CACHE, 188
ER_RPL_RECOVERY_ERROR_READ_RELAY_LOG, 188
ER_RPL_RECOVERY_FILE_MASTER_POS_INFO, 188
ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG, 188
ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_MASTER, 188
ER_RPL_RECOVERY_REPLICATE_SAME_SERVER_ID_REQUEST, 188
ER_RPL_RELAY_LOG_INDEX_NEEDS_FILE_NOT_DIRECTORY, 196
ER_RPL_RELAY_LOG_NEEDS_FILE_NOT_DIRECTORY, 196
ER_RPL_RELAY_LOG_RECOVERY_INFO_AFTER_CLONE, 499
ER_RPL_REPLICA_MONITOR_IO_THREAD_EXITING, 515
ER_RPL_REPLICA_MONITOR_IO_THREAD_RECONNECT_CHA, 515
ER_RPL_REPO_HAS_GAPS, 135
ER_RPL_REWRITEDB_EMPTY_FROM, 147
ER_RPL_REWRITEDB_EMPTY_TO, 147
ER_RPL_REWRITEDB_MISSING_ARROW, 147
ER_RPL_SERVER_ID_MISSING, 189
ER_RPL_SLAVE_ADDITIONAL_ERROR_INFO_FROM_DA, 194
ER_RPL_SLAVE_APPLY_LOG_EVENT_FAILED_INVALID_NOM, 496
ER_RPL_SLAVE_AUTO_POSITION_IS_1_AND_GTID_MODE_L, 187
ER_RPL_SLAVE_CANT_INIT_RELAY_LOG_POSITION, 190
ER_RPL_SLAVE_CANT_INITIALIZE_SLAVE_WORKER, 192
ER_RPL_SLAVE_CANT_INIT_RELAY_LOG_POSITION, 191
ER_RPL_SLAVE_CANT_START_SLAVE_FOR_CHANNEL, 187
ER_RPL_SLAVE_CANT_STOP_SLAVE_FOR_CHANNEL, 188
ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION, 195
ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION, 195
ER_RPL_SLAVE_COULD_NOT_CREATE_CHANNEL_LIST, 175
ER_RPL_SLAVE_DUMP_THREAD_KILLED_BY_MASTER, 191
ER_RPL_SLAVE_ERROR_INFO_FROM_DA, 194
ER_RPL_SLAVE_ERROR_LOADING_USER_DEFINED_LIBRA, 194
ER_RPL_SLAVE_ERROR_READING_FROM_SERVER, 190
ER_RPL_SLAVE_ERROR_READING_RELAY_LOG_EVENTS, 195
ER_RPL_SLAVE_ERROR_REQUESTING_BINLOG_DUMP, 192
ER_RPL_SLAVE_ERROR_RETRYING, 190
ER_RPL_SLAVE_ERROR_RUNNING_QUERY, 194

ER_RPL_SLAVE_FAILED_TO_CREATE_CHANNEL_FROM_MASTER_SLAVE_SQL_THREAD_DETECTED_UNEXPECTEDLY
176
ER_RPL_SLAVE_FAILED_TO_CREATE_OR_RECOVER_IN_POPEN_RESPONSE_THREAD_EXITING, 194
187
ER_RPL_SLAVE_FAILED_TO_INIT_A_MASTER_INFO_STRUCTURE,
176
ER_RPL_SLAVE_FAILED_TO_INIT_MASTER_INFO_STRUCTURE_SLAVE_SQL_THREAD_STARTING_WITH_PRIVILEGES
176
ER_RPL_SLAVE_FAILED_TO_INIT_PARTITIONS_HASHER_RPL_SLAVE_SQL_THREAD_STOP_CMD_EXEC_TIME
193
453
ER_RPL_SLAVE_FILTER_CREATE_FAILED, 236
ER_RPL_SLAVE_FLUSH_RELAY_LOGS_NOT_ALLOWED
192
229
ER_RPL_SLAVE_FORCING_TO_RECONNECT_IO_THREAD
191
ER_RPL_SLAVE_GENERIC_MESSAGE, 175
193
ER_RPL_SLAVE_GLOBAL_FILTERS_COPY_FAILED,
236
ER_RPL_SLAVE_INCORRECT_CHANNEL, 230
ER_RPL_SLAVE_INSECURE_CHANGE_MASTER,
211
229
ER_RPL_SLAVE_IO_THREAD_ABORTED_WAITING_FOR_RELAY_LOG_SPACE,
192
193
ER_RPL_SLAVE_IO_THREAD_CANT_REGISTER_ON_MASTER_THREADS_UNEXPECTED_BEGIN_IN_STREAM, 178
191
ER_RPL_SLAVE_IO_THREAD_DETECTS_UNEXPECTED_XID_EVENT_SEQUENCE,
195
196
ER_RPL_SLAVE_IO_THREAD_EXITING, 192
178
ER_RPL_SLAVE_IO_THREAD_KILLED, 191
ER_RPL_UNSUPPORTED_UNIGNORABLE_EVENT_IN_STREAM
189
ER_RPL_SLAVE_NDB_TABLES_NOT_AVAILABLE,
193
174
ER_RPL_ZOMBIE_ENCOUNTERED, 133
196
98
ER_RPL_SLAVE_NEXT_LOG_IS_ACTIVE, 195
66
ER_RPL_SLAVE_NEXT_LOG_IS_INACTIVE, 195
35
ER_RPL_SLAVE_QUEUE_EVENT_FAILED_INVALID_CONFIGURATION_NAME_PARTITION_FIELD, 42
194
137
ER_RPL_SLAVE_QUEUE_EVENT_FAILED_INVALID_NON_RUNNING_THREADS_STARTED, 137
496
136
ER_RPL_SLAVE_READ_INVALID_EVENT_FROM_MASTER_THREADS_SCHEDULER_STOPPING_FAILED_TO_CREATE_WORKER
194
137
ER_RPL_SLAVE_REPORT_HOST_TOO_LONG,
190
137
ER_RPL_SLAVE_REPORT_PASSWORD_TOO_LONG, ER_SCHEDULER_WAITING, 136
190
ER_RPL_SLAVE_REPORT_USER_TOO_LONG,
190
ER_SCHEMA_DIR_CREATE_FAILED, 91
ER_SCHEMA_DIR_EXISTS, 91
ER_SCHEMA_DIR_MISSING, 91
ER_SCHEMA_DIR_UNKNOWN, 91
ER_RPL_SLAVE_RESET_FILTER_OPTIONS, 236
ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED,
190
497
ER_RPL_SLAVE_SECONDS_BEHIND_MASTER_DUBIOUS_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED
194
498
ER_SCHEMA_READ_ONLY, 124

ER_SDI_GET_KEYS_INVALID_TABLESPACE, 130
ER_SDI_OPERATION_FAILED, 89
ER_SDI_OPERATION_FAILED_MISSING_RECORD, 121
ER_SECONDARY_ENGINE, 113
ER_SECONDARY_ENGINE_DDL, 113
ER_SECONDARY_ENGINE_PLUGIN, 112
ER_SECOND_PASSWORD_CANNOT_BE_EMPTY, 112
ER_SECURE_AUTH_VALUE_UNSUPPORTED, 139
ER_SECURE_TRANSPORT_REQUIRED, 71
ER_SEC_FILE_PRIV_ARGUMENT_TOO_LONG, 142
ER_SEC_FILE_PRIV_CANT_ACCESS_DIR, 141
ER_SEC_FILE_PRIV_CANT_STAT, 141
ER_SEC_FILE_PRIV_DIRECTORY_INSECURE, 141
ER_SEC_FILE_PRIV_DIRECTORY_PERMISSIONS, 142
ER_SEC_FILE_PRIV_EMPTY, 141
ER_SEC_FILE_PRIV_IGNORED, 141
ER_SEC_FILE_PRIV_NULL, 141
ER_SELECT_REDUCED, 19
ER_SEMISYNC_ADD_ACK_TO_SLOT, 258
ER_SEMISYNC_BINLOG_REPLY_IS_AHEAD, 257
ER_SEMISYNC_BINLOG_WRITE_OUT_OF_ORDER, 255
ER_SEMISYNC_CLEARED_ACTIVE_TRANSACTION_TID, 255
ER_SEMISYNC_CLEARED_ALL_ACTIVE_TRANSACTION_TID, 255
ER_SEMISYNC_DISABLED_ON_MASTER, 256
ER_SEMISYNC_EXECUTION_FAILED_ON_MASTER, 260
ER_SEMISYNC_FAILED_REGISTER_SLAVE_TO_RECEIVER, 259
ER_SEMISYNC_FAILED_TO_ALLOCATE_TRX_NODE, 255
ER_SEMISYNC_FAILED_TO_INSERT_TRX_NODE, 258
ER_SEMISYNC_FAILED_TO_START_ACK_RECEIVER, 258
ER_SEMISYNC_FAILED_TO_STOP_ACK_RECEIVER, 258
ER_SEMISYNC_FORCED_SHUTDOWN, 256
ER_SEMISYNC_FUNCTION_CALLED_TWICE, 256
ER_SEMISYNC_INIT_WAIT_POS, 257
ER_SEMISYNC_INSERT_LOG_INFO_IN_ENTRY, 255
ER_SEMISYNC_MASTER_FAILED_ON_NET_FLUSH, 258
ER_SEMISYNC_MASTER_GOT_REPLY_AT_POS, 256
ER_SEMISYNC_MASTER_OOM, 256
ER_SEMISYNC_MASTER_SIGNAL_ALL_WAITING_THREADS, 257
ER_SEMISYNC_MASTER_TRX_WAIT_POS, 257
ER_SEMISYNC_MISSING_MAGIC_NO_FOR_SEMISYNC_PKT, 260
ER_SEMISYNC_MOVE_BACK_WAIT_POS, 257
ER_SEMISYNC_NOT_SUPPORTED_BY_MASTER, 261
ER_SEMISYNC_NO_SPACE_IN_THE_PKT, 258
ER_SEMISYNC_PROBE_LOG_INFO_IN_ENTRY, 255
ER_SEMISYNC_RECEIVED_ACK_IS_SMALLER, 258
ER_SEMISYNC_REPLY_BINLOG_FILE_TOO_LARGE, 256
ER_SEMISYNC_REPLY_MAGIC_NO_ERROR, 256
ER_SEMISYNC_REPLY_PKT_LENGTH_TOO_SMALL, 256
ER_SEMISYNC_RPL_ENABLED_ON_MASTER, 256
ER_SEMISYNC_RPL_INIT_FOR_TRX, 255
ER_SEMISYNC_RPL_SWITCHED_OFF, 257
ER_SEMISYNC_RPL_SWITCHED_ON, 257
ER_SEMISYNC_SERVER_REPLY, 256
ER_SEMISYNC_SLAVE_NET_FLUSH_REPLY_FAILED, 260
ER_SEMISYNC_SLAVE_REPLY, 260
ER_SEMISYNC_SLAVE_REPLY_WITH_BINLOG_INFO, 260
ER_SEMISYNC_SLAVE_SEND_REPLY_FAILED, 260
ER_SEMISYNC_SLAVE_SET_FAILED, 261
ER_SEMISYNC_SLAVE_START, 260
ER_SEMISYNC_SOCKET_FD_TOO_LARGE, 260
ER_SEMISYNC_STARTING_ACK_RECEIVER_THREAD, 260
ER_SEMISYNC_START_BINLOG_DUMP_TO_SLAVE, 259
ER_SEMISYNC_STOPPING_ACK_RECEIVER_THREAD, 259
ER_SEMISYNC_STOP_BINLOG_DUMP_TO_SLAVE, 259
ER_SEMISYNC_SYNC_HEADER_UPDATE_INFO, 258
ER_SEMISYNC_TRACE_ENTER_FUNC, 254
ER_SEMISYNC_TRACE_EXIT, 255
ER_SEMISYNC_TRACE_EXIT_WITH_BOOL_EXIT_CODE, 255
ER_SEMISYNC_TRACE_EXIT_WITH_INT_EXIT_CODE, 254
ER_SEMISYNC_TRX_SKIPPED_AT_POS, 258
ER_SEMISYNC_UNREGISTERED_REPLICATOR, 260
ER_SEMISYNC_UNREGISTER_BINLOG_STORAGE_OBSERVER, 259
ER_SEMISYNC_UNREGISTER_BINLOG_TRANSMIT_OBSERVER, 259

ER_SEMISYNC_UNREGISTER_TRX_OBSERVER_FAILED
259 ER_SERVER_RPL_ENCRYPTION_FAILED_TO_GENERATE
473
ER_SEMISYNC_UPDATE_EXISTING_SLAVE_ACK,
258 ER_SERVER_RPL_ENCRYPTION_FAILED_TO_REMOVE
473
ER_SEMISYNC_WAIT_FOR_BINLOG_TIMEDOUT,
257 ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ROTATE
473
ER_SEMISYNC_WAIT_TIME_ASSESSMENT_FOR_COMBINATION
257 ER_SERVER_RPL_ENCRYPTION_FAILED_TO_STORE_KEYRING
473
ER_SEMISYNC_WAIT_TIME_FOR_BINLOG_SENT,
257 ER_SERVER_RPL_ENCRYPTION_HEADER_ERROR,
473
ER_SERVERID_TOO_LARGE, 150 ER_SERVER_RPL_ENCRYPTION_IGNORE_ROTATE_MASTER
474
ER_SERVER_ACL_TABLE_ERROR, 458 ER_SERVER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION
481 ER_SERVER_RPL_ENCRYPTION_KEYRING_INVALID_KEY
472
ER_SERVER_BINLOG_MASTER_KEY_ROTATION_FAILED
482 ER_SERVER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED
473
ER_SERVER_BINLOG_UNSAFE_SYSTEM_FUNCTION, ER_SERVER_RPL_ENCRYPTION_KEY_NOT_FOUND,
485 ER_SERVER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY
472
ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2,
458 ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_INITIALIZE
473
ER_SERVER_CANT_OPEN_FILE, 457 ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_ROTATE
473
ER_SERVER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2,
458 ER_SERVER_SHUTDOWN, 6
473
ER_SERVER_COL_COUNT_DOESNT_MATCH_PLEASEUPDATE_V2,
458 ER_SERVER_SHUTDOWN_COMPLETE, 231
473
ER_SERVER_COST_FAILED_TO_READ, 177 ER_SERVER_SHUTDOWN_INFO, 461
177 ER_SERVER_SLAVE_CONVERSION_FAILED, 458
177 ER_SERVER_SLAVE_IGNORED_TABLE, 458
ER_SERVER_COST_INVALID_COST_CONSTANT,
177 ER_SERVER_SLAVE_INIT_QUERY_FAILED, 458
177 ER_SERVER_SLAVE_MI_INIT_REPOSITORY, 456
ER_SERVER_DISK_FULL_NOWAIT, 457 ER_SERVER_SLAVE_RLI_INIT_REPOSITORY,
456
ER_SERVER_FILE_NOT_FOUND, 457 ER_SERVER_UPGRADE_CHECKING_DB, 484
456 ER_SERVER_UPGRADE_EMPTY_SYS, 484
ER_SERVER_FILE_USED, 457 ER_SERVER_UPGRADE_FAILED, 483
473
ER_SERVER_GTID_UNSAFE_CREATE_DROP_TEMP_TABLES_IN_TRANSACTION
467 ER_SERVER_UPGRADE_FROM_VERSION, 478
474 ER_SERVER_UPGRADE_HELP_TABLE_STATUS,
473
ER_SERVER_HANDLER_ERROR, 457 ER_SERVER_UPGRADE_INFO_FILE, 483
247 ER_SERVER_TABLE_CHECK_FAILED, 458
ER_SERVER_ISNT_AVAILABLE, 72 ER_SERVER_TEST_MESSAGE, 459
20 ER_SERVER_UNKNOWN_ERROR, 456
ER_SERVER_IS_IN_SECURE_AUTH_MODE, 20 ER_SERVER_UNKNOWN_SYSTEM_VARIABLE,
456
ER_SERVER_MASTER_FATAL_ERROR_READING_BINLOG,
455 ER_SERVER_UPGRADE_NO_SYS_VERSION, 484
456 ER_SERVER_UPGRADE_OFF, 483
457 ER_SERVER_UPGRADE_PENDING, 483
ER_SERVER_NOT_FORM_FILE, 457 ER_SERVER_UPGRADE_REQUIRED,
456 ER_SERVER_UPGRADE_REPAIR_STATUS, 483
ER_SERVER_NO_SESSION_TO_SEND_TO, 456 ER_SERVER_UPGRADE_SKIP, 483
456 ER_SERVER_UPGRADE_STATUS, 483
ER_SERVER_NO_SYSTEM_TABLE_ACCESS, 456 ER_SERVER_UPGRADE_SYSTEM_TABLES, 484
ER_SERVER_OFFLINE_MODE, 61
ER_SERVER_OUTOFMEMORY, 233
ER_SERVER_OUT_OF_RESOURCES, 233
ER_SERVER_OUT_OF_SORTMEMORY, 457
ER_SERVER_RECORD_FILE_FULL, 457
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ENCRYPTION
477 ER_SERVER_UPGRADE_REPAIR_STATUS, 483
472 ER_SERVER_UPGRADE_SKIP, 483
ER_SERVER_UPGRADE_STATUS, 483
ER_SERVER_UPGRADE_SYSTEM_TABLES, 484

ER_SERVER_UPGRADE_SYS_SCHEMA, 483	ER_SLAVE_CHANNEL_SQL_SKIP_COUNTER, 65
ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNT, 484	ER_SLAVE_CHANNEL_SQL_THREAD_MUST_STOP, 65
ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED, 484	ER_SLAVE_CHANNEL_WAS_NOT_RUNNING, 65
ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE, 484	ER_SLAVE_CHANNEL_WAS_RUNNING, 65
ER_SLAVE_CONFIGURATION, 52	
ER_SLAVE_CONVERSION_FAILED, 44	
ER_SLAVE_CORRUPT_EVENT, 39	
ER_SLAVE_CREATE_EVENT_FAILURE, 455	
ER_SLAVE_FATAL_ERROR, 455	
ER_SLAVE_HAS_MORE_GTIDS_THAN_MASTER, 59	
ER_SLAVE_HEARTBEAT_FAILURE, 456	
ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE, 40	
ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX, 45	
ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN, 45	
ER_SLAVE_IGNORED_SSL_PARAMS, 20	
ER_SLAVE_IGNORED_TABLE, 18	
ER_SLAVE_INFORMATION_SERVER_IDS, 42	
ER_SLAVE INCIDENT, 456	
ER_SLAVE_KILLED_AFTER_RECONNECT, 243	
ER_SLAVE_MASTER_COM_FAILURE, 456	
ER_SLAVE_MAX_CHANNELS_EXCEEDED, 65	
ER_SLAVE_MI_INIT_REPOSITORY, 57	
ER_SLAVE_MULTIPLE_CHANNELS_CMD, 65	
ER_SLAVE_NEW_CHANNEL_WRONG_REPOSITORY, 64	
ER_SLAVE_NOT_RUNNING, 16	
ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS, 243	
ER_SLAVE_POSSIBLY_DIVERGED_AFTER_DDL, 96	
ER_SLAVE_RECONNECT_FAILED, 243	
ER_SLAVE_RELAY_LOG_PURGE_FAILED, 236	
ER_SLAVE_RELAY_LOG_READ_FAILURE, 456	
ER_SLAVE_RELAY_LOG_TRUNCATE_INFO, 236	
ER_SLAVE_RELAY_LOG_WRITE_FAILURE, 456	
ER_SLAVE_RLI_INIT_REPOSITORY, 58	
ER_SLAVE_SILENT_RETRY_TRANSACTION, 53	
ER_SLAVE_SQL_THREAD_MUST_STOP, 60	
ER_SLAVE_ANONYMOUS_TO_GTID_IS_LOCAL_OR_USER, 516	ER_SLAVE_SQL_THREAD_STOPPED_AFTER_GTIDS_REACHED, 170
ER_SLAVE_CANT_CREATE_CONVERSION, 44	ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS_ALREADY_STOPPED, 170
ER_SLAVE_CANT_USE_TEMPDIR, 196	ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS_REACHED, 170
ER_SLAVE_CHANGE_MASTER_TO_EXECUTED, 195	ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS_REACHED, 170
ER_SLAVE_CHANNEL_DOES_NOT_EXIST, 64	ER_SLAVE_SQL_THREAD_STOPPED_GAP_TRX_PROCESSED, 170
ER_SLAVE_CHANNEL_IO_THREAD_MUST_STOP, 60	ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_CONDITION_BA, 170
ER_SLAVE_CHANNEL_MUST_STOP, 65	ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_POSITION_REACHED, 170
ER_SLAVE_CHANNEL_NAME_INVALID_OR_TOO_LONG, 64	ER_SLAVE_THREAD, 16
ER_SLAVE_CHANNEL_OPERATION_NOT_ALLOWED, 69	ER_SLAVE_WORKER_STOPPED_PREVIOUS_THD_ERROR, 61

ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGERGED, 103	ER_GSTD_MODE_MERGED_WITH_STRICT_MODE, 231
ER_SPATIAL_CANT_HAVE_NULL, 19	ER_SQL_REPLICA_SKIP_COUNTER_USED_WITH_GTID_MODE, 128
ER_SPATIAL_FUNCTIONAL_INDEX, 100	ER_SQL_SLAVE_SKIP_COUNTER_NOT_SETTABLE_IN_GTID_MODE, 57
ER_SPATIAL_MUST_HAVE_GEOM_COL, 44	ER_SQL_SLAVE_SKIP_COUNTER_USED_WITH_GTID_MODE, 127
ER_SPATIAL_UNIQUE_INDEX, 96	ER_SQL_USER_TABLE_ALTER_WARNING, 155
ER_SPECIFIC_ACCESS_DENIED_ERROR, 17	ER_SQL_USER_TABLE_CREATE_WARNING, 155
ER_SPVAR_NONINTEGER_TYPE, 126	ER_SRS_ATTRIBUTE_STRING_TOO_LONG, 95
ER_SP_ALREADY_EXISTS, 22	ER_SRS_GEOGCS_INVALID_AXES, 97
ER_SP_BADRETURN, 23	ER_SRS_ID_ALREADY_EXISTS, 94
ER_SP_BADSELECT, 23	ER_SRS_INVALID_ANGLULAR_UNIT, 97
ER_SP_BADSTATEMENT, 23	ER_SRS_INVALID_CHARACTER_IN_ATTRIBUTE, 95
ER_SP_BAD_CURSOR_QUERY, 23	ER_SRS_INVALID_INVERSE_FLATTENING, 97
ER_SP_BAD_CURSOR_SELECT, 23	ER_SRS_INVALID_PRIME_MERIDIAN, 97
ER_SP_BAD_SQLSTATE, 28	ER_SRS_INVALID_SEMI_MAJOR_AXIS, 97
ER_SP_BAD_VAR_SHADOW, 31	ER_SRS_MISSING_MANDATORY_ATTRIBUTE, 94
ER_SP_CANT.Alter, 24	ER_SRS_MULTIPLE_ATTRIBUTE_DEFINITIONS, 94
ER_SP_CANT_SET_AUTOCOMMIT, 30	ER_SRS_NAME_CANT_BE_EMPTY_OR_WHITESPACE, 94
ER_SP_CASE_NOT_FOUND, 24	ER_SRS_NOT_CARTESIAN, 76
ER_SP_COND_MISMATCH, 23	ER_SRS_NOT_CARTESIAN_UNDEFINED, 76
ER_SP_CURSOR_AFTER_HANDLER, 24	ER_SRS_NOT_FOUND, 77
ER_SP_CURSOR_ALREADY_OPEN, 23	ER_SRS_NOT_GEOGRAPHIC, 96
ER_SP_CURSOR_MISMATCH, 23	ER_SRS_ORGANIZATION_CANT_BE_EMPTY_OR_WHITESPACE, 94
ER_SP_CURSOR_NOT_OPEN, 23	ER_SRS_PARSE_ERROR, 75
ER_SP_DOES_NOT_EXIST, 22	ER_SRS_PROJ_PARAMETER_MISSING, 75
ER_SP_DROP_FAILED, 22	ER_SR_BOGUS_VALUE, 152
ER_SP_DUP_COND, 24	ER_SR_INVALID_CONTEXT, 153
ER_SP_DUP_CURS, 24	ER_SSL_FIPS_MODE_ERROR, 269
ER_SP_DUP_HANDLER, 28	ER_SSL_LIBRARY_ERROR, 138
ER_SP_DUP_PARAM, 24	ER_SSL_MEMORY_INSTRUMENTATION_INIT_FAILED, 468
ER_SP_DUP_VAR, 24	ER_SSL_SERVER_CERT_VERIFY_FAILED, 487
ER_SP_FETCH_NO_DATA, 24	ER_SSL_TRYING_DATADIR_DEFAULTS, 150
ER_SP_LABEL_MISMATCH, 22	ER_STACKSIZE_UNEXPECTED, 149
ER_SP_LABEL_REDEFINE, 22	ER_STACK_OVERRUN, 11
ER_SP_LILABEL_MISMATCH, 22	ER_STACK_OVERRUN_NEED_MORE, 30
ER_SP_LOAD_FAILED, 75	ER_STARTING_AS, 143
ER_SP_NORETURN, 23	ER_STARTING_INIT, 461
ER_SP_NORETURNEND, 23	ER_STARTING_REPLICA_MONITOR_IO_THREAD, 127
ER_SP_NOT_VAR_ARG, 28	ER_STARTUP, 28
ER_SP_NO_AGGREGATE, 31	ER_STATEMENT_NOT_ALLOWED_AFTER_START_TRANSACTION, 123
ER_SP_NO_DROP_SP, 25	ER_STD_BAD_ALLOC_ERROR, 62
ER_SP_NO_RECursion, 29	ER_STD_DOMAIN_ERROR, 62
ER_SP_NO_RECURSIVE_CREATE, 22	ER_STD_INVALID_ARGUMENT, 63
ER_SP_NO_RETSET, 28	ER_STD_LENGTH_ERROR, 62
ER_SP_RECursion_LIMIT, 31	ER_STD_LOGIC_ERROR, 63
ER_SP_STORE_FAILED, 22	ER_STD_OUT_OF_RANGE_ERROR, 63
ER_SP_SUBSELECT_Nyi, 24	ER_STD_OVERFLOW_ERROR, 63
ER_SP_UNDECLARED_VAR, 24	
ER_SP_UNINIT_VAR, 23	
ER_SP_VARCOND_AFTER_CURSHNDLR, 24	
ER_SP_WRONG_NAME, 31	
ER_SP_WRONG_NO_OF_ARGS, 23	
ER_SP_WRONG_NO_OF_FETCH_ARGS, 24	
ER_SQLTHREAD_WITH_SECURE_SLAVE, 50	
ER_SQL_AUTHOR_DEFAULT_ROLES_FAIL, 155	
ER_SQL_HA_READ_FAILED, 152	
ER_SQL_MODE_MERGED, 69	

ER_STD_RANGE_ERROR, 63
ER_STD_REGEX_ERROR, 110
ER_STD_RUNTIME_ERROR, 63
ER_STD_UNDERFLOW_ERROR, 63
ER_STD_UNKNOWN_EXCEPTION, 63
ER_STMT_CACHE_FULL, 46
ER_STMT_HAS_NO_OPEN_CURSOR, 29
ER_STMT_NOT_ALLOWED_IN_SF_OR_TRG, 24
ER_STOP_REPLICA_MONITOR_IO_THREAD_TIMEOUT, 127
ER_STOP_SLAVE_IO_THREAD_DISK_SPACE, 269
ER_STOP_SLAVE_IO_THREAD_TIMEOUT, 58
ER_STOP_SLAVE_SQL_THREAD_TIMEOUT, 58
ER_STORAGE_ENGINE_NOT_LOADED, 59
ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_FORMAT_TABLE_DEF_CHANGED, 28
44
ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_FORMAT_HAS_NO_FT, 50
37
ER_STORED_FUNCTION_PREVENTS_SWITCH_SQL_L086_BIN,
45
ER_SUBPARTITION_ERROR, 34
ER_SUBPARTITION_NAME, 41
ER_SUBQUERY_NO_1_ROW, 18
ER_SUBQUERY_TRANSFORM_REJECTED, 122
ER_SWITCH_TMP_ENGINE, 80
ER_SYNTAX_ERROR, 13
ER_SYSTEMD_NOTIFY_CONNECT_FAILED, 331
ER_SYSTEMD_NOTIFY_PATH_TOO_LONG, 331
ER_SYSTEMD_NOTIFY_WRITE_FAILED, 331
ER_SYSTEM_SCHEMA_NOT_FOUND, 133
ER_SYSTEM_TABLES_NOT_SUPPORTED_BY_STORAGE_ENGINE, 233
210
ER_SYSTEM_TABLE_NOT_TRANSACTIONAL, 210
ER_SYSTEM_VIEW_INIT_FAILED, 234
ER_SYSVAR_CHANGE_DURING_QUERY, 116
ER_SYS_VAR_COMPONENT_FAILED_TO_MAKE_VARIABLE_ABLE, 269
ER_SYS_VAR_COMPONENT_FAILED_TO_PARSE_VARIABLE, 269
ER_SYS_VAR_COMPONENT_OOM, 268
ER_SYS_VAR_COMPONENT_UNKNOWN_VARIABLE_TYPE, 269
ER_SYS_VAR_COMPONENT_VARIABLE_SET_READ_ONLY, 269
ER_SYS_VAR_NOT_FOUND, 462
ER_TABLEACCESS_DENIED_ERROR, 12
ER_TABLENAME_NOT_ALLOWED_HERE, 19
ER_TABLESPACE_AUTO_EXTEND_ERROR, 35
ER_TABLESPACE_CANNOT_BE_DECRYPTED, 107
ER_TABLESPACE_CANNOT_BE_ENCRYPTED, 107
ER_TABLESPACE_CANNOT_ENCRYPT, 73
ER_TABLESPACE_DISCARDED, 53
ER_TABLESPACE DUP_FILENAME, 83
ER_TABLESPACE_ENGINE_MISMATCH, 87
ER_TABLESPACE_EXISTS, 53
ER_TABLESPACE_IS_NOT_EMPTY, 68
ER_TABLESPACE_MISSING, 53
ER_TABLESPACE_MISSING_WITH_NAME, 75
ER_TABLESPACE_TYPE_UNKNOWN, 108
ER_TABLES_DIFFERENT_METADATA, 48
ER_TABLE_CANT_HANDLE_AUTO_INCREMENT, 14
ER_TABLE_CANT_HANDLE_BLOB, 14
ER_TABLE_CANT_HANDLE_FT, 17
ER_TABLE_CANT_HANDLE_SPKEYS, 31
ER_TABLE_CHECK_INTACT, 151
ER_TABLE_CORRUPT, 58
ER_TABLE_CREATED_WITH_DIFFERENT_VERSION, 167
6RDTABLE_DEF_CHANGED, 28
ER_TABLE_EXISTS_ERROR, 6
ER_TABLE_INCOMPATIBLE_DECIMAL_FIELD, 1086_BIN,
166
ER_TABLE_IN_FK_CHECK, 47
ER_TABLE_IN_SYSTEM_TABLESPACE, 53
ER_TABLE_MUST_HAVE_A_VISIBLE_COLUMN, 129
116
ER_TABLE_MUST_HAVE_COLUMNS, 10
ER_TABLE_NAME, 41
ER_TABLE_NAME_CAUSES_TOO_LONG_PATH, 498
116
ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED, 498
498
ER_TABLE_NEEDS_DUMP_UPGRADE, 250
ER_TABLE_NEEDS_REBUILD, 46
ER_TABLE_NEEDS_UPGRADE, 31
10
ER_TABLE_NOT_LOCKED, 10
9
ER_TABLE_REFERENCED, 73
73
ER_TABLE_UPGRADE_REQUIRED, 232
ER_TABLE_VALUE_CONSTRUCTOR_CANNOT_HAVE_DEFAULT, 232
ER_TABLE_VALUE_CONSTRUCTOR_MUST_HAVE_COLUMN, 232
98
ER_TABLE_WRONG_KEY_DEFINITION, 167
108
ER_TARGET_TABLESPACE_UNENCRYPTED, 108
463
187
186
187
187
187
187
187

ER_TC_RECOVERING_AFTER_CRASH_USING,	ER_TOO_BIG_FIELDLENGTH, 8
186	ER_TOO_BIG_FOR_UNCOMPRESS, 19
ER_TC_RECOVERY_FAILED THESE_ARE_YOUR_OPTIONS,	ER_TOO_BIG_PRECISION, 29
187	ER_TOO_BIG_ROWSIZE, 11
ER_TC_RESTART_WITHOUT_TC_HEURISTIC_RECOVER,	ER_TOO_BIG_SCALE, 29
187	ER_TOO_BIG_SELECT, 10
ER_TEMPORARY_NAME, 41	ER_TOO_BIG_SET, 9
ER_TEMP_FILE_WRITE_FAILURE, 58	ER_TOO_HIGH_LEVEL_OF_NESTING_FOR_SELECT,
ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT,	98 ER_TOO_LONG_BODY, 30
98	ER_TOO_LONG_FIELD_COMMENT, 40
ER_TEMP_TABLE_PREVENTS_SWITCH_OUT_OF_RBR,	37 ER_TOO_LONG_IDENT, 7
ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG_FORMAT_INDEX_COMMENT,	98 44
98	ER_TOO_LONG_KEY, 8
ER_TEXTFILE_NOT_READABLE, 8	ER_TOO_LONG_ROUTINE_COMMENT, 75
ER_TF_FORBIDDEN_JOIN_TYPE, 90	ER_TOO_LONG_SET_ENUM_VALUE, 75
ER_TF_MUST_HAVE_ALIAS, 90	ER_TOO_LONG_STRING, 14
ER_THE_USER_ABIDES, 146	ER_TOO_LONG_TABLESPACE_COMMENT, 83
ER_THREAD_HANDLING_OOM, 140	ER_TOO_LONG_TABLE_COMMENT, 40
ER_THREAD_POOL_ALGORITHM_INVALID, 251	ER_TOO_LONG_TABLE_PARTITION_COMMENT,
ER_THREAD_POOL_BUFFER_TOO_SMALL, 253	52
ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC,	252 ER_TOO_MANY_CONCURRENT_CLONES, 86
ER_THREAD_POOL_CON_HANDLER_INIT_FAILED,	252 ER_TOO_MANY_CONCURRENT_TRXS, 41
252	ER_TOO_MANY_FIELDS, 11
ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT,	253 ER_TOO_MANY_KEYS, 7
253	ER_TOO_MANY_KEY_PARTS, 8
ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT,	253 ER_TOO_MANY_PARTITIONS_ERROR, 33
252	ER_TOO_MANY_PARTITION_FUNC_FIELDS_ERROR,
ER_THREAD_POOL_FAILED_TO_CREATE_POOL,	42
253	ER_TOO_MANY_ROWS, 14
ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_ABSTRACT,	253 ER_TOO_MANY_STORAGE_ENGINES, 156
ER_THREAD_POOL_INIT_FAILED, 252	ER_TOO_MANY_TABLES, 11
ER_THREAD_POOL_INVALID_PRIO_KICKUP_TIMER,	253 ER_TOO_MANY_USER_CONNECTIONS, 16
252	ER_TOO_MANY_VALUES_ERROR, 42
ER_THREAD_POOL_INVALID_STALL_LIMIT, 252	ER_TRACK_VARIABLES_BOGUS, 146
ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED,	252 ER_TRANSACTION_ROLLBACK_DURING_COMMIT,
253	66
ER_THREAD_POOL_MAX_UNUSED_THREADS_INVALID,	253 ER_TRANSFORM_SOURCE_SRS_MISSING_TOWGS84,
252	98
ER_THREAD_POOL_NOT_SUPPORTED_ON_PLATFORM,	251 ER_TRANSFORM_TARGET_SRS_MISSING_TOWGS84,
251	98
ER_THREAD_POOL_PFS_TABLES_ADD_FAILED,	472 ER_TRANSFORM_TARGET_SRS_NOT_SUPPORTED,
472	97
ER_THREAD_POOL_PFS_TABLES_INIT_FAILED,	472 ER_TRANSPORTS_WHAT_TRANSPORTS, 144
472	ER_TRANS_CACHE_FULL, 15
ER_THREAD_POOL_PLUGIN_STARTED, 252	ER_TREE_CORRUPT_2_CONSECUTIVE_RED,
ER_THREAD_POOL_RATE_LIMITED_ERROR_MSGS,	253 209
253	ER_TREE_CORRUPT_INCORRECT_BLACK_COUNT,
ER_THREAD_POOL_SIZE_TOO_HIGH, 251	209
ER_THREAD_POOL_SIZE_TOO_LOW, 251	ER_TREE_CORRUPT_PARENT_SHOULD_POINT_AT_PAR,
ER_THREAD_PRIORITY_IGNORED, 230	208
ER_TLS_CONFIGURATION_REUSE, 506	ER_TREE_CORRUPT_RIGHT_IS_LEFT, 209
ER_TLS_CONFIGURED_FOR_CHANNEL, 506	ER_TREE_CORRUPT_ROOT_SHOULD_BE_BLACK,
ER_TMPDIR_PATH_TOO_LONG, 513	208
ER_TOO_BIG_DISPLAYWIDTH, 30	ER_TRG_ALREADY_EXISTS, 25
ER_TOO_BIG_ENUM, 75	ER_TRG_CANT_CHANGE_ROW, 26

ER_TRG_CANT_OPEN_TABLE, 39
ER_TRG_CANT_PARSE, 151
ER_TRG_CORRUPTED_FILE, 39
ER_TRG_CREATION_CTX_NOT_SET, 232
ER_TRG_DOES_NOT_EXIST, 25
ER_TRG_INVALID_CREATION_CTX, 39
ER_TRG_IN_WRONG_SCHEMA, 30
ER_TRG_NO_CLIENT_CHARSET, 138
ER_TRG_NO_CREATION_CTX, 39
ER_TRG_NO_DEFINER, 31
ER_TRG_NO_SUCH_ROW_IN_TRG, 26
ER_TRG_ON_VIEW_OR_TEMP_TABLE, 26
ER_TRG_WITHOUT_DEFINER, 138
ER_TRG_WRONG_ORDER, 478
ER_TRHEAD_POOL_LOW_LEVEL_INIT_FAILED, 253
ER_TRIGGER_INVALID_VALUE, 132
ER_TRUNCATED_WRONG_VALUE, 21
ER_TRUNCATED_WRONG_VALUE_FOR_FIELD, 26
ER_TRUNCATE_ILLEGAL_FK, 45
ER_TRX_GTID_COLLECT_REJECT, 155
ER_TRX_WRITE_SET_OOM, 156
ER_TURNING_LOGGING_OFF_FOR_THE_DURATION, 85
225
ER_TURNING_ON_PARTIAL_REVOKES, 482
ER_TX_EXTRACTION_ALGORITHM_FOR_BINLOG_TX, 168
235
ER_TZ_CANT_BUILD_MKTIME_MAP, 169
ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE, 168
ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE, 168
ER_TZ_CANT_OPEN_AND_LOCK_TIME_ZONE_TABLE, 168
ER_TZ_ERROR_LOADING_LEAP_SECOND_TABLE, 168
ER_TZ_NO_TRANSITION_TYPES_IN_TIME_ZONE, 169
ER_TZ_OOM_INITIALIZING_TIME_ZONES, 168
ER_TZ_OOM_LOADING_LEAP_SECOND_TABLE, 168
ER_TZ_OOM_LOADING_TIME_ZONE_DESCRIPTION, 169
ER_TZ_OOM_WHILE_LOADING_TIME_ZONE, 170
ER_TZ_OOM_WHILE_SETTING_TIME_ZONE, 170
ER_TZ_TOO_MANY_LEAPS_IN_LEAP_SECOND_TABLE, 168
ER_TZ_TRANSITION_TABLE_BAD_TRANSITION_TYPE, 169
ER_TZ_TRANSITION_TABLE_LOAD_ERROR, 169
ER_TZ_TRANSITION_TABLE_TOO_MANY_TRANSITIONS, 169
ER_TZ_TRANSITION_TYPE_TABLE_ABBREVIATIONS, 169
ER_TZ_TRANSITION_TYPE_TABLE_LOAD_ERROR, 169
ER_TZ_TRANSITION_TYPE_TABLE_TYPE_TOO_LARGE, 169
ER_TZ_UNKNOWN_OR_ILLEGAL_DEFAULT_TIME_ZONE, 168
ER_UDF_ALREADY_EXISTS, 462
ER_UDF_CANT_ALLOC_FOR_FUNCTION, 154
ER_UDF_CANT_ALLOC_FOR_STRUCTURES, 154
ER_UDF_CANT_OPEN_FUNCTION_TABLE, 154
ER_UDF_DROP_DYNAMICALLY_REGISTERED, 85
ER_UDF_ERROR, 74
ER_UDF_EXISTS, 11
ER_UDF_INVALID_ROW_IN_FUNCTION_TABLE, 154
ER_UDF_NO_PATHS, 11
ER_UDF_REGISTER_ERROR, 512
ER_UDF_REGISTER_SERVICE_ERROR, 512
ER_UDF_UNREGISTER_ERROR, 512
ER_UNKNOWN_AUTH_ID_OR_ACCESS_DENIED_FOR_GRANT, 108
ER_UNABLE_TO_BUILD_HISTOGRAM, 85
ER_UNABLE_TO_COLLECT_LOG_STATUS, 95
ER_UNABLE_TO_DROP_COLUMN_STATISTICS, 85
ER_UNABLE_TO_RESOLVE_HOSTNAME, 137
ER_UNABLE_TO_RESOLVE_IP, 137
ER_UNABLE_TO_STORE_COLUMN_STATISTICS, 85
ER_UNABLE_TO_STORE_STATISTICS, 78
ER_UNABLE_TO_UPDATE_COLUMN_STATISTICS, 85
ER_UNDISCLOSED_PARSE_ERROR_IN_DIGEST_FN, 91
ER_UNDO_RECORD_TOO_BIG, 46
ER_UNEXPECTED_GEOMETRY_TYPE, 75
ER_UNIQUE_KEY_NEED_ALL_FIELDS_IN_PF, 34
ER_UNIT_NOT_FOUND, 115
ER_UNKNOWN ALTER_ALGORITHM, 52
ER_UNKNOWN ALTER_LOCK, 53
ER_UNKNOWN_AUTHID, 76
ER_UNKNOWN_AUTH_ID_IN_MANDATORY_ROLE, 237
ER_UNKNOWN_CHARACTER_SET, 11
ER_UNKNOWN_COLLATION, 20
ER_UNKNOWN_COM_ERROR, 6
ER_UNKNOWN_ERROR, 10
ER_UNKNOWN_ERROR_DETECTED_IN_SE, 243
ER_UNKNOWN_ERROR_NUMBER, 153
ER_UNKNOWN_EXPLAIN_FORMAT, 52
ER_UNKNOWN_KEY_CACHE, 21
ER_UNKNOWN_LOCALE, 42
ER_UNKNOWN_NETWORK_NAMESPACE, 486
ER_UNKNOWN_PARTITION, 48
ER_UNKNOWN PROCEDURE, 10
ER_UNKNOWN_STMT_HANDLER, 18
ER_UNKNOWN_STORAGE_ENGINE, 21
ER_UNKNOWN_SYSTEM_VARIABLE, 15

ER_UNKNOWN_TABLE, 10	ER_USER_REQUIRES_ROOT, 144
ER_UNKNOWN_TABLESPACE_TYPE, 468	ER_USER_WHAT_USER, 144
ER_UNKNOWN_TABLE_IN_UPGRADE, 492	ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTION_BLOCK, 128
ER_UNKNOWN_TARGET_BINLOG, 26	ER_UUID_INVALID, 139
ER_UNKNOWN_TIME_ZONE, 22	ER_UUID_IS, 139
ER_UNKNOWN_UNSUPPORTED_STORAGE_ENGINE, 139	ER_UUID_SALT, 139
ER_UNKNOWN_VARIABLE_IN_PERSISTED_CONFIG_FILE, 462	ER_VALGRIND_COUNT_LEAKS, 153
ER_UNRESOLVED_HINT_NAME, 68	ER_VALGRIND_DO_QUICK_LEAK_CHECK, 153
ER_UNRESOLVED_TABLE_LOCK, 79	ER_VALIDATE_PWD_CONVERT_TO_BUFFER_FAILED, 332
ER_UNSUPPORTED_LOG_ENGINE, 38	ER_VALIDATE_PWD_COULD_BE_NULL, 332
ER_UNSUPPORTED_ACTION_ON_DEFAULT_VAL_GENERATED, 101	ER_VALIDATE_PWD_DICT_FILE_NOT_LOADED, 335
ER_UNSUPPORTED_ACTION_ON_GENERATED_COLUMN, 67	ER_VALIDATE_PWD_DICT_FILE_NOT_SPECIFIED, 335
ER_UNSUPPORTED_ALTER_ENCRYPTION_INPLACE, 73	ER_VALIDATE_PWD_DICT_FILE_OPEN_FAILED, 335
ER_UNSUPPORTED_ALTER_INPLACE_ON_VIRTUAL_COLUMN, 67	ER_VALIDATE_PWD_DICT_FILE_TOO_BIG, 266
ER_UNSUPPORTED_ALTER_ONLINE_ON_VIRTUAL_COLUMN, 72	ER_VALIDATE_PWD_FAILED_TO_GET_FLD_FROM_SECURITY_CONTEXT, 266
ER_UNSUPPORTED_DATE, 143	ER_VALIDATE_PWD_FAILED_TO_GET_SECURITY_CTX, 266
ER_UNSUPPORTED_ENGINE, 47	ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE, 266
ER_UNSUPPORTED_EXTENSION, 10	ER_VALIDATE_PWD_LENGTH_CHANGED, 266
ER_UNSUPPORTED_INDEX_ALGORITHM, 74	ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED, 331
ER_UNSUPPORTED_PS, 22	ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED, 332
ER_UNSUPPORTED_SQL_MODE, 114	ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED, 332
ER_UNSUPPORTED_USE_OF_GRANT_AS, 108	ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED, 332
ER_UNSUPPORTED_COMPRESSED_TEMPORARY_TABLE, 74	ER_VALIDATE_PWD_STRING_HANDLER_MEM_ALLOCATE_FAILED, 332
ER_UNTIL_COND_IGNORED, 21	ER_VALIDATE_PWD_STRONG_POLICY_DICT_FILE_UNREGISTERED, 332
ER_UPDATE_GTIID_PURGED_WITH_GR, 116	ER_VALIDATE_PWD_VARIABLE_REGISTRATION_FAILED, 332
ER_UPDATE_INFO, 12	ER_VALIDATE_PWD_VARIABLE_UNREGISTRATION_FAILED, 332
ER_UPDATE_LOG_DEPRECATED_IGNORED, 23	ER_VARIABLE_IS_NOT_INT_TYPE_ERROR, 45
ER_UPDATE_LOG_DEPRECATED_TRANSLATED, 23	ER_VARIABLE_IS_NOT_STRUCT, 20
ER_UPDATE_TABLE_USED, 9	ER_VARIABLE_IS_READONLY, 40
ER_UPDATE_WITHOUT_KEY_IN_SAFE_MODE, 14	ER_VARIABLE_NOT_PERSISTED, 78
ER_UPDATING_DD_TABLE, 75	ER_VARIABLE_NOT_SETTABLE_IN_SP, 55
ER_UPGRADE_NONEXISTENT_SCHEMA, 513	ER_VARIABLE_NOT_SETTABLE_IN_TRANSACTION, 50
ER_UPGRADE_PARSE_ERROR, 467	ER_VAR_CANT_BE_READ, 18
ER_UPGRADE_WITH_PARTITIONED_TABLES_REJECTED, 493	ER_VAR_DOES_NOT_EXIST, 84
ER_USERNAME, 32	ER_VERBOSE_HINT, 146
ER_USERNAME_TRUNCATED, 507	ER_PRINCIPAL_NEEDS_RESET, 140
ER_USER_ACCESS_DENIED_FOR_USER_ACCOUNT, 120	ER_VIEW_CHECKSUM, 27
ER_USER_ALREADY_EXISTS, 71	ER_VIEW_CHECK_FAILED, 26
ER_USER_COLUMN_OLD_LENGTH, 73	
ER_USER_DOES_NOT_EXIST, 71	
ER_USER_LIMIT_REACHED, 17	
ER_USER_LOCK_DEADLOCK, 63	
ER_USER_LOCK_WRONG_NAME, 63	
ER_USER_NOT_IN_EXTRA_USERS_BINLOG_POSSIBLE, 165	
ER_USER_REFERENCED_AS_DEFINER, 126	

ER_VIEW_CREATION_CTX_NOT_SET, 232
ER_VIEW_DELETE_MERGE_VIEW, 27
ER_VIEW_FRM_NO_USER, 30
ER_VIEW_INVALID, 25
ER_VIEW_INVALID_CREATION_CTX, 39
ER_VIEW_MULTIUPDATE, 27
ER_VIEW_NONUPD_CHECK, 26
ER_VIEW_NO_CREATION_CTX, 39
ER_VIEW_NO_EXPLAIN, 25
ER_VIEW_NO_INSERT_FIELD_LIST, 27
ER_VIEW_OTHER_USER, 30
ER_VIEW_PREVENT_UPDATE, 30
ER_VIEW_RECURSIVE, 31
ER_VIEW_SELECT_CLAUSE, 25
ER_VIEW_SELECT_TMPTABLE, 25
ER_VIEW_SELECT_VARIABLE, 25
ER_VIEW_UNKNOWN_CHARSET_OR_COLLATION, 133
ER_VIEW_UNPARSABLE, 167
ER_VIEW_WRONG_LIST, 25
ER_VTOKEN_PLUGIN_TOKEN_MISMATCH, 69
ER_VTOKEN_PLUGIN_TOKEN_NOT_FOUND, 69
ER_WAITPID_FAILED, 248
ER_WARNING_AUTHCACHE_INVALID_USER_ATTRIBUTES, 474
ER_WARNING_DISCARD_OLD_PASSWORD_CLAUSE, 474
ER_WARNING_NOT_COMPLETE_ROLLBACK, 15
ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_CASCADE, 49
ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_DROP, 49
ER_WARNING_PASSWORD_HISTORY_CLAUSES_VOID, 87
ER_WARNING_RETAIN_CURRENT_PASSWORD_CLAUSE, 474
ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECON, 131
ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECON, 525
ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTA, 131
ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTA, 525
ER_WARN_ALLOWED_PACKET_OVERFLOWED, 22
ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAME, 129
ER_WARN_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN, 495
ER_WARN_BAD_MAX_EXECUTION_TIME, 68
ER_WARN_BINLOG_PARTIAL_UPDATES_DISABLED, 88
ER_WARN_BINLOG_PARTIAL_UPDATES_SUGGESTS_P, 88
ER_WARN_BINLOG_V1_ROW_EVENTS_DISABLED, 88
ER_WARN_CANT_DROP_DEFAULT_KEYCACHE, 30
ER_WARN_CLIENT_DEPRECATED_PARTITION_PREFIX_KEY, 122
ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_M, 518
ER_WARN_CONFLICTING_HINT, 68
ER_WARN_DATA_OUT_OF_RANGE, 20
ER_WARN_DATA_OUT_OF_RANGE_FUNCTIONAL_INDEX, 99
ER_WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX, 99
ER_WARN_DA_PRIVILEGE_NOT_REGISTERED, 117
ER_WARN_DEPRECATED_FLOAT_AUTO_INCREMENT, 110
ER_WARN_DEPRECATED_FLOAT_DIGITS, 110
ER_WARN_DEPRECATED_FLOAT_UNSIGNED, 110
ER_WARN_DEPRECATED_FOUND_ROWS, 121
ER_WARN_DEPRECATED_INNER_INTO, 121
ER_WARN_DEPRECATED_INTEGER_DISPLAY_WIDTH, 111
ER_WARN_DEPRECATED_JSON_TABLE_ON_ERROR_ON_E, 121
ER_WARN_DEPRECATED_NESTED_COMMENT_SYNTAX, 102
ER_WARN_DEPRECATED_SQLMODE, 65
ER_WARN_DEPRECATED_SQL_CALC_FOUND_ROWS, 121
ER_WARN_DEPRECATED_SQL_CALC_FOUND_ROWS, 21
ER_WARN_DEPRECATED_SYNTAX_NO_REPLACEMENT, 130
ER_WARN_DEPRECATED_SYNTAX_WITH_VER, 468
ER_WARN_DEPRECATED_SYSVAR_UPDATE, 65
ER_WARN_DEPRECATED_TLS_VERSION_FOR_CHANNEL, 522
ER_WARN_DEPRECATED_TLS_VERSION_FOR_CHANNEL_C, 130
ER_WARN_DEPRECATED_USER_SET_EXPR, 101
ER_WARN_DEPRECATED_UTF8MB3_CHARSET_OPTION, 468
ER_WARN_DEPRECATED_UTF8MB3_COLLATION, 102
ER_WARN_DEPRECATED_UTF8MB3_COLLATION_OPTION, 468
ER_WARN_DEPRECATED_UTF8MB3_COLLATION_OPTION, 468
ER_WARN_DEPRECATED_VALUES_FUNCTION_ALWAYS_NU, 468
ER_WARN_DEPRECATED_YEAR_UNSIGNED, 121
ER_WARN_DEPRECATED_YEAR_UNSIGNED, 111
ER_WARN_ENGINE_TRANSACTION_ROLLBACK, 40
ER_WARN_FIELD_RESOLVED, 20

ER_WARN_FUNC_INDEX_NOT_APPLICABLE,	ER_WARN_TRIGGER_DOESNT_HAVE_CREATED,
115	60
ER_WARN_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GETER_WARN_VARIABLE UNKNOWN_KEYRING_AWS_REGION,	494
524	494
ER_WARN_GTID_THRESHOLD_BREACH, 516	ER_WARN_UNKNOWN_QB_NAME, 68
ER_WARN_HOSTNAME_WONT_WORK, 21	ER_WARN_UNLOAD_THE_NOT_PERSISTED, 77
ER_WARN_HYPERGRAPH_EXPERIMENTAL, 125	ER_WARN_UNSUPPORTED_HINT, 75
ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTIONSON_UNSUPPORTED_MAX_EXECUTION_TIME,	68
482	68
ER_WARN_INDEX_NOT_APPLICABLE, 48	ER_WARN_USING_OTHER_HANDLER, 20
ER_WARN_INVALID_DB_RESTRICTIONS, 482	ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED,
ER_WARN_INVALID_HINT, 84	125
ER_WARN_INVALID_TIMESTAMP, 22	ER_WARN_VIEW_MERGE, 25
ER_WARN_I_S_SKIPPED_TABLE, 44	ER_WARN_VIEW_WITHOUT_KEY, 25
ER_WARN_LEGACY_SYNTAX_CONVERTED, 59	ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOG,
ER_WARN_LOG_DEPRECATED_PARTITION_PREFIX_484,	ER_WARN_WRONG_COMPRESSION_LEVEL_LOG,
504	140
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPTED,	ER_WASTEFUL_NET_BUFFER_SIZE, 140
494	494
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_HAVE_CARD_NOT_ALLOWED_FOR_MULTIADDRESS,	ER_WINDOW_DUPLICATE_NAME, 82
494	82
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_NEEDS_ERPLWINDOWRCFROLARITY_IN_WINDOW_GRAPH,	ER_WINDOW_EXPLAIN_JSON, 82
495	82
ER_WARN_NO_KEYRING_COMPONENT_SERVICE_FOERNDWINDOW_FRAME_END_ILLEGAL, 81	ER_WINDOW_FRAME_END_ILLEGAL, 81
518	81
ER_WARN_NO_SERVERID_SPECIFIED, 231	ER_WINDOW_FRAME_ILLEGAL, 81
ER_WARN_NULL_TO_NOTNULL, 20	ER_WINDOW_FRAME_START_ILLEGAL, 81
ER_WARN_ONLY_MASTER_LOG_FILE_NO_POS,	ER_WINDOW_FUNCTION_IGNORES_FRAME, 83
61	83
ER_WARN_ON MODIFYING_GTID_EXECUTED_TABLEER_WINDOW_ILLEGAL_ORDER_BY, 82	ER_WINDOW_INVALID_WINDOW_FUNC_ALIAS_USE,
69	82
ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO, 61	ER_WINDOW_INVALID_WINDOW_FUNC_USE, 82
61	82
ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR, 68	ER_WINDOW_NESTED_WINDOW_FUNC_USE_IN_WINDOW, 82
68	82
ER_WARN_PARTIAL_REVOKE_AND_DB_GRANT, 482	ER_WINDOW_NO_CHILD_PARTITIONING, 81
482	82
ER_WARN_PROPERTY_STRING_PARSE_FAILED, 477	ER_WINDOW_NO_GROUP_ORDER, 82
477	82
ER_WARN_PURGE_LOG_IN_USE, 57	ER_WINDOW_NO_GROUP_ORDER_UNUSED, 82
ER_WARN_PURGE_LOG_IS_ACTIVE, 57	ER_WINDOW_NO_INHERIT_FRAME, 81
ER_WARN_QC_RESIZE, 21	ER_WINDOW_NO_REDEFINE_ORDER_BY, 81
ER_WARN_REMOVED_SQL_MODE, 469	ER_WINDOW_NO SUCH_WINDOW, 80
ER_WARN_REPLICA_ANONYMOUS_TO_GTID_UUID_SAMEWINDOWRANGEGRANULE_NUMERIC_TYPE,	ER_WINDOW_RANGE_BOUND_NOT_CONSTANT, 82
524	82
ER_WARN_RESERVED_SRID_RANGE, 95	ER_WINDOW_RANGE_FRAME_ORDER_TYPE,
ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_MASTER_EOF,	83
496	83
ER_WARN_SQL_AFTER_MTS_GAPS_GAP_NOT_CALCULATED,	ER_WINDOW_RANGE_FRAME_TEMPORAL_TYPE,
131	83
ER_WARN_SRS_ID_ALREADY_EXISTS, 94	ER_WINDOW_ROWS_INTERVAL_USE, 82
ER_WARN_SRS_NOT_FOUND, 75	ER_WINDOW_SE_NOT_ACCEPTABLE, 83
ER_WARN_SRS_NOT_FOUND_AXIS_ORDER, 79	ER_WIN_LISTEN_BUT_HOW, 145
ER_WARN_TLS_CHANNEL_INITIALIZATION_ERROR, 505	ER_WIN_LOAD_LIBRARY_FAILED, 247
ER_WARN_TOO_FEW_RECORDS, 19	ER_WL9236_NOW_UNUSED, 83
ER_WARN_TOO_MANY_RECORDS, 19	ER_WRITEABLE_CONFIG_REMOVED, 142
	ER_WRITE_ROW_TO_PARTITION_FAILED, 237
	ER_WRITE_SET_EXCEEDS_LIMIT, 74
	ER_WRONG_ARGUMENTS, 16

ER_WRONG_AUTO_KEY, 8	ER_WRONG_TYPE_COLUMN_VALUE_ERROR, 42
ER_WRONG_COLUMN_NAME, 14	ER_WRONG_TYPE_FOR_COLUMN_PREFIX_IDX_FLD, 246
ER_WRONG_COMPRESSION_ALGORITHM_CLIENT, 117	ER_WRONG_TYPE_FOR_VAR, 18
ER_WRONG_COMPRESSION_LEVEL_CLIENT, 117	ER_WRONG_USAGE, 17
ER_WRONG_COUNT_FOR_KEY, 209	ER_WRONG_VALUE, 35
ER_WRONG_COUNT_FOR_ORIGIN, 209	ER_WRONG_VALUE_COUNT, 7
ER_WRONG_COUNT_OF_ELEMENTS, 209	ER_WRONG_VALUE_COUNT_ON_ROW, 12
ER_WRONG_DATETIME_SPEC, 142	ER_WRONG_VALUE_FOR_TYPE, 28
ER_WRONG_DB_NAME, 10	ER_WRONG_VALUE_FOR_VAR, 18
ER_WRONG_EXPR_IN_PARTITION_FUNC_ERROR, 33	ER_WRONG_VALUE_FOR_VAR_PLUS_ACTIONABLE_PART, 123
ER_WRONG_FIELD_SPEC, 7	ER_X509_CANT_CHMOD_KEY, 161
ER_WRONG_FIELD_TERMINATORS, 8	ER_X509_CANT_CREATE_CERT, 161
ER_WRONG_FIELD_WITH_GROUP, 7	ER_X509_CANT_READ_CA_CERT, 161
ER_WRONG_FIELD_WITH_GROUP_V2, 65	ER_X509_CANT_READ_CA_KEY, 161
ER_WRONG_FILE_NAME, 68	ER_X509_CANT_WRITE_CERT, 161
ER_WRONG_FK_DEF, 18	ER_X509_CANT_WRITE_KEY, 161
ER_WRONG_FK_OPTION_FOR_GENERATED_COLUMN, 67	ER_X509_CIPHERS_MISMATCH, 161
ER_WRONG_GROUP_FIELD, 7	ER_X509_ISSUER_MISMATCH, 161
ER_WRONG_JSON_TABLE_VALUE, 90	ER_X509_NEEDS_RSA_PRIVKEY, 161
ER_WRONG_KEY_COLUMN, 14	ER_X509_SUBJECT_MISMATCH, 161
ER_WRONG_KEY_COLUMN_FUNCTIONAL_INDEX, 100	ER_XAER_DUPID, 30
ER_WRONG_LOCK_OF_SYSTEM_TABLE, 29	ER_XAER_INVAL, 27
ER_WRONG_MRGR_TABLE, 14	ER_XAER_NOTA, 27
ER_WRONG_MVI_VALUE, 115	ER_XAER_OUTSIDE, 27
ER_WRONG_NAME_FOR_CATALOG, 21	ER_XAER_RMERR, 28
ER_WRONG_NAME_FOR_INDEX, 21	ER_XAER_RMFFAIL, 27
ER_WRONG_NATIVE_TABLE_STRUCTURE, 44	ER_XA_CANT_CREATE_MDL_BACKUP, 492
ER_WRONG_NUMBER_OF_COLUMNS_IN_SELECT, 17	ER_XA_COMMITTING_XID, 154
ER_WRONG_OBJECT, 25	ER_XA_IGNORENING_XID, 154
ER_WRONG_OUTER_JOIN, 11	ER_XA_NO_MULTI_2PC_HEURISTIC_RECOVER, 155
ER_WRONG_OUTER_JOIN_UNUSED, 11	ER_XA_RBDEADLOCK, 39
ER_WRONG_PARAMCOUNT_TO_NATIVE_FCT, 38	ER_XA_RBROLLBACK, 28
ER_WRONG_PARAMCOUNT_TO_PROCEDURE, 10	ER_XA_RBTIMEOUT, 39
ER_WRONG_PARAMETERS_TO_NATIVE_FCT, 38	ER_XA_RECOVERY_DONE, 155
ER_WRONG_PARAMETERS_TO_PROCEDURE, 10	ER_XA_RECOVER_EXPLANATION, 155
ER_WRONG_PARAMETERS_TO_STORED_FCT, 38	ER_XA_RECOVER_FOUND_TRX_IN_SE, 154
ER_WRONG_PARTITION_NAME, 37	ER_XA_RECOVER_FOUND_XA_TRX, 154
ER_WRONG_PERFSHEMA_USAGE, 44	ER_XA_REPLICATION_FILTERS, 114
ER_WRONG_SIZE_NUMBER, 35	ER_XA_RETRY, 73
ER_WRONG_SPVAR_TYPE_IN_LIMIT, 45	ER_XA_ROLLING_BACK_XID, 154
ER_WRONG_SRID_FOR_COLUMN, 87	ER_XA_STARTING_RECOVERY, 154
ER_WRONG_STRING_LENGTH, 32	ER_XPLUGIN_ALL_IO_INTERFACES_DISABLED, 274
ER_WRONG_SUB_KEY, 9	ER_XPLUGIN_BUFFER_PAGE_ALLOC_FAILED, 271
ER_WRONG_SUM_SELECT, 7	ER_XPLUGIN_CAPABILITY_CLIENT_INTERACTIVE_FAILED, 278
ER_WRONG_TABLESPACE_NAME, 68	ER_XPLUGIN_CAPABILITY_EXPIRED_PASSWORD, 277
ER_WRONG_TABLE_NAME, 10	ER_XPLUGIN_CLIENT_KILL_MSG, 276
	ER_XPLUGIN_CLIENT_RELEASE_TRIGGERED, 276
	ER_XPLUGIN_CLIENT_SSL_HANDSHAKE_FAILED, 273

ER_XPLUGIN_CLOSING_CLIENTS_ON_SHUTDOWN, 274
ER_XPLUGIN_COMPRESSION_ERROR, 494
ER_XPLUGIN_DETECTED_HANGING_CLIENTS, 271
ER_XPLUGIN_EMPTY_ADMIN_CMD, 277
ER_XPLUGIN_ERROR_MSG, 267
ER_XPLUGIN_ERROR_READING_SOCKET, 274
ER_XPLUGIN_ERROR_WRITING_TO_CLIENT, 274
ER_XPLUGIN_EXCEPTION_IN_EVENT_LOOP, 272
ER_XPLUGIN_EXCEPTION_IN_TASK_SCHEDULER, 272
ER_XPLUGIN_EXISTING_USER_ACCOUNT_WITH_INCORRECT_GRANT, 275
ER_XPLUGIN_FAILED_AT_SSL_CONF, 273
ER_XPLUGIN_FAILED_TO_ACCEPT_CLIENT, 271
ER_XPLUGIN_FAILED_TO_BIND_INTERFACE_ADDRESS, 506
ER_XPLUGIN_FAILED_TO_CLOSE_SQL_SESSION, 276
ER_XPLUGIN_FAILED_TO_CREATE_SESSION_FOR_CONN, 273
ER_XPLUGIN_FAILED_TO_EXECUTE_ADMIN_CMD, 277
ER_XPLUGIN_FAILED_TO_GET_CREATION_STMT, 277
ER_XPLUGIN_FAILED_TO_GET_ENGINE_INFO, 277
ER_XPLUGIN_FAILED_TO_GET_SECURITY_CTX, 276
ER_XPLUGIN_FAILED_TO_GET_SYS_VAR, 277
ER_XPLUGIN_FAILED_TO_INITIALIZE_SESSION, 273
ER_XPLUGIN_FAILED_TO_INTERRUPT_SESSION, 276
ER_XPLUGIN_FAILED_TO_OPEN_INTERNAL_SESSION, 277
ER_XPLUGIN_FAILED_TO_PREPARE_IO_INTERFACE, 271
ER_XPLUGIN_FAILED_TO_RESET_IPV6_V6ONLY_FLAG, 278
ER_XPLUGIN_FAILED_TO_SCHEDULE_CLIENT, 271
ER_XPLUGIN_FAILED_TO_SET_MIN_NUMBER_OF_WORKERS, 273
ER_XPLUGIN_FAILED_TO_SET_SO_REUSEADDR_FLAG, 277
ER_XPLUGIN_FAILED_TO_STOP_SERVICES, 455
ER_XPLUGIN_FAILED_TO_SWITCH_CONTEXT, 278
ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX, 467
ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX_THREADS, 276
ER_XPLUGIN_FAILED_TO_UNREGISTER_UDF, 278
ER_XPLUGIN_FAILED_TO_USE_SSL_CONF, 267
ER_XPLUGIN_FAILED_TO_VALIDATE_ADDRESS, 505
ER_XPLUGIN_FAIL_TO_GET_RESULT_DATA, 277
ER_XPLUGIN_FORCE_STOP_CLIENT, 271
ER_XPLUGIN_GET_PEER_ADDRESS FAILED, 278
ER_XPLUGIN_INVALID_AUTH_METHOD, 274
ER_XPLUGIN_INVALID_MSG_DURING_CLIENT_INIT, 274
ER_XPLUGIN_IPv6_AVAILABLE, 276
ER_XPLUGIN_LISTENER_SETUP_FAILED, 272
ER_XPLUGIN_LISTENER_STATUS_MSG, 275
ER_XPLUGIN_LISTENER_SYS_VARIABLE_ERROR, 275
ER_XPLUGIN_MAX_AUTH_ATTEMPTS_REACHED, 271
ER_XPLUGIN_MESSAGE_TOO_LONG, 273
ER_XPLUGIN_PEER_DISCONNECTED_WHILE_READING, 274
ER_XPLUGIN_READ_FAILED_CLOSING_CONNECTION, 274
ER_XPLUGIN_REFERENCE_TO_SECURE_CONN_WITH, 267
ER_XPLUGIN_REFERENCE_TO_USER_ACCOUNT_DOC, 272
ER_XPLUGIN_RETRYING_BIND_ON_PORT, 275
ER_XPLUGIN_SCHEDULER_STARTED, 274
ER_XPLUGIN_SCHEDULER_STOPPED, 275
ER_XPLUGIN_SERVER_EXITED, 266
ER_XPLUGIN_SERVER_EXITING, 266
ER_XPLUGIN_SERVER_STARTS_HANDLING_CONNECTION, 275
ER_XPLUGIN_SERVER_STOPPED_HANDLING_CONNECTION, 276
ER_XPLUGIN_SHUTDOWN_TRIGGERED, 275
ER_XPLUGIN_SRV_SESSION_INIT_THREAD_FAILED, 272
ER_XPLUGIN_SSL_HANDSHAKE_WITH_SERVER_FAILED, 273
ER_XPLUGIN_STARTUP_FAILED, 266
ER_XPLUGIN_TASK_SCHEDULING_FAILED, 272
ER_XPLUGIN_UNABLE_TO_ACCEPT_CONNECTION, 273
ER_XPLUGIN_UNEXPECTED_EXCEPTION_DISPATCHING, 272
ER_XPLUGIN_UNEXPECTED_MSG_DURING_AUTHENTICATION, 274
ER_XPLUGIN_UNINITIALIZED_MESSAGE, 273
ER_XPLUGIN_UNIX_SOCKET_NOT_CONFIGURED, 276
ER_XPLUGIN_USER_ACCOUNT_WITH_ALL_PERMISSIONS, 275
ER_XPLUGIN_USING_SSL_CONF_FROM_MYSQLX, 267

ER_XPLUGIN_USING_SSL_CONF_FROM_SERVER, ER_AGGREGATE_IN_ORDER_NOT_SELECT error code, 64
267
ER_XPLUGIN_USING_SSL_FOR_TLS_CONNECTIONER_AGGREGATE_ORDER_FOR_UNION error code, 61
267
ER_XPLUING_NET_STARTUP_FAILED, 272
ER_YES, 3
ER_ZLIB_Z_BUF_ERROR, 19
ER_ZLIB_Z_DATA_ERROR, 19
ER_ZLIB_Z_MEM_ERROR, 19
WARN_COND_ITEM_TRUNCATED, 41
WARN_DATA_TRUNCATED, 20
WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX, 99
WARN_NAMED_PIPE_ACCESS_EVERYONE, 59
WARN_NON_ASCII_SEPARATOR_NOT_IMPLEMENTER_ALTER_OPERATION_NOT_SUPPORTED_REASON_AUTOIN
41
WARN_NO_MASTER_INFO, 40
WARN_ON_BLOCKHOLE_IN_RBR, 57
WARN_OPTION_BELOW_LIMIT, 46
WARN_OPTION_IGNORED, 40
WARN_PLUGIN_BUSY, 40
WARN_UNENCRYPTED_TABLE_IN_ENCRYPTED_DB
107
WARN_UNSUPPORTED_ACL_TABLES_READ, 126
WARN_USELESS_SPATIAL_INDEX, 90
ER_ABORTING error code, 143
ER_ABORTING_CONNECTION error code, 13
ER_ABORTING_USER_CONNECTION error code, 231
ER_ACCESS_DENIED_CHANGE_USER_ERROR error code, 58
ER_ACCESS_DENIED_ERROR error code, 6
ER_ACCESS_DENIED_ERROR_WITHOUT_PASSWORD error code, 232
ER_ACCESS_DENIED_ERROR_WITH_PASSWORD error code, 232
ER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED
error code, 498
ER_ACCESS_DENIED_FOR_USER_ACCOUNT_LOCKED
error code, 232
ER_ACCESS_DENIED_NO_PASSWORD_ERROR error code, 45
ER_ACCOUNT_HAS BEEN LOCKED error code, 68
ER_ACL_OPERATION_FAILED error code, 74
ER_ACL_WRONG_OR_MISSING_ACL_TABLES_LOG error code, 489
ER_ADDRESSES_FOR_HOSTNAME_HEADER error code, 137
ER_ADDRESSES_FOR_HOSTNAME_LIST_ITEM error code, 137
ER_ADD_PARTITION_NO_NEW_PARTITION error code, 34
ER_ADD_PARTITION_SUBPART_ERROR error code, 34
ER_ADMIN_WRONG_MRG_TABLE error code, 32
ER_AES_INVALID_IV error code, 58
ER_AGGREGATE_ORDER_NON_AGG_QUERY error code, 61
ER_ALTER_CONSTRAINT_ENFORCEMENT_NOT_SUPPORTED error code, 119
ER_ALTER_FILEGROUP_FAILED error code, 36
ER_ALTER_INFO error code, 9
ER_ALTER_OPERATION_NOT_SUPPORTED error code, 56
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_CHANGE
error code, 56
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COLUMN
error code, 56
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COPY
error code, 56
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FK_CHE
error code, 56
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FK_REL
error code, 56
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FTS
error code, 56
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_GIS
error code, 63
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_HIDDEN
error code, 56
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NOPK
error code, 56
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NOT_N
error code, 57
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_PARTITION
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_PASSWORD_LOCK
ER_AMBIGUOUS_FIELD_TERM error code, 32
ER_ANONYMOUS_AUTH_ID_NOT_ALLOWED_IN_MANDATORY
error code, 237
ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME
error code, 128
ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW_CHANGE
error code, 131
ER_APPLIER_LOG_EVENT_VALIDATION_ERROR
error code, 86
ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_REQ
error code, 127
ER_ATTRIBUTE_IGNORED error code, 89
ER_AUDIT_API_ABORT error code, 71
ER_AUDIT_CANT_ABORT_COMMAND error code, 229
ER_AUDIT_CANT_ABORT_EVENT error code, 229
ER_AUDIT_LOG_CANNOT_GENERATE_PASSWORD
error code, 495
ER_AUDIT_LOG_CANNOT_READ_PASSWORD error
code, 489

ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD	ER_AUDIT_LOG_HAS_NOT_BEEN_INSTALLED error code, 493
error code, 489	
ER_AUDIT_LOG_CANNOT_SET_LOG_POLICY_WITH_HOST_NAME_INVALID_CHARACTER	ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER error code, 460
error code, 262	
ER_AUDIT_LOG_CANNOT_STORE_PASSWORD	ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIR error code, 262
error code, 489	
ER_AUDIT_LOG_COULD_NOT_CREATE_AES_KEY	ER_AUDIT_LOG_INSUFFICIENT_PRIVILEGE error code, 116
error code, 460	
ER_AUDIT_LOG_COULD_NOT_OPEN_FILE_FOR_READING	ER_AUDIT_LOG_INVALID_FILE_CONTENT error code, 488
error code, 488	
ER_AUDIT_LOG_EC_WRITER_FAILED_TO_CREATE_FILTER	ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED error code, 459
error code, 263	
ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_COMPRESSION	ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXIST error code, 461
error code, 263	
ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_ENCRYPTION	ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE_EMPTY error code, 459
error code, 263	
ER_AUDIT_LOG_ENCRYPTION_PASSWORD_CANNOT_BE_CHANGED	ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR error code, 459
error code, 460	
ER_AUDIT_LOG_ENCRYPTION_PASSWORD_HAS_NOTEENDED	ER_AUDIT_LOG_JSON_READER_BUF_TOO_SMALL error code, 264
error code, 460	
ER_AUDIT_LOG_FILE_AUTO_PRUNED	ER_AUDIT_LOG_JSON_READER_FAILED_TO_OPEN_FILE error code, 264
error code, 518	
ER_AUDIT_LOG_FILE_HAS_BEEN_SUCCESSFULLY_PRUNED	ER_AUDIT_LOG_JSON_READER_FAILED_TO_PARSE error code, 264
error code, 488	
ER_AUDIT_LOG_FILE_NAME_DOES_NOT_HAVE_REQUIRED_FORMAT	ER_AUDIT_LOG_JSON_READER_FILE_PARSING_ERROR error code, 264
error code, 488	
ER_AUDIT_LOG_FILE_NAME_KEYRING_ID_VALUE_IS_INVALID	ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY error code, 460
error code, 488	
ER_AUDIT_LOG_FILE_NAME_TIMESTAMP_VALUE_IS_INVALID	ER_AUDIT_LOG_KEYRING_ID_TIMESTAMP_VALUE_IS_INVALID error code, 488
error code, 488	
ER_AUDIT_LOG_FILE_PRUNE_FAILED	ER_AUDIT_NO_KEYRING_PLUGIN_INSTALLED error code, 460
error code, 518	
ER_AUDIT_LOG_FILTER_FAILED_TO_CLOSE_TABLE	ER_AUDIT_READONLYONLY_INCLUDE_LIST_USED error code, 262
error code, 265	
ER_AUDIT_LOG_FILTER_FAILED_TO_DELETE_FROM_TABLE	ER_AUDIT_LOG_PASSWORD_HAS BEEN_COPIED error code, 489
error code, 265	
ER_AUDIT_LOG_FILTER_FAILED_TO_INIT_TABLE_FOR_RERENAME	ER_AUDIT_LOG_RENAME_LOG_FILE_BEFORE_FLUSH error code, 263
error code, 265	
ER_AUDIT_LOG_FILTER_FAILED_TO_INSERT_INTO_TABLE	ER_AUDIT_LOG_SUPER_PRIVILEGE_REQUIRED error code, 492
error code, 265	
ER_AUDIT_LOG_FILTER_FAILED_TO_READ_TABLE	ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST error code, 262
error code, 265	
ER_AUDIT_LOG_FILTER_FAILED_TO_STORE_TABLE	ER_AUDIT_LOG_TABLE_DEFINITION_NOT_UPDATED error code, 461
error code, 264	
ER_AUDIT_LOG_FILTER_FAILED_TO_UPDATE_TABLE	ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE error code, 460
error code, 264	
ER_AUDIT_LOG_FILTER_FLD_FILTERNAME_CANNOT_BE_EMPTY	ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_COUNT error code, 493
error code, 265	
ER_AUDIT_LOG_FILTER_INVALID_COLUMN_COUNT	ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_TYPE error code, 492
error code, 264	
ER_AUDIT_LOG_FILTER_INVALID_COLUMN_DEFINITION	ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH error code, 493
error code, 264	
ER_AUDIT_LOG_FILTER_IS_NOT_INSTALLED	ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH error code, 74
error code, 262	
ER_AUDIT_LOG_FILTER_RESULT_MSG	ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALL error code, 460
error code, 264	
ER_AUDIT_LOG_FILTER_USER_AND_HOST_CANNOT_BE_EMPTY	ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER error code, 459
error code, 265	

ER_AUDIT_LOG_WRITER_DEST_FILE_ALREADY_EXISTS AUTHCACHE_USER_TABLE_DODGY error code, 163
error code, 263
ER_AUDIT_LOG_WRITER_FAILED_TO_WRITE_TO_FILER_AUTH_CANT_ACTIVATE_ROLE error code, 161
error code, 263 ER_AUTH_CANT_CREATE_RSA_PAIR error code,
ER_AUDIT_LOG_WRITER_INCOMPLETE_FILE_RENAME~~ER~~
error code, 263 ER_AUTH_CANT_SET_DEFAULT_PLUGIN error
code, 149
ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED
error code, 263 ER_AUTH_CANT_WRITE_PRIVKEY error code, 162
error code, 263 ER_AUTH_CERTS_SAVED_TO_DATADIR error code,
ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT~~ER~~
error code, 167 ER_AUTH_CERT_GENERATION_DISABLED error
code, 162
ER_AUDIT_PLUGIN_HAS_INVALID_DATA error code, 168 ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_R
error code, 481
ER_AUDIT_WARNING error code, 229 ER_AUTH_KERBEROS_LOGGER_GENERIC_MSG
error code, 525
ER_AUTHCACHE_CANT_INIT_GRANT_SUBSYSTEM
error code, 165 ER_AUTH_TABLESKEYS_SAVED_TO_DATADIR error code, 162
error code, 164
ER_AUTHCACHE_DB_ENTRY_LOWERCASED_REVOKER~~ER~~
error code, 164 ER_AUTH_KEY_GENERATION_DISABLED error
code, 163
ER_AUTHCACHE_DB_IGNORED_EMPTY_NAME
error code, 164 ER_AUTH_KEY_GENERATION_SKIPPED_PAIR_PRESENT
error code, 162
ER_AUTHCACHE_DB_SKIPPED_NEEDS_RESOLVE
error code, 164 ER_AUTH_LDAP_ERROR_LOGGER_ERROR_MSG
error code, 268
ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPT~~ER~~
error code, 507 ER_AUTH_RSA_CANT_FIND error code, 160
ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTH~~ER~~
error code, 507 ER_AUTH_RSA_CANT_PARSE error code, 160
ER_AUTHCACHE_EXPIRED_PASSWORD_UNSUPPORTED~~ER~~
error code, 164 ER_AUTH_RSA_FILES_NOT_FOUND error code, 160
ER_AUTHCACHE_PLUGIN_CONFIG error code, 163 ER_AUTH_SSL_CONF_PREVENTS_CERT_GENERATION
error code, 163 error code, 162
ER_AUTHCACHE_PROCS_PRIV_ENTRY_IGNORED_BA~~ER~~
error code, 165 ER_AUTOINC_READ_FAILED error code, 32
ER_AUTHCACHE_PROCS_PRIV_SKIPPED_NEEDS_RES~~ER~~
error code, 165 ER_AUTO_INCREMENT_CONFLICT error code, 57
ER_AUTHCACHE_PROXY_PRIV_SKIPPED_NEEDS~~ER~~
error code, 163 ER_AUTO_POSITION_OPTIONS_FAILED error code, 150
ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAM
error code, 507 ER_BACK_IN_TIME error code, 143
ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTH~~ER~~
error code, 507 ER_BAD_FIELD_ERROR error code, 7
ER_AUTHCACHE_ROLE_TABLES_DODGY error
code, 163 ER_BAD_FT_COLUMN error code, 21
ER_AUTHCACHE_TABLES_PRIV_SKIPPED_NEEDS~~ER~~
error code, 165 ER_BAD_HOST_ERROR error code, 5
ER_AUTHCACHE_TABLE_PROXY_PRIV_MISSING
error code, 164 ER_BAD_LOG_STATEMENT error code, 38
ER_AUTHCACHE_USER_IGNORED_DEPRECATED_PAS~~ER~~
error code, 163 ER_BAD_NULL_ERROR error code, 6
ER_AUTHCACHE_USER_IGNORED_INVALID_PASSWORD~~ER~~
error code, 164 ER_BAD_SLAVE_UNTIL_COND error code, 20
ER_AUTHCACHE_USER_IGNORED_NEEDS_PLUGIN
error code, 163 ER_BAD_TABLE_ERROR error code, 6
ER_AUTHCACHE_USER_SKIPPED_NEEDS_RESOLVE~~ER~~
error code, 163 ER_BEFORE_DML_VALIDATION_ERROR error code, 66
ER_BEG_INITFILE error code, 145

ER_BINLOG_ATTACHING_THREAD_MEMORY_FINALLY_FAILED	ER_BINLOG_EVENTS_READ_FROM_RELAY_LOG_INFO error code, 221
ER_BINLOG_CACHE_SIZE_GREATER_THAN_MAX error code, 48	ER_BINLOG_EVENT_WRITE_TO_STMT_CACHE_FAILED error code, 236
ER_BINLOG_CACHE_SIZE_TOO_LARGE error code, 230	ER_BINLOG_EXPIRAY_LOG_DAYS_AND_SECS_USED_TOO_GREAT error code, 249
ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX error code, 222	ER_BINLOG_EXPIRE_LOG_DAYS_AND_SECS_USED_TOO_GREAT error code, 91
ER_BINLOG_CANT_CLEAR_IN_USE_FLAG_FOR_CRASHED_BINLOG error code, 225	ERBINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE_REBUILD error code, 221
ER_BINLOG_CANT_CLOSE_TMP_INDEX error code, 223	ERBINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REBUILD error code, 221
ER_BINLOG_CANT_COPY_INDEX_TO_TMP error code, 223	ERBINLOG_FAILED_TO_DELETE_LOG_FILE error code, 224
ER_BINLOG_CANT_CREATE_CACHE_FOR_LOG error code, 220	ERBINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBUILD error code, 222
ER_BINLOG_CANT_DELETE_FILE error code, 222	ERBINLOG_FAILED_TO_OPEN_REGISTER_FILE error code, 224
ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG error code, 224	ERBINLOG_FAILED_TO_OPEN_TEMPORARY_INDEX_FILE error code, 225
ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX_ERROR_CODE_F22S error code, 224	ERBINLOG_FAILED_TO_READ_REGISTER_FILE error code, 224
ER_BINLOG_CANT_FIND_LOG_IN_INDEX error code, 224	ERBINLOG_FAILED_TO_REINIT_REGISTER_FILE error code, 224
ER_BINLOG_CANT_GENERATE_NEW_FILE_NAME error code, 221	ERBINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_REBUILD error code, 221
ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAYLOG_FILE error code, 222	ERBINLOG_FAILED_TO_RUN_AFTER_FLUSH_HOOK error code, 225
ER_BINLOG_CANT_MOVE_TMP_TO_INDEX error code, 223	ERBINLOG_FAILED_TO_RUN_AFTER_SYNC_HOOK error code, 225
ER_BINLOG_CANT_OPEN_CRASHED_BINLOG error code, 225	ERBINLOG_FAILED_TO_SET_PURGE_INDEX_FILE_NAME error code, 224
ER_BINLOG_CANT_OPEN_FOR_LOGGING error code, 220	ERBINLOG_FAILED_TO_SYNC_INDEX_FILE error code, 220
ER_BINLOG_CANT_OPEN_LOG error code, 220	ERBINLOG_FAILED_TO_SYNC_INDEX_FILE_IN_OPEN error code, 221
ER_BINLOG_CANT_OPEN_TMP_INDEX error code, 222	ERBINLOG_FAILED_TO_WRITE_DROP_FOR_TEMP_TABLE error code, 210
ER_BINLOG_CANT_RESIZE_CACHE error code, 219	ERBINLOG_FATAL_ERROR error code, 39
ER_BINLOG_CANT_SET_TMP_INDEX_NAME error code, 222	ERBINLOG_FILE_BEING_READ_NOT_PURGED error code, 219
ER_BINLOG_CANT_TRIM_CRASHED_BINLOG error code, 225	ERBINLOG_FILE_EXTENSION_NUMBER_EXHAUSTED error code, 220
ER_BINLOG_CANT_USE_FOR_LOGGING error code, 221	ERBINLOG_FILE_EXTENSION_NUMBER_RUNNING_LOW error code, 220
ER_BINLOG_CRASHED_BINLOG_TRIMMED error code, 225	ERBINLOG_FILE_NAME_TOO_LONG error code, 220
ER_BINLOG_CRASH_RECOVERY_FAILED error code, 226	ERBINLOG_FILE_OPEN_FAILED error code, 236
ER_BINLOG_CREATE_ROUTINE_NEED_SUPER error code, 29	ERBINLOG_IO_ERROR_READING_HEADER error code, 219
ER_BINLOG_END error code, 143	ERBINLOG_LOGGING_IMPOSSIBLE error code, 39
ER_BINLOG_ERROR_GETTING_NEXT_LOG_FROM_INNODB_BINLOG_LOGGING INCIDENT_TO_STOP_SLAVES error code, 222	ERBINLOG_LOGGING_INCIDENT_TO_STOP_SLAVES error code, 224
ER_BINLOG_ERROR_READING_GTIDS_FROM_BINARYLOG error code, 221	ERBINLOG_LOGGING_NOT_POSSIBLE error code, 249
ER_BINLOG_ERROR_READING_GTIDS_FROM_RELAYLOG error code, 220	ERBINLOG_LOGICAL_CORRUPTION error code, 57
ER_BINLOG_EVENTS_READ_FROM_BINLOG_INFO error code, 221	ERBINLOG_MALFORMED_OR_OLD_RELAY_LOG error code, 249

ER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATIONS_UNSAFE_ACL_TABLE_READ_IN_DML_DDL
error code, 105
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEAR_BINLOG_UNSAFE_AND_STMT_ENGINE error
error code, 105
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEAR_BINLOG_UNSAFE_AUTOINC_COLUMNS error
error code, 105
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_OPERATE_BINLOG_UNSAFE_AUTOINC_NOT_FIRST error
error code, 105
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_RESET_BINLOG_UNSAFE_CREATE_IGNORE_SELECT
error code, 105
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_RESET_BINLOG_UNSAFE_CREATE_REPLACE_SELECT
error code, 105
ER_BINLOG_MULTIPLE_ENGINES_AND_SELF_LOGGING_UNSAFE_CREATE_SELECT_AUTOINC
error code, 43
ER_BINLOG_NEEDS_SERVERID error code, 148
ER_BINLOG_OOM_WRITING_DELETE_WHILE_OPENING_TABLE
error code, 210
ER_BINLOG_PURGE_EMFILE error code, 38
ER_BINLOG_PURGE_FATAL_ERR error code, 26
ER_BINLOG_PURGE_LOGS_CALLED_WITH_FILE_NOT_FOUND
error code, 223
ER_BINLOG_PURGE_LOGS_CANT_COPY_TO_REGISTERED_FILE
error code, 223
ER_BINLOG_PURGE_LOGS_CANT_FLUSH_REGISTERED_FILE
error code, 223
ER_BINLOG_PURGE_LOGS_CANT_UPDATE_INDEX_FILE
error code, 223
ER_BINLOG_PURGE_LOGS_FAILED_TO_PURGE_LOGGER_BINLOG_UNSAFE_MULTIPLE_ENGINES_AND_SELF_LOGGING
error code, 223
ER_BINLOG_PURGE_PROHIBITED error code, 26
ER_BINLOG_RECOVERING_AFTER_CRASH_USING
error code, 225
ER_BINLOG_ROW_ENGINE_AND_STMT_ENGINE
error code, 42
ER_BINLOG_ROW_INJECTION_AND_STMT_ENGINE
error code, 43
ER_BINLOG_ROW_INJECTION_AND_STMT_MODE
error code, 43
ER_BINLOG_ROW_LOGGING_FAILED error code, 36
ER_BINLOG_ROW_MODE_AND_STMT_ENGINE
error code, 42
ER_BINLOG_ROW_VALUE_OPTION_IGNORED error
code, 454
ER_BINLOG_ROW_VALUE_OPTION_USED_ONLY_FOREIGN
error code, 454
ER_BINLOG_STMT_CACHE_SIZE_GREATER_THAN_MAX
error code, 48
ER_BINLOG_STMT_CACHE_SIZE_TOO_LARGE
error code, 230
ER_BINLOG_STMT_MODE_AND_NO_REPL_TABLES
error code, 56
ER_BINLOG_STMT_MODE_AND_ROW_ENGINE
error code, 43
ER_BINLOG_UNABLE_TO_ROTATE_GTID_TABLE_REUSE_BLOBS_AND_NO_TERMINATED error code, 8
error code, 485

error code, 127
code, 43
code, 43
code, 47
error code, 46
error code, 47
error code, 47
ER_BINLOG_UNSAFE_DEFAULT_EXPRESSION_IN_SUBSTATEMENT
error code, 148
ER_BINLOG_UNSAFE_FULLTEXT_PLUGIN error
code, 59
ER_BINLOG_UNSAFE_INSERT_IGNORE_SELECT
error code, 230
ER_BINLOG_UNSAFE_INSERT_SELECT_UPDATE
error code, 230
ER_BINLOG_UNSAFE_INSERT_TWO_KEYS error
code, 47
ER_BINLOG_UNSAFE_LIMIT error code, 43
ER_BINLOG_UNSAFE_MESSAGE_AND_STATEMENT
error code, 230
ER_BINLOG_UNSAFE_MIXED_STATEMENT error
code, 45
error code, 45
ER_BINLOG_UNSAFE_NONTRANS_AFTER_TRANS
error code, 43
ER_BINLOG_UNSAFE_NOWAIT error code, 80
ER_BINLOG_UNSAFE_REPLACE_SELECT error
code, 46
ER_BINLOG_UNSAFE_ROUTINE error code, 29
ER_BINLOG_UNSAFE_SKIP_LOCKED error code, 79
ER_BINLOG_UNSAFE_STATEMENT error code, 39
ER_BINLOG_UNSAFE_SYSTEM_FUNCTION error
code, 43
ER_BINLOG_UNSAFE_SYSTEM_TABLE error code,
43
ER_BINLOG_UNSAFE_SYSTEM_VARIABLE error
code, 43
ER_BINLOG_UNSAFE_UDF error code, 43
ER_BINLOG_UNSAFE_UPDATE_IGNORE error code,
43
ER_BINLOG_UNSAFE_WRITE_AUTOINC_SELECT
error code, 47
ER_BINLOG_UNSAFE_XA error code, 74
ER_BINLOG_USE_V1_ROW_EVENTS_IGNORED
error code, 454
ER_BINLOG_WARNING_SUPPRESSED error code,
226
ER_BLOB_CANT_HAVE_DEFAULT error code, 10

ER_BLOB_FIELD_IN_PART_FUNC_ERROR error code, 34	ER_CANNOT_SET_SERVER_VERSION_IN_TABLESPACE_H error code, 478
ER_BLOB_KEY_WITHOUT_LENGTH error code, 14	ER_CANNOT_SET_TABLESPACE_ENCRYPTION error code, 107
ER_BLOB_USED_AS_KEY error code, 8	ER_CANNOT_SET_TABLE_ENCRYPTION error code, 107
ER_BOOST_GEOMETRY_CENTROID_EXCEPTION error code, 62	ER_CANNOT_USER error code, 27
ER_BOOST_GEOMETRY_EMPTY_INPUT_EXCEPTION error code, 62	ER_CANNOT_USER_REFERENCED_AS_DEFINER error code, 126
ER_BOOST_GEOMETRY_INCONSISTENT_TURNS_EXCEPTION error code, 68	ER_CANNOT_USE_AUTOEXTEND_SIZE_CLAUSE error code, 129
ER_BOOST_GEOMETRY_OVERLAY_INVALID_INPUT_EXCEPTION error code, 62	ER_CANNOT_USE_ENCRYPTION_CLAUSE error code, 130
ER_BOOST_GEOMETRY_SELF_INTERSECTION_POINT_EXCEPTION error code, 62	ER_CANT_ACCESS_CAPATH error code, 150
ER_BOOST_GEOMETRY_TURN_INFO_EXCEPTION error code, 62	ER_CANT_AGGREGATE_2COLLATIONS error code, 20
ER_BOOST_GEOMETRY_UNKNOWN_EXCEPTION error code, 62	ER_CANT_AGGREGATE_3COLLATIONS error code, 20
ER_BOOTSTRAP_CANT_THREAD error code, 132	ER_CANT_AGGREGATE_NCOLLATIONS error code, 20
ER_BUFPOOL_RESIZE_INPROGRESS error code, 71	ER_CANT_CHANGE_GAFTID_ANONYMOUS_OBJECT error code, 214
ER_CACHING_SHA2_PASSWORD_SECOND_PASSWORD_CANT_ANONYMOUS_OBJECT error code, 475	ER_CANT_CHANGE_TX_CHARACTERISTICS error code, 37
ER_CALL_ME_LOCALHOST error code, 144	ER_CANT_CHECK_PID_PATH error code, 331
ER_CANNOT_ADD_FOREIGN error code, 17	ER_CANT_CHOWN_DATADIR error code, 149
ER_CANNOT_ADD_FOREIGN_BASE_COL_STORED error code, 73	ER_CANT_COMBINE_ANONYMOUS_TO_GTID_AND_AUTOP
ER_CANNOT_ADD_FOREIGN_BASE_COL_VIRTUAL error code, 72	error code, 127
ER_CANNOT_ALTER_SRID_DUE_TO_INDEX error code, 87	ER_CANT_CREATE_ADMIN_THREAD error code, 474
ER_CANNOT_CHANGE_TO_ROOT_DIR error code, 234	ER_CANT_CREATE_CACHE_FOR_DB_OPT error code, 215
ER_CANNOT_CONVERT_STRING error code, 110	ER_CANT_CREATE_DB error code, 3
ER_CANNOT_CREATE_VIRTUAL_INDEX_CONSTRAINT error code, 72	ER_CANT_CREATE_FILE error code, 3
ER_CANNOT_DISCARD_TEMPORARY_TABLE error code, 60	ER_CANT_CREATE_GEOMETRY_OBJECT error code, 28
ER_CANNOT_DROP_COLUMN_FUNCTIONAL_INDEX error code, 99	ER_CANT_CREATE_HANDLER_FILE error code, 34
ER_CANNOT_FIND_KEY_IN_KEYRING error code, 73	ER_CANT_CREATE_HANDLER_OBJECT_FOR_TABLE error code, 214
ER_CANNOT_GET_SERVER_VERSION_FROM_TABLE error code, 477	ER_CANT_CREATE_HANDLE_MGR_THREAD error code, 135
ER_CANNOT_GRANT_ROLES_TO_ANONYMOUS_USER error code, 112	ER_CANT_CREATE_INTERRUPT_THREAD error code, 136
ER_CANNOT_GRANT_SYSTEM_PRIV_TO_MANDATORY error code, 114	ER_CANT_CREATE_NAMED_PIPES_THREAD error code, 142
ER_CANNOT_LOAD_FROM_TABLE_V2 error code, 47	ER_CANT_CREATE_PID_FILE error code, 141
ER_CANNOT_LOCK_USER_MANAGEMENT_CACHES error code, 77	ER_CANT_CREATE_SCHEDULER_THREAD error code, 136
ER_CANNOT_LOG_PARTIAL_DROP_DATABASE_WITH_TRANSACTION error code, 65	ER_CANT_CREATE_SHM_THREAD error code, 142
ER_CANNOT_SET_DATABASE_ENCRYPTION error code, 107	ER_CANT_CREATE_SHUTDOWN_THREAD error code, 141
ER_CANNOT_SET_LOG_ERROR_SERVICES error code, 235	ER_CANT_CREATE_TABLE error code, 3
	ER_CANT_CREATE_TABLE_SHARE_FROM_FRM error code, 213
	ER_CANT_CREATE_TCPIP_THREAD error code, 142
	ER_CANT_CREATE_TEST_FILE error code, 140
	ER_CANT_CREATE_THREAD error code, 12
	ER_CANT_CREATE_USER_WITH_GRANT error code, 28

ER_CANT_CREATE_UUID error code, 139
ER_CANT_DETACH_SESSION_LEFT_BY_PLUGIN error code, 181
ER_CANT_DO_IMPLICIT_COMMIT_IN_TRX_WHEN_GTID_NEXT_IS_996ET error code, 51
ER_CANT_DO_THIS_DURING_AN_TRANSACTION error code, 15
ER_CANT_DROP_FIELD_OR_KEY error code, 9
ER_CANT_ENFORCE_GTID_CONSISTENCY_WITH_ONGOING_GTID_VIOLATING_TX error code, 67
ER_CANT_EXECUTE_IN_READ_ONLY_TRANSACTION error code, 52
ER_CANT_FIND_DL_ENTRY error code, 11
ER_CANT_FIND_SYSTEM_REC error code, 4
ER_CANT_FIND_UDF error code, 11
ER_CANT_GET_STAT error code, 4
ER_CANT_HASH_DO_AND_IGNORE_RULES error code, 149
ER_CANT_IDENTIFY_CHARSET_USING_DEFAULT error code, 215
ER_CANT_INCREASE_MAX_OPEN_FILES error code, 145
ER_CANT_INITIALIZE_BUILTIN_PLUGINS error code, 148
ER_CANT_INITIALIZE_DYNAMIC_PLUGINS error code, 148
ER_CANT_INITIALIZE_EARLY_PLUGINS error code, 148
ER_CANT_INITIALIZE_GTID error code, 148
ER_CANT_INITIALIZE_UDF error code, 11
ER_CANT_INIT_DBs error code, 146
ER_CANT_INIT_SCHEDULER_THREAD error code, 136
ER_CANT_INIT_TC_LOG error code, 136
ER_CANT_INIT_TIMER error code, 150
ER_CANT_JOIN_SHUTDOWN_THREAD error code, 149
ER_CANT_LOCK error code, 4
ER_CANT_LOCK_LOG_TABLE error code, 36
ER_CANT_LOCK_TABLE error code, 214
ER_CANT_LOCK_TABLESPACE error code, 214
ER_CANT MODIFY_SRID_0 error code, 95
ER_CANT_MODIFY_SRS_USED_BY_COLUMN error code, 95
ER_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES error code, 167
ER_CANT_OPEN_CA error code, 150
ER_CANT_OPEN_DATADIR_AFTER_UPGRADE_FAILURE error code, 216
ER_CANT_OPEN_DB_OPT_USING_DEFAULT_CHARSET error code, 215
ER_CANT_OPEN_DIR error code, 216
ER_CANT_OPEN_ERROR_LOG error code, 150
ER_CANT_OPEN_FILE error code, 4
ER_CANT_OPEN_FRM_FILE error code, 167
ER_CANT_OPEN_LIBRARY error code, 11
ER_CANT_OPEN_TABLE MYSQL_PROC error code, 216

ER_CANT_PARSE_STORED_ROUTINE_BODY error code, 216
ER_CANT_PROCESS_EXPRESSION_FOR_GENERATED_COLUMN_NEXT_IS_996ET
ER_CANT_READ_DIR error code, 4
ER_CANT_READ_ERRMSGS error code, 146
ER_CANT_READ_FRM_FILE error code, 167
ER_CANT_READ_TABLE MYSQL_PROC error code, 216
ER_CANT_REMOVE_ALL_FIELDS error code, 9
ER_CANT_REMOVE_PID_FILE error code, 141
ER_CANT_RENAME_LOG_TABLE error code, 38
ER_CANT_REOPEN_TABLE error code, 12
ER_CANT_REPLICATE_ANONYMOUS_WITH_AUTO_POSITION error code, 459
ER_CANT_REPLICATE_ANONYMOUS_WITH_GTID_MODE_ON error code, 459
ER_CANT_REPLICATE_GTID_WITH_GTID_MODE_OFF error code, 459
ER_CANT_RESET_MASTER error code, 73
ER_CANT_SAVE_GTIDS error code, 149
ER_CANT_SET_ANONYMOUS_TO_GTID_AND_WAIT_UNTIL_SQL error code, 128
ER_CANT_SET_DATADIR error code, 149
ER_CANT_SET_DATA_DIR error code, 472
ER_CANT_SET_ERROR_LOG_SERVICE error code, 93
ER_CANT_SET_ERROR_SUPPRESSION_LIST error code, 97
ER_CANT_SET_ERROR_SUPPRESSION_LIST_FROM_COMMAND error code, 464
ER_CANT_SET_GTID_MODE error code, 67
ER_CANT_SET_GTID_NEXT_LIST_TO_NON_NULL_WHEN_GTID_IS_996ET error code, 51
ER_CANT_SET_GTID_NEXT_TO_ANONYMOUS_WHEN_GTID_MODE_IS_996ET error code, 51
ER_CANT_SET_GTID_NEXT_TO_GTID_WHEN_GTID_MODE_IS_996ET error code, 51
ER_CANT_SET_GTID_NEXT_WHEN_OWNING_GTID error code, 52
ER_CANT_SET_GTID_PURGED_DUE_SETS_CONSTRAINTS error code, 77
ER_CANT_SET_GTID_PURGED_WHEN_GTID_EXECUTED_IS_NONE error code, 55
ER_CANT_SET_GTID_PURGED_WHEN_OWNED_GTIDS_IS_NONE error code, 55
ER_CANT_SET_HANDLER_REFERENCE_FOR_TABLE error code, 214
ER_CANT_SET_PATH_FOR error code, 216
ER_CANT_SET_PERSISTED error code, 153
ER_CANT_SET_SQL_AFTER_OR_BEFORE_GTIDS_WITH_ANONYMOUS error code, 128
ER_CANT_SET_UP_PERSISTED_VALUES error code, 149
ER_CANT_SET_VARIABLE_WHEN_OWNING_GTID error code, 69
ER_CANT_START_ERROR_LOG_SERVICE error code, 233

ER_CANT_STAT_DATADIR error code, 149	ER_CHECK_CONSTRAINT_NOT_FOUND error code, 107
ER_CANT_STAT_FILE error code, 224	ER_CHECK_CONSTRAINT_REFERERS_AUTO_INCREMENT_C error code, 106
ER_CANT_UPDATE_TABLE_IN_CREATE_TABLE_SELECT error code, 48	ER_CHECK_CONSTRAINT_REFERERS_UNKNOWN_COLUMN error code, 106
ER_CANT_UPDATE_USED_TABLE_IN_SF_OR_TRG error code, 30	ER_CHECK_CONSTRAINT_ROW_VALUE error code, 106
ER_CANT_UPDATE_WITH_READLOCK error code, 17	ER_CHECK_CONSTRAINT_VARIABLES error code, 106
ER_CANT_UPGRADE_GENERATED_COLUMNS_TO_DIE error code, 214	ER_CLIENT_DOES_NOT_SUPPORT error code, 87
ER_CANT_USE_ANONYMOUS_TO_GTID_WITH_GTID_ERROR_CODE constraint violated error code, 127	ER_CLIENT_GTD_UNSAFE_CREATE_DROP_TEMP_TABLE error code, 98
ER_CANT_USE_AUTO_POSITION_WITH_GTID_MODE error code, 67	ER_CLIENT_INTERACTION_TIMEOUT error code, 130
ER_CANT_USE_OPTION_HERE error code, 18	ER_CLIENT_KEYRING_UDF_KEY_INVALID error code, 117
ER_CANT_USE_SAME_UUID_AS_GROUP_NAME error code, 128	ER_CLIENT_KEYRING_UDF_KEY_TOO_LONG error code, 118
ER_CANT_USE_SAME_UUID_AS_VIEW_CHANGE_UUID error code, 130	ER_CLIENT_KEYRING_UDF_KEY_TYPE_INVALID error code, 118
ER_CANT_WAIT_FOR_EXECUTED_GTID_SET_WHILE error code, 72	ER_CLIENT_LOCAL_FILES_DISABLED error code, 119
ER_CAPACITY_EXCEEDED error code, 72	ER_CLIENT_PRIVILEGE_CHECKS_USER_CANNOT_BE_AN error code, 117
ER_CAPACITY_EXCEEDED_IN_PARSER error code, 73	ER_CLIENT_PRIVILEGE_CHECKS_USER_CORRUPT error code, 117
ER_CAPACITY_EXCEEDED_IN_RANGE_OPTIMIZER error code, 72	ER_CLIENT_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST error code, 117
ER_CA_SELF_SIGNED error code, 138	ER_CLIENT_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APP error code, 117
ER_CHANGED_ENFORCE_GTID_CONSISTENCY error code, 135	ER_CLONE_CLIENT_TRACE error code, 472
ER_CHANGED_GTID_MODE error code, 135	ER_CLONE_CONFIG error code, 111
ER_CHANGED_MAX_CONNECTIONS error code, 146	ER_CLONE_CREATE_HANDLER_FAIL_TRACE error code, 245
ER_CHANGED_MAX_OPEN_FILES error code, 145	ER_CLONE_DDL_IN_PROGRESS error code, 86
ER_CHANGED_TABLE_OPEN_CACHE error code, 146	ER_CLONE_DISK_SPACE error code, 112
ER_CHANGE_MASTER_PASSWORD_LENGTH error code, 63	ER_CLONE_DONOR error code, 111
ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_FAILURE error code, 116	ER_CLONE_DONOR_TRACE error code, 471
ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_IS_ABSENT error code, 117	ER_CLONE_DONOR_VERSION error code, 111
ER_CHANGE_MASTER_WRONG_COMPRESSION_LEVEL error code, 116	ER_CLONE_HANDLER_ERROR_CODE error code, 112
ER_CHANGE_RPL_INFO_REPOSITORY_FAILURE error code, 49	ER_CLONE_HANDLER_EXISTS error code, 244
ER_CHANGE_RPL_SRC_WRONG_COMPRESSION_ALGORITHM_IS_DISALLOWED error code, 130	ER_CLONE_HANDLER_EXIST_TRACE error code, 244
ER_CHARACTER_SET_MISMATCH error code, 125	ER_CLONE_INFO_CLIENT error code, 471
ER_CHECKING_TABLE error code, 213	ER_CLONE_INFO_SERVER error code, 472
ER_CHECKREAD error code, 4	ER_CLONE_LOOPBACK error code, 112
ER_CHECK_CONSTRAINT_CLAUSE_USING_FK_REFERRAL_ERROR_CODE constraint violation error code, 107	
ER_CHECK_CONSTRAINT_FUNCTION_IS_NOT_ALLOWED error code, 106	
ER_CHECK_CONSTRAINT_NAMED_FUNCTION_IS_NOT_DEFINED error code, 106	

ER_CLONE_NETWORK_PACKET error code, 120
ER_CLONE_OS error code, 111
ER_CLONE_PLATFORM error code, 111
ER_CLONE_PLUGIN_MATCH error code, 111
ER_CLONE_PLUGIN_NOT_LOADED error code, 244
ER_CLONE_PLUGIN_NOT_LOADED_TRACE error code, 244
ER_CLONE_PROTOCOL error code, 111
ER_CLONE_PROTOCOL_ERROR error code, 471
ER_CLONE_PROTOCOL_TRACE error code, 471
ER_CLONE_REMOTE_ERROR error code, 471
ER_CLONE_SERVER_TRACE error code, 472
ER_CLONE_SHUTDOWN_TRACE error code, 490
ER_CLONE_SYS_CONFIG error code, 111
ER_CLONE_TOO_MANY_CONCURRENT_CLONES error code, 86
ER_CMD_NEED_SUPER error code, 86
ER_COALESCE_ONLY_ON_HASH_PARTITION error code, 34
ER_COALESCE_PARTITION_NO_PARTITION error code, 35
ER_COLLATION_CHARSET_MISMATCH error code, 19
ER_COLUMNACCESS_DENIED_ERROR error code, 13
ER_COLUMN_CHANGE_SIZE error code, 113
ER_COLUMN_CHECK_CONSTRAINT_REFERENCES_CONFIGURATION WITHOUT_GROUP error code, 106
ER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2 error code, 53
ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE error code, 37
ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE error code, 60
ER_COMMIT_NOT_ALLOWED_IN_SF_OR_TRG error code, 29
ER_COMPONENTS_CANT_ACQUIRE_SERVICE_IMPLEMENTATION error code, 76
ER_COMPONENTS_CANT_LOAD error code, 76
ER_COMPONENTS_CANT_RELEASE_SERVICE error code, 77
ER_COMPONENTS_CANT_SATISFY_DEPENDENCY error code, 76
ER_COMPONENTS_CANT_UNLOAD error code, 77
ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION error code, 249
ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP error code, 138
ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_DEINIT_CONN_CONTROL_FAILED_TO_UPDATE_CONN_DELAY_HANDLER error code, 518
ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_INIT_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_RESPONSE error code, 518
ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN error code, 138
ER_COMPONENTS_LOAD_CANT_INITIALIZE error code, 77
ER_COMPONENTS_LOAD_CANT_REGISTER_SERVICEIMPLEMENTATION_CREATE_EVENT error code, 77
ER_COMPONENTS_NO_SCHEME error code, 76
ER_COMPONENTS_NO_SCHEME_SERVICE error code, 76
ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP error code, 138
ER_COMPONENTS_UNLOAD_CANT_DEINITIALIZE error code, 77
ER_COMPONENTS_UNLOAD_CANT_UNREGISTER_SERVICE error code, 77
ER_COMPONENTS_UNLOAD_DUPLICATE_IN_GROUP error code, 77
ER_COMPONENTS_UNLOAD_NOT_LOADED error code, 77
ER_COMPONENT_FILTER_CONFUSED error code, 269
ER_COMPONENT_FILTER_DIAGNOSTICS error code, 93
ER_COMPONENT_FILTER_FLABBERGASTED error code, 85
ER_COMPONENT_FILTER_WRONG_VALUE error code, 455
ER_COMPONENT_MANIPULATE_ROW_FAILED error code, 77
ER_COMPONENT_TABLE_INCORRECT error code, 77
ER_COND_ITEM_TOO_LONG error code, 42
ER_CONNECTION_ABORTED error code, 454
ER_CONNECTION_HANDLING_OOM error code, 140
ER_CONNECT_TO_FOREIGN_DATA_SOURCE error code, 29
ER_CONNECT_TO_MASTER error code, 17
ER_CONN_CONNATTR_TRUNCATED error code, 160
ER_CONN_CONTROL_DELAY_ACTION_INIT_FAILED error code, 271
ER_CONN_CONTROL_ERROR_MSG error code, 268
ER_CONN_CONTROL_EVENT_COORDINATOR_INIT_FAILED error code, 270
ER_CONN_CONTROL_FAILED_TO_SET_CONN_DELAY error code, 271
ER_CONN_INVALID_CONN_DELAY_TYPE error code, 270
ER_CONN_INIT_CONNECT_IGNORED error code, 270
ER_CONN_PER_THREAD_NO_THREAD error code, 157

ER_CONN_PIP_CANT_CREATE_PIPE error code, 156
ER_CONN_SHM_CANT_CREATE_CONNECTION error code, 156
ER_CONN_SHM_CANT_CREATE_SERVICE error code, 156
ER_CONN_SHM_LISTENER error code, 156
ER_CONN_SOCKET_ACCEPT_FAILED error code, 160
ER_CONN_SOCKET_SELECT_FAILED error code, 160
ER_CONN_TCP_ADDRESS error code, 157
ER_CONN_TCP_BIND_FAIL error code, 158
ER_CONN_TCP_BIND_RETRY error code, 158
ER_CONN_TCP_CANT_RESET_V6ONLY error code, 158
ER_CONN_TCP_CANT_RESOLVE_HOSTNAME error code, 157
ER_CONN_TCP_CREATED error code, 157
ER_CONN_TCP_ERROR_WITH_STRERROR error code, 157
ER_CONN_TCP_IPV6_AVAILABLE error code, 157
ER_CONN_TCP_IPV6_UNAVAILABLE error code, 157
ER_CONN_TCP_IP_NOT_LOGGED error code, 158
ER_CONN_TCP_IS THERE_ANOTHER_USING_PORT error code, 157
ER_CONN_TCP_LISTEN_FAIL error code, 158
ER_CONN_TCP_NO_SOCKET error code, 157
ER_CONN_TCP_RESOLVE_INFO error code, 158
ER_CONN_TCP_START_FAIL error code, 158
ER_CONN_TPC_BIND_FAIL error code, 158
ER_CONN_UNIX_IS THERE_ANOTHER_USING_SOCKET error code, 157
ER_CONN_UNIX_LISTEN_FAILED error code, 159
ER_CONN_UNIX_LOCK_FILE_CANT_CLOSE error code, 160
ER_CONN_UNIX_LOCK_FILE_CANT_CREATE error code, 159
ER_CONN_UNIX_LOCK_FILE_CANT_DELETE error code, 160
ER_CONN_UNIX_LOCK_FILE_CANT_OPEN error code, 159
ER_CONN_UNIX_LOCK_FILE_CANT_READ error code, 159
ER_CONN_UNIX_LOCK_FILE_CANT_SYNC error code, 160
ER_CONN_UNIX_LOCK_FILE_CANT_WRITE error code, 159
ER_CONN_UNIX_LOCK_FILE_EMPTY error code, 159
ER_CONN_UNIX_LOCK_FILE_FAIL error code, 158
ER_CONN_UNIX_LOCK_FILE_GIVING_UP error code, 159
ER_CONN_UNIX_LOCK_FILE_PIDLESS error code, 159
ER_CONN_UNIX_NO_BIND_NO_START error code, 159
ER_CONN_UNIX_NO_FD error code, 159
ER_CONN_UNIX_PATH_TOO_LONG error code, 158
ER_CONN_UNIX_PID_CLAIMED_SOCKET_FILE error code, 158
ER_CONSECUTIVE_REORG_PARTITIONS error code, 35
ER_CONSTRAINT_NOT_FOUND error code, 119
ER_CON_COUNT_ERROR error code, 5
ER_CORE_VALUES error code, 142
ER_CORRUPTED_JSON_DIFF error code, 88
ER_CORRUPT_HELP_DB error code, 19
ER_COULD_NOT_APPLY_JSON_DIFF error code, 88
ER_COULD_NOT_CREATE_WINDOWS_REGISTRY_KEY error code, 467
ER_COULD_NOT_REINITIALIZE_AUDIT_LOG_FILTERS error code, 460
ER_CRASHED_ON_REPAIR error code, 15
ER_CRASHED_ON_USAGE error code, 15
ER_CREATED_SYSTEM_WITH_VERSION error code, 242
ER_CREATE_FILEGROUP_FAILED error code, 35
ER_CREATING_NEW_UUID error code, 139
ER_CREATING_NEW_UUID_FIRST_START error code, 234
ER_CREDENTIALLESS_AUTO_USER_BAD error code, 140
ER_CREDENTIALS CONTRADICT_TO_HISTORY error code, 87
ER_CTE_MAX_RECUSION_DEPTH error code, 87
ER_CTE_RECURSIVE_FORBIDDEN_JOIN_ORDER error code, 80
ER_CTE_RECURSIVE_FORBIDS_AGGREGATION error code, 80
ER_CTE_RECURSIVEQUIRES_NONRECUSIVE_FIRST error code, 80
ER_CTE_RECURSIVEQUIRES_SINGLE_REFERENCE error code, 80
ER_CTE_RECURSIVEQUIRES_UNION error code, 80
ER_CURRENT_PASSWORD_CANNOT_BE_RETAINED error code, 114
ER_CURRENT_PASSWORD_NOT_REQUIRED error code, 114
ER_CUT_VALUE_GROUP_CONCAT error code, 19
ER_CYCLE_TIMER_IS_NOT_AVAILABLE error code, 245
ER_DATABASE_NAME error code, 40
ER_DATA_DIRECTORY_UNUSABLE error code, 467
ER_DATA_DIRECTORY_UNUSABLE_DELETEABLE error code, 490
ER_DATA_OUT_OF_RANGE error code, 45
ER_DATA_TOO_LONG error code, 28
ER_DATETIME_FUNCTION_OVERFLOW error code, 30
ER_DA_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY error code, 112
ER_DA_CANT_OPEN_ERROR_LOG error code, 126
ER_DA_ERROR_LOG_COMPONENT_FLUSH_FAILED error code, 131

ER_DA_ERROR_LOG_MULTIPLE_FILTERS error code, 126
ER_DA_ERROR_LOG_TABLE_DISABLED error code, 126
ER_DA_GRP_RPL_RECOVERY_ENDPOINT_FORMAT error code, 122
ER_DA_GRP_RPL_RECOVERY_ENDPOINT_INVALID error code, 123
ER_DA_GRP_RPL_STARTED_AUTO_REJOIN error code, 116
ER_DA_INVALID_CONDITION_NUMBER error code, 49
ER_DA_NO_ERROR_LOG_PARSER_CONFIGURED error code, 126
ER_DA_OOM error code, 120
ER_DA_PLUGIN_INSTALL_ERROR error code, 113
ER_DA_RPL_GTID_TABLE_CANNOT_OPEN error code, 113
ER_DA_SSL_LIBRARY_ERROR error code, 113
ER_DA_UDF_INVALID_ARGUMENT_TO_SET_CHARSET error code, 120
ER_DA_UDF_INVALID_CHARSET error code, 118
ER_DA_UDF_INVALID_CHARSET_SPECIFIED error code, 118
ER_DA_UDF_INVALID_COLLATION error code, 118
ER_DA_UDF_INVALID_EXTENSION_ARGUMENT_TYPE error code, 118
ER_DA_UDF_INVALID_RETURN_TYPE_TO_SET_CHARSET error code, 120
ER_DA_UNKNOWN_ERROR_NUMBER error code, 113
ER_DBACCESS_DENIED_ERROR error code, 6
ER_DBUG_CHECK_SHARES_DROPPED error code, 186
ER_DBUG_CHECK_SHARES_INFO error code, 186
ER_DB_ACCESS_DENIED error code, 112
ER_DB_CREATE_EXISTS error code, 4
ER_DB_DROP_EXISTS error code, 4
ER_DB_DROP_RMDIR error code, 4
ER_DB_DROP_RMDIR2 error code, 84
ER_DB_OPT_NOT_FOUND_USING_DEFAULT_CHARSET error code, 215
ER_DDL_IN_PROGRESS error code, 86
ER_DDL_LOG_ERROR error code, 37
ER_DDL_MSG_1 error code, 525
ER_DD_ABORTING_PARTIAL_UPGRADE error code, 165
ER_DD_CACHE_NOT_EMPTY_AT_SHUTDOWN error code, 134
ER_DD_CANT_CREATE_OBJECT_KEY error code, 134
ER_DD_CANT_CREATE_SP error code, 214
ER_DD_CANT_FETCH_TABLE_DATA error code, 214
ER_DD_CANT_FIX_SE_DATA error code, 214
ER_DD_CANT_GET_OBJECT_KEY error code, 134
ER_DD_CANT_RESOLVE_VIEW error code, 152
ER_DD_CREATED_FOR_UPGRADE error code, 166
ER_DD_ERROR_CREATING_ENTRY error code, 214
ER_DD_FAILSAFE error code, 132
ER_DD_FRM_EXISTS_FOR_TABLE error code, 166
ER_DD_INITIALIZE error code, 250
ER_DD_INITIALIZE_SQL_ERROR error code, 461
ER_DD_INIT_FAILED error code, 133
ER_DD_INIT_UPGRADE_FAILED error code, 133
ER_DD_METADATA_NOT_FOUND error code, 134
ER_DD_MINOR_DOWNGRADE error code, 251
ER_DD_MINOR_DOWNGRADE_VERSION_NOT_SUPPORTED error code, 251
ER_DD_NO_VERSION_FOUND error code, 251
ER_DD_NO_WRITES_NO_REPOPULATION error code, 132
ER_DD_OBJECT_RELEASEER_REMAINS error code, 134
ER_DD_OBJECT_REMAINS error code, 134
ER_DD_OBJECT_REMAINS_IN_RELEASEER error code, 134
ER_DD_POPULATING_TABLES FAILED error code, 134
ER_DD_RESTART error code, 250
ER_DD_SCHEMA_NOT_FOUND error code, 165
ER_DD_SE_INIT_FAILED error code, 165
ER_DD_TABLESPACE_NOT_FOUND error code, 151
ER_DD_TABLE_NOT_FOUND error code, 165
ER_DD_TRG_CANT_ADD error code, 151
ER_DD_TRG_CONNECTION_COLLATION_MISSING error code, 151
ER_DD_TRG_DB_COLLATION_MISSING error code, 151
ER_DD_TRG_DEFINER_OOM error code, 151
ER_DD_TRG_FILE_UNREADABLE error code, 151
ER_DD_UPDATING_PLUGIN_MD_FAILED error code, 134
ER_DD_UPGRADE error code, 250
ER_DD_UPGRADE_COMPLETED error code, 486
ER_DD_UPGRADE_DD_OPEN_FAILED error code, 240
ER_DD_UPGRADE_DD_POPULATED error code, 241
ER_DD_UPGRADE_FAILED_FIND_VALID_DATA_DIR error code, 242
ER_DD_UPGRADE_FAILED_INIT_DD_SE error code, 242
ER_DD_UPGRADE_FAILED_TO_ACQUIRE_TABLESPACE error code, 240
ER_DD_UPGRADE_FAILED_TO_CREATE_INDEX_STATS error code, 241
ER_DD_UPGRADE_FAILED_TO_CREATE_TABLE_STATS error code, 241
ER_DD_UPGRADE_FAILED_TO_FETCH_TABLES error code, 241
ER_DD_UPGRADE_FAILED_TO_FETCH_TABLESPACES error code, 240
ER_DD_UPGRADE_FAILED_TO_RESOLVE_TABLESPACE_ENG error code, 240
ER_DD_UPGRADE_FAILED_TO_UPDATE_VER_NO_IN_TABLES error code, 250

ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_ER_DEFAULT_VAL_GENERATED_VARIABLES error code, 242
ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_ER_DONT_USE_WITH_GRACE error code, 138
error code, 242
ER_DD_UPGRADE_FOUND_PREPARED_XA_TRANSACTION error code, 121
error code, 498
ER_DD_UPGRADE_INDEX_STATS_MIGRATE_COMPLETE error code, 100
error code, 241
ER_DD_UPGRADE_INFO_FILE_CLOSE_FAILED error code, 108
error code, 241
ER_DD_UPGRADE_INFO_FILE_OPEN_FAILED error code, 67
error code, 241
ER_DD_UPGRADE_OFF error code, 110
ER_DD_UPGRADE_RENAME_IDX_STATS_FILE_FAILED error code, 95
error code, 240
ER_DD_UPGRADE_SCHEMA_UNAVAILABLE error code, 525
error code, 251
ER_DD_UPGRADE_SDI_INFO_UPDATE_FAILED error code, 248
ER_DD_UPGRADE_SE_LOGS_FAILED error code, 248
ER_DD_UPGRADE_START error code, 140
ER_DD_UPGRADE_TABLESPACE_MIGRATION_FAILED error code, 522
error code, 241
ER_DD_UPGRADE_TABLE_INTACT_ERROR error code, 95
error code, 247
ER_DD_UPGRADE_TABLE_STATS_MIGRATE_COMPLETE error code, 248
error code, 241
ER_DD_UPGRADE_VERSION_NOT_SUPPORTED error code, 232
error code, 251
ER_DD_UPGRADE_VIEW_COLUMN_NAME_TOO_LONGER error code, 193
error code, 250
ER_DD_VERSION_FOUND error code, 132
ER_DD_VERSION_INSTALLED error code, 132
ER_DD_VERSION_UNSUPPORTED error code, 132
ER_DD_VIEW_CANT_ALLOC_CHARSET error code, 133
ER_DD_VIEW_CANT_CREATE error code, 134
ER_DD_VIEW_WITHOUT_DEFINER error code, 153
ER_DEBUG_SYNC_EXECUTED error code, 135
ER_DEBUG_SYNC_HIT error code, 135
ER_DEBUG_SYNC_HIT_LIMIT error code, 41
ER_DEBUG_SYNC_OOM error code, 136
ER_DEBUG_SYNC_THREAD_MAX error code, 135
ER_DEBUG_SYNC_TIMEOUT error code, 41
ER_DEFAULT_AS_VAL_GENERATED error code, 101
ER_DEFAULT_SE_UNAVAILABLE error code, 150
ER_DEFAULT_VAL_GENERATED_FUNCTION_IS_NOT_ER_DONT_WAIT_FULL_NOWAIT error code, 90
error code, 101
ER_DEFAULT_VAL_GENERATED_NAMED_FUNCTION_ER_DONT_SUPPORT_SLAVE_PRESERVE_COMMIT_ORDER error code, 61
error code, 101
ER_DEFAULT_VAL_GENERATED_NON_PRIOR error code, 61
error code, 100
ER_DEFAULT_VAL_GENERATED_REF_AUTO_INC ER_DONT_SUPPORT_SLAVE_PRESERVE_COMMIT_ORDER error code, 249
error code, 100
ER_DEFAULT_VAL_GENERATED_ROW_VALUE ER_DROP_DATABASE_FAILED_RMDIR_MANUALLY error code, 35
error code, 101
ER_DROP_INDEX_FK error code, 36

ER_DROP_LAST_PARTITION error code, 34
ER_DROP_PARTITION_NON_EXISTENT error code, 34
ER_DUPLICATED_VALUE_IN_TYPE error code, 21
ER_DUPLICATE_OPTION_KEY error code, 79
ER_DUPLICATE_SYS_VAR error code, 462
ER_DUPLICATE_TABLE_LOCK error code, 79
ER_DUP_ARGUMENT error code, 17
ER_DUP_ENTRY error code, 7
ER_DUP_ENTRY_AUTOINCREMENT_CASE error code, 37
ER_DUP_ENTRY_WITH_KEY_NAME error code, 38
ER_DUP_FD_OPEN_FAILED error code, 234
ER_DUP_FIELDNAME error code, 7
ER_DUP_INDEX error code, 55
ER_DUP_KEY error code, 4
ER_DUP_KEYNAME error code, 7
ER_DUP_LIST_ENTRY error code, 61
ER_DUP_SIGNAL_SET error code, 41
ER_DUP_UNIQUE error code, 14
ER_DUP_UNKNOWN_IN_INDEX error code, 57
ER_EMPTY_PIPELINE_FOR_ERROR_LOG_SERVICE error code, 93
ER_EMPTY_PRIVILEGE_NAME_IGNORED error code, 512
ER_EMPTY_QUERY error code, 7
ER_ENDING_INIT error code, 461
ER_END_INITFILE error code, 145
ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONE_GTID_CANT_GET_NOCHECK_FOR_DROPPING_EVENT error code, 68
ER_ENGINE_ATTRIBUTE_NOT_SUPPORTED error code, 123
ER_ENGINE_CANT_DROP_MISSING_TABLE error code, 83
ER_ENGINE_CANT_DROP_TABLE error code, 83
ER_ENGINE_COST_FAILED_TO_READ error code, 177
ER_ENGINE_COST_INVALID_CONST_CONSTANT_FOR_PSI_ENGINE error code, 177
ER_ENGINE_COST_INVALID_DEVICE_TYPE_FOR_SE error code, 177
ER_ENGINE_COST_UNKNOWN_COST_CONSTANT error code, 177
ER_ENGINE_COST_UNKNOWN_STORAGE_ENGINE error code, 177
ER_ENGINE_OUT_OF_MEMORY error code, 60
ER_ERRMSG_CANT_FIND_FILE error code, 166
ER_ERRMSG_CANT_READ error code, 166
ER_ERRMSG_LOADING_55_STYLE error code, 166
ER_ERRMSG_MISSING_IN_FILE error code, 166
ER_ERRMSG_OOM error code, 166
ER_ERRMSG_REPLACEMENTS_FAILED error code, 228
ER_ERRMSG_REPLACEMENT_DODGY error code, 228
ER_ERROR_DURING_COMMIT error code, 15
ER_ERROR_DURING_FLUSH_LOGS error code, 15
ER_ERROR_DURING_FLUSH_LOG_COMMIT_PHASE error code, 249
ER_ERROR_DURING_OPTIMIZE_TABLE error code, 213
ER_ERROR_DURING_ROLLBACK error code, 15
ER_ERROR_ENABLING_KEYS error code, 213
ER_ERROR_INFO_FROM_DA error code, 458
ER_ERROR_IN_TRIGGER_BODY error code, 46
ER_ERROR_IN_UNKNOWN_TRIGGER_BODY error code, 46
ER_ERROR_LOG_DESTINATION_NOT_A_FILE error code, 513
ER_ERROR_ON_MASTER error code, 59
ER_ERROR_ON MODIFYING_GTID_EXECUTED_TABLE error code, 72
ER_ERROR_ON_READ error code, 4
ER_ERROR_ON_RENAME error code, 4
ER_ERROR_ON_WRITE error code, 4
ER_ERROR_WHEN_EXECUTING_COMMAND error code, 17
ER_EVENT_ALREADY_EXISTS error code, 36
ER_EVENT_CANNOT_ALTER_IN_THE_PAST error code, 38
ER_EVENT_CANNOT_CREATE_IN_THE_PAST error code, 38
ER_EVENT_CANT_FIND_TIMEZONE error code, 215
ER_EVENT_CANT_GET_CHARSET error code, 215
ER_EVENT_CANT_GET_COLLATION error code, 215
ER_EVENT_CANT_GET_NOCHECK_FOR_DROPPING_EVENT error code, 219
ER_EVENT_CANT_GET_TIMEZONE_FROM_FIELD error code, 215
ER_EVENT_CANT_INIT_QUEUE error code, 136
ER_EVENT_CANT_OPEN_TABLE_MYSQL_EVENT error code, 216
ER_EVENT_DOES_NOT_EXIST error code, 36
ER_EVENT_DROPPING error code, 179
ER_EVENT_ERROR_DURING_COMPILATION error code, 178
ER_EVENT_EXECUTION_FAILED error code, 136
ER_EVENT_EXECUTION_FAILED_CANT_AUTHENTICATE_USER error code, 178
ER_EVENT_EXECUTION_FAILED_USER_LOST_EVEN_PRIVILEGE error code, 178
ER_EVENT_EXEC_TIME_IN_THE_PAST error code, 36
ER_EVENT_INTERVAL_NOT_POSITIVE_OR_TOO_BIG error code, 36
ER_EVENT_INVALID_CREATION_CTX error code, 39
ER_EVENT_LAST_EXECUTION error code, 136
ER_EVENT_MESSAGE_STACK error code, 136
ER_EVENT_PURGING_QUEUE error code, 136
ER_EVENT_RECUSION_FORBIDDEN error code, 38
ER_EVENT_SAME_NAME error code, 36

ER_EVENT_SCHEDULER_ERROR_GETTING_EVENT error code, 219
ER_FAILED_TO_FETCH_MANDATORY_ROLE_LIST error code, 119

ER_EVENT_SCHEDULER_ERROR_LOADING_FROM_DB error code, 219
ER_FAILED_TO_FIND_COLLATION_NAME error code, 233

ER_EVENT_SCHEDULER_GOT_BAD_DATA_FROM_TABLE error code, 219
ER_FAILED_TO_FIND_DL_ENTRY error code, 230

ER_EVENT_SET_VAR_ERROR error code, 37
ER_FAILED_TO_FIND_LOCALE_NAME error code, 233

ER_EVENT_UNABLE_TO_DROP_EVENT error code, 219
ER_FAILED_TO_FIND_MYSQLD_STATUS error code, 248

ER_EXCEEDED_MV_KEYS_NUM error code, 115
ER_FAILED_TO_GENERATE_UNIQUE_LOGFILE error code, 230

ER_EXCEEDED_MV_KEYS_SPACE error code, 115
ER_FAILED_TO_GET_ABSOLUTE_PATH error code, 234

ER_EXCEPTIONS_WRITE_ERROR error code, 40
ER_FAILED_TO_HANDLE_DEFAULTS_FILE error code, 462

ER_EXCESS_ARGUMENTS error code, 146
ER_FAILED_TO_INIT_SYS_VAR error code, 462

ER_EXPIRE_LOGS_DAYS_IGNORED error code, 249
ER_FAILED_TO_INIT_THREAD_ATTR_FOR_GTID_TABLE_C

ER_EXPLAIN_NOT_SUPPORTED error code, 60
error code, 171

ER_FAILED_DEFAULT_ROLES error code, 76
ER_FAILED_TO_JOIN_GTID_TABLE_COMPRESSION_THRE

ER_FAILED_READ_FROM_PAR_FILE error code, 45
error code, 171

ER_FAILED_REVOKE_ROLE error code, 76
ER_FAILED_TO_LOCK_MEM error code, 145

ER_FAILED_ROLE_GRANT error code, 76
ER_FAILED_TO_OPEN_COST_CONSTANT_TABLES error code, 177

ER_FAILED_START_MYSQLD_DAEMON error code, 234
error code, 238

ER_FAILED_TO_ACQUIRE_LOCK_ON_RESOURCE_GROUP error code, 238
ER_FAILED_TO_OPEN_SHARED_LIBRARY error code, 230

ER_FAILED_TO_ADD_RESOURCE_GROUP_TO_MAP error code, 238
ER_FAILED_TO_PERSIST_RESOURCE_GROUP_METADATA error code, 237

ER_FAILED_TO_ADD_RPL_FILTER error code, 244
ER_FAILED_TO_READ_FILE error code, 230

ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP error code, 238
ER_FAILED_TO_REMOVE_TEMP_TABLE error code, 210

ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP error code, 238
ER_FAILED_TO_SET_PERSISTED_OPTIONS error code, 248

ER_FAILED_TO_ALLOCATE_SSL_BIO error code, 462
ER_FAILED_TO_START_SLAVE_THREAD error code, 243

ER_FAILED_TO_APPLY_RESOURCE_GROUP_CONTROLLER error code, 238
ER_FAILED_TO_STORE_SDI_FOR_TABLESPACE error code, 241

ER_FAILED_TO_BINLOG_DROP_EVENT error code, 243
ER_FAILED_TO_UPDATE_RESOURCE_GROUP error code, 237

ER_FAILED_TO_BUILD_DO_AND_IGNORE_TABLE_HASH error code, 244
ER_FAILED_TO_WRITE_TO_FILE error code, 230

ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE error code, 171
ER_FAILED_TO_XML_CHROOT error code, 144

ER_FAILED_TO_CONSTRUCT_DROP_EVENT_QUERY error code, 243
ER_FAIL_SETGID error code, 144

ER_FAILED_TO_CREATE_CLONE_HANDLER error code, 244
ER_FAIL_SETREUID error code, 144

ER_FAILED_TO_CREATE_GTID_TABLE_COMPRESSION error code, 171
ER_FAIL_SETUID error code, 144

ER_FAILED_TO_CREATE_TABLE error code, 21
ER_FEATURE_DISABLED error code, 71

ER_FAILED_TO_CREATE_TABLE_COMPRESSION error code, 171
ER_FEATURE_NOT_AVAILABLE error code, 67

ER_FAILED_TO_CREATE_SDI_FOR_TABLESPACE error code, 240
ER_FEATURE_UNSUPPORTED error code, 89

ER_FAILED_TO_DECREMENT_NUMBER_OF_THREADS error code, 83
ER_FIELD_IN_GROUPING_NOT_GROUP_BY error code, 33

ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE error code, 171
ER_FIELD_NOT_FOUND_PART_ERROR error code, 10

ER_FAILED_TO_DESERIALIZE_RESOURCE_GROUP error code, 237
ER_FIELD_SPECIFIED_TWICE error code, 10

ER_FAILED_TO_DETERMINE_IF_ROLE_IS_MANDATORY error code, 42
ER_FIELD_TYPE_NOT_ALLOWED_AS_PARTITION_FIELD error code, 119

ER_FILEGROUP_OPTION_ONLY_ONCE error code, 35
ER_FILESORT_TERMINATED error code, 233
ER_FILE_CORRUPT error code, 59
ER_FILE_EXISTS_DURING_UPGRADE error code, 216
ER_FILE_EXISTS_ERROR error code, 9
ER_FILE_HAS_OLD_FORMAT error code, 232
ER_FILE_NOT_FOUND error code, 4
ER_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS error code, 495
ER_FILE_TYPE_UNKNOWN error code, 167
ER_FILE_USED error code, 5
ER_FILSORT_ABORT error code, 5
ER_FIREWALL_ACCESS_DENIED error code, 261
ER_FIREWALL_DEPRECATED_USER_PROFILE error code, 522
ER_FIREWALL_FAILED_TO_READ_FIREWALL_TABLES error code, 261
ER_FIREWALL_FAILED_TO_REG_DYNAMIC_PRIVILEGES error code, 261
ER_FIREWALL_PFS_TABLE_REGISTER_FAILED error code, 517
ER_FIREWALL_RECORDING_STMT_WAS_TRUNCATED error code, 261
ER_FIREWALL_RECORDING_STMT_WITHOUT_TEXT error code, 261
ER_FIREWALL_RELOADING_CACHE error code, 262
ER_FIREWALL_RESET_FOR_USER error code, 262
ER_FIREWALL_SERVICES_NOT_ACQUIRED error code, 517
ER_FIREWALL_SKIPPED_UNKNOWN_USER_MODE error code, 261
ER_FIREWALL_STATUS_FLUSHED error code, 262
ER_FIREWALL_SUSPICIOUS_STMT error code, 261
ER_FIREWALL_UDF_REGISTER_FAILED error code, 517
ER_FIXING_CLIENT_CHARSET error code, 145
ER_FK_CANNOT_CHANGE_ENGINE error code, 101
ER_FK_CANNOT_DROP_PARENT error code, 96
ER_FK_CANNOT_OPEN_PARENT error code, 54
ER_FK_CANNOT_USE_VIRTUAL_COLUMN error code, 97
ER_FK_COLUMN_CANNOT_CHANGE error code, 55
ER_FK_COLUMN_CANNOT_CHANGE_CHILD error code, 55
ER_FK_COLUMN_CANNOT_DROP error code, 54
ER_FK_COLUMN_CANNOT_DROP_CHILD error code, 54
ER_FK_COLUMN_NOT_NULL error code, 54
ER_FK_DEPTH_EXCEEDED error code, 60
ER_FK_DUP_NAME error code, 54
ER_FK_FAIL_ADD_SYSTEM error code, 54
ER_FK_INCOMPATIBLE_COLUMNS error code, 102
ER_FK_INCORRECT_OPTION error code, 54
ER_FK_NO_COLUMN_PARENT error code, 97
ER_FK_NO_INDEX_CHILD error code, 54
ER_FK_NO_INDEX_PARENT error code, 54
ER_FORBID_SCHEMA_CHANGE error code, 31
ER_FORCE_CLOSE_THREAD error code, 231
ER_FORCING_CLOSE error code, 8
ER_FOREIGN_DATA_SOURCE_DOESNT_EXIST error code, 29
ER_FOREIGN_DATA_STRING_INVALID error code, 30
ER_FOREIGN_DATA_STRING_INVALID_CANT_CREATE error code, 29
ER_FOREIGN_DUPLICATE_KEY_OLD_UNUSED error code, 36
ER_FOREIGN_DUPLICATE_KEY_WITHOUT_CHILD_INFO error code, 50
ER_FOREIGN_DUPLICATE_KEY_WITH_CHILD_INFO error code, 50
ER_FOREIGN_KEY_ON_PARTITIONED error code, 34
ER_FOREIGN_KEY_WITH_ATOMIC_CREATE_SELECT error code, 123
ER_FOREIGN_SERVER_DOESNT_EXIST error code, 32
ER_FOREIGN_SERVER_EXISTS error code, 32
ER_FOUND_MISSING_GTIDS error code, 331
ER_FOUND_ROWS_WHILE_REPAIRING error code, 213
ER_FPARSER_BAD_HEADER error code, 24
ER_FPARSER_EOF_IN_COMMENT error code, 24
ER_FPARSER_EOF_IN_UNKNOWN_PARAMETER error code, 25
ER_FPARSER_ERROR_IN_PARAMETER error code, 25
ER_FPARSER_TOO_BIG_FILE error code, 24
ER_FSEEK_FAIL error code, 26
ER_FT_BOOL_SYNTAX_INVALID error code, 140
ER_FT_MATCHING_KEY_NOT_FOUND error code, 15
ER_FULLTEXT_FUNCTIONAL_INDEX error code, 100
ER_FULLTEXT_NOT_SUPPORTED_WITH_PARTITIONING error code, 49
ER_FUNCTIONAL_INDEX_DATA_IS_TOO_LONG error code, 115
ER_FUNCTIONAL_INDEX_FUNCTION_IS_NOT_ALLOWED error code, 99
ER_FUNCTIONAL_INDEX_ON_FIELD error code, 100
ER_FUNCTIONAL_INDEX_ON_JSON_OR_GEOMETRY_FUNCTION error code, 99
ER_FUNCTIONAL_INDEX_ON_LOB error code, 99
ER_FUNCTIONAL_INDEX_PRIMARY_KEY error code, 99
ER_FUNCTIONAL_INDEX_REF_AUTO_INCREMENT error code, 99
ER_FUNCTIONAL_INDEX_ROW_VALUE_IS_NOT_ALLOWED error code, 104
ER_FUNCTION_DOES_NOT_SUPPORT_CHARACTER_SET error code, 124
ER_FUNCTION_NOT_DEFINED error code, 12
ER_FUNC_INEXISTENT_NAME_COLLISION error code, 40

ER_FUTURE_DATE error code, 143	ER_GROUP_REPLICATION_PASSWORD_LENGTH
ER_GENERATED_COLUMN_FUNCTION_IS_NOT_ALLOWED error code, 66	ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED
ER_GENERATED_COLUMN_NAMED_FUNCTION_IS_NOT_ALLOWED error code, 100	ER_GROUP_REPLICATION_RUNNING error code, 66
ER_GENERATED_COLUMN_NON_PRIOR error code, 67	ER_GROUP_REPLICATION_STOP_APPLIER_THREAD_TIME error code, 66
ER_GENERATED_COLUMN_REF_AUTO_INC error code, 67	ER_GROUP_REPLICATION_USER_EMPTY_MSG error code, 122
ER_GENERATED_COLUMN_ROW_VALUE error code, 100	ER_GROUP_REPLICATION_USER_MANDATORY_MSG error code, 122
ER_GENERATED_COLUMN_VARIABLES error code, 100	ER_GRP_DELAYED_VCLE_LOGGING error code, 485
ER_GEOMETRY_IN_UNKNOWN_LENGTH_UNIT error code, 113	ER_GRP_OPERATION_NOT_ALLOWED_GR_MUST_STOP error code, 121
ER_GEOMETRY_PARAM_LATITUDE_OUT_OF_RANGE error code, 96	ER_GRP_RPL_ABORTS_AS_SSL_NOT_SUPPORTED_BY_M
ER_GEOMETRY_PARAM_LONGITUDE_OUT_OF_RANGE error code, 96	error code, 315
ER_GET_ERRMSG error code, 22	ER_GRP_RPL_ADD_GRPSID_TO_GRP_TIDSID_MAP_ERROR
ER_GET_ERRNO error code, 5	error code, 291
ER_GET_ERRNO_FROM_STORAGE_ENGINE error code, 232	ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_LOCAL_GTID_F
ER_GET_STACKED_DA_WITHOUT_ACTIVE_HANDLER error code, 59	error code, 302
ER_GET_TEMPORARY_ERRMSG error code, 22	ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTID
ER_GIS_DATA_WRONG_ENDIANESS error code, 63	error code, 302
ER_GIS_DIFFERENT_SRIDS error code, 62	ER_GRP_RPL_ADD_GTID_TO_GRP_TID_EXECUTED_ERROR
ER_GIS_DIFFERENT_SRIDS_AGGREGATION error code, 130	error code, 291
ER_GIS_INVALID_DATA error code, 62	ER_GRP_RPL_ADD_RETRIEVED_SET_TO_GRP_GTID_EXE
ER_GIS_MAX_POINTS_IN_GEOMETRY_OVERFLOWED error code, 69	error code, 292
ER_GIS_UNKNOWN_ERROR error code, 62	ER_GRP_RPL_ADD_VIEW_CHANGE_UUID_TO_GRP_SID_M
ER_GIS_UNKNOWN_EXCEPTION error code, 62	error code, 524
ER_GIS_UNSUPPORTED_ARGUMENT error code, 62	ER_GRP_RPL_ALL_DONORS_LEFT_ABORT_RECOVERY
ER_GLOBAL_VARIABLE error code, 18	error code, 304
ER_GLOBSTAT_CHANGE_DURING_QUERY error code, 116	ER_GRP_RPL_ALL_OBSERVERS_UNREGISTERED
ER_GNO_EXHAUSTED error code, 50	error code, 315
ER_GRANT_WRONG_HOST_OR_USER error code, 13	ER_GRP_RPL_APPENDING_DATA_TO_INTERNAL_CACHE
ER_GROUPING_ON_TIMESTAMP_IN_DST error code, 116	error code, 308
ER_GROUP_REPLICATION_APPLIER_INIT_ERROR error code, 66	ER_GRP_RPL_APPLIER_CHANNEL_STILL_RUNNING
ER_GROUP_REPLICATION_COMMAND_FAILURE error code, 89	error code, 517
ER_GROUP_REPLICATION_COMMUNICATION_LAYER error code, 66	ER_GRP_RPL_APPLIER_EXECUTION_FATAL_ERROR
ER_GROUP_REPLICATION_COMMUNICATION_LAYER error code, 66	error code, 290
ER_GROUP_REPLICATION_CONFIGURATION error code, 66	ER_GRP_RPL_APPLIER_HANDLER_IS_IN_USE
ER_GROUP_REPLICATION_MAX_GROUP_SIZE error code, 73	error code, 319
	ER_GRP_RPL_APPLIER_HANDLER_NOT_INITIALIZED
	ER_GRP_RPL_APPLIER_HANDLER_ROLE_IS_IN_USE
	ER_GRP_RPL_APPLIER_INITIALIZED error code, 315
	ER_GRP_RPL_APPLIER_NOT_STARTED_DUE_TO_RUNNING error code, 315
	ER_GRP_RPL_APPLIER_PIPELINE_NOT_DISPOSED error code, 290
	ER_GRP_RPL_APPLIER_TERMINATION_TIMED_OUT_ON_S error code, 313

ER_GRP_RPL_APPLIER_THD_EXECUTION_ABORTEDER_GRP_RPL_CHECK_STATUS_TABLE error code, 305
error code, 290
ER_GRP_RPL_APPLIER_THD_KILLED error code, 491
289
ER_GRP_RPL_APPLIER_THD_SETUP_ERROR error code, 491
error code, 299
ER_GRP_RPL_APPLIER_THD_START_ERROR error code, 315
error code, 299
ER_GRP_RPL_APPLIER_THD_STOP_ERROR error code, 466
error code, 299
ER_GRP_RPL_APPOINTED_PRIMARY_NOT_PRESENTER_GRP_RPL_CONFIGURATION_ACTION_ERROR error code, 465
error code, 465
ER_GRP_RPL_AUTO_INC_OFFSET_RESET error code, 466
error code, 301
ER_GRP_RPL_AUTO_INC_OFFSET_SET error code, 465
error code, 301
ER_GRP_RPL_AUTO_INC_RESET error code, 465
error code, 301
ER_GRP_RPL_AUTO_INC_SET error code, 465
error code, 301
ER_GRP_RPL_BINLOG_CHECKSUM_SET error code, 316
error code, 306
ER_GRP_RPL_BINLOG_DISABLED error code, 304
error code, 298
ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP error code, 465
error code, 298
ER_GRP_RPL_BROADCASTING_TRANS_TO_GRP_FAILEDGRP_RPL_CONTACT_WITH_SRV_FAILED error code, 302
error code, 309
ER_GRP_RPL_BROADCAST_COMMIT_MSSG_TOO_BIG error code, 303
error code, 322
ER_GRP_RPL_BROADCAST_COMMIT_TRANS_MSSG_FAILED error code, 465
error code, 290
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_ERRORRESTART_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL error code, 305
error code, 307
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_OFFLINER_MODE_GRP_RPL_CREATE_SESSION_UNABLE error code, 304
error code, 307
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_READONLY_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM error code, 297
error code, 307
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPING_GRP_RPL_DEBUG_OPTIONS error code, 321
error code, 307
ER_GRP_RPL_CANT_GENERATE_GTID error code, 483
292
ER_GRP_RPL_CANT_KILL_THREAD error code, 296
ER_GRP_RPL_CANT_READ_GRP_GTID_EXTRACTED error code, 294
error code, 293
ER_GRP_RPL_CANT_READ_GTID error code, 465
error code, 293
ER_GRP_RPL_CANT_READ_WRITE_SET_ITEM error code, 305
error code, 293
ER_GRP_RPL_CERTIFICATE_SIZE_ERROR error code, 465
error code, 289
ER_GRP_RPL_CERTIFICATION_INITIALIZATION_FAILURE error code, 291
error code, 292
ER_GRP_RPL_CERTIFICATION_REC_PROCESS error code, 524
error code, 310
ER_GRP_RPL_CERTIFIER_MSSG_PROCESS_ERROR error code, 296
error code, 294
ER_GRP_RPL_CHANGE_GRP_MEM_NOT_PROCESSED error code, 291
error code, 295
ER_GRP_RPL_CHANNEL_THREAD_WHEN_GROUP_ACTIVE_RUNNING error code, 291
error code, 465
ER_GRP_RPL_COMMUNICATION_SSL_CONF_INFO error code, 291
error code, 315
ER_GRP_RPL_CONFIGURATION_ACTION_END error code, 466
error code, 466
ER_GRP_RPL_CONFIGURATION_ACTION_KILLED_ERROR error code, 466
error code, 466
ER_GRP_RPL_CONFIGURATION_ACTION_LOCAL_TERMINATION error code, 465
error code, 465
ER_GRP_RPL_CONFIGURATION_ACTION_START error code, 465
error code, 465
ER_GRP_RPL_CONFIG_RECOVERY error code, 465
error code, 304
ER_GRP_RPL_CONFLICT_DETECTION_DISABLED error code, 294
error code, 294
ER_GRP_RPL_CONN_INTERNAL_PLUGIN_FAIL error code, 303
error code, 303
ER_GRP_RPL_CONTACT_WITH_SRV_FAILED error code, 302
error code, 309
ER_GRP_RPL_COPY_FROM_EMPTY_STRING error code, 303
error code, 322
ER_GRP_RPL_CREATE_APPLIER_CACHE_ERROR error code, 289
error code, 290
ER_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL error code, 305
error code, 307
ER_GRP_RPL_CREATE_SESSION_UNABLE error code, 304
error code, 307
ER_GRP_RPL_DISABLE_READ_ONLY_FAILED error code, 296
error code, 297
ER_GRP_RPL_DISABLE_SRV_READ_MODE_RESTRICTED error code, 294
error code, 293
ER_GRP_RPL_DEFAULT_TABLE_ENCRYPTION_DIFF_FROM_G error code, 483
error code, 292
ER_GRP_RPL_DISABLE_SRV_READ_MODE_RESTRICTED error code, 294
error code, 293
ER_GRP_RPL_DONOR_CONN_TERMINATION error code, 305
error code, 310
ER_GRP_RPL_DONOR_SERVER_CONN error code, 305
error code, 310
ER_GRP_RPL_DONOR_TRANS_INFO_ERROR error code, 291
error code, 292
ER_GRP_RPL_DONOR_VIEW_CHANGE_UUID_TRANS_INFO_E error code, 524
error code, 310
ER_GRP_RPL_ENABLE_READ_ONLY_FAILED error code, 296
error code, 294
ER_GRP_RPL_ERROR_FETCHING_GTID_EXECUTED_SET error code, 291
error code, 295
ER_GRP_RPL_ERROR_FETCHING_GTID_SET error code, 291
error code, 296
ER_GRP_RPL_ERROR_GTID_EXECUTION_INFO error code, 289

ER_GRP_RPL_ERROR_GTID_SET_EXTRACTION	ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGINE
error code, 464	error code, 311
ER_GRP_RPL_ERROR_MSG	ER_GRP_RPL_FAILED_TO_INIT_HANDLER
error code, 268	error code, 314
ER_GRP_RPL_ERROR_ON_CERT_DB_INSTALL	ER_GRP_RPL_FAILED_TO_INSERT_TRX_ON_TCM_ON_AFT
error code, 478	error code, 475
ER_GRP_RPL_ERROR_ON_MESSAGE_SENDING	ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_EV
error code, 465	MSSG_CODE, 306
ER_GRP_RPL_ERROR_SENDING_SINGLE_PRIMARY	ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME
error code, 290	error code, 315
ER_GRP_RPL_ERROR_STOPPING_CHANNELS	ER_GRP_RPL_FAILED_TO_PARSE_THE_VIEW_CHANGE_U
error code, 290	error code, 524
ER_GRP_RPL_ERROR_VERIFYING_SIDNO	ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_OB
error code, 292	ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_O
ER_GRP_RPL_ERROR WHILE_WAITING_FOR_CONFLICT_DETECTION	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME_O
error code, 309	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OB
ER_GRP_RPL_ESTABLISHING_CONN_GRP_REC_DONOR	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OB
error code, 304	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OB
ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHER_DONOR	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OB
error code, 304	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OB
ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_DONOR	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OB
error code, 304	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OB
ER_GRP_RPL_EVENT_HANDLING_ERROR	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OB
error code, 289	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OB
ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE	ER_GRP_RPL_FAILED_TO_SHUTDOWN_REGISTRY_MODULE
error code, 297	error code, 313
ER_GRP_RPL_EXIT_GRP_GCS_ERROR	ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_ENG
error code, 321	error code, 312
ER_GRP_RPL_FAILED_TO_BOOTSTRAP_EVENT_HANDLING_INFRASTRUCTURE	ER_GRP_RPL_FAILED_TO_START_ON_BOOT
error code, 319	ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_WITH
ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBERSHIP_NOTIFICATION	ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER
error code, 306	ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL
ER_GRP_RPL_FAILED_TO_BROADCAST_MEMBER_STATUS_NOTIFICATION	ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE
error code, 306	ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE
ER_GRP_RPL_FAILED_TO_CALL_GRP_COMMUNICATION_INTERFACE	ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE_O
error code, 312	ER_GRP_RPL_FATAL_REC_PROCESS error code,
ER_GRP_RPL_FAILED_TO_CONFIRM_IF_SERVER_LEAVE_GRP	ER_GRP_RPL_FETCH_FORMAT_DESC_LOG_EVENT_FAILED
error code, 312	ER_GRP_RPL_FETCH_GTID_LOG_EVENT_FAILED
ER_GRP_RPL_FAILED_TO_CREATE_COMMIT_CACHE	ER_GRP_RPL_FETCH_LOG_EVENT_FAILED error
error code, 309	ER_GRP_RPL_FETCH_SNAPSHOT_VERSION_FAILED
ER_GRP_RPL_FAILED_TO_CREATE_TRANS_CONTEXT	ER_GRP_RPL_FETCH_TRANS_CONTEXT_FAILED
error code, 307	ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FA
ER_GRP_RPL_FAILED_TO_ENABLE_READ_ONLY_MODE_ON_SHUTDOWN	ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FA
error code, 313	ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FA
ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY_MODE_B01	ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FA
error code, 311	ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FA
ER_GRP_RPL_FAILED_TO_EXTRACT_TRANS_WRITE_SET	ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FA
error code, 308	ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FA
ER_GRP_RPL_FAILED_TO_GATHER_TRANS_WRITE_SET	ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FA
error code, 308	ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FA
ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GRP	ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FA
error code, 315	ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FA
ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_VIEW_CHANGE_UUID	ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FA
error code, 524	ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FA
ER_GRP_RPL_FAILED_TO_INIT_APPLIER_HANDLER	ER_GRP_RPL_FETCH_TRANS_DATA_FAILED error
error code, 319	code, 300
ER_GRP_RPL_FAILED_TO_INIT_APPLIER_MODULE	ER_GRP_RPL_FETCH_TRANS_SIDNO_ERROR
error code, 315	error code, 292

ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_ER_GRP_RPL_GTI
D_MODE_OFF error code, 316
error code, 302 ER_GRP_RPL_GTI
D_PURGED_EXTRACT_ERROR
error code, 491
ER_GRP_RPL_GTI
D_SET_EXTRACT_ERROR error
code, 297
ER_GRP_RPL_GTI
D_SET_EXTRACT_ERROR_DURING_REC
OV
error code, 477
ER_GRP_RPL_INCORRECT_TYPE_SET_FOR_PARALLEL_APPL
error code, 303
ER_GRP_RPL_FLOW_CTRL_MAX_QUOTA_SMALLER_THAN_300_Q
UOTAS
error code, 318 ER_GRP_RPL_INIT_CERTIFICATION_INFO_FAILURE
error code, 304
ER_GRP_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_MAX_200_Q
UOTA
error code, 317 ER_GRP_RPL_INTERNAL_QUERY error code, 303
ER_GRP_RPL_FLOW_CTRL_MIN_RECOVERY_QUOTA_ER_GRP_RPL_TH
AN_ABOVE_MAX_BONI_Q
UOTA_FORMAT error
code, 306
ER_GRP_RPL_FORCE_MEMBERS_MUST_BE_EMPTY_ER_GRP_RPL_INVALID_COMMUNICATION_PROTOCOL
error code, 482
error code, 311 ER_GRP_RPL_INVALID_DEBUG_OPTIONS error
code, 321
ER_GRP_RPL_FORCE_MEMBERS_SET_UPDATE_NOTE_ALONE_ERPL_INVALID_DEBUG_OPTIONS error
code, 318
ER_GRP_RPL_FORCE_MEMBERS_WHEN_LEAVE_ER_GRP_RPL_INVALID_GTID_SET error code, 292
error code, 478 ER_GRP_RPL_INVALID_SSL_RECOVERY_STRING
error code, 318
ER_GRP_RPL_FORCE_MEMBER_VALUE_SET error
code, 322 ER_GRP_RPL_INVALID_TRANS_WRITE_SET_EXTRACTION_VA
R
error code, 316
ER_GRP_RPL_FORCE_MEMBER_VALUE_SET_ERROR_ER_GRP_RPL_IS_STARTING error code, 504
error code, 322 ER_GRP_RPL_IS_STOPPED error code, 313
ER_GRP_RPL_IS_STOPPING error code, 313
ER_GRP_RPL_GCS_GR_ERROR_MSG error code,
323 ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION_RUNNING
error code, 465
ER_GRP_RPL_GCS_INTERFACE_ERROR error
code, 321 ER_GRP_RPL_JOIN_WHEN_GROUP_ACTION_RUNNING
error code, 465
ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTE_ER_GRP_RPL_KILLED_FAILED_ID error code, 303
error code, 321 ER_GRP_RPL_KILLED_SESSION_ID error code, 303
ER_GRP_RPL_GROUP_NAME_PARSE_ERROR ER_GRP_RPL_LOCAL_GTID_SETS_PROCESS_ERROR
error code, 298
ER_GRP_RPL_GROUP_NAME_SAME_AS_VIEW_CHANGE_ER_GRP_RPL_LOG_REPLICA_UPDATES_NOT_SET
error code, 523
ER_GRP_RPL_GRP_CHANGE_INFO_EXTRACT_ERROR_ER_GRP_RPL_LOG_SLAVE_UPDATES_NOT_SET
error code, 297
ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILED_ER_GRP_RPL_LOWER_CASE_TABLE_NAMES_DIFF_FROM_GR
error code, 321
ER_GRP_RPL_GRP_COMMUNICATION_INIT_WITH_CONFIG_ER_GRP_RPL_MASTER_INFO_REPO_MUST_BE_TABLE
error code, 318
ER_GRP_RPL_GRP_MEMBER_OFFLINE error code,
321 ER_GRP_RPL_MAXIMUM_CONNECTION_RETRIES_REACHED
error code, 304
ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID ER_GRP_RPL_MEMBER_ACTIONS_RESET error
code, 317
ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID_ER_GRP_RPL_MEMBER_ACTION_DEFAULT_CONFIGURATION
error code, 521
ER_GRP_RPL_GRP_NAME_IS_SAME_AS_ANONYMOUS_ER_GRP_RPL_MEMBER_ACTION_DISABLED error
code, 516
ER_GRP_RPL_GRP_NAME_IS_TOO_LONG error
code, 317 ER_GRP_RPL_MEMBER_ACTION_ENABLED error
code, 522
ER_GRP_RPL_GRP_NAME_OPTION_MANDATORY_ER_GRP_RPL_MEMBER_ACTION_FAILURE error
code, 521
ER_GRP_RPL_GRP_VIEW_CHANGE_UUID_IS_INCOMPATIBLE_ER_GRP_RPL_MEMBER_ACTION_FAILURE error
error code, 523
ER_GRP_RPL_GTI
D_ALREADY_USED error code,
289 ER_GRP_RPL_MEMBER_ACTION_FAILURE_IGNORE
error code, 520
ER_GRP_RPL_GTI
D_EXECUTED_EXTRACT_ERROR_ER_GRP_RPL_MEMBER_ACTION_GET_EXCHANGEABLE_DATA
error code, 521

ER_GRP_RPL_MEMBER_ACTION_INVALID_ACTIONS error code, 294
error code, 522
ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_MEMBER error code, 309
error code, 521
ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_RECEIVER error code, 307
error code, 521
ER_GRP_RPL_MEMBER_ACTION_TRIGGERED error code, 300
error code, 520
ER_GRP_RPL_MEMBER_ACTION_UNABLE_TO_SET_DEFAULT_CONFIGURATION error code, 306
error code, 521
ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS error code, 302
error code, 521
ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS error code, 303
error code, 522
ER_GRP_RPL_MEMBER_ADDED error code, 295
ER_GRP_RPL_MEMBER_ALREADY_EXISTS error code, 297
ER_GRP_RPL_MEMBER_CFG_INCOMPATIBLE_WITH_ERROR error code, 293
error code, 299
ER_GRP_RPL_MEMBER_CHANGE error code, 296
ER_GRP_RPL_MEMBER_CONF_INFO error code, 312
ER_GRP_RPL_MEMBER_CONTACT_RESTORED error code, 295
ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR error code, 296
ER_GRP_RPL_MEMBER_EXPelled error code, 296
ER_GRP_RPL_MEMBER_LEFT_GRP error code, 296
ER_GRP_RPL_MEMBER_NOT_FOUND error code, 304
ER_GRP_RPL_MEMBER_Removed error code, 295
ER_GRP_RPL_MEMBER_SERVER_UUID_IS_INCOMPATIBLE error code, 312
ER_GRP_RPL_MEMBER_STATS_INFO error code, 322
ER_GRP_RPL_MEMBER_STOP_RPL_CHANNELS_ERROR error code, 299
ER_GRP_RPL_MEMBER_TRANS_GREATER_THAN_ERROR error code, 298
ER_GRP_RPL_MEMBER_VERSION_LOWER_THAN_ERROR error code, 298
ER_GRP_RPL_MEMBER_VER_INCOMPATIBLE error code, 298
ER_GRP_RPL_MEMBER_VER_READ_COMPATIBLE error code, 488
ER_GRP_RPL_MEM_ONLINE error code, 294
ER_GRP_RPL_MEM_REACHABLE error code, 295
ER_GRP_RPL_MEM_UNREACHABLE error code, 295
ER_GRP_RPL_MESSAGE_SERVICE_FATAL_ERROR error code, 493
ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE error code, 116
ER_GRP_RPL_MISSING_GRP_RPL_ACTION_COORDINATOR error code, 310
error code, 464
ER_GRP_RPL_MISSING_GRP_RPL_APPLIER error code, 294
ER_GRP_RPL_MODULE_TERMINATE_ERROR error code, 317
ER_GRP_RPL_MSG_DISCARDED error code, 294
ER_GRP_RPL_MSG_TOO_LONG_BROADCASTING_TRANSACTION error code, 309
ER_GRP_RPL_MULTIPLE_CACHE_TYPE_NOT_SUPPORTED error code, 307
ER_GRP_RPL_NEEDS_INNODB_TABLE error code, 300
ER_GRP_RPL_NEW_PRIMARY_ELECTED error code, 302
ER_GRP_RPL_NO_POSSIBLE_RECOVERY error code, 303
ER_GRP_RPL_NO_STAGE_SERVICE error code, 466
ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEMORY error code, 297
ER_GRP_RPL_NO_VALID_DONOR error code, 304
ER_GRP_RPL_NULL_PACKET error code, 293
ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE error code, 310
ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFICATION error code, 306
ER_GRP_RPL_PIPELINE_CREATE_FAILED error code, 322
ER_GRP_RPL_PIPELINE_FLUSH_FAIL error code, 323
ER_GRP_RPL_PIPELINE_REINIT_FAILED_READ error code, 323
ER_GRP_RPL_PIPELINE_REINIT_FAILED_WRITE error code, 323
ER_GRP_RPL_PLUGIN_ABORT error code, 461
ER_GRP_RPL_PLUGIN_STRUCT_INIT_NOT_POSSIBLE_ON_ERROR error code, 311
ER_GRP_RPL_PREV_REC_SESSION_RUNNING error code, 309
ER_GRP_RPL_PRIMARY_ELECTION_PROCESS_ERROR error code, 466
ER_GRP_RPL_PRIMARY_ELECTION_STOP_ERROR error code, 466
ER_GRP_RPL_PRIMARY_KEY_NOT_DEFINED error code, 300
ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP error code, 295
ER_GRP_RPL_PROCESS_GTID_SET_ERROR error code, 293
ER_GRP_RPL_PROCESS_INTERSECTION_GTID_SET_ERROR error code, 293
ER_GRP_RPL_PURGE_APPLIER_LOGS error code, 299
ER_GRP_RPL_PURGE_REC error code, 305
ER_GRP_RPL_QUERY_FAIL error code, 303
ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY_SUPER_ERROR error code, 310
ER_GRP_RPL_READ_UNABLE_FOR_SUPER_READ_ONLY error code, 310
ER_GRP_RPL_RECEIVED_SET_MISSING_GTIDS error code, 293

ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING ER_GRP_RPL_SERVER_ALREADY_LEFT error code, error code, 129
312
ER_GRP_RPL_RECOVERY_ENDPOINT_FORMAT ER_GRP_RPL_SERVER_CONN_ERROR error code, error code, 505
291
ER_GRP_RPL_RECOVERY_ENDPOINT_INTERFACES_ER_GRP_RPL_SERVER_IS_ALREADY_LEAVEING error code, 505
error code, 312
ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID ER_GRP_RPL_SERVER_SET_TO_OFFLINE_MODE_DUE_TO_ER error code, 505
error code, 493
ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID_DONER_ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DUE_TO_ER error code, 505
error code, 321
ER_GRP_RPL_RECOVERY_EVAL_ERROR error ER_GRP_RPL_SERVER_UDF_ERROR error code, code, 491
467
ER_GRP_RPL_RECOVERY_MODULE_TERMINATION_ER_GRP_RPL_SERVER_IS_WORKING_AS_SECONDARY error code, 313
error code, 311
ER_GRP_RPL_RECOVERY_STRAT_CHOICE error ER_GRP_RPL_SESSION_OPEN_FAILED error code, code, 492
296
ER_GRP_RPL_RECOVERY_STRAT_CLONE_PURGED ER_GRP_RPL_SET_GRP_COMMUNICATION_ENG_LOGGER_FA error code, 491
error code, 321
ER_GRP_RPL_RECOVERY_STRAT_CLONE_THRESHOLD_ER_GRP_RPL_SET_STABLE_TRANS_ERROR error code, 491
code, 293
ER_GRP_RPL_RECOVERY_STRAT_FALLBACK ER_GRP_RPL_SIDNO_FETCH_ERROR error code, error code, 492
290
ER_GRP_RPL_RECOVERY_STRAT_NO_FALLBACK ER_GRP_RPL_SINGLE_PRIM_MODE_NOT_ALLOWED_WITH_U error code, 492
error code, 317
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_DEPENDENCIES_ER_GRP_RPL_SKIP_COMPUTATION_TRANS_COMMITTED error code, 476
error code, 293
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_GROUP_ER_GRP_RPL_APPLIER_THREAD_ERROR_OUT error code, 475
error code, 323
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_SYNC_ER_GRP_RPL_SLAVE_IO_THREAD_UNBLOCKED error code, 476
error code, 323
ER_GRP_RPL_REINIT_OF_COMMIT_CACHE_FOR_WRITE_ER_GRP_RPL_SLAVE_IO_THD_PRIMARY_UNKNOWN error code, 309
error code, 300
ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_READ_ER_GRP_RPL_SLAVE_IO_THREAD_ERROR_OUT error code, 308
error code, 323
ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_WRITE_ER_GRP_RPL_SLAVE_IO_THREAD_UNBLOCKED error code, 309
error code, 323
ER_GRP_RPL_RELAY_LOG_INFO_REPO_MUST_BE_TABLE_ER_GRP_RPL_SLAVE_PRESERVE_COMMIT_ORDER_NOT_SET error code, 316
error code, 317
ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_DEPENDENCIES_ER_GRP_RPL_SLAVE_IO_THD_ON_SECONDARY_MEMBER error code, 476
error code, 300
ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_WAIT_ER_GRP_RPL_SQL_THREADS_SQL_PRIMARY_UNKNOWN error code, 477
error code, 300
ER_GRP_RPL_RELEASE_COMMIT_AFTER_GROUP_PIECES_ER_GRP_RPL_SLAVE_THREAD_ERROR_ON_CLONE error code, 475
error code, 492
ER_GRP_RPL_REPLICA_PRESERVE_COMMIT_ORDER_ER_GRP_RPL_SQL_SERVICE_COMM_SESSION_NOT_INITIALIZED error code, 317
error code, 319
ER_GRP_RPL_REQUESTING_NON_MEMBER_SERVER_ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SECURITY error code, 313
error code, 320
ER_GRP_RPL_RESET_APPLIER_MODULE_LOGS_ERROR_ER_GRP_RPL_SQL_SERVICE_FAILED_TO_INIT_SESSION_THR error code, 299
error code, 319
ER_GRP_RPL_SLAVE_IO_THD_ON_SECONDARY_MEMBER_ER_GRP_RPL_SQL_SERVICE_FAILED_TO_RUN_SQL_QUERY error code, 300
error code, 320
ER_GRP_RPL_SEND_STATS_ERROR error code, ER_GRP_RPL_SQL_SERVICE_MAX_CONN_ERROR_FROM_SE 322
error code, 320
ER_GRP_RPL_SEND_TRX_PREPARED_MESSAGE_FAILED_ER_GRP_RPL_SQL_SERVICE_RETRIES_EXCEEDED_ON_SESS error code, 475
error code, 320
ER_GRP_RPL_SEND_TRX_SYNC_BEFORE_EXECUTION_ER_GRP_RPL_SQL_SERVICE_SERVER_ACCESS_DENIED_FOR error code, 476
error code, 320

ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_CONN error code, 320
ER_GRP_RPL_SQL_SERVICE_SERVER_INTERNAL_FAILURE error code, 320
ER_GRP_RPL_SQL_SERVICE_SERVER_SESSION_KILLED error code, 319
ER_GRP_RPL_SRV_BLOCKED error code, 295
ER_GRP_RPL_SRV_BLOCKED_FOR_SECS error code, 295
ER_GRP_RPL_SRV_GTID_WAIT_ERROR error code, 485
ER_GRP_RPL_SRV_NOT_ONLINE error code, 294
ER_GRP_RPL_SRV_ONLINE error code, 294
ER_GRP_RPL_SRV_PRIMARY_MEM error code, 296
ER_GRP_RPL_SRV_SECONDARY_MEM error code, 296
ER_GRP_RPL_SRV_WAIT_TIME_OUT error code, 302
ER_GRP_RPL_SSL_DISABLED error code, 315
ER_GRP_RPL_STARTED_AUTO_REJOIN error code, 482
ER_GRP_RPL_STARTING_GRP_REC error code, 305
ER_GRP_RPL_START_FAILED error code, 298
ER_GRP_RPL_START_GRP_RPL_FAILED error code, 303
ER_GRP_RPL_STOPPING_GRP_REC error code, 305
ER_GRP_RPL_STOP_REP_CHANNEL error code, 323
ER_GRP_RPL_SUPER_READ_OFF error code, 303
ER_GRP_RPL_SUPER_READ_ON error code, 303
ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERROR error code, 297
ER_GRP_RPL_SUPPORTS_ONLY_ONE_FORCE_MEMBER_SET error code, 318
ER_GRP_RPL_TIMEOUT_ON_VIEW_AFTER_JOINING_ERROR error code, 312
ER_GRP_RPL_TIMEOUT_RECEIVED_VC_LEAVE_ON_REDUNDANCY_NODE error code, 512
ER_GRP_RPL_TIMEOUT_RECEIVED_VC_ON_REJOIN error code, 482
ER_GRP_RPL_TIMEOUT RECEIVING_VIEW_CHANGE_ERROR error code, 313
ER_GRP_RPL_TRANS_GREATER_THAN_GRP error code, 298
ER_GRP_RPL_TRANS_NOT_PRESENT_IN_GRP error code, 298
ER_GRP_RPL_TRANS_SIZE_EXCEEDS_LIMIT error code, 308
ER_GRP_RPL_TRANS_WRITE_SET_EXTRACTION_NOSET error code, 306
ER_GRP_RPL_TRANS_WRITE_SET_EXTRACT_DIFF_FROM_GRP error code, 299
ER_GRP_RPL_TRX_ALREADY_EXISTS_ON_TCM_ON_HANDLER error code, 475
ER_GRP_RPL_TRX_DOES_NOT_EXIST_ON_TCM_ON_HANDLER error code, 476
ER_GRP_RPL_TRX_WAIT_FOR_GROUP_GTID_EXECUTED error code, 477
ER_GRP_RPL_TRX_WAIT_FOR_GROUP_PREPARE_FAILED error code, 476
ER_GRP_RPL_TRX_WAIT_FOR_SYNC_BEFORE_EXECUTION error code, 477
ER_GRP_RPL_UDF_ERROR error code, 115
ER_GRP_RPL_UDF_REGISTER_ERROR error code, 466
ER_GRP_RPL_UDF_REGISTER_SERVICE_ERROR error code, 466
ER_GRP_RPL_UDF_UNREGISTER_ERROR error code, 466
ER_GRP_RPL_UNABLE_TO_CERTIFY_PLUGIN_TRANSACTION error code, 311
ER_GRP_RPL_UNABLE_TO_CONVERT_EVENT_TO_PACKET error code, 323
ER_GRP_RPL_UNABLE_TO_CONVERT_PACKET_TO_EVENT error code, 322
ER_GRP_RPL_UNABLE_TO_ENSURE_EXECUTION_RECORD error code, 310
ER_GRP_RPL_UNABLE_TO_EVALUATE_APPLIER_STATUS error code, 310
ER_GRP_RPL_UNABLE_TO_INIT_COMMUNICATION_ENGINE error code, 316
ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_APP error code, 305
ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_FAILED error code, 305
ER_GRP_RPL_UNABLE_TO_RESET_SERVER_READ_MODE error code, 310
ER_GRP_RPL_UNBLOCK_CERTIFIED_TRANSACTION error code, 311
ER_GRP_RPL_UNBLOCK_WAITING_THREAD error code, 299
ER_GRP_RPL_UNKNOWN_GRP_RPL_APPLIER_PIPELINE_NODE error code, 318
ER_GRP_RPL_UNREACHABLE_MAORITY_TIMEOUT_FOR_REDUNDANCY_NODE error code, 320
ER_GRP_RPL_UNSUPPORTED_TRANSACTION_ISOLATION error code, 307
ER_GRP_RPL_UPDATE_GRP_GTIID_EXECUTED_ERROR error code, 307
ER_GRP_RPL_UPDATE_GRP_GTIID_VIEW_CHANGE_UUID_ERROR error code, 524
ER_GRP_RPL_UPDATE_GTIID_SET_ERROR error code, 292
ER_GRP_RPL_UPDATE_LAST_CONFLICT_FREE_TRANSACTION error code, 292
ER_GRP_RPL_UPDATE_SERV_CERTIFICATE_FAILED error code, 296
ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_REF_VERSION_ERROR error code, 302
ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_REF_VERSION_ERROR error code, 292
ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_VERSION_ERROR error code, 296
ER_GRP_RPL_VIEW_CHANGE_UUID_DIFF_FROM_GRP error code, 320
ER_GRP_RPL_REMOTE_PREPARE error code, 320

ER_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE error code, 131
ER_GRP_RPL_VIEW_CHANGE_UUID_INVALID error code, 523
ER_GRP_RPL_VIEW_CHANGE_UUID_IS_SAME_AS_ANOTHER_INNODB_TABLE error code, 523
ER_GRP_RPL_VIEW_CHANGE_UUID_PARSE_ERROR error code, 524
ER_GRP_RPL_VIEW_CHANGE_UUID_SAME_AS_GROUP error code, 523
ER_GRP_RPL_WAITING_FOR_VIEW_UPDATE error code, 312
ER_GRP_RPL_WAIT_FOR_DEPENDENCIES_FAILED error code, 476
ER_GRP_RPL_WHILE_SENDING_MSG_REC error code, 310
ER_GRP_RPL_WHILE_STOPPING_REP_CHANNEL error code, 310
ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODED error code, 306
ER_GRP_RPL_WRITE_TO_BINLOG_CACHE_FAILED error code, 308
ER_GRP_RPL_WRITE_TO_TRANSACTION_MESSAGE error code, 308
ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN error code, 104
ER_GRP_TRX_CONSISTENCY_BEFORE error code, 104
ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED error code, 104
ER_GRP_ELECTED_PRIMARY_GTID_INFORMATION error code, 497
ER_GR_HOLD_KILLED error code, 102
ER_GR_HOLD_MEMBER_STATUS_ERROR error code, 102
ER_GR_HOLD_WAIT_TIMEOUT error code, 102
ER_GTID_ALREADY_ADDED_BY_USER error code, 171
ER_GTID_EXECUTED_WAS_CHANGED error code, 55
ER_GTID_EXECUTED_WAS_UPDATED error code, 231
ER_GTID_MODE_CAN_ONLY_CHANGE_ONE_STEP_AT_A_TIME error code, 52
ER_GTID_MODE_OFF error code, 64
ER_GTID_MODE_ON_REQUIRES_ENFORCE_GTID_CONSISTENCY error code, 51
ER_GTID_NEXT_CANT_BE_AUTOMATIC_IF_GTID_NEVER_LISTENED_TO_IT error code, 50
ER_GTID_NEXT_TYPE_UNDEFINED_GROUP error code, 55
ER_GTID_NEXT_TYPE_UNDEFINED_GTID error code, 55
ER_GTID_PURGED_WAS_CHANGED error code, 55
ER_GTID_PURGED_WAS_UPDATED error code, 231
ER_IB_LIST_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION error code, 101
ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_ASSIGNMENT error code, 59
ER_IB_NOMINUS_SAFE_BINLOG_SPLITTABLE_STATEMENT_AND_ASSIGNMENT error code, 58
ER_IB_UNSAFE_CREATE_DROP_TEMPORARY_TABLE_IN_TRANSACTION error code, 51
ER_IB_UNSAFE_CREATE_SELECT error code, 51
ER_IB_UNSAFE_NON_TRANSACTIONAL_TABLE error code, 51
ER_HANDLERTON_OOM error code, 156
ER_HANDSHAKE_ERROR error code, 5
ER_HEALTH_ERROR error code, 516
ER_HEALTH_INFO error code, 516
ER_HEALTH_WARNING error code, 516
ER_HEALTH_WARNING_DISK_USAGE_LEVEL_1 error code, 516
ER_IB_HEALTH_WARNING_DISK_USAGE_LEVEL_2 error code, 516
ER_IB_HEALTH_WARNING_DISK_USAGE_LEVEL_3 error code, 517
ER_IB_HOSTNAME error code, 32
ER_HOSTNAME_DOESNT_RESOLVE_TO error code, 137
ER_HOSTNAME_RESEMBLES_IPV4 error code, 137
ER_HOSTNAME_TOO_LONG error code, 122
ER_HOSTNAME_TRUNCATED error code, 507
ER_HOST_IS_BLOCKED error code, 12
ER_HOST_NOT_PRIVILEGED error code, 12
ER_HYPERGRAPH_NOT_SUPPORTED_YET error code, 125
ER_IB_CANNOT_UPGRADE_WITH_DISCARDED_TABLESPACES error code, 507
ER_IB_CLONE_GTID_PERSIST error code, 348
ER_IB_CLONE_INTERNAL error code, 346
ER_IB_CLONE_NON_INNODB_TABLE error code, 490
ER_IB_CLONE_OPERATION error code, 490
ER_IB_CLONE_PUNCH_HOLE error code, 347
ER_IB_CLONE_RESTART error code, 490
ER_IB_CLONE_SQL error code, 347
ER_IB_CLONE_START_STOP error code, 490
ER_IB_CLONE_STATUS_FILE error code, 347
ER_IB_CLONE_TIMEOUT error code, 347
ER_IB_CLONE_USER_DATA error code, 490
ER_IB_CLONE_VALIDATE error code, 347
ER_IB_ERR_DECOMPRESS_FAILED error code, 513
ER_IB_LIST_WRONG_ENCRYPT_FAILED error code, 513
ER_IB_DBLWR_KEY_MISSING error code, 514
ER_IB_ERR_DDL_LOG_INSERT_FAILURE error code, 507
ER_IB_ERR_FOUND_N_DUPLICATE_KEYS error code, 511
ER_IB_ERR_FOUND_N_RECORDS_WRONG_ORDER error code, 511

ER_IB_ERR_INDEX_DUPLICATE_KEY error code, 510
ER_IB_ERR_INDEX_RECORDS_WRONG_ORDER error code, 510
ER_IB_ERR_LOG_PARSING_BUFFER_OVERFLOW error code, 509
ER_IB_ERR_NOT_ENOUGH_MEMORY_FOR_PARSE error code, 509
ER_IB_ERR_PAGE_ARCH_INVALID_DOUBLE_WRITE error code, 504
ER_IB_ERR_PAGE_ARCH_INVALID_FORMAT error code, 504
ER_IB_ERR_PAGE_ARCH_RECOVERY_FAILED error code, 504
ER_IB_ERR_PARALLEL_READ_OOM error code, 511
ER_IB_ERR_RECOVERY_REDO_DISABLED error code, 506
ER_IB_ERR_SCHED_SETAFFNINITY_FAILED error code, 509
ER_IB_ERR_TEMP_TABLESPACE_DIR_CONTAINS_SEMICOLONS error code, 509
ER_IB_ERR_TEMP_TABLESPACE_DIR_DOESNT_EXIST error code, 508
ER_IB_ERR_TEMP_TABLESPACE_DIR_EMPTY error code, 509
ER_IB_ERR_TEMP_TABLESPACE_DIR_SUBDIR_OF_DATA error code, 509
ER_IB_ERR_UNKNOWN_PAGE_FETCH_MODE error code, 509
ER_IB_ERR_ZLIB_BUF_ERROR error code, 510
ER_IB_ERR_ZLIB_DATA_ERROR error code, 510
ER_IB_ERR_ZLIB_MEM_ERROR error code, 510
ER_IB_ERR_ZLIB_UNCOMPRESS_FAILED error code, 510
ER_IB_ERR_ZLIB_UNKNOWN_ERROR error code, 510
ER_IB_FAILED_TO_DELETE_TABLESPACE_FILE error code, 508
ER_IB_INNODB_TBSP_OUT_OF_SPACE error code, 517
ER_IB_LOB_ROLLBACK_INDEX_LEN error code, 496
ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION error code, 507
ER_IB_MSG_0 error code, 333
ER_IB_MSG_1 error code, 333
ER_IB_MSG_10 error code, 334
ER_IB_MSG_100 error code, 342
ER_IB_MSG_1000 error code, 427
ER_IB_MSG_1001 error code, 427
ER_IB_MSG_1002 error code, 427
ER_IB_MSG_1003 error code, 427
ER_IB_MSG_1004 error code, 427
ER_IB_MSG_1005 error code, 427
ER_IB_MSG_1006 error code, 427
ER_IB_MSG_1007 error code, 427
ER_IB_MSG_1008 error code, 427
ER_IB_MSG_1009 error code, 427
ER_IB_MSG_101 error code, 342
ER_IB_MSG_1010 error code, 427
ER_IB_MSG_1011 error code, 428
ER_IB_MSG_1012 error code, 428
ER_IB_MSG_1013 error code, 428
ER_IB_MSG_1014 error code, 428
ER_IB_MSG_1015 error code, 428
ER_IB_MSG_1016 error code, 428
ER_IB_MSG_1017 error code, 428
ER_IB_MSG_1018 error code, 428
ER_IB_MSG_1019 error code, 428
ER_IB_MSG_102 error code, 342
ER_IB_MSG_1020 error code, 428
ER_IB_MSG_1021 error code, 428
ER_IB_MSG_1022 error code, 429
ER_IB_MSG_1023 error code, 429
ER_IB_MSG_1024 error code, 429
ER_IB_MSG_1025 error code, 429
ER_IB_MSG_1026 error code, 429
ER_IB_MSG_1027 error code, 429
ER_IB_MSG_1028 error code, 429
ER_IB_MSG_1029 error code, 429
ER_IB_MSG_103 error code, 342
ER_IB_MSG_1030 error code, 429
ER_IB_MSG_1031 error code, 429
ER_IB_MSG_1032 error code, 429
ER_IB_MSG_1033 error code, 430
ER_IB_MSG_1034 error code, 430
ER_IB_MSG_1035 error code, 430
ER_IB_MSG_1036 error code, 430
ER_IB_MSG_1037 error code, 430
ER_IB_MSG_1038 error code, 430
ER_IB_MSG_1039 error code, 430
ER_IB_MSG_104 error code, 342
ER_IB_MSG_1040 error code, 430
ER_IB_MSG_1041 error code, 430
ER_IB_MSG_1042 error code, 430
ER_IB_MSG_1043 error code, 430
ER_IB_MSG_1044 error code, 431
ER_IB_MSG_1045 error code, 431
ER_IB_MSG_1046 error code, 431
ER_IB_MSG_1047 error code, 431
ER_IB_MSG_1048 error code, 431
ER_IB_MSG_1049 error code, 431
ER_IB_MSG_105 error code, 342
ER_IB_MSG_1050 error code, 431
ER_IB_MSG_1051 error code, 431
ER_IB_MSG_1052 error code, 431
ER_IB_MSG_1053 error code, 431
ER_IB_MSG_1054 error code, 432
ER_IB_MSG_1055 error code, 432
ER_IB_MSG_1056 error code, 432
ER_IB_MSG_1057 error code, 432
ER_IB_MSG_1058 error code, 432
ER_IB_MSG_1059 error code, 432
ER_IB_MSG_106 error code, 342
ER_IB_MSG_1060 error code, 432
ER_IB_MSG_1061 error code, 432
ER_IB_MSG_1062 error code, 432

ER_IB_MSG_1272 error code, 461
ER_IB_MSG_1273 error code, 462
ER_IB_MSG_1274 error code, 463
ER_IB_MSG_1275 error code, 463
ER_IB_MSG_1276 error code, 463
ER_IB_MSG_1277 error code, 463
ER_IB_MSG_1278 error code, 463
ER_IB_MSG_1279 error code, 463
ER_IB_MSG_128 error code, 344
ER_IB_MSG_1280 error code, 464
ER_IB_MSG_1281 error code, 464
ER_IB_MSG_1282 error code, 464
ER_IB_MSG_1283 error code, 464
ER_IB_MSG_1284 error code, 464
ER_IB_MSG_1285 error code, 487
ER_IB_MSG_129 error code, 345
ER_IB_MSG_13 error code, 334
ER_IB_MSG_130 error code, 345
ER_IB_MSG_131 error code, 345
ER_IB_MSG_132 error code, 345
ER_IB_MSG_133 error code, 345
ER_IB_MSG_134 error code, 345
ER_IB_MSG_135 error code, 345
ER_IB_MSG_1357 error code, 508
ER_IB_MSG_1358 error code, 508
ER_IB_MSG_1359 error code, 508
ER_IB_MSG_136 error code, 345
ER_IB_MSG_137 error code, 345
ER_IB_MSG_1372 error code, 509
ER_IB_MSG_1373 error code, 509
ER_IB_MSG_1374 error code, 509
ER_IB_MSG_1375 error code, 510
ER_IB_MSG_138 error code, 345
ER_IB_MSG_1381 error code, 510
ER_IB_MSG_139 error code, 345
ER_IB_MSG_14 error code, 334
ER_IB_MSG_140 error code, 346
ER_IB_MSG_141 error code, 346
ER_IB_MSG_142 error code, 346
ER_IB_MSG_143 error code, 346
ER_IB_MSG_144 error code, 346
ER_IB_MSG_145 error code, 346
ER_IB_MSG_146 error code, 346
ER_IB_MSG_147 error code, 346
ER_IB_MSG_148 error code, 346
ER_IB_MSG_149 error code, 346
ER_IB_MSG_15 error code, 334
ER_IB_MSG_150 error code, 347
ER_IB_MSG_151 error code, 347
ER_IB_MSG_152 error code, 347
ER_IB_MSG_153 error code, 347
ER_IB_MSG_154 error code, 347
ER_IB_MSG_155 error code, 347
ER_IB_MSG_156 error code, 348
ER_IB_MSG_157 error code, 348
ER_IB_MSG_158 error code, 348
ER_IB_MSG_159 error code, 348
ER_IB_MSG_16 error code, 334
ER_IB_MSG_160 error code, 348
ER_IB_MSG_161 error code, 348
ER_IB_MSG_162 error code, 348
ER_IB_MSG_163 error code, 348
ER_IB_MSG_164 error code, 348
ER_IB_MSG_165 error code, 348
ER_IB_MSG_166 error code, 349
ER_IB_MSG_167 error code, 349
ER_IB_MSG_168 error code, 349
ER_IB_MSG_169 error code, 349
ER_IB_MSG_17 error code, 334
ER_IB_MSG_170 error code, 349
ER_IB_MSG_171 error code, 349
ER_IB_MSG_172 error code, 349
ER_IB_MSG_173 error code, 349
ER_IB_MSG_174 error code, 349
ER_IB_MSG_175 error code, 349
ER_IB_MSG_176 error code, 349
ER_IB_MSG_177 error code, 350
ER_IB_MSG_178 error code, 350
ER_IB_MSG_179 error code, 350
ER_IB_MSG_18 error code, 334
ER_IB_MSG_180 error code, 350
ER_IB_MSG_181 error code, 350
ER_IB_MSG_182 error code, 350
ER_IB_MSG_183 error code, 350
ER_IB_MSG_184 error code, 350
ER_IB_MSG_185 error code, 350
ER_IB_MSG_186 error code, 350
ER_IB_MSG_187 error code, 350
ER_IB_MSG_188 error code, 351
ER_IB_MSG_189 error code, 351
ER_IB_MSG_19 error code, 335
ER_IB_MSG_190 error code, 351
ER_IB_MSG_191 error code, 351
ER_IB_MSG_192 error code, 351
ER_IB_MSG_193 error code, 351
ER_IB_MSG_194 error code, 351
ER_IB_MSG_195 error code, 351
ER_IB_MSG_196 error code, 351
ER_IB_MSG_197 error code, 351
ER_IB_MSG_198 error code, 351
ER_IB_MSG_199 error code, 352
ER_IB_MSG_2 error code, 333
ER_IB_MSG_20 error code, 335
ER_IB_MSG_200 error code, 352
ER_IB_MSG_201 error code, 352
ER_IB_MSG_202 error code, 352
ER_IB_MSG_203 error code, 352
ER_IB_MSG_204 error code, 352
ER_IB_MSG_205 error code, 352
ER_IB_MSG_206 error code, 352
ER_IB_MSG_207 error code, 352
ER_IB_MSG_208 error code, 352
ER_IB_MSG_209 error code, 352
ER_IB_MSG_21 error code, 335
ER_IB_MSG_210 error code, 353
ER_IB_MSG_211 error code, 353

ER_IB_MSG_526 error code, 382
ER_IB_MSG_527 error code, 383
ER_IB_MSG_528 error code, 383
ER_IB_MSG_529 error code, 383
ER_IB_MSG_53 error code, 338
ER_IB_MSG_530 error code, 383
ER_IB_MSG_531 error code, 383
ER_IB_MSG_532 error code, 383
ER_IB_MSG_533 error code, 383
ER_IB_MSG_534 error code, 383
ER_IB_MSG_535 error code, 383
ER_IB_MSG_536 error code, 383
ER_IB_MSG_537 error code, 383
ER_IB_MSG_538 error code, 384
ER_IB_MSG_539 error code, 384
ER_IB_MSG_54 error code, 338
ER_IB_MSG_540 error code, 384
ER_IB_MSG_541 error code, 384
ER_IB_MSG_542 error code, 384
ER_IB_MSG_543 error code, 384
ER_IB_MSG_544 error code, 384
ER_IB_MSG_545 error code, 384
ER_IB_MSG_546 error code, 384
ER_IB_MSG_547 error code, 384
ER_IB_MSG_548 error code, 384
ER_IB_MSG_549 error code, 385
ER_IB_MSG_55 error code, 338
ER_IB_MSG_550 error code, 385
ER_IB_MSG_551 error code, 385
ER_IB_MSG_552 error code, 385
ER_IB_MSG_553 error code, 385
ER_IB_MSG_554 error code, 385
ER_IB_MSG_555 error code, 385
ER_IB_MSG_556 error code, 385
ER_IB_MSG_557 error code, 385
ER_IB_MSG_558 error code, 385
ER_IB_MSG_559 error code, 385
ER_IB_MSG_56 error code, 338
ER_IB_MSG_560 error code, 386
ER_IB_MSG_561 error code, 386
ER_IB_MSG_562 error code, 386
ER_IB_MSG_563 error code, 386
ER_IB_MSG_564 error code, 386
ER_IB_MSG_565 error code, 386
ER_IB_MSG_566 error code, 386
ER_IB_MSG_567 error code, 386
ER_IB_MSG_568 error code, 386
ER_IB_MSG_569 error code, 387
ER_IB_MSG_57 error code, 338
ER_IB_MSG_570 error code, 387
ER_IB_MSG_571 error code, 387
ER_IB_MSG_572 error code, 387
ER_IB_MSG_573 error code, 387
ER_IB_MSG_574 error code, 387
ER_IB_MSG_575 error code, 387
ER_IB_MSG_576 error code, 387
ER_IB_MSG_577 error code, 387
ER_IB_MSG_578 error code, 387
ER_IB_MSG_579 error code, 387
ER_IB_MSG_57_STAT_SPACE_DELETE_FAIL error code, 503
ER_IB_MSG_57_UNDO_SPACE_DELETE_FAIL error code, 499
ER_IB_MSG_58 error code, 338
ER_IB_MSG_580 error code, 388
ER_IB_MSG_581 error code, 388
ER_IB_MSG_582 error code, 388
ER_IB_MSG_583 error code, 388
ER_IB_MSG_584 error code, 388
ER_IB_MSG_585 error code, 388
ER_IB_MSG_586 error code, 388
ER_IB_MSG_587 error code, 388
ER_IB_MSG_588 error code, 388
ER_IB_MSG_589 error code, 388
ER_IB_MSG_59 error code, 338
ER_IB_MSG_590 error code, 388
ER_IB_MSG_591 error code, 389
ER_IB_MSG_592 error code, 389
ER_IB_MSG_593 error code, 389
ER_IB_MSG_594 error code, 389
ER_IB_MSG_595 error code, 389
ER_IB_MSG_596 error code, 389
ER_IB_MSG_597 error code, 389
ER_IB_MSG_598 error code, 389
ER_IB_MSG_599 error code, 389
ER_IB_MSG_6 error code, 333
ER_IB_MSG_60 error code, 338
ER_IB_MSG_600 error code, 389
ER_IB_MSG_601 error code, 389
ER_IB_MSG_602 error code, 390
ER_IB_MSG_603 error code, 390
ER_IB_MSG_604 error code, 390
ER_IB_MSG_605 error code, 390
ER_IB_MSG_606 error code, 390
ER_IB_MSG_607 error code, 390
ER_IB_MSG_608 error code, 390
ER_IB_MSG_609 error code, 390
ER_IB_MSG_61 error code, 338
ER_IB_MSG_610 error code, 390
ER_IB_MSG_611 error code, 390
ER_IB_MSG_612 error code, 390
ER_IB_MSG_613 error code, 391
ER_IB_MSG_614 error code, 391
ER_IB_MSG_615 error code, 391
ER_IB_MSG_616 error code, 391
ER_IB_MSG_617 error code, 391
ER_IB_MSG_618 error code, 391
ER_IB_MSG_619 error code, 391
ER_IB_MSG_62 error code, 338
ER_IB_MSG_620 error code, 391
ER_IB_MSG_621 error code, 391
ER_IB_MSG_622 error code, 391
ER_IB_MSG_623 error code, 391
ER_IB_MSG_624 error code, 392
ER_IB_MSG_625 error code, 392
ER_IB_MSG_626 error code, 392

ER_IB_MSG_940 error code, 421
ER_IB_MSG_941 error code, 421
ER_IB_MSG_942 error code, 421
ER_IB_MSG_943 error code, 421
ER_IB_MSG_944 error code, 421
ER_IB_MSG_945 error code, 422
ER_IB_MSG_946 error code, 422
ER_IB_MSG_947 error code, 422
ER_IB_MSG_948 error code, 422
ER_IB_MSG_949 error code, 422
ER_IB_MSG_95 error code, 341
ER_IB_MSG_950 error code, 422
ER_IB_MSG_951 error code, 422
ER_IB_MSG_952 error code, 422
ER_IB_MSG_953 error code, 422
ER_IB_MSG_954 error code, 422
ER_IB_MSG_955 error code, 422
ER_IB_MSG_956 error code, 423
ER_IB_MSG_957 error code, 423
ER_IB_MSG_958 error code, 423
ER_IB_MSG_959 error code, 423
ER_IB_MSG_96 error code, 342
ER_IB_MSG_960 error code, 423
ER_IB_MSG_961 error code, 423
ER_IB_MSG_962 error code, 423
ER_IB_MSG_963 error code, 423
ER_IB_MSG_964 error code, 423
ER_IB_MSG_965 error code, 423
ER_IB_MSG_966 error code, 423
ER_IB_MSG_967 error code, 424
ER_IB_MSG_968 error code, 424
ER_IB_MSG_969 error code, 424
ER_IB_MSG_97 error code, 342
ER_IB_MSG_970 error code, 424
ER_IB_MSG_971 error code, 424
ER_IB_MSG_972 error code, 424
ER_IB_MSG_973 error code, 424
ER_IB_MSG_974 error code, 424
ER_IB_MSG_975 error code, 424
ER_IB_MSG_976 error code, 424
ER_IB_MSG_977 error code, 424
ER_IB_MSG_978 error code, 425
ER_IB_MSG_979 error code, 425
ER_IB_MSG_98 error code, 342
ER_IB_MSG_980 error code, 425
ER_IB_MSG_981 error code, 425
ER_IB_MSG_982 error code, 425
ER_IB_MSG_983 error code, 425
ER_IB_MSG_984 error code, 425
ER_IB_MSG_985 error code, 425
ER_IB_MSG_986 error code, 425
ER_IB_MSG_987 error code, 425
ER_IB_MSG_988 error code, 425
ER_IB_MSG_989 error code, 426
ER_IB_MSG_99 error code, 342
ER_IB_MSG_990 error code, 426
ER_IB_MSG_991 error code, 426
ER_IB_MSG_992 error code, 426
ER_IB_MSG_993 error code, 426
ER_IB_MSG_994 error code, 426
ER_IB_MSG_995 error code, 426
ER_IB_MSG_996 error code, 426
ER_IB_MSG_997 error code, 426
ER_IB_MSG_998 error code, 426
ER_IB_MSG_999 error code, 426
ER_IB_MSG_BAD_DBWR_FILE_NAME error code, 499
ER_IB_MSG_BTREE_LEVEL_LIMIT_EXCEEDED error code, 490
ER_IB_MSG_CANNOT_FIND_DD_UNDO_SPACE error code, 505
ER_IB_MSG_CANNOT_OPEN_57_UNDO error code, 434
ER_IB_MSG_CLOCK_GETTIME_FAILED error code, 487
ER_IB_MSG_CLOCK_MONOTONIC_UNSUPPORTED error code, 487
ER_IB_MSG_CREATED_UNDO_SPACE error code, 513
ER_IB_MSG_CREATE_LOG_FILE error code, 503
ER_IB_MSG_DBWR_1285 error code, 499
ER_IB_MSG_DBWR_1286 error code, 499
ER_IB_MSG_DBWR_1287 error code, 499
ER_IB_MSG_DBWR_1288 error code, 499
ER_IB_MSG_DBWR_1290 error code, 499
ER_IB_MSG_DBWR_1291 error code, 499
ER_IB_MSG_DBWR_1292 error code, 500
ER_IB_MSG_DBWR_1293 error code, 500
ER_IB_MSG_DBWR_1294 error code, 500
ER_IB_MSG_DBWR_1295 error code, 500
ER_IB_MSG_DBWR_1296 error code, 500
ER_IB_MSG_DBWR_1297 error code, 500
ER_IB_MSG_DBWR_1298 error code, 500
ER_IB_MSG_DBWR_1300 error code, 500
ER_IB_MSG_DBWR_1301 error code, 500
ER_IB_MSG_DBWR_1304 error code, 500
ER_IB_MSG_DBWR_1305 error code, 500
ER_IB_MSG_DBWR_1306 error code, 501
ER_IB_MSG_DBWR_1307 error code, 501
ER_IB_MSG_DBWR_1308 error code, 501
ER_IB_MSG_DBWR_1309 error code, 501
ER_IB_MSG_DBWR_1310 error code, 501
ER_IB_MSG_DBWR_1311 error code, 501
ER_IB_MSG_DBWR_1312 error code, 501
ER_IB_MSG_DBWR_1313 error code, 501
ER_IB_MSG_DBWR_1314 error code, 501
ER_IB_MSG_DBWR_1315 error code, 501
ER_IB_MSG_DBWR_1316 error code, 501
ER_IB_MSG_DBWR_1317 error code, 502
ER_IB_MSG_DBWR_1318 error code, 502
ER_IB_MSG_DBWR_1319 error code, 502
ER_IB_MSG_DBWR_1320 error code, 502
ER_IB_MSG_DBWR_1321 error code, 502
ER_IB_MSG_DBWR_1322 error code, 502
ER_IB_MSG_DBWR_1323 error code, 502
ER_IB_MSG_DBWR_1324 error code, 502

ER_IB_MSG_DBLWR_1325 error code, 502	ER_IB_MSG_INVALID_LOCATION_WRONG_DB error code, 505
ER_IB_MSG_DBLWR_1326 error code, 502	ER_IB_MSG_LOCK_FREE_HASH_USAGE_STATS error code, 471
ER_IB_MSG_DBLWR_1327 error code, 502	ER_IB_MSG_MADVISE_FAILED error code, 469
ER_IB_MSG_DDL_LOG_DELETE_BY_ID_OK error code, 394	ER_IB_MSG_MADV_DONTDUMP_UNSUPPORTED error code, 469
ER_IB_MSG_DDL_LOG_DELETE_BY_ID_TMCT error code, 485	ER_IB_MSG_MASTER_KEY_ROTATED error code, 513
ER_IB_MSG_DDL_LOG_FAIL_POST_DDL error code, 485	ER_IB_MSG_MAX_UNDO_SPACES_REACHED error code, 469
ER_IB_MSG_DEPRECATED_INNODB_UNDO_TABLESPACE error code, 471	ER_IB_MSG_NOT_END_WITH_IBU error code, 470
ER_IB_MSG_DICT_PARTITION_NOT_FOUND error code, 498	ER_IB_MSG_NO_ENCRYPT_PROGRESS_FOUND error code, 463
ER_IB_MSG_DIR_DOES_NOT_EXIST error code, 471	ER_IB_MSG_NUM_POOLS error code, 469
ER_IB_MSG_DOWNGRADE_PARTITION_FILE error code, 496	ER_IB_MSG_PAGE_ARCH_NO_RESET_POINTS error code, 503
ER_IB_MSG_DROPPED_UNDO_SPACE error code, 513	ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER error code, 485
ER_IB_MSG_ERROR_OPENING_NEW_UNDO_SPACE error code, 469	ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT error code, 485
ER_IB_MSG_FAILED_SDI_Z_BUF_ERROR error code, 469	ER_IB_MSG_RESUME_OP_FOR_SPACE error code, 463
ER_IB_MSG_FAILED_SDI_Z_MEM_ERROR error code, 470	ER_IB_MSG_SCANNING_TEMP_TABLESPACE_DIR error code, 508
ER_IB_MSG_FAILED_TO_ALLOCATE_WAIT error code, 469	ER_IB_MSG_SDI_Z_STREAM_ERROR error code, 470
ER_IB_MSG_FAILED_TO_FINISH_TRUNCATE error code, 471	ER_IB_MSG_SDI_Z_UNKNOWN_ERROR error code, 470
ER_IB_MSG_FAIL_TO_SAVE_SPACE_STATE error code, 469	ER_IB_MSG_SKIP_HIDDEN_DIR error code, 495
ER_IB_MSG_FIL_STATE_MOVED_CHANGED_NAME error code, 497	ER_IB_MSG_STATS_SAMPLING_TOO_LARGE error code, 517
ER_IB_MSG_FIL_STATE_MOVED_CHANGED_PATH error code, 497	ER_IB_MSG_TOO_LONG_PATH error code, 486
ER_IB_MSG_FIL_STATE_MOVED_CORRECTED error code, 497	ER_IB_MSG_TRX_RECOVERY_ROLLBACK_COMPLETED error code, 446
ER_IB_MSG_FIL_STATE_MOVED_TOO_MANY error code, 497	ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETED error code, 507
ER_IB_MSG_FOUND_WRONG_UNDO_SPACE error code, 470	ER_IB_MSG_UNDO_ALTERED_ACTIVE error code, 511
ER_IB_MSG_GENERAL_TABLESPACE_UNDER_DATADIR error code, 370	ER_IB_MSG_UNDO_ALTERED_INACTIVE error code, 511
ER_IB_MSG_GTID_FLUSH_AT_SHUTDOWN error code, 503	ER_IB_MSG_UNDO_INJECT_CRASH error code, 511
ER_IB_MSG_IGNORE_SCAN_PATH error code, 368	ER_IB_MSG_UNDO_INJECT_FAILURE error code, 512
ER_IB_MSG_IMPLICIT_TABLESPACE_IN_DATADIR error code, 370	ER_IB_MSG_UNDO_MARKED_ACTIVE error code, 511
ER_IB_MSG_INCORRECT_SIZE error code, 513	ER_IB_MSG_UNDO_MARKED_EMPTY error code, 511
ER_IB_MSG_INJECT_CRASH error code, 512	ER_IB_MSG_UNDO_MARKED_FOR_TRUNCATE error code, 443
ER_IB_MSG_INJECT_FAILURE error code, 512	ER_IB_MSG_UNDO_TRUNCATE_COMPLETE error code, 444
ER_IB_MSG_INNODB_END_INITIALIZE error code, 503	ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_CLONE error code, 511
ER_IB_MSG_INNODB_START_INITIALIZE error code, 503	ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_FAILURE error code, 444
ER_IB_MSG_INVALID_LOCATION_FOR_TABLE error code, 386	ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_LOG_CREATE error code, 444
ER_IB_MSG_INVALID_LOCATION_FOR_TABLESPACE error code, 505	

ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_MDL error code, 511	ER_ILLEGAL_PRIVILEGE_LEVEL error code, 85
ER_IB_MSG_UNDO_TRUNCATE_FAIL_TO_READ_LOGFILE error code, 443	ER_ILLEGAL_REFERENCE error code, 19
ER_IB_MSG_UNDO_TRUNCATE_START error code, 443	ER_ILLEGAL_USER_VAR error code, 63
ER_IB_MSG_UNDO_TRUNCATE_TOO_OFTEN error code, 504	ER_ILLEGAL_VALUE_FOR_TYPE error code, 26
ER_IB_MSG_UNDO_TRUNC_BEFORE_UNDO_LOGGING error code, 470	ER_IMPLICIT_COMPARISON_FOR_JSON error code, 124
ER_IB_MSG_UNDO_TRUNC_BEFOR_DD_UPDATE error code, 470	ER_IMPOSSIBLE_STRING_CONVERSION error code, 124
ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE error code, 470	ER_IMP_INCOMPATIBLE_CFG_VERSION error code, 120
ER_IB_MSG_UNDO_TRUNC_TRUNK_BEFORE_RSEG error code, 470	ER_IMP_INCOMPATIBLE_DD_VERSION error code, 84
ER_IB_MSG_UNEXPECTED_FILE_EXISTS error code, 361	ER_IMP_INCOMPATIBLE_MYSQLD_VERSION error code, 84
ER_IB_MSG_UNPROTECTED_LOCATION_ALLOWED error code, 366	ER_IMP_INCOMPATIBLE_SDI_VERSION error code, 84
ER_IB_MSG_UPGRADE_PARTITION_FILE error code, 496	ER_IMP_NO_FILES_MATCHED error code, 84
ER_IB_MSG_UPGRADE_PARTITION_FILE_IMPORT error code, 497	ER_IMP_SCHEMA_DOES_NOT_EXIST error code, 84
ER_IB_MSG_USING_UNDO_SPACE error code, 469	ER_IMP_TABLE_ALREADY_EXISTS error code, 84
ER_IB_MSG_WAIT_FOR_ENCRYPT_THREAD error code, 463	ER_INCONSISTENT_ERROR error code, 455
ER_IB_MSG_WRONG_TABLESPACE_DIR error code, 471	ER_INCONSISTENT_PARTITION_INFO_ERROR error code, 33
ER_IB_RECV_FIRST_REC_GROUP_INVALID error code, 486	ER_INCONSISTENT_TYPE_OF_FUNCTIONS_ERROR error code, 33
ER_IB_RELCK_LATCH_ORDER_VIOLATION error code, 508	ER_INCORRECT_CURRENT_PASSWORD error code, 113
ER_IB_TABLESPACE_PATH_VALIDATION_SKIPPED error code, 506	ER_INCORRECT_GLOBAL_LOCAL_VAR error code, 18
ER_IB_TMP_TABLESPACE_CANNOT_CREATE_DIRECTORY error code, 508	ER_INCORRECT_TYPE error code, 64
ER_IB_UNABLE_TO_EXPAND_TEMPORARY_TABLESPACE error code, 508	ER_INDEX_COLUMN_TOO_LONG error code, 46
ER_IB_WARN_OPEN_PARTITION_FILE error code, 497	ER_INDEX_CORRUPT error code, 46
ER_IB_WRN_FAILED_TO_ACQUIRE_SERVICE error code, 520	ER_INDEX_TYPE_NOT_SUPPORTED_FOR_SPATIAL_INDEX error code, 96
ER_IB_WRN_FAST_SHUTDOWN_REDO_DISABLED error code, 506	ER_INIT_BOOTSTRAP_COMPLETE error code, 179
ER_IB_WRN_OLD_GEOMETRY_TYPE error code, 520	ER_INIT_CANT_OPEN_BOOTSTRAP_FILE error code, 179
ER_IB_WRN_PAGE_ARCH_FLUSH_DATA error code, 503	ER_INIT_CREATING_DD error code, 180
ER_IB_WRN_REDO_DISABLED error code, 506	ER_INIT_DATABRICKS_NPQDATADIR_EXISTS_AND_NOT_WRITABLE_WONT_INIT error code, 180
ER_IB_WRN_REDO_ENABLED error code, 506	ER_INIT_DATABRICKS_NPQDATADIR_EXISTS_AND_PATH_TOO_LONG_WONT_INIT error code, 180
ER_IDENT_CAUSES_TOO_LONG_PATH error code, 57	ER_INIT_DATADIR_EXISTS_WONT_INITIALIZE error code, 179
ER_IDENT_CAUSES_TOO_LONG_PATH_IN_UPGRADE error code, 492	ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE error code, 179
ER_ILLEGAL_GRANT_FOR_TABLE error code, 13	ER_INIT_FAILED_TO_GENERATE_ROOT_PASSWORD error code, 495
ER_ILLEGAL_HA error code, 5	ER_INIT_GENERATING_TEMP_PASSWORD_FOR_ROOT error code, 179
ER_ILLEGAL_HA_CREATE_OPTION error code, 32	ER_INIT_ROOT_WITHOUT_PASSWORD error code, 179
	ER_INNODB_ACTIVE_INDEX_CHANGE_FAILED error code, 246
	ER_INNODB_AUTOEXTEND_SIZE_OUT_OF_RANGE error code, 129
	ER_INNODB_CANNOT_BE_IGNORED error code, 93
	ER_INNODB_CANNOT_CREATE_TABLE error code, 246

ER_INNODB_CANT_BUILD_INDEX_XLATION_TABLE error code, 228
ER_INNODB_CANT_FIND_INDEX_IN_INNODB_DD error code, 227
ER_INNODB_CANT_OPEN_TABLE error code, 227
ER_INNODB_CLOSING_CONNECTION_ROLLS_BACK error code, 227
ER_INNODB_CLUSTERED_INDEX_PRIVATE error code, 228
ER_INNODB_COMPRESSION_FAILURE error code, 129
ER_INNODB_DIFF_IN_REF_LEN error code, 246
ER_INNODB_DIRTY_WATER_MARK_NOT_LOW error code, 227
ER_INNODB_ERROR_LOGGER_FATAL_MSG error code, 248
ER_INNODB_ERROR_LOGGER_MSG error code, 248
ER_INNODB_FAILED_TO_FIND_IDX error code, 245
ER_INNODB_FAILED_TO_FIND_IDX_FROM_DICT_CACHE error code, 245
ER_INNODB_FAILED_TO_FIND_IDX_WITH_KEY_NO error code, 245
ER_INNODB_FILES_SAME error code, 227
ER_INNODB_FORCED_RECOVERY error code, 58
ER_INNODB_FT_AUX_NOT_HEX_ID error code, 58
ER_INNODB_FT_LIMIT error code, 52
ER_INNODB_FT_WRONG_DOCID_COLUMN error code, 52
ER_INNODB_FT_WRONG_DOCID_INDEX error code, 52
ER_INNODB_IDX_CNT_FEWER_THAN_DEFINED_IN_MYSQLNNODB_REDLOG_ARCHIVE_FAILED error code, 246
ER_INNODB_IDX_CNT_MORE_THAN_DEFINED_IN_MYSQLNNODB_REDLOG_ARCHIVE_FILE_CREATE error code, 246
ER_INNODB_IDX_COLUMN_CNT_DIFF error code, 246
ER_INNODB_ILLEGAL_COLON_IN_POOL error code, 226
ER_INNODB_IMPORT_ERROR error code, 54
ER_INNODB_INCOMPATIBLE_WITH_TABLESPACE error code, 129
ER_INNODB_INDEX_COLUMN_INFO_UNLIKE_MYSQL error code, 227
ER_INNODB_INDEX_CORRUPT error code, 54
ER_INNODB_INTERNAL_INDEX error code, 246
ER_INNODB_INVALID_AUTOEXTEND_SIZE_VALUE error code, 129
ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY error code, 226
ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY_LOCATION error code, 472
ER_INNODB_INVALID_LOG_GROUP_HOME_DIR error code, 226
ER_INNODB_INVALID_MONITOR_COUNTER_NAME error code, 247
ER_INNODB_INVALID_PAGE_SIZE error code, 227
ER_INNODB_IO_CAPACITY_EXCEEDS_MAX error code, 227
ER_INNODB_IO_WRITE_ERROR_RETRYING error code, 514
ER_INNODB_IO_WRITE_FAILED error code, 514
ER_INNODB_MANDATORY error code, 140
ER_INNODB_MONITOR_DEFAULT_VALUE_NOT_DEFINED error code, 247
ER_INNODB_MONITOR_IS_ENABLED error code, 247
ER_INNODB_NO_FT_TEMP_TABLE error code, 52
ER_INNODB_ONLINE_LOG_TOO_BIG error code, 52
ER_INNODB_OUT_OF_RESOURCES error code, 498
ER_INNODB_PARTITION_TABLE_LOWERCASED error code, 228
ER_INNODB_PK_NOT_IN_MYSQL error code, 228
ER_INNODB_PK_ONLY_IN_MYSQL error code, 228
ER_INNODB_READ_ONLY error code, 58
ER_INNODB_REDO_ARCHIVING_ENABLED error code, 124
ER_INNODB_REDO_DISABLED error code, 123
ER_INNODB_REDO_LOG_ARCHIVE_ACTIVE error code, 109
ER_INNODB_REDO_LOG_ARCHIVE_DIRS_INVALID error code, 109
ER_INNODB_REDO_LOG_ARCHIVE_DIR_CLASH error code, 109
ER_INNODB_REDO_LOG_ARCHIVE_DIR_EMPTY error code, 109
ER_INNODB_REDO_LOG_ARCHIVE_DIR_PERMISSIONS error code, 109
ER_INNODB_REDLOG_ARCHIVE_FAILED error code, 109
ER_INNODB_REDLOG_ARCHIVE_INACTIVE error code, 109
ER_INNODB_REDLOG_ARCHIVE_LABEL_NOT_FOUND error code, 109
ER_INNODB_REDLOG_ARCHIVE_NO SUCH_DIR error code, 109
ER_INNODB_REDLOG_ARCHIVE_SESSION error code, 110
ER_INNODB_REDLOG_ARCHIVE_START_SUBDIR_PATH error code, 108
ER_INNODB_REDLOG_ARCHIVE_START_TIMEOUT error code, 108
ER_INNODB_TRX_XLATION_TABLE_OOM error code, 227
ER_INNODB_UNABLE_TO_ACQUIRE_DD_OBJECT error code, 504
ER_INNODB_UNDO_LOG_FULL error code, 60
ER_INNODB_UNKNOWN_COLLATION error code, 226
ER_INNODB_UNREGISTERED_TRX_ACTIVE error code, 227
ER_INNODB_USE_MONITOR_GROUP_NAME error code, 246

ER_INSECURE_CHANGE_MASTER error code, 49
ER_INSECURE_PLAIN_TEXT error code, 49
ER_INSERT_INFO error code, 9
ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_DIRECT
error code, 44
ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_INFORMAT
error code, 44
ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_SQL_ROLLBACK
error code, 45
ER_INSTALL_PLUGIN_CONFLICT_CLIENT error
code, 131
ER_INSTALL_PLUGIN_CONFLICT_LOG error code,
525
ER_INTERNAL_ERROR error code, 53
ER_INVALID_ADMIN_ADDRESS error code, 474
ER_INVALID_ARGUMENT_FOR_LOGARITHM error
code, 60
ER_INVALID_BITWISE_AGGREGATE_OPERANDS_SIZE
error code, 75
ER_INVALID_BITWISE_OPERANDS_SIZE error code,
75
ER_INVALID_CAST error code, 125
ER_INVALID_CAST_POLYGON_RING_DIRECTION
error code, 130
ER_INVALID_CAST_TO_GEOMETRY error code, 130
ER_INVALID_CAST_TO_JSON error code, 70
ER_INVALID_CHARACTER_STRING error code, 22
ER_INVALID_CHARSET_AND_DEFAULT_IS_MB
error code, 167
ER_INVALID_COLLATION_FOR_CHARSET error
code, 233
ER_INVALID_DD_OBJECT error code, 75
ER_INVALID_DD_OBJECT_ID error code, 75
ER_INVALID_DD_OBJECT_NAME error code, 75
ER_INVALID_DEFAULT error code, 7
ER_INVALID_DEFAULT_UTF8MB4_COLLATION
error code, 95
ER_INVALID_ENCRYPTION_OPTION error code, 73
ER_INVALID_ENCRYPTION_REQUEST error code,
107
ER_INVALID_ERROR_LOG_NAME error code, 150
ER_INVALID_FIELD_SIZE error code, 60
ER_INVALID_GEOJSON_CRS_NOT_TOP_LEVEL
error code, 90
ER_INVALID_GEOJSON_MISSING_MEMBER error
code, 64
ER_INVALID_GEOJSON_UNSPECIFIED error code,
64
ER_INVALID_GEOJSON_WRONG_TYPE error code,
64
ER_INVALID_GROUP_FUNC_USE error code, 10
ER_INVALID_INFO_IN_FRM error code, 167
ER_INVALID_INSTRUMENT error code, 139
ER_INVALID_JSON_ATTRIBUTE error code, 123
ER_INVALID_JSON_BINARY_DATA error code, 70
ER_INVALID_JSON_CHARSET error code, 70
ER_INVALID_JSON_CHARSET_IN_FUNCTION error
code, 70
ER_INVALID_JSON_DATA error code, 64
ER_INVALID_JSON_PATH error code, 70
ER_INVALID_JSON_PATH_ARRAY_CELL error code,
70
ER_INVALID_JSON_PATH_CHARSET error code, 70
ER_INVALID_JSON_PATH_WILDCARD error code,
70
ER_INVALID_JSON_TEXT error code, 70
ER_INVALID_JSON_TEXT_IN_PARAM error code, 70
ER_INVALID_JSON_TYPE error code, 110
ER_INVALID_JSON_VALUE_FOR_CAST error code,
71
ER_INVALID_JSON_VALUE_FOR_FUNC_INDEX
error code, 115
ER_INVALID_MULTIPLE_CLAUSES error code, 108
ER_INVALID_NAMED_PIPE_FULL_ACCESS_GROUP
error code, 481
ER_INVALID_NO_OF_ARGS error code, 83
ER_INVALID_ON_UPDATE error code, 21
ER_INVALID_OPTION_CHARACTERS error code, 79
ER_INVALID_OPTION_END_CHARACTER error
code, 79
ER_INVALID_OPTION_KEY error code, 78
ER_INVALID_OPTION_KEY_VALUE_PAIR error code,
78
ER_INVALID_OPTION_START_CHARACTER error
code, 79
ER_INVALID_OPTION_VALUE error code, 78
ER_INVALID_OR_OLD_TABLE_OR_DB_NAME error
code, 186
ER_INVALID_PARAMETER_USE error code, 125
ER_INVALID_PROPERTY_KEY error code, 477
ER_INVALID_REPLICATION_TIMESTAMPS error
code, 236
ER_INVALID_RPL_WILD_TABLE_FILTER_PATTERN
error code, 64
ER_INVALID_THREAD_ID error code, 89
ER_INVALID_THREAD_PRIORITY error code, 88
ER_INVALID_TIME_ZONE_INTERVAL error code, 125
ER_INVALID_TYPE_FOR_JSON error code, 70
ER_INVALID_USER_ATTRIBUTE_JSON error code,
123
ER_INVALID_USE_OF_FORCE_OPTION error code,
89
ER_INVALID_USE_OF_NULL error code, 12
ER_INVALID_VALUE_FOR_ENFORCE_GTID_CONSISTENCY
error code, 135
ER_INVALID_VALUE_OF_BIND_ADDRESSES error
code, 464
ER_INVALID_VCPU_ID error code, 88
ER_INVALID_VCPU_RANGE error code, 88
ER_INVALID_XPLUGIN_SOCKET_SAME_AS_SERVER
error code, 504
ER_INVALID_YEAR_COLUMN_LENGTH error code,
54
ER_IO_ERR_LOG_INDEX_READ error code, 26
ER_IO_READ_ERROR error code, 53
ER_IO_WRITE_ERROR error code, 53

ER_IPSOCK_ERROR error code, 8
ER_IS_QUERY_INVALID_CLAUSE error code, 78
ER_I_S_SKIPPED_TABLESPACE error code, 87
ER_JSON_BAD_ONE_OR_ALL_ARG error code, 70
ER_JSON_DOCUMENT_NULL_KEY error code, 71
ER_JSON_DOCUMENT_TOO_DEEP error code, 71
ER_JSON_KEY_TOO_BIG error code, 70
ER_JSON_PARSE_ERROR error code, 153
ER_JSON_SCHEMA_VALIDATION_ERROR_WITH_DETAIL error code, 118
ER_JSON_USED_AS_KEY error code, 70
ER_JSON_VACUOUS_PATH error code, 70
ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX error code, 115
ER_JSON_VALUE_TOO_BIG error code, 70
ER_JT_MAX_NESTED_PATH error code, 90
ER_JT_VALUE_OUT_OF_RANGE error code, 90
ER_KERBEROS_CREATE_USER error code, 131
ER_KEYCACHE_OOM error code, 143
ER_KEYRING_ACCESS_DENIED_ERROR error code, 74
ER_KEYRING_AWS_CMK_ID_NOT_SET error code, 287
ER_KEYRING_AWS_FAILED_TO_ACCESS_DATAFILE error code, 287
ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_FROM_ERROR error code, 286
ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID_FROM_ERROR error code, 286
ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_ERROR error code, 287
ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_ERROR error code, 286
ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS error code, 288
ER_KEYRING_AWS_FAILED_TO_DECRYPT_KEY error code, 289
ER_KEYRING_AWS_FAILED_TO_ENCRYPT_KEY error code, 288
ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_ERROR error code, 288
ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUE_TO_ERROR error code, 288
ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEY error code, 288
ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIALS error code, 287
ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERIOR_ERROR error code, 287
ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_ERROR error code, 287
ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE error code, 286
ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP error code, 288
ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY error code, 289
ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK error code, 289
ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID error code, 285
ER_KEYRING_AWS_FAILED_TO_SET_REGION error code, 286
ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_FILE error code, 288
ER_KEYRING_AWS_INCORRECT_FILE error code, 288
ER_KEYRING_AWS_INCORRECT_PROXY error code, 493
ER_KEYRING_AWS_INCORRECT_REGION error code, 288
ER_KEYRING_AWS_INIT_FAILURE error code, 287
ER_KEYRING_AWS_INVALID_CONF_FILE_PATH error code, 286
ER_KEYRING_AWS_INVALID_DATA_FILE_PATH error code, 286
ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER error code, 287
ER_KEYRING_AWS_UDF_AWS_KMS_ERROR error code, 73
ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_EMPTY_KEY error code, 279
ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_INVALID_KEY error code, 279
ER_KEYRING_COMPONENT_EXCEPTION error code, 518
ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR error code, 518
ER_KEYRING_COMPONENT_NOT_INITIALIZED error code, 518
ER_KEYRING_ENCRYPTED_FILE_DECRYPTION_FAILED error code, 284
ER_KEYRING_ENCRYPTED_FILE_ENCRYPTION_FAILED error code, 284
ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_CREATE_KEY error code, 285
ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_FLUSH_KEY error code, 284
ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_RESTORE_KEY error code, 284
ER_KEYRING_ENCRYPTED_FILE_FOUND_MALFORMED_BACKUP error code, 284
ER_KEYRING_ENCRYPTED_FILE_GEN_KEY_FAILED_DUE_TO_ERROR error code, 285
ER_KEYRING_ENCRYPTED_FILE_INIT_FAILURE error code, 285
ER_KEYRING_ENCRYPTED_FILE_INVALID_KEYRING_DIR error code, 285
ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_INVALID error code, 285

ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_TOO_SHORT error code, 285
ER_KEYRING_FAILED_TO_CREATE_KEYRING_DIR error code, 278
ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE error code, 279
ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING error code, 280
ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING error code, 280
ER_KEYRING_FAILED_TO_GENERATE_KEY error code, 279
ER_KEYRING_FAILED_TO_GET_FILE_STAT error code, 280
ER_KEYRING_FAILED_TO_LOAD_KEYRING_CONTAINER error code, 280
ER_KEYRING_FAILED_TO_REMOVE_FILE error code, 280
ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_ERROR error code, 281
ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP error code, 279
ER_KEYRING_FAILED_TO_SET_KEYRING_FILE_DATA error code, 280
ER_KEYRING_FAILED_TO_TRUNCATE_FILE error code, 280
ER_KEYRING_FILE_INIT_FAILED error code, 278
ER_KEYRING_FILE_IO_ERROR error code, 280
ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE error code, 279
ER_KEYRING_INCORRECT_FILE error code, 279
ER_KEYRING_INTERNAL_EXCEPTION_FAILED_FILE error code, 279
ER_KEYRING_INVALID_KEY_LENGTH error code, 278
ER_KEYRING_INVALID_KEY_TYPE error code, 278
ER_KEYRING_KEY_FETCH_FAILED_DUE_TO_EMPTY error code, 281
ER_KEYRING_LOGGER_ERROR_MSG error code, 262
ER_KEYRING_MIGRATE_FAILED error code, 454
ER_KEYRING_MIGRATION_EXTRA_OPTIONS error code, 333
ER_KEYRING_MIGRATION_FAILED error code, 250
ER_KEYRING_MIGRATION_FAILURE error code, 74
ER_KEYRING_MIGRATION_STATUS error code, 74
ER_KEYRING_MIGRATION_SUCCESSFUL error code, 250
ER_KEYRING_OKV_CONNECTION_TO_SERVER_FAILED error code, 282
ER_KEYRING_OKV_FAILED_TO_ACTIVATE_KEYS error code, 283
ER_KEYRING_OKV_FAILED_TO_ADD_ATTRIBUTE error code, 282
ER_KEYRING_OKV_FAILED_TO_FETCH_KEY error code, 283
ER_KEYRING_OKV_FAILED_TO_FIND_SERVER_ENTRY error code, 282
ER_KEYRING_OKV_FAILED_TO_FIND_STANDBY_SERVER_ENTRY error code, 282
ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY error code, 283
ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR error code, 281
ER_KEYRING_OKV_FAILED_TO_INIT_CLIENT error code, 282
ER_KEYRING_OKV_FAILED_TO_INIT_SSL_LAYER error code, 282
ER_KEYRING_OKV_FAILED_TO_LOAD_KEY_UID error code, 282
ER_KEYRING_OKV_FAILED_TO_LOAD_SSL_TRUST_STORE error code, 283
ER_KEYRING_OKV_FAILED_TO_PARSE_CONF_FILE error code, 282
ER_KEYRING_OKV_FAILED_TO_REMOVE_KEY error code, 282
ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY error code, 283
ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY_SIGNATURE error code, 283
ER_KEYRING_OKV_FAILED_TO_SET_CERTIFICATE_FILE error code, 283
ER_KEYRING_OKV_FAILED_TO_SET_KEY_FILE error code, 284
ER_KEYRING_OKV_FAILED_TO_STORE_KEY error code, 283
ER_KEYRING_OKV_FAILED_TO_STORE_OR_GENERATE_KEY error code, 283
ER_KEYRING_OKV_INCORRECT_KEY_VAULT_CONFIGURED error code, 281
ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INTERNAL_ERROR error code, 281
ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INcorrect_CONFIGURATION error code, 281
ER_KEYRING_OKV_INVALID_KEY_LENGTH_FOR_CIPHER error code, 281
ER_KEYRING_OKV_INVALID_KEY_TYPE error code, 281
ER_KEYRING_OKV_KEY_MISMATCH error code, 284
ER_KEYRING_OPERATION_FAILED_DUE_TO_INTERNAL_ERROR error code, 279
ER_KEYRING_UDF_KEYRING_SERVICE_ERROR error code, 73
ER_KEYRING_UNKNOWN_ERROR error code, 280
ER_KEY_COLUMN_DOES_NOT_EXISTS error code, 8
ER_KEY_DOES_NOT_EXISTS error code, 14
ER_KEY_NOT_FOUND error code, 5
ER_KEY_PART_0 error code, 27
ER_KEY_REF_DO_NOT_MATCH_TABLE_REF error code, 18
ER_KILLED_THREADS_OF_PLUGIN error code, 181
ER_KILLING_THREAD error code, 180
ER_KILL_DENIED_ERROR error code, 9
ER_LATITUDE_OUT_OF_RANGE error code, 85
ER_LCTN_CHANGED error code, 250
ER_LCTN_NOT_FOUND error code, 455

ER_LDAP_AUTH_CERTIFICATE_NAME error code, 326	ER_LDAP_AUTH_FREEING_CONNECTION error code, 328
ER_LDAP_AUTH_COMMUNICATION_HOST_INFO error code, 329	ER_LDAP_AUTH_GETTING_CONNECTION_FROM_POOL error code, 328
ER_LDAP_AUTH_CONNECTION_CREATOR_ENTER error code, 328	ER_LDAP_AUTH_GRP_DN_PARSING_FAILED error code, 479
ER_LDAP_AUTH_CONNECTION_GET_LDAP_INFO_NUEIR_LDAP_AUTH_GRP_INCORRECT_ATTRIBUTE error code, 329	ER_LDAP_AUTH_GRP_INFO_FOUND_IN_MANY_OBJECTS error code, 478
ER_LDAP_AUTH_CONNECTION_POOL_INIT_FAILED error code, 327	ER_LDAP_AUTH_GRP_IS_FULL_DN error code, 326
ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTER error code, 331	ER_LDAP_AUTH_GRP_NULL_ATTRIBUTE_VALUE error code, 479
ER_LDAP_AUTH_CONNECTION_PUSHED_TO_POOL error code, 328	ER_LDAP_AUTH_GRP_OBJECT_HAS_USER_INFO error code, 479
ER_LDAP_AUTH_CONN_POOL_DEINITIALIZING error code, 325	ER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL error code, 478
ER_LDAP_AUTH_CONN_POOL_INITIALIZING error code, 325	ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL error code, 326
ER_LDAP_AUTH_CONN_POOL_NOT_CREATED error code, 324	ER_LDAP_AUTH_GRP_USER_OBJECT_HAS_GROUP_INFO error code, 478
ER_LDAP_AUTH_CREATE_CONNECTION_KEY error code, 329	ER_LDAP_AUTH_INFO_FOR_USER error code, 325
ER_LDAP_AUTH_CREATING_LDAP_CONNECTION error code, 328	ER_LDAP_AUTH_INIT_FAILED error code, 330
ER_LDAP_AUTH_deinit_FAILED error code, 324	ER_LDAP_AUTH_LDAPS error code, 479
ER_LDAP_AUTH_deleting_CONNECTION_KEY error code, 329	ER_LDAP_AUTH_LDAP_INFO_NULL error code, 328
ER_LDAP_AUTH_DISTINGUISHED_NAME error code, 330	ER_LDAP_AUTH_MAX_ALLOWED_CONNECTION_LIMIT_HIT error code, 327
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION error code, 330	ER_LDAP_AUTH_MAX_POOL_SIZE_SET_FAILED error code, 327
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT error code, 324	ER_LDAP_AUTH_METHOD_TO_CLIENT error code, 329
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT error code, 324	ER_LDAP_AUTH_OBJECT_CREATE_TIMESTAMP error code, 326
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT error code, 324	ER_LDAP_AUTH_OR_GROUP_RETRIEVAL_FAILED error code, 330
ER_LDAP_AUTH_FAILED_TO_CREATE_OR_GET_CONNECTION_POOL error code, 324	ER_LDAP_AUTH_PLUGIN_FAILED_TO_READ_PACKET error code, 328
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY error code, 327	ER_LDAP_AUTH_POOLED_CONNECTION_KEY error code, 329
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_ERROR_CODE_IS_SETABLE_MAX_SIZE_ZERO error code, 327	ER_LDAP_AUTH_PLUGIN_NOT_IN_POOL error code, 324
ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION error code, 330	ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION error code, 330
ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_ERRORE_RUGIAPI NOT IN POOL error code, 327	ER_LDAP_AUTH_POOL_REINITIALIZING error code, 325
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DEINITIALIZED_STATE error code, 327	ER_LDAP_AUTH_RETURNING_CONNECTION_TO_POOL error code, 328
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INITIALIZED_STATE error code, 327	ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO error code, 329
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_RESETTING_SASL_PROCESS_SASL error code, 326	ER_LDAP_AUTH_SASL_DISABLE_MAX_SIZE error code, 329
ER_LDAP_AUTH_FAILED_TO_POOL_deinit error code, 326	ER_LDAP_AUTH_SASL_REQUEST_FROM_CLIENT error code, 329
ER_LDAP_AUTH_FAILED_TO_SEARCH_DN error code, 331	ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME error code, 326
ER_LDAP_AUTH_FAILED_TO_WRITE_PACKET error code, 325	ER_LDAP_AUTH_SEARCH_USER_GROUP_ATTR_NOT_FOUND error code, 328

ER_LDAP_AUTH_SETTING_USERNAME error code, 325
ER_LDAP_AUTH_SKIPPING_USER_GROUP_SEARCH error code, 324
ER_LDAP_AUTH_STARTED_FOR_USER error code, 330
ER_LDAP_AUTH_STARTING_TLS error code, 329
ER_LDAP_AUTH_TLS_CONF error code, 324
ER_LDAP_AUTH_TLS_CONNECTION error code, 324
ER_LDAP_AUTH_USER_AUTH_DATA error code, 325
ER_LDAP_AUTH_USER_BIND_FAILED error code, 330
ER_LDAP_AUTH_USER_FOUND_IN_MANY_GRPS error code, 326
ER_LDAP_AUTH_USER_GROUP_SEARCH_FAILED error code, 330
ER_LDAP_AUTH_USER_GROUP_SEARCH_INFO error code, 325
ER_LDAP_AUTH_USER_GROUP_SEARCH_ROOT_BINER LOCK_NOWAIT error code, 80
error code, 467
ER_LDAP_AUTH_USER_HAS_MULTIPLE_GRP_NAMES error code, 326
ER_LDAP_AUTH_USER_NOT_FOUND_IN_ANY_GRP error code, 326
ER_LDAP_AUTH_ZERO_MAX_POOL_SIZE_UNCHANGED error code, 325
ER_LDAP_EMPTY_USERDN_PASSWORD error code, 489
ER_LDAP_MAPPING_CHECK_DELIMI_QUOTE error code, 480
ER_LDAP_MAPPING_EMPTY_MAPPING error code, 479
ER_LDAP_MAPPING_GETTING_NEXT_MAPPING error code, 480
ER_LDAP_MAPPING_GET_USER_PROXY error code, 479
ER_LDAP_MAPPING_INFO error code, 479
ER_LDAP_MAPPING_IS_QUOTE error code, 481
ER_LDAP_MAPPING_NON_DESIRED_STATE error code, 481
ER_LDAP_MAPPING_NO_SEPEARATOR_END_OF_GRDR LOG_COMPONENT_FLUSH_FAILED error code, 525
error code, 480
ER_LDAP_MAPPING_PARSING_CURRENT_STATE error code, 480
ER_LDAP_MAPPING_PARSING_ERROR error code, 481
ER_LDAP_MAPPING_PARSING_MAPPING_INFO error code, 480
ER_LDAP_MAPPING_PROCESS_DELIMITER error code, 480
ER_LDAP_MAPPING_PROCESS_DELIMITER_COMMANOT FOUNDNTF_MSG error code, 248
error code, 480
ER_LDAP_MAPPING_PROCESS_DELIMITER_EQUAL_NOT FOUND error code, 480
ER_LDAP_MAPPING_PROCESS_DELIMITER_TRY_COMMAALOG_PURGE_UNKNOWN_ERR error code, 27
error code, 480
ER_LDAP_MAPPING_PROCESS_MAPPING error code, 479
ER_LDAP_MAPPING_TRIMMING_SPACES error code, 481
ER_LDAP_MAPPING_USER_DONT_BELONG_GROUP error code, 479
ER_LIMITED_PART_RANGE error code, 35
ER_LOAD_DATA_INFILE_FAILED_IN_UNEXPECTED_WAY error code, 153
ER_LOAD_FROM_FIXED_SIZE_ROWS_TO_VAR error code, 28
ER_LOAD_INFO error code, 9
ER_LOCAL_VARIABLE error code, 18
ER_LOCKING_SERVICE_DEADLOCK error code, 69
ER_LOCKING_SERVICE_TIMEOUT error code, 69
ER_LOCKING_SERVICE_WRONG_NAME error code, 69
ER_LOCK_ABORTED error code, 44
ER_LOCK_DEADLOCK error code, 16
ER_LOCK_ORDER_DEPENDENCIES_SYNTAX error code, 490
ER_LOCK_ORDER_FAILED_READ_FILE error code, 489
ER_LOCK_ORDER_FAILED_WRITE_FILE error code, 490
ER_LOCK_ORDER_INIT_FAILED error code, 488
ER_LOCK_ORDER_MESSAGE error code, 489
ER_LOCK_ORDER_SCANNER_SYNTAX error code, 490
ER_LOCK_OR_ACTIVE_TRANSACTION error code, 15
ER_LOCK_REFUSED_BY_ENGINE error code, 72
ER_LOCK_TABLE_FULL error code, 16
ER_LOCK_WAIT_TIMEOUT error code, 16
ER_LOG_BIN_BETTER_WITH_NAME error code, 148
ER_LOG_CANNOT_WRITE error code, 133
ER_LOG_CANNOT_WRITE_EXTENDED error code, 493
ER_LOG_COMPONENT_CANNOT_INIT error code, 514
ER_LOG_FILES_GIVEN_LOG_OUTPUT_IS_TABLE error code, 147
ER_LOG_FILE_CANNOT_OPEN error code, 269
ER_LOG_FILE_INVALID error code, 147
ER_LOG_GENERAL_CANNOT_OPEN error code, 133
ER_LOG_IN_USE error code, 27
ER_LOG_OUTPUT CONTRADICTORY error code, 146
ER_LOG_PRIV_CHECKS_REQUIRE_ROW_FORMAT_NOT_SET NOT FOUND error code, 496
ER_LOG_PURGE_NO_FILE error code, 39
ER_LOG_PURGE_UNKNOWN_ERR error code, 27
ER_LOG_SLOW_CANNOT_OPEN error code, 133
ER_LOG_SYSLOG_CANNOT_OPEN error code, 132

ER_LOG_SYSLOG_FACILITY_FAIL error code, 132
ER_LONGITUDE_OUT_OF_RANGE error code, 84
ER_LOWER_CASE_TABLE_NAMES_CS_DD_ON_CI_F
ER_INNODB_GRANT_SYSTEM_TABLE error code, 237
ER_MISSING_CURRENT_PASSWORD error code, 114
ER_MISSING_SKIP_SLAVE error code, 20
ER_MISSING_TABLESPACE_FILE error code, 86
ER_MIXING_NOT_ALLOWED error code, 17
ER_MIX_HANDLER_ERROR error code, 33
ER_MIX_OF_GROUP_FUNC_AND_FIELDS error code, 12
ER_MIX_OF_GROUP_FUNC_AND_FIELDS_V2 error code, 65
ER_MTR_MSG_1 error code, 525
ER_MTS_CANT_PARALLEL error code, 49
ER_MTS_CHANGE_MASTER_CANT_RUN_WITH_GAPS error code, 53
ER_MTS_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX error code, 57
ER_MTS_FEATURE_IS_NOT_SUPPORTED error code, 49
ER_MTS_INCONSISTENT_DATA error code, 49
ER_MTS_RECOVERY_FAILURE error code, 53
ER_MTS_RESET_WORKERS error code, 53
ER_MTS_UPDATED_DBs_GREATER_MAX error code, 49
ER_MULTIPLE_CONSTRAINTS_WITH_SAME_NAME error code, 118
ER_MULTIPLE_DEF_CONST_IN_LIST_PART_ERROR error code, 33
ER_MULTIPLE_INTO_CLAUSES error code, 120
ER_MULTIPLE_JSON_VALUES error code, 122
ER_MULTIPLE_PRI_KEY error code, 7
ER_MULTI_UPDATE_KEY_CONFLICT error code, 46
ER_MUST_CHANGE_EXPIRED_PASSWORD error code, 233
ER_MUST_CHANGE_PASSWORD error code, 54
ER_MUST_CHANGE_PASSWORD_LOGIN error code, 57
ER_MYINIT_FAILED error code, 145
ER_MYISAM_CHECK_METHOD_ERROR error code, 247
ER_MYISAM_CRASHED_ERROR error code, 247
ER_MYISAM_CRASHED_ERROR_IN error code, 156
ER_MYISAM_CRASHED_ERROR_IN_THREAD error code, 156
ER_MYSQLBACKUP_MSG error code, 494
ER_NATIVE_PASSWORD_SECOND_PASSWORD_U
error code, 475
ER_MY_NET_WRITE_FAILED_FALLING_BACK_ON_STDERR error code, 213
ER_M_BIGGER_THAN_D error code, 29
ER_NAME_BECOMES_EMPTY error code, 32
ER_NANOSECOND_TIMER_IS_NOT_AVAILABLE error code, 245

ER_NATIVE_FCT_NAME_COLLISION error code, 38
ER_NDBINFO_NOT_UPGRADING_SCHEMA error code, 503
ER_NDBINFO_UPGRADING_SCHEMA error code, 503
ER_NDBINFO_UPGRADING_SCHEMA_FAIL error code, 503
ER_NDB_BINLOG_BLOB_REQUIRES_PK error code, 204
ER_NDB_BINLOG_CANT_COMMIT_TO_NDB_BINLOG error code, 202
ER_NDB_BINLOG_CANT_CREATE_BLOB error code, 205
ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB error code, 204
ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB_AND_DROPPED error code, 204
ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB_DROPPED error code, 205
ER_NDB_BINLOG_CANT_CREATE_PURGE_THD error code, 226
ER_NDB_BINLOG_CANT_DISCOVER_TABLE_FROM_SCHEMA error code, 199
ER_NDB_BINLOG_CANT_DROP_EVENT_FROM_DB error code, 205
ER_NDB_BINLOG_CANT_INJECT_APPLY_STATUS_WRITE_ROW error code, 207
ER_NDB_BINLOG_CANT_LOCK_NDB_BINLOG_INDEX error code, 202
ER_NDB_BINLOG_CANT_RELEASE_SLOCK error code, 200
ER_NDB_BINLOG_CANT_REOPEN_SHADOW_TABLE error code, 201
ER_NDB_BINLOG_CANT_WRITE_TO_NDB_BINLOG_INDEX error code, 202
ER_NDB_BINLOG_CLEANING_UP_SETUP_LEFTOVERS error code, 198
ER_NDB_BINLOG_CLUSTER_FAILURE error code, 206
ER_NDB_BINLOG_CLUSTER_HAS_RECONNECTED error code, 207
ER_NDB_BINLOG_CLUSTER_RESTARTED_RESET_MASTER error code, 206
ER_NDB_BINLOG_CREATE_TABLE_EVENT error code, 183
ER_NDB_BINLOG_CREATE_TABLE_EVENT_FAILED error code, 204
ER_NDB_BINLOG_CREATE_TABLE_EVENT_INFO error code, 204
ER_NDB_BINLOG_CREATING_NDBEVENTOPERATION error code, 205
ER_NDB_BINLOG_DISCOVER_REUSE_OLD_EVENT error code, 205
ER_NDB_BINLOG_DISCOVER_TABLE_EVENT_INFO error code, 204
ER_NDB_BINLOG_ERROR_DURING_GCI_COMMIT error code, 208
ER_NDB_BINLOG_ERROR_DURING_GCI_ROLLBACK error code, 208
ER_NDB_BINLOG_ERROR_HANDLING_SCHEMA_EVENT error code, 207
ER_NDB_BINLOG_ERROR_INFO_FROM_DA error code, 183
ER_NDB_BINLOG_FAILED_CREATE_EVENT_OPERATIONS_DUE_TO_INDEX error code, 184
ER_NDB_BINLOG_FAILED_CREATE_TABLE_EVENT_OPERATIONS_DUE_TO_INDEX error code, 183
ER_NDB_BINLOG_FAILED_TO_GET_TABLE error code, 204
ER_NDB_BINLOG_FORMAT_CHANGED_FROM_STMT_TO_MIXED error code, 184
ER_NDB_BINLOG_GENERIC_MESSAGE error code, 203
ER_NDB_BINLOG_GOT_DIST_PRIV_EVENT_FLUSHING_PRIVILEGE error code, 201
ER_NDB_BINLOG_GOT_SCHEMA_EVENT error code, 201
ER_NDB_BINLOG_INJECTING_RANDOM_WRITE_FAILURE error code, 208
ER_NDB_BINLOG_INJECTOR_DISCARDING_ROW_EVENT_METADATA error code, 206
ER_NDB_BINLOG_LATEST_TRX_IN_EPOCH_NOT_IN_BINLOG error code, 208
ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_CONTINUATION error code, 207
ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_WAITING error code, 207
ER_NDB_BINLOG_NDBEVENT_EXECUTE_FAILED error code, 205
ER_NDB_BINLOG_NDB_LOG_APPLY_STATUS_FORCING_FULL error code, 203
ER_NDB_BINLOG_NDB_LOG_TRANSACTION_IDQUIRES_V error code, 203
ER_NDB_BINLOG_NDB_TABLES_INITIALLY_READ_ONLY error code, 185
ER_NDB_BINLOG_NDB_TABLES_WRITABLE error code, 207
ER_NDB_BINLOG_NOT_LOGGING error code, 204
ER_NDB_BINLOG_ONLINE_ALTER_RENAME_COMPLETE error code, 201
ER_NDB_BINLOG_OPENING_INDEX error code, 202
ER_NDB_BINLOG_RELEASETING_EXTRA_SHARE_REFERENCES error code, 208
ER_NDB_BINLOG_REMAINING_OPEN_TABLES error code, 208
ER_NDB_BINLOG_REMAINING_OPEN_TABLE_INFO error code, 208
ER_NDB_BINLOG_RENAME_EVENT error code, 184
ER_NDB_BINLOG_REPLY_TO error code, 200
ER_NDB_BINLOG_SERVER_SHUTDOWN_DURING_NDB_CLUSTER error code, 206
ER_NDB_BINLOG_SHUTDOWN_DETECTED error code, 207

ER_NDB_BINLOG_SIGNALLING_UNKNOWN_VALUE	ER_NDB_CLUSTER_SCHEMA_INFO error code, 173
error code, 200	ER_NDB_CLUSTER_WRONG_NUMBER_OF_FUNCTION_AR
ER_NDB_BINLOG_SKIPPING_DROP_OF_DB_CONTAINING_LOCAL_TABLES	ER_NDB_COLUMN_DEFAULTS_DIFFER error code,
error code, 201	ER_NDB_COLUMN_INFO error code, 182
ER_NDB_BINLOG_SKIPPING_DROP_OF_LOCAL_TABLE	ER_NDB_COLUMN_SHOULD_NOT_HAVE_NATIVE_DEFAULT
error code, 201	error code, 182
ER_NDB_BINLOG_SKIPPING_LOCAL_TABLE error	ER_NDB_CONFLICT_FN_PARSE_ERROR error
code, 200	code, 204
ER_NDB_BINLOG_SKIPPING_OLD_SCHEMA_OPERATION	ER_NDB_CONFLICT_FN_SETUP_ERROR error
error code, 201	code, 204
ER_NDB_BINLOG_SKIPPING_RENAME_OF_LOCAL_TABLE	ER_NDB_CONFLICT_GENERIC_MESSAGE error
error code, 201	code, 203
ER_NDB_BINLOG_STARTING_LOG_AT_EPOCH	ER_NDB_COULD_NOT_GET_APPLY_STATUS_SHARE
error code, 207	error code, 206
ER_NDB_BINLOG_UNHANDLED_ERROR_FOR_TABLE	ER_NDB_CREATE_EVENT_OPS_LOGGING_INFO
error code, 206	error code, 205
ER_NDB_BINLOG_UNKNOWN_NON_DATA_EVENT	ER_NDB_CREATING_SHARE_IN_OPEN error code,
error code, 206	ER_NDB_CREATED_AFTER_KILL
ER_NDB_BINLOG_USING_SERVER_ID_0_SLAVES_WILL_BE_DELETED	ER_NDB_CREATING_TABLE error code, 197
error code, 203	error code, 200
ER_NDB_BINLOG_WRITE_TO_NDB_BINLOG_INDEX_FAILED	ER_NDB_DISCARDING_EVENT_ID_VERSION_MISMATCH
error code, 203	error code, 200
ER_NDB_BINLOG_WRITING_TO_NDB_BINLOG_INDEXER_NDB_DISCARDING_EVENT_NO_OBJ	ER_NDB_DISCARDING_EVENT_NO_OBJ error code,
error code, 202	200
ER_NDB_CANT_ALLOC_GLOBAL_NDB_CLUSTER_CONNECTION	ER_NDB_DISCONNECT_INFO error code, 181
error code, 218	ER_NDB_DISCOVERED_MISSING_DB error code,
ER_NDB_CANT_ALLOC_GLOBAL_NDB_OBJECT	ER_NDB_DISCOVERED_REMAINING_DB error code,
error code, 218	198
ER_NDB_CANT_ALLOC_NDB_CLUSTER_CONNECTION	ER_NDB_DISTRIBUTED_INFO error code, 199
error code, 218	ER_NDB_DISTRIBUTING_ERR error code, 229
ER_NDB_CANT_FIND_TABLE error code, 200	ER_NDB_DISTRIBUTION_COMPLETE error code,
ER_NDB_CANT_PARSE_NDB_CLUSTER_CONNECTION	199
error code, 217	ER_NDB_DUPLICATE_NODEID_IN_NDB_CLUSTER_CONNECTION
ER_NDB_CANT_START_CONNECT_THREAD error	error code, 217
code, 218	ER_NDB_EMPTY_NODEID_IN_NDB_CLUSTER_CONNECTIO
ER_NDB_CLEANING_STRAY_TABLES error code,	error code, 217
197	ER_NDB_ERROR_IN_GET_AUTO_INCREMENT error
ER_NDB_CLEAR_SLOCK_INFO error code, 200	code, 184
ER_NDB_CLUSTER_FAILURE error code, 201	ER_NDB_ERROR_IN_READAUTOINCREMENTVALUE
ER_NDB_CLUSTER_FIND_ALL_DBs_FAIL error	error code, 183
code, 198	ER_NDB_FAILED_TO_SET_UP_TABLE error code,
ER_NDB_CLUSTER_FIND_ALL_DBs_RETRY error	198
code, 198	ER_NDB_FIELD_INFO error code, 182
ER_NDB_CLUSTER_FREE_SHARE_INFO error code,	ER_NDB_FLUSHING_TABLE_INFO error code, 197
185	ER_NDB_FOUND_UNCOMMITTED_AUTOCOMMIT
ER_NDB_CLUSTER_GENERIC_MESSAGE error	error code, 183
code, 173	ER_NDB_HANDLE_TRAILING_SHARE_INFO error
ER_NDB_CLUSTER_GET_SHARE_INFO error code,	code, 185
185	ER_NDB_IGNORED_UNKNOWN_EVENT error code,
ER_NDB_CLUSTER_MARK_SHARE_DROPPED_DESTROY_INDBSHAREERIC_ERROR	202
error code, 185	ER_NDB_ILLEGAL_VALUE_FOR_NDB_RECV_THREAD_CPU
ER_NDB_CLUSTER_MARK_SHARE_DROPPED_INFO	error code, 186
error code, 185	ER_NDB_INFO_FAILED_TO_CREATE_NDBINFO
ER_NDB_CLUSTER_OOM_THD_NDB error code, 185	error code, 173
ER_NDB_CLUSTER_REAL_FREE_SHARE_DROP_FAILED	
error code, 185	
ER_NDB_CLUSTER_REAL_FREE_SHARE_INFO	
error code, 185	

ER_NDB_INFO_FAILED_TO_INIT_NDBINFO error code, 173

ER_NDB_INFO_FOUND_UNEXPECTED_FIELD_TYPE error code, 173

ER_NDB_INITIALIZE_GIVEN_CLUSTER_PLUGIN_DISABLED error code, 184

ER_NDB_INVALID_NODEID_IN_NDB_CLUSTER_CONNECTOR_POOL_NODEIDS error code, 217

ER_NDB_LOG_ENTRY error code, 226

ER_NDB_LOG_ENTRY_WITH_PREFIX error code, 226

ER_NDB_MISMATCH_IN_FRM_DISCOVERING error code, 198

ER_NDB_MISSING_FRM_DISCOVERING error code, 198

ER_NDB_NODEID_NOT_FIRST_IN_NDB_CLUSTER_CONNECTION_POOL_NODEIDS error code, 217

ER_NDB_NODE_ID_AND_MANAGEMENT_SERVER_INFO error code, 181

ER_NDB_NODE_INFO error code, 218

ER_NDB_NOT_WAITING_FOR_DISTRIBUTING error code, 199

ER_NDB_NUMBER_OF_CHANNELS error code, 229

ER_NDB_OOM_GET_NDB_BLOBS_VALUE error code, 197

ER_NDB_OOM_IN_FIX_UNIQUE_INDEX_ATTR_ORDER error code, 182

ER_NDB_POOL_SIZE_MUST_MATCH_NDB_CLUSTER_CONNECTOR_POOL_NODEIDS error code, 217

ER_NDB_QUERY_FAILED error code, 180

ER_NDB_REMAINING_OPEN_TABLES error code, 206

ER_NDB_REMAINING_OPEN_TABLE_INFO error code, 206

ER_NDB_REPLICATION_SCHEMA_ERROR error code, 40

ER_NDB_SCHEMA_DISTRIBUTION_FAILED error code, 199

ER_NDB_SCHEMA_DISTRIBUTION_REPORTS_SUBSCRIPTION_TOO_MANY_CPUS_IN_NDB_RECV_THREAD_CPU_MAX error code, 199

ER_NDB_SCHEMA_DISTRIBUTION_REPORTS_UNSUBSCRIPTION_TRAILING_SHARE_RELEASED_BY_CLOSE_CACHED error code, 199

ER_NDB_SCHEMA_GENERIC_MESSAGE error code, 179

ER_NDB_SERVER_ID_RESERVED_OR_TOO_LARGE error code, 203

ER_NDB_SHARE_ALREADY_EXISTS error code, 185

ER_NDB_SKIPPING_SETUP_TABLE error code, 198

ER_NDB_SLAVE_BINLOG_MISSING_INFO_FOR_CONFERENCED_TRANSACTION_READ_OOM error code, 186

ER_NDB_SLAVE_CANT_ALLOCATE_TABLE_SHARE error code, 183

ER_NDB_SLAVE_CONFLICT_DETECTIONQUIRES_TRANSACTION_INSTEAD_OF_DIR error code, 182

ER_NDB_SLAVE_CONFLICT_FUNCTIONQUIRES_TRANSACTION_NEED_REPREPARE error code, 182

ER_NDB_SLAVE_ERROR_IN_UPDATE_CREATE_INFO error code, 486

ER_NDB_SLAVE_LOGGING_EXCEPTIONS_TO error code, 172

ER_NDB_SLAVE_LOW_EPOCH_RESOLUTION error code, 172

ER_NDB_SLAVE_MALFORMED_EVENT_RECEIVED_ON_TABLE error code, 182

ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_UNKNOWN error code, 181

ER_NDB_SLAVE_MISSING_DATA_FOR_TIMESTAMP_COLUMN error code, 172

ER_NDB_SLAVE_PARALLEL_WORKERS error code, 229

ER_NDB_SLAVE_PREVIOUS_EPOCH_NOT_COMMITTED CONNECTION_POOL_NODEIDS error code, 172

ER_NDB_SLAVE_SAW_ALREADY_COMMITTED_EPOCH error code, 172

ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS error code, 172

ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS_ON error code, 172

ER_NDB_SLAVE_TOO_MANY_RETRIES error code, 183

ER_NDB_STARTING_CONNECT_THREAD error code, 218

ER_NDB_TABLES_INITIALLY_READ_ONLY_ON_RECONNECT CONNECTION_POOL_NODEIDS error code, 151

ER_NDB_TABLE_IS_NOT_DISTRIBUTED error code, 197

ER_NDB_TABLE_OPENED_READ_ONLY error code, 184

ER_NDB_THREAD_TIMED_OUT error code, 197

ER_NDB_TIMED_OUT_IN_DROP_TABLE error code, 205

ER_NDB_TIMEOUT_WHILE_DISTRIBUTING error code, 199

ER_NDB_UNEXPECTED_RENAME_TYPE error code, 184

ER_NDB_USING_NODEID error code, 217

ER_NDB_USING_NODEID_LIST error code, 218

ER_NDB_WAITING_INFO error code, 198

ER_NDB_WAITING_INFO_WITH_MAP error code, 198

ER_NEED_LOG_BIN error code, 148

ER_NEED_REPREPARE error code, 40

ER_NETWORK_NAMESPACES_NOT_SUPPORTED error code, 183

ER_NETWORK_NAMESPACE_FILE_PATH_TOO_LONGER_NOTE_KEYRING_COMPONENT_STORE_FAILED
error code, 486
ER_NETWORK_NAMESPACE_NOT_ALLOWED_FOR_WRITE_TO_ADDRESS_COMPONENT_WRITE_MAXIMUM_DATA
error code, 486
ER_NETWORK_READ_EVENT_CHECKSUM_FAILURE
error code, 455
ER_NET_ERROR_ON_WRITE error code, 13
ER_NET_FCNTL_ERROR error code, 13
ER_NET_OK_PACKET_TOO_LARGE error code, 64
ER_NET_PACKETS_OUT_OF_ORDER error code, 13
ER_NET_PACKET_TOO_LARGE error code, 13
ER_NET_READ_ERROR error code, 13
ER_NET_READ_ERROR_FROM_PIPE error code, 13
ER_NET_READ_INTERRUPTED error code, 13
ER_NET_UNCOMPRESS_ERROR error code, 13
ER_NET_WAIT_ERROR error code, 487
ER_NET_WAIT_ERROR2 error code, 520
ER_NET_WRITE_INTERRUPTED error code, 14
ER_NEW_ABORTING_CONNECTION error code, 15
ER_NO error code, 3
ER_NONEXISTING_GRANT error code, 12
ER_NONEXISTING_PROC_GRANT error code, 28
ER_NONEXISTING_TABLE_GRANT error code, 13
ER_NONPOSITIVE_RADIUS error code, 94
ER_NONUNIQ_TABLE error code, 7
ER_NONUPDATEABLE_COLUMN error code, 25
ER_NON_BOOLEAN_EXPR_FOR_CHECK_CONSTRAINT
error code, 106
ER_NON_DEFAULT_VALUE_FOR_GENERATED_COLUMN
error code, 67
ER_NON_GROUPING_FIELD_USED error code, 31
ER_NON_INSERTABLE_TABLE error code, 32
ER_NON_RO_SELECT_DISABLE_TIMER error code, 61
ER_NON_UNIQ_ERROR error code, 6
ER_NON_UPDATABLE_TABLE error code, 21
ER_NORMAL_SERVER_SHUTDOWN error code, 454
ER_NORMAL_SHUTDOWN error code, 8
ER_NOTE_KEYRING_COMPONENT_AES_DATA_IDENTITY
error code, 519
ER_NOTE_KEYRING_COMPONENT_AES_INVALID_KEY
error code, 519
ER_NOTE_KEYRING_COMPONENT_AES_INVALID_MODE
error code, 519
ER_NOTE_KEYRING_COMPONENT_AES_OPERATION
error code, 519
ER_NOTE_KEYRING_COMPONENT_GENERATE_FAILED
error code, 520
ER_NOTE_KEYRING_COMPONENT_INITIALIZED
error code, 518
ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA
error code, 520
ER_NOTE_KEYRING_COMPONENT_METADATA_ITERATOR
error code, 520
ER_NOTE_KEYRING_COMPONENT_READ_DATA_NOTE
error code, 519
ER_NOTE_KEYRING_COMPONENT_REMOVE_FAILED
error code, 519
error code, 519
ER_NOT_ALLOWED_COMMAND error code, 13
ER_NOT_ALLOWED_WITH_START_TRANSACTION
error code, 123
ER_NOT_FORM_FILE error code, 5
ER_NOT_HINT_UPDATABLE_VARIABLE error code, 87
ER_NOT_IMPLEMENTED_FOR_CARTESIAN_SRS
error code, 94
ER_NOT_IMPLEMENTED_FOR_GEOGRAPHIC_SRS
error code, 85
ER_NOT_IMPLEMENTED_FOR_PROJECTED_SRS
error code, 94
ER_NOT_IMPLEMENTED_GET_TABLESPACE_STATISTICS
error code, 269
ER_NOT_KEYFILE error code, 5
ER_NOT_RIGHT_NOW error code, 145
ER_NOT_SUPPORTED_AUTH_MODE error code, 19
ER_NOT_SUPPORTED_YET error code, 18
ER_NOT_VALID_PASSWORD error code, 54
ER_NO_ACCESS_TO_NATIVE_FCT error code, 79
ER_NO_BINARY_LOGGING error code, 27
ER_NO_BINLOG_ERROR error code, 35
ER_NO_CSV_NO_LOG_TABLES error code, 147
ER_NO_DB_ERROR error code, 6
ER_NO_DEFAULT error code, 18
ER_NO_DEFAULT_FOR_FIELD error code, 26
ER_NO_DEFAULT_FOR_VIEW_FIELD error code, 29
ER_NO_ERROR_LOG_PARSER_CONFIGURED error
code, 513
ER_NO_FORMAT_DESCRIPTION_EVENT_BEFORE_BINLOG
error code, 39
ER_NO_FT_MATERIALIZED_SUBQUERY error code, 60
ER_NO_PARTITION_FOR_GIVEN_VALUE error code,
35
ER_NO_PARTITION_FOR_GIVEN_VALUE_SILENT
error code, 38
ER_NO_PARTS_ERROR error code, 34
ER_NO_PERMISSION_TO_CREATE_USER error
code, 16
ER_NO_REFERENCED_ROW error code, 17
ER_NO_REFERENCED_ROW_2 error code, 31
ER_NO_SECURE_TRANSPORTS_CONFIGURED
error code, 71
ER_NO_THREADS_IN_SESSION_FAILED
error code, 113
ER_NO SUCH_DB error code, 74
ER_NO_THREADS_IN_SESSION_FAILED
error code, 8
ER_NO SUCH_INDEX_PARAMETER
error code, 8
ER_NO SUCH_TABLE error code, 13
ER_NO SUCH_THREAD error code, 9
ER_NO SUCH_USER error code, 30
ER_NO_SUPER WITHOUT_USER_PLUGIN error
code, 164

ER_NO_SYSTEM_SCHEMA_ACCESS error code, 78
ER_NO_SYSTEM_TABLESPACE_ACCESS error code, 78
ER_NO_SYSTEM_TABLE_ACCESS error code, 78
ER_NO_SYSTEM_TABLE_ACCESS_FOR_DICTIONARY error code, 78
ER_NO_SYSTEM_TABLE_ACCESS_FOR_SYSTEM_TABLE error code, 78
ER_NO_SYSTEM_TABLE_ACCESS_FOR_TABLE error code, 78
ER_NO_SYSTEM_VIEW_ACCESS error code, 85
ER_NO_TABLES_USED error code, 9
ER_NO_THD_NO_UUID error code, 138
ER_NO_TRIGGER_ON_SYSTEM_SCHEMA error code, 32
ER_NO_UNIQUE_LOGFILE error code, 9
ER_NPIPE_CANT_CREATE error code, 228
ER_NPIPE_FAILED_TO_INIT_SECURITY_DESCRIPTOR error code, 171
ER_NPIPE_FAILED_TO_SET_SECURITY_DESCRIPTOR error code, 171
ER_NPIPE_PIPE_ALREADY_IN_USE error code, 172
ER_NULL_COLUMN_IN_INDEX error code, 11
ER_NULL_IN_VALUES_LESS_THAN error code, 37
ER_NUMERIC_JSON_VALUE_OUT_OF_RANGE error code, 70
ER_OLD_FILE_FORMAT error code, 31
ER_OLD_KEYFILE error code, 5
ER_OLD_PASSWORDS_NO_MIDDLE_GROUND error code, 140
ER_OLD_TEMPORALS_UPGRADED error code, 58
ER_ONLY_FD_AND_RBR_EVENTS_ALLOWED_IN_BINLOG_PARTITION_MAXVALUE_ERROR error code, 33
ER_ONLY_IMPLEMENTED_FOR_SRID_0_AND_4326 error code, 91
ER_ONLY_INTEGERS_ALLOWED error code, 38
ER_ONLY_ON_RANGE_LIST_PARTITION error code, 34
ER_OOM error code, 145
ER_OOM_SAVE_GTIDS error code, 455
ER_OPEN_AS_READONLY error code, 5
ER_OPEN_ROLE_TABLES error code, 76
ER_OPERAND_COLUMNS error code, 18
ER_OPTION_PREVENTS_STATEMENT error code, 21
ER_OPT_WRONG_TREE error code, 132
ER_OUTOFCMEMORY error code, 5
ER_OUT_OF_RESOURCES error code, 5
ER_OUT_OF_SORTMEMORY error code, 5
ER_PAGE_TRACKING_CANNOT_PURGE error code, 104
ER_PAGE_TRACKING_NOT_STARTED error code, 104
ER_PAGE_TRACKING_RANGE_NOT_TRACKED error code, 104
ER_PARSER_TRACE error code, 132
ER_PARSE_ERROR error code, 7
ER_PARSE_ERROR_IN_DIGEST_FN error code, 91
ER_PARSING_VIEW error code, 138
ER_PARTIAL_REVOKES_EXIST error code, 114
ER_PARTIAL_REVOKES_AND_DB_GRANT_BOTH_EXISTS error code, 115
ER_PARTITION_CLAUSE_ON_NONPARTITIONED error code, 49
ER_PARTITION_COLUMN_LIST_ERROR error code, 42
ER_PARTITION_CONST_DOMAIN_ERROR error code, 37
ER_PARTITION_ENTRY_ERROR error code, 33
ER_PARTITION_EXCHANGE_DIFFERENT_OPTION error code, 48
ER_PARTITION_EXCHANGE_FOREIGN_KEY error code, 48
ER_PARTITION_EXCHANGE_PART_TABLE error code, 48
ER_PARTITION_EXCHANGE_TEMP_TABLE error code, 48
ER_PARTITION_FIELDS_TOO_LONG error code, 42
ER_PARTITION_FUNCTION_FAILURE error code, 35
ER_PARTITION_FUNCTION_IS_NOT_ALLOWED error code, 37
ER_PARTITION_FUNC_NOT_ALLOWED_ERROR error code, 33
ER_PARTITION_HANDLER_ADMIN_MSG error code, 247
ER_PARTITION_INSTEAD_OF_SUBPARTITION error code, 48
ER_PARTITION_MAXVALUE_ERROR error code, 37
ER_PARTITION_MERGE_ERROR error code, 37
ER_PARTITION_MGMT_ON_NONPARTITIONED error code, 34
ER_PARTITION_MOVE_CREATED_DUPLICATE_ROW PLEASE error code, 229
ER_PARTITION_NAME error code, 41
ER_PARTITION_NOT_DEFINED_ERROR error code, 33
ER_PARTITION_NO_TEMPORARY error code, 37
ER_PARTITIONQUIRES_VALUES_ERROR error code, 32
ER_PARTITION_WRONG_NO_PART_ERROR error code, 33
ER_PARTITION_WRONG_NO_SUBPART_ERROR error code, 33
ER_PARTITION_WRONG_VALUES_ERROR error code, 32
ER_PART_EXPR_TOO_LONG error code, 85
ER_PASSWORD_ANONYMOUS_USER error code, 12
ER_PASSWORD_CANNOT_BE_RETAINED_ON_PLUGIN_CHANGE error code, 114
ER_PASSWORD_EXPIRATION_NOT_SUPPORTED_BY_AUTHENTICATION error code, 90
ER_PASSWORD_EXPIRE_ANONYMOUS_USER error code, 60

ER_PASSWORD_FORMAT error code, 54
ER_PASSWORD_NOT_ALLOWED error code, 12
ER_PASSWORD_NO_MATCH error code, 12
ER_PATH_IN_DATADIR error code, 86
ER_PATH_LENGTH error code, 44
ER_PERFSHEMA_COMPONENTS_INFRASTRUCTURE error code, 234
ER_PERFSHEMA_TABLES_INIT FAILED error code, 149
ER_PERFSHEMA_TABLES_INIT_FAILED error code, 235
ER_PERSISTENT_PRIVILEGES_BOOTSTRAP error code, 235
ER_PERSIST_ONLY_ACCESS_DENIED_ERROR error code, 86
ER_PERSIST_OPTION_HOST_TRUNCATED error code, 487
ER_PERSIST_OPTION_STATUS error code, 269
ER_PERSIST_OPTION_USER_TRUNCATED error code, 487
ER_PER_CHANNEL_RPL_FILTER_CONF_FOR_GRP_RBR_PLUGIN_OOM error code, 212
ER_PFS_MALLOC_ARRAY_OOM error code, 245
ER_PFS_MALLOC_ARRAY_OVERFLOW error code, 245
ER_PFS_NOTIFICATION_FUNCTION_REGISTER_FAILED error code, 238
ER_PID_FILEPATH_LOCATIONS_INACCESSIBLE error code, 462
ER_PID_FILE_PRIV_DIRECTORY_INSECURE error code, 331
ER_PK_INDEX_CANT_BE_INVISIBLE error code, 76
ER_PLUGGABLE_PROTOCOL_COMMAND_NOT_SUPPORTED error code, 69
ER_PLUGIN_BAD_OPTIONS error code, 212
ER_PLUGIN_CANNOT_BE_UNINSTALLED error code, 58
ER_PLUGIN_CANT_LOAD error code, 211
ER_PLUGIN_CANT_OPEN_PLUGIN_TABLE error code, 211
ER_PLUGIN_CANT_SET_PERSISTENT_OPTIONS error code, 213
ER_PLUGIN_COMMON_FAILED_TO_OPEN_FILTER_TABLE error code, 268
ER_PLUGIN_COMMON_FAILED_TO_OPEN_TABLE error code, 268
ER_PLUGIN_DELETE_BUILTIN error code, 40
ER_PLUGIN_DID_NOT_DEINITIALIZE_THREADS error code, 181
ER_PLUGIN_DISABLED error code, 212
ER_PLUGIN_FAILED_DEINITIALIZATION error code, 211
ER_PLUGIN_FAILED_TO_OPEN_TABLE error code, 459
ER_PLUGIN_FAILED_TO_OPEN_TABLES error code, 459
ER_PLUGIN_FORCING_SHUTDOWN error code, 211
ER_PLUGIN_HAS_CONFLICTING_SYSTEM_VARIABLES error code, 212
ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_DEINITIALIZE_THREADS error code, 211
ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_SHUTDOWN error code, 211
ER_PLUGIN_INIT_FAILED error code, 152
ER_PLUGIN_SHUTDOWN_UNINSTALL_ERROR error code, 468
ER_PLUGIN_INVALID_TABLE_DEFINITION error code, 525
ER_PLUGIN_IS_NOT_LOADED error code, 35
ER_PLUGIN_IS_PERMANENT error code, 45
ER_PLUGIN_LOAD_OPTIONS_IGNORED error code, 495
ER_PLUGIN_LOAD_PARAMETER_TOO_LONG error code, 211
ER_PLUGIN_NOT_EARLY error code, 108
ER_PLUGIN_NOT_EARLY_DUP error code, 487
ER_PLUGIN_NO_INSTALL error code, 47
ER_PLUGIN_NO_INSTALL_DUP error code, 487
ER_PLUGIN_NO_UNINSTALL error code, 47
ER_PLUGIN_SHUTTING_DOWN_PLUGIN error code, 211
ER_PLUGIN_UNINSTALL_ERROR error code, 468
ER_PLUGIN_UNKNOWN_VARIABLE_TYPE error code, 212
ER_PLUGIN_VARIABLE_MISSING_NAME error code, 212
ER_PLUGIN_VARIABLE_NOT_ALLOCATED_THREAD_LOCAL error code, 212
ER_PLUGIN_VARIABLE_SET_READ_ONLY error code, 212
ER_POINTLESS_WITHOUT_SLOWLOG error code, 140
ER_POLYGON_TOO_LARGE error code, 96
ER_PREPARE_FOR_SECONDARY_ENGINE error code, 481
ER_PREVENTS_VARIABLE_WITHOUT_RBR error code, 66
ER_PRIMARY_CANT_HAVE_NULL error code, 14
ER_PRIVILEGE_SYSTEM_INIT_FAILED error code, 235
ER_PROCACCESS_DENIED_ERROR error code, 26
ER_PROC_AUTO_GRANT_FAIL error code, 28
ER_PROC_AUTO_REVOKED_FAIL error code, 28
ER_PROTOCOL_COMPRESSION_RESET_LOG error code, 494
ER_PS_MANY_PARAM error code, 27
ER_PS_NO_RECURSION error code, 30
ER_QUERY_CACHE_DISABLED error code, 42
ER_QUERY_INTERRUPTED error code, 23
ER_QUERY_ON_FOREIGN_DATA_SOURCE error code, 29

ER_QUERY_TIMEOUT error code, 61
ER_RANGE_NOT_INCREASING_ERROR error code, 33
ER_READING_TABLE_FAILED error code, 153
ER_READY error code, 8
ER_READ_LOG_EVENT_FAILED error code, 243
ER_READ_ONLY_MODE error code, 55
ER_READ_ONLY_TRANSACTION error code, 16
ER REALLY_RUN_AS_ROOT error code, 144
ER_RECORD_FILE_FULL error code, 10
ER_RECOVERING_TABLE error code, 213
ER_REFERENCED_TRG_DOES_NOT_EXIST error code, 60
ER_REGEXP_BAD_ESCAPE_SEQUENCE error code, 92
ER_REGEXP_BAD_INTERVAL error code, 92
ER_REGEXP_BUFFER_OVERFLOW error code, 92
ER_REGEXP_ERROR error code, 12
ER_REGEXP_ILLEGAL_ARGUMENT error code, 92
ER_REGEXP_INDEX_OUTOFGBOUNDS_ERROR error code, 92
ER_REGEXP_INTERNAL_ERROR error code, 92
ER_REGEXP_INVALID_BACK_REF error code, 92
ER_REGEXP_INVALID_CAPTURE_GROUP_NAME error code, 113
ER_REGEXP_INVALID_FLAG error code, 114
ER_REGEXP_INVALID_RANGE error code, 93
ER_REGEXP_LOOK_BEHIND_LIMIT error code, 93
ER_REGEXP_MAX_LT_MIN error code, 92
ER_REGEXP_MISMATCHED_PAREN error code, 92
ER_REGEXP_MISSING_CLOSE_BRACKET error code, 93
ER_REGEXP_PATTERN_TOO_BIG error code, 93
ER_REGEXP_RULE_SYNTAX error code, 92
ER_REGEXP_STACK_OVERFLOW error code, 93
ER_REGEXP_STRING_NOT_TERMINATED error code, 91
ER_REGEXP_TIME_OUT error code, 93
ER_REGEXP_UNIMPLEMENTED error code, 92
ER_REGEX_NUMBER_TOO_BIG error code, 126
ER_RELAY_LOG_FAIL error code, 26
ER_RELAY_LOG_INIT error code, 27
ER_RELAY_LOG_SPACE_LIMIT_DISABLED error code, 464
ER_RELOAD_KEYRING_FAILURE error code, 130
ER_REMOVED_SPACES error code, 32
ER_RENAMED_NAME error code, 41
ER_RENAME_ROLE error code, 76
ER_REORG_HASH_ONLY_ON_SAME_NO error code, 34
ER_REORG_NO_PARAM_ERROR error code, 34
ER_REORG_OUTSIDE_RANGE error code, 35
ER_REORG_PARTITION_NOT_EXIST error code, 35
ER_REPLACE_INACCESSIBLE_ROWS error code, 63
ER_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME error code, 516
ERQUIRES_PRIMARY_KEY error code, 14
ER_REQUIRE_ROW_FORMAT_INVALID_VALUE error code, 119
ER_RESERVED_SYNTAX error code, 27
ER_RESERVED_TABLESPACE_NAME error code, 95
ER_RESET_MASTER_TO_VALUE_OUT_OF_RANGE error code, 79
ER_RESIGNAL_WITHOUT_ACTIVE_HANDLER error code, 41
ER_RESOURCE_GROUP_BIND_FAILED error code, 89
ER_RESOURCE_GROUP_BUSY error code, 89
ER_RESOURCE_GROUP_DISABLED error code, 89
ER_RESOURCE_GROUP_EXISTS error code, 88
ER_RESOURCE_GROUP_IS_DISABLED error code, 238
ER_RESOURCE_GROUP_METADATA_UPDATE_SKIPPED error code, 237
ER_RESOURCE_GROUP_NOT_EXISTS error code, 88
ER_RESOURCE_GROUP_POST_INIT_FAILED error code, 234
ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED error code, 234
ER_RESOURCE_GROUP_VALIDATION_FAILED error code, 238
ER_RESTART_RECEIVED_INFO error code, 250
ER_RESTART_SERVER_FAILED error code, 94
ER_RES_GRP FAILED DETERMINE_CPU_COUNT error code, 239
ER_RES_GRP FAILED TO DETERMINE_NICE_CAPABILITY error code, 239
ER_RES_GRP FAILED TO GET_THREAD_HANDLE error code, 239
ER_RES_GRP FEATURE NOT AVAILABLE error code, 239
ER_RES_GRP GET_THREAD_PRIO NOT SUPPORTED error code, 239
ER_RES_GRP INVALID_THREAD_PRIORITY error code, 239
ER_RES_GRP INVALID_VCPU_ID error code, 249
ER_RES_GRP INVALID_VCPU_RANGE error code, 249
ER_RES_GRP SET_THREAD_PRIORITY FAILED error code, 239
ER_RES_GRP SET_THR_AFFINITY FAILED error code, 238
ER_RES_GRP SET_THR_AFFINITY_TO_CPUS FAILED error code, 239
ER_RES_GRP SOLARIS_PROCESSOR_AFFINITY FAILED error code, 240
ER_RES_GRP SOLARIS_PROCESSOR_BIND_TO_CPUID FAILED error code, 240
ER_RES_GRP SOLARIS_PROCESSOR_BIND_TO_THREAD FAILED error code, 240
ASRGRESUPGRNAMEHD_UNBIND_FROM_CPU FAILED error code, 239
ER_RETRYING_REPAIR_WITHOUT_QUICK error code, 213

ER_RETRYING_REPAIR_WITH_KEYCACHE error code, 213	ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEAT_INFO error code, 180
ER_REVOKED_GRANTS error code, 20	ER_RPL_BINLOG_STARTING_DUMP error code, 180
ER_REWRITER_LOAD_FAILED error code, 270	ER_RPL_BINLOG_STORAGE_DELEGATES_INIT_FAILED error code, 152
ER_REWRITER_OOM error code, 270	ER_RPL_BINLOG_TRANSMIT_DELEGATES_INIT_FAILED error code, 152
ER_REWRITER_QUERY_ERROR_MSG error code, 266	ER_RPL_CANT_ADD_DO_TABLE error code, 146
ER_REWRITER_QUERY_FAILED error code, 266	ER_RPL_CANT_ADD_IGNORE_TABLE error code, 146
ER_REWRITER_READ_FAILED error code, 270	ER_RPL_CANT_CREATE_SLAVE_THREAD error code, 189
ER_REWRITER_TABLE_MALFORMED_ERROR error code, 270	ER_RPL_CANT_FIND_FOLLOWUP_FILE error code, 193
ER_ROLE_GRANTED_TO_ITSELF error code, 129	ER_RPL_CANT_HAVE_SAME_BASENAME error code, 231
ER_ROLE_NOT_GRANTED error code, 76	ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_RLI_INIT_INFO error code, 196
ER_ROW_DATA_TOO_BIG_TO_WRITE_IN_BINLOG error code, 243	ER_RPL_CANT_MAKE_PATHS error code, 148
ER_ROW_DOES_NOT_MATCH_GIVEN_PARTITION_SE	ER_RPL_CANT_OPEN_INFO_TABLE error code, 173
error code, 49	ER_RPL_CANT_OPEN_LOG_IN_RLI_INIT_INFO error code, 197
ER_ROW_DOES_NOT_MATCH_PARTITION error code, 48	ER_RPL_CANT_SCAN_INFO_TABLE error code, 173
ER_ROW_IN_WRONG_PARTITION error code, 57	ER_RPL_CANT_STOP_SLAVE_WHILE_LOCKED_BACKUP error code, 110
ER_ROW_IN_WRONG_PARTITION_PLEASE_REPAIR error code, 155	ER_RPL_CHANGING_RELAY_LOG_INFO_REPO_TYPE_FAILED error code, 175
ER_ROW_IS_REFERENCED error code, 17	ER_RPL_CHANNELS_REQUIRE_NON_ZERO_SERVER_ID error code, 174
ER_ROW_IS_REFERENCED_2 error code, 31	ER_RPL_CHANNELS_REQUIRE_TABLES_AS_INFO_REPOS error code, 174
ER_ROW_SINGLE_PARTITION_FIELD_ERROR error code, 42	ER_RPL_CORRUPTED_INFO_TABLE error code, 173
ER_RPL_ASYNC_CHANNEL_CANT_CONNECT error code, 514	ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE error code, 174
ER_RPL_ASYNC_CHANNEL_CANT_CONNECT_NO_QUORUM error code, 514	ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MASTER error code, 104
ER_RPL_ASYNC_CHANNEL_STOPPED_QUORUM_LOSS error code, 514	ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT error code, 104
ER_RPL_ASYNC_EXECUTING_QUERY error code, 515	ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY error code, 102
ER_RPL_ASYNC_MANAGED_NAME_ADDED error code, 515	ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY error code, 103
ER_RPL_ASYNC_MANAGED_NAME_REMOVED error code, 515	ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY error code, 103
ER_RPL_ASYNC_READ_FAILOVER_TABLE error code, 515	ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS error code, 103
ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFFER error code, 124	ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY error code, 103
ER_RPL_ASYNC_RECONNECT_FAIL_NO_SOURCE error code, 512	ER_RPL_ENCRYPTION_HEADER_ERROR error code, 103
ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF error code, 124	ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY error code, 102
ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF_CHANGE error code, 517	ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED error code, 103
ER_RPL_ASYNC_SENDER_ADDED error code, 514	ER_RPL_ENCRYPTION_KEY_NOT_FOUND error code, 102
ER_RPL_ASYNC_SENDER_REMOVED error code, 514	ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED error code, 103
ER_RPL_BINLOG_FILTERS_OOM error code, 142	
ER_RPL_BINLOG_MASTER SENDS HEARTBEAT error code, 180	
ER_RPL_BINLOG_MASTER_USES_CHECKSUM_AND_UPGRADE error code, 180	
ER_RPL_BINLOG_RELAY_DELEGATES_INIT_FAILED error code, 152	

ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTION error code, 103
ER_RPL_GTID_UNSAFE_STMT_ON_TEMPORARY_TABLE error code, 454

ER_RPL_ERROR_CHANGING_MASTER_INFO_REPO error code, 175
ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR error code, 179

ER_RPL_ERROR_CHANGING_RELAY_LOG_INFO_REPO error code, 175
ER_RPL_INCONSISTENT_SEQUENCE_NO_IN_TRX error code, 174

ER_RPL_ERROR_CHECKING_REPOSITORY error code, 175
ER_RPL_INCONSISTENT_TIMESTAMPS_IN_TRX error code, 174

ER_RPL_ERROR_CREATING_MASTER_INFO error code, 174
ER_RPL_INFINITY_DENIED error code, 150

ER_RPL_ERROR_CREATING_RELAY_LOG_INFO error code, 175
ER_RPL_INFINITY_IGNORED error code, 151

ER_RPL_ERROR_READING_MASTER_CONFIGURATION error code, 210
ER_RPL_INFO_DATA_TOO_LONG error code, 48

ER_RPL_ERROR_LOOKING_FOR_LOG error code, 193
ER_RPL_IO_THREAD_KILLED error code, 243

ER_RPL_ERROR_READING_SLAVE_WORKER_CONFIGURATION error code, 209
ER_RPL_LOG_ENTRY_EXCEEDS_SLAVE_MAX_ALLOWED_PACKET error code, 192

ER_RPL_ERROR_WRITING_MASTER_CONFIGURATION error code, 210
ER_RPL_LOG_ENTRY_EXCEEDS_SLAVE_MAX_ALLOWED_PACKET error code, 192

ER_RPL_ERROR_WRITING_RELAY_LOG_CONFIGURATION error code, 197
ER_RPL_MTS_CHECKPOINT_PERIOD_DIFFERS_FROM_CNT error code, 193

ER_RPL_ERROR_WRITING_SLAVE_WORKER_CONFIGURATION error code, 209
ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO error code, 193

ER_RPL_FAILED_TO_CREATE_CACHE_FOR_INFO_FILE error code, 176
ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO_FOR_WORKER error code, 192

ER_RPL_FAILED_TO_CREATE_NEW_INFO_FILE error code, 176
ER_RPL_MTS_RECOVERY_CANT_OPEN_RELAY_LOG error code, 189

ER_RPL_FAILED_TO_DELETE_FROM_SLAVE_WORKERS error code, 175
ER_RPL_MTS_RECOVERY_COMPLETE error code, 191

ER_RPL_FAILED_TO_OPEN_INFO_FILE error code, 176
ER_RPL_MTS_RECOVERY_FAILED_TO_START_COORDINATOR error code, 189

ER_RPL_FAILED_TO_OPEN_RELAY_LOG error code, 209
ER_RPL_MTS_RECOVERY_STARTING_COORDINATOR error code, 189

ER_RPL_FAILED_TO_RESET_STATE_IN_SLAVE_INFO error code, 175
ER_RPL_MTS_RECOVERY_SUCCESSFUL error code, 189

ER_RPL_FAILED_TO_STAT_LOG_IN_INDEX error code, 196
ER_RPL_MTS_SLAVE_COORDINATOR_HAS_WAITED error code, 210

ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL error code, 244
ER_RPL_MTS_STATISTICS error code, 191

ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED error code, 235
ER_RPL_MULTISOURCEQUIRES_TABLE_TYPE_REPOSITORY error code, 176

ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED error code, 235
ER_RPL_OPEN_INDEX_FILE_FAILED error code, 196

ER_RPL_PLEASE_USE_OPTION_RELAY_LOG error code, 196

ER_RPL_GTID_LOG_EVENT_IN_STREAM error code, 178
ER_RPL_PLUGIN_FUNCTION_FAILED error code, 152

ER_RPL_GTID_MEMORY_FINALLY_AVAILABLE error code, 176
ER_RPL_RECOVERY_ERROR error code, 188

ER_RPL_GTID_MODE_REQUIRESENFORCE_GTID_CONSISTENCY_ERROR_FREEING_IO_CACHE error code, 231
ER_RPL_RECOVERY_ERROR_FREEING_IO_CACHE error code, 188

ER_RPL_GTID_TABLE_CANNOT_OPEN error code, 133
ER_RPL_RECOVERY_ERROR_READ_RELAY_LOG error code, 188

ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT error code, 467
ER_RPL_REPLICATION_FILE_MASTER_POS_INFO error code, 188

ER_RPL_GTID_UNSAFE_STMT_CREATE_SELECT error code, 454
ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG_INDIRECT error code, 188

ER_RPL_GTID_UNSAFE_STMT_ON_NON_TRANS_TAB error code, 453
ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_MASTER error code, 188

ER_RPL_RECOVERY_REPLICATE_SAME_SERVER_ID error code, 188
ER_RPL_RECOVERY_SKIPPED_GROUP_REPLICATION error code, 188
ER_RPL_RELAY_LOG_INDEX_NEEDS_FILE_NOT_DIRECTORY error code, 196
ER_RPL_RELAY_LOG_NEEDS_FILE_NOT_DIRECTORY error code, 196
ER_RPL_RELAY_LOG_RECOVERY_INFO_AFTER_CLOSE error code, 499
ER_RPL_REPLICA_MONITOR_IO_THREAD_EXITING error code, 515
ER_RPL_REPLICA_MONITOR_IO_THREAD_RECONNECT error code, 515
ER_RPL_REPO_HAS_GAPS error code, 135
ER_RPL_REPO_SHOULD_BE_TABLE error code, 174
ER_RPL_REWRITEDB_EMPTY_FROM error code, 147
ER_RPL_REWRITEDB_EMPTY_TO error code, 147
ER_RPL_REWRITEDB_MISSING_ARROW error code, 147
ER_RPL_RLI_INIT_INFO_MSG error code, 247
ER_RPL_SERVER_ID_MISSING error code, 189
ER_RPL_SLAVE_ADDITIONAL_ERROR_INFO_FROM_DA error code, 194
ER_RPL_SLAVE_APPLY_LOG_EVENT_FAILED_INVALID_ROW_FORMAT error code, 496
ER_RPL_SLAVE_AUTO_POSITION_IS_1_AND_GTID_MODE_IS_STOPPED error code, 187
ER_RPL_SLAVE_CANT_FLUSH_MASTER_INFO_FILE error code, 190
ER_RPL_SLAVE_CANT_INITIALIZE_SLAVE_WORKER error code, 192
ER_RPL_SLAVE_CANT_INIT_RELAY_LOG_POSITION error code, 191
ER_RPL_SLAVE_CANT_START_SLAVE_FOR_CHANNEL error code, 187
ER_RPL_SLAVE_CANT_STOP_SLAVE_FOR_CHANNEL error code, 188
ER_RPL_SLAVE_CANNOT_USE_CHARSET error code, 195
ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION_IS_RESUMED error code, 195
ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION_IS_STALLED error code, 191
ER_RPL_SLAVE_COULD_NOT_CREATE_CHANNEL_LIST error code, 175
ER_RPL_SLAVE_DUMP_THREAD_KILLED_BY_MASTER error code, 191
ER_RPL_SLAVE_ERROR_INFO_FROM_DA error code, 194
ER_RPL_SLAVE_ERROR_LOADING_USER_DEFINED_LIBRARY error code, 194
ER_RPL_SLAVE_ERROR_READING_FROM_SERVER error code, 190
ER_RPL_SLAVE_ERROR_READING_RELAY_LOG_EVENTS error code, 195
ER_RPL_SLAVE_ERROR_RETRYING error code, 190
ER_RPL_SLAVE_ERROR_RUNNING_QUERY error code, 176
ER_RPL_SLAVE_FAILED_TO_CREATE_CHANNEL_FROM_MASTER error code, 192
ER_RPL_SLAVE_FAILED_TO_CREATE_OR_RECOVER_INFO error code, 187
ER_RPL_SLAVE_FAILED_TO_INIT_A_MASTER_INFO_STRUCTURE error code, 176
ER_RPL_SLAVE_FAILED_TO_INIT_MASTER_INFO_STRUCTURE error code, 176
ER_RPL_SLAVE_FAILED_TO_INIT_PARTITIONS_HASH error code, 193
ER_RPL_SLAVE_FILTER_CREATE_FAILED error code, 236
ER_RPL_SLAVE_FLUSH_RELAY_LOGS_NOT_ALLOWED error code, 229
ER_RPL_SLAVE_FORCING_TO_RECONNECT_IO_THREAD error code, 191
ER_RPL_SLAVE_GENERIC_MESSAGE error code, 175
ER_RPL_SLAVE_GLOBAL_FILTERS_COPY_FAILED error code, 236
ER_RPL_SLAVE_INCORRECT_CHANNEL error code, 192
ER_RPL_SLAVE_INSECURE_CHANGE_MASTER error code, 191
ER_RPL_SLAVE_IO_THREAD_ABORTED_WAITING_FOR_REPLY error code, 192
ER_RPL_SLAVE_IO_THREAD_CANT_REGISTER_ON_MASTER error code, 191
ER_RPL_SLAVE_IO_THREAD_DETECTED_UNEXPECTED_ERROR error code, 195
ER_RPL_SLAVE_IO_THREAD_EXITING error code, 192
ER_RPL_SLAVE_IO_THREAD_KILLED error code, 192
ER_RPL_SLAVE_IO_THREAD_STOP_CMD_EXEC_TIMEOUT error code, 453
ER_RPL_SLAVE_IO_THREAD_WAS_KILLED error code, 195
ER_RPL_SLAVE_MASTER_UUID_HAS_CHANGED error code, 195
ER_RPL_SLAVE_NDB_TABLES_NOT_AVAILABLE error code, 193
ER_RPL_SLAVE_NEW_MASTER_INFO_NEEDS_REPO_TYPE error code, 196
ER_RPL_SLAVE_NEXT_LOG_IS_ACTIVE error code, 195
ER_RPL_SLAVE_NEXT_LOG_IS_INACTIVE error code, 195
ER_RPL_SLAVE_QUEUE_EVENT_FAILED_INVALID_CONFIGURATION error code, 194
ER_RPL_SLAVE_QUEUE_EVENT_FAILED_INVALID_NON_RESPONSE error code, 496

ER_RPL_SLAVE_READ_INVALID_EVENT_FROM_MASTER error code, 42
error code, 194
ER_RPL_SLAVE_REPORT_HOST_TOO_LONG error code, 190
ER_RPL_SLAVE_REPORT_PASSWORD_TOO_LONG error code, 190
ER_RPL_SLAVE_REPORT_USER_TOO_LONG error code, 190
ER_RPL_SLAVE_RESET_FILTER_OPTIONS error code, 236
ER_RPL_SLAVE_SECONDS_BEHIND_MASTER_DUBIOUS error code, 190
ER_RPL_SLAVE_SKIP_COUNTER_EXECUTED error code, 194
ER_RPL_SLAVE_SQL_THREAD_DETECTED_UNEXPECTED_CODE_SEQUENCE error code, 496
ER_RPL_SLAVE_SQL_THREAD_EXITING error code, 194
ER_RPL_SLAVE_SQL_THREAD_IO_ERROR_READING_ERROR_GET_KEYS_INVALID_TABLESPACE error code, 195
ER_RPL_SLAVE_SQL_THREAD_STARTING error code, 193
ER_RPL_SLAVE_SQL_THREAD_STARTING_WITH_PRIVILEGE_CHECKS error code, 495
ER_RPL_SLAVE_SQL_THREAD_STOP_CMD_EXEC_TIMROSE_SECONDARY_ENGINE_DDL error code, 453
ER_RPL_SLAVE_STOPPING_AS_MASTER_OOM error code, 192
ER_RPL_SLAVE_USES_CHECKSUM_AND_MASTER_PRR_SECURE_AUTH_VALUE_UNSUPPORTED error code, 190
ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED_ER_SECURE_TRANSPORT_REQUIRED error code, 193
ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED_ER_SWITCH_INQUIRIV_ARGUMENT_TOO_LONG error code, 193
ER_RPL_SSL_INFO_IN_MASTER_INFO_IGNORED error code, 211
ER_RPL_TIMESTAMPS_RETURNED_TO_NORMAL error code, 236
ER_RPL_TRX_DELEGATES_INIT_FAILED error code, 152
ER_RPL_UNEXPECTED_BEGIN_IN_STREAM error code, 178
ER_RPL_UNEXPECTED_COMMIT_ROLLBACK_OR_XID_ER_ROSE_EVENT_IN_STREAM_ERROR error code, 178
ER_RPL_UNEXPECTED_XA_ROLLBACK_IN_STREAM error code, 178
ER_RPL_UNSUPPORTED_UNIGNORABLE_EVENT_IN_SEMISYNC_BINLOG_REPLY_IS_AHEAD error code, 178
ER_RPL_WORKER_CANT_FIND_NEXT_RELAY_LOG error code, 210
ER_RPL_WORKER_CANT_READ_RELAY_LOG error code, 209
ER_RPL_WORKER_ID_IS error code, 174
ER_RPL_ZOMBIE_ENCOUNTERED error code, 133
ER_RUNNING_APPLIER_PREVENTS_SWITCH_GLOBAL_ER_IS_SYNC_DISABLED_ON_MASTER error code, 98
ER_RUN_HOOK_ERROR error code, 66
ER_SAME_NAME_PARTITION error code, 35
ER_SCHEDULER_KILLING error code, 137
ER_SCHEDULER_STARTED error code, 137
ER_SCHEDULER_STOPPED error code, 136
ER_SCHEDULER_STOPPING_FAILED_TO_CREATE_WORKER error code, 137
ER_SCHEDULER_STOPPING_FAILED_TO_GET_EVENT error code, 137
ER_SCHEDULER_WAITING error code, 136
ER_SCHEMA_DIR_CREATE_FAILED error code, 91
ER_SCHEMA_DIR_EXISTS error code, 91
ER_SCHEMA_DIR_MISSING error code, 91
ER_SCHEMA_DIR_UNKNOWN error code, 91
ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED_ER_IS_SYNC_DISABLED_ON_MASTER error code, 137
ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_DDL error code, 498
ER_SCHEMA_READ_ONLY error code, 124
ER_SDIDN_GET_KEYS_INVALID_TABLESPACE error code, 130
ER_SDI_OPERATION_FAILED error code, 89
ER_SDI_OPERATION_FAILED_MISSING_RECORD error code, 112
ER_SECONDARY_ENGINE error code, 113
ER_SECONDARY_ENGINE_DDL error code, 113
ER_SECONDARY_ENGINE_PLUGIN error code, 112
ER_SECOND_PASSWORD_CANNOT_BE_EMPTY error code, 112
ER_SECURE_AUTH_VALUE_UNSUPPORTED error code, 139
ER_SECURE_TRANSPORT_REQUIRED error code, 71
ER_SWITCH_INQUIRIV_ARGUMENT_TOO_LONG error code, 142
ER_SEC_FILE_PRIV_CANT_ACCESS_DIR error code, 141
ER_SEC_FILE_PRIV_CANT_STAT error code, 141
ER_SEC_FILE_PRIV_DIRECTORY_INSECURE error code, 141
ER_SEC_FILE_PRIV_DIRECTORY_PERMISSIONS error code, 142
ER_SEC_FILE_PRIV_EMPTY error code, 141
ER_SECURE_EVENT_IN_STREAM_ERROR error code, 141
ER_SEC_FILE_PRIV_NULL error code, 141
ER_SELECT_REDUCED error code, 19
ER_SEMISYNC_ADD_ACK_TO_SLOT error code, 258
ER_SEMISYNC_BINLOG_REPLY_IS_AHEAD error code, 257
ER_SEMISYNC_BINLOG_WRITE_OUT_OF_ORDER error code, 255
ER_SEMISYNC_CLEARED_ACTIVE_TRANSACTION_TILL_POS error code, 255
ER_SEMISYNC_CLEARED_ALL_ACTIVE_TRANSACTION_NODE error code, 255
ER_SEMISYNC_IS_SYNC_DISABLED_ON_MASTER error code, 256
ER_SEMISYNC_EXECUTION_FAILED_ON_MASTER error code, 260

ER_SEMISYNC_FAILED_REGISTER_SLAVE_TO_RECEIVER	ER_SEMISYNC_SLAVE_REPLY_WITH_BINLOG_INFO
error code, 259	error code, 260
ER_SEMISYNC_FAILED_TO_ALLOCATE_TRX_NODE	ER_SEMISYNC_SLAVE_SEND_REPLY_FAILED error code, 260
error code, 255	ER_SEMISYNC_SLAVE_SET FAILED error code, 261
ER_SEMISYNC_FAILED_TO_INSERT_TRX_NODE	ER_SEMISYNC_SLAVE_START error code, 260
error code, 258	ER_SEMISYNC_SOCKET_FD_TOO_LARGE error code, 260
ER_SEMISYNC_FAILED_TO_START_ACK_RECEIVER	ER_SEMISYNC_STARTING_ACK_RECEIVER_THD error code, 259
error code, 258	ER_SEMISYNC_START_BINLOG_DUMP_TO_SLAVE error code, 259
ER_SEMISYNC_FAILED_TO_STOP_ACK_RECEIVER	ER_SEMISYNC_STOPPING_ACK_RECEIVER_THREAD error code, 259
error code, 261	ER_SEMISYNC_STOP_BINLOG_DUMP_TO_SLAVE error code, 259
ER_SEMISYNC_FAILED_WAIT_ON_DUMP_SOCKET	ER_SEMISYNC_SYNC_HEADER_UPDATE_INFO error code, 258
error code, 259	ER_SEMISYNC_TRACE_ENTER_FUNC error code, 254
ER_SEMISYNC_FORCED_SHUTDOWN	ER_SEMISYNC_TRACE_EXIT error code, 255
error code, 256	ER_SEMISYNC_TRACE_EXIT_WITH_BOOL_EXIT_CODE error code, 255
ER_SEMISYNC_FUNCTION_CALLED_TWICE	ER_SEMISYNC_TRACE_EXIT_WITH_INT_EXIT_CODE error code, 254
error code, 256	ER_SEMISYNC_TRX_SKIPPED_AT_POS error code, 258
ER_SEMISYNC_INIT_WAIT_POS	ER_SEMISYNC_UNREGISTERED_REPLICATOR error code, 260
error code, 257	ER_SEMISYNC_UNREGISTER_BINLOG_STORAGE_OBSERVER error code, 259
ER_SEMISYNC_INSERT_LOG_INFO_IN_ENTRY	ER_SEMISYNC_UNREGISTER_BINLOG_TRANSMIT_OBSERVER error code, 259
error code, 255	ER_SEMISYNC_UNREGISTER_TRX_OBSERVER_FAILED error code, 259
ER_SEMISYNC_MASTER_FAILED_ON_NET_FLUSH	ER_SEMISYNC_UPDATE_EXISTING_SLAVE_ACK error code, 258
error code, 258	ER_SEMISYNC_WAIT_FOR_BINLOG_TIMEDOUT error code, 257
ER_SEMISYNC_MASTER_GOT_REPLY_AT_POS	ER_SEMISYNC_WAIT_TIME_ASSESSMENT_FOR_COMMIT error code, 257
error code, 256	ER_SEMISYNC_WAIT_TIME_FOR_BINLOG_SENT error code, 257
ER_SEMISYNC_MASTER_OOM	ER_SERVERID_TOO_LARGE error code, 150
error code, 256	ER_SERVER_ACL_TABLE_ERROR error code, 458
ER_SEMISYNC_MASTER_SIGNAL_ALL_WAITING_THREADS	ER_SERVER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_SYNC error code, 481
error code, 257	ER_SERVER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_SYNC error code, 482
ER_SEMISYNC_MASTER_TRX_WAIT_POS	ER_SERVER_BINLOG_UNSAFE_SYSTEM_FUNCTION error code, 485
error code, 257	ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2 error code, 458
ER_SEMISYNC_MISSING_MAGIC_NO_FOR_SEMISYNC_PKT	ER_SERVER_CANT_OPEN_FILE error code, 457
error code, 260	ER_SERVER_COL_COUNT_DOESNT_MATCH_CORRUPTED error code, 458
ER_SEMISYNC_MOVE_BACK_WAIT_POS	ER_SERVER_COL_COUNT_DOESNT_MATCH PLEASE_UPDATE error code, 458
error code, 257	
ER_SEMISYNC_NOT_SUPPORTED_BY_MASTER	
error code, 261	
ER_SEMISYNC_NO_SPACE_IN_THE_PKT	
error code, 258	
ER_SEMISYNC_PROBE_LOG_INFO_IN_ENTRY	
error code, 255	
ER_SEMISYNC_RECEIVED_ACK_IS_SMALLER	
error code, 258	
ER_SEMISYNC_REPLY_BINLOG_FILE_TOO_LARGE	
error code, 256	
ER_SEMISYNC_REPLY_MAGIC_NO_ERROR	
error code, 256	
ER_SEMISYNC_REPLY_PKT_LENGTH_TOO_SMALL	
error code, 256	
ER_SEMISYNC_RPL_ENABLED_ON_MASTER	
error code, 256	
ER_SEMISYNC_RPL_INIT_FOR_TRX	
error code, 255	
ER_SEMISYNC_RPL_SWITCHED_OFF	
error code, 257	
ER_SEMISYNC_RPL_SWITCHED_ON	
error code, 257	
ER_SEMISYNC_SERVER_REPLY	
error code, 256	
ER_SEMISYNC_SLAVE_NET_FLUSH_REPLY_FAILED	
error code, 260	
ER_SEMISYNC_SLAVE_REPLY	
error code, 260	

ER_SERVER_COST_FAILED_TO_READ error code, 177
ER_SERVER_COST_INVALID_COST_CONSTANT error code, 177
ER_SERVER_COST_UNKNOWN_COST_CONSTANT error code, 177
ER_SERVER_DISK_FULL_NOWAIT error code, 457
ER_SERVER_FILE_NOT_FOUND error code, 457
ER_SERVER_FILE_USED error code, 457
ER_SERVER_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE error code, 458
ER_SERVER_HANDLER_ERROR error code, 457
ER_SERVER_INIT_COMPILED_IN_COMMANDS error code, 247
ER_SERVER_ISNT_AVAILABLE error code, 72
ER_SERVER_IS_IN_SECURE_AUTH_MODE error code, 20
ER_SERVER_MASTER_FATAL_ERROR_READING_BINLOG error code, 455
ER_SERVER_NET_PACKET_TOO_LARGE error code, 456
ER_SERVER_NEW_ABORTING_CONNECTION error code, 457
ER_SERVER_NOT_FORM_FILE error code, 457
ER_SERVER_NO_SESSION_TO_SEND_TO error code, 456
ER_SERVER_NO_SYSTEM_TABLE_ACCESS error code, 456
ER_SERVER_OFFLINE_MODE error code, 61
ER_SERVER_OUTOFMEMORY error code, 233
ER_SERVER_OUT_OF_RESOURCES error code, 233
ER_SERVER_OUT_OF_SORTMEMORY error code, 457
ER_SERVER_RECORD_FILE_FULL error code, 457
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT error code, 477
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_FETCH error code, 472
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY error code, 473
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY error code, 473
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ROTATE_MASTER_KEY error code, 473
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_STORE error code, 473
ER_SERVER_RPL_ENCRYPTION_HEADER_ERROR error code, 473
ER_SERVER_RPL_ENCRYPTION_IGNORE_ROTATE_MASTER_KEY error code, 474
ER_SERVER_RPL_ENCRYPTION_KEYRING_INVALID_KEY error code, 472
ER_SERVER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED error code, 473
ER_SERVER_RPL_ENCRYPTION_KEY_NOT_FOUND error code, 472
ER_SERVER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED error code, 473
ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_INITIALIZE error code, 473
ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_ROTATE_MASTER_KEY error code, 474
ER_SERVER_SHUTDOWN error code, 6
ER_SERVER_SHUTDOWN_COMPLETE error code, 231
ER_SERVER_SHUTDOWN_INFO error code, 461
ER_SERVER_SLAVE_CONVERSION_FAILED error code, 458
ER_SERVER_SLAVE_IGNORED_TABLE error code, 458
ER_SERVER_SLAVE_INIT_QUERY_FAILED error code, 458
ER_SERVER_SLAVE_MI_INIT_REPOSITORY error code, 456
ER_SERVER_SLAVE_RLI_INIT_REPOSITORY error code, 456
ER_SERVER_STARTUP_ADMIN_INTERFACE error code, 474
ER_SERVER_STARTUP_MSG error code, 233
ER_SERVER_TABLE_CHECK_FAILED error code, 458
ER_SERVER_TEST_MESSAGE error code, 459
ER_SERVER_UNKNOWN_ERROR error code, 456
ER_SERVER_UNKNOWN_SYSTEM_VARIABLE error code, 456
ER_SERVER_UPGRADE_CHECKING_DB error code, 484
ER_SERVER_UPGRADE_EMPTY_SYS error code, 484
ER_SERVER_UPGRADE_FAILED error code, 483
ER_SERVER_UPGRADE_FROM_VERSION error code, 478
ER_SERVER_UPGRADE_HELP_TABLE_STATUS error code, 485
ER_SERVER_UPGRADE_INFO_FILE error code, 483
ER_SERVER_UPGRADE_MYSQL_TABLES error code, 484
ER_SERVER_UPGRADE_NO_SYS_VERSION error code, 483
ER_SERVER_UPGRADE_OFF error code, 483
ER_SERVER_UPGRADE_PENDING error code, 483
ER_SERVER_UPGRADE_REPAIR_REQUIRED error code, 483
ER_SERVER_UPGRADE_REPAIR_STATUS error code, 483
ER_SERVER_UPGRADE_SKIP error code, 483
MASTER_KEY_APPGRADE_STATUS error code, 483
ER_SERVER_UPGRADE_SYSTEM_TABLES error code, 484
ER_SERVER_UPGRADE_SYS_SCHEMA error code, 484
ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNT error code, 484
ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED error code, 484

ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE	ER_SLAVE_CHANNEL_OPERATION_NOT_ALLOWED error code, 484
ER_SLAVE_CHANNEL_SQL_SKIP_COUNTER	error code, 65
ER_SLAVE_CHANNEL_SQL_THREAD_MUST_STOP	error code, 65
ER_SLAVE_CHANNEL_WAS_NOT_RUNNING	error code, 65
ER_SLAVE_CHANNEL_WAS_RUNNING	error code, 65
ER_SLAVE_CONFIGURATION	error code, 52
ER_SLAVE_CONVERSION_FAILED	error code, 44
ER_SLAVE_CORRUPT_EVENT	error code, 39
ER_SLAVE_CREATE_EVENT_FAILURE	error code, 455
ER_SLAVE_FATAL_ERROR	error code, 455
ER_SLAVE_HAS_MORE_GTIDS_THAN_MASTER	error code, 455
ER_SLAVE_HEARTBEAT_FAILURE	error code, 456
ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE	error code, 40
ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX	error code, 45
ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN	error code, 45
ER_SLAVE_IGNORED_SSL_PARAMS	error code, 20
ER_SLAVE_IGNORED_TABLE	error code, 18
ER_SLAVE_IGNORE_SERVER_IDS	error code, 42
ER_SLAVE INCIDENT	error code, 456
ER_SLAVE_KILLED_AFTER_RECONNECT	error code, 243
ER_SLAVE_MASTER_COM_FAILURE	error code, 456
ER_SLAVE_MAX_CHANNELS_EXCEEDED	error code, 65
ER_SLAVE_MI_INIT_REPOSITORY	error code, 57
ER_SLAVE_MULTIPLE_CHANNELS_CMD	error code, 65
ER_SLAVE_NEW_CHANNEL_WRONG_REPOSITORY	error code, 64
ER_SLAVE_NOT_RUNNING	error code, 16
ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS	error code, 16
ER_SLAVE_Possibly_DIVERGED_AFTER_DDL	error code, 96
ER_SLAVE_RECONNECT_FAILED	error code, 243
ER_SLAVE_RELAY_LOG_PURGE_FAILED	error code, 236
ER_SLAVE_RELAY_LOG_READ_FAILURE	error code, 456
ER_SLAVE_RELAY_LOG_TRUNCATE_INFO	error code, 236
ER_SLAVE_RELAY_LOG_WRITE_FAILURE	error code, 456
ER_SLAVE_RLI_INIT_REPOSITORY	error code, 58
ER_SLAVE_SILENT_RETRY_TRANSACTION	error code, 53
ER_SLAVE_SQL_THREAD_MUST_STOP	error code, 60

ER_SLAVE_SQL_THREAD_STOPPED_AFTER_GTIDS_ERASERNO_RECURSION error code, 29
error code, 170
ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS_ERLSPAND_ARPSEIDerror code, 28
error code, 170
ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS_ERSPHORE_FAILED error code, 22
error code, 170
ER_SLAVE_SQL_THREAD_STOPPED_GAP_TRX_PROC_ERSSPDUNDECLARED_VAR error code, 24
error code, 170
ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_CONDITION_BADARCOND_AFTER_CURSHNDLR error code, 24
error code, 170
ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_POSITIONERRSRCPWRONG_NAME error code, 31
error code, 170
ER_SLAVE_THREAD error code, 16
ER_SLAVE_WORKER_STOPPED_PREVIOUS_THD_ERORR
error code, 61
ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGING_TO_FILE
error code, 103
ER_SPATIAL_CANT_HAVE_NULL error code, 19
ER_SPATIAL_FUNCTIONAL_INDEX error code, 100
ER_SPATIAL_MUST_HAVE_GEOM_COL error code, 44
ER_SPATIAL_UNIQUE_INDEX error code, 96
ER_SPECIFIC_ACCESS_DENIED_ERROR error code, 17
ER_SPVAR_NONINTEGER_TYPE error code, 126
ER_SP_ALREADY_EXISTS error code, 22
ER_SP_BADRETURN error code, 23
ER_SP_BADSELECT error code, 23
ER_SP_BADSTATEMENT error code, 23
ER_SP_BAD_CURSOR_QUERY error code, 23
ER_SP_BAD_CURSOR_SELECT error code, 23
ER_SP_BAD_SQLSTATE error code, 28
ER_SP_BAD_VAR_SHADOW error code, 31
ER_SP_CANT.Alter error code, 24
ER_SP_CANT_SET_AUTOCOMMIT error code, 30
ER_SP_CASE_NOT_FOUND error code, 24
ER_SP_COND_MISMATCH error code, 23
ER_SP_CURSOR_AFTER_HANDLER error code, 24
ER_SP_CURSOR_ALREADY_OPEN error code, 23
ER_SP_CURSOR_MISMATCH error code, 23
ER_SP_CURSOR_NOT_OPEN error code, 23
ER_SP_DOES_NOT_EXIST error code, 22
ER_SP_DROP_FAILED error code, 22
ER_SP_DUP_COND error code, 24
ER_SP_DUP_CURS error code, 24
ER_SP_DUP_HANDLER error code, 28
ER_SP_DUP_PARAM error code, 24
ER_SP_DUP_VAR error code, 24
ER_SP_FETCH_NO_DATA error code, 24
ER_SP_LABEL_MISMATCH error code, 22
ER_SP_LABEL_REDEFINE error code, 22
ER_SP_LILABEL_MISMATCH error code, 22
ER_SP_LOAD_FAILED error code, 75
ER_SP_NORETURN error code, 23
ER_SP_NORETURNEND error code, 23
ER_SP_NOT_VAR_ARG error code, 28
ER_SP_NO_AGGREGATE error code, 31
ER_SP_NO_DROP_SP error code, 25
ER_SP_NO_RECURSIVE_CREATE error code, 22
ER_SP_RECUSION_LIMIT error code, 31
ER_SP_SUBSELECT_NYI error code, 24
ER_SP_UNINIT_VAR error code, 23
ER_SQLTHREAD_WITH_SECURE_SLAVE error code, 155
ER_SQL_AUTHOR_DEFAULT_ROLES_FAIL error code, 155
ER_SQL_HA_READ_FAILED error code, 152
ER_SQL_MODE_MERGED error code, 69
ER_SQL_MODE_MERGED_WITH_STRICT_MODE error code, 231
ER_SQL_REPLICA_SKIP_COUNTER_USED_WITH_GTID_MODE error code, 128
ER_SQL_SLAVE_SKIP_COUNTER_NOT_SETTABLE_IN_GTID_MODE error code, 57
ER_SQL_SLAVE_SKIP_COUNTER_USED_WITH_GTID_MODE_C error code, 127
ER_SQL_USER_TABLE_ALTER_WARNING error code, 155
ER_SQL_USER_TABLE_CREATE_WARNING error code, 155
ER_SRS_ATTRIBUTE_STRING_TOO_LONG error code, 95
ER_SRS_GEOGCS_INVALID_AXES error code, 97
ER_SRS_ID_ALREADY_EXISTS error code, 94
ER_SRS_INVALID_ANGULAR_UNIT error code, 97
ER_SRS_INVALID_CHARACTER_IN_ATTRIBUTE error code, 95
ER_SRS_INVALID_INVERSE_FLATTENING error code, 97
ER_SRS_INVALID_PRIME_MERIDIAN error code, 97
ER_SRS_INVALID_SEMI_MAJOR_AXIS error code, 97
ER_SRS_MISSING_MANDATORY_ATTRIBUTE error code, 94
ER_SRS_MULTIPLE_ATTRIBUTE_DEFINITIONS error code, 94
ER_SRS_NAME_CANT_BE_EMPTY_OR_WHITESPACE error code, 94
ER_SRS_NOT_CARTESIAN error code, 76
ER_SRS_NOT_CARTESIAN_UNDEFINED error code, 76
ER_SRS_NOT_FOUND error code, 77
ER_SRS_NOT_GEOGRAPHIC error code, 96
ER_SRS_ORGANIZATION_CANT_BE_EMPTY_OR_WHITESPACE error code, 94
ER_SRS_PARSE_ERROR error code, 75

ER_SRS_PROJ_PARAMETER_MISSING error code, 75	ER_SUBQUERY_TRANSFORM_REJECTED error code, 122
ER_SR_BOGUS_VALUE error code, 152	ER_SWITCH_TMP_ENGINE error code, 80
ER_SR_INVALID_CONTEXT error code, 153	ER_SYNTAX_ERROR error code, 13
ER_SSL_FIPS_MODE_ERROR error code, 269	ER_SYSTEMD_NOTIFY_CONNECT_FAILED error code, 331
ER_SSL_LIBRARY_ERROR error code, 138	ER_SYSTEMD_NOTIFY_PATH_TOO_LONG error code, 331
ER_SSL_MEMORY_INSTRUMENTATION_INIT FAILED error code, 468	ER_SYSTEMD_NOTIFY_WRITE_FAILED error code, 331
ER_SSL_SERVER_CERT_VERIFY_FAILED error code, 487	ER_SYSTEM_SCHEMA_NOT_FOUND error code, 133
ER_SSL_TRYING_DATADIR_DEFAULTS error code, 150	ER_SYSTEM_TABLES_NOT_SUPPORTED_BY_STORAGE_E
ER_STACKSIZE_UNEXPECTED error code, 149	error code, 233
ER_STACK_OVERRUN error code, 11	ER_SYSTEM_TABLE_NOT_TRANSACTIONAL error code, 210
ER_STACK_OVERRUN_NEED_MORE error code, 30	ER_SYSTEM_VIEW_INIT_FAILED error code, 234
ER_STARTING_AS error code, 143	ER_SYSVAR_CHANGE_DURING_QUERY error code, 116
ER_STARTING_INIT error code, 461	ER_SYS_VAR_COMPONENT_FAILED_TO_MAKE_VARIABLE
ER_STARTING_REPLICA_MONITOR_IO_THREAD error code, 127	TRANSACTION, 269
ER_STARTUP error code, 28	ER_SYS_VAR_COMPONENT_FAILED_TO_PARSE_VARIABLE
ER_STATEMENT_NOT_ALLOWED_AFTER_START_TRANSACTION error code, 123	error code, 269
ER_STD_BAD_ALLOC_ERROR error code, 62	ER_SYS_VAR_COMPONENT_OOM error code, 268
ER_STD_DOMAIN_ERROR error code, 62	ER_SYS_VAR_COMPONENT_UNKNOWN_VARIABLE_TYPE
ER_STD_INVALID_ARGUMENT error code, 63	error code, 269
ER_STD_LENGTH_ERROR error code, 62	ER_SYS_VAR_COMPONENT_VARIABLE_SET_READ_ONLY
ER_STD_LOGIC_ERROR error code, 63	error code, 269
ER_STD_OUT_OF_RANGE_ERROR error code, 63	ER_SYS_VAR_NOT_FOUND error code, 462
ER_STD_OVERFLOW_ERROR error code, 63	ER_TABLEACCESS_DENIED_ERROR error code, 12
ER_STD_RANGE_ERROR error code, 63	ER_TABLENAME_NOT_ALLOWED_HERE error code, 19
ER_STD_REGEX_ERROR error code, 110	ER_TABLESPACE_AUTO_EXTEND_ERROR error
ER_STD_RUNTIME_ERROR error code, 63	code, 35
ER_STD_UNDERFLOW_ERROR error code, 63	ER_TABLESPACE_CANNOT_BE_DECRYPTED error
ER_STD_UNKNOWN_EXCEPTION error code, 63	code, 107
ER_STMT_CACHE_FULL error code, 46	ER_TABLESPACE_CANNOT_BE_ENCRYPTED error
ER_STMT_HAS_NO_OPEN_CURSOR error code, 29	code, 107
ER_STMT_NOT_ALLOWED_IN_SF_OR_TRG error code, 24	ER_TABLESPACE_CANNOT_ENCRYPT error code,
ER_STOP_REPLICA_MONITOR_IO_THREAD_TIMEOUT error code, 127	73
ER_STOP_SLAVE_IO_THREAD_DISK_SPACE error code, 269	ER_TABLESPACE_DISCARDED error code, 53
ER_STOP_SLAVE_IO_THREAD_TIMEOUT error code, 58	ER_TABLESPACE_DUP_FILENAME error code, 83
ER_STORAGE_ENGINE_NOT_LOADED error code, 59	ER_TABLESPACE_ENGINE_MISMATCH error code,
ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_DIRECT error code, 44	87
ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_FORMATS_DIFFERENT_METADATA error code, 48	ER_TABLESPACE_EXISTS error code, 53
ER_STORED_FUNCTION_PREVENTS_SWITCH_SQL_LOG_BUNDLE error code, 45	ER_TABLESPACE_IS_NOT_EMPTY error code, 68
ER_SUBPARTITION_ERROR error code, 34	ER_TABLESPACE_MISSING error code, 53
ER_SUBPARTITION_NAME error code, 41	ER_TABLESPACE_MISSING_WITH_NAME error
ER_SUBQUERY_NO_1_ROW error code, 18	code, 108
	ER_TABLE_CANT_HANDLE_AUTO_INCREMENT
	LOG_BUNDLE, 14
	ER_TABLE_CANT_HANDLE_BLOB error code, 14
	ER_TABLE_CANT_HANDLE_FT error code, 17
	ER_TABLE_CANT_HANDLE_SPKEYS error code, 31
	ER_TABLE_CHECK_INTACT error code, 151
	ER_TABLE_CORRUPT error code, 58

ER_TABLE_CREATED_WITH_DIFFERENT_VERSION error code, 167
ER_TABLE_DEF_CHANGED error code, 28
ER_TABLE_EXISTS_ERROR error code, 6
ER_TABLE_HAS_NO_FT error code, 50
ER_TABLE_INCOMPATIBLE_DECIMAL_FIELD error code, 166
ER_TABLE_INCOMPATIBLE_YEAR_FIELD error code, 166
ER_TABLE_IN_FK_CHECK error code, 47
ER_TABLE_IN_SYSTEM_TABLESPACE error code, 53
ER_TABLE_MUST_HAVE_A_VISIBLE_COLUMN error code, 129
ER_TABLE_MUST_HAVE_COLUMNS error code, 10
ER_TABLE_NAME error code, 41
ER_TABLE_NAME_CAUSES_TOO_LONG_PATH error code, 116
ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED error code, 498
ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED error code, 498
ER_TABLE_NEEDS_DUMP_UPGRADE error code, 250
ER_TABLE_NEEDS_REBUILD error code, 46
ER_TABLE_NEEDS_UPGRADE error code, 31
ER_TABLE_NOT_LOCKED error code, 10
ER_TABLE_NOT_LOCKED_FOR_WRITE error code, 9
ER_TABLE_REFERENCED error code, 73
ER_TABLE_SCHEMA_MISMATCH error code, 53
ER_TABLE_UPGRADE_REQUIRED error code, 232
ER_TABLE_VALUE_CONSTRUCTOR_CANNOT_HAVE_DEFAULT error code, 119
ER_TABLE_VALUE_CONSTRUCTOR_MUST_HAVE_COLUMN error code, 119
ER_TABLE_WITHOUT_PK error code, 98
ER_TABLE_WRONG_KEY_DEFINITION error code, 167
ER_TARGET_TABLESPACE_UNENCRYPTED error code, 108
ER_TARGET_TS_UNENCRYPTED error code, 463
ER_TC_BAD_MAGIC_IN_TC_LOG error code, 187
ER_TC_CANT_AUTO_RECOVER_WITH_TC_HEURISTIC error code, 186
ER_TC_HEURISTIC_RECOVERY_FAILED error code, 187
ER_TC_HEURISTIC_RECOVERY_MODE error code, 187
ER_TC_NEED_N_SE_SUPPORTING_2PC_FOR_RECOVERY error code, 187
ER_TC_RECOVERING_AFTER_CRASH_USING error code, 186
ER_TC_RECOVERY_FAILED_THESE_ARE_YOUR_OPTIONS error code, 187
ER_TC_RESTART_WITHOUT_TC_HEURISTIC_RECOVERY error code, 187
ER_TEMPORARY_NAME error code, 41
ER_TEMP_FILE_WRITE_FAILURE error code, 58
ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG_FOR error code, 98
ER_TEMP_TABLE_PREVENTS_SWITCH_OUT_OF_RBR error code, 37
ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG_FOR error code, 98
ER_TEXTFILE_NOT_READABLE error code, 8
ER_TF_FORBIDDEN_JOIN_TYPE error code, 90
ER_TF_MUST_HAVE_ALIAS error code, 90
ER_THE_USER_ABIDES error code, 146
ER_THREAD_HANDLING_OOM error code, 140
ER_THREAD_POOL_ALGORITHM_INVALID error code, 251
ER_THREAD_POOL_BUFFER_TOO_SMALL error code, 253
ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC_DATA error code, 252
ER_THREAD_POOL_CON_HANDLER_INIT_FAILED error code, 252
ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT error code, 253
ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT_HANDLE error code, 252
ER_THREAD_POOL_FAILED_TO_CREATE_POOL error code, 253
ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_AUTH_CODE error code, 253
ER_THREAD_POOL_INIT_FAILED error code, 252
ER_THREAD_POOL_INVALID_PRIO_KICKUP_TIMER error code, 252
ER_THREAD_POOL_INVALID_STALL_LIMIT error code, 252
ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED error code, 253
ER_THREAD_POOL_MAX_UNUSED_THREADS_INVALID error code, 252
ER_THREAD_POOL_NOT_SUPPORTED_ON_PLATFORM error code, 251
ER_THREAD_POOL_PFS_TABLES_ADD_FAILED error code, 472
ER_THREAD_POOL_PFS_TABLES_INIT_FAILED error code, 472
ER_THREAD_POOL_PLUGIN_STARTED error code, 252
ER_THREAD_POOL_RATE_LIMITED_ERROR_MSGS error code, 253
ER_THREAD_POOL_SIZE_TOO_HIGH error code, 251
ER_THREAD_POOL_SIZE_TOO_LOW error code, 251
ER_THREAD_PRIORITY_IGNORED error code, 230
ER_TLS_CONFIGURATION_REUSE error code, 506
ER_TLS_CONFIGURED_FOR_CHANNEL error code, 506
ER_TMPDIR_PATH_TOO_LONG error code, 513
ER_TOO_BIG_DISPLAYWIDTH error code, 30
ER_TOO_BIG_ENUM error code, 75

ER_TOO_BIG_FIELDLENGTH error code, 8
ER_TOO_BIG_FOR_UNCOMPRESS error code, 19
ER_TOO_BIG_PRECISION error code, 29
ER_TOO_BIG_ROWSIZE error code, 11
ER_TOO_BIG_SCALE error code, 29
ER_TOO_BIG_SELECT error code, 10
ER_TOO_BIG_SET error code, 9
ER_TOO_HIGH_LEVEL_OF_NESTING_FOR_SELECT
error code, 32
ER_TOO_LONG_BODY error code, 30
ER_TOO_LONG_FIELD_COMMENT error code, 40
ER_TOO_LONG_IDENT error code, 7
ER_TOO_LONG_INDEX_COMMENT error code, 44
ER_TOO_LONG_KEY error code, 8
ER_TOO_LONG_ROUTINE_COMMENT error code,
75
ER_TOO_LONG_SET_ENUM_VALUE error code, 75
ER_TOO_LONG_STRING error code, 14
ER_TOO_LONG_TABLESPACE_COMMENT error
code, 83
ER_TOO_LONG_TABLE_COMMENT error code, 40
ER_TOO_LONG_TABLE_PARTITION_COMMENT
error code, 52
ER_TOO_MANY_CONCURRENT_CLONES error
code, 86
ER_TOO_MANY_CONCURRENT_TRXS error code,
41
ER_TOO_MANY_FIELDS error code, 11
ER_TOO_MANY_KEYS error code, 7
ER_TOO_MANY_KEY_PARTS error code, 8
ER_TOO_MANY_PARTITIONS_ERROR error code,
33
ER_TOO_MANY_PARTITION_FUNC_FIELDS_ERROR
error code, 42
ER_TOO_MANY_ROWS error code, 14
ER_TOO_MANY_STORAGE_ENGINES error code,
156
ER_TOO_MANY_TABLES error code, 11
ER_TOO_MANY_USER_CONNECTIONS error code,
16
ER_TOO_MANY_VALUES_ERROR error code, 42
ER_TRACK_VARIABLES_BOGUS error code, 146
ER_TRANSACTION_ROLLBACK_DURING_COMMIT
error code, 66
ER_TRANSFORM_SOURCE_SRS_MISSING_TOWGS84
error code, 98
ER_TRANSFORM_SOURCE_SRS_NOT_SUPPORTED
error code, 97
ER_TRANSFORM_TARGET_SRS_MISSING_TOWGS84
error code, 98
ER_TRANSFORM_TARGET_SRS_NOT_SUPPORTED
error code, 97
ER_TRANSPORTS_WHAT_TRANSPORTS error
code, 144
ER_TRANS_CACHE_FULL error code, 15
ER_TREE_CORRUPT_2_CONSECUTIVE_RED
error code, 209
ER_TREE_CORRUPT_INCORRECT_BLACK_COUNT
error code, 209
ER_TREE_CORRUPT_PARENT_SHOULD_POINT_AT_PARE
error code, 208
ER_TREE_CORRUPT_RIGHT_IS_LEFT error code,
209
ER_TREE_CORRUPT_ROOT_SHOULD_BE_BLACK
error code, 208
ER_TRG_ALREADY_EXISTS error code, 25
ER_TRG_CANT_CHANGE_ROW error code, 26
ER_TRG_CANT_OPEN_TABLE error code, 39
ER_TRG_CANT_PARSE error code, 151
ER_TRG_CORRUPTED_FILE error code, 39
ER_TRG_CREATION_CTX_NOT_SET error code, 232
ER_TRG_DOES_NOT_EXIST error code, 25
ER_TRG_INVALID_CREATION_CTX error code, 39
ER_TRG_IN_WRONG_SCHEMA error code, 30
ER_TRG_NO_CLIENT_CHARSET error code, 138
ER_TRG_NO_CREATION_CTX error code, 39
ER_TRG_NO_DEFINER error code, 31
ER_TRG_NO SUCH_ROW_IN_TRG error code, 26
ER_TRG_ON_VIEW_OR_TEMP_TABLE error code,
26
ER_TRG_WITHOUT_DEFINER error code, 138
ER_TRG_WRONG_ORDER error code, 478
ER_TRHEAD_POOL_LOW_LEVEL_INIT_FAILED
error code, 253
ER_TRIGGER_INVALID_VALUE error code, 132
ER_TRUNCATED_WRONG_VALUE error code, 21
ER_TRUNCATED_WRONG_VALUE_FOR_FIELD
error code, 26
ER_TRUNCATE_ILLEGAL_FK error code, 45
ER_TRX_GTID_COLLECT_REJECT error code, 155
ER_TRX_WRITE_SET_OOM error code, 156
ER_TURNING_LOGGING_OFF_FOR_THE_DURATION
error code, 225
ER_TURNING_ON_PARTIAL_REVOKES error code,
482
ER_TX_EXTRACTION_ALGORITHM_FOR_BINLOG_TX_DEP
error code, 235
ER_TZ_CANT_BUILD_MKTIME_MAP error code, 169
ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE
error code, 168
ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE_ID
error code, 168
ER_TZ_CANT_OPEN_AND_LOCK_TIME_ZONE_TABLE
error code, 168
ER_TZ_ERROR_LOADING_LEAP_SECOND_TABLE
error code, 168
ER_TZ_NO_TRANSITION_TYPES_IN_TIME_ZONE
error code, 169
ER_TZ_OOM_INITIALIZING_TIME_ZONES error
code, 168
ER_TZ_OOM_LOADING_LEAP_SECOND_TABLE
error code, 168
ER_TZ_OOM_LOADING_TIME_ZONE_DESCRIPTION
error code, 169

ER_TZ_OOM_WHILE_LOADING_TIME_ZONE error code, 170	ER_UNEXPECTED_GEOMETRY_TYPE error code, 75
ER_TZ_OOM_WHILE_SETTING_TIME_ZONE error code, 170	ER_UNIQUE_KEY_NEED_ALL_FIELDS_IN_PF error code, 34
ER_TZ_TOO_MANY_LEAPS_IN_LEAP_SECOND_TABLE error code, 168	ER_UNIT_NOT_FOUND error code, 115
ER_TZ_TRANSITION_TABLE_BAD_TRANSITION_TYPE error code, 169	ER_UNKNOWN_ALTER_ALGORITHM error code, 52
ER_TZ_TRANSITION_TABLE_LOAD_ERROR error code, 169	ER_UNKNOWN_ALTER_LOCK error code, 53
ER_TZ_TRANSITION_TABLE_TOO_MANY_TRANSITIONS error code, 169	ER_UNKNOWN_AUTHID error code, 76
ER_TZ_TRANSITION_TYPE_TABLE_ABBREVIATIONS error code, 169	ER_UNKNOWN_AUTH_ID_IN_MANDATORY_ROLE error code, 237
ER_TZ_TRANSITION_TYPE_TABLE_LOAD_ERROR error code, 169	ER_UNKNOWN_CHARACTER_SET error code, 11
ER_TZ_TRANSITION_TYPE_TABLE_TYPE_TOO_LARGER UNKNOWN_ERROR_NUMBER error code, 169	ER_UNKNOWN_COLLATION error code, 20
ER_TZ_UNKNOWN_OR_ILLEGAL_DEFAULT_TIME_ZONE error code, 168	ER_UNKNOWN_COM_ERROR error code, 6
ER_UDF_ALREADY_EXISTS error code, 462	ER_UNKNOWN_ERROR error code, 10
ER_UDF_CANT_ALLOC_FOR_FUNCTION error code, 154	ER_UNKNOWN_ERROR_DETECTED_IN_SE error code, 243
ER_UDF_CANT_ALLOC_FOR_STRUCTURES error code, 154	ER_UNKNOWN_EXPLAIN_FORMAT error code, 52
ER_UDF_CANT_OPEN_FUNCTION_TABLE error code, 154	ER_UNKNOWN_KEY_CACHE error code, 21
ER_UDF_DROP_DYNAMICALLY_REGISTERED error code, 85	ER_UNKNOWN_LOCALE error code, 42
ER_UDF_ERROR error code, 74	ER_UNKNOWN_NETWORK_NAMESPACE error code, 486
ER_UDF_EXISTS error code, 11	ER_UNKNOWN_PARTITION error code, 48
ER_UDF_INVALID_ROW_IN_FUNCTION_TABLE error code, 154	ER_UNKNOWN_PROCEDURE error code, 10
ER_UDF_NO_PATHS error code, 11	ER_UNKNOWN_STMT_HANDLER error code, 18
ER_UDF_REGISTER_ERROR error code, 512	ER_UNKNOWN_STORAGE_ENGINE error code, 21
ER_UDF_REGISTER_SERVICE_ERROR error code, 512	ER_UNKNOWN_SYSTEM_VARIABLE error code, 15
ER_UDF_UNREGISTER_ERROR error code, 512	ER_UNKNOWN_TABLE error code, 10
ER_UNKNOWN_AUTH_ID_OR_ACCESS_DENIED_FOR error code, 108	ER_UNKNOWN_TABLESPACE error code, 468
ER_UNABLE_TO_BUILD_HISTOGRAM error code, 85	ER_UNKNOWN_TABLESPACE_TYPE error code, 468
ER_UNABLE_TO_COLLECT_LOG_STATUS error code, 95	ER_UNKNOWN_TABLE_IN_UPGRADE error code, 492
ER_UNABLE_TO_DROP_COLUMN_STATISTICS error code, 85	ER_UNKNOWN_TARGET_BINLOG error code, 26
ER_UNABLE_TO_RESOLVE_HOSTNAME error code, 137	ER_UNKNOWN_TIME_ZONE error code, 22
ER_UNABLE_TO_RESOLVE_IP error code, 137	ER_UNKNOWN_UNSUPPORTED_STORAGE_ENGINE error code, 139
ER_UNABLE_TO_SET_OPTION error code, 96	ER_UNKNOWN_VARIABLE_IN_PERSISTED_CONFIG_FILE error code, 462
ER_UNABLE_TO_STORE_COLUMN_STATISTICS error code, 85	ER_UNRESOLVED_HINT_NAME error code, 68
ER_UNABLE_TO_STORE_STATISTICS error code, 78	ER_UNSOLVED_TABLE_LOCK error code, 79
ER_UNABLE_TO_UPDATE_COLUMN_STATISTICS error code, 85	ER_UNSUPPORTED_LOG_ENGINE error code, 38
ER_UNDISCLOSED_PARSE_ERROR_IN_DIGEST_FN error code, 91	ER_UNSUPPORTED_ACTION_ON_DEFAULT_VAL_GENERATED error code, 101
ER_UNDO_RECORD_TOO_BIG error code, 46	ER_UNSUPPORTED_ACTION_ON_GENERATED_COLUMN error code, 67
	ER_UNSUPPORTED_ALTER_ENCRYPTION_INPLACE error code, 73
	ER_UNSUPPORTED_ALTER_INPLACE_ON_VIRTUAL_COLUMN error code, 67
	ER_UNSUPPORTED_ALTER_ONLINE_ON_VIRTUAL_COLUMN error code, 72
	ER_UNSUPPORTED_DATE error code, 143
	ER_UNSUPPORTED_ENGINE error code, 47
	ER_UNSUPPORTED_EXTENSION error code, 10
	ER_UNSUPPORTED_INDEX_ALGORITHM error code, 74
	ER_UNSUPPORTED_PS error code, 22
	ER_UNSUPPORTED_SQL_MODE error code, 114

ER_UNSUPPORTED_USE_OF_GRANT_AS error code, 108	ER_VALIDATE_PWD_FAILED_TO_GET_FLD_FROM_SECURITY_CONTEXT error code, 266
ER_UNSUPPORTED_COMPRESSED_TEMPORARY_TABLE error code, 74	ER_VALIDATE_PWD_FAILED_TO_GET_SECURITY_CONTEXT error code, 266
ER_UNTIL_COND_IGNORED error code, 21	ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE error code, 266
ER_UPDATE_GTID_PURGED_WITH_GR error code, 116	ER_VALIDATE_PWD_LENGTH_CHANGED error code, 266
ER_UPDATE_INFO error code, 12	ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED error code, 331
ER_UPDATE_LOG_DEPRECATED_IGNORED error code, 23	ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED error code, 332
ER_UPDATE_LOG_DEPRECATED_TRANSLATED error code, 23	ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED error code, 332
ER_UPDATE_TABLE_USED error code, 9	ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED error code, 332
ER_UPDATE_WITHOUT_KEY_IN_SAFE_MODE error code, 14	ER_VALIDATE_PWD_STRING_HANDLER_MEM_ALLOCATION_FAILED error code, 332
ER_UPDATING_DD_TABLE error code, 75	ER_VALIDATE_PWD_STRONG_POLICY_DICT_FILE_UNSPECIFIED error code, 332
ER_UPGRADE_NONEXISTENT_SCHEMA error code, 513	ER_VALIDATE_PWD_VARIABLE_REGISTRATION_FAILED error code, 332
ER_UPGRADE_PARSE_ERROR error code, 467	ER_VALIDATE_PWD_VARIABLE_UNREGISTRATION_FAILED error code, 332
ER_UPGRADE_WITH_PARTITIONED_TABLES_REJECTED error code, 493	BROKEN_BLOB_PASSWORD_LOCK
ER_USERNAME error code, 32	ER_VALUES_IS_NOT_INT_TYPE_ERROR error code, 45
ER_USERNAME_TRUNCATED error code, 507	ER_VARIABLE_IS_NOT_STRUCT error code, 20
ER_USER_ACCESS_DENIED_FOR_USER_ACCOUNT error code, 120	ER_VARIABLE_IS_READONLY error code, 40
ER_USER_ALREADY_EXISTS error code, 71	ER_VARIABLE_NOT_PERSISTED error code, 78
ER_USER_COLUMN_OLD_LENGTH error code, 73	ER_VARIABLE_NOT_SETTABLE_IN_SF_OR_TRIGGER error code, 50
ER_USER_DOES_NOT_EXIST error code, 71	ER_INCOMPATIBLE_NOT_SETTABLE_IN_SP error code, 55
ER_USER_LIMIT_REACHED error code, 17	ER_VARIABLE_NOT_SETTABLE_IN_TRANSACTION error code, 50
ER_USER_LOCK_DEADLOCK error code, 63	ER_VAR_CANT_BE_READ error code, 18
ER_USER_LOCK_WRONG_NAME error code, 63	ER_VAR_DOES_NOT_EXIST error code, 84
ER_USER_NOT_IN_EXTRA_USERS_BINLOG_POSSIBLY_INCOMPATIBLE error code, 165	ACTIVATE_INACTIVE_LOCAL_ORIGINAL_ID
ER_USER_REFERENCED_AS_DEFINER error code, 126	ER_VERBOSEQUIRES_HELP error code, 140
ER_USER_REQUIRES_ROOT error code, 144	ER_VIEW_CHECKSUM error code, 27
ER_USER_WHAT_USER error code, 144	ER_VIEW_CHECK_FAILED error code, 26
ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTION_INCOMPATIBLE error code, 128	ER_VIEW_CREATION_CTX_NOT_SET error code, 232
ER_UUID_INVALID error code, 139	ER_VIEW_DELETE_MERGE_VIEW error code, 27
ER_UUID_IS error code, 139	ER_VIEW_FRM_NO_USER error code, 30
ER_UUID_SALT error code, 139	ER_VIEW_INVALID error code, 25
ER_UUID_SCRUB error code, 139	ER_VIEW_INVALID_CREATION_CTX error code, 39
ER_VALGRIND_COUNT_LEAKS error code, 153	ER_VIEW_MULTIUPDATE error code, 27
ER_VALGRIND_DO_QUICK_LEAK_CHECK error code, 153	ER_VIEW_NONUPD_CHECK error code, 26
ER_VALIDATE_PWD_CONVERT_TO_BUFFER_FAILED error code, 332	ER_VIEW_NO_CREATION_CTX error code, 39
ER_VALIDATE_PWD_COULD_BE_NULL error code, 332	ER_VIEW_NO_EXPLAIN error code, 25
ER_VALIDATE_PWD_DICT_FILE_NOT_LOADED error code, 265	ER_VIEW_NO_INSERT_FIELD_LIST error code, 27
ER_VALIDATE_PWD_DICT_FILE_NOT_SPECIFIED error code, 265	ER_VIEW_OTHER_USER error code, 30
ER_VALIDATE_PWD_DICT_FILE_OPEN_FAILED error code, 332	ER_VIEW_PREVENT_UPDATE error code, 30
ER_VALIDATE_PWD_DICT_FILE_TOO_BIG error code, 266	ER_VIEW_RECURSIVE error code, 31
	ER_VIEW_SELECT_CLAUSE error code, 25
	ER_VIEW_SELECT_TMPTABLE error code, 25
	ER_VIEW_SELECT_VARIABLE error code, 25

ER_VIEW_UNKNOWN_CHARSET_OR_COLLATION	ER_WARN_DA_PRIVILEGE_NOT_REGISTERED
error code, 133	error code, 117
ER_VIEW_UNPARSABLE error code, 167	ER_WARN_DEPRECATED_FLOAT_AUTO_INCREMENT
ER_VIEW_WRONG_LIST error code, 25	error code, 110
ER_VTOKEN_PLUGIN_TOKEN_MISMATCH error code, 69	ER_WARN_DEPRECATED_FLOAT_DIGITS error code, 110
ER_VTOKEN_PLUGIN_TOKEN_NOT_FOUND error code, 69	ER_WARN_DEPRECATED_FLOAT_UNSIGNED error code, 110
ER_WAITPID_FAILED error code, 248	ER_WARN_DEPRECATED_FOUND_ROWS error code, 121
ER_WARNING_AUTHCACHE_INVALID_USER_ATTRIBUTE error code, 474	ER_WARN_DEPRECATED_INNER_INTO error code, 121
ER_WARNING_DISCARD_OLD_PASSWORD_CLAUSE_V2ID error code, 474	ER_WARN_DEPRECATED_INTEGER_DISPLAY_WIDTH error code, 111
ER_WARNING_NOT_COMPLETE_ROLLBACK error code, 15	ER_WARN_DEPRECATED_JSON_TABLE_ON_ERROR_ON_EMP_CREATEDETEMP_TABLE
ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_CREATEDTEMP_TABLE error code, 49	ER_WARN_DEPRECATED_NESTED_COMMENT_SYNTAX
ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_DROPPEDTEMP_TABLE error code, 49	ER_WARN_DEPRECATED_SQLMODE error code, 65
ER_WARNING_PASSWORD_HISTORY_CLAUSES_VOID error code, 87	ER_WARN_DEPRECATED_SQL_CALC_FOUND_ROWS error code, 121
ER_WARNING_RETAIN_CURRENT_PASSWORD_CLAUSE_IS_DEPRECATED error code, 474	ER_WARN_DEPRECATED_SYNTAX_NO_REPLACEMENT
ER_WARN_AUDIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS error code, 131	ER_WARN_DEPRECATED_SYNTAX_WITH_VER
ER_WARN_AUDIT_LOG_MAX_SIZE_AND_PRUNE_SECONDSLOG error code, 525	ER_WARN_DEPRECATED_SYSVAR_UPDATE error
ER_WARN_AUDIT_LOG_MAX_SIZE_CLOSE_TO_ROTATEONLOG error code, 131	ER_WARN_DEPRECATED_TLS_VERSION_FOR_CHANNEL
ER_WARN_AUDIT_LOG_MAX_SIZE_CLOSE_TO_ROTATEONLOG error code, 525	ER_WARN_DEPRECATED_TLS_VERSION_FOR_CHANNEL_CLI
ER_WARN_ALLOWED_PACKET_OVERFLOWED error code, 22	ER_WARN_DEPRECATED_USER_SET_EXPR error
ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAMESPACE error code, 129	ER_WARN_DEPRECATED_UTF8MB3_CHARSET_OPTION
ER_WARN_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY8_ROLES error code, 495	ER_WARN_DEPRECATED_UTF8MB3_COLLATION
ER_WARN_BAD_MAX_EXECUTION_TIME error code, 68	error code, 102
ER_WARN_BINLOG_PARTIAL_UPDATES_DISABLED error code, 88	ER_WARN_DEPRECATED_UTF8MB3_COLLATION_OPTION
ER_WARN_BINLOG_PARTIAL_UPDATES_SUGGESTS_PARTIALIMAGES error code, 88	error code, 468
ER_WARN_BINLOG_V1_ROW_EVENTS_DISABLED error code, 88	ER_WARN_DEPRECATED_UTF8_ALIAS_OPTION
ER_WARN_CANT_DROP_DEFAULT_KEYCACHE error code, 30	error code, 121
ER_WARN_CLIENT_DEPRECATED_PARTITION_PREFIX1KEY error code, 122	ER_WARN_DEPRECATED_VALUES_FUNCTION_ALWAYS_NULL
ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFESTNOT400 error code, 518	ER_WARN_ENGINE_TRANSACTION_ROLLBACK
ER_WARN_CONFLICTING_HINT error code, 68	ER_WARN_FIELD_RESOLVED error code, 20
ER_WARN_DATA_OUT_OF_RANGE error code, 20	ER_WARN_FUNC_INDEX_NOT_APPLICABLE error
ER_WARN_DATA_OUT_OF_RANGE_FUNCTIONAL_INDEX error code, 99	code, 115
ER_WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX error code, 99	ER_WARN_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIA error code, 524
	ER_WARN_GTID_THRESHOLD_BREACH error code, 516

ER_WARN_HOSTNAME_WONT_WORK error code, 21	ER_WARN_TOO_MANY_RECORDS error code, 19
ER_WARN_HYPERGRAPH_EXPERIMENTAL error code, 125	ER_WARN_TRIGGER_DOESNT_HAVE_CREATED error code, 60
ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTIONS error code, 482	ER_WARN_UNKNOWN_KEYRING_AWS_REGION error code, 494
ER_WARN_INDEX_NOT_APPLICABLE error code, 48	ER_WARN_UNKNOWN_QB_NAME error code, 68
ER_WARN_INVALID_DB_RESTRICTIONS error code, 482	ER_WARN_UNLOAD_THE_NOT_PERSISTED error code, 77
ER_WARN_INVALID_HINT error code, 84	ER_WARN_UNSUPPORTED_HINT error code, 75
ER_WARN_INVALID_TIMESTAMP error code, 22	ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME error code, 68
ER_WARN_I_S_SKIPPED_TABLE error code, 44	ER_WARN_USING_OTHER_HANDLER error code, 20
ER_WARN_LEGACY_SYNTAX_CONVERTED error code, 59	ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED error code, 125
ER_WARN_LOG_DEPRECATED_PARTITION_PREFIX error code, 504	ER_WARN_VIEW_MERGE error code, 25
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPT error code, 494	ER_WARN_VIEW_WITHOUT_KEY error code, 25
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST error code, 494	ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOG error code, 494
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_NEEDS_ERP_WRONG_LEVEL error code, 495	ER_WARN_WRONG_COMPRESSION_LEVEL_LOG error code, 494
ER_WARN_NO_KEYRING_COMPONENT_SERVICE_FOUND error code, 518	ER_WILDCARD_NOT_ALLOWED_FOR_MULTIADDRESS_BINDING error code, 486
ER_WARN_NO_SERVERID_SPECIFIED error code, 231	ER_WINDOW_CIRCULARITY_IN_WINDOW_GRAPH error code, 80
ER_WARN_NULL_TO_NOTNULL error code, 20	ER_WINDOW_DUPLICATE_NAME error code, 82
ER_WARN_ONLY_MASTER_LOG_FILE_NO_POS error code, 61	ER_WINDOW_EXPLAIN_JSON error code, 82
ER_WARN_ON MODIFYING_GTID_EXECUTED_TABLE error code, 69	ER_WINDOW_FRAME_END_ILLEGAL error code, 81
ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO error code, 61	ER_WINDOW_FRAME_ILLEGAL error code, 81
ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR error code, 68	ER_WINDOW_FRAME_START_ILLEGAL error code, 81
ER_WARN_PARTIAL_REVOKE_AND_DB_GRANT error code, 482	ER_WINDOW_FUNCTION_IGNORES_FRAME error code, 83
ER_WARN_PROPERTY_STRING_PARSE_FAILED error code, 477	ER_WINDOW_ILLEGAL_ORDER_BY error code, 82
ER_WARN_PURGE_LOG_IN_USE error code, 57	ER_WINDOW_INVALID_WINDOW_FUNC_ALIAS_USE error code, 82
ER_WARN_PURGE_LOG_IS_ACTIVE error code, 57	ER_WINDOW_INVALID_WINDOW_FUNC_USE error code, 82
ER_WARN_QC_RESIZE error code, 21	ER_WINDOW_INVALID_WINDOW_FUNC_USE_IN_WINDOW error code, 82
ER_WARN_REMOVED_SQL_MODE error code, 469	ER_WINDOW_NO_CHILD_PARTITIONING error code, 81
ER_WARN_REPLICA_ANONYMOUS_TO_GTID_UUID SAMEWINDOWNOGROUPORDER_UNUSED error code, 524	ER_WINDOW_NO_GROUP_ORDER error code, 82
ER_WARN_RESERVED_SRID_RANGE error code, 95	ER_WINDOW_NO_INHERIT_FRAME error code, 81
ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROMMASTER_NOREDEFINE_ORDER_BY error code, 496	ER_WINDOW_NO_REDEFINE_ORDER_BY error code, 81
ER_WARN_SQL_AFTER_MTS_GAPS_GAP_NOT_CALCULATED error code, 131	ER_WINDOW_NO SUCH_WINDOW error code, 80
ER_WARN_SRS_ID_ALREADY_EXISTS error code, 94	ER_WINDOW_RANGE_BOUND_NOT_CONSTANT error code, 82
ER_WARN_SRS_NOT_FOUND error code, 75	ER_WINDOW_RANGE_FRAME_NUMERIC_TYPE error code, 81
ER_WARN_SRS_NOT_FOUND_AXIS_ORDER error code, 79	ER_WINDOW_RANGE_FRAME_ORDER_TYPE error code, 81
ER_WARN_TLS_CHANNEL_INITIALIZATION_ERROR error code, 505	ER_WINDOW_RANGE_FRAME_TEMPORAL_TYPE error code, 81
ER_WARN_TOO_FEW_RECORDS error code, 19	ER_WINDOW_ROWS_INTERVAL_USE error code, 82

ER_WINDOW_SE_NOT_ACCEPTABLE error code, 83
ER_WIN_LISTEN_BUT_HOW error code, 145
ER_WIN_LOAD_LIBRARY_FAILED error code, 247
ER_WL9236_NOW_UNUSED error code, 83
ER_WRITABLE_CONFIG_REMOVED error code, 142
ER_WRITE_ROW_TO_PARTITION_FAILED error code, 237
ER_WRITE_SET_EXCEEDS_LIMIT error code, 74
ER_WRONG_ARGUMENTS error code, 16
ER_WRONG_AUTO_KEY error code, 8
ER_WRONG_COLUMN_NAME error code, 14
ER_WRONG_COMPRESSION_ALGORITHM_CLIENT error code, 117
ER_WRONG_COMPRESSION_LEVEL_CLIENT error code, 117
ER_WRONG_COUNT_FOR_KEY error code, 209
ER_WRONG_COUNT_FOR_ORIGIN error code, 209
ER_WRONG_COUNT_OF_ELEMENTS error code, 209
ER_WRONG_DATETIME_SPEC error code, 142
ER_WRONG_DB_NAME error code, 10
ER_WRONG_EXPR_IN_PARTITION_FUNC_ERROR error code, 33
ER_WRONG_FIELD_SPEC error code, 7
ER_WRONG_FIELD_TERMINATORS error code, 8
ER_WRONG_FIELD_WITH_GROUP error code, 7
ER_WRONG_FIELD_WITH_GROUP_V2 error code, 65
ER_WRONG_FILE_NAME error code, 68
ER_WRONG_FK_DEF error code, 18
ER_WRONG_FK_OPTION_FOR_GENERATED_COLUMN error code, 67
ER_WRONG_GROUP_FIELD error code, 7
ER_WRONG_JSON_TABLE_VALUE error code, 90
ER_WRONG_KEY_COLUMN error code, 14
ER_WRONG_KEY_COLUMN_FUNCTIONAL_INDEX error code, 100
ER_WRONG_LOCK_OF_SYSTEM_TABLE error code, 29
ER_WRONG_MRGR_TABLE error code, 14
ER_WRONG_MVI_VALUE error code, 115
ER_WRONG_NAME_FOR_CATALOG error code, 21
ER_WRONG_NAME_FOR_INDEX error code, 21
ER_WRONG_NATIVE_TABLE_STRUCTURE error code, 44
ER_WRONG_NUMBER_OF_COLUMNS_IN_SELECT error code, 17
ER_WRONG_OBJECT error code, 25
ER_WRONG_OUTER_JOIN error code, 11
ER_WRONG_OUTER_JOIN_UNUSED error code, 11
ER_WRONG_PARAMCOUNT_TO_NATIVE_FCT error code, 38
ER_WRONG_PARAMCOUNT_TO_PROCEDURE error code, 10
ER_WRONG_PARAMETERS_TO_NATIVE_FCT error code, 38
ER_WRONG_PARAMETERS_TO_PROCEDURE error code, 10
ER_WRONG_PARAMETERS_TO_STORED_FCT error code, 38
ER_WRONG_PARTITION_NAME error code, 37
ER_WRONG_PERFSCHEMA_USAGE error code, 44
ER_WRONG_SIZE_NUMBER error code, 35
ER_WRONG_SPVAR_TYPE_IN_LIMIT error code, 45
ER_WRONG_SRID_FOR_COLUMN error code, 87
ER_WRONG_STRING_LENGTH error code, 32
ER_WRONG_SUB_KEY error code, 9
ER_WRONG_SUM_SELECT error code, 7
ER_WRONG_TABLESPACE_NAME error code, 68
ER_WRONG_TABLE_NAME error code, 10
ER_WRONG_TYPE_COLUMN_VALUE_ERROR error code, 42
ER_WRONG_TYPE_FOR_COLUMN_PREFIX_IDX_FLD error code, 246
ER_WRONG_TYPE_FOR_VAR error code, 18
ER_WRONG_USAGE error code, 17
ER_WRONG_VALUE error code, 35
ER_WRONG_VALUE_COUNT error code, 7
ER_WRONG_VALUE_COUNT_ON_ROW error code, 12
ER_WRONG_VALUE_FOR_TYPE error code, 28
ER_WRONG_VALUE_FOR_VAR error code, 18
ER_WRONG_VALUE_FOR_VAR_PLUS_ACTIONABLE_PART error code, 123
ER_X509_CANT_CHMOD_KEY error code, 161
ER_X509_CANT_CREATE_CERT error code, 161
ER_X509_CANT_READ_CA_CERT error code, 161
ER_X509_CANT_READ_CA_KEY error code, 161
ER_X509_CANT_WRITE_CERT error code, 161
ER_X509_CANT_WRITE_KEY error code, 161
ER_X509_CIPHERS_MISMATCH error code, 161
ER_X509_ISSUER_MISMATCH error code, 161
ER_X509_NEEDS_RSA_PRIVKEY error code, 161
ER_X509_SUBJECT_MISMATCH error code, 161
ER_XAER_DUPID error code, 30
ER_XAER_INVAL error code, 27
ER_XAER_NOTA error code, 27
ER_XAER_OUTSIDE error code, 27
ER_XAER_RMERR error code, 28
ER_XAER_RMFAL error code, 27
ER_XA_CANT_CREATE_MDL_BACKUP error code, 492
ER_XA_COMMITTING_XID error code, 154
ER_XA_IGNORING_XID error code, 154
ER_XA_NO_MULTI_2PC_HEURISTIC_RECOVER error code, 155
ER_XA_RBDEADLOCK error code, 39
ER_XA_RBROLLBACK error code, 28
ER_XA_RBTIMEOUT error code, 39
ER_XA_RECOVERY_DONE error code, 155
ER_XA_RECOVER_EXPLANATION error code, 155
ER_XA_RECOVER_FOUND_TRX_IN_SE error code, 154
ER_XA_RECOVER_FOUND_XA_TRX error code, 154
ER_XA_REPLICATION_FILTERS error code, 114
ER_XA_RETRY error code, 73

ER_XA_ROLLING_BACK_XID error code, 154	ER_XPLUGIN_FAILED_TO_OPEN_INTERNAL_SESSION error code, 277
ER_XA_STARTING_RECOVERY error code, 154	ER_XPLUGIN_FAILED_TO_PREPARE_IO_INTERFACES error code, 271
ER_XPLUGIN_ALL_IO_INTERFACES_DISABLED error code, 274	ER_XPLUGIN_FAILED_TO_RESET_IPV6_V6ONLY_FLAG error code, 278
ER_XPLUGIN_BUFFER_PAGE_ALLOC_FAILED error code, 271	ER_XPLUGIN_FAILED_TO_SCHEDULE_CLIENT error code, 271
ER_XPLUGIN_CAPABILITY_CLIENT_INTERACTIVE_FAILED error code, 278	ER_XPLUGIN_FAILED_TO_SET_MIN_NUMBER_OF_WORKERS error code, 273
ER_XPLUGIN_CAPABILITY_EXPIRED_PASSWORD error code, 277	ER_XPLUGIN_FAILED_TO_SET_SO_REUSEADDR_FLAG error code, 277
ER_XPLUGIN_CLIENT_KILL_MSG error code, 276	ER_XPLUGIN_FAILED_TO_STOP_SERVICES error code, 455
ER_XPLUGIN_CLIENT_RELEASE_TRIGGERED error code, 276	ER_XPLUGIN_FAILED_TO_SWITCH_CONTEXT error code, 278
ER_XPLUGIN_CLIENT_SSL_HANDSHAKE_FAILED error code, 273	ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX error code, 467
ER_XPLUGIN_CLOSING_CLIENTS_ON_SHUTDOWN error code, 274	ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX_TO_R error code, 276
ER_XPLUGIN_COMPRESSION_ERROR error code, 494	ER_XPLUGIN_FAILED_TO_UNREGISTER_UDF error code, 278
ER_XPLUGIN_DETECTED_HANGING_CLIENTS error code, 271	ER_XPLUGIN_FAILED_TO_USE_SSL_CONF error code, 267
ER_XPLUGIN_EMPTY_ADMIN_CMD error code, 277	ER_XPLUGIN_FAILED_TO_VALIDATE_ADDRESS error code, 505
ER_XPLUGIN_ERROR_MSG error code, 267	ER_XPLUGIN_FAIL_TO_GET_RESULT_DATA error code, 277
ER_XPLUGIN_ERROR_READING_SOCKET error code, 274	ER_XPLUGIN_FORCE_STOP_CLIENT error code, 271
ER_XPLUGIN_ERROR_WRITING_TO_CLIENT error code, 274	ER_XPLUGIN_GET_PEER_ADDRESS_FAILED error code, 271
ER_XPLUGIN_EXCEPTION_IN_EVENT_LOOP error code, 272	ER_XPLUGIN_INVALID_AUTH_METHOD error code, 274
ER_XPLUGIN_EXCEPTION_IN_TASK_SCHEDULER error code, 272	ER_XPLUGIN_INVALID_MSG_DURING_CLIENT_INIT error code, 274
ER_XPLUGIN_EXISTING_USER_ACCOUNT_WITH_INCOMPLETE_GRANTS error code, 275	ER_XPLUGIN_IPv6_AVAILABLE error code, 276
ER_XPLUGIN_FAILED_AT_SSL_CONF error code, 273	ER_XPLUGIN_LISTENER_SETUP_FAILED error code, 272
ER_XPLUGIN_FAILED_TO_ACCEPT_CLIENT error code, 271	ER_XPLUGIN_LISTENER_STATUS_MSG error code, 275
ER_XPLUGIN_FAILED_TO_BIND_INTERFACE_ADDRESS error code, 506	ER_XPLUGIN_LISTENER_SYS_VARIABLE_ERROR error code, 275
ER_XPLUGIN_FAILED_TO_CLOSE_SQL_SESSION error code, 276	ER_XPLUGIN_MAX_AUTH_ATTEMPTS_REACHED error code, 271
ER_XPLUGIN_FAILED_TO_CREATE_SESSION_FOR_CORNPLUGIN_LISTENER_SYS_VARIABLE_ERROR error code, 273	ER_XPLUGIN_MESSAGE_TOO_LONG error code, 273
ER_XPLUGIN_FAILED_TO_EXECUTE_ADMIN_CMD error code, 277	ER_XPLUGIN_PEER_DISCONNECTED_WHILE_READING_M error code, 274
ER_XPLUGIN_FAILED_TO_GET_CREATION_STMT error code, 277	ER_XPLUGIN_READ_FAILED_CLOSING_CONNECTION error code, 274
ER_XPLUGIN_FAILED_TO_GET_ENGINE_INFO error code, 277	ER_XPLUGIN_REFERENCE_TO_SECURE_CONN_WITH_XP error code, 267
ER_XPLUGIN_FAILED_TO_GET_SECURITY_CTX error code, 276	ER_XPLUGIN_REFERENCE_TO_USER_ACCOUNT_DOC_SE error code, 272
ER_XPLUGIN_FAILED_TO_GET_SYS_VAR error code, 277	ER_XPLUGIN_RETRYING_BIND_ON_PORT error code, 275
ER_XPLUGIN_FAILED_TO_INITIALIZE_SESSION error code, 273	
ER_XPLUGIN_FAILED_TO_INTERRUPT_SESSION error code, 276	

ER_XPLUGIN_SCHEDULER_STARTED error code, 274
ER_XPLUGIN_SCHEDULER_STOPPED error code, 275
ER_XPLUGIN_SERVER_EXITED error code, 266
ER_XPLUGIN_SERVER_EXITING error code, 266
ER_XPLUGIN_SERVER_STARTS_HANDLING_CONNECTIONS error code, 275
ER_XPLUGIN_SERVER_STOPPED_HANDLING_CONNECTIONS error code, 276
ER_XPLUGIN_SHUTDOWN_TRIGGERED error code, 275
ER_XPLUGIN_SRV_SESSION_INIT_THREAD_FAILED error code, 272
ER_XPLUGIN_SSL_HANDSHAKE_WITH_SERVER_FAILED error code, 273
ER_XPLUGIN_STARTUP_FAILED error code, 266
ER_XPLUGIN_TASK_SCHEDULING_FAILED error code, 272
ER_XPLUGIN_UNABLE_TO_ACCEPT_CONNECTION error code, 273
ER_XPLUGIN_UNABLE_TO_USE_USER_SESSION_ACCOUNT error code, 272
ER_XPLUGIN_UNEXPECTED_EXCEPTION_DISPATCHING_CMD error code, 272
ER_XPLUGIN_UNEXPECTED_MSG_DURING_AUTHENTICATION error code, 274
ER_XPLUGIN_UNINITIALIZED_MESSAGE error code, 273
ER_XPLUGIN_UNIX_SOCKET_NOT_CONFIGURED error code, 276
ER_XPLUGIN_USER_ACCOUNT_WITH_ALL_PERMISSIONS error code, 275
ER_XPLUGIN_USING_SSL_CONF_FROM_MYSQLX error code, 267
ER_XPLUGIN_USING_SSL_CONF_FROM_SERVER error code, 267
ER_XPLUGIN_USING_SSL_FOR_TLS_CONNECTION error code, 267
ER_XPLUGING_NET_STARTUP_FAILED error code, 272
ER_YES error code, 3
ER_ZLIB_Z_BUF_ERROR error code, 19
ER_ZLIB_Z_DATA_ERROR error code, 19
ER_ZLIB_Z_MEM_ERROR error code, 19

W

WARN_COND_ITEM_TRUNCATED error code, 41
WARN_DATA_TRUNCATED error code, 20
WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX error code, 99
WARN_NAMED_PIPE_ACCESS_EVERYONE error code, 59
WARN_NON_ASCII_SEPARATOR_NOT_IMPLEMENTED error code, 41
WARN_NO_MASTER_INFO error code, 40
WARN_ON_BLOCKHOLE_IN_RBR error code, 57
WARN_OPTION_BELOW_LIMIT error code, 46