

Key Ceremony — Loop Review Checklist (Automation)

A recurring, **non-custodial** review checklist that continuously attests the key-management lifecycle — the QA/Compliance **verify** lane run as an agent loop. Verify only; never mint.

Version: 1.0 Date: 2026-06-22

Companion to: KEY-MANAGEMENT-LIFECYCLE.md (§8 rotation, §9 ceremony, §10 glossary, §12 ownership)

Run mode: recurring automated review (e.g. Claude Code /loop), non-custodial - verify only

0. PURPOSE & GUARDRAIL

A recurring agent loop that **continuously attests** the key-management posture of the stack without ever touching a secret. It is the automation embodiment of the QA/Compliance *verify* lane in the Interactive Key Ceremony (KEY-MANAGEMENT-LIFECYCLE.md §9.7).

Non-custodial guardrail (hard rule). This loop **verifies by side-effect** — HTTP status, masked previews, fingerprints, file *presence*. It **never reads, prints, or stores a secret value**. Any check that would require seeing a key is **out of scope** and must be handed to the Deployment Officer (human). A finding is *reported*, never *remediated* by the loop (remediation = a privileged write = human-only, §9.1).

Cadence: daily lightweight scan; full review weekly; mandatory run after any deploy, scope change, or incident. Cadence triggers map to PMO ownership (§12.2).

Escalation routing (RACI, §12): WARN / FAIL → **Compliance Officer** (attest) + **PMO** (schedule remediation ceremony). PII-plane findings → **DPO**. Execution → **Deployment Officer**. A for residual risk → **CISO**.

1. ROTATION CADENCE COMPLIANCE (§8.1)

- ❑ **Root ADMIN_KEY** within rotation window (annual / personnel-change). — *check*: last `executed_by` rotate record date < 365d.
- ❑ **Rotatable / delegate key** within window (quarterly / team-change). — *check*: audit record date < 90d.
- ❑ **JWT_SECRET** within window (annual). — *check*: audit record date.
- ❑ **Shopify Admin token** auto-rotation healthy (not expired/stale). — *check*: `GET` a cheap authed endpoint → `200`; not `401/502`.
- ❑ No credential **past its cryptoperiod** (§10). — *check*: every key in §2 inventory has a dated rotation record.

2. AUDIT-TRAIL INTEGRITY (§9.4)

- ❑ Every ceremony since last review has **one append-only record**. — *check*: record count delta ≥ ceremony count.
- ❑ Each record carries **fingerprints only** (`sha256[:8]`), **no key values**. — *check*: grep records for anything key-shaped → must be **zero**.
- ❑ Each record names **distinct** `executed_by` vs `verified_by` (SoD, §9.7.1). — *check*: fields differ.
- ❑ `old_fp → new_fp` present and **different** for every rotate. — *check*: fingerprints not equal.
- ❑ `reason`, `overlap_window`, `consumers_updated` populated. — *check*: no empty fields.

3. EXPOSURE SCAN – `.ENV` / CLI / GIT (§9.6)

- ❑ **No real secrets in any** `.env` / `.dev.vars` committed to git. – *check*: `git log` / `git grep` for secret patterns → zero; `.dev.vars` git-ignored.
- ❑ **No secret in shell history or tool logs** from inline use. – *check*: scan for inline `Bearer` / `sk_` / `re_` / `key=` patterns → zero.
- ❑ **Cloudflare secrets are write-only** (read-back masked). – *check*: read endpoint returns `mask/(set)`, never a value.
- ❑ **Local key dotfiles** exist and are `chmod 600`. – *check*: file *presence* + perms only (never `cat`).
- ❑ No secret echoed into the **transcript/context** during this run. – *self-audit*: loop emitted zero raw values.

4. LEAST PRIVILEGE & SCOPE OF COMPROMISE (§10, §11)

- ❑ **Shopify GraphQL token** scoped to only used `read_*` / `write_*` – no unused scopes. – *check*: granted scopes vs call inventory.
- ❑ **Tenant tokens** (`crm_t_*`) are shop-scoped; none carry admin scope. – *check*: token metadata.
- ❑ **Market site tokens** stored apart from config, write-only, one-site blast radius. – *check*: `GET /admin/markets` shows `(set)` flag only.
- ❑ **GA4** `api_secret` server-side only; never shipped to the browser. – *check*: not present in any client bundle.
- ❑ No long-lived, broad token where an expiring/scoped one exists. – *check*: inventory review.

5. ROLES, SOD & OWNERSHIP (§9.7, §12)

- ❑ **Executor ≠ attester** held by distinct people this period. — *check*: audit `executed_by` vs Compliance sign-off identity.
- ❑ Every reviewed activity has **exactly one Accountable**. — *check*: RACI rows (§12.2).
- ❑ **DPO consulted** on any ceremony touching `JWT_SECRET` / `XANO_API_KEY`. — *check*: PII-plane records carry DPO approval.
- ❑ **Agent (this loop) is non-custodial** — appears only as verify/record support. — *self-audit*: no `R` / `A` write performed.

6. MIGRATION-SPECIFIC HEALTH (§11)

- ❑ **Shopify**: GraphQL Admin calls server-side only; token never client-exposed. — *check*: no token in browser/network from client.
- ❑ **Shopify**: platform token expiry/auto-rotation succeeding (no dead-refresh loop). — *check*: recent self-heal success in logs.
- ❑ **Google**: GA4 server-side `api_secret` present, write-only, rotated per schedule. — *check*: `(set)` flag + rotation date.
- ❑ **Google**: Consent Mode v2 gate intact before ad-signal credential use (EEA). — *check*: consent gate present.
- ❑ **Agentic codegen** that touched GraphQL/integrations introduced **no inline secret**. — *check*: diff scan since last review.

7. LOOP OUTPUT CONTRACT

Each run emits a single fingerprint-only summary (safe to publish):

```
date:          <UTC>

run_by:        agent:loop-review

scope:         [cadence, audit, exposure, least-priv, roles, migration]

result:        PASS | WARN | FAIL

findings:      <count> ( <n> WARN, <n> FAIL )

escalated_to:  [compliance?, pmo?, dpo?, deployment-officer?]

secrets_seen:  0                # MUST always be 0 - non-custodial invariant

next_run:      <UTC>
```

Stop conditions: any `FAIL` halts the loop and pages the routed owner (§12). The loop **never** attempts remediation — it opens a ceremony request and exits.

8. EXAMPLE `/LOOP` INVOCATION

```
/loop 1d Review docs/KEY-CEREMONY-LOOP-REVIEW.md against the live stack.

Verify by side-effect only – never read or print a secret. Emit the §7 output

contract; on any FAIL, stop and route per §12. secrets_seen must be 0.
```