SPECS · DATA COLLABORATION

CRM Sync — Clean Room Utility & Security Rules

The **Cloudflare-native clean room**: how CRM Sync joins and activates customer data under GDPR/CCPA/CPRA rules on D1, R2, and Durable Objects — privacy-safe data collaboration on the network the worker already runs on.


Version: **1.1 – Cloudflare-Native Architecture** Date: **2026-05-27** Classification: **Public · Spec**

Compliance: **GDPR Art. 6/9, CCPA §1798.140, CPRA, UK DPA 2018**

Infrastructure: **Cloudflare D1 + R2 + Durable Objects (same network as Hydrogen/Worker)**

1. What Is a Clean Room

A data clean room is a **controlled environment where two or more parties match their datasets without either party seeing the other's raw data**.


YOUR DATA
(CRM Sync)
Raw PII:
• email
• name
• phone
• address
You upload:
• SHA-256(email)
• order data
• segments
• consent proof
CLEAN ROOM
YOU CANNOT SEE THEIRS
THEY CANNOT SEE YOURS
ONLY MATCHED AGGREGATES COME OUT
THEIR DATA
(NielsenIQ / Circana / Google)
Raw PII:
• loyalty card ID
• panel member ID
• receipt data
They upload:
• SHA-256(email)
• POS data
• panel segments
• store-level $
OUTPUTS
(aggregated, non-reversible)
• Match rate: 34%
• Attribution lift: 2.3x
• Cross-channel

```
                        │    LTV: $142      │
                        │  • Segment overlap│
                        │    indices        │
                        └──────────────────┘
```

Key property: Neither party can reverse-engineer the other's raw data. Only pre-agreed aggregate statistics come out.

---

2. Why You Need One

Without a clean room, connecting D2C data to retail measurement requires sharing raw PII — which violates:

REGULATION	VIOLATION	PENALTY
GDPR Art. 6	No lawful basis for sharing raw email with third party for profiling	Up to €20M or 4% global revenue
CCPA §1798.140	"Sale" of personal information without opt-out mechanism	$7,500 per intentional violation
CPRA	Sharing for cross-context behavioral advertising without consent	$7,500 per record

A clean room makes the same matching possible **without sharing raw PII**.

---


3. Architecture: Cloudflare-Native Clean Room

CRM Sync implements a **self-hosted clean room** on Cloudflare's edge infrastructure — the same network that hosts the Shopify Hydrogen storefront (Oxygen Workers) and the CRM Sync worker. No AWS, Snowflake, or third-party clean room service required.

3.1 Why Cloudflare-Native

FACTOR	EXTERNAL CLEAN ROOM (AWS/SNOWFLAKE)	CLOUDFLARE-NATIVE
Data residency	Data leaves your infrastructure	Data stays on your Cloudflare account
Cost	AWS compute + storage per query	D1: free tier 5M reads/day; R2: free egress
Network	Cross-cloud hops (CF → AWS → CF)	Same edge network as Hydrogen + Worker
Latency	Partner-dependent setup time	Instant — same-stack queries
Control	Governed by provider's policies	You own the governance rules entirely
Multi-tenant	Separate accounts per tenant	Same D1 database, tenant-scoped queries

3.2 Component Mapping



```
│                                                                    │
└────────────────────────────────────────────────────────────────────┘
```

3.3 wrangler.toml Bindings

```
# D1 — Clean room query engine (SQLite at the edge)
[[d1_databases]]
binding = "CLEAN_ROOM_DB"
database_name = "crm-clean-room"
database_id = "..."  # Set after `wrangler d1 create crm-clean-room`

# R2 — Upload staging + audit archive (already used for analytics exports)
[[r2_buckets]]
binding = "ANALYTICS_EXPORTS"
bucket_name = "crm-analytics-exports"

# Durable Objects — Per-partner session isolation
[durable_objects]
bindings = [
  { name = "CLEAN_ROOM_SESSION", class_name = "CleanRoomSession" }
]

[[migrations]]
tag = "v1"
new_classes = ["CleanRoomSession"]
```

3.4 D1 Schema

```
-- Partner uploads (their hashed data loaded into D1 for matching)
CREATE TABLE IF NOT EXISTS partner_uploads (
  id INTEGER PRIMARY KEY AUTOINCREMENT,
  session_id TEXT NOT NULL,
  partner TEXT NOT NULL,           -- "nielseniq", "circana", "google_adh"
  hashed_email TEXT NOT NULL,
  attributes TEXT,                 -- JSON: POS data, panel segments, etc.
  uploaded_at TEXT DEFAULT (datetime('now')),
  expires_at TEXT NOT NULL,        -- Auto-delete after 90 days
  UNIQUE(session_id, partner, hashed_email)
);

-- CRM uploads (our hashed data, loaded per-session)
CREATE TABLE IF NOT EXISTS crm_uploads (
  id INTEGER PRIMARY KEY AUTOINCREMENT,
  session_id TEXT NOT NULL,
  hashed_email TEXT NOT NULL,
  segments TEXT,                   -- JSON array
  order_data TEXT,                 -- JSON: order_count_30d, order_total_30d, etc.
  channel_source TEXT,
  has_mandate INTEGER DEFAULT 0,
  consent_scope TEXT NOT NULL,
  consent_granted_at TEXT NOT NULL,
  uploaded_at TEXT DEFAULT (datetime('now')),
  UNIQUE(session_id, hashed_email)
);

-- Query results (aggregated outputs only)
```

```
CREATE TABLE IF NOT EXISTS query_results (
  id INTEGER PRIMARY KEY AUTOINCREMENT,
  session_id TEXT NOT NULL,
  query_template TEXT NOT NULL,    -- "attribution_lift", "segment_overlap", etc.
  result TEXT NOT NULL,            -- JSON: aggregated, non-PII output
  computed_at TEXT DEFAULT (datetime('now')),
  match_rate REAL,
  records_matched INTEGER,
  aggregation_threshold_met INTEGER DEFAULT 1
);


-- Indexes for performance
CREATE INDEX IF NOT EXISTS idx_partner_session ON partner_uploads(session_id);
CREATE INDEX IF NOT EXISTS idx_partner_email ON partner_uploads(hashed_email);
CREATE INDEX IF NOT EXISTS idx_crm_session ON crm_uploads(session_id);
CREATE INDEX IF NOT EXISTS idx_crm_email ON crm_uploads(hashed_email);
CREATE INDEX IF NOT EXISTS idx_partner_expires ON partner_uploads(expires_at);
```

3.5 Durable Object: CleanRoomSession

```
// Each clean room analysis runs inside an isolated Durable Object
// Partner = NielsenIQ, Circana, or Google ADH
// Session = one analysis window (e.g., "attribution_lift for May 2026")

export class CleanRoomSession implements DurableObject {
  private state: DurableObjectState;
  private env: Env;

  constructor(state: DurableObjectState, env: Env) {
    this.state = state;
    this.env = env;
  }

  async fetch(request: Request): Promise<Response> {
    const url = new URL(request.url);

    switch (url.pathname) {
      case "/init":
        return this.initSession(request);
      case "/load-crm-data":
        return this.loadCRMData(request);
      case "/load-partner-data":
        return this.loadPartnerData(request);
      case "/run-query":
        return this.runQuery(request);
      case "/status":
        return this.getStatus();
      case "/destroy":
```

```
      return this.destroySession();
    default:
      return new Response("Not found", { status: 404 });
  }
}

private async initSession(request: Request): Promise<Response> {
  const body = await request.json() as {
    partner: string;
    analysis: string;
    tenant_shop: string;
    expires_at: string;
  };

  await this.state.storage.put("session", {
    ...body,
    status: "initialized",
    created_at: new Date().toISOString(),
    crm_loaded: false,
    partner_loaded: false,
  });

  // Set alarm for auto-expiry (90 days max)
  const expiresAt = new Date(body.expires_at).getTime();
  await this.state.storage.setAlarm(expiresAt);

  return Response.json({ ok: true, status: "initialized" });
}

private async runQuery(request: Request): Promise<Response> {
```

```
    const session = await this.state.storage.get("session") as any;
    if (!session?.crm_loaded || !session?.partner_loaded) {
      return Response.json({ ok: false, error: "Both datasets must be loaded" }, { status: 400
    }

    const { template } = await request.json() as { template: string };

    // Execute pre-approved query template against D1
    const result = await executeQueryTemplate(
      this.env.CLEAN_ROOM_DB,
      session.session_id || this.state.id.toString(),
      template
    );

    // Archive result to R2
    await this.env.ANALYTICS_EXPORTS.put(
      `audit/clean-room/${new Date().getFullYear()}/${session.session_id || this.state.id}/${te
      JSON.stringify(result)
    );

    return Response.json(result);
  }

  // Auto-cleanup on alarm (TTL expired)
  async alarm(): Promise<void> {
    await this.destroySession();
  }

  private async destroySession(): Promise<Response> {
    const session = await this.state.storage.get("session") as any;
```

```
    const sessionId = session?.session_id || this.state.id.toString();

    // Delete all session data from D1
    await this.env.CLEAN_ROOM_DB.prepare(
      "DELETE FROM partner_uploads WHERE session_id = ?"
    ).bind(sessionId).run();

    await this.env.CLEAN_ROOM_DB.prepare(
      "DELETE FROM crm_uploads WHERE session_id = ?"
    ).bind(sessionId).run();

    // Log deletion in audit trail
    await this.env.ANALYTICS_EXPORTS.put(
      `audit/clean-room/deletions/${sessionId}.json`,
      JSON.stringify({
        session_id: sessionId,
        deleted_at: new Date().toISOString(),
        reason: "ttl_expired",
      })
    );

    await this.state.storage.deleteAll();
    return Response.json({ ok: true, status: "destroyed" });
  }
}
```

3.6 External Partner Integration

For partners that require **their own** clean room infrastructure (AWS Clean Rooms, Snowflake), the worker acts as a **clean room client** — uploading hashed

data to the partner's environment:

PARTNER	THEIR INFRASTRUCTURE	CRM SYNC ROLE
NielsenIQ Connect	AWS Clean Rooms / S3 drop	Upload hashed CSV to their S3; they run queries
Circana Unify	Snowflake Data Clean Rooms	Upload hashed JSON via API; they run queries
Google Ads Data Hub	BigQuery	Upload via GA4 Measurement Protocol; Google runs queries
Self-hosted	Cloudflare D1 (this spec)	Both datasets loaded into D1; we run queries

The Cloudflare-native clean room handles **self-hosted analysis**. Partner-hosted clean rooms use the existing analytics export delivery pipeline (see `ANALYTICS-EXPORT-SPEC.md`).

4. Security Rules

4.1 Data Classification

CLASSIFICATION	DEFINITION	EXAMPLES	CLEAN ROOM HANDLING
PII-Direct	Identifies a person on its own	Email, phone, name, address	**NEVER leaves your system raw.** SHA-256 hashed before any export.
PII-Indirect	Identifies when combined with other data	ZIP code, age range, gender	Allowed in clean room as attributes, not as match keys.
Pseudonymous	Hashed/tokenized identifier	SHA-256(email), CRM user_id	**This is what enters the clean room.** Still PII under GDPR.
Aggregated	Statistical, non-reversible	"34% match rate", "2.3x lift"	**This is what exits the clean room.** No longer PII.
Commercial	Business transaction data	Order total, SKU, date	Allowed in clean room, attached to pseudonymous ID.
Consent	Proof of permission	Consent record, timestamp, scope	**Must accompany every record** — proves lawful basis.

4.2 Immutable Security Rules

```
RULE 1: RAW PII NEVER LEAVES
_____________________________

No raw email, phone, name, or address is ever transmitted to any
external system, clean room, analytics platform, or partner.
All PII is hashed (SHA-256, lowercase, trimmed) before export.
This rule has NO exceptions and NO overrides.

RULE 2: CONSENT BEFORE COMPUTATION
_____________________________________

Every record entering a clean room must have a verifiable consent
record with:
  - scope: "analytics_partners" or "clean_room"
  - granted_at: timestamp
  - method: "explicit_optin" (not pre-checked, not bundled)
  - revoked_at: NULL (not revoked)
Records without consent are excluded at the Xano query level.
The worker DOES NOT filter — Xano filters at source.

RULE 3: MINIMUM NECESSARY DATA
_________________________________

Only export fields required for the specific analysis.
Customer attribution: hashed_email + order_data + utm_source
Segment overlap: hashed_email + crm_tags
Category analysis: hashed_email + SKU/UPC + quantity
NEVER export: password_hash, JWT tokens, internal IDs, session data,
              IP addresses, device fingerprints, browsing history

RULE 4: AGGREGATION THRESHOLD
```

_____

Clean room outputs must meet minimum aggregation thresholds:

- Minimum group size: 50 individuals
- No single-record outputs allowed
- Suppress any segment with < 50 members

This prevents re-identification via small-group inference.

RULE 5: NO REVERSE ENGINEERING

_____

Clean room queries are pre-approved and templated.

Ad-hoc queries that could enumerate individual records are blocked.

Query templates are reviewed by DPO before activation.

Neither party can export the matched record set — only aggregates.

RULE 6: TIME-BOUNDED ACCESS

_____

Data uploaded to a clean room expires automatically:

- Analysis window: 90 days max
- Match keys: deleted after computation
- Results: retained for 12 months (aggregates only)
- Consent revocation: triggers deletion within 72 hours

RULE 7: AUDIT EVERYTHING

_____

Every clean room operation is logged:

- Who initiated the analysis
- What data was uploaded (record count, field list, hash of dataset)
- What query was executed
- What results were returned

```
  - When data was deleted

Audit logs are immutable (R2 archive) and retained for 5 years.
```

4.3 Hashing Standard

```
// CANONICAL HASHING — used across all exports and clean room uploads
// Already implemented in worker (line 2252)

async function hashPII(value: string): Promise<string> {
  const encoder = new TextEncoder();
  const data = encoder.encode(value.toLowerCase().trim());  // normalize first
  const hash = await crypto.subtle.digest("SHA-256", data);
  return Array.from(new Uint8Array(hash))
    .map(b => b.toString(16).padStart(2, "0"))
    .join("");
}

// IMPORTANT: All parties must use the SAME normalization:
//   1. Convert to lowercase
//   2. Trim whitespace
//   3. SHA-256 hash
//   4. Hex-encode (lowercase)
//
// "John@Example.com " → "john@example.com" → SHA-256 → "a1b2c3..."
//
// If NielsenIQ uses a different normalization, match rates drop to ~0%.
// Confirm normalization spec with each partner before first upload.
```

4.4 Salting Policy

```
CLEAN ROOM EXPORTS: NO SALT
_____________________________

SHA-256 without salt. This is intentional.
Both parties must produce the same hash for the same email
to enable matching. Salt would make matching impossible.


This means SHA-256(email) is a pseudonymous identifier,
NOT an anonymized one. It is still PII under GDPR.
Consent is therefore REQUIRED (Rule 2).


INTERNAL STORAGE: SALTED
_________________________

Password hashing uses PBKDF2 with random salt (line 212).
These are NEVER exported. Only the unsalted SHA-256 email
hash is used for clean room matching.
```

---

5. Consent Architecture

5.1 New Consent Scope: `clean_room`

Added alongside existing consent scopes in `consent_records` table:

SCOPE	PURPOSE	REQUIRED FOR
`tos`	Terms of Service	Account creation
`privacy`	Privacy Policy	Account creation
`marketing`	Marketing communications	Email/SMS campaigns
`cookie`	Cookie tracking	Browser analytics
`a2a`	Agent-to-Agent commerce	UCP mandates
`ap2`	Agent-to-Person commerce	UCP agent checkout
`analytics_partners`	**Share hashed data with measurement partners**	**NielsenIQ/Circana export**
`clean_room`	**Include in privacy-safe data matching**	**Clean room computations**

5.2 Consent Collection UI

Extension Auth tab — new toggle group:

Data Sharing & Measurement

Analytics Partner Sharing

Share hashed purchase data with retail measurement partners (e.g., NielsenIQ, Circana) for aggregated market research.

Partners: [NielsenIQ] [Circana]

Privacy-Safe Data Matching (Clean Room)

Allow your hashed email to be matched against partner datasets in a secure clean room environment. No raw personal data is shared.

Your data is automatically deleted after 90 days.

5.3 Consent Verification at Export

```
-- Xano query: only export users with valid, unrevoked consent
SELECT
  u.id,
  SHA256(LOWER(TRIM(u.email))) as hashed_email,
  uc.crm_segments,
  -- order data joined separately
FROM storefront_users u
JOIN user_claims uc ON uc.user_id = u.id
JOIN consent_records cr ON cr.user_id = u.id
WHERE cr.consent_type = 'clean_room'
  AND cr.action = 'granted'
  AND cr.revoked_at IS NULL
  AND NOT EXISTS (
    -- Check for later revocation
    SELECT 1 FROM consent_records cr2
    WHERE cr2.user_id = u.id
      AND cr2.consent_type = 'clean_room'
      AND cr2.action = 'revoked'
      AND cr2.timestamp > cr.timestamp
  )
```

5.4 Consent Revocation Flow

```
User revokes clean_room consent
         │
         ▼
Worker: POST /auth/consent
  { scope: "clean_room", action: "revoked" }
         │
         ▼
Xano: INSERT consent_records
  { user_id, consent_type: "clean_room", action: "revoked", timestamp }
         │
         ├──► Future exports: user excluded (query filter)
         │
         ├──► Active clean rooms: deletion request within 72 hours
         │    POST {clean_room_provider}/api/delete
         │    { match_key: SHA-256(email) }
         │
         └──► R2 audit log: revocation recorded
```

6. Clean Room Data Flow

6.1 Export Preparation (Xano → Worker → Clean Room)

```
┌──────────────────────────────────────────────────────────────────┐
│  XANO BACKGROUND TASK: prepare_clean_room_upload                 │
│                                                                  │
│  1. Query users WHERE consent = clean_room AND NOT revoked       │
│  2. Hash all PII fields:                                         │
│     • SHA-256(lowercase(trim(email)))                            │
│     • SHA-256(phone) — if consented and available                │
│  3. Attach non-PII attributes:                                   │
│     • CRM segment tags (lifestyle, preferences)                  │
│     • Order history (UPCs, quantities, dates, totals)            │
│     • Channel source (utm_source, utm_medium)                    │
│     • UCP signals (mandate_used: true/false)                     │
│  4. Validate: ensure no raw PII in output                        │
│  5. Generate manifest:                                           │
│     • Record count                                               │
│     • Field list                                                 │
│     • SHA-256 of entire dataset (integrity check)                │
│     • Consent proof summary (count by scope, oldest grant date)  │
│  6. Insert into integration_queue (status: ready)                │
│  7. POST webhook → Worker /events/deliver                        │
│                                                                  │
└──────────────────────────────────────────────────────────────────┘
```

6.2 Upload Record Schema

```
interface CleanRoomRecord {
  // Match keys (hashed — the ONLY way to link across datasets)
  hashed_email: string;          // SHA-256 hex
  hashed_phone?: string;         // SHA-256 hex, optional

  // Attributes (non-PII, attached to match key)
  segments: string[];            // ["health_conscious", "subscriber", "high_ltv"]
  order_count_30d: number;       // Orders in last 30 days
  order_total_30d: number;       // Revenue in last 30 days
  avg_order_value: number;
  product_categories: string[];  // ["supplements", "protein", "skincare"]
  upcs_purchased: string[];      // Mapped from Shopify SKU → UPC
  channel_source: string;        // "google_ads" | "organic" | "email" | "social" | "agent_ucp"
  has_mandate: boolean;          // UCP agent mandate signal
  first_purchase_date: string;   // ISO date
  customer_lifetime_days: number;

  // Consent proof (travels with the record)
  consent_scope: string;         // "clean_room"
  consent_granted_at: string;    // ISO timestamp
  consent_method: string;        // "explicit_optin"

  // Metadata
  export_date: string;           // ISO date
  tenant_shop: string;           // Multi-tenant scoping
}

// VERIFICATION: Before upload, scan every record:
```

```
// - hashed_email matches /^[a-f0-9]{64}$/

// - No field contains "@" (email leak check)

// - No field contains a phone pattern /\d{10,}/

// - No field contains a name pattern (NER check optional)

// - consent_granted_at is a valid timestamp and is before export_date
```

6.3 PII Leak Prevention

```
// Run BEFORE any clean room upload — last line of defense

function validateCleanRoomPayload(records: CleanRoomRecord[]): { valid: boolean; violations: st
  const violations: string[] = [];

  for (let i = 0; i < records.length; i++) {
    const r = records[i];
    const prefix = `Record ${i}`;

    // Hash format check
    if (!/^[a-f0-9]{64}$/.test(r.hashed_email)) {
      violations.push(`${prefix}: hashed_email is not a valid SHA-256 hash`);
    }
    if (r.hashed_phone && !/^[a-f0-9]{64}$/.test(r.hashed_phone)) {
      violations.push(`${prefix}: hashed_phone is not a valid SHA-256 hash`);
    }

    // Scan all string fields for PII leaks
    const allStrings = JSON.stringify(r);

    // Email pattern
    if (/@[a-zA-Z0-9.-]+\.[a-zA-Z]{2,}/.test(allStrings)) {
      violations.push(`${prefix}: contains email pattern — raw PII leak`);
    }

    // Phone pattern (10+ consecutive digits)
    if (/\d{10,}/.test(allStrings.replace(/[a-f0-9]{64}/g, ""))) {  // exclude hashes
      violations.push(`${prefix}: contains phone number pattern`);
```

```
    }

    // Name-like patterns in non-segment fields
    // (segments are allowed to contain words like "health_conscious")

    // Consent check
    if (!r.consent_scope || !r.consent_granted_at) {
      violations.push(`${prefix}: missing consent proof`);
    }

    if (r.consent_granted_at > r.export_date) {
      violations.push(`${prefix}: consent granted AFTER export — temporal violation`);
    }
  }

  // Aggregation threshold — minimum 50 records
  if (records.length > 0 && records.length < 50) {
    violations.push(`Dataset has ${records.length} records — below minimum threshold of 50`);
  }

  return { valid: violations.length === 0, violations };
}

// ENFORCEMENT: If validation fails, the upload is BLOCKED.
// No override. No manual approval. Fix the data and re-run.
```

7. Clean Room Query Templates

Pre-approved queries — ad-hoc queries are **not allowed**.

Q1: Attribution Lift

Question: "Did customers who saw our Google Ad and bought D2C also buy in-store?"

```
-- Runs INSIDE the clean room (neither party sees raw data)
SELECT
  crm.channel_source,
  COUNT(DISTINCT crm.hashed_email) as crm_customers,
  COUNT(DISTINCT CASE WHEN retail.hashed_email IS NOT NULL
    THEN crm.hashed_email END) as also_bought_retail,
  ROUND(100.0 * COUNT(DISTINCT CASE WHEN retail.hashed_email IS NOT NULL
    THEN crm.hashed_email END) / COUNT(DISTINCT crm.hashed_email), 1) as match_pct,
  AVG(CASE WHEN retail.hashed_email IS NOT NULL
    THEN retail.units_sold END) as avg_retail_units
FROM crm_upload crm
LEFT JOIN retail_data retail ON crm.hashed_email = retail.hashed_email
GROUP BY crm.channel_source
HAVING COUNT(DISTINCT crm.hashed_email) >= 50  -- aggregation threshold
```

Output (what you receive):

CHANNEL_SOURCE	CRM_CUSTOMERS	ALSO_BOUGHT_RETAIL	MATCH_PCT	AVG_RETAIL_UNITS
google_ads	2,340	798	34.1%	4.2
organic	5,120	1,024	20.0%	2.8
agent_ucp	156	72	46.2%	6.1
email	890	267	30.0%	3.5

Q2: Segment Overlap

Question: "Which CRM segments have the highest retail purchase overlap?"

```
SELECT
  UNNEST(crm.segments) as segment,
  COUNT(DISTINCT crm.hashed_email) as segment_size,
  COUNT(DISTINCT CASE WHEN retail.hashed_email IS NOT NULL
    THEN crm.hashed_email END) as retail_match,
  AVG(retail.total_spend) as avg_retail_spend
FROM crm_upload crm
LEFT JOIN retail_data retail ON crm.hashed_email = retail.hashed_email
GROUP BY UNNEST(crm.segments)
HAVING COUNT(DISTINCT crm.hashed_email) >= 50
ORDER BY avg_retail_spend DESC
```

Q3: UCP Mandate Impact

Question: "Do customers who used AI agent mandates spend more in-store?"

```
SELECT
  crm.has_mandate,
  COUNT(DISTINCT crm.hashed_email) as customers,
  AVG(crm.order_total_30d) as avg_dtc_spend,
  AVG(retail.total_spend) as avg_retail_spend,
  AVG(crm.order_total_30d + COALESCE(retail.total_spend, 0)) as avg_total_spend
FROM crm_upload crm
LEFT JOIN retail_data retail ON crm.hashed_email = retail.hashed_email
GROUP BY crm.has_mandate
HAVING COUNT(DISTINCT crm.hashed_email) >= 50
```

Q4: Google Ads Offline Conversion (for import back to Google)

```
-- Output format compatible with Google Ads offline conversion import
SELECT
  crm.hashed_email,
  retail.purchase_date as conversion_date,
  retail.total_spend as conversion_value,
  'in_store_purchase' as conversion_action
FROM crm_upload crm
JOIN retail_data retail ON crm.hashed_email = retail.hashed_email
WHERE crm.channel_source = 'google_ads'
  AND retail.purchase_date BETWEEN crm.first_purchase_date
      AND DATE_ADD(crm.first_purchase_date, INTERVAL 30 DAY)
-- NOTE: This outputs hashed_email (not raw) — Google matches
-- against their own hash of the user's Google account email
```

---

8. Implementation on Existing Stack

Worker: Clean Room Session Endpoints

```
POST /admin/clean-room/session

Authorization: Bearer {ADMIN_KEY}

Body: {

  "partner": "nielseniq",           // or "circana", "google_adh", "self"

  "analysis": "attribution_lift",   // pre-approved query template

  "date_range": { "from": "2026-04-01", "to": "2026-05-27" },

  "shop": "hx-stage.myshopify.com"  // tenant scoping

}


Response: {

  "ok": true,

  "session_id": "cru_a1b2c3d4",

  "records": 4821,

  "records_excluded_no_consent": 1203,

  "pii_validation": "passed",

  "manifest_hash": "sha256:e5f6g7...",

  "destination": "d1://crm-clean-room/session/cru_a1b2c3d4",

  "expires_at": "2026-08-25T00:00:00Z"

}
```

```
POST /admin/clean-room/partner-upload

Authorization: Bearer {ADMIN_KEY}

Content-Type: application/json

Body: {

  "session_id": "cru_a1b2c3d4",

  "partner": "nielseniq",

  "records": [

    { "hashed_email": "a1b2c3...", "attributes": { "units_sold": 4, ... } }

  ]

}


Response: {

  "ok": true,

  "records_loaded": 12450,

  "session_status": "partner_loaded"

}
```

```
POST /admin/clean-room/query

Authorization: Bearer {ADMIN_KEY}

Body: {

  "session_id": "cru_a1b2c3d4",

  "template": "attribution_lift"    // pre-approved template only

}


Response: {

  "session_id": "cru_a1b2c3d4",

  "status": "completed",

  "analysis": "attribution_lift",

  "results": { ... },               // aggregated, non-PII outputs

  "computed_at": "2026-05-27T14:30:00Z",

  "match_rate": 0.341,

  "records_matched": 1644,

  "records_total": 4821,

  "aggregation_threshold_met": true

}
```

```
GET /admin/clean-room/results?session_id=cru_a1b2c3d4

Authorization: Bearer {ADMIN_KEY}


Response: {

  "session_id": "cru_a1b2c3d4",

  "status": "completed",

  "queries": [ ... ],               // all query results for this session

  "data_expires_at": "2026-08-25T00:00:00Z",

  "audit_url": "r2://audit/clean-room/2026/cru_a1b2c3d4/"

}
```

```
DELETE /admin/clean-room/session?session_id=cru_a1b2c3d4

Authorization: Bearer {ADMIN_KEY}


Response: {

  "ok": true,

  "session_id": "cru_a1b2c3d4",

  "status": "destroyed",

  "records_deleted": { "crm": 4821, "partner": 12450, "results": 3 }

}
```

D1 Query Execution (replaces external clean room compute)

```
// Pre-approved query templates executed against D1
async function executeQueryTemplate(
  db: D1Database,
  sessionId: string,
  template: string
): Promise<QueryResult> {
  const queries: Record<string, string> = {
    attribution_lift: `
      SELECT
        c.channel_source,
        COUNT(DISTINCT c.hashed_email) as crm_customers,
        COUNT(DISTINCT CASE WHEN p.hashed_email IS NOT NULL
          THEN c.hashed_email END) as also_bought_retail,
        ROUND(100.0 * COUNT(DISTINCT CASE WHEN p.hashed_email IS NOT NULL
          THEN c.hashed_email END) / COUNT(DISTINCT c.hashed_email), 1) as match_pct
      FROM crm_uploads c
      LEFT JOIN partner_uploads p ON c.hashed_email = p.hashed_email
        AND c.session_id = p.session_id
      WHERE c.session_id = ?1
      GROUP BY c.channel_source
      HAVING COUNT(DISTINCT c.hashed_email) >= 50
    `,
    segment_overlap: `
      SELECT
        json_each.value as segment,
        COUNT(DISTINCT c.hashed_email) as segment_size,
        COUNT(DISTINCT CASE WHEN p.hashed_email IS NOT NULL
          THEN c.hashed_email END) as retail_match
```

```
      FROM crm_uploads c, json_each(c.segments)
      LEFT JOIN partner_uploads p ON c.hashed_email = p.hashed_email
        AND c.session_id = p.session_id
      WHERE c.session_id = ?1
      GROUP BY json_each.value
      HAVING COUNT(DISTINCT c.hashed_email) >= 50
    `,
    // ... additional templates
  };

  const sql = queries[template];
  if (!sql) throw new Error(`Unknown query template: ${template}`);

  const result = await db.prepare(sql).bind(sessionId).all();
  return {
    template,
    rows: result.results,
    aggregation_threshold_met: true,
    computed_at: new Date().toISOString(),
  };
}
```

Xano: Clean Room Preparation Task

Same pattern as analytics export — Xano does the heavy lifting:

```
1. Query users with clean_room consent (unrevoked)
2. Join order data, CRM tags, UCP mandate history
3. Map Shopify SKUs → UPCs
4. Hash all PII (hashPII function — shared normalization)
5. Run PII leak validation
6. Format as JSON for D1 insert (self-hosted) or CSV/Parquet (partner-hosted)
7. Insert into integration_queue → webhook to Worker
8. Worker loads data into D1 (self-hosted) or uploads to partner S3/API (partner-hosted)
```

---

9. Audit Trail

Every clean room operation generates an immutable audit record:

```
interface CleanRoomAuditEntry {
  audit_id: string;                    // UUID
  operation: "upload" | "query" | "result" | "delete" | "consent_revocation";
  session_id: string;
  provider: string;                    // "cloudflare_d1" | "partner_s3" | "partner_api" | "goo
  tenant_shop: string;
  initiated_by: string;               // admin key preview or "system_cron"

  // Upload details
  record_count?: number;
  fields_included?: string[];          // ["hashed_email", "segments", "order_count_30d"]
  fields_excluded?: string[];          // ["raw_email" — never included but logged as proof]
  consent_summary?: {
    total_users: number;
    consented_users: number;
    excluded_no_consent: number;
  };
  dataset_hash?: string;              // SHA-256 of entire upload — integrity proof

  // Query details
  query_template?: string;            // "attribution_lift" — only pre-approved templates

  // Result details
  match_rate?: number;
  aggregation_threshold_met?: boolean;

  // Timing
  timestamp: string;
  data_expires_at?: string;
```

```
  // Compliance
  legal_basis: string;                // "consent" — Art. 6(1)(a) GDPR
  dpo_approved_template: boolean;
}

// Storage: R2 archive (immutable, 5-year retention)
// Path: audit/clean-room/{year}/{month}/{audit_id}.json
```

10. Stakeholder Access

CAPABILITY	A (CREATOR)	B (SHARED)	C (PRIVATE)
Configure clean room provider	✓	×	✓ Own account
Trigger upload	✓	×	✓
View results	✓	×	✓
Approve query templates	✓ (DPO role)	×	✓ (their DPO)
Manage consent toggles	✓ Extension	✓ Extension	✓ Extension
View audit trail	✓	×	✓
Delete clean room data	✓	×	✓
Consent revocation propagation	✓ Auto	✓ Auto	✓ Auto

11. Security Incident Response

Scenario: Clean room data breach at partner

```
1. IMMEDIATE (0-1 hours)
   ├─ Revoke partner API credentials (KV delete)
   ├─ DELETE FROM partner_uploads / crm_uploads WHERE session involves partner
   ├─ Destroy Durable Object sessions for affected partner
   ├─ Log incident in R2 audit trail
   └─ Notify DPO

2. ASSESSMENT (1-24 hours)
   ├─ Determine what data was exposed
   ├─ Data was hashed — assess re-identification risk
   ├─ If hashed emails + other attributes could enable
   │   re-identification → treat as PII breach
   └─ Document in incident report

3. NOTIFICATION (24-72 hours)
   ├─ If GDPR applies and risk to individuals:
   │   Notify supervisory authority within 72 hours
   ├─ If high risk to individuals:
   │   Notify affected data subjects
   └─ Log notification in audit trail

4. REMEDIATION
   ├─ Review partner's security posture
   ├─ Consider partner suspension
```

```
   ├─ Review aggregation thresholds
   └─ Update DPO-approved query templates if needed
```

Scenario: User requests deletion (GDPR Art. 17)

```
1. User submits deletion request via POST /auth/delete-account
2. Worker processes account deletion (existing flow)
3. ADDITIONALLY:
   ├─ Query D1: SELECT session_id FROM crm_uploads WHERE hashed_email = ?
   ├─ For each session with matching records:
   │   DELETE FROM crm_uploads WHERE hashed_email = ? AND session_id = ?
   │   DELETE FROM partner_uploads WHERE hashed_email = ? AND session_id = ?
   ├─ For partner-hosted clean rooms:
   │   POST {partner}/api/delete-records { match_keys: [hashed_email] }
   ├─ Log all deletions in R2 audit trail
   └─ Confirm deletion within 72 hours
4. Cron cleanup: verify D1 deletion complete + partner confirmations received
```
