

Redipol RDP 05 Re-dispersible Powder Polymer

Technical Data Sheet

Characteristics

Redipol RDP 05 is a type of re-dispersible emulsion powder copolymerized with VAC/Veova/E.

Applications

Used as soft plaster for exterior walls, in exterior walls for heat preservation and insulation in flexible cement based polymer mortar products and also joint cements. Soft emulsion powder, dispersible in water. It can increase the adhesion between mortar and its substrates, improve the mechanic property and constructibility of the mortar.

Typical Properties	
Appearance	White powder, free flow
Solid Content	≥ 98.0 %
Ash Content	10 ± 2 %
Bulk Density	300~500
Avarage particle size μ m	App. 80
Viscosity of 50 % Water Solution(pa s)	0.5~2.0
PH Value	6~8
Minimum Film Forming Temperature	-1°C

Packaging

25 Kg's multi layer paper - PE bag.

Storage

Store it in cool, dry place below 30°C. Validity period of the product is 180 days.

Warning: The information contained in this document is given in good faith and based on our current knowledge. It is only an indication and is in no way binding, particularly as regards of infringement or prejudice to third parties through the use of our products. We guarantee that our products comply with its sales specifications.



Phone: +86 021 65266643 e-mail: sales@yil-long.con Fax : +86 021 65266463 Web : www.yil-long.con