

SPECIALTIES

Dry Mortars Applications

Emsland Group

Starch Based Building Material Additives





Introduction

Emsland in Dry Mortar

As a leading potato starch producer
Emsland Group has more than 20 years
of experience with dry mortar starch
additives. Our dedicated building
application center is located in
Emlichheim, the headquarters of the
Emsland Group. In Emlichheim we also



dispose of the most modern production equipment, dedicated for the production of high quality modified starch based additives for building applications.

Open innovation



Together with our customers we are constantly creating new solutions for dry mortar applications. The best condition therefore is a trusting customer partnership. We offer customers a wide range of products and services specially designed to meet their specific needs and demands.

Often this has ended in new and innovative additives for our customers. In addition we give education and training to generate the best performance for our customers. This leads to sustainable relationships, where our customers benefit continuously from Emsland Group innovative power.





Product selection guide

	Cement dry mortar		Gypsum mortars			
	Tile adhesive	Rendering mortar	Manual plaster	Machine plaster	Joint filler	Finishing plaster
Emset KH 6 Multi purpose	+++	++	+++	+	+	+
Emset KH 4 Cost effectiveness	++	++	++	+	+	+
Emset KCH 25 Low effect on cement setting	++	++	++	+	+	+
Emset MC 5 Ideal for finishing	+	+	+	+	+	+++
F 7890* Multi purpose	++	++	++	+	++	+
F 9110* Fast swelling for machine applications	+	+	++	+++	+	+

^{*} F products are currently only available for trial quantities.





Standard lime – cement render and lightweight cement render

Formulations in parts by weight:

Component	Limecement render	Lightweight cement render
Portland cement (CEM1 32.5R)	8 – 12	18 – 25
Hydrated lime	6 – 8	0 – 5
Quartzsand, 0.2 – 0.8 mm	80 – 85	
Limestonesand		60 – 75
Limestonedust		5 – 7
Expanded polystyrene / perlite		1 – 2
Starch ether (Emset KH 6)*	0.01 – 0.03	0.01 – 0.03
Hydrophobic agent	0.15 – 0.25	0.1 – 0.2
Air-entraining agent	0.015 – 0.03	0.03 – 0.05
Methyl cellulose,		
viscosity (15.000 mPa.s, unmodified)	0.08 – 0.12	0.1 – 0.12

- Very good workability
- Excellent anti sagging
- Alternative product 1: Emset KH 4
 - Less effect on cement setting
 - Good workability
 - o Good anti sagging

- Alternative product 2: Emset MC 5
 - Advised for thin layer finishes
 - o Gives very smooth mortar





Repair mortar

Component	Parts by weight
Portland cement (CEM1 32.5R)	30 – 35
Aluminate cement	0 – 5
Quartzsand, 0.2 – 0.8 mm	40 – 45
Anhydride	10 – 40
Redispersible powder	30 – 50
Starch ether (Emset KH 6)*	0.01 - 0.03
Cellulose Ether (medium viscous)	0.15 - 0.25
Cellulose fibres	0 - 0.05

- o Very good workability
- o Excellent anti sagging
- Alternative product 1: Emset KH 4
 - o Less effect on cement setting
 - o Good workability
 - o Good anti sagging





Cementitious tile adhesives

Component	Specification	Low cost tile adhesive	C1T tile adhesive	C2T tile adhesive
Portland cement	CEM 1 (42.5R)	30	25 – 30	35 – 45
Limestoneflour	< 0.1 mm		5 - 10	
Quartzsand	0 ~ 0.3 mm	70	55 – 65	55 – 65
Redispersible polymer powder	VAE based		0 – 2	1 – 3
Hydrophobic agent	Magnesium stearate		0 - 0.5	0 – 0.5
Cellulose ether	Unmodified 25,000 mPa.s	0.2	0.2 – 0.3	0.2 – 0.4
Starch ether	Emset KH 6 *	0.1	0.0.3 – 0.06	0.03 – 0.06





Tile adhesive classification:

method	C1	C1T	C2	C2T
Adhesion (EN1348)	≥ 0.5 N/mm ²	≥ 0.5 N/mm ²	≥ 1 N/mm ²	≥ 1 N/mm ²
Open time ≥ 20 Min	> 0.5 N/mm ²	≥0.5 N/mm ²	≥ 0.5 N/mm ²	≥0.5 N/mm ² ,
(EN 1346)	2 0.3 14/11111			≥ 30 Min
Sagging (EN 1308)		≤ 0.5 mm		≤ 0. 5 mm

- o Very good anti sagging
- o Excellent open time
- o Very good workability
- Alternative product 1: Emset KCH 25
 - o Low effect on cement setting
 - Good workability
 - o Good anti sagging
 - o Good open time





Gypsum, gypsum – lime, and lightweight gypsum plaster

	Gypsumplaster	Gypsum – lime	Gypsum
			Lightweight
Component		plaster	plaster
Gypsum	74 – 98	40 – 50	70 – 100
Limestone		20 – 35	
Hydrated lime	1.5 – 5	15 – 20	2 – 5
Perlite		0.3 – 0.8	3 – 5
Starch ether (Emset KH 6)*	0.02 – 0.05	0.02 - 0.05	0.03 – 0.10
Air-entraining agent	0.015 – 0.03	0.015 – 0.03	0.01 – 0.03
Setting retarder	0.025 – 0.05	0.025 - 0.04	0.025 - 0.04
Methyl cellulose,			
(viscosity 30 000 mPa.s unmodified)	0.16 – 0.23	0.16 – 0.23	0.2 – 0.24

- Very good workability
- o Excellent anti sagging
- Alternative product 1: F9110
 - Specially for spray on applications
 - Very good workability
 - o Excellent anti sagging

- Alternative product 2: Emset MC 5
 - Advised for thin layer finishing plasters
 - o Gives very smooth plaster





Gypsum based fillers

	Joint Filler	Crack Filler
Component		plaster
Gypsum	30 – 60	60 - 75
Limestone	40 - 70	25 – 40
Hydrated lime	1.5 – 5	1,5 – 5
Starch ether (Emset KH 6)*	0.02 - 0.05	0.02 - 0.05
Setting retarder	0.025 - 0.05	0.025 – 0.04
Methyl cellulose,		
(viscosity 30 000 mPa.s unmodified)	0.25 - 0.35	0.25 – 0.35
Synthetic binder		
(PVOH and/or redispersible powder)	0,5 – 1,5	0.3 - 0.5

- o Very good workability
- o Excellent anti sagging
- Alternative product 2: Emset MC 5
 - o Advised for thin layer finishing plasters
 - o Gives very smooth filler





EMSLAND GROUP

'using nature to create' – this guiding principle characterises the company philosophy behind the Emsland Group. Harvested raw materials are processed into innovative trendsetting quality products in tune with nature. The most important raw material is the potato. Starch from this crop forms the basis for the success of the Emsland Group.

With a unique and creative range of products, expertise and local service, the Emsland Group has gained a foothold in the market and is not only Germany's largest producer of potato starch, but is also a global leader in manufacturing refined starch products, proteins and fibres as well as potato flakes and granules. For many years now, alternative raw materials such as peas and beans have been included in our processing procedures. This step has formed the basis for the creation of new starches, protein and fibre products with the aim to tap into new markets.

TECHNOLOGY AND RESEARCH

The Emsland Group has specialised in processing and refining renewable raw materials. Starches and other products from potatoes, cassava, corn, peas and beans are successfully developed and produced for different applications.

Thanks to an innovative and extensive range of products, services and a lot of technical expertise, Emsland Group has been able to establish itself at a global level. In order to adapt to this position in the market and to secure it long term, the outcome of our research activity is implemented consistently. This also involves the investment in new technologies.

This way, it is possible to carry out a large part of the production according to company-own formulae and specially developed technologies. In competition which is becoming increasingly stronger, it is not only important to the client to have a reliable business associate but also one which offers creative and trendsetting product solutions.

QUALITY DIRECTIVES

The Emsland Group has made an excellent name for itself in the starch industry – not only through continuous investment in the latest technologies, but also through its qualified staff. Without the specialist competencies and dedication of each individual person in the Emsland Group, it would not be possible to assure quality or to achieve quality improvements.

In order to secure the quality requirement for the future as well, a dedicated team of staff capable of implementing expertise and identifying with the company aims is indispensable. The Emsland Group has clear quality directives and is certified. Further details can be found at www.emsland-group.de.

In the research laboratory new formulae are developed and tested. Running parallel to this, the continuity of product quality is subjected to the closest scrutiny in the quality laboratory. We only allow top-grade products to be shipped around the world. In the end, it is not only existing clients which should remain, but new clients should also be convinced of the quality of our products. Performance and service are key factors in trustworthy teamwork.

Disclaimer

All information and data in this brochure are in accordance with the best practise experiences and laboratory examinations of Emsland-Stärke GmbH and Emsland Group The indications are based on the current state of development, technology and research and should be taken as information on the products of Emsland Group, but must not be understood as promise of characteristics. Emsland Group cannot assume liability for the product information and products, as the conditions under which the stocking, treatment and processing occur are out of the control of Emsland Group.

Liability claims against Emsland Group which refer to material or immaterial damages caused by the use or disuse of the offered products and product information of Emsland Group are basically exempted, unless demonstrably intended or grossly negligent fault exists which directly caused the damage. In particular Emsland Group assumes no liability that the offered products or product information are economically utilizable, technically executable or useful or that the offered products and product information do not infringe the rights of third persons.

