ULTRALUBE® E-810

Product Description:

Ultralube® E-810 is a water based wax emulsion improving the surface qualities of aqueous overprint varnishes, printing inks, lacquers, varnishes, leather coatings and floor polishes.
Ultralube® E-810 is characterized by the hardness of the wax used.

Technical Data:

Form supplied	**: yellowish transparent liquid**
Solids type	**: HDPE wax**
Solids content	**: 35% ± 1**
pH	**: 9.0 ± 0.5**
Ionic character	**: nonionic**
Melting range	**: ~137°C**

Properties:

Ultralube® E-810 is used in:

- **parquet lacquers**
- **furniture lacquers**
- **overprint varnishes**
- **printing inks**
- **leather coatings**
- **floor polishes**

at a high degree of gloss.

Processing:

Ultralube® E-810 is stirred directly into the formulation.

Dosage:

3-8% in reference to the entire formulation

in order to increase or improve:

- **mar and scuff resistance**
- **abrasion resistance**
- **anti blocking**
- **slip**
- **dirt pick up resistance (especially floor polishes)**

Packaging:

- 120 kg drum - 1000 kg IBC - tank car

Storage / Transport:

This product is stable for at least six months at temperatures of 5°C to 25°C.

!! Keep from freezing and temperatures higher than 30°C !!

Transport Classifications:

For further information please refer to the material safety data sheet.

EEC-Labelling Requirements:

For further information please refer to the material safety data sheet.

FDA-/BfR-Regulations:

FDA : All raw materials used in Ultralube® E-810 fulfil the requirements of FDA 21, CFR 176.170 and 176.180 .

BfR : All raw materials used in Ultralube® E-810 fulfil the requirements of BfR XIV and XXXVI.

issue date: 27.01.2011
edition/supersedes: 12/10 / ML
revision: 3

keim *additec* surface GmbH
Hugo-Wagener-Straße 9
D-55481 Kirchberg/Hunsrück
Tel. +49 (0) 6763/9333 – 0
Fax +49 (0) 6763/9333 – 30

Geschäftsführer:
Helmut Keim
information@keim-additec.de
www.keim-additec.de

Steuernummer:
40/662/0185/2
USt-IdNr.:
DE 148083246

Handelsregister:
Amtsgericht
Bad Kreuznach
HRB Nr. 2440