



ORGAL® K 635 N

SA 6483

Styrene Acrylic Copolymer

1/07

INTRODUCTION

ORGAL K 635 N is an APEO, Ammonia free and formaldehyde free, low Tg, Styrene Acrylic copolymer emulsion that forms a clear, elastic and slightly tacky film when dried above 0°C. It is formulated to be compatible with cement mixtures. It has excellent adhesion, flexibility, durability and water resistance.

TYPICAL PROPERTIES

Appearance	Milky White Liquid
Solid Content % ±1	53
Viscosity (Brookfield LVI 3/60)	max.1000 cps
pH	6.0- 8.0
Tg	- 23°C

APPLICATION

ORGAL K 635 N is especially suitable for the formulation of moisture barrier coatings, roof coatings, sealants and 2 component cement based roof coating systems.

- Compatible with cement mixtures
- Water resistance
- Excellent adhesion
- Excellent flexibility

PRODUCT HANDLING - STORAGE SHELF LIFE

To ensure safe storage of this emulsion, containers should be well sealed to prevent the water evaporation and skin forming. The emulsion must be stored between 5-25°C for a maximum of 12 months and freezing must be avoided.



ORGANİK KİMYA A.Ş.
ORGANİK BUILDING
Cendere Yolu No:16
34396 Ayazağa - İstanbul - TÜRKİYE
Tel: +90 (212) 331 00 00
Fax: +90 (212) 331 00 01
E-mail: organik@organik.com.tr
Web - Site: <http://www.organik.com.tr>

Teknik bütündeki bilgi ve öneriler, güvenilir olmakla birlikte, mamüllerimizin kullanım koşulları ve metodları kontrolümüz dışında olduğundan herhangi bir garanti anlamı taşımamaktadır. Müşterilerimize, mamüllerimizin ve önerilerimizin uygunluğu saptanmadan kullanıma geçmemelerini tavsiye ederiz.

These suggestions and data are based on the information we believe to be reliable. They are offered in good faith but without guarantee as conditions and methods of use are beyond our control. We recommend that the prospective user determine the suitability of the materials before adapting them on a commercial scale.