

Fast quantification of splice junctions from RNA-seq data by *sjcount* v3.0

Dmitri D. Pervouchine*

Centre for Genomic Regulation (CRG), Barcelona, Spain

June 17, 2014

1 Synopsis

The purpose of *sjcount* is to provide a fast utility for counting splice junctions in BAM files. It is the annotation-agnostic version of *bam2ssj*. This document describes the version **v3.0** of *sjcount*. The older versions of *sjcount* (v1.0, v2.0) is also included in the package under the name *deprecated*.

2 Changes since v2.0

There has been a substantial change between v2.0 and v3.0.

1. The utility now counts and reports reads with multisplits
2. Accordingly, the output format has changed to account for multisplits
3. A simpler and more efficient data structure is now used to store and parse multisplits
4. Test routines are now added to check the quality and integrity of the output as compared to the output of a perl script with easily controlled syntax

*email: dp@crg.eu

3 Installation and usage

See README.md file for installation instructions. The program *sjcount* is used from the command line with the following keys

```
sjcount -bam bam_file [-ssj junctions_output] [-ssc boundary_output]
        [-read1 0|1] [-read2 0|1] [-unstranded] [-nbins number_of_bins]
        [-lim number_of_lines] [-quiet]
```

where

- **bam_file** is a sorted input BAM file with a header
- **junctions_output** is the output file with junction counts
- **boundary_output** is the output file with boundary counts
- **read1** 0/1, reverse complement read1 no/yes (default=no)
- **read2** 0/1, reverse complement read2 no/yes (default=no)
- **unstranded**, force strand=0
- **nbins** number of offset bins, (default=1)
- **maxnh** the max value of the NH tag, (default=none)
- **lim** stop after reading these many lines, (default=no limit)
- **quiet** – suppress verbose output **NOTE: use -quiet if you redirect stderr to a file!**

The output consists of two files. First, a tab-delimited file containing multi-split counts is produced as follows

chr1_100_200_+	1	34	1
chr1_100_200_+	1	36	1
chr1_100_200_+	1	37	6
chr1_100_200_+	1	38	3
chr1_100_200_300_400_+	2	49	1
chr1_100_400_+	1	33	1
...

where the first column contains the coordinates of the split alignment (including multi-splits, see below). The second column contains the number of splits. The third column contains the offset defined as the distance within the short read sequence of the latest split (defined below). The last column is the respective count, i.e., the number of split-mapped reads with the given combination of alignment coordinates and offset.

For instance, `chr1_100_200_+` denotes an alignment that was split once between positions 100 and 200 on the '+' strand, while `chr1_100_200_300_400_+` denotes an alignment that was split twice, first between positions 100 and 200, and then between positions 300 and 400. The coordinates are 1-based and always refer to terminal *exonic* nucleotides. The strand is denoted by '+' and '-' for stranded data or by '.' for unstranded data.

The second output is also a tab-delimited file which contains the counts of read alignments that *overlap* exon boundaries (exon boundaries are defined by splice junctions in the previous file). In this version all alignments that overlap an exon boundary by at least one nucleotide are counted (in older versions only continuous alignments were counted). This second file is optional and is needed to compute the completeness of splicing index [2, 3].

4 Method

By definition, we say that we observe a *splice junction* each time we see an 'N' symbol in the CIGAR attribute of the alignment. If the CIGAR attribute contains several N's, then we have a *multi-split* or *n-split*, where *n* is the number of N's in CIGAR. In this terms, each 1-split defines one splice junction while each *n-split* defines *n* splice junctions.

Each multi-split is counted according to the number of splits so that, for example, the alignment `chr1_100_200_300_400_500_600_+` is counted once as a 3-split, two times as a 2-split (`chr1_100_200_300_400_+` and `chr1_300_400_500_600_+`), and three times as single-split (`chr1_100_200_+`, `chr1_300_400_+`, and `chr1_500_600_+`). The positions of splits are decided entirely by the mapper which produced the alignment.

As an example, consider the multi-split alignment shown in Figure 1 below. In the output file it will be counted in three lines: in `chr1_31_52_+` as having 1 split, in `chr1_64_78_+` as having 1 split, and in `chr1_31_52_64_78_+` as having 2 splits. One may want to subset the output to regular splice junctions by requiring the second column be equal to one.

Artifacts may arise from combining counts that come from different starting

ment the counter corresponding to its offset. If the offset is larger than or equal to n_{bins} then it is set to be equal to $n_{bins} - 1$.

For example, in the default settings we have $n_{bins} = 1$. This means that the bin number will be $1 - 1 = 0$ for all supporting reads, regardless of their offset ($t = 14$ for Q1, $t = 12$ for Q2–Q4, and $t = 8$ for Q5–Q6 in Figure 2). Therefore, there is only one counter to increment, and the result will be so called "collapsed" counts. The output corresponding to Figure 2 will then be

Ref_31_52_+	1	0	6
-------------	---	---	---

By contrast, if we set n_{bins} equal to read length, there will be a separate counter for each offset and the output corresponding to Figure 2 will be

Ref_31_52_+	1	8	2
Ref_31_52_+	1	12	3
Ref_31_52_+	1	14	1

One single number is usually reported for each splice junction as an endpoint. Normally, the user wants to know how many reads aligned to a certain split regardless of the offset. This number is equal to the sum of counts for the given alignment over all values of offset. In other words, the total number of counts is obtained from offset-specific counts by aggregation using the function $f(x_1, \dots, x_n) = x_1 + \dots + x_n$.

Offset-specific counts are quite useful when aggregating by using different functions. For example, the number of *staggered* counts is the result of aggregation using $f(x_1, \dots, x_n) = \theta(x_1) + \dots + \theta(x_n)$, where $\theta(x) = 1$ for $x > 0$ and $\theta(x) = 0$ for $x \leq 0$. Another useful function is *entropy*, which is obtained from the offset-specific counts by aggregation with

$$f(x_1, \dots, x_n) = \log_2\left(\sum_{i=1}^n x_i\right) - \frac{\sum_{i=1}^n x_i \log_2(x_i)}{\sum_{i=1}^n x_i}.$$

The entropy and the number of staggered reads can be used to filter out artefactual read counts. Note that *sjcount* only reports offset-specific counts, while the aggregation is left to the user.

References

- [1] B. Kakaradov, H. Y. Xiong, L. J. Lee, N. Jojic, and B. J. Frey. Challenges in estimating percent inclusion of alternatively spliced junctions from RNA-seq data. *BMC Bioinformatics*, 13 Suppl 6:S11, 2012.

- [2] D. D. Pervouchine, D. G. Knowles, and R. Guigo. Intron-centric estimation of alternative splicing from RNA-seq data. *Bioinformatics*, 29(2):273–274, Jan 2013.
- [3] H. Tilgner, D. G. Knowles, R. Johnson, C. A. Davis, S. Chakraborty, S. Djebali, J. Curado, M. Snyder, T. R. Gingeras, and R. Guigo. Deep sequencing of subcellular RNA fractions shows splicing to be predominantly co-transcriptional in the human genome but inefficient for lncRNAs. *Genome Res.*, 22(9):1616–1625, Sep 2012.