

# Creation of timepoints and timeseries for SWITCH Mexico Model

Aldo Sayeg Pasos Trejo<sup>1,2</sup>

<sup>1</sup>*Physics Departament. Facultad de Ciencias. Universidad Nacional Autónoma de México*

<sup>2</sup>*Visiting Student Researcher for the Berkeley Energy and Climate Institute at University of California, Berkeley*

December 28, 2016

## 1 Introduction

When we are working with data that is a function of time and we want to make an analysis of the data evolution on a given period of time, it is not necessary to analyze the complete function, as the most important information of the function can be obtained by only analyzing the function in a determined set of timepoints contained in the time period. This is the Statistical theory of timepoints. The SWITCH model receives time-dependent data already organized in timepoints. In this document, we will discuss SWITCH's timepoints classification and the timepoints selection that was done for the SWITCH Mexico implementation.

## 2 SWITCH time structure

The current version of the SWITCH model groups time at 3 different levels. These levels are:

- **Investment periods:** an investment period is a set of consecutive years that describe the timescale of investment decisions. The order of magnitude of the investment periods is typically from 5 to 15 years. Investment periods are represented with a string of text, which is preferred to give information of the years in the investment period.
- **Timeseries:** subdivision of an investment period that contains a certain amount of timepoints. Each timeseries could represent a day, a month or a complete week. The number of time points in each timeseries does not have to be the same for all timeseries. Timeseries are represented with a string.
- **Timepoints:** timepoints are the smallest time division. Each timepoint normally has a duration in the order of hours. Timepoints are described by two values: a timepoint ID, that can be any kind of data, and a string called "timestamp" that has a free form. It is suggested that the timestamp of a given timepoint contains information about the timepoint, such as the date of the time point.

For a more detailed description of SWITCH's time organization, we suggest to check out the "SWITCH input description" document[?].

## 3 SWITCH Mexico timepoint creation

For the description of Mexico's electricity grid we based our selection after reviewing information contained in SWITCH master timescales document [?] and other SWITCH input repositories, such as Chile[?] and Nicaragua. As all the information regarding fuel costs and load projections is from 2016 to 2030, we selected as **investment periods** 3 equal sized (5 years) divisions of this interval. The description of this investment periods is contained in the "periods.tab" SWITCH input file located at the "Main Tabs" folder of SWITCH Mexico Github repository[?].

For the **timeseries**, we choosed that each timeseries would be 2 days of each and year. This selected days would be the day with the peak load of Mexico's electricity grid and the median load day. The string that represents each timeseries consists of the year followed by the month of the timeseries and finally a letter: "P" for peak load days and "M" for median load days.

The **timepoints** consisted of 12 days inside each day of a given timeseries. Each point represented a 2 hour period

of that day. The parity of the hours selected for each year was arbitrary for the median day and we choosed the even hours of the day. For the peak day timeseries, as we needed to include the value of the peak load as it is fundamental for the good implementation of the model, we selected the hours with the parity of the peak load hour. For example, if the peak load was at hour 15:00, we selected the odd hours for the peak load day timepoints: 1:00,3:00...,13:00,15:00,... . The timestamp asociated to each timepoint consisted on a string describing the day, month, day an hour represented by that timepoint. After creating all the time points, we sorted them by the time they represnt and assign them their ID as their position in this sorted list, beginning from 0.

We programmed a Python script to create the SWITCH input files asociated with this values. The script is called "Timepoints and timeseries creation.py" and is located at the "Loads" folder of the SWITCH Mexico Github repository, while the "timepoints.tab" and "timeseries.tab" tables containing these information are located at the "Main Tabs" folder of the same repository.[?].

### 3.1 Details of the python script

The SWITCH input tables just mentioned contain columns that are calculated in specific ways, just as the "timescales.py" document explains[?]. For example, the "scale\_to\_period" column of the "timeseries.tab" file describes the number of times a timeseries is expected to repeat itself in an investment period. For the timeseries representing the peak day of one month and year, this "scale\_to\_period" value is weighted by a factor that specifies that this timeseries represnts only one day of that month, meanwhile for the median day timeseries the factor weights this value uses the fact that the time series represents all the other days of the month. The following equations show the calculation of this factor in detail:

$$sp_{Peak} = \frac{1 \text{ timeseries}}{24 \text{ hours}} \times \frac{24 \text{ hour}}{1 \text{ day}} \times \frac{1 \text{ day}}{1 \text{ month}} \times \frac{12 \text{ Months}}{1 \text{ year}} \times \frac{5 \text{ years}}{1 \text{ periods}} \quad (1)$$

$$sp_{Median} = \frac{1 \text{ timeseries}}{24 \text{ hours}} \times \frac{24 \text{ hour}}{1 \text{ day}} \times \frac{k - 1 \text{ days}}{1 \text{ month}} \times \frac{12 \text{ Months}}{1 \text{ year}} \times \frac{5 \text{ years}}{1 \text{ periods}} \quad (2)$$

Where  $k$  is the number of days in the month of the given timeseries.

## References

- [1] SWITCH input description document.
- [2] SWITCH Chile small-input directory. <https://github.com/bmaluenda/SWITCH-Pyomo-Chile/tree/Chile/inputs-chile-small>
- [3] SWITCH master timescales document. [https://github.com/switch-model/switch/blob/master/switch\\_mod/timescales.py](https://github.com/switch-model/switch/blob/master/switch_mod/timescales.py)
- [4] SWITCH Mexico Github repository. [https://github.com/sergiocastellanos/switch\\_mexico\\_data](https://github.com/sergiocastellanos/switch_mexico_data)