

Midterm Revision:

1.Which of the following addresses is used to identify a specific device on a network?

a.	Logical Address	c.	physical Address
b.	port Address	d.	all of the above

2.Which of the following is an example of a logical address?

a.	00:1A:2B:3C:4D:5E	c.	192.168.1.1
b.	COM1	d.	80:00:20:0A:B1:2D

3.Which OSI layer is responsible for end-to-end communication and error recovery?

a.	Network Layer	c.	Application Layer
b.	Transport Layer	d.	physical Layer

4.Which address type is used to distinguish different processes running on the same machine?

a.	Physical Address	c.	port Address
b.	Logical Address	d.	netBroadcast

5.The Address Resolution Protocol (ARP) is primarily used to resolve:

a.	Port addresses to IP	c.	MAC addresses to names
b.	IP addresses to addresses	d.	Logical addresses to s

6.How many bits are there in an IPv4 address?

a.	32	c.	128
b.	64	d.	256

7.Which address type uniquely identifies a network interface on a LAN?

a.	Port Address	c.	Specific Address
b.	Logical Address	d.	Domain Address

8.What is the minimum payload size for Ethernet?

a.	46 bytes	c.	64 bytes
b.	128 bytes	d.	1518 bytes

9.The alerts the receiving system to the coming frame and enables it to synchronize its input timing

a.	CRC	c.	SFD
b.	The logical Address	d.	Preamble

10.The warns the station or stations that this is the last chance for synchronization.

a.	Source Address	c.	SFD
b.	DNS	d.	Preamble

11. which of the following addresses is considered as unicast address?

a. 4A:30:10:21:10:1A

b. 4F:30:10:21:10:1A

c. 4D:30:10:21:10:1A

d. 49:30:10:21:10:1A

12. The address which changing form hop to hop is the

.....

a. Port Address

b. Specific Address

c. Logical Address

d. physical address

13. An extended service set (ESS) is made up of

a. only one BSS with 2 APs	b. Ad hoc network
c. two or more BSS with Aps	d. only one infrastructure

14. In an Ethernet LAN frame, the minimum and maximum payload of data are.....bits.

a. 1500, 2048

b. 46, 2048

c. 64, 1024

d. 64, 1500

15. The physical Address is used at the.....

a. physical layer

b. Transport Layer

c. Network layer

d. Application layer

16. What is the major factor that makes coaxial cable less susceptible to noise than twisted pair cable?

a. inner conductor

b. diameter of cable

c. outer conductor

d. Insulating material

17. The network layer adds a header to the packet coming from the upper layer that is

- | | |
|--|----------------------------------|
| <i>a. physical address</i> | <i>b. Logical address</i> |
| <i>c. service point address</i> | <i>d. Real address</i> |

18. the frequency of failure is a measure of

- | | |
|------------------------------|-------------------------------|
| <i>a. Performance</i> | <i>b. Readability</i> |
| <i>c. Security</i> | <i>d. Availability</i> |

19. The five components of a data communication system are.....

- a. sender, receiver, transmission medium, message, and OSI.***
- b. sender, receiver, transmission medium, Protocol, and OSI.***
- c. sender, receiver, transmission medium, message, and protocol.***
- d. sender, receiver, transmission Data, OSI, and protocol.***

_____ 20. The unit of communication at the physical layer is -----

- | | |
|------------------------|--------------------------|
| <i>a. bit</i> | <i>c. packet</i> |
| <i>b. frame</i> | <i>d. message</i> |

_____ 21. In which topology, direct traffic is not allowed between device?

- | | |
|--------------------------------|--------------------------------|
| <i>a. Mesh topology</i> | <i>c. Star topology</i> |
| <i>b. Bus Topology</i> | <i>d. Ring Topology</i> |

_____ 22. The port Address is used at the

- | | |
|----------------------------------|----------------------------------|
| <i>a. physical layer</i> | <i>c. transport layer</i> |
| <i>b. data-link layer</i> | <i>d. network layer</i> |

- ____ 23. The physical Address is used at the
- a. data-link layer
 - b. transport layer
 - c. physical layer
 - d. network layer
- ____ 24. Communication between a computer and a keyboard involves _____ transmission.
- a. simplex
 - b. half-duplex
 - c. full-duplex
 - d. All of the above
- ____ 25. The port Address identifies a..... on a host
- a. protocol
 - b. process
 - c. message
 - d. None of the above
- ____ 26. The presentation layer is responsible for:
- a. translation
 - b. encryption
 - c. compression
 - d. All of the above
- ____ 27. Moving of frames from one hop to another is the responsibility of the
- a. data link layer
 - b. transport layer
 - c. physical layer
 - d. network layer
- ____ 28. Which of the following is categorized according to physical connection?
- a. star
 - b. bus
 - c. ring
 - d. any of the above
- ____ 29. Which of the following is not a physical address?
- a. 07:01:02:01:2C:DB
 - b. 07:DD1:02:01:2C:4B
 - c. CC:CC:CC:CC:CC:CC
 - d. BB:01:02:01:2C:4B
- ____ 30. The Means what is communicated, how it is communicated, and when it is communicated.
- a. isp
 - b. protocol
 - c. topolgy
 - d. communication system

____ 31. the address which changing form hop to hop is the

- a. port address
- b. specific address
- c. logical address
- d. physiacl address

____ 32. The _____ is the physical path over which a message travels.

- a. protocol
- b. medium
- c. simplex
- d. signal

____ 33. TCP/IP is only concerned with

- a. transport layer
- b. network layer
- c. Application layer
- d. All of the above

____ 34. The..... Layer is responsible for movement of individual bits from one

- a. transport layer
- b. network layer
- c. Application layer
- d. All of the above

____ 35. The network layer is responsible for delivery of individual..... from source to destination

- a. payload
- b. packets
- c. bits
- d. frames

____ 36. Delivery of message from one process to another is the responsibility of Layer

- a. datalink
- b. transportation
- c. physical
- d. networks

____ 37. performance, reliability, and security are

- a. A physical layers criterias
- b. A protocol criterias
- c. A network Criterias
- d. all of the above

____ 38. the frequency of failure is a measure of

- a. performance
- b. security
- c. reliability
- d. availability

____ 39. Keyboards and traditional monitors are examples of

- a. simplex devices
- b. protocol
- c. input devices
- d. any of the above

____ 40. connection provides a dedicated link between two devices.

- a. minimum point
- b. multi point
- c. point to point
- d. network

____ 41. a fault or break in the topology stops all transmission, even between devices on the same side of the problem.

- a. bus
- b. star
- c. mesh
- d. None of the above

____ 42. the ARP associate a relation between

- a. port address and logical address
- b. physical address and logical address
- c. SPA and physical address
- d. SPA and Port address

43. the address which changing form hop to hop is the

- a. port address**
- b. specific address**
- c. logical address**
- d. physical address**

44. The network layer is responsible for delivery of individual..... from source to destination

- a. payload**
- b. packets**
- c. bits**
- d. frames**

45. Which guided media type is most susceptible to electromagnetic interference (EMI)?

- a. Coaxial Cable**
- b. Fiber-Optic Cable**
- c. Twisted-Pair Cable**
- d. Ring Topology**

46. How many bits are there in an IPv4 address?

- a. 32**
- b. 64**
- c. 128**
- d. 256**

47. Which OSI layer is responsible for end-to-end communication and error recovery?

- a. Network Layer**
- b. Transport Layer**
- c. Application Layer**
- d. physical Layer**

48. Which address type is used to distinguish different processes running on the same machine?

- a. Physical Address**
- b. Logical Address**
- c. port Address**
- d. nonbroadcast Address**

49. Which type of cable is most commonly used in Ethernet networks?

- | | |
|------------------------------|-----------------------------|
| a. Coaxial Cable | c. Fiber-Optic Cable |
| b. Twisted-Pair Cable | d. Infrared |

50. Which transmission medium has the shortest range?

- | | |
|------------------------------|---------------------|
| a. Coaxial Cable | c. microwave |
| b. Twisted-Pair Cable | d. Infrared |

51. Which of the following is NOT affected by electrical noise?

- | | |
|------------------------------|-----------------------------|
| a. Twisted-Pair Cable | c. infrared |
| b. Coaxial Cable | d. fiber-optic cable |