

Chapter 1

Changes in Virgile's PhD

1.0.1 Type unification

Section 3.3, definition 9, page 27.

Rule [SELF1] should be: $mg(t, \mathbf{Self}, t) = \mathbf{Self}, id$

Rule [SELF2] should be: $mg(t, t, \mathbf{Self}) = \mathbf{Self}, id$

1.0.2 Normal form algorithm

Section 3.7.1, page 36.

In the algorithm, line 10 should be: $\mathbb{W}_1 \leftarrow ((\psi_{i_0} \otimes \phi), \mathbb{X})$.

In the algorithm, line 13 should be: $\mathbb{W}_2 \leftarrow (\mathbb{W}_2, \phi)$.

In the running text, page 37, line 8, the same modification must be done to get “on garde $\psi_{i_0} \otimes \phi$ dans $\mathbb{W}_1 \dots$ ”.

1.0.3 Typing rules for parametrised species

Section 3.8, figure 3.2, page 43.

Rule [COL-PRM] should be:

$$\frac{\mathcal{C}, \Omega \vdash e^S : a \quad \mathcal{C} + C : \mathcal{A}(a, C), \Omega \vdash \mathbf{species} S(prms) \mathbf{inherits} e_1^S, \dots, e_{h_f}^S = \Phi_1 \dots \Phi_n : t_S}{\mathcal{C}, \Omega \vdash \mathbf{species} S(C \text{ is } e^S, prms) \mathbf{inherits} e_1^S, \dots, e_{h_f}^S = \Phi_1 \dots \Phi_n : (C \text{ is } a)t_S}$$

1.0.4 Dependency on the carrier

Section 3.9.4, definition 28, page 50.

The definition should be: “Soit une expression e , si une sous-expression de e ~~a le type~~ **fait référence à** (“contient”) \mathbf{Self} , il y a une decl-dépendance vis-à-vis du type support.”

In English: “Let’s have e an expression, if a sub-expression of e ~~has type~~ **makes reference to** (“contains”) \mathbf{Self} , then there is a decl-dependency on the carrier”.

This is more accurate since an expression having type $\mathbf{int} \rightarrow \mathbf{Self}$ does not have type \mathbf{Self} , but when we state its type, \mathbf{Self} occurs in the type and must be bound somewhere (and the decl-dependency on the carrier is just there for this purpose).

1.0.5 Dependencies in a species

Section 3.9.5, definition 31, page 53.

Lines 3 and 4 should be:

$$\forall j < n, y_j \in \mathbb{I} y_i \mathbb{I}_S \cup \mathbb{I} y_{j+1} \mathbb{I}_S \\ x_1 <_S^{def} x_2 \hat{=} \exists \{y_i\}_{i=1 \dots n} \text{ tel que } y_1 \odot_S x_1, y_n \odot_S x_2, \forall j < n, y_j \in \mathbb{I} y_{j+1} \mathbb{I}_S$$

1.0.6 Parameters used by a method

Section 3.9.5, definition 66, page 124.

To understand the rules [BODY], [TYPE], [DEF-DEP], [UNIVERS] and [PRM], it should be stated that implicitly the parameter $C_{p'}$ has the form:

$$C_{p'} \text{ is/in } \tau_{p'}$$

1.0.7 Instanciation of species parameters

Section 3.9.5, definition 67, page 124.

Second rule should be:
$$\frac{x \uparrow S = S_h \quad \mathcal{E}(S_h) = (C_1 \cdot \tau_1, \dots, C_{p_f} \cdot \tau_{p_f}) \quad l_h = e_1 \dots e_{p_f}}{\text{Inst}_S(x) = \{\text{Inst}_{C_p}(e_p)_{C_p \in \mathcal{U}_{S_h}(x)}\}}$$

1.0.8 Translation example in OCaml

Section 8.2, page 152.

The code sample shown and the explanation about `create` at the top of the page is wrong or at least not complete. In effect, if presented this way, we don't know from where `create` comes. In fact, we must use the one coming from the species we "implement". So a qualified notation (i.e. module name + function name) is required.

1.0.9 Dependencies of a method

Section 8.3.1, definition 72, page 153.

Missing notion of order

All along the rules, dependencies are stated as a set of names. In fact this is incomplete since there can be dependencies between these names for a collection parameter. So they must be ordered according to their own dependencies (i.e. according to def-dependencies inside the hosting species that is that collection parameter).

For instance:

```
species S1 ... =
  let eq = ... ;
  theorem th1 : all x in ..., !eq (...) ...
  proof = ... ;
end ;;

species S2 (P is S1) ... =
  theorem th2 : all x in P, ...
  proof = ... property P!th1 ... ;
end ;;
```

In `S1`, `th1` decl-depends on `eq`. In `S2`, method `th2` has a dependencies on its collection parameter `P` methods. Especially, on `P!th1`, and completions rules require to add `P!eq` (in order to express the "type" of `th1`, i.e. its statement). Since in `P`, `th1` decl-depends on `eq`, when making λ -liftings to abstract `P`'s methods in the dependencies on methods of parameters in `S1`, we must ensure that `eq` is λ -filter before `th1` otherwise `eq` will be unbound in `th1`.

This order is given by the dependencies of the methods inside the species used as collection parameter.

Missing rule

The rules [DEF-DEP], [UNIVERS] and [PRM] can add dependencies on parameters after rule [BODY] and [TYPES]. However, the added methods can have decl-dependencies via their “types”. An this is not taken into account by the current set of rules. To circumvent, a new rule is added, [DIDOU] (better name to be found, but the day I thought to this rule, I was very poor in naming schemes ☺). This rule intuitively takes the all dependencies found by [BODY], [TYPES], [DEF-DEP], [UNIVERS] and [PRM] as initial set and performs a fixpoint by adding for each method of dependencies, its decl-dependencies coming from its “type” (i.e. ML-like type for computational methods, and statement for logical methods). Of course, when tracking decl-dependencies of a method, we address the method body in its species. But this species is a collection parameter. So before adding the found method to the set of dependencies on collection parameters of the analysed species, we must replace in the method, occurrences of `Self` by the by the species parameter from where this method comes.

Missing substitution in rule [PRM]

First, the rule [PRM] needs further explanations to understand its presentation. It must first be understood that in this rule, the species S has the following form:

species $S(C_p \text{ is } \dots, C_{p'} \text{ is } S'(C_p))$

Moreover, implicitly $i_{p'}$ is the interface of $C_{p'}$. And C_p is a valid implementation of the parameter C'_k (having the interface i'_k) of the species S' .

Now, the rule says:

$$\frac{i_{p'} = S'(e_1, \dots, C_p, \dots) \quad \mathcal{E}(S') = (C'_1 \cdot i'_1, \dots, C'_k \cdot i'_k, \dots) \quad y \in \text{Deps}(S', C'_k)[z] \quad z \in \text{Deps}(S, C_{p'})[x]}{y \in \text{Deps}(S, C_p)[x]}$$

This rule forget to show that we must instantiate the formal parameter of S' by the effective argument provided. In effect, in the bodies/types of the methods of S' (those methods the conclusion adds to the currently computed dependencies set), parameters are those of S' , not our current ones we use to instantiate the formal ones of S' ! To prevent those of S' to remain in the expressions and be unbound, we do the instantiation here.

Inconsistency between inherited/re-computed dependencies

When computing dependencies on collection parameters of a method, it is never clearly stated about how to compute them when the method is inherited.

One way is to compute from scratch the dependencies from the body of the inherited method. The second is to recover the inherited dependencies and to perform substitution of formal parameters of the inherited species by effective arguments used in the `inherits` species expression.

This last process is in fact very difficult due to the amount of information recorded in the parameters/methods descriptions (moreover, making severe usage of sharing).

So we really prefer to use the first method that naturally create the data-structures and information to record. The only problem is that during inheritance, some dependencies present in the original inherited species may “disappear” due to parameters instantiations.

For example:

In fact, the problem is that when we compute dependencies on collection parameters, in the case where we inherit from a species having 2 parameters instantiated by the same argument, we get into a fusion of the methods we depend on.

But, the method generator coming from the originally inherited method expects to be applied to as many arguments that *lambda*-lifting were created.

In the above example, S and T are instantiated both by G . So we get 1 dependency on $G!\text{rep}$ (the carrier) and 1 on $G!\text{equal}$ although the method generator expects 3 arguments : twice $G!\text{rep}$ and one $G!\text{equal}$ because in `Couple` was abstracted on the carrier of S , the carrier of T and $T!\text{equal}$. Because we work with sets to represent dependencies, twice $G!\text{rep}$ is $\dots 1 G!\text{rep}$. And same thing for $G!\text{equal}$.

```

species Simple =
  signature equal : Self -> Self -> bool ;
end ;;

species Couple (S is Simple, T is Simple) =
  signature morph: S -> T;
  let equiv(e1, e2) = T!equal(!morph(e1), !morph(e2));
end ;;

species Bug (G is Simple) inherits Couple (G, G) =
  theorem theo: true
  proof =
    <1>1
      prove true
      <2>f qed assumed { * * }
    <1>2 qed by definition of equiv ;
end ;;

```

We described the problem here via a dependency on the carrier, but it is the same thing with dependencies on other methods: we would just need to make `equiv` depending for instance on `S!equal` and `S!equal`.

The solution is to make a mix between the two initial solutions. First, we compute the abstractions due to dependencies on collection parameters in the body of the method once inherited. This way, we naturally let data-structures be created and sharing what they need. In fact, this gives us a “skeleton” of dependencies where some λ -liftings may have disappeared compared to the number of required in the inherited species. But, we know that all the methods involved in the dependencies are present, may be not with the right number of occurrences. Then we take the dependencies scheme of tin inherited method and we rebuild a final dependencies structure by replacing in the inherited one all the occurrences of dependencies on the formal parameter by the corresponding effective argument (used during instantiation) ones. This way, we just “remap” the computed dependencies on the inherited ones’ scheme.

In the example above, this means that we compute in `Bug` that we have dependencies on `G!rep` and `G!equal`. We look back in the inherited `Couple` dependencies, we find `S!rep`, `S!rep` and `T!equal`. So we construct the final dependencies as `S!rep[S<-G]` `S!rep[S<-G]` and `T!equal[T<-G]`

Dependencies on collection parameters for record type

Computing real dependencies on collection parameters for record type is not clearly stated. For OCaml, it is quite trivial since we don’t have any logical methods, hence we can only have dependencies via “types”. For OCaml, the situation is more tricky. In fact, due to logical methods (theorems and properties), dependencies may more complex, involving types and methods found in the expressions forming the logical statements.

The same kind of problems arises than above (missing rule): an extra rule is needed (the [DIDOU] rule), but the only difference is that since the record type only shows “types”, the initial set of dependencies to close is the one obtained by the rule [TYPE].

It is not yet formally clear that computing dependencies required by the record type is complete. Experiment seems to show that yes, but further theoretical investigations should be performed.

Taking a wider set of dependencies (for instance the same than those computed method per method, all grouped in a single big union) would lead to extra arguments (by λ -lifting) to the record type that would not be used. This is unwanted for 2 reasons: efficiency/readability of the generated code, and more importantly, the risk to have variables not bound to a type, inferred as polymorphics, and for which Coq would say that it “can’t infer a type for this placeholder”.

1.0.10 Coq code generation model

The problem

The initial Coq code generation model appeared to have a strong weakness. Moreover, it was strongly different from the OCaml one. Let’s understand the weakness on a simple example. . . The problem is:

```

species IntModel inherits Basic_object =
  representation = basics#int ;
  let one in Self = 1 ;
  let modulo (a, b) = if true then a else (if false then b else one) ;
end ;;

species Me (Naturals is IntModel, n in Naturals) =
  representation = Naturals ;

  theorem lookatme : all x in Self, basics#base_eq (n, Naturals!one)
    proof : assumed { * * } ;

  let reduce (x in Naturals) in Self = Naturals!modulo (x, n) ;
end ;;

```

The generated Coq code follows (at least, for the interesting part of our problem, i.e. the lookatme theorem):

We see that there is a Section for the species Me. The theorem lookatme is in a nested Section (Chapter is a synonym for Section in Coq).

It depends on one coming from Natural (which is a collection parameter), and on n which is an entity parameter.

Hence, naturally, we will need to abstract these 3 things (one, n and the type Natural). This really performed by the 4 Variables at the beginning of the Section lookatme. Hence, looking at the type of the **theorem generator Me__lookatme inside** the Section lookatme, we see that it has type:

since the Section is not closed, because the Variables are not yet abstracted by the Coq's Section mechanism.

We now close the Section, then naturally the **theorem generator Me__lookatme** turns having the type:

Great ! the Variables have been abstracted for us by Coq. Now, the idea is that this generator will be used to create a collection like:

Let's continue and close the Chapter (\simeq a Section) of species Me. And then, here the theorem generator Me__lookatme turns unfortunately to have type:

We see that we have an extra Naturals_T : Set in

forall (Naturals_T _p_Naturals_T : Set) ...

So now, we have 2 arguments of type Set. Why ?

Let's have a look in the outer Section related to the species Me. We had a Variable already abstracting the type of the collection parameter Natural, namely **Variable** Natural_T : Set. And so, by closing the outer Section of the species Me, Coq abstracted once again. Then, it is the outer Section that brings the problem, not the inner one.

And obviously, this typing problem makes so that when we try to create collection like above, we do not apply the method generator to the number of arguments that Coq expects.

A solution could be to say "let's remove the Variable Natural_T : Set from the outer Section". Right, no ! Since we do not λ -lift in properties (generated as Hypothesis in Coq), if a FoCaLize property needs to make reference to this type, we need a way to speak of it. And if we remove it, then we are not able anymore to speak of it...

A few remarks

- The annoying Section is then the outer one, the one of the species. Indeed, when we leave the inner Section, the theorem gets right abstracted on the inner Variable.
- This only arises on theorems because they are the only ones to be in a nested Section.
- Moreover, we can note in this code generation model that the Local self_xxx are always generated even when the method xxx is inherited. The reason is that since we do not λ -lift in properties (leading to Coq Hypothesis), if a property depends on another method, it really need to have a way to speak of it in the property's statement. And namely, that's via this self_xxx. However, in the OCaml code generation model,

inherited methods are not generated again, hence do not lead to `local_xxx` definitions. This is not really homogeneous.

Conclusion

In order to solve this problem and to make `Coq` and `OCaml` code generation models (hence `Coq` and `OCaml` generated codes), we decided to use the same model, without `Sections` and `Chapter's`, and to manage abstractions ourselves via explicit λ -liftings even for properties and theorems.

This raises a technical problem however since `Zenon` does not support yet higher order. And in fact, with this generation model, our theorems get parametrised by all the λ -lifted definitions. To circumvent this problem, we decided to only reintroduce `Sections` in the code dedicated to be sent to `Zenon`, then map back the proved theorems onto regular λ -lifted definitions. This means that on `Zenon's` the point of view, there is no λ -lifts, all is first order, and it can exhibit a proof. Once we get the proof done, we apply it to the stated theorem in the `Section` to get a temporary version of the theorem. And finally, after closing the `Section` for `Zenon`, we transform this temporary version into a fully λ -lifted definition.

```

Chapter Me.
Record Me (Naturals_T : Set) (_p_n_n : Naturals_T)
  (_p_Naturals_one : Naturals_T) : Type :=
mk_Me {
  Me_T := Set ;
  (* From species ok__in_example#Me. *)
  Me_lookatme :
    forall x : Me_T, Is_true ((basics.base_eq _ _p_n_n _p_Naturals_one)) ;
  (* From species ok__in_example#Me. *)
  Me_reduce : Naturals_T -> Me_T
}.

(* Variable abstracting the species parameter [Naturals]. *)
Variable Naturals_T : Set.
(* Variable abstracting the species parameter [n]. *)
Variable n_n : Naturals_T.

(* Carrier representation. *)
Let self_T : Set := Naturals_T.

(* Variable(s) induced by dependencies on methods from species
parameter(s). *)
Variable Naturals_modulo : Naturals_T -> Naturals_T -> Naturals_T.
Variable Naturals_one : Naturals_T.

(* From species ok__in_example#Me. *)
Section lookatme.
(* Due to a decl-dependency on species parameter carrier type 'Naturals'. *)
Variable _p_Naturals_T : Set.
(* Due to a decl-dependency on method 'one' of species parameter 'Naturals'. *)
Variable _p_Naturals_one : _p_Naturals_T.
(* Due to a decl-dependency on method 'n' of species parameter 'n'. *)
Variable _p_n_n : _p_Naturals_T.
Theorem Me__lookatme :
  forall x : self_T, Is_true ((basics.base_eq _ _p_n_n _p_Naturals_one)).
(* Artificial use of type 'Naturals_T' to ensure abstraction of it's
related variable in the theorem section. *)
assert (___force_abstraction_p_Naturals_T := _p_Naturals_T).
(* Artificial use of method '_p_Naturals_one' to ensure abstraction of
it's related variable in the theorem section. *)
assert (___force_abstraction_p_Naturals_one := _p_Naturals_one).
(* Artificial use of method '_p_n_n' to ensure abstraction of it's
related variable in the theorem section. *)
assert (___force_abstraction_p_n_n := _p_n_n).
apply basics.magic_prove.
Qed.
End lookatme.

Let self_lookatme :
  forall x : self_T, Is_true ((basics.base_eq _ n_n Naturals_one)) :=
  Me__lookatme Naturals_T Naturals_one n_n.

...
End Me.

```

```

Me__lookatme:
self_T -> Is_true (basics.base_eq _p_Naturals_T _p_n_n _p_Naturals_one)

```

```
Me__lookatme :  
  forall (_p_Naturals_T : Set) (_p_Naturals_one _p_n_n : _p_Naturals_T),  
    self_T -> Is_true (basics.base_eq _p_Naturals_T _p_n_n _p_Naturals_one)
```

```
collection ConcreteInt implements IntModel ;;  
collection ConcreteMe implements Me (ConcreteInt, ConcreteInt!one) ;;
```

```
Me__lookatme:  
  forall (Naturals_T _p_Naturals_T : Set)  
    (_p_Naturals_one _p_n_n : _p_Naturals_T),  
    Naturals_T ->  
      Is_true (basics.base_eq _p_Naturals_T _p_n_n _p_Naturals_one)
```


Chapter 2

Code generation model

The code generation model is the now closely the same for both OCaml and Coq generated source files. The main difference comes from the fact that in OCaml, logical methods are discarded. However, except for the case of Zenon proofs where we introduce Coq Section, the generation model for “computation” and logical methods are exactly the the same. This especially means that dependencies are “manually” abstracted by explicit λ -lifting instead of using (like in the previous compiler) the Coq’s Section mechanism. In the same order of idea, in order to have a common model, both OCaml and Coq code are based on a record-oriented structure for the species and collection, with explicit record fields accesses.

2.1 Species

2.1.1 Species header

The generated code for a species is hosted by a module whose name is the species’ name. This way, it is possible to have species having the same names of methods without conflict. The module hence defines the name-space of “things” contained in and induced by a species.

2.1.2 Carrier representation

In OCaml, if the structure of the carrier of the species is known (i.e. if the method representation was defined), then we generate a type definition whose name is `me_as_carrier` and body is the type translation of the corresponding FoCaLize type expression.

In such a type definition, carriers of species parameters appearing in the species’ carrier are abstracted by type variables. The naming scheme of these variable is “’” + the species parameter’s name un-capitalised + “_as_carrier” + an integer stamp that is unique (inside this type definition). Since species names in FoCaLize are capitalised and capitalised identifiers in OCaml are reserved for modules and sum type value constructors, we need to un-capitalise the name when generating OCaml code. For the stamp, it is required to prevent several type variable from having the same name in case the species is parameterised by both a collection parameter and an entity parameter whose names differ only by the capitalisation of the first letter.

For instance, the following header of a species definition:

```
species Cartesian_product(A is Setoid, B is Setoid) =  
  representation = A * B;  
  ...
```

will generate the OCaml type definition:

```
module Cartesian_product =  
  struct  
    (* Carrier’s structure explicitly given by "rep". *)
```

```

type ('a0_as_carrier, 'b1_as_carrier) me_as_carrier =
  'a0_as_carrier * 'b1_as_carrier
...

```

In fact, *a posteriori*, I think now that it's useless in case of a species, even closed. This type definition is only used in the case of a collection.

In **Coq**, no definition generated, the knowledge of the structure of the carrier being reflected directly is needed in the methods (see later).

2.1.3 The record type

The type of data representing a species is a record type. We first examine its header, i.e. stuff before this type definition's body, then it's body.

The record header

The name of this type is always `me_as_species`. It can be parametrised due to various abstraction requirements induced by the late-binding feature of **FoCaLize**. **OCaml** requires a parameter not needed for **Coq**: this is the only fundamental difference. We will see that abstractions (hence, parameters) required by **Coq** can involve methods but this is only because some of the dependencies that are present in the **Coq**code are always trivially absent in the **OCaml** code.

1. First come all the species parameter carriers appearing in the **types** of the methods of the species. Each carrier will be abstracted by one type variable. This allows to “late-bind” the representation of the species parameters. We say here “appearing in the **types**...”: be aware that the type of “computational” methods are ML-like types and the ones of logical methods are their **statement** ! We do not explain here how these parameters are found: this is the role of dependency computation on species parameters.

The naming scheme of these type variable in **OCaml** is the same than described above for the carrier representation.

In **Coq** these parameters of the type are not “really type variables” but arguments of type `Set` (simply a technical question). Their naming scheme is the species parameter's name + “_T”.

2. Next, **only in the OCaml code**, the record type is always parametrised by a type variable representing the carrier of (i.e. the internal representation of the type encapsulated in this) species. By convention, this type variable is always named `'me_as_carrier` (don't confuse with `me_as_carrier` that is the name of the type definition representing the effective structure of the carrier when it is known).

In **Coq** we don't have this mandatory type parameter, but instead of it, we will have one extra field in the body of the record. This variable enable to “late-bind” the representation of the species.

3. Finally come all the methods of the species parameter appearing in the **types** of the methods of the species. Since in **OCaml** the type of a method can only involve type constructors (a ML-like type), it is clear that we won't have any such parameters. In effect, in **OCaml** the logical methods are discarded. However, since for the type of a logical method is its logical statement, to **Coq**'s side, we can have any expression inside their type.. In particular, we can have calls to some collection parameters' methods. Having these parameters in the record type allows the “late-binding” on the collection parameter itself (i.e. on by which effective collection will be used to instantiate the parameter). The naming scheme for the parameters induced by these dependencies is “_p_” + the species parameter's name + _ + the method's name.

There is a special a case: the entity parameters. We will explain this after the following example.

Let's now change our previous example to illustrate the header of our record type in **OCaml** and **Coq**:

```

species Cartesian_product(A is Setoid, B is Setoid) =
  representation = A * B;
  let make (x in A, y in B) in Self = (x, y) ;
  let equiv (x in Self) = ... A!equal (...) && B!equal (...) ;
  theorem thm : all x in A, A!tst (x) -> ...
  proof = ... by property A!commutes ... ;
  ...

```

We can see that we have:

- the carrier defined,
- a method make of type $A \rightarrow B \rightarrow \text{Self}$
- a method equiv having type $\text{Self} \rightarrow \text{bool}$, having dependencies on the methods equal of the collection parameters A and B, but in its **body**, not in its type (equal doesn't appear in equiv's type). Hence, the record type (in Coq and in OCaml) won't have any parameter to abstract the dependencies on these methods.
- a theorem thm of “type” $\text{all } x \text{ in } A, A!tst(x) \rightarrow \dots$ and “body”(proof) ... **by property** A!commutes ... Hence, it has dependencies on A!tst in its type and on A!commutes in its body. This means that in Coq the record type will have a parameter to abstract the dependency found in the type of the theorem, i.e. A!tst but not for A!commutes

The record type for OCaml will then look like:

```

module Cartesian_product =
  struct
    (* Carrier's structure explicitly given by "rep". *)
    type ('a0_as_carrier, 'b1_as_carrier) me_as_carrier =
      'a0_as_carrier * 'b1_as_carrier
    type ('a0_as_carrier, 'b1_as_carrier, 'me_as_carrier) me_as_species =
      ...

```

In Coq a record is introduced by a constructor. By convention, we always name it mk_record. The record type for Coq will then look like:

```

Module Cartesian_product.
  Record Cartesian_product (A_T : Set) (B_T : Set)
    (_p_A_tst : A_T -> basics.bool__t) : Type :=
    mk_record
  ...

```

The entity parameters In OCaml they can never appear in the record type since in ML-like types, we can't have expressions. However, in Coq it is possible to have dependency on an entity parameter in a theorem or property statement (i.e. in the type of a logical method). For example:

```

species Me (Naturals is IntModel, n in Naturals) =
  representation = Naturals ;

  theorem myth : all x in Self,
    basics#syntactic_equal (n, Naturals!un)
  proof = assumed { * * } ;
  end ;;

```

The theorem myth shows a dependency on the entity parameter n. In this case, the record type will be parametrised by this entity parameter like if it was a collection parameter's method. Obviously, an entity parameter doesn't have methods since it is a “value” and not a species. So we don't have any notion of method in the naming scheme. We choose to name these entity parameters by “_p_” + the entity parameter's name + _ + the the entity parameter's name again.

```
Module Me.
Record Me (Naturals_T : Set) (_p_n_n : Naturals_T)
  (_p_Naturals_un : Naturals_T) : Type :=
  mk_record
...
```

The record type for OCaml will then look like:

```
module Cartesian_product =
struct
(* Carrier's structure explicitly given by "rep". *)
type ('a0_as_carrier, 'b1_as_carrier) me_as_carrier =
  'a0_as_carrier * 'b1_as_carrier
type ('a0_as_carrier, 'b1_as_carrier, 'me_as_carrier) me_as_species =
...
```

The record type for Coq will then look like:

```
Module Cartesian_product.
Record Cartesian_product (A_T : Set) (B_T : Set)
  (_p_A_tst : A_T -> basics.bool__t) : Type :=
  mk_record
...
```

The entity parameters In OCaml they can never appear in the record type since in ML-like types, we can't have expressions. However, in Coq it is possible to have dependency on an entity parameter in a theorem or property statement (i.e. in the type of a logical method). For example:

```
species Me (Naturals is IntModel, n in Naturals) =
  representation = Naturals ;

theorem myth : all x in Self,
  basics#syntactic_equal (n, Naturals!un)
proof = assumed { * * } ;
end ;;
```

The theorem `myth` show a dependency on the entity parameter `n`. In this case, the record type will be parameterised by this entity parameter like if it was a collection parameter's method. Obviously, an entity parameter doesn't have methods since it is a "value" and not a species. So we don't have any notion of method in the naming scheme. We choose to name these entity parameters by "`_p_`" + the entity parameter's name + `_` + the the entity parameter's name again.

Fields and their types

Now we saw the header of the record type definition, we must address its body, i.e. its fields. Roughly speaking, the fields will be all the methods with their types hosted in the species in normal form. By "all" we mean the methods declared, defined in the species and those inherited. Because the species is in normal form, this means that we do not have several times a method: inheritance has been resolved and chose the right version of each method to keep.

The type accompanying each method is, like we previously said, a ML-like type for "computational" methods and a logical statement for logical methods. This especially means that since logical methods are discarded in OCaml, in this target language, we will only have ML-like types.

The only important difference between OCaml and Coq is that in Coq we always have an extra (and first) field representing the carrier of the species (remember that in OCaml, instead, we had a type definition that we didn't have in Coq). This field always appears as `rf_T :> Set ;` and represents the type encapsulated in the species. In OCaml, the field corresponding to a method is straight the method's name. In Coq, the field's name is "`rf_`" + the method's name ("`rf`" for **r**ecord **f**ield).

Let's now take a simple example and seen the record types in OCaml and in Coq.

```
species Me (Naturals is IntModel, n in Naturals) =
  representation = Naturals ;
```

```

theorem daube : all x in Self,
  basics#syntactic_equal (n, Naturals!un)
proof = assumed { * * } ;

let junk (x in Self) in int = 1 ;

let reduce (x in Naturals) in Self =
  Naturals!modulo (x, n) ;
end ;;

```

```

module Me =
struct
  (* Carrier's structure explicitly given by "rep". *)
  type ('naturals0_as_carrier, 'nl_as_carrier) me_as_carrier =
    'naturals0_as_carrier
  type ('naturals0_as_carrier, 'nl_as_carrier, 'me_as_carrier) me_as_species = {
    (* From species ok__in_example#Me. *)
    junk : 'me_as_carrier -> Basics._focty_int ;
    (* From species ok__in_example#Me. *)
    reduce : 'naturals0_as_carrier -> 'me_as_carrier ;
  }

```

```

Module Me.
Record Me (Naturals_T : Set) (_p_n_n : Naturals_T)
  (_p_Naturals_un : Naturals_T) : Type :=
mk_record {
  rf_T :> Set ;
  (* From species ok__in_example#Me. *)
  rf_daube :
    forall x : rf_T,
      Is_true ((basics.syntactic_equal _ _p_n_n _p_Naturals_un)) ;
  (* From species ok__in_example#Me. *)
  rf_junk : rf_T -> basics.int__t ;
  (* From species ok__in_example#Me. *)
  rf_reduce : Naturals_T -> rf_T
}.

```

Note that in the generated Coq code, the method daube (in fact, the theorem) contains an application of `basics.syntactic_equal`. We can see the mechanism of explicit polymorphism and the interest of having kept in the Coq code generation environment the number of extra arguments (`_s`) that must be added to identifiers in applicative position.

2.1.4 Methods

Once the record type is defined, it is time to generate the definitions corresponding to the various methods of the species. Several cases exist: a method can be declared, defined and in each case either at the current inheritance level or inherited from an ancestor.

Inherited, declared, defined ?

First of all, the point is that methods only declared or **inherited** are **never** leading to generated code, neither in OCaml, nor in Coq. This means that only methods freshly defined in the species are leading to code.

Defined methods

In term of generation model, there is no difference between OCaml and Coq. The point is because in OCaml we don't have logical methods, all what we will explain about theorems and proof is trivially out of the subject for OCaml. Hence we won't make any difference in our explanation here, simply considering both kinds of methods independently of the target language.

There are 2 kinds of methods: “computational” and logical. The generation model makes only a difference for theorems because they have a proof, but the final definition of both kinds of method uses the same mechanism: making explicit abstractions (λ -lifts) for all the types and **declared** methods (from `Self` or from the species parameters) the defined method depends on. Moreover, an entity parameter (since it’s in fact a value) will appear as an argument of a method if it is used by it: it becomes hence an argument of the method.

To help us, we need 3 notions. We don’t examine here how they are computed. This will be investigated later and is mostly described in Virgile Prevosto’s PhD.

- The carriers present in the methods from parameters (and in the type of entity parameters) and methods of `Self` the method depends on. Since they are atomic types, there is no ordering issue in this set.
- The “minimal typing environment”. It represents the **ordered** set of methods of `Self` a method depends on. It must be ordered because some of the dependencies can depend on some others. Because of the well-formation property, we are sure this order exists.
- The **ordered** set of methods from parameters the method depends on.

A method will lead to a let of theorem definition depending on its kind. The generated name is the same than in the `FoCaLize` source. labelident-stringification Only a “stringification” is done when the method is an operator (e.g. `=`, `+`, `+=e`, ...). This stringification is done on the fly using a very simple mechanism (check function `pp_vname_with_operators_expanded` in the source file `focalize/focalizec/src//basement/parsetree_utils.ml`).

The generated definition is in fact a **method generator**, not the method itself. Its is a function that is parametrised by all the thing the method depends on, and whose body is the method’s body”. This mechanism serves the late-binding feature and allow to really create a method once things it depends on are defined by applying the generator to the effective definitions of the methods the current method depends on. Hence, until the method we depend on are not yet defined, one can still work with our method generator. Moreover, this allows to make several effective methods from a same generator, by applying different effective definitions for λ -lifted parameters of the generator.

Next come all the λ -lifts that represent the dependencies of the method: In the following order come:

1. The parameters representing the carriers of species parameters appearing in the method (i.e. used in its whole definition). Their name is “`_p_`” + the species parameter’s name + “`_T`”.
2. The parameters representing the methods of species’ parameters the current method depends on. They are ordered in 2 directions. First, all the methods of a same parameter are consecutive and we λ -lift following the order of apparition of the species parameters. Second, for each species parameter, the consecutive list of its methods is ordered according to their own dependencies together.

The first point naturally ensure that following the species parameters’ order, definitions of methods of a parameter can only depend on former parameters (otherwise, scoping and type-checking would have told “Unbound ...”). The second point is not obtained for free. We must really order the methods of a species parameter according to their own dependencies “on `Self`’s methods” in their hosting species. For instance, let’s imagine that in a species, we need to abstract `P1!eq_refl : all x in Self, !equal (x, x)` and `P1!equal : Self -> Self -> bool`, clearly to have `P1!eq_refl` well typed, `P1!equal` must be known, hence appear sooner (i.e. must be λ -lifted before `P1!eq_refl`).

Methods are named by “`_p_`” + the species parameter’s name + “`_`” + the method’s name.

The translation mechanisms of expressions is not studied in this section since it isn’t really part of the “species” compilation model. We can however note that in the body of a species parameter’s method, calls performed to other methods of **this** parameter (i.e. so, obviously, on which the method of the parameter depends on) are done using the naming scheme: “`_p_`” + the species parameter’s name + “`_`” + called method’s name (flag `SMS_from_param` used when calling the function `Species_record_type_generation.generate_logical_expr`).

3. The parameters representing the methods of ourselves (i.e. of `Self`) we **decl**-depend on. They are named by “`abst_`” + the method’s name. The only exception is in case where the method is the `representation`, the name will be `abst_T`.

Methods on which we **def**-depend are not abstracted (i.e. not represented by λ -lifting). In effect, since we depend on their **definition**, they are defined (the compiler ensures that) and their effective definition must be used in the body of the method that depends on. Otherwise, their would be no link between the fact the method depends on a definition and a λ -lift that would represent any definition that will be provided one days, nobody know when and where !

Finally comes the translation of the method definition itself, i.e. it’s parameters (if the definition is functional) and its body. As above, we leave for later the translation mechanisms of expressions. We can however note that in the body of a method, calls performed to other methods of `Self` (i.e. so obviously on which we depend) are done using the naming scheme: “`abst_`” + the called method’s name (flag `SMS_abstracted` used when calling the function `Species_record_type_generation.generate_logical_expr`).

Attention, theorems require some intermediate cooking before one can directly build their method generator. In effect, their proof may involve a script for `Zenon` and in this case, a complex process must be inserted in order to get the proof done to finally get the method generator. This will be explained in section ??odo1.

Sample code to help to summarise

We take a part of the example given in Virgile Prevosto’s Phd, section 2.2.2 starting page 14 to illustrate the model we exposed until now. Attention, we explicitly skipped (removed in the generated listings) code dealing with collection generator we will explain in the next section.

```
species Setoide inherits Basic_object =
  signature ( = ) : Self -> Self -> bool ;
  signature element : Self ;
  let different (x, y) = basics#not_b (x = y) ;

  property refl : all x in Self, x = x ;
  property symm : all x y in Self, Self!( = ) (x, y) -> y = x ;
end ;;

species Monoide inherits Setoide =
  signature ( * ) : Self -> Self -> Self ;
  signature un : Self ;
  let element = Self! un * !un ;
end ;;

species Setoide_produit (A is Setoide, B is Setoide) inherits Setoide =
  representation = (A * B) ;

  let ( = ) (x, y) =
    and_b
    (A!( = ) (basics#fst (x), basics#fst (y)),
     B!( = ) (snd (x), snd (y))) ;
  let creer (x, y) in Self = basics#pair (x, y) ;
  let element = Self!creer (A!element, B!element) ;
  let print (x) =
    "(" ^ A!print (fst (x)) ^ "," ^ B!print (snd (x)) ^ ")" ;

  proof of refl = (* by definition of ( = ) *) assumed { * * } ;
  proof of symm = assumed { * * } ;

end ;;
```

```
module Setoide =
  struct
```

```

type 'me_as_carrier me_as_species = {
  (* From species ok_phd_sample#Setoide. *)
  element : 'me_as_carrier ;
  (* From species ok_phd_sample#Setoide. *)
  _equal_ : 'me_as_carrier -> 'me_as_carrier -> Basics._focty_bool ;
  (* From species basics#Basic_object. *)
  parse : Basics._focty_string -> 'me_as_carrier ;
  (* From species basics#Basic_object. *)
  print : 'me_as_carrier -> Basics._focty_string ;
  (* From species ok_phd_sample#Setoide. *)
  different : 'me_as_carrier -> 'me_as_carrier -> Basics._focty_bool ;
}
let different abst__equal_ (x : 'me_as_carrier) (y : 'me_as_carrier) =
  (Basics.not_b (abst__equal_ x y))
end ;;

module Monoide =
struct
  type 'me_as_carrier me_as_species = {
    (* From species ok_phd_sample#Monoide. *)
    un : 'me_as_carrier ;
    (* From species ok_phd_sample#Monoide. *)
    _star_ : 'me_as_carrier -> 'me_as_carrier -> 'me_as_carrier ;
    (* From species ok_phd_sample#Setoide. *)
    _equal_ : 'me_as_carrier -> 'me_as_carrier -> Basics._focty_bool ;
    (* From species basics#Basic_object. *)
    parse : Basics._focty_string -> 'me_as_carrier ;
    (* From species basics#Basic_object. *)
    print : 'me_as_carrier -> Basics._focty_string ;
    (* From species ok_phd_sample#Monoide. *)
    element : 'me_as_carrier ;
    (* From species ok_phd_sample#Setoide. *)
    different : 'me_as_carrier -> 'me_as_carrier -> Basics._focty_bool ;
  }
  let element abst_un abst__star_ = (abst__star_ abst_un abst_un)
end ;;

module Setoide_produit =
struct
  (* Carrier's structure explicitly given by "rep". *)
  type ('a0_as_carrier, 'b1_as_carrier) me_as_carrier =
    'a0_as_carrier * 'b1_as_carrier
  type ('a0_as_carrier, 'b1_as_carrier, 'me_as_carrier) me_as_species = {
    (* From species ok_phd_sample#Setoide_produit. *)
    creer : 'a0_as_carrier -> 'b1_as_carrier -> 'me_as_carrier ;
    (* From species basics#Basic_object. *)
    parse : Basics._focty_string -> 'me_as_carrier ;
    (* From species ok_phd_sample#Setoide_produit. *)
    print : 'me_as_carrier -> Basics._focty_string ;
    (* From species ok_phd_sample#Setoide_produit. *)
    _equal_ : 'me_as_carrier -> 'me_as_carrier -> Basics._focty_bool ;
    (* From species ok_phd_sample#Setoide_produit. *)
    element : 'me_as_carrier ;
    (* From species ok_phd_sample#Setoide. *)
    different : 'me_as_carrier -> 'me_as_carrier -> Basics._focty_bool ;
  }
  let creer (x : 'a0_as_carrier) (y : 'b1_as_carrier) = (Basics.pair x y)
  let print _p_A_print _p_B_print (x : 'me_as_carrier) =
    (Basics._hat_ "("
      (Basics._hat_ (_p_A_print (Basics.fst x))
        (Basics._hat_ ", " (Basics._hat_ (_p_B_print (Basics.snd x)) "))))))
  let _equal_ _p_A_equal_ _p_B_equal_ (x : 'me_as_carrier)
    (y : 'me_as_carrier) =
    (Basics.and_b (_p_A_equal_ (Basics.fst x) (Basics.fst y))
      (_p_B_equal_ (Basics.snd x) (Basics.snd y)))

```



```

let element _p_A_element _p_B_element abst_creer =
  (abst_creer _p_A_element _p_B_element)

<<<< ATTENTION:                                     >>>>
<<<< SKIPPED THE COLLECTION GENERATOR STUFF THAT WE EXPLAIN LATER >>>>
end ;;

```

```

Module Setoide.
Record Setoide : Type :=
mk_record {
  rf_T :> Set ;
  (* From species ok_phd_sample#Setoide. *)
  rf_element : rf_T ;
  (* From species ok_phd_sample#Setoide. *)
  rf_equal_ : rf_T -> rf_T -> basics.bool__t ;
  (* From species basics#Basic_object. *)
  rf_parse : basics.string__t -> rf_T ;
  (* From species basics#Basic_object. *)
  rf_print : rf_T -> basics.string__t ;
  (* From species ok_phd_sample#Setoide. *)
  rf_different : rf_T -> rf_T -> basics.bool__t ;
  (* From species ok_phd_sample#Setoide. *)
  rf_refl : forall x : rf_T, Is_true ((rf_equal_ x x)) ;
  (* From species ok_phd_sample#Setoide. *)
  rf_symm :
    forall x y : rf_T,
      Is_true ((rf_equal_ x y)) -> Is_true ((rf_equal_ y x))
}.

Definition different (abst_T : Set)
  (abst_equal_ : abst_T -> abst_T -> basics.bool__t) (x : abst_T)
  (y : abst_T) : basics.bool__t := (basics.not_b (abst_equal_ x y)).

End Setoide.

Module Monoide.
Record Monoide : Type :=
mk_record {
  rf_T :> Set ;
  (* From species ok_phd_sample#Monoide. *)
  rf_un : rf_T ;
  (* From species ok_phd_sample#Monoide. *)
  rf_star_ : rf_T -> rf_T -> rf_T ;
  (* From species ok_phd_sample#Setoide. *)
  rf_equal_ : rf_T -> rf_T -> basics.bool__t ;
  (* From species basics#Basic_object. *)
  rf_parse : basics.string__t -> rf_T ;
  (* From species basics#Basic_object. *)
  rf_print : rf_T -> basics.string__t ;
  (* From species ok_phd_sample#Monoide. *)
  rf_element : rf_T ;
  (* From species ok_phd_sample#Setoide. *)
  rf_different : rf_T -> rf_T -> basics.bool__t ;
  (* From species ok_phd_sample#Setoide. *)
  rf_refl : forall x : rf_T, Is_true ((rf_equal_ x x)) ;
  (* From species ok_phd_sample#Setoide. *)
  rf_symm :
    forall x y : rf_T,
      Is_true ((rf_equal_ x y)) -> Is_true ((rf_equal_ y x))
}.

Definition element (abst_T : Set) (abst_un : abst_T)
  (abst_star_ : abst_T -> abst_T -> abst_T) : abst_T :=
  (abst_star_ abst_un abst_un).

```

End Monoide.

Module Setoide_produit.

```
Record Setoide_produit (A_T : Set) (B_T : Set) : Type :=
mk_record {
  rf_T :> Set ;
  (* From species ok_phd_sample#Setoide_produit. *)
  rf_creer : A_T -> B_T -> rf_T ;
  (* From species basics#Basic_object. *)
  rf_parse : basics.string__t -> rf_T ;
  (* From species ok_phd_sample#Setoide_produit. *)
  rf_print : rf_T -> basics.string__t ;
  (* From species ok_phd_sample#Setoide_produit. *)
  rf_equal_ : rf_T -> rf_T -> basics.bool__t ;
  (* From species ok_phd_sample#Setoide_produit. *)
  rf_element : rf_T ;
  (* From species ok_phd_sample#Setoide. *)
  rf_different : rf_T -> rf_T -> basics.bool__t ;
  (* From species ok_phd_sample#Setoide_produit. *)
  rf_refl : forall x : rf_T, Is_true ((rf_equal_ x x)) ;
  (* From species ok_phd_sample#Setoide_produit. *)
  rf_symm :
    forall x y : rf_T,
      Is_true ((rf_equal_ x y)) -> Is_true ((rf_equal_ y x))
}.
```

```
Definition creer (_p_A_T : Set) (_p_B_T : Set)
(abst_T := ((_p_A_T * _p_B_T)%type)) (x : _p_A_T) (y : _p_B_T) :
abst_T := (basics.pair _ _ x y).
```

```
Definition print (_p_A_T : Set) (_p_B_T : Set) (_p_A_print :
_p_A_T -> basics.string__t) (_p_B_print : _p_B_T -> basics.string__t)
(abst_T := ((_p_A_T * _p_B_T)%type)) (x : abst_T) : basics.string__t :=
(basics._hat_ coq_builtins.__a_string
  (basics._hat_ (_p_A_print (basics.fst _ _ x))
    (basics._hat_ coq_builtins.__a_string
      (basics._hat_ (_p_B_print (basics.snd _ _ x))
        coq_builtins.__a_string))))).
```

```
Definition _equal_ (_p_A_T : Set) (_p_B_T : Set) (_p_A_equal_ :
_p_A_T -> _p_A_T -> basics.bool__t) (_p_B_equal_ :
_p_B_T -> _p_B_T -> basics.bool__t) (abst_T := ((_p_A_T * _p_B_T)%type))
(x : abst_T) (y : abst_T) : basics.bool__t :=
(basics.and_b (_p_A_equal_ (basics.fst _ _ x) (basics.fst _ _ y))
  (_p_B_equal_ (basics.snd _ _ x) (basics.snd _ _ y))).
```

```
Definition element (_p_A_T : Set) (_p_B_T : Set) (_p_A_element : _p_A_T)
(_p_B_element : _p_B_T) (abst_T : Set)
(abst_creer : _p_A_T -> _p_B_T -> abst_T) : abst_T :=
(abst_creer _p_A_element _p_B_element).
```

```
(* From species ok_phd_sample#Setoide_produit. *)
Theorem refl (_p_A_T : Set) (_p_B_T : Set) (abst_T : Set)
(abst_equal_ : abst_T -> abst_T -> basics.bool__t):
  forall x : abst_T, Is_true ((abst_equal_ x x)).
(* Proof assumed because " ". *)
apply coq_builtins.magic_prove.
Qed.
```

```
(* From species ok_phd_sample#Setoide_produit. *)
Theorem symm (_p_A_T : Set) (_p_B_T : Set) (abst_T : Set)
(abst_equal_ : abst_T -> abst_T -> basics.bool__t):
  forall x y : abst_T,
    Is_true ((abst_equal_ x y)) -> Is_true ((abst_equal_ y x)).
(* Proof assumed because " ". *)
apply coq_builtins.magic_prove.
Qed.
```

```
<<<< ATTENTION: >>>>
<<<< SKIPPED THE COLLECTION GENERATOR STUFF THAT WE EXPLAIN LATER >>>>
End Setoide_produit.
```

Defined recursive methods

The compilation scheme of a recursive function is pretty different and will be explained in the dedicated section ?? . It however finally uses the same abstraction mechanism (i.e. λ -lifted things). The main difference is induced by the use of the Coq construct “Function” and the need for a termination proof.

2.1.5 Fully defined species

In case a species is fully defined, i.e. all its methods are defined, no more remaining only declared, the species can be turned into a collection by an `implements`. To allow creating collections, we must then add to this species a **collection generator**. The intuitive view of such a generator is that it is a function that takes the parameters required by the method generators and feed them with their related parameters to produce a bunch of effective **methods**. Hence, the collection generator takes as many parameters as the method generators of the species need to abstract the dependencies of the methods (i.e. in fact, the λ -lifts of each method generator) and apply each method generator to the set of parameters it needs. Hence applying the collection to effective arguments will create a bunch of effective methods of the species by applying the method generators. Technically, this bunch of methods is stored in a value of ... the record type representing the species. Hence, a collection is just a value of this record type, storing functions (methods) provided to process value whose type is the carrier of the species.

You may note that this carrier type is not recorded in the record structure. However, methods of the record will obviously have traces of this type in their own type schemes. Turning the carrier abstract (i.e. not exporting its internal structure), it becomes impossible to manipulate it except via the provided methods, i.e. functions stored in the record value representing one collection.

Collection generator function’s header

As presented above, the collection generator is a function. Its name is always `collection_create`. As we said, this functions take arguments that represent all the things abstracted in the method generators of the species.

Attention: Because to have a collection generator, the species must be fully defined, it is clear that the only things that can remain abstracted are species parameters’ carriers, species parameters’ methods and entity parameters ! Never some methods of “Self” since all the methods of “Self” are ... defined !

Local functions

For each method of the species, we will create a “real method”, i.e. create a local function of the collection generator, applying the method generator to its required arguments taken among the effective arguments of the collection generator. Hence, for each method of the species, we build (locally to the collection generator) a function. These local functions will be named: “local_” + method’s name. We have 2 possible cases to find the method generator to use to create the collection generator:

- Either the method generator belongs to the current inheritance level (i.e. the method was defined at this level in the species). In this case, this generator is simply the name of the method because a local function in the module was generated with this name. In the following sample code, that’s the case for the methods `creer`, `print`, `element`, ...
- Or the method generator belongs a previous inheritance level (i.e. the method was defined previously, in an ancestor). In this case, the name of the method generator is qualified by the module hosting the ancestor. This means that is the ancestor belongs to another compilation unit, we need to also specify the module on which the compilation unit is mapped. This gives a name like: `file as module + “. + hosting species name + “. + name of the method corresponding to this generator`. In the following sample code, that’s the case for the method `parse` defined in the species `Basic_object` of the compilation unit “`basics.fcl`”.

Creating the record value

Now we have our bunch of functions representing the methods of the species, we just need to create a value of the record type by feeding each record fields with its related function we locally created.

And then, the return value of the collection generator is the record value. Hence, this shows clearly that a collection is in fact a value whose type is the record type we created to model the species.

Sample code to help to summarise

Like we did to explain the code generation model of species in 2.1.4, we use the same sample we used in 2.1.4 and complete the parts about collection generators we previously snipped in the species `Setoide_produit` (the other species, not being fully defined, don't have a collection generator). [language=MyOCaml]

```
<<<< ATTENTION: >>>>
<<<< STUFF BEFORE, PREVIOUSLY SEEN IN PREVIOUS EXPLANATIONS >>>>

module Setoide_produit =
  struct
    <<<< ATTENTION: >>>>
    <<<< STUFF BEFORE, PREVIOUSLY SEEN IN PREVIOUS EXPLANATIONS >>>>

    (* Fully defined 'Setoide_produit' species's collection generator. *)
    let collection_create () _p_B_element _p_B_equal_ _p_B_print _p_A_element
      _p_A_equal_ _p_A_print =
      (* From species ok_phd_sample#Setoide_produit. *)
      let local_creer = creer in
      (* From species basics#Basic_object. *)
      let local_parse = Basics.Basic_object.parse in
      (* From species ok_phd_sample#Setoide_produit. *)
      let local_print = print _p_A_print _p_B_print in
      (* From species ok_phd_sample#Setoide_produit. *)
      let local_equal_ = _equal_ _p_A_equal_ _p_B_equal_ in
      (* From species ok_phd_sample#Setoide_produit. *)
      let local_element = element _p_A_element _p_B_element local_creer in
      (* From species ok_phd_sample#Setoide. *)
      let local_different = Setoide.different local_equal_ in
      { creer = local_creer ;
        parse = local_parse ;
        print = local_print ;
        _equal_ = local_equal_ ;
        element = local_element ;
        different = local_different ;
      }

    end ;;
```

In the above OCaml you may notice that the collection generator takes a “spurious” `()` (“unit”) parameter. This is not a mistake and is only used to prevent a collection generator that does not need any parameter (because there is no collection and entity parameter for this species) from having no argument.

In effect, in this case, for sake of non-expansivity, ML type system doesn't allow to generalise type variables appearing in values that are not functional (roughly, very roughly speaking, since there are other cases ... Let's say that functional value can have their type generalised).

This is a problem since type variables appearing the the module representing a species won't be generalisable, then, as soon we create a collection, we instance these type variables by the carrier representation and by parameters' carriers. And if we want to create another collection, since the variables are now instantiated (they are not polymorphic) we can't instantiate them by other types. And we get a type error on OCaml side. For a full example, see the sample code in section 2.1.5.

Obviously, we could add this extra parameter only if the collection generator has no parameter, but for sake of simplicity and homogeneity, we prefer to add it in all the cases.

[language=MyCoq]

```

<<<< ATTENTION: >>>>
<<<< STUFF BEFORE, PREVIOUSLY SEEN IN PREVIOUS EXPLANATIONS >>>>

Module Setoide_produit.
  <<<< ATTENTION: >>>>
  <<<< STUFF BEFORE, PREVIOUSLY SEEN IN PREVIOUS EXPLANATIONS >>>>

  (* Fully defined 'Setoide_produit' species's collection generator. *)
Definition collection_create (_p_A_T : Set) (_p_B_T : Set) _p_A_element
  _p_A_equal_ _p_A_print _p_B_element _p_B_equal_ _p_B_print :=
  let local_rep := ((_p_A_T * _p_B_T)%type) in
  (* From species ok_phd_sample#Setoide_produit. *)
  let local_creer := creer _p_A_T _p_B_T in
  (* From species basics#Basic_object. *)
  let local_parse := basics.Basic_object.parse local_rep in
  (* From species ok_phd_sample#Setoide_produit. *)
  let local_print := print _p_A_T _p_B_T _p_A_print _p_B_print in
  (* From species ok_phd_sample#Setoide_produit. *)
  let local_equal_ := _equal_ _p_A_T _p_B_T _p_A_equal_ _p_B_equal_ in
  (* From species ok_phd_sample#Setoide_produit. *)
  let local_element := element _p_A_T _p_B_T _p_A_element _p_B_element
    local_rep local_creer in
  (* From species ok_phd_sample#Setoide. *)
  let local_different := Setoide.different local_rep local_equal_ in
  (* From species ok_phd_sample#Setoide_produit. *)
  let local_refl := refl _p_A_T _p_B_T local_rep local_equal_ in
  (* From species ok_phd_sample#Setoide_produit. *)
  let local_symm := symm _p_A_T _p_B_T local_rep local_equal_ in
  mk_record (_p_A_T : Set) (_p_B_T : Set) local_rep local_creer local_parse
  local_print local_equal_ local_element local_different local_refl
  local_symm.

End Setoide_produit.

```

Sample code for extra () parameter for OCaml

As described in 2.1.5, here is a full example showing the need to have an extra () in OCaml for collection generators.

```

use "basics" ;;
open "basics" ;;

let print_bool =
  internal bool -> string
  external | caml -> { * string_of_bool * } | coq -> { * (* [Unsure] *) * }
;;
let ext_nil =
  internal list ('a)
  external | caml -> { * [] * } | coq -> { * (* [Unsure] *) * }
;;
let ext_cons =
  internal 'a -> list ('a) -> basics#list ('a)
  external | caml -> { * (fun e l -> e :: l) * } | coq -> { * (* [Unsure] *) * }
;;
let ext_head =
  internal list ('a) -> 'a
  external | caml -> { * List.hd * } | coq -> { * (* [Unsure] *) * }
;;
let ext_tail =
  internal list ('a) -> list ('a)
  external | caml -> { * List.tl * } | coq -> { * (* [Unsure] *) * }
;;

```

```

species Concrete_list (E is Basic_object) =
  representation = basics#list (E) ;
  let equal (x in Self, y in Self) in bool = syntactic_equal (x, y) ;
  let nil in Self = ext_nil ;
  let cons (e, l) in Self = ext_cons (e, l) ;
  let head (l in Self) in E = ext_head (l) ;
  let tail (l in Self) in Self = ext_tail (l) ;
  let rec map (f, l) =
    if equal (l, nil) then nil
    else
      let h = head (l) in
      let q = tail (l) in
      let h2 = f (h) in
      let q2 = map (f, q) in
      cons (h2, q2) ;
end ;;

```

Once compiled to OCaml we get the following code:

```

let print_bool = string_of_bool ;;
let ext_nil = [] ;;
let ext_cons = (fun e l -> e :: l) ;;
let ext_head = List.hd ;;
let ext_tail = List.tl ;;

module Concrete_list =
  struct
    (* Carrier's structure explicitly given by "rep". *)
    type 'e0_as_carrier me_as_carrier = 'e0_as_carrier Basics._focty_list
    type ('e0_as_carrier, 'me_as_carrier) me_as_species = {
      (* From species test#Concrete_list. *)
      cons : 'e0_as_carrier ->
        'e0_as_carrier Basics._focty_list -> 'me_as_carrier ;
      (* From species test#Concrete_list. *)
      equal : 'me_as_carrier -> 'me_as_carrier -> Basics._focty_bool ;
      (* From species test#Concrete_list. *)
      head : 'me_as_carrier -> 'e0_as_carrier ;
      (* From species test#Concrete_list. *)
      nil : 'me_as_carrier ;
      (* From species test#Concrete_list. *)
      tail : 'me_as_carrier -> 'me_as_carrier ;
      (* From species test#Concrete_list. *)
      map : ('e0_as_carrier -> 'e0_as_carrier) ->
        'me_as_carrier -> 'me_as_carrier ;
    }
    let cons (e : 'e0_as_carrier) (l : 'e0_as_carrier Basics._focty_list) =
      (ext_cons e l)
    let equal (x : 'me_as_carrier) (y : 'me_as_carrier) =
      (Basics.syntactic_equal x y)
    let head (l : 'me_as_carrier) = (ext_head l)
    let nil = ext_nil
    let tail (l : 'me_as_carrier) = (ext_tail l)
    let rec map abst_cons abst_equal abst_head abst_nil abst_tail
      (f : 'e0_as_carrier -> 'e0_as_carrier) (l : 'me_as_carrier) =
      if (abst_equal l abst_nil) then abst_nil else let h = (abst_head l)
      in
        let q = (abst_tail l) in
        let h2 = (f h)
        in
          let q2 = (map abst_cons abst_equal abst_head abst_nil abst_tail f q)
          in
            (abst_cons h2 q2)
    (* Fully defined 'Concrete_list' species's collection generator. *)
    let collection_create !!! WE REMOVED THE EXTRA () !!! =
      (* From species test#Concrete_list. *)

```

```

let local_cons = cons in
(* From species test#Concrete_list. *)
let local_equal = equal in
(* From species test#Concrete_list. *)
let local_head = head in
(* From species test#Concrete_list. *)
let local_nil = nil in
(* From species test#Concrete_list. *)
let local_tail = tail in
(* From species test#Concrete_list. *)
let local_map = map local_cons local_equal local_head local_nil
local_tail in
{ cons = local_cons ;
  equal = local_equal ;
  head = local_head ;
  nil = local_nil ;
  tail = local_tail ;
  map = local_map ;
}

end ;;

```

If we check the interface of the OCaml compilation unit, we can see that the module `Concrete_list` has type:

```

module Concrete_list :
sig
  type 'a me_as_carrier = 'a Basics._focty_list
  type ('a, 'b) me_as_species = {
    cons : 'a -> 'a Basics._focty_list -> 'b;
    equal : 'b -> 'b -> Basics._focty_bool;
    head : 'b -> 'a;
    nil : 'b;
    tail : 'b -> 'b;
    map : ('a -> 'a) -> 'b -> 'b;
  }
  val cons : 'a -> 'a Basics._focty_list -> 'a list
  val equal : 'a -> 'a -> bool
  val head : 'a list -> 'a
  val nil : 'a list
  val tail : 'a list -> 'a list
  val map :
    ('a -> 'b -> 'b) ->
    ('c -> 'b -> bool) ->
    ('c -> 'a) -> 'b -> ('c -> 'c) -> ('a -> 'a) -> 'c -> 'b
  val collection_create : ('_a, '_a Basics._focty_list) me_as_species
end

```

where the function `collection_create` has a non generalised type variable `'_a`. Hence, to continue the example, we just need to create two collections, one with `int` as carrier, the other with `bool` and to create 2 collections of lists using these 2 collections as argument.

```

species Contrete_int inherits Basic_object =
  representation = basics#int ;
  let print = string_of_int ;
end ;;
collection Int implements Contrete_int ;;

species Contrete_bool inherits Basic_object =
  representation = basics#bool ;
  let print = print_bool ;
end ;;
collection Bool implements Contrete_bool ;;

```

When creating the last collection implementing list of booleans, the `'_a` type variable was already instantiated by `int`, hence leading to OCaml complaining:

File ".....", line 210, characters 13-33:

This expression has type

```
int -> int Basics._focty_list -> int Basics._focty_list
```

but is here used with type

```
bool -> Bool.me_as_carrier Basics._focty_list -> me_as_carrier
```

Hence, adding a dummy parameter to the collection generator, it can now be generalised (i.e. become polymorphic) and there is no more instantiation issue.

2.2 Collection

Collections are compiled differently as species but they start by exactly the same kind of record type definition. This record type will represent the type of data in the target language collections are mapped onto.

Things differ after. In effect, we do not need anymore to create the methods since all were already defined in the fully defined species we “implements”. The aim to get a collection, it to get a value of the record type, where fields are filled with the functions representing methods of the species we “implements”. In this species we created a “collection generator” that was a function taking arguments representing dependencies on the species parameters (collection and entity) and returning a value of the record type ...a collection. So, to compile a collection, we will apply the collection generator to things it need to give us material to finally create the collection value that will always be named `effective_collection`.

Once done, we will get from the record generated by the collection generator of the species we “implements”, each field’s value and put it in a record whose type is **our** (i.e. the collection) type. It is then simply a verbatim copy since collection never add fields; so the species the collection implements and the collection have the same methods, so the records have the same fields. With this process, we ensure that the collection will be only type-compatible with itself and won’t be type-compatible with the species it “implements” and also not with other collections extracted from this species (with the same arguments).

Now, the question is to know what to apply to the collection generator of the species we “implements”. In fact, we need to apply this generator to the methods of the collections used to instantiate the collection parameters of the species we “implements”. For instance, going on with our example started in 2.1.4, we add a few FoCaLize code to create a `Monoide_produit` some fully defined species to represent integers to finally build a collection representing couples of integers:

More FoCaLize code to create collections

```
species Monoide_produit (C is Monoide, D is Monoide)
  inherits Monoide, Setoide_produit (C, D) =
...
end ;;

species Entiers_concrets inherits Monoide =
  representation = basics#int ;
...
end ;;

collection Les_entiers implements Entiers_concrets ;;

collection Couple_d_entiers implements
  Monoide_produit (Les_entiers, Les_entiers)
;;
```

We get interested directly by the way to get the collection `Couple_d_entiers` since it is more interesting because the implemented species has collection parameters. For the collection `Les_entiers`, the process is the same, except there is no problem of instantiation because there is no parameter. Here we see that the collection parameters `C` and `D` of `Monoide_produit` were instantiated by the collections `Les_entiers` and `Les_entiers`. The collection generator of `Couple_d_entiers` is parametrised (due to dependencies on species parameters) by several methods of the species parameters (amongst others, trust me ☺, `un`, `print`, `element`, ...). We then must apply the

collection generator to the corresponding methods of “by what C” was instantiated and “by what D” was instantiated, i.e from `Les_entiers` and from `Les_entiers`.

Now, where can we get these methods of `Les_entiers` ? Since it is a collection, the module hosting the collection contains a `effective_collection` value that has a type being a record. Then we just need to pick in the fields of this value to have the arguments we want to give to the collection generator.

Note: It appears that in this case, since the 2 parameters are “is the same collection”, the dependencies will be the same twice. But that’s just for this particular case. By the way, this also means that we do not “optimise” telling “Oh, I see the dependencies are exactly on the same functions of the same species, so let’s keep only one occurrence of the parameter...”. No we keep the model without exception.

We then get the generated OCaml code for the 2 create collections:

OCaml code for collections

```
module Les_entiers =
struct
  (* Carrier's structure explicitly given by "rep". *)
  type me_as_carrier = Basics._focty_int
  type 'me_as_carrier me_as_species = {
    (* From species ok_phd_sample#Entiers_concrets. *)
    parse : Basics._focty_string -> me_as_carrier ;
    (* From species ok_phd_sample#Entiers_concrets. *)
    print : me_as_carrier -> Basics._focty_string ;
    (* From species ok_phd_sample#Entiers_concrets. *)
    un : me_as_carrier ;
    (* From species ok_phd_sample#Entiers_concrets. *)
    _star_ : me_as_carrier -> me_as_carrier -> me_as_carrier ;
    (* From species ok_phd_sample#Entiers_concrets. *)
    _equal_ : me_as_carrier -> me_as_carrier -> Basics._focty_bool ;
    (* From species ok_phd_sample#Monoide. *)
    element : me_as_carrier ;
    (* From species ok_phd_sample#Setoide. *)
    different : me_as_carrier -> me_as_carrier -> Basics._focty_bool ;
  }
  let effective_collection =
    let t =
      Entiers_concrets.collection_create () in
    { parse = t.Entiers_concrets.parse ;
      print = t.Entiers_concrets.print ;
      un = t.Entiers_concrets.un ;
      _star_ = t.Entiers_concrets._star_ ;
      _equal_ = t.Entiers_concrets._equal_ ;
      element = t.Entiers_concrets.element ;
      different = t.Entiers_concrets.different ;
    }
  end ;;
end

module Couple_d_entiers =
struct
  (* Carrier's structure explicitly given by "rep". *)
  type me_as_carrier = Les_entiers.me_as_carrier * Les_entiers.me_as_carrier
  type 'me_as_carrier me_as_species = {
    (* From species ok_phd_sample#Setoide_produit. *)
    creer : Les_entiers.me_as_carrier ->
      Les_entiers.me_as_carrier -> me_as_carrier ;
    (* From species basics#Basic_object. *)
    parse : Basics._focty_string -> me_as_carrier ;
    (* From species ok_phd_sample#Setoide_produit. *)
    print : me_as_carrier -> Basics._focty_string ;
    (* From species ok_phd_sample#Monoide_produit. *)
    _star_ : me_as_carrier -> me_as_carrier -> me_as_carrier ;
    (* From species ok_phd_sample#Setoide_produit. *)
    _equal_ : me_as_carrier -> me_as_carrier -> Basics._focty_bool ;
    (* From species ok_phd_sample#Setoide_produit. *)
  }
end
```

```

element : me_as_carrier ;
(* From species ok_phd_sample#Monoide_produit. *)
un : me_as_carrier ;
(* From species ok_phd_sample#Setoide. *)
different : me_as_carrier -> me_as_carrier -> Basics._focty_bool ;
}
let effective_collection =
let t =
Monoide_produit.collection_create ()
Les_entiers.effective_collection.Les_entiers.un
Les_entiers.effective_collection.Les_entiers._star_
Les_entiers.effective_collection.Les_entiers._equal_
Les_entiers.effective_collection.Les_entiers.print
Les_entiers.effective_collection.Les_entiers.element
Les_entiers.effective_collection.Les_entiers.un
Les_entiers.effective_collection.Les_entiers._star_
Les_entiers.effective_collection.Les_entiers._equal_
Les_entiers.effective_collection.Les_entiers.print
Les_entiers.effective_collection.Les_entiers.element in
{ creer = t.Monoide_produit.creer ;
parse = t.Monoide_produit.parse ;
print = t.Monoide_produit.print ;
_star_ = t.Monoide_produit._star_ ;
_equal_ = t.Monoide_produit._equal_ ;
element = t.Monoide_produit.element ;
un = t.Monoide_produit.un ;
different = t.Monoide_produit.different ;
}
end ;;

```

The Coq code follows exactly the same scheme. It appears to be more tricky and bigger for 2 reasons: first logical methods are in the model, second the record access notation is much more complex in Coq than it is in OCaml (where one just need to say `val.field`).

In effect in Coq to access a field of a value of type record, one must provide, of course the value and the field name, but also all the effective arguments that were provided when the type record was created from the `mk_record` that represents the species. For instance, our collection `Couple_d_entiers` "implements" a `Monoide_produit`. Looking at the record type of `Monoide_produit`, we see:

```

Record Monoide_produit (C_T : Set) (D_T : Set) : Type :=
mk_record {
rf_T :> Set ;
(* From species ok_phd_sample#Setoide_produit. *)
rf_creer : C_T -> D_T -> rf_T ;
...

```

that is we have 2 parameters that are the carriers of the collection parameters. When we want to pick values from the fields of the value returned by the collection generator (hence from the one of `Monoide_produit`), we will need to make explicit by what these parameters were instantiated when we used the generator. And here, we instantiated twice with the carrier of `Les_entiers`. Then, accessing the field `rf_creer` (corresponding to the method `creer` of the species `Monoide_produit`) of the value `v` returned by the collection generator:

```

let t :=
Monoide_produit.collection_create
Les_entiers.effective_collection.(Les_entiers.rf_T)
Les_entiers.effective_collection.(Les_entiers.rf_T)
.... in

```

will look like:

```

t.(Monoide_produit.rf_creer
Les_entiers.effective_collection.(Les_entiers.rf_T)
Les_entiers.effective_collection.(Les_entiers.rf_T))

```

So the full generated Coq code will be:

```

Module Les_entiers.
Record Les_entiers : Type :=
mk_record {
  rf_T :> Set ;
  (* From species ok_phd_sample#Entiers_concrets. *)
  rf_parse : basics.string__t -> rf_T ;
  (* From species ok_phd_sample#Entiers_concrets. *)
  rf_print : rf_T -> basics.string__t ;
  (* From species ok_phd_sample#Entiers_concrets. *)
  rf_un : rf_T ;
  (* From species ok_phd_sample#Entiers_concrets. *)
  rf_star_ : rf_T -> rf_T -> rf_T ;
  (* From species ok_phd_sample#Entiers_concrets. *)
  rf_equal_ : rf_T -> rf_T -> basics.bool__t ;
  (* From species ok_phd_sample#Monoide. *)
  rf_element : rf_T ;
  (* From species ok_phd_sample#Setoide. *)
  rf_different : rf_T -> rf_T -> basics.bool__t ;
  (* From species ok_phd_sample#Entiers_concrets. *)
  rf_refl : forall x : rf_T, Is_true ((rf_equal_ x x)) ;
  (* From species ok_phd_sample#Entiers_concrets. *)
  rf_symm :
    forall x y : rf_T,
      Is_true ((rf_equal_ x y)) -> Is_true ((rf_equal_ y x))
}.

Let effective_collection :=
let t :=
  Entiers_concrets.collection_create in
mk_record t.(Entiers_concrets.rf_T) t.(Entiers_concrets.rf_parse)
  t.(Entiers_concrets.rf_print) t.(Entiers_concrets.rf_un)
  t.(Entiers_concrets.rf_star_) t.(Entiers_concrets.rf_equal_)
  t.(Entiers_concrets.rf_element) t.(Entiers_concrets.rf_different)
  t.(Entiers_concrets.rf_refl) t.(Entiers_concrets.rf_symm).

End Les_entiers.

Module Couple_d_entiers.
Record Couple_d_entiers : Type :=
mk_record {
  rf_T :> Set ;
  (* From species ok_phd_sample#Setoide_produit. *)
  rf_creer : Les_entiers.effective_collection.(Les_entiers.rf_T) ->
    Les_entiers.effective_collection.(Les_entiers.rf_T) -> rf_T ;
  (* From species basics#Basic_object. *)
  rf_parse : basics.string__t -> rf_T ;
  (* From species ok_phd_sample#Setoide_produit. *)
  rf_print : rf_T -> basics.string__t ;
  (* From species ok_phd_sample#Monoide_produit. *)
  rf_star_ : rf_T -> rf_T -> rf_T ;
  (* From species ok_phd_sample#Setoide_produit. *)
  rf_equal_ : rf_T -> rf_T -> basics.bool__t ;
  (* From species ok_phd_sample#Setoide_produit. *)
  rf_element : rf_T ;
  (* From species ok_phd_sample#Monoide_produit. *)
  rf_un : rf_T ;
  (* From species ok_phd_sample#Setoide. *)
  rf_different : rf_T -> rf_T -> basics.bool__t ;
  (* From species ok_phd_sample#Setoide_produit. *)
  rf_refl : forall x : rf_T, Is_true ((rf_equal_ x x)) ;
  (* From species ok_phd_sample#Setoide_produit. *)
  rf_symm :
    forall x y : rf_T,
      Is_true ((rf_equal_ x y)) -> Is_true ((rf_equal_ y x))
}

```

```

    }.
  Let effective_collection :=
    let t :=
      Monoide_produit.collection_create
      Les_entiers.effective_collection.(Les_entiers.rf_T)
      Les_entiers.effective_collection.(Les_entiers.rf_T)
      Les_entiers.effective_collection.(Les_entiers.rf_un)
      Les_entiers.effective_collection.(Les_entiers.rf__star_)
      Les_entiers.effective_collection.(Les_entiers.rf__equal_)
      Les_entiers.effective_collection.(Les_entiers.rf_print)
      Les_entiers.effective_collection.(Les_entiers.rf_element)
      Les_entiers.effective_collection.(Les_entiers.rf_un)
      Les_entiers.effective_collection.(Les_entiers.rf__star_)
      Les_entiers.effective_collection.(Les_entiers.rf__equal_)
      Les_entiers.effective_collection.(Les_entiers.rf_print)
      Les_entiers.effective_collection.(Les_entiers.rf_element) in
    mk_record
      t.(Monoide_produit.rf_T
        Les_entiers.effective_collection.(Les_entiers.rf_T)
        Les_entiers.effective_collection.(Les_entiers.rf_T))
      t.(Monoide_produit.rf_creer
        Les_entiers.effective_collection.(Les_entiers.rf_T)
        Les_entiers.effective_collection.(Les_entiers.rf_T))
      t.(Monoide_produit.rf_parse
        Les_entiers.effective_collection.(Les_entiers.rf_T)
        Les_entiers.effective_collection.(Les_entiers.rf_T))
      t.(Monoide_produit.rf_print
        Les_entiers.effective_collection.(Les_entiers.rf_T)
        Les_entiers.effective_collection.(Les_entiers.rf_T))
      t.(Monoide_produit.rf__star_
        Les_entiers.effective_collection.(Les_entiers.rf_T)
        Les_entiers.effective_collection.(Les_entiers.rf_T))
      t.(Monoide_produit.rf__equal_
        Les_entiers.effective_collection.(Les_entiers.rf_T)
        Les_entiers.effective_collection.(Les_entiers.rf_T))
      t.(Monoide_produit.rf_element
        Les_entiers.effective_collection.(Les_entiers.rf_T)
        Les_entiers.effective_collection.(Les_entiers.rf_T))
      t.(Monoide_produit.rf_un
        Les_entiers.effective_collection.(Les_entiers.rf_T)
        Les_entiers.effective_collection.(Les_entiers.rf_T))
      t.(Monoide_produit.rf_different
        Les_entiers.effective_collection.(Les_entiers.rf_T)
        Les_entiers.effective_collection.(Les_entiers.rf_T))
      t.(Monoide_produit.rf_refl
        Les_entiers.effective_collection.(Les_entiers.rf_T)
        Les_entiers.effective_collection.(Les_entiers.rf_T))
      t.(Monoide_produit.rf_symm
        Les_entiers.effective_collection.(Les_entiers.rf_T)
        Les_entiers.effective_collection.(Les_entiers.rf_T)).
  End Couple_d_entiers.

```

2.3 Toplevel values

At toplevel, since we are not in a species, there is no possible dependencies on species parameters (since there is no parameter) and no possible dependencies on methods of `Self` (since there is no notion of `Self`). For this reason, we do not have to wonder about how naming methods of `Self` and of species parameters.

Hence, code generation for toplevel value definitions (either constants or functions) is a simple translation into the target language with no particular analysis to do before-hand. The name of the generated definition is simply the name

given in the FoCaLize source file and the definition is generated at toplevel.

Hence, we are in the case where there is no more problems than those intrinsic to the target language. For instance, in Coq, we will have to be careful with polymorphic identifiers and handle the explicit polymorphism by providing extra type arguments like seen in 2.1.3.

For instance:

FoCaLize toplevel value definition

```
let x = 42 ;;

let fst (x) =
  match x with
  | (v, _) -> v
;;
```

Generated OCaml toplevel value definition

```
let x = 42 ;;

let snd (x : 'a * 'b) =
  match x with
  | (_, v) ->
    (begin
      v
    end)
;;
```

In the Coq code, we see again here a hack to speak of the type of tuples. In effect, we must explicitly tell Coq that the `*` used in the type expression `(__var_a * __var_b)` is the `*` dealing with **types**. That's the reason of the presence of the `%type` notation post-fixing the type expression of the tuple.

Generated Coq toplevel value definition

```
Let x : basics.int__t := 42.

Let snd (__var_a : Set) (__var_b : Set) (x : ((__var_a * __var_b)%type)) :
  __var_b :=
  match x with
  | (_, v) =>
    v
  end.
```

2.4 Toplevel theorems

Toplevel theorems, like toplevel values do not have any dependencies since they are not in a species. Hence they are generated like other theorems, with the `Section` mechanism for the proof part (if the proof is done in FoCaL Proof Language), but with no λ -lifting stuff.

For instance:

FoCaLize toplevel theorem definition

```
theorem beq_trans :
  all x y z in 'a, x = y -> y = z -> x = z
  proof = assumed { * Import trusted external code. * } ;;
```

Generated Coq toplevel theorem definition

```
Theorem beq_trans :
  forall __var_a : Set, forall x y z : __var_a,
    Is_true ((_equal_ _ x y)) ->
      Is_true ((_equal_ _ y z)) -> Is_true ((_equal_ _ x z)).
```

```
(* Proof assumed because " Import trusted external code. ". *)
apply coq_builtins.magic_prove.
Qed.
```

2.5 Type definitions

Type definitions always appear at toplevel, i.e. outside a species. For a given type definition named “myty” in FoCaLize, the corresponding generated names are historically a few different in OCaml and in Coq. In OCaml the generated type will be named “tt_fopty_” + mty. In Coq, the generated type will be named mty + “__t”.

We have 4 kinds of type definitions:

- **Alias** : the definition doesn’t create a new type (i.e. a new set of values inhabiting a type) but is a shortcut for naming a (complex ?) type expression. For instance: `type t = alias (int * char * int);;` The type constructor `t` is only an alias for the type of tuples with 3 components whose first and third components are an integer and second one is a character. In particular, `t` will be unifiable with any occurrence of its alias.
- **Union** : the definition create a new sum type and gives its value constructors. This new type will be compatible with only itself. For instance: `type t = |A |B (int * char);;` The type constructor `t` denotes the type whose 2 value constructors are `A` and `B`. The constructor `B` is parametrised by a pair of an integer and a character.
- **Record**: the definition create a new record type and gives its fields names and types. This new type will be compatible with only itself. For instance: `type t = { name :string ;birth :int } ;;` The type constructor `t` denotes the record type whose 2 fields are named `name` and `birth` and types are respectively `string` and `int`.
- **External** : the definition establishes the link between a type of an external language and its representation in FoCaLize. Because they are quite complex, they will be studied in more details in a next dedicated section (see ??).

2.5.1 Type alias

As stated before, such a **type definition** introduces a new type name (i.e. type constructor) to represent a **type expression**. Fortunately, both OCaml and Coq have the notion of type alias. Hence, we simply need to translate the FoCaLize type expression in the corresponding target type expression. This doesn’t pose any particular problem. The only thing to remind is that since in Coq polymorphism is explicit, if a type definition is parametrised by a type variable, then one must explicitly give this variable the type `Set`. In OCaml there is no need to give the type of this variable, the syntax only requires to bind this variable name in the type definition’s name (i.e.

`type 'a t = ... ;;`).

Below follow a few simple alias type definitions examples with their corresponding generated source code in Coq and OCaml.

Generated Coq type definition

```
open "basics" ;;

type t = alias int ;;
type u = alias (t * (char * bool * string)) ;;
type poly_pair ('a) = alias ('a * 'a) ;;
type inv_prod ('a, 'b) = alias ('b * 'a) ;;
```

Generated Coq type definition

```
type _fopty_t = Basics._fopty_int ;;
type _fopty_u =
  Basics._fopty_int *
  (Basics._fopty_char * Basics._fopty_bool * Basics._fopty_string) ;;
```

```

type 'a _focty_poly_pair = 'a * 'a ;;
type ('a, 'b) _focty_inv_prod = 'b * 'a ;;

```

Generated Coq type definition

```

Require basics.
Definition t__t := basics.int__t.
Definition u__t :=
  ((basics.int__t
    * (((basics.char__t * basics.bool__t * basics.string__t)%type))%type).
Definition poly_pair__t (__var_a : Set) := ((__var_a * __var_a)%type).
Definition inv_prod__t (__var_b : Set) (__var_c : Set) :=
  ((__var_c * __var_b)%type).

```

The only technical thing is to make sure that type variables are correctly identified all along the unifications to be sure that they are properly link between their declaration (with the type name) and their usage. This is illustrated by the `inv_prod` definition where we want to have variables inverted between the binding order and their usage order.

Be careful that the aliases we made here are **tuples**. They use the type constructor `*` (star) to create **one** type expression that is a tuple compound of several type (sub-)expressions. This will not have to be confused with the problem of parametrising sum type value constructors with **one** tuple of several components or several values as explained later in 2.5.2.

2.5.2 Type union (sum type)

As stated before, such a sum type definition introduces a new type name (i.e. type constructor) with its value constructors. Again fortunately, both OCaml and Coq have the notion of sum type. Hence, we do not need to encode sums, we need to translate them into the corresponding constructs in the target languages. Each value constructor in FoCaLize will lead to a value constructor in the target languages.

In OCaml the return type of a constructor doesn't need to be explicit. Conversely, in Coq it needs to be. Hence for the simple sum type definition:

Simple sum type in FoCaLize

```

type t =
  | A
  | B
;;

```

we get the following OCaml code where only the value constructors names A and B are emitted:

Simple sum type generated in OCaml

```

type _focty_t =
  | A
  | B
;;

```

Whereas in Coq, in addition to the constructors names, one must explicitly say that they are values of this type:

Simple sum type generated in Coq

```

Inductive t__t : Set :=
  | A : (t__t)
  | B : (t__t).

```

Parametrised value constructors are a bit more complex. We first introduce the simplest case, where value constructors have one parameter. In this case, in OCaml code, we have the quite obvious translation that tells “of” the argument's type. In Coq the constructor will simply be considered to have a functional type whose argument is the type of the value constructor's argument and whose return type is the defined type itself. Hence, even for recursive and/or parametrised type definitions, we easily generate the code of the example:

Sum types with simply parametrised value constructors

```
type t_poly ('a) =  
  | None  
  | Some ('a)  
;;  
  
type t_rec =  
  | TR1 (int)  
  | TR2 (t_rec)  
;;  
  
type t_poly_rec ('a) =  
  | TPR1 ('a)  
  | TPR2 (t_poly_rec ('a))  
;;
```

in OCaml to get:

Sum type generated in OCaml

```
type 'a _focty_t_poly =  
  | None  
  | Some of ('a)  
;;  
type _focty_t_rec =  
  | TR1 of (Basics._focty_int)  
  | TR2 of (_focty_t_rec)  
;;  
type 'a _focty_t_poly_rec =  
  | TPR1 of ('a)  
  | TPR2 of ('a _focty_t_poly_rec)  
;;
```

and in Coq to get:

Sum type generated in Coq

```
Inductive t_poly__t (__var_a : Set) : Set :=  
  | None : (t_poly__t __var_a)  
  | Some : (__var_a -> (t_poly__t __var_a)).  
  
Inductive t_rec__t : Set :=  
  | TR1 : (basics.int__t -> t_rec__t)  
  | TR2 : (t_rec__t -> t_rec__t).  
  
Inductive t_poly_rec__t (__var_b : Set) : Set :=  
  | TPR1 : (__var_b -> (t_poly_rec__t __var_b))  
  | TPR2 : ((t_poly_rec__t __var_b) -> (t_poly_rec__t __var_b)).
```

in both of which see that the generated type constructor's name is consistently the same between the code of the name of the definition and the generated type expressions (so, recursive) where this type constructor's name appears.

The translation of sum type is quite complete, but we still need to deal with a choice of representation to do about value constructors that “look having” several parameters, like in

Value constructor parameterised by “several” arguments

```
type t_prm_val_cstr =  
  | C (int * int * int)  
;;
```

In such a case, is the value constructor C parametrised by **three** integers or by **one** tuple of 3 integers ? This makes a particular difference in Coq because value constructors are curried. For Coq unless an explicit tuple is stated, the value constructor for the above example must have the functional type `int -> int -> int -> int -> t_prm_val_cstr`.

Of course, it would be possible to always group the arguments into one unique tuple, but making proofs using such a value constructor would not be tractable (dixit Renaud). In OCaml, since we do not have this concern of proof, this choice would not be a real problem.

In fact, in the syntax, FoCaLize propose two value constructor argument expressions different: one for “several” parameters and one for 1 tuple parameter of “several” components. Hence, translation into the target languages are not ambiguous. In a sum type definition, for a value constructor, arguments separated by , (“comma”) are considered as “several arguments”, and arguments separated by * (“star”) are considered as grouped inside one unique argument that is a tuple. Hence, for the following FoCaLize example:

Value constructor parameterised by “several” arguments (2)

```
type t_prm_val_cstr =
  | C (int * int * int)
  | D (int, int, int)
;;
```

we get the generated OCaml code that follows, where we do make any difference between one and several arguments: all is every considered as a tuple

Value constructor parameterised by “several” arguments in OCaml (2)

```
type _focty_t_prm_val_cstr =
  | C of ((Basics._focty_int * Basics._focty_int * Basics._focty_int))
  | D of (Basics._focty_int * Basics._focty_int * Basics._focty_int)
;;
```

and the generated Coq code where the types of C and D are clearly different:

Value constructor parameterised by “several” arguments in Coq (2)

```
Inductive t_prm_val_cstr__t : Set :=
  | C :
    (((basics.int__t * basics.int__t * basics.int__t)%type)) ->
    t_prm_val_cstr__t
  | D :
    (basics.int__t -> basics.int__t -> basics.int__t -> t_prm_val_cstr__t).
```

2.5.3 Record type

As stated before, such a record type definition introduces a new type name (i.e. type constructor) with its fields labels and types. Again fortunately, both OCaml and Coq have the notion of record type. Hence, we do not need to encode record, we need to translate them into the corresponding constructs in the target languages. Each field in FoCaLize will lead to a field in the record generated in the target languages.

The translation process is simple since it map a each field label of the FoCaLize definition onto a field label of the same name in the target language: The type of the field is generated like any type expression in the target language.

Record type definitions in FoCaLize

```
type r0 = { x0 = int ; y0 = float } ;;
type r1 ('a) = { x1 = 'a } ;;
```

Generated record type definitions in OCaml

```
type _focty_r0 = {
  x0 : Basics._focty_int ;
  y0 : Basics._focty_float ;
} ;;

type 'a _focty_r1 = {
  x1 : 'a ;
} ;;
```

The only difference for **Coq** is (like already encountered when dealing with the record type representing species and collections, in 2.1.3 and 2.2) that a record type definition requires a “record constructor”. By convention, it will always be named by “mk_” + the record type’s name + “__t”.

Generated record type definitions in **Coq**

```
Record r0__t : Type :=
  mk_r0__t {
    x0 : basics.int__t ;
    y0 : basics.float__t
  }.

Record r1__t (__var_c : Set) : Type :=
  mk_r1__t {
    x1 : __var_c
  }.
```

2.6 External definitions

External definitions are intended to make the interface between code imported from foreign target languages to be able to use it on **FoCaLize**’s side. There are 2 kinds of external definitions: type definitions and value definitions.

Type definitions are used either to import basic types and to allows **FoCaLize** to map its internal types on them (for instance, `int`, `bool`, etc that are built-in type in **FoCaLize** and that must be mapped onto their **OCaml** and **Coq** counterparts), or to specify the type of values developed outside **FoCaLize** and that we want to use from **FoCaLize**.

Value definitions are used to provide support (i.e. primitives to manipulate) and inhabitants to external types or to provide values of a type known in **FoCaLize** but whose construction was done outside the **FoCaLize** source code.

Any external definition contains 2 aspects: its “internal” view that says how the defined entity must be seen by **FoCaLize** (during its analyses) and its “external” view that says how this entity must be mapped onto target languages (during code generation) when it is used in a **FoCaLize** source code.

2.6.1 External type definitions

An external type definition starts like a regular type definition, i.e. by the type constructor’s name and possibly parameters: **type** (‘a, ‘b) t =). The body of the definition shows that it is an external by having the following shape:

```
type t =
  internal ...
  external ...
and ...
and ...
```

Attention: Be careful that the `and ...` are **not** other type definitions: they are optional and belong to the current external type definition. We will see later the meaning.

The internal clause

For a type definition, the `internal` clause shows at which **FoCaLize** type definition the body of the external definition corresponds. In fact this is equivalent to establish an alias between the structure of the external type and the structure of the type definition inside **FoCaLize**.

However, since we do not always want to really have this alias (i.e. an equivalence between the internal and external representations), this clause can be empty. In this case, the created type constructor will be fully abstract on **FoCaLize**’s side and the only way to make and manipulate values of this type will have to be provided via other external (values) definitions or via built-ins of the compiler.

So, when the `internal` clause is not empty, we said that is represented a type definition. Hence this clause can have 3 shapes: an alias, a sum or a record (the 3 kinds of type definitions in **FoCaLize**). For example (with the first case representing a fully abstract type as described above):

```

type int =
  internal (* Internal#int *)
  ...
;;

type foc_diag ('a) =
  internal alias ('a * 'a)
  ...
;;

type list ('a) =
  internal
  | []
  | ( :: ) ('a, list ('a))
  ...
;;

type foc_record ('a, 'b) =
  internal { hcode = int ; contents = ('b * 'a) }
  ...
;;

```

The first definition creates a type `int` that is fully abstract. Obviously, this one will be used magically by the internals of the compiler, so no need to have external definitions to manipulate its representation, this will be built-in in the compiler. Consult 2.6.1 for a discussion about this mechanism.

The second definition creates a parametrised type `foc_diag` that will internally be compatible with a pair of elements of the same type.

The third definition creates a parametrised type `list` that is made of 2 value constructors: `[]` with no argument and `::` with 2 arguments (not a tuple). Hence this corresponds to an internal representation of a sum type. We can see here how to define the lists like they are in `Coq` and `OCaml` to directly map them onto those of `Coq` and `OCaml`, without making any internal hack inside the compiler. We could have defined our custom lists by a regular type definition like

```

type list ('a) =
  | []
  | ( :: ) ('a, list ('a))
;;

```

but we wouldn't have been able to make so that constructors directly map onto their counterparts in `Coq` and `OCaml` (in effect, these constructors being non-regular identifiers, they would have been “stringified” like we saw in ??).

The fourth and last definition creates a parametrised type `foc_record` that is a record type with 2 fields: `hcode` and `contents`.

So, a question: but why to use external definitions to create such types ? It should be possible to define these sum and record types by a regular definition ! The answer, partially given about the `list` example is that this allows to control manually and explicitly the mapping of the type and of its components (fields and value constructors) into the target languages. We will see a clear example once we have ended the case of `foc_diag`.

To summarise, the `internal` clause controls how the type is seen on FoCaLize's side.

The external clause

The external clause tells how the **type constructor** (not its components like fields, value constructors : this will be done by the extra and `...` clauses described below in 2.6.1) must be **defined** into the target languages. In other words, what to emit to define the type constructor in the target languages.

Like in any `external` clause, we have an enumeration of mapping “language \mapsto external code”. Languages can syntactically be `coq`, `caml` or a string for other languages not internally handled by the FoCaLize compiler.

External code is an arbitrary string enclosed by { * and * } that will be emitted verbatim at code generation pass when the type constructor will have to be defined.

At code generation time, the shape of the definition in OCaml will look like: `type` followed by the enumeration of polymorphic type variables “`_focty_`” + type’s name = followed by the verbatim copy of the external code. The polymorphic type variables are named as usual in OCaml. If there are several then they comma-separated and enclosed between parentheses. Their name are , ‘a, then , ‘b, then , ‘c and if there are more than 26, it goes on with ‘aa, ‘ab etc.... In fact it is like printing their numbers in base 26, using lowercase letters as digits.

In Coq, it will look like: `Definition` followed the the type’s name + “`_t`” followed by the enumeration of the polymorphic type variables := followed by the verbatim copy of the external code. The polymorphic type variables are named by “`__var_`” + “a”, then “b”, then “c”. Like for OCaml the suffix is the variable’s number written in base 26. Hence the name of the 27th variable will be `__var_ab`. In Coq we must explicitly annotate variables with the type `Set`.

Hence, with the definitions we started in our example, the beginning of the generated code in OCaml and Coq will look like:

OCaml code for external definitions

```
type _focty_int = ...
type 'a _focty_foc_diag = ...
type 'a _focty_list = ...
type ('a, 'b) _focty_foc_record = ...
```

Coq code for external definitions

```
Definition foc_diag__t (__var_a : Set) := ...
Definition list__t (__var_a : Set) := ...
Definition foc_record__t (__var_a : Set) (__var_b : Set) :=
```

Continuing our previous example, we state the FoCaLize external type definitions:

External type definitions (2)

```
coq_require "coq_stubs" ;;

type int =
  internal (* Internal#int *)
  external
  | caml -> { * int *}
  | coq -> { * Z *}
;;

type foc_diag ('a) =
  internal alias ('a * 'a)
  external
  | caml -> { * ('a * 'a) *}
  | coq -> { * ((__var_a * __var_a)%type) *}
;;

type list ('a) =
  internal
  | []
  | ( :: ) ('a, list ('a))
  external
  | caml -> { * 'a list *}
  | coq -> { * (list __var_a) *} (* From the List module. *)
  ...
;;

type foc_record ('a, 'b) =
  internal { hcode = int ; contents = ('b * 'a) }
  external
  | caml -> { * ('b, 'a) Ml_stubs.bbt_record *}
  | coq -> { * coq_stubs.foc_record ['b, 'a] *}
```

```
...
;;
```

In the first definition we see that to define the `int` **type constructor** in OCaml, we will emit “int” and in Coq, we will emit “Z”. That’s because we want the `int` **type constructor** to be mapped onto these existing types of the target languages.

The second definition shows that we want `foc_diag` to be defined as a pair in OCaml and in Coq.

In the third definition, we say that lists are implemented in OCaml by its native lists and in Coq, by an existing data-type (the one provided by Coq’s module “List”).

Finally, in the last definition, we want to say that the type `foc_record` is implemented by a user-defined type. For instance, a record type in both OCaml and Coq. Due to the way the code is emitted we can’t write directly in the external code a record definition in each of the target languages: it would be syntactically incorrect. So, instead, we say that the type `foc_record` is implemented by a type name given in a other source file (one file for OCaml and one for Coq). We must remember that the generated definition in the target languages will correspond to an alias (i.e. of the form `type name = external-code` in OCaml, and `Definition name := external-code` in Coq), so we must put in the external code only things that will comply the target language’s syntax. For instance, specifying for the Coq language a definition like:

```
type foc_diag ('a) =
  internal alias ('a * 'a)
  external
  | caml -> { * ('a * 'a) * }
  | coq -> { * Record : Type :=
            mk_foc_diag (alpha : Set) {
              fst : alpha ;
              snd : alpha } * }
;;
```

would lead to a syntactically incorrect garbage rejected by Coq like:

```
Definition foc_diag__t (__var_a : Set) :=
  Record : Type :=
    mk_foc_diag (alpha : Set) {
      fst : alpha ;
      snd : alpha } .
```

Attention: In the sample code in FoCaLize we are studying, when we extended it, we added a first line that reads `coq_require "coq_stubs";;` This is needed to make so Coq can see definitions of the source file `Coq_stubs.v` in which we wrote our stubs for Coq. Since the FoCaLize compiler doesn’t analyse inside the external code, it can’t see that there is a dependency for Coq onto this source file, hence can’t add itself in the generated Coq file the `Require` directive. By adding this `coq_require` directive in the FoCaLize source code, we tell the compiler to add the corresponding `Require` directive in the generated Coq code.

Finally, one may note in this last definition that a FoCaLize `foc_record ('a, 'b)` is implemented by a `('b, 'a) Ml_stubs.bbt_record`. We inverted the parameters ! This means that so they will be in the generated definition (have a look in the sample generated code below) !

We now continue to inspect the generated code in both OCaml and Coq:

OCaml code for external definitions (2)

```
type _focty_int = int ;;
type 'a _focty_foc_diag = ('a * 'a) ;;
type 'a _focty_list = 'a list ;;
type ('a, 'b) _focty_foc_record = ('b, 'a) Ml_stubs.bbt_record ;;
```

and:

Coq code for external definitions (2)

```
Require coq_stubs.
```

```

Definition int__t := Z.
Definition foc_diag__t (__var_a : Set) := ((__var_a * __var_a)%type) .
Definition list__t (__var_a : Set) := (list __var_a) .
Definition foc_record__t (__var_a : Set) (__var_b : Set) :=
  coq_stubs.foc_record __var_b __var_a .

```

To fully understand the mapping mechanism, we must now see the stubs written for each target language.

Stub file ml_stubs.ml

```

type ('c, 'd) bbt_record = {
  bbt_hashing_code : int ;
  bbt_contents : ('c * 'd)
} ;;

```

Stub file coq_stubs.v

```

Require Export ZArith. (* To have type Z. *)

Record foc_record (param_a : Set) (param_b : Set) : Type :=
  mk_foc_record {
    hc : Z;
    conts : ((param_a * param_b)%type)
  }.

```

The extra and ... clauses

Finally, there are still two things to describe... We know how the type constructor must be seen internally, how it must be mapped onto target languages but we don't know yet on what to map the sum value constructors and the record fields names !

The extra and directive are here for this purpose and will be used only in case of sum or record type definitions. We now complete our external definitions:

External type definitions (3)

```

type list ('a) =
  internal
  | []
  | ( :: ) ('a, list ('a))
  external
  | caml -> { * 'a list *}
  | coq -> { * (list __var_a) *} (* From the List module. *)

and [] =
  | caml -> { * [] *}
  | coq -> { * List.nil *}

and ( :: ) =
  | caml -> { * ( :: ) *}
  | coq -> { * List.cons *}
;;

type foc_record ('a, 'b) =
  internal { hcode = int ; contents = ('b * 'a) }
  external
  | caml -> { * ('b, 'a) Ml_stubs.bbt_record *}
  | coq -> { * coq_stubs.foc_record __var_b __var_a *}

  and hcode =
  | caml -> { * Ml_stubs.bbt_hashing_code *}
  | coq -> { * coq_stubs.hc *}

  and contents =

```

```
| caml -> { * Ml_stubs.bbt_contents *}
| coq -> { * coq_stubs.conds *}
;;
```

We must note that for `foc_record`, we mapped the record fields onto the related fields present in our stubs source files. Obviously, an external type definition must consistently map the type constructor, its field label or value constructor to a definition existing in the target language. For instance, if we mapped `foc_record` to a type `t1`, and its field labels to labels of a type `t2` or to field names that do not exist in the target language, then the compilation of the generated code would fail. It is important to see that the compilation process on FoCaLize's side wouldn't point out any error: however Coqor/and OCaml would complain.

External type definitions and built-in types.

A propos de `basics.fcl`. Blabla à propos du fait que le nom `(int)` est justement bien senti car dans le compilateur, on utilise justement "int" comme nom de constructeur pour inférer le type des expressions entières. Etc...

2.6.2 External value definitions

Chapter 3

Compiler sources architecture

3.1 focalizec source tree

The compiler source tree is split into several directories and files described below. The root of the compiler sources is located in `focalize/focalizec`. All directories and files given below are relative to this root. In some of the directories is a sub-directory called `odoc`. It can be safely ignored and is only used when invoking `verb+make doc+` to store the `ocamldoc` output (HTML documentation extracted from the source code of **FoCaLize**). In the below enumeration (d x) stands for "directory" whose content is at *x* nesting level of the root (i.e. of `focalize/focalizec`) and (f) stands for "file".

- `Makefile` (f) : The toplevel Makefile building the compiler, the standard library, the extra libraries, the documentation generator, the **FoCaLize** documentations and the contributions. This Makefile indeed trigger the build process in all the deeper directories.
- `Makefile.common` (f) : Defines once for all the implicit rules and suffixes that will be used in deeper Makefiles.
- `.config_var` (f) : File generated during the "configure" process (invoked by the file `configure` below and that records the various things among installation paths, installed commands and tools, ...
- `Makefile.config` (f) : Defines once for all the commands according to the information the "configure" process recorded. It especially include the `.config_var` file that kept trace of what the "configure" process defined.
- `TAGS` (f) : Documentation file where developers are invited to note all the tags added to the development tree under CVS, with a description of the status of the development tree when the tag was set (or the reason why to put a tag).
- `TODO` (f) : More or less describes points that are still pending.
- `configure` (f) : Script used to detect available commands and tools, to ask the user where to install **FoCaLize** components, ... Parts of its output is stored in the above file `.config_var`.
- `doc_src` (d 1) : The directory containing all the documentations at destination of the users.
 - `Makefile` (f) : Makefile triggering the documentations build.
 - `html` (d 2) : The **FoCaLize** WEB site in HML format.
 - * `Includes` (d 3)
 - `aftertitle-eng.html` (f)
 - `aprestitre-fra.html` (f)

- avanttitre-fra.html (f)
- basdepage-fra.html (f)
- beforetitle-eng.html (f)
- bottomofpage-eng.html (f)
- copyright-eng.html (f)
- copyright-fra.html (f)
- doctype (f)
- endofpage-eng.html (f)
- findepage-fra.html (f)
- hautdepage-fra.html (f)
- htmlc-version.html (f)
- maquette-eng.html (f)
- maquette-fra.html (f)
- powered_by_caml.html (f)
- topage-eng.html (f)
- * Makefile (f)
- * Makefile.html (f)
- * images (d 3) : Directory containing images for the WEB site.
 - focal_picture.jpg (f) : A niiiice 3D picture done with Povray ☺.
- man (d 2) : Directory containing the “man” manual.
 - * Makefile (f)
 - * focalizec.env (f)
 - * focalizec.man (f) : “man” for focalizec.
 - * focalizedep.man (f) : “man” for focalizedep.
- tex (d 2) : Documentations in LaTeX format.
 - * Makefile (f)
 - * refman (d 3) : Directory containing the reference manual.
 - Makefile (f)
 - basic_concepts.tex (f)
 - bibli.bib (f) : Contains bibliography references.
 - building_species.tex (f)
 - compiler_err_msgs.tex (f) : About the focalizec compiler error messages.
 - compiler_opts.tex (f) : About the focalizec compiler command line options.
 - constructs_syntax.tex (f)
 - doc_gen.tex (f) : About the FoCaLize automated documentation generation (option focalize-doc of focalizec).
 - fullpage.sty (f)
 - glimpse.tex (f) : Short presentation of the language to give a first an rapid taste.
 - header_html_snapshot.ps (f)
 - introduction.tex (f)
 - lexical_conventions.tex (f) : About FoCaLize lexical conventions, description of the tokens and syntax.
 - macros.hva (f)
 - macros.tex (f) : LaTeX macros used in the reference manual.
 - mathml_snapshot.ps (f)

- `more_on_meths.tex` (f)
 - `motivations.tex` (f)
 - `output.tex` (f) : About what the **focalizec** compiler generates.
 - `pres_requir.tex` (f)
 - `proofs.tex` (f)
 - `refman.html` (f)
 - `refman.hva` (f)
 - `refman.pdf` (f)
 - `refman.tex` (f) : Entry point of the reference manual.
 - `syntaxdef.hva` (f)
 - `syntaxdef.sty` (f)
- `src` (d 1) : Root of the sources of **focalizec** and **focalizedep**.
 - `attic` (d) : Contains miscellaneous interesting parts of code that have been written one day, that are not used anymore, but that we didn't want to trash in case it could serve in the future.
 - * `ast.mli`, `lib_pp.ml`, `lib_pp.mli`, `misc.ml`, `new2old.ml`, `new2old.mli`, `oldsourcify.ml`, `oldsourcify.mli`, `printer.ml`, `printtree.ml`, `string_search_stuff.ml`
 - * May be more...
 - `basement` (d 2) : Contains the early basic bricks of the compiler.
 - * `Makefile` (f) : Trigger build in this directory.
 - * `configuration.ml` (f) : Manages version number (and by side effect the `-help` option output text) and the command line options flags.
 - * `configuration.mli` (f)
 - * `files.ml` (f) : Contains primitives dealing with files, taking into account search path, files suffixes, read/write object files, ...
 - * `files.mli` (f)
 - * `handy.ml` (f) : Various general functions, on lists, pretty-printers, font setting...
 - * `handy.mli` (f)
 - * `installation.ml` (f) : File automatically generated by the “configure” process and record as OCaml source, the various installation paths and commands the **focalizec** compiler need to know when dealing with **FoCaLize** source files.
 - * `location.ml` (f) : Defines the type of “locations”, i.e. point in a source file and gives primitives to work with them.
 - * `location.mli` (f)
 - * `miscHelpers.ml` (f) : Mostly contains 1 function used during several passes to bind formal names to their types from a type scheme and a list of formal names. May be could somewhere else to save one file...
 - * `miscHelpers.mli` (f)
 - * `parsetree.mli` (f) : The description of the AST.
 - * `parsetree_utils.ml` (f) : General utilities to process the AST.
 - * `parsetree_utils.mli` (f)
 - * `types.ml` (f) : The description of the types structure and operations to work with them. Because types are a complex structure with invariants, they are exported as opaque to prevent breaking these invariants. Hence, any function dealing with the intimate representation of a type must be in this file since this is the only location where this representation is visible.
 - * `types.mli` (f) :

- `ccodegen (d)` : Dedicated to the C code generation back-end. Maintained by Julien Blond and is not currently included in **FoCaLize**.
 - * ...not stable.
- `commoncodegen (d 2)` : Contains processing common to all target languages that is performed in any case before emitting the target code.
 - * `Makefile (f)` :
 - * `abstractions.ml (f)` : Performs the synthesis of λ -lifted things, summarising def and decl-dependencies and dependencies on collection parameters methods. It especially performs the final (complete) computation of dependencies on collection parameters, applying the various completion rules on the dependencies found previously by the rules [TYPE] and [BODY].
 - * `abstractions.mli (f)`
 - * `context.mli (f)` : The structure of the “context”, i.e. the structure inductively passed to each function during this pass and that group into one single record type all the information needed by the various functions. This a handy way to prevent from having numerous parameters to pass each time to the functions.
 - * `externals_generation_errs.ml (f)` : Exceptions that can be raised when generating code for “external” definitions, i.e. definitions that are not written in native **FoCaLize** language and used to interface with other programming languages.
 - * `externals_generation_errs.mli (f)`
 - * `minEnv.ml (f)` : Compute the “Coqminimal typing environment”.
 - * `minEnv.mli (f)`
 - * `misc_common.ml (f)` : Various type definitions and functions used in several points during this pass.
 - * `misc_common.mli (f)`
 - * `recursion.ml (f)` : Deals the the recursive functions processing.
 - * `recursion.mli (f)`
 - * `visUniverse.ml (f)` : Compute the “visible universe”.
 - * `visUniverse.mli (f)`
- `contributes (d 2)` : Contains contribution source codes written by users that are not developers of the compiler and its framework.
 - * `Makefile (f)`
 - * `automata (d 3)` : Hierarchical automata. Maintained by Philippe Ayrault.
 - `Makefile (f)`
 - `gen_def.fcl (f)`
 - `main.fcl (f)`
 - `request.fcl (f)`
 - `switch_automata.fcl (f)`
 - `switch_recovery_automata.fcl (f)`
 - `switch_recovery_normal_automata.fcl (f)`
 - `switch_recovery_reverse_automata.fcl (f)`
 - * `utils (d 3)` : Various utilities. Maintained by Philippe Ayrault.
 - `Makefile (f)`
 - `pair.fcl (f)`
 - `peano.fcl (f)`
 - * `voter (d 3)` : Model of a generic voter. Maintained by Philippe Ayrault.
 - `Makefile (f)`

- `etat_vote.fcl` (f)
 - `main.fcl` (f)
 - `num_capteur.fcl` (f)
 - `value.fcl` (f)
 - `vote.fcl` (f)
- `coqcodegen` (d 2) : Contains **Coq** code generation back-end.
 - * `FOCAL_COQ_MAPPINGS` (f) : Short (incomplete) description of how **FoCaLize** names are mapped onto **Coq** names in the generated source code.
 - * `Makefile` (f)
 - * `main_coq_generation.ml` (f) : Entry point of **Coq** code generation. Start code generation for a compilation unit, deals with toplevel entities (`let`, theorems, expressions and type definitions) and triggers processing of species, collections.
 - * `rec_let_gen.ml` (f) : Manages parts of the code generation for recursive functions with stuff dedicated to **Coq**.. Especially, generates the termination lemmas and transforms arguments of a recursive into a tuple.
 - * `rec_let_gen.mli` (f)
 - * `species_coq_generation.ml` (f) : Main part of code generation for species and collections.
 - * `species_coq_generation.mli` (f)
 - * `species_record_type_generation.ml` (f) : Deals with the generation of the record type representing species and collections. Also generates code for expressions.
 - * `species_record_type_generation.mli` (f)
 - * `type_coq_generation.ml` (f) : Deals with code generation for (toplevel) type definitions.
 - * `type_coq_generation.mli` (f)
- `devdocs` (d 2) : The current documentation explaining the compiler’s architecture and mechanisms.
 - * `foc2ocaml.tex`, `pending.txt` (f) : Oldies. Should disappear.
 - * `legacy.tex` (f) : The main **LaTeX**file. Compile it to get the current documentation.
 - * `macros.tex` (f) : Miscellaneous macros to make life easier ☺.
 - * `mathpartir.sty` : Inference rules package.
 - * `phd_changes.tex` : Things we changed, corrected, enhanced since Virgile Prevosto’s PhD Thesis.
- `docgen` (d 2) : Source for **focalizec** automated documentation generation (`-focalize-doc` option of the compiler) as XML files.
 - * `Makefile` (f) :
 - * `doc_lexer.mll` : Lexer to scan “@”-markups in a **FoCaLize** source code.
 - * `env_docgen.ml` : Contains the documentation environment mechanisms. This environment maps methods names onto some optional MathML and **LaTeX** code.
 - * `env_docgen.mli` (f)
 - * `focdoc.css` (f) : **FoCaLizeDoc**-XML style sheet.
 - * `focdoc.dtd` (f) :
 - * `focdoc.rnc` (f) :
 - * `focdoc.xsd` (f) :
 - * `focdoc2html.xsl` : Transforms some **FoCaLizeDoc**-XML into HTML + MathML.
 - * `focdoc2tex.xsl` (f) : Transforms some **FoCaLizeDoc**-XML into **LaTeX**.
 - * `main_docgen.ml` (f) : Engine extracting information from a **FoCaLize** source code to produce **FoCaLizeDoc**-XML.
 - * `main_docgen.mli` (f)

- * mmlctop2_0.xsl (f) : Transforms HTML + MathML into HTML.
- * proposition.xsl (f) : : Processing of logical expressions from FoCaLizeDoc-XML to HTML + MathML.
- * proposition2tex.xsl (f) : Processing of logical expressions from FoCaLizeDoc-XML to LaTeX.
- * utils_docgen.ml (f) : Various helpers used for XML production.
- * utils_docgen.mli (f)
- extlib (d 2) : Libraries higher level than the basic standard library. Especially contains formal calculus structures.
 - * Makefile (f)
 - * access_control (d 3) : Access control policies. Maintained by Lionel Habib and Mathieu Jaume.
 - Makefile (f)
 - access_control.fcl (f)
 - ensembles_finis.fcl (f)
 - hru.fcl (f)
 - rbac.fcl (f)
 - ticket.fcl (f)
 - tm (d 4)
 - graph.ml (f)
 - trust_management.fcl (f)
 - unix.fcl (f)
 - * algebra (d 3) : Formal calculus library. Maintained by Renaud Rioboo.
 - Makefile (f)
 - additive_law.fcl (f)
 - arrays.fcl (f)
 - arrays externals.v (f)
 - big_integers.fcl (f)
 - constants.fcl (f)
 - integers.fcl (f)
 - iterators.fcl (f)
 - multiplicative_law.fcl (f)
 - parse_poly.fcl (f)
 - polys_abstract.fcl (f)
 - product_structures.fcl (f)
 - quotient_structures.fcl (f)
 - randoms.fcl (f)
 - randoms externals.ml (f)
 - randoms externals.v (f)
 - rings_fields.fcl (f)
 - small_integers.fcl (f)
 - weak_structures.fcl (f)
 - weak_structures externals.ml (f)
 - weak_structures externals.v (f)
- focalizedep (d 2) : The dependencies generator to create Makefiles.
 - * Makefile (f)

- * `directive_lexer.mll` (f) : Lexer to scan open and use directives in a FoCaLize source.
- * `make_depend.ml` (f) : Source of the generator.
- `mlcodegen` (d 2) : Contains OCaml code generation back-end.
 - * `FOCAL_ML_MAPPINGS` (f) : Short (incomplete) description of how FoCaLize names are mapped onto OCaml names in the generated source code.
 - * `Makefile` (f)
 - * `base_exprs_ml_generation.ml` (f)
 - * `base_exprs_ml_generation.mli` (f)
 - * `main_ml_generation.ml` (f)
 - * `main_ml_generation.mli` (f)
 - * `misc_ml_generation.ml` (f)
 - * `misc_ml_generation.mli` (f)
 - * `species_ml_generation.ml` (f)
 - * `species_ml_generation.mli` (f)
 - * `type_ml_generation.ml` (f)
 - * `type_ml_generation.mli` (f)
- `parser` (d 2) : Contains the lexical and syntactic analysers to process FoCaLize source code.
 - * `Makefile` (f)
 - * `dump_ptree.ml` (f) : Dumps the AST structure of a file in raw text mode. Used for debugging purpose.
 - * `dump_ptree.mli` (f)
 - * `lex_file.ml` (f) : Initial attempt to have a small “main” to check the behaviour of the lexer on a file at the early stages of development. This is not used anymore.
 - * `lexer.mll` (f)
 - * `lexer.spec` (f) : Trace of thoughts we had all along the time. Initially contained ideas about the language syntax, (at lexical level) to make it smooth.
 - * `parse_file.ml` (f) : Initial attempt to have a small “main” to check the behaviour of the parser on a file at the early stages of development. This is not used anymore.
 - * `parse_file.mli` (f)
 - * `parser.mly` (f) : The parser description in `ocamlyacc`.
 - * `parser.spec` (f) : Trace of thoughts we had all along the time. Initially contained ideas about the language syntax, (at syntactic level) to make it smooth. Next other ideas were added, beyond syntax, more oriented toward the AST structure.
 - * `sourcify.ml` (f) : Dumps the AST structure of a file in FoCaLize syntax. Gives back a source code from a parsed code. This is mostly useful for debugging purpose. May be used by customers to pretty-print their source, but I don’t recommend. This more specially serves to report pieces of code in a good-looking form in error messages. Each time we need to tell the user something involving a piece of code, we pretty-print it with functions provided here.
 - * `sourcify.mli` (f)
 - * `sourcify_token.ml` (f) : Not used anymore. Was used to test the lexer at the early stages of development. It was used to print the found token.
 - * `test` (d 3) : Oldies originally used to test the lexer/parser in the early times. No used anymore.
 - `sets_orders.fcl` (f) : First translation of a file of the standard library used to test the lexer/parser. Not used anymore.
- `scoper` (d 2) : Old stuff. Was discarded a long time ago. The directory is empty by the way.

- `stdlib (d 2)` : The standard library. Most of these sources are maintained by Renaud Rioboo. A few ones (basics and built-ins) are low-level code close to the compiler and maintained by the core compiler development team.
 - * `Makefile (f)`
 - * `basics.fcl (f)` : Basic bricks and internal-related stuff. Contains the primitive type definitions and some very basic functions for **FoCaLize**.
 - * `coq_builtins.v (f)` : Basic bricks and internal-related stuff especially dedicated to **Coq** code.
 - * `generic_proof_cases.v (f)` : Contains built-in stuff for **Coq** about built-in lists and some tactics.
 - * `lattices.fcl (f)`
 - * `ml_builtins.ml (f)` : Basic bricks and internal-related stuff especially dedicated to **OCaml** code.
 - * `orders.fcl (f)`
 - * `orders_and_lattices.fcl (f)`
 - * `products.fcl (f)`
 - * `quotients.fcl (f)`
 - * `sets.fcl (f)`
 - * `sets_externals.ml (f)` : External definitions to link for **OCaml** related to `sets.fcl`.
 - * `sets_orders.fcl (f)`
 - * `sets_orders_externals.ml (f)` : External definitions to link for **OCaml** related to `sets_orders.fcl`.
 - * `strict_orders.fcl (f)`
 - * `sums.fcl (f)`
 - * `wellfounded.fcl (f)` : Define well foundation, termination orders for recursive function definitions for **Coq**.
 - * `wellfounded_externals.v (f)` : External definitions to link for **OCaml** related to `wellfounded.fcl`.
- `toplevel (d 2)`
 - * `Makefile (f)`
 - * `exc_wrapper.ml (f)` : Firewall designed to recover all the exceptions that can be raised during a source compilation and issues the related error message. Roughly, this code wraps the main call to the compilation engine.
 - * `focalizec.ml (f)` : The compiler entry point.
 - * `focalizec.mli (f)`
 - * `fodump.ml (f)` : For debug only, dumps (partially) the content of a **FoCaLize** object file (“fo” file).
- `typing (d 2)` : Performs the type-checking of the language, normal form of species, checks well-formation of species, compute def and decl-dependencies, initiate computation of dependencies on collection parameters’ methods, resolves inheritance.
 - * `Makefile (f)`
 - * `ast_equal.ml (f)` : Implements equality test between logical expressions (indeed, between expressions since logical statements fully embed expressions).
 - * `ast_equal.mli (f)`
 - * `depGraphData.mli (f)` : Defines the structure of the dependencies graph used to compute well-formation from def and decl-dependencies.
 - * `dep_analysis.ml (f)` : Handles the dependencies analyses on methods of `Self`, i.e. def and decl-dependencies.
 - * `dep_analysis.mli (f)`

- * `env.ml (f)` : Structure of the environments used all along the compilation. Contains a generic environment structure, the specialised scoping environment the specialised typing environment, the specialised **OCaml** code generation environment and the specialised **Coq** code generation environment. All these environments are instantiations of the generic environment structure. Also contains data-structures used from type-checking up to code generation to record the various information about analysed species, collections, methods, types, ... Some of these data-structures will appear in later passes, picked-up from these environments.
- * `env.mli (f)`
- * `infer.ml` : Core engine performing type-checking, inheritance resolution, normal form of species, check of well-formation, def and decl-dependencies computation and triggers the initial computation of dependencies on collection parameters' methods.
- * `infer.mli (f)`
- * `param_dep_analysis.ml (f)` : Handles the initial computation of dependencies on collection parameters' methods. The computed dependencies will have to be completed later in the next pass.
- * `param_dep_analysis.mli (f)`
- * `scoping.ml (f)` : Performs scoping analysis.
- * `scoping.mli`
- * `substColl.ml (f)` : Performs substitution of a collection (name/carrier) by another one or `Self` in an AST.
- * `substColl.mli (f)`
- * `substExpr.ml (f)` : Performs substitution of an expression (i.e. `Parsetree.expr`) by another in an AST.
- * `substExpr.mli (f)`
- `tests (d 1)` : Various little tests we wrote to shake the compiler or to ensure that some particular features/processing required by the compiler were really working. This code is most of the time meaningless and only design to target a particular point of the compilation process. The naming scheme is: a source file name starting by "`ko__`" must lead to an error (an error message, not a failure of the compiler), a source file name starting by "`ok__`" must be accepted by the compiler and lead to effective code.
 - `Makefile (f)`
 - `ko__bad_self_use.fcl (f)`
 - `ko__param_toy.fcl (f)`
 - `ko__test_error.fcl (f)`
 - `ko__test_rec.fcl (f)`
 - `ok__baby_toy.fcl (f)` : A bit of everything, without any order.
 - `ok__baby_toy_externals.ml` : External code to link for **OCaml** related to `ok__baby_toy.fcl`.
 - `ok__caveat.fcl (f)` : Illustrates the pitfall of sum type constructors that have **1** argument that is a tuple or **several** arguments but are hardly different from the syntax point of view.
 - `ok__coll_outside.fcl (f)` : Example showing how now use a collection defined outside the current one (i.e. the used one not a parameter) in a collection or a species.
 - `ok__definition_72_rule_PRM.fcl (f)` : Illustrates the need for rule **PRM** in definition 72 page 153 in Virgile Prevosto's PhD.
 - `ok__in_example.fcl (f)` : Example showing how now use the `in` parameter without allowing their type to be anymore a "`ml type`".
 - `ok__in_example2.fcl (f)` : Same purpose than for `ok__in_example.fcl`.

- `ok__list.fcl (f)` : Example showing how to make lists as species in **FoCaLize**. It also illustrates the need for the extra unit argument to the collection generator “`collection_create`” in case it has no arguments, what would prevent **OCaml** from generalising the type of this generator. This example must pass in **OCaml** but is not yet accepted in **Coq**.
- `ok__multiple_inherit.fcl (f)` : Used to track the provenance of methods in case of multiple inheritance.
- `ok__need_inspect_self.fcl (f)` : Example showing how now use the need to inspect the structure of representation while computing the “`used_species_parameters_ty`” in the case where a method has a def-dependency on `Self`.
- `ok__need_re_ordering.fcl (f)` : Example showing the need of the final re-organisation of methods due to the collapsing procedure of properties and proof ofs.
- `ok__odd_even.fcl (f)` : Example showing simple mutually recursive methods that must pass for **OCaml** code generation. Note that **Coq** code generation does not yet handle mutual recursion.
- `ok__phd_def_deps.fcl (f)` : Example of Virgile Prevosto’s Phd, section 3.9.6, page 56. Illustrates the need for the erasing procedure.
- `ok__phd_meths_gen.fcl (f)` : Example from Virgile Prevosto’s Phd, section 6.4.3, page 115.
- `ok__phd_sample.fcl (f)` : The initial example given in Virgile Prevosto’s Phd, section 2.2.2 starting page 14.
- `ok__scoping_tricky.fcl (f)` : Example showing scoping occurrences of a same name in case where this name is not recursively defined. Combines the stuff with late-binding.
- `ok__term_measure.fcl (f)` : Is designed to be a successful use of termination proofs. Still doesn’t pass.
- `ok__toplevel_odd_even.fcl (f)` : Example showing simple mutually recursive toplevel functions that must pass for **OCaml** code generation. Note that **Coq** code generation does not yet handle mutual recursion.
- `ok__torture_params.fcl (f)` : Example showing how to torture parametrised species. It exhibits various non-trivial cases that must pass and lead to effective **OCamlCoq** code. These examples make heavy use of `in`, `is` parameters and inheritance to shake the compiler’s instantiation of parameters during inheritance.

3.2 Other tools

Aside **focalizec** itself and its library, 2 others tools explicitly dedicated to the **FoCaLize** packages exist.

3.2.1 zenon

Maintained by Damien Doliger, he is the man in the place to describe ☺.

3.2.2 zvtov

Maintained by Damien Doliger, he is the man in the place to describe ☺.

3.3 Passes and directories

Each directory described above roughly corresponds to one pass of the compiler except the directory `src/basement` which contains basic stuff used a bit everywhere. The order of the tasks performed at compile-time can be mapped on the source directories as follows:

1. `src/toplevel` : Entry point of the compiler, performing I/O and administrative tasks to initiate the compilation process.
2. `src/parser` : Lex and parse the source code
3. `src/typing` : Scopes the parsed source (i.e. the primary AST, hence leading to a “scoped” AST), then type-check the scoped AST (hence leading to a “typed” AST), resolves inheritance, compute def and decl-dependencies, ensure well-formation and performs a first partial computation of dependencies on collection parameters’ methods.
4. `src/commoncodegen` : Compute final abstractions (i.e. λ -liftings) due to def and decl-dependencies and dependencies on collection parameters’ methods. This process is in fact done once for OCaml code generation and once for Coq code generation (obviously if code generation for each language is enabled via the command line options of the compiler). The OCaml code production is done first is the Coq one is also requested.
5. `src/mlcodegen` : Emits the OCaml code if requested.
6. `src/commoncodegen` : As describe above but for Coq code generation if requested.
7. `src/coqcodegen` : Emits the Coq code if requested.

Libraries, standard (`src/stdlib`) and other libraries (`src/extlib`) are compiled once, when the compiler is built. Then they get installed according to the user’s configuration and not touched anymore. However, when compiling a FoCaLize program, they will be used if references are done to entities they host.

During the compilation of the FoCaLize source, only object files of the libraries are needed. OCaml and Coq files of the libraries will be used once `focalizec` has output the generated code, in order to produce the whole OCaml executable or Coq model.

Chapter 4

Lexing / parsing

4.1 Lexing

The lexing process is performed as usual, by a lexer created by `ocamllex`. The description of the lexer is located in `src/parser/lexer.mll`. The structure of this file is like any regular lexer for a realistic language.

The keywords of the language is stored in a hash-table to prevent the automaton from being too big. Each time a stream of alpha-numeric characters that can be either an identifier or a keyword is found, we lookup in this hash-table. If the word made of this stream of characters belongs to the hash-table, then we return the corresponding token, else we return an identifier based on the form of the word (capitalised or not).

As any lexer, each time it is called (by the lexer), it returns one and only one lexem.

4.2 Parsing

The lexing process is performed as usual, by a lexer created by `ocamlyacc`. The description of the parser is located in `src/parser/parser.mly`. The structure of this file is like any regular parser for a realistic language. The parser doesn't try to implements recovery on error, hence, it describes the syntax of the language without any addition (conversely to OCaml or gcc's parsers).

The important rule applied in the parser is that at each AST node it creates, it record the corresponding location (extend) in the source file and the corresponding (optional) documentation (i.e. special comments kept in the AST). This mechanism is performed by a set of basic functions with names derivated from `mk` (`mk_loc`, `mk_doc_elem`, `mk_doc`, `mk_local_ident`, `mk`, ...). This especially means that one never must create an AST node by hand. Any created AST node must be created via these basic functions.

The parser, returns a complete AST corresponding to the parse of the whole submitted source file. It currently doesn't have an entry rule returning only an AST for one definition. This especially means that the result of the parsing is always an AST node of the form `Parsetree.file`.

Chapter 5

The environments structure

All along the compilation pass, we need to keep trace of various information about compiled entities (methods, types, identifiers, ...). This is done by a kind of association list, mapping a name of entity onto an information.

Depending on the compilation passe, the nature of the recorded information is different. However, the basis of name mapping is always the same. For this reason, instead of building several times the name mapping system, we decided to create a structure of generic environments which can be instantiated by specific information to record for each compilation pass.

Environments implementation is located in the file `src/typing/env.ml`.

5.1 The generic environment

5.1.1 Environment “recording” structure

As previously stated, the core of an environment is to map names onto information. In **FoCaLize** names can designate several types of entities:

- Sum type value constructors (e.g. `None`, `Some`).
- Record type field labels.
- Types constructors (e.g. `int`, `option`).
- Values.
- Species.

To ensure there is no conflicts between these different types of entities, i.e. to be allowed to give a same name to a record types field and to a type constructor or a value identifier, an environment will keep separate name-spaces for each type of entity.

As we stated before, an environment maps a name (the **key**) onto an information (the **value**). Hence, the **key** of an environment being a name, it will be mapped onto a `Parsetree.vname`. Since we want environments to record different values (to be polymorphic in fact), the **value** will be a different type variable for each name-space.

Hence, the generic environments have type:

To create a module system, we need to wrap this core structure inside a module providing access to this structure, i.e. search the **value** bound to a **key**: `find` and add binding of a **key** to a **value**: `add`. Obviously, we need these 2 functions for each name-space.

```

type ('a, 'b, 'c, 'd, 'e) generic_env = {
  constructors : (Parsetree.constructor_name * 'a binding_origin) list ;
  labels : (Parsetree.vname * 'b binding_origin) list ;
  types : (Parsetree.vname * 'c binding_origin) list ;
  values : (Parsetree.vname * 'd binding_origin) list ;
  species : (Parsetree.vname * 'e binding_origin) list
}

```

5.1.2 Principle of making an environment

We would like to directly create a functor taking as argument a module whose signature implements the types of bound information in each name-space for an environment and gives back a module providing the functions `find` and `add` for each name-space, in this environment. The idea is then to apply this functor to a set of various modules to get the scoping environment, the typing environment, the OCaml and the Coq code generation environments.

This simplistic view fails because of the notion of “modules”, i.e. in FoCaLize compilation units.

In effect, since compilation units host definitions, they can be seen as modules. Hence we need an extra function to search inside “modules”. This will especially serve to look-up names qualified by the `#`-notation. For example the identifier `basics!int` is bound in the module `basics` by the name `int`. This `find_module` function doesn’t need to be visible in our generic environments since it only serves for internal purpose. It must conceptual take a module name, an environment and return the “sub”-environment composed of all the definitions hosted by the module. This `find_module` function is then dependant of the type of the the name-space in which to look-up in the managed environment. On must have 1 `find_module` for when we look-up for values, one for when we look-up for types, one for sum type constructors, one for record field labels, etc... The problem is that “creating” the “sub”-environment from the informations contained in a module depend on the structure of information recorded in the environment. This means that we can’t consider these informations as anymore polymorphic since we know to know their structure to build the “sub”-environment.

For this reason, we proceed in two steps, i.e. two functors. One, `EMAccess`, will provide the “way to access” the information kept as **values** in the environment. The second (`Make`) will take a module produced by the previous one and glue the structure of the environment (i.e. in fact the association list) with the access primitives provided.

5.1.3 EMAccess : accessing functions for an environment

module is required to have the signature:

The fields type definitions `constructor_bound_data`, `label_bound_data`, `type_bound_data`, `value_bound_data` and `species_bound_data` respectively represent the information the environment maps onto names of sum type value constructors, record field labels, type constructors, values and species.

Next come the `find_module` function that looks for a “module” name (the `Types.fname` option, we will see later the reason of the option) in the current environment and returns the environment composed of all the definitions present in this module (compilation unit). For technical reason, some extra arguments are passed to this function and we will explain their presence later.

Next come the `pervasives` value that is the initial (may non-empty) environment containing built-in bindings that are needed. Note that this environment may be the empty environment (i.e. containing no binding) is nothing has to exist in a built-in way.

Next come a the function `make_value_env_from_species_methods` whose purpose can be understood once the module system is understood. Basically, this function must create an environment, populating the values name-space with information extracted from the methods of a species.

Finally, the function `post_process_method_value_binding` can also be understood via the module system mechanism. This function takes a collection name, an information bound to a value and is applied on this information. This function is called by `find_value` to post-process the information bound to a value name if needed.


```

module type EnvModuleAccessSig =
  type constructor_bound_data
  type label_bound_data
  type type_bound_data
  type value_bound_data
  type species_bound_data
  val find_module :
    loc: Location.t -> current_unit: Types.fname -> Types.fname option ->
      (constructor_bound_data, label_bound_data, type_bound_data,
       value_bound_data, species_bound_data)
    generic_env ->
      (constructor_bound_data, label_bound_data, type_bound_data,
       value_bound_data, species_bound_data)
    generic_env
  val pervasives : unit ->
    (constructor_bound_data, label_bound_data, type_bound_data,
     value_bound_data, species_bound_data)
    generic_env
  val make_value_env_from_species_methods :
    Parsetree.qualified_vname -> species_bound_data ->
      (constructor_bound_data, label_bound_data, type_bound_data,
       value_bound_data, species_bound_data)
    generic_env
  val post_process_method_value_binding :
    Parsetree.qualified_vname -> value_bound_data -> value_bound_data
end

```

Table 5.1: Sample code for EMAccess signature

For sake of simplicity, we decide to group the types definitions representing information bound for each name-space of an environment in a module. This is not mandatory but allows a better structure of the code.

5.1.4 Make-ing the environment

This functor finally create the final environment structure, linking the access functions provided by its argument (of interface EMAccess) and the basic structure of generic environment (('a, 'b, 'c, 'd, 'e) generic_env).

This functor must create a module whose signature contains an abstract type representing the environment, an abstract value representing the empty environment (i.e. with no binding), an abstract value representing the “pervasives” environment and finally, for each name-space a search function and an extension function (i.e. a function that adds a binding to an environment, then returning this environment with the binding “in front”). This means that an environment (dedicated to a “Blabla” processing) will have a signature like (forget the noisy arguments we spoke about, like loc, current_unit, we will check them in detail later) :

We address now some remarks about the Make functor. This functor provides the environment access functions that do not depends on the structure of data stored in the environment. However, it uses the functions that depends on that are provided by its argument module.

As a general scheme, for each name-space xxx, we have 3 functions:

- add_xxx : Adds a binding to the environment (exported function).
- find_xxx : Entry point to find the information bound to an identifier (exported function).
- find_xxx_vname : Find the information bound to a Parsetree.vname (not exported). This function is just an internal used by find_xxx_vname once it decomposed the initially looked-up identifier into a primitive Parsetree.vname.

```

module BlablaEnv :
sig
  type t
  val empty : unit -> t
  val pervasives : unit -> t

  val add_value :
    Parsetree.vname -> BlablaInformation.value_binding_info -> t -> t
  val find_value :
    loc: Location.t -> current_unit: Types.fname ->
      current_species_name: string option -> Parsetree.expr_ident -> t ->
      BlablaInformation.value_binding_info

  val add_constructor : Parsetree.constructor_name -> Types.fname -> t -> t
  val find_constructor :
    loc: Location.t -> current_unit: Types.fname ->
      Parsetree.constructor_ident -> t -> Types.fname

  val add_label : Parsetree.vname -> Types.fname -> t -> t
  val find_label :
    loc: Location.t -> current_unit: Types.fname -> Parsetree.label_ident ->
      t -> Types.fname

  val add_type :
    loc: Location.t -> Parsetree.vname ->
      BlablaInformation.type_binding_info ->
      t -> t
  val find_type :
    loc: Location.t -> current_unit: Types.fname -> Parsetree.ident -> t ->
      BlablaInformation.type_binding_info

  val add_species :
    loc: Location.t -> Parsetree.vname ->
      BlablaInformation.species_binding_info -> t -> t
  val find_species :
    loc: Location.t -> current_unit: Types.fname -> Parsetree.ident ->
      t -> BlablaInformation.species_binding_info
end

```

Adding a binding

All the environment extension functions (add_xxx) are quite simple, they just add a binding to the association list in field of the environment related to the right name-space. One may note that an added binding is always tagged `BO_absolute`. This means that the binding comes in the environment from the current compilation unit, opposite as the tag `BO_opened` that serves to identify bindings present in the environment due to an open directive.

Looking for a binding (except for values)

Look-up functions are more complex, especially the one looking for values. We now describe the general look-up mechanism that is exactly the one used for `find_label`, `find_constructor` and `find_type`.

The first and simplest case is when the looked-up identifier doesn't have any qualification. In this case, it must trivially be searched in the related association list of the current environment.

The second case involves a qualified identifier and is more complex. The principle is to split the looked-up name into a scope specifier (a qualification) and a simple name. For instance, `foo` has no scope specifier and a simple name equal to "foo". Conversely, `basics#bar` has the scope specifier "basics" and the simple name "bar". Then, from the scope specifier (i.e. in fact an "module" name), we try to load the ("sub")-environment of this module. If the specifier is `None`, then we will get back the current environment. It is in this environment that we will perform the search (like in the first case described above since the obtained identifier doesn't have anymore qualification). Now, the point is to

check if we are allowed to accept to find a binding induced by an open directive. This is usually the case except if the identifier has an explicit qualification equal to `None` or `Some (file)` where `file` is the current compilation unit.

The first point allows to recover an identifier defined in the **current compilation unit** even if some opened modules imported identifiers wearing the same name. This features strongly relies on the fact that the parser **must** parse qualified identifiers like `#foo` as a **global** one with `None` as qualifier. In other words, such an identifier means “the related definition being at toplevel in the current compilation unit”.

The second point simply states that if we are looking for a qualified identifier being in the current compilation unit, then it must not be searched among identifiers imported by opened modules.

Based on this information, we simply look-up in the association list to find the related binding.

```
( * ***** *)
(** {b Descr} : Looks-up for an [ident] inside the types environment.

    {b Rem} : Exported outside this module. *)
( * ***** *)
let rec find_type ~loc ~current_unit type_ident (env : t) =
  match type_ident.Parsetree.ast_desc with
  | Parsetree.I_local vname ->
    ( * No explicit scoping information was provided, hence * )
    ( * opened modules bindings are acceptable. *)
    find_type_vname ~loc ~allow_opened: true vname env
  | Parsetree.I_global qvname ->
    let (opt_scope, vname) = opt_scope_vname qvname in
    let env' = EAccess.find_module ~loc ~current_unit opt_scope env in
    ( * Check if the lookup can return something *)
    ( * coming from an opened module. *)
    let allow_opened = allow_opened_p current_unit opt_scope in
    find_type_vname ~loc ~allow_opened vname env'

( * ***** *)
(** {b Descr} : Looks-up for a [vname] inside the types environment.

    {b Rem} : Not exported outside this module. *)
( * ***** *)
and find_type_vname ~loc ~allow_opened vname (env : t) =
  try env_list_assoc ~allow_opened vname env.types with
  | Not_found -> raise (Unbound_type (vname, loc))
```

Table 5.2: Sample code for simple look-up function

Looking for a binding for values

This case is more subtle since it involves more kinds of identifiers, especially because of the “!-notation”. Processing for local and global identifiers (`Parsetree.I_local` and `Parsetree.I_global`) are the same as previously described.

We must then address the case of finding a binding for a method with the “!”-notation (i.e. `Parsetree.EI_method`). There are two different cases.

1. There is no species qualification before the `!`, or the specified species is `Self`. In this case then the searched identifier must belong to the inheritance of `Self`. First, this means that opened stuff is forbidden. Next, because the values bucket is so that inherited methods and our methods belong to it, we just have to search for the `vname` inside the current environment.
2. There remain the case where there is an explicit species qualifier different of `Self`. We still have two cases.

- (a) The specified species is the current species (not `Self`, the real name of the current species). This may arise because of substitution performed during typechecking in species signatures. In this case, the search is obviously the same than the previous case since it is really like the case where the qualifier is `Self`.
- (b) In the other cases, we must recover the environment in where to search (i.e. the environment compound of the definitions present in the species), according to if the species is qualified by a module name. Note that in this environment, all the imported bindings are tagged `BO_absolute`. This tag allows to make the difference between bindings introduced by the definitions of the current compilation unit and those brought by opened modules. So if the species is hosted in a module (i.e. compilation unit), we first get this module's environment otherwise we keep the current environment. Then we look for the species/collection definition. We transform all its definitions into an environment via the function `EMAccess.make_value_env_from_species_methods`. Finally in this environment, we look for the binding of the method name.

This should be sufficient, but in case of scoping environment, we still have to modify the value bound to our identifier. For this reason, we have an extra function provided by the `EMAccess` module that will be finally applied on the obtained value. Currently, in the other environments, this function is the identity (do nothing on the argument) since we only found a job to do in case of the scoping environment. We will describe what this function really does in the case of the scoping environment in its dedicated section.

5.2 Scoping environment

The scoping environment provides information required to compute the scope of an identifier. In other words, it enables to state the extend in the program where an identifier is visible. The aim is to prevent name confusion and to ensure that names are identified by (i.e. related to) only one definition.

5.2.1 The `ScopeInformation` module

We first look at the information bound to each name in the different name-spaces.

Sum type value constructors

Since these identifiers are always introduced by type definitions that are at toplevel, we only need to remind in which compilation unit they were introduced, hence hosted. Then a constructor will be bound in the environment to a compilation unit name.

Record type field names

For the same reason than for the sum type value constructors, Record type field names are bound to a compilation unit name.

Values

Information bound to value identifiers is more complex since it must depict the different cases of identifiers.

- `SBI_file` The identifier is at toplevel of a file (including the current file). We record the file name.
- `SBI_method_of_self` The identifier is a method implicitly of `Self`.
- `SBI_method_of_coll` The identifier is a method explicitly of a collection. We record the fully qualified name of the collection.
Attention: while inserting a method at its definition point in the environment, it must always be tagged with `SBI_method_of_self`. The tag `SBI_method_of_coll` can only be returned by `find_value` who may perform a change on the fly if required.
- `SBI_local` The identifier is locally bound (`let` or function parameter).

Types

Type constructors may be separated in two categories:

- `TBI_builtin_or_var` The type identifier is either a type variable name (‘a for instance) or a built-in type. In these two cases, the constructor is not hosted in a type definition in a particular compilation unit. In effect, type variables arise during the type-checking process and are not attached to a particular type definition. In fact, a type variable **is not** a type constructor and only this justifies the fact it doesn’t belong to a particular compilation unit.
On the other side, we allow the possibility to have built-in type constructors in the `FoCaLize` language. This means that we can have type constructors related to no type definition written as `FoCaLize`. In this case, the compiler must deal internally with this type constructor. Currently this feature is not used since even basic types constructors like `int`, `bool`, `char`, ... have a regular `FoCaLize` (external) definition.
- `TBI_defined_in` The identifier is a type constructor name defined at toplevel by a type definition in a file. We record the hosting compilation unit.

Species

Data recorded for species is the most complex. It must depict the scope of the species name itself, but also give information about the methods and parameters available through this species. For this reason, we have a record grouping several things.

First, `(spbi_methods` records the list of **all** the methods names owned by the species, **including those added by inheritance**. Methods however appear only once and are ordered from the most recent ancestor are in head of the list. In case of multiple inheritance, we consider that ancestors are older from left to right.

Next, we record information about the species’s parameters (`spbi_params_kind`). For each parameter we simple record if it is a collection (`SPK_is`) or entity (`SPK_in`) parameter.

Finally (`spbi_scope`), we record if the current species is defined at toplevel in a compilation unit (`SPBI_file`) or is a collection parameter of another species (`SPBI_parameter`).

5.2.2 The ScopingEMAccess module

This module provides the functions we previously stated to help the generic environment module to access the information stored in the environment. We have 2 functions to inspect.

The function `make_value_env_from_species_methods` simply takes the list of the method names of the species and add them as methods “**of the species**” passed as argument (usage of `SBI_method_of_coll`) in the **values** name-space. Here the insertion explicitly shows that the methods inserted in the environment are those of a particular species, not of `Self`. Moreover, the methods are tagged as `BO_absolute` to say that by default they do not come from an “opened” module since we consider that may be the species comes from an “opened” module, but not its methods who are hosted **in** the species.

The function `post_process_method_value_binding` is important for the scoping environment (and in fact, currently we have such a function in the interface of `EMAccess` only because we need to make a special job in the case of the scoping environment). Its job consists in changing the tag of the methods of the species from `SBI_method_of_self` to `SBI_method_of_coll`. In effect when we create a species, its methods are tagged as being “of `Self`”. But when we load the methods of this species in an environment we must say that these methods are not belonging to the currently processed species but are belonging to the species from which we loaded the methods in our environment.

For example, let’s examine the following source code: When we are scoping in the Species `S` the method `meth1` we encounter the expression (identifier) `P!meth2`. To scope this identifier we need to get the list (i.e. a “sub”-environment) containing the methods of `P` in order to search for the name `meth2` among them. When `P` was “created” (in fact when it was scoped) we inserted in its scoping description the fact that it had a method `meth2 ... of Self` (yep, inside `P`, `meth2` is really a method of `Self`). So it was tagged with `SBI_method_of_self`. So if we insert

```

species S (P is ...) =
  let meth1 (x) = ... P!meth2 ... ;
end ;;
}

```

straight-line this information in our environment, while scoping our species *S* we will see that there exists a method *meth2 ...* of *Self*, i.e. of *S* which is wrong. For this reason, we must change the tag of *meth2* before inserting the binding in our environment.

5.3 Typing environment

The typing environment provides information required to type-check the program, i.e. to infer types where they are not written, to check that explicitly written types are correct and to annotate the AST with the type found type of each AST node. Moreover, FoCaLize requires more than type-checking “à la” ML. We will also record information about dependencies.

5.3.1 The `TypeInformation` module

We first look at the information bound to each name in the different name-spaces. We will speak here of *type* and *type scheme*. The difference between them will be exposed later while presenting the type-checking process. Let’s intuitively say that a *type scheme* is a “template” from which one can extract a *type* by “instanciation” of the scheme. So in **expressions**, only *types* are present, *type schemes* are bound to **definitions**.

Sum type value constructors

A sum type value constructor is considered as a function taking as many parameters as they have arguments and returning a value whose type is the one hosting the constructor (i.e. the current type definition). For example: *leads*

```

type t =
  | A
  | B of (int * bool)
  | C of (int, bool)
;;

```

to 3 value constructors of types: *A*: *t*, *B* : (*int* * *bool*) -> *t* and *C*: *int* -> *bool* -> *t*. Note the difference between *B* and *C*: the first one take 1 argument that is a pair, the second take 2 arguments.

So, for each constructor of a sum type, we record its type scheme (*ctr_scheme*) and if it has arguments or not (*ctr_arity*, that can be *CA_zero* or *CA_some*).

Later, to type-checking an expression using a constructor applied to some arguments, we will simply simulate a regular function application and type-check this application like any other one. That the reason why we also need to know if the constructor has argument(s) or not since if it has none, there is no application to simulate: the constructor is not a function but a value with the right type directly.

Record type field names

In the same idea than for sum type value constructors, a record type field label will be considered as a function taking 1 argument whose type is the type of the field and returning a value whose type is the one hosting the field label (i.e. the current type definition). For example: *leads* to 2 value field labels of types: *lb11*: *int* -> *t* and *lb12* : *string* -> *t*.

```
type t = {  
  lbl1 : int ;  
  lbl2 : string }  
;;
```

So, for each field label, we simply record its type scheme (`field_scheme`) . We also record if the field is mutable or not (`field_mut`) but this features is not used (for extension purpose) since **FoCaLize** doesn't handle mutability (i.e references).

Values

Values are simply bound to their type scheme.

Types

Type constructors must be bound to more complex information since they must exhibit the kind of definition they are introduced by. We have 4 kinds of definitions:

- `TK_abstract` The constructor represents an abstract definition, i.e. a type whose values are not introduced by the definition itself. For instance, `int` is abstract since its values do not appear in the type definition: they are built-in in the compiler. Type abbreviations are also handled this way. This means that defining `type t = (int * string)` create a type `t` that is abstract. Since there is no value and no structure information in the definition, we do not need to record anything special.
- `TK_external` The constructor represents a type whose representation is explicitly provided for external languages. In other words, we import in **FoCaLize** types from (an)other language(s). We record on what this constructor must be mapped in the various foreign languages, the value constructors or field labels if some exist that can be used on **FoCaLize**'s side and on what to map them in the various foreign languages.
- `TK_variant` The constructor represents a sum type definition. Hence values are given in the definition's structure itself. Hence we record the list of value constructor names with for each its arity and its type scheme (in fact these 2 things are the same than recorded for each value constructor in the related name-space).
- `TK_record` The constructor represents a record type definition. Hence, field labels are given in the definition's structure itself. Hence we record the list of these fields names with their type scheme and their mutability (like for sum types value constructors, these 2 things are those recorded for each field label in the related name-space).

Species

The structure of information recorded about species is pretty complex since it must depict the complete species structure, most importantly the parameters and all the methods stuff, but some other additional things used during type-checking stage.

- `spe_kind` Describes if the species is a toplevel collection (`SCK_toplevel_collection`), a toplevel species (`SCK_toplevel_species`) or a collection parameter (`SCK_species_parameter`).
- `spe_is_closed` This boolean tells if the species is fully defined (even if not turned into a collection). This information will be useful to know when collection generators must be created.
- `spe_sig_params` The list of descriptions of the parameters the species has, ordered the same way they appear in the species definition (i.e. the left-most in head of the list). We will examine the structure of this information a bit later.

- `spe_sig_methods` The list of description of all the methods of the species. We will examine the structure of this information a bit later. One may note that like for scoping information, all the methods are present, i.e. the inherited also, once and in the inheritance resolution order. This way, the methods represent the “normal form” of the species as described in the theory.
- `spe_dep_graph` We record here the dependency graph of the species’ methods. Hence, this deals with methods “of Self” and represents def and decl-dependencies. This doesn’t include dependencies on collection parameters !

Species parameter information Since FoCaLize provides 2 kinds of parameters we have 2 types of information to record:

- For entity parameters, `SPAR_in`, we keep the parameter’s name, the collection representing its type and the flag telling if this collection is a parameter, a toplevel one (like for the field `spe_kind` of a species description seen above).

For example, species `S (Nat is ..., n in Nat)` will record for `n` that its name is “in”, its type is `Nat` and that this type is from a collection that is a collection parameter (i.e. `SCK_species_parameter`) and not a toplevel one.

- For collection parameters, `SPAR_is` we record more information, especially things that have already be computed about the species the parameter is “is” in order to have a quick access to information instead of computing it each time we encounter a collection parameter of a certain “type”. To base our presentation let’s take the case of the species taken just above for the entity parameters.

- We record the name of the parameter with its compilation unit name. In fact, this will be the “type” of the collection this parameter makes available in the hosting species. In our example, `Nat` is both the name of the parameter and the type that uniquely represents the collection is bring. In effect, to use methods of this parameter, we will use `Nat!xxx`. By adding the compilation unit name, we exactly build a “type of species” like we use anywhere else in the compiler.
- Like for entity parameters we record the flag telling if the species the parameter is “is” a parameter, a toplevel collection or a toplevel species. In our example, assuming that `Nat` is a species defined somewhere else, we would have `SCK_toplevel_species`.
- Next come the list of all the methods descriptions the parameter has. This list is exactly of the same type than the list that describes a species methods (whose structure will be examined just after). It is in fact the normalised form of the species methods the parameter has.
- Since a collection parameter “is” a species expression, not only a simple identifier (for example `P2` and `P3` in species `S (P1 is ..., P2 is T (P1), P3 is U (P1, P2)) = ... ;;` who are built by applying arguments to parametrised species, we must record the complete species expression denoting what “is” the parameter. Instead of directly recording the AST part representing the expression, we translate it into a custom type.

In effect, in the AST, expressions used to represent species expressions are general expressions for sake of parsing technical issues. But in fact, due to the structure of the syntax, only a few kinds of AST nodes can be created. In particular, expressions coming out from the parser have restricted forms (invariants due to the syntax). Hence, instead of always assuming these invariants hold in the expressions representing species expressions, we prefer to convert them in a dedicated structure, more restricted than the general expressions, to enforce these invariants to hold directly by the type of the structure. For this reason, we record the species expression under the form of a `Parsetree_utils.simple_species_expr`.

Method information Depending on the kind of the methods we have different structures to record. In any case, we always record the history of the method, i.e. where it was defined and from where and how it was inherited until it arrives in the current species (structure `from_history`) and its name. The kinds of method are basically summarised by the type `spe_sig_methods` and can be:

- `SF_sig` represents a signature. since we do not have anything more than a type for this method, we keep it as a type scheme.
- `SF_let` represents a `let` definition, either “computational” or “logical”. We record the list of parameter names of the definition (if it’s a constant, then this list is empty), the type scheme of the definition, its the body (“computational” or “logical”), a termination proof if it has some, a structure telling if during type-checking we detected def and decl-dependencies on the carrier (on `representation`) and finally the flags found in the AST telling if the definition was `logical` and was recursive.
- `SF_let_rec` Here is a list of information identical to what we store for `SF_let`, one for each recursively defined functions (i.e. only 1 element in the list if there is no mutually recursive functions).
- `SF_theorem` represents a theorem definition. We record the mapping of type variables found in the `forall` and `exists` in the property’s logical expression onto their name. This is a technical point. In fact, theorems and properties do not have a type scheme. Their “type” is their logical statement. However, it is possible to have universally quantified type variables appearing in a theorem statement. Without a type scheme we are not able to technically instantiate these variables in a consistent way. To we patch this leak of scheme by recording for each universally quantified type variables, what identifier in the statement has this type. Next, we record the logical statement of the theorem, its proof, and like for `SF_let`, information on dependencies found on the carrier.
- `SF_property` represents a property definition. We record the same information than for a theorem, except the proof since a property doesn’t have any proof.

5.3.2 The `TypingEMAccess` module

The access module for the typing environments is quite trivial. The function `make_value_env_from_species_methods` works simply inserting the methods of a species in the value bucket like it’s done for the scoping environments. The only point is that since theorems and properties do not have a type scheme, we insert them with a trivial type scheme whose body (core type) is simply `prop`.

The function `post_process_method_value_binding` is trivial and is the identity. In effect, we do not need any post-processing like we needed for scoping environments.

5.4 OCaml code generation environment

The OCaml code generation environment provides information required to generate the target OCaml source code.

5.4.1 The `MlGenInformation` module

We first look at the information bound to each name in the different name-spaces.

Sum type value constructors

In this bucket, we only record on which string a sum type value constructor that has been introduced by a type definition involving an external representation must be translated into OCaml.

For instance, in OCaml, `Nil` will be mapped onto `[]` and `Cons` to `(::)`. It may be clearly noticed that for OCaml, only constructors coming from **external** sum types are entered in the generation environment. Hence, if a constructor is not found, then this means that it comes from a regular FoCaLize type definition, not dealing with any external material, hence must be simply translated into OCaml using the name given in FoCaLize side.

Record type field names

FoCaLize's records are generated as real records in the target languages. Hence, we only need to remind the name on which to map each record field name of the FoCaLize type definition. Conversely to the sum type value constructors, all the record field labels are recorded in the environment.

Values

For OCaml code generation, we do not need any information about values. Hence, the type of the bound values is trivially `unit`. But in fact, we will never enter values nor look for values in such an environment.

Types

Types also do not need any information to be generated. Hence, they are handled like values above in term of environment.

Species

For species (and collections) we must find a way to know their methods and other information coming from the dependency computation. All this is recorded in the `species_binding_info` structure below:

- The list of parameters (collection and entity) of the species with their kind. This information is the same than the one stored in the type-checking environment.
- The list of methods the species has. This information is the same than the one stored in the type-checking environment. Remember that it represents the methods present in the normal form of the species, i.e. with not double, with inheritance resolved and in the right order (to prevent dependency issues).
- An optional `collection_generator_info` describing, if available, the structure of the species' collection generator. This generator is optional because species that are non fully defined do not have any collection generator although they are entered in the environment. Generator data is used to prevent computing several times (in case where several collections are built from a same closed species) and contains:
 - The list of species parameters names and kinds the species whose collection generator belongs to has. This list is positional, i.e. that the first name of the list is the name of the first species parameter and so on. The kind of a parameter is the same thing than the one recorded in the scoping environment.
 - The list mapping for each parameter name, the set of methods the collection generator depends on, hence must be provided an instance to be used. Note that the list is not guaranteed to be ordered according to the order of the species parameters names (that's why we have the information about this order given in the first component of the `species_binding_info` structure we are globally describing).
- Finally, a flag telling if this information is bound to a species (`COS_species` or a collection (`COS_collection`)).

5.4.2 The MlGenEMAccess module

The access module for the OCaml code generation environments is really trivial. The function `make_value_env_from_species` has no meaning for OCaml code generation environments because we do not provide any `find_value` function and that's this function that requires `make_value_env_from_species_methods`.

The function `post_process_method_value_binding` is trivial and is the identity. In effect, we do not need any post-processing like we needed for scoping environments.

5.5 Coq code generation environment

The Coq code generation environment provides information required to generate the target Coq source code. Its structure will be pretty close to the OCaml environment. Most of the differences are induced by the explicit polymorphism in Coq (that imposes to keep trace of polymorphic type variables) and by the presence of logical methods (i.e. theorems, that were discarded in OCaml).

5.5.1 The CoqGenInformation module

We first look at the information bound to each name in the different name-spaces.

Sum type value constructors

The idea behind information bound to sum type value constructors is about the same than in OCaml. We want to know if needed on what string to map a constructor name if it comes from an external type definition. But we always need another information to handle polymorphic constructors.

In effect, in Coq a polymorphic function (because constructors are functions in fact) must be provided one extra argument for each polymorphic type variable appearing in the type of the function. This argument must have type Set and be provided at application-time, like the other remaining (regular) explicit arguments of the function definition. In fact, Coq can infer the value of these arguments and we can simply use a `_` (underscore) in place of these extra arguments at application-time. However, we need to know how many `_`s must be generated (i.e. how many extra arguments the constructor has due to its polymorphism). For instance, the type `t` defined in Coq by: introduces 1

```
Inductive t (alpha : Set) : Set :=  
  | A : (alpha -> (t alpha)).
```

value constructor A with not 1 argument, but 2 ! If we want to create a `t` value parametrised by the integer 1,

```
Coq < Check (A 1).  
Toplevel input, characters 9-10:  
> Check (A 1).  
>      ^  
Error: The term "1" has type "nat" while it is expected to have type "Set".
```

To have a valid application, we must add one `_` before our 1, like in:

```
Coq < Check (A _ 1).  
A nat 1  
      : t nat
```

We could be more explicit by directly providing the value of the first argument that is in our case `nat`:

```
Coq < Check (A nat 1).  
A nat 1  
      : t nat
```

but since Coq knows to infer it, we prefer let Coq doing the work (type-checking get simpler on FoCaLize's side).

For this reason any sum type value constructor is recorded in the environment with an optional mapping to a name on Coq side and the number of extra arguments it must be apply to due to the type generalised variables appearing in its type.

Record type field names

Record type field names are handled like in OCaml.

Values

In the same order of idea than for sum type value constructors we need to record the number of extra arguments to apply (when the value is functional) due to polymorphic type variables present in the value's type.

Moreover, for technical reasons due to **Zenon**, we also need to remind if the value is a toplevel property (`VB_toplevel_property` with its logical expression body), a toplevel let-bound value (`VB_toplevel_let_bound`) or something else (`VB_non_toplevel`).

Types

Like in OCaml, types also do not need any information to be generated.

Species

Species are bound to exactly the same information than they are in OCaml code generation environments.

5.5.2 The `CoqGenEMAccess` module

The access module for the OCaml code generation environments is pretty simple and works exactly like for type-checking environments.

Chapter 6

Scoping

Chapter 7

Typechecking

7.0.3 Type inference

7.0.4 Environments structures

7.0.5 Inheritance resolution

7.0.6 Dependency on Self's methods calculus

7.0.7 Normal form

Chapter 8

Intermediate form

8.0.8 Computing dependencies on parameters

Chapter 9

OCaml code generation

Chapter 10

Coq code generation

10.0.9 Theorems and proofs

10.0.10 Recursive functions

Chapter 11

Doc generation

Chapter 12

focalizedep

Index

`%type`, 29

alias, 30

tuple, 29

type

- alias, 30

- record, 33

- sum, 31

- tuple, 29

- union, 31