

# The Why, How, and When of Representations for Complex Systems\*

Leo Torres<sup>†</sup>

Ann S. Blevins<sup>‡</sup>

Danielle Bassett<sup>‡</sup>

Tina Eliassi-Rad<sup>†</sup>

**Abstract.** Complex systems, composed at the most basic level of units and their interactions, describe phenomena in a wide variety of domains, from neuroscience to computer science and economics. The wide variety of applications has resulted in two key challenges: the generation of many domain-specific strategies for complex systems analyses that are seldom revisited, and the compartmentalization of representation and analysis ideas within a domain due to inconsistency in complex systems language. In this work we propose basic, domain-agnostic language in order to advance toward a more cohesive vocabulary. We use this language to evaluate each step of the complex systems analysis pipeline, beginning with the system under study and data collected, then moving through different mathematical frameworks for encoding the observed data (i.e., graphs, simplicial complexes, and hypergraphs), and relevant computational methods for each framework. At each step we consider different types of *dependencies*; these are properties of the system that describe how the existence of an interaction among a set of units in a system may affect the possibility of the existence of another relation. We discuss how dependencies may arise and how they may alter the interpretation of results or the entirety of the analysis pipeline. We close with two real-world examples using coauthorship data and email communications data that illustrate how the system under study, the dependencies therein, the research question, and the choice of mathematical representation influence the results. We hope this work can serve as an opportunity for reflection for experienced complex systems scientists, as well as an introductory resource for new researchers.

**Key words.** complex systems, dependencies, graph theory, simplicial complexes, hypergraphs

**AMS subject classifications.** 00-02, 00A69, 00A71

**DOI.** 10.1137/20M1355896

\*Received by the editors July 27, 2020; accepted for publication (in revised form) January 25, 2021; published electronically August 5, 2021. The views and conclusions contained in this document are those of the authors and should not be interpreted as representing the official policies, either expressed or implied, of the Combat Capabilities Development Command Army Research Laboratory or the U.S. Government. The U.S. Government is authorized to reproduce and distribute reprints for Government purposes not withstanding any copyright notation here on.

<https://doi.org/10.1137/20M1355896>

**Funding:** The work of the second and third authors was supported by the Army Research Office through grants Falk-W911NF-18-1-0244, Grafton-W911NF-16-1-0474, and DCIST-W911NF-17-2-0181, by the National Science Foundation (NSF) through grants PHY-1554488 and IIS-1926757, and by the Paul G. Allen Family Foundation. The work of the first and fourth authors was partially supported by the NSF through grant IIS-1741197 and by the Combat Capabilities Development Command Army Research Laboratory under Cooperative Agreement W911NF-13-2-0045.

<sup>†</sup>Network Science Institute, Northeastern University, Boston, MA 02115 USA (leo@leotrs.com, tina@eliassi.org).

<sup>‡</sup>Department of Bioengineering, University of Pennsylvania, Philadelphia, PA 19104 USA (annsize@seas.upenn.edu, dsb@seas.upenn.edu).

**Contents**

<b>I</b>	<b>Introduction</b>	<b>436</b>
1.1	Definitions . . . . .	438
<b>2</b>	<b>Dependencies by the System, for the System</b>	<b>440</b>
2.1	Subset Dependencies . . . . .	440
2.2	Temporal Dependencies . . . . .	442
2.3	Spatial Dependencies . . . . .	444
2.4	External Sources of Dependencies . . . . .	445
<b>3</b>	<b>Formal Representations of Complex Systems</b>	<b>446</b>
3.1	Graphs . . . . .	447
3.2	Simplicial Complexes . . . . .	448
3.3	Hypergraphs . . . . .	449
3.4	Variations and Other Frameworks . . . . .	450
3.5	Encoding System Dependencies . . . . .	453
<b>4</b>	<b>Mathematical Relationships between Frameworks</b>	<b>456</b>
<b>5</b>	<b>Methods Suitable for Each Representation</b>	<b>459</b>
5.1	Methods for Graphs . . . . .	460
5.2	Methods for Simplicial Complexes . . . . .	461
5.3	Methods for Hypergraphs . . . . .	463
5.4	Methods and Dependencies . . . . .	464
<b>6</b>	<b>Examples</b>	<b>464</b>
6.1	Coauthorship . . . . .	465
6.2	Email Communications . . . . .	468
<b>7</b>	<b>Applications</b>	<b>471</b>
<b>8</b>	<b>Discussion and Conclusion</b>	<b>473</b>
<b>9</b>	<b>Citation Diversity Statement</b>	<b>474</b>
	<b>Acknowledgments</b>	<b>475</b>
	<b>References</b>	<b>475</b>


**I. Introduction.** The term “complex system” is used to describe a multitude of systems of markedly different scales, from the atomic scale of interacting atoms to the vast scale of the entire universe, as well as markedly different behaviors, from starling murmurations to the viral spread of information on social media. Though distinct definitions exist, and not one is globally agreed upon, in general a complex system is (a) a collection of objects or agents with high cardinality, which (b) interact with one another in a nontrivial way such that (c) the collective behavior of the system is unexpected or different from, or not immediately predictable from, the aggregation of the behavior of the individual parts. This unique collective behavior is often said to *emerge* from the dynamics of the parts [104, 110]. For example, a population

of neurons (units) connect via synapses (interactions) and consequently can perform computations (collective behavior). Additional real-world examples include cellular reactions in photosynthesis, food webs in ecology, transactions in local markets, interconnected worldwide trading in economics, and various technologies such as the Internet and the power grid.

In order to study complex systems across disciplines and domains, it is important to represent the system concretely using a unifying mathematical language. In recent decades, the discipline of network science has arisen as the main focus of development of such a language [144]. Network scientists typically study complex systems by first modeling them using the tools and theoretical constructions afforded by disciplines such as discrete mathematics and computational data structures. These formal theories, which we refer to as *frameworks* (see section 1.1), enable the application of tried and true methodologies from different subfields within the mathematical, physical, and computational sciences. Furthermore, these frameworks allow for the execution of efficient algorithms and can be used to infer the structure, function, and dynamics of a system. This process is undeniably enriched by the multitude of perspectives. However, what makes the process somewhat challenging is that each encounter with a new complex system requires the construction of a new abstract object tailored to it. Network science is far from developing a single, unified representation that allows the study of all possible system structures and behaviors [116]. Indeed, there is currently not one, but a wealth of related frameworks, each of which captures particular perspectives and properties of the system under study. As complexity scientists, we benefit from the creativity of those from a variety of disciplines, and the resulting myriad approaches make complexity science an adaptable and cutting-edge field.

However, this wealth of frameworks, and the resulting wealth of accompanying analysis pipelines, can also create challenges for the study of complex systems. It can hinder interdisciplinary communication, as researchers in one discipline may be unfamiliar with the representations and analyses used in another. Even within a single subfield, various approaches to representing and analyzing the same complex system can hinder collective insight across research groups or projects [34]. As a consequence, it is difficult and sometimes impossible to gather insight across systems, which directly hampers the progress of complexity science [135]. As researchers striving for precision and efficiency, we must address this challenge by understanding the assumptions underlying each framework, as well as the relationships between frameworks, and the impact of both framework assumptions and relations on our analyses and interpretations of results.

In this work we aim to collect and synthesize this wealth of analysis pipelines—from raw data procurement and clean-up to analysis results and final conclusions—while providing a common vocabulary for a continuing discussion. While achieving a single, unified language is unlikely, we can at the very least begin to simplify and condense the pipelines currently in use. For clarity, we begin by defining the fundamental terms used throughout the paper. The main text follows the flow of Figure 1.1, which illustrates a simplified representation of the analysis pipeline used when studying a complex system, insofar as it pertains to the formal representation of the system. We begin with an investigation of common system properties that can lead to biased analysis results if ignored, which we call *dependencies*, followed by definitions of three mathematical frameworks commonly used for representation. Next, we highlight mathematical relationships between frameworks that one might utilize in order to answer particular research questions, and finally we provide examples of computa-



**Fig. 1.1** *Prototypical analysis pipeline for complex systems.* We begin with the system under study and ask what sorts of elementary units exist, what relations exist that group elements together, and what dependencies might influence the existence of relations among units. We then turn to the question of how to represent the units, relations, and their dependencies; to answer this question, we must choose a framework. Finally, we seek to interpret the outcomes of computations performed on the representation, and from those interpretations we reach a conclusion about the structure and function of the system.

tions suited for each of the three frameworks. Throughout the text we repeatedly ask how these dependencies and other modeling choices may influence the pipeline steps discussed. We provide two examples using a coauthorship dataset and the Enron emails dataset [23] to demonstrate the effects of various analysis pipelines on the results obtained from the same underlying system. Finally, we close by suggesting that each modeling decision in a research analysis pipeline be taken on a case-by-case basis and with consideration of the dependencies, frameworks, relationships, and research questions.

**1.1. Definitions.** In this work we use a consistent language to allow for effective and precise communication among scientists across disciplines. Here we provide a list of terms that we will use throughout this paper and their definitions. By condensing the vocabulary and providing precise definitions of often abstract concepts, we hope to operationalize the study of the structure and behavior of complex systems.

- **Unit, element, or node:** an individual object, agent, or part of a system. Unless otherwise specified, we denote the set of  $n$  nodes by  $V = \{v_1, v_2, \dots, v_n\}$ .
- **Relation:** a set  $r$  of one or more nodes, such that  $r \subseteq V$ . In practice, node relations can arise from correlations in data, observed interactions between units, or groups of elements known to function collectively. A relation  $r$  can be *dyadic* if it contains exactly two units ( $|r| = 2$ ), or *polyadic* if the relation contains three or more units ( $|r| > 2$ ). If  $r$  contains  $k$  nodes, then we say *the  $k$  nodes in  $r$  are related*. In some parts of the literature, polyadic relations have also been called “higher order” relations and have been used to refer to motifs in graphs [24]. To avoid confusion, however, in this paper we will use “higher order” to refer exclusively to a particular framework introduced in section 3.5. We denote the set of relations by  $\mathcal{R}$  unless a domain-specific convention already exists.
- **Property:** information attached to a node or relation. We call the set of properties  $\mathcal{P}$  and let  $p$  be the assignment map sending  $V \times \mathcal{R} \rightarrow \mathcal{P}$ . For example, a relation formed by the co-firing of neurons can be assigned a frequency, and a relation formed among individuals can have a categorical property such as “teammates.” In this work we focus on the units and relations in a complex system, as these are common to all complex systems. Additional

properties, including dynamics, are also crucial for system function, but our scope is limited to the structural representation of complex systems.

- **System:** a collection of units  $V$ , relations  $\mathcal{R}$ , and (optionally) any properties  $\mathcal{P}$ , such that the collection needs no other pieces in order to function completely or to interact autonomously with its environment. The set of units forms the components of the system, while the patterns found in the set of relations are called the system's *structure*. An example of a such pattern would be finding a particular node involved in far more relations than expected. The system's activity, including changes in nodes, relations, and properties over time, is sometimes called its *function* or *behavior*. An example of behavior would be finding that the number of relations a particular node is involved in fluctuates over time.
- **Complex system:** a system whose units and relations together exhibit a qualitatively different functionality than the sum of its units acting individually; this is the main object of study. In this work, "system" always refers to a complex system.
- **System fragment:** a subset of the nodes and relations of a system. Formally, if we write a system as a tuple of nodes and relations  $(V, \mathcal{R})$ , a system fragment would be written  $(V', \mathcal{R}')$  with  $V' \subseteq V$  and  $\mathcal{R}' \subseteq \mathcal{R}$  a set of relations on node set  $V'$ . Researchers usually do not have access to all units or all relevant relations. Instead, they usually have access to—and must perform their studies on—fragments of a system. Sometimes this limited access is due to the vast number of units (a human brain contains on the order of  $10^{11}$  neurons); at other times it is due to the inability of our current tools to record all the relations among them (genes that express at low levels are difficult to detect); at still other times it is due to other constraints (social media companies may not release their data due to privacy concerns). We do not require a system fragment to itself operate as a system; that is, a system fragment may not necessarily have the ability to fully function or interact with its environment. Consider the complex system of cell metabolism in humans. Even with contemporary tools, we do not have access to all data pertaining to this system. In order to study it, we usually focus on a single aspect most relevant to the question at hand—for example, the set of all experimentally quantifiable proteins (units) and the set of known protein complexes that they form (relations). We refer to the combination of these two sets as the "protein complex fragment" of the cell metabolism system.
- **Dependency:** a property of a system in which the existence of one relation provides information about the existence of another relation. In this case we could say that one relation is dependent on another relation. Conversely, a relation is independent from another relation if the existence of one relation in no way affects the (probability of the) existence of the other. See section 2 for formal definitions of the three types of dependencies we discuss in this work.
- **Framework:** a mathematical construction or theory (a collection of definitions, results, and theorems) that can be used to represent, model, encode, and study a complex system. In this paper, we will explicitly discuss the graph, simplicial complex, and hypergraph frameworks.
- **Representation:** a mathematical or computational encoding of a specific complex system (or a fragment of one). A representation is the materialization

of a specific framework, e.g., it is one concrete, specific graph, as opposed to the mathematical theory, or framework, of graphs.<sup>1</sup> For example, one might study the brain by *representing* it as a graph with a node for each lobe and edges joining two nodes if they are physically adjacent. In this case, the brain is the system, graph theory is the framework, and the graph of  $n$  nodes that mirrors the brain connections is the representation.

- **Encode:** the process of taking a system or data collected from a system and formulating it as a representation using a specific framework.

In the rest of the paper we will assume the reader has already defined what should constitute a node and a relation within their system. We refer the reader to [37] for a thorough discussion of how to choose nodes and relations when these choices are not straightforward.

**2. Dependencies by the System, for the System.** When studying or modeling a complex system composed of many parts, several design decisions must be made. We begin by considering one specific and rather fundamental choice, which is sometimes only implied and at other times outright neglected. This choice regards the decision of which *system dependencies* one should seek to appropriately and accurately encode. Reiterating our definition above, *a dependency is a property of the system in which the existence of one relation provides information about the existence of another relation*. Said another way, does the system have underlying rules or restrictions that cause interactions to occur or units to behave in particular ways? For example, in a social system of individuals and friendships, if two individuals live physically close to one another, then their likelihood of becoming friends is larger than if they lived far apart. Furthermore, if they live near each other, then they are also more likely to meet and consequently befriend each other's neighbors. In this way, knowledge of the existence of one friendship informs us of the possible existence of other friendships, because the friendships (relations) between people (units) are affected by geographical distance (dependency).

Such system-level dependencies can manifest in different ways; here we will constrain ourselves to a discussion of three of the most commonly observed dependency types. Specifically, we discuss *subset* dependencies (does a large relation influence the existence of smaller subrelations?), *temporal* dependencies (does temporal nearness of elements influence their relations?), and *spatial* dependencies (does the physical proximity of elements influence their relations?). We acknowledge that dependencies other than those described in this work exist within real-world systems; in many domains of inquiry, ongoing research efforts seek to define the proper avenues for illuminating dependencies and approaches for their incorporation.

**2.1. Subset Dependencies.** When investigating a complex system, we often record its elements and the observed relations containing two or more of those elements. For example, we might record objects and shared observable features [129], people and shared conversations [232], or neurons and their co-firing [54]. Here, we can think of the system as a set of nodes  $V$  and a set of observed relations  $\mathcal{R}$  in which each relation  $r \in \mathcal{R}$  is a subset of  $V$  and is meant to represent one observed interaction between  $k$  elements. In this setup, some nodes may participate in many relations, while others participate in very few or none at all. It is then important to ask: If we observe the relation  $r = \{v_0, \dots, v_{k-1}\} \in \mathcal{R}$ , does it imply that some

<sup>1</sup>For readers familiar with object-oriented programming, we liken the difference between “framework” and “representation” to that between “class” and “object.”


subset  $r'$  of  $r$  is also a relation? If so, the system exhibits the type of dependency that we call a *subset dependency*. For example, in the words-and-features system fragment, if three words (ball, egg, globe, written as  $v_1, v_2, v_3$ ) correspond to objects that share a particular feature (each of them is round, so that “is round” defines a relation  $r = \{v_0, v_1, v_2\}$ ), then any two of the objects must also share that same feature (then  $r' = \{v_0, v_1\}$ ,  $r'' = \{v_1, v_2\}$ , and  $r''' = \{v_0, v_2\}$  are all relations). One can make a similar argument for people conversing with one another and for neurons co-firing. In these cases, every subset of any set of related nodes is also related. However, we will see examples later when only some, or none, of the relation subsets are also relations, and we will describe this scenario as indicating the presence of a different type of dependency. Concretely, *we will say that a system with nodes  $V$  and relations  $\mathcal{R}$  exhibits a subset dependency if, for  $r \in \mathcal{R}$  and  $r' \subset r$ , we must have that  $r' \in \mathcal{R}$  whenever  $P(r')$  is true, where  $P$  is some logical predicate*. For instance, in the words-and-features system, the logical predicate determines whether words corresponding to objects share a feature. In that system, since a subset of words for objects in a relation always share a feature, the logical predicate is always true, and we see clearly that a subset dependency exists in the system.

To illustrate this specific type of dependency, in Figure 2.1 we show a system fragment of chemical reactions (left) and a system fragment of objects with shared physical descriptors (right). On the left side of Figure 2.1, molecules or compounds correspond to nodes and reactions define relations between nodes, so that if  $k$  compounds together exclusively form the reactants and products of one reaction, then those  $k$  nodes are related. We see that  $O_2$  and  $H_2O$  participate in multiple reactions together, for example,  $2H_2 + O_2 \rightarrow 2H_2O$ , but we do not observe a reaction that *exclusively* uses  $O_2$  and  $H_2O$ . Therefore, this system fragment does not display the property that all subsets of relations are also relations, since we have that  $\{O_2, H_2O\} \subset \{H_2, O_2, H_2O\}$  and  $\{H_2, O_2, H_2O\} \in \mathcal{R}$ , but that  $\{O_2, H_2O\} \notin \mathcal{R}$ . In contrast, the right side of Figure 2.1 shows a collection of objects and features (shape and color) in which each object may share physical features with other objects. In this case, a relation  $r_{\square} = \{\blacksquare, \blacksquare, \blacksquare\}$  contains all objects that are square. Notice that by our definition of relation for this system fragment, we immediately find that  $r' = \{\blacksquare, \blacksquare\}$  is also a relation. Specifically, the pink and red squares are related because they share the feature “square,” but also any subset of the squares will also be related because they, too, share the feature “square.” This example of objects and shared features does display the subset dependency, since subsets of related nodes are also related.

When a system displays a subset dependency, we must ask ourselves whether we should explicitly represent that property in our model. The answer to that question will depend on, among other things, the available data, the research question, and how we define relations among nodes. Incorporating the subset dependency in a representation usually requires the data to include polyadic relations, which are not always directly observable. Additionally, if the research question involves trajectories through related nodes, it may or may not be necessary to incorporate polyadic relations and thus the system’s subset dependencies explicitly, since often we can answer questions about trajectories between nodes using exclusively dyadic relations between nodes.

Most commonly, the choice of whether to include the subset dependency affects the formal representation used to encode the system and consequently the results of downstream analyses. For example, if Marta is involved in a group of people having conversations and we define relations as shared conversations (so that a subset depen-






**Fig. 2.1** *Are subsets of related nodes necessarily related?* Systems may exhibit a subset dependence, which occurs when a relation between nodes implies the existence of a relation between any subset that satisfies a certain logical predicate. (Left) System fragment composed of molecules and chemical reactions. Here,  $O_2$ ,  $H_2O$ , and  $H_2$  participate in the reaction  $O_2 + 2H_2 \rightarrow 2H_2O$ , but a subset of these compounds does not independently engage in a reaction, such as  $O_2$  and  $H_2O$ . (Right) System fragment composed of objects with observable features such as color and shape. All objects that are squares are related by the presence of the shared feature “square.” Any subset of these square objects will also still possess the shared feature “square,” and thus will also be related. In this case, the logical predicate is always true.

dependency exists), then if we count the number  $p$  of people with whom Marta converses, we do not know if Marta had  $p$  separate conversations with each of the  $p$  individuals, or if she participated in one large conversation with all  $p$  people. Without a distinction, Marta’s popularity with others could be vastly over- or underestimated. This example illustrates how the occurrence of subset dependence can be determined by the definition of relation. In section 3 we explore the benefits and drawbacks of a few abstract frameworks that capture different types of dependencies. For now, we stress that the presence or absence of subset dependencies influences the computations we can perform and the frameworks we can use.

**2.2. Temporal Dependencies.** Next we consider systems in which we observe information, individuals, or goods moving along trajectories through time. A simple example would be a city subway system where passengers ride the train from one stop to the next until they reach their destination. In such systems we must ask the question: Does the current location of an individual affect where they might move next? We say a system exhibits a temporal dependency if the existence of relations at time  $t$  affects the behavior of units or relations at time  $t' > t$ . Said another way, it might be that trajectories or walks within systems that display temporal dependency are not Markovian, since the future trajectory of a walker depends not only on its current location but also on some previous trajectories of itself or other units.

Consider a subway system in which passengers can travel via trains to stations  $A$  through  $H$  (see Figure 2.2). If our complex system consists of passengers commuting via the subway, then our observed data might include explicit passenger routes. For example, in Figure 2.2 we record the routes of six passengers, each of whom commutes from the suburbs (stations  $A$ ,  $B$ , and  $C$ ) to downtown (stations  $D$ ,  $E$ ,  $F$ ,  $G$ , and  $H$ ). For the purpose of the example, we assume that passengers do not transfer between distinct train lines during their commute. If we now represent our data as a set of stations (units) and we connect two stations  $i$  and  $j$  if  $j$  immediately follows station  $i$  in at least one passenger route (relations), we obtain the subway map shown in the bottom left of Figure 2.2. Because this diagram records all known movements






**Fig. 2.2** By incorporating temporal dependencies into the representation, we obtain a more accurate subway map. Given data from six commuting passengers ( $P_1, P_2, \dots, P_6$ ) who do not switch trains (top left), how can we obtain the underlying subway map? We could create a graph in which two stations are connected if a passenger transferred from one station to another. However, such a graph would suggest that a passenger could commute from station B to F without switching trains (bottom left), which is not possible in this system. If instead we untangle the subway lines by respecting the temporal dependency and treating trains that arrive at station D from station C as different from those arriving from station B, then we can clearly see the necessary transfer between subway lines required for the B to F commute (bottom right).

of passengers between pairs of stations, we might confidently proceed to the next analysis step. However, it is worth noting that this particular representation suggests that the red path from station B to station F is a possible commute for a passenger. Yet when we look back at the data itself, such a commute seems extremely unlikely since the sequence  $B - D - E - F$  never occurs. The fact that this route appears natural from the representation, but not from the data, points to the fact that our system contains a temporal dependency and, importantly, that this dependency is not well reflected in the particular representation we chose.

As discussed in great detail in [24, 176, 70, 60, 119, 160], the fundamental limitation of keeping only pairwise sequential relations, as is done in the bottom left of Figure 2.2, is that in the representation we assume that traversal across each link is Markovian and therefore its probability is independent of the probability of traversing any other link in the system. More explicitly, paraphrased from [118], by representing the system as a graph (see section 3 for a definition) we assume that the edges  $(i, j)$  and  $(j, k)$  are independent and that the two-step transition from  $i$  to  $k$  proceeds in two independent steps. This assumption can easily be violated by a real system, as seen in our toy example, since sometimes one step in this traversal is dependent on which particular steps came before (i.e., transitions are not Markovian). Mismanaging temporal dependencies in systems can lead to misleading results that can, for example, over-represent the importance of edges that are rarely used or create non-existent connections. We will discuss a framework that is particularly appropriate for representing temporal dependencies in section 3.



**Fig. 2.3** *Spatial dependencies within a system can complicate our representations of the data. In our example system, we have (left) connection information that is independent of any system embedding and (middle) spatial information indicating where the nodes physically reside. A possible combination of the two information types (right) can be used to better understand the physical constraints on the topology. If long distance connections are costly for that system, the combined representation allows the investigator to assess the prevalence and location of those costly (and thus potentially surprising) connections.*

**2.3. Spatial Dependencies.** The third and final type of dependency that we discuss here arises from the physical nearness of units within a system. For example, in the human connectome a brain region is likely to extend white matter tracts to neighboring regions, providing physical conduits for electrical activity [202]. In granular materials, resistance to external forces relies on interactions only between particles that physically touch [158]. More generally, many spatial systems are so named because the spatial location of nodes affects their likelihood of interacting with one another [13, 14]. *Here we say that a system exhibits a spatial dependency if the distance between two or more nodes influences the existence of a relation that contains them.* More formally, consider a system whose nodes are labeled by  $V = \{v_1, v_2, \dots, v_n\}$  and each node  $v_i$  has associated to it a point  $x_i$  in some metric space. Then this system exhibits a spatial dependency if the probability of a relation between nodes  $v_1, v_2, \dots, v_k$  is a function of the pairwise distances between the corresponding locations  $x_1, x_2, \dots, x_k$ .

Many such systems exist in the natural and manufactured worlds. Indeed, spatial restrictions influence communication in cell populations [117, 167], trade in economic networks [99], and passengers in transportation networks [224, 123]. As an example of spatial dependency within an abstract system, we might begin with knowledge of only the pattern of related nodes. We display this structural information in the left panel of Figure 2.3 with circles corresponding to nodes and lines joining circle pairs whose corresponding nodes are related. From the structural information alone we might expect that relating the pink and red nodes is just as difficult or costly as relating the red and dark red nodes; we might therefore infer that the two relations are equally crucial to the system's function. However, if the system exists within an environment containing coordinates and a distance function, with each node having spatial coordinates and a measure of distance between each pair, then this spatial information could offer a different perspective on the system. In the middle panel of Figure 2.3, we see that the nodes, now depicted with colored pins, are spread out so that some are more spatially clustered whereas others are less so. Considered on its own, the spatial information gives us no insight into the actual relations present in the system, but it does provide information which might help us predict the likelihood that nodes are related.

In many spatial systems such as the brain or city transportation, relations between distant nodes are unfavorable due to the higher cost of creation and maintenance, while short-range relations are far easier to construct. In the face of this association between the physical distance across a relation and its cost, we might consider the distances between nodes and infer that the red and dark red nodes are likely to be related, while the pink and red nodes are not. When we finally combine the topological and spatial information (Figure 2.3, right), we can then leverage the two information types to understand which relations are the most surprising or make hypotheses about which relations are most important to the system. For example, the dyadic relation between the pink and red nodes might be very costly given the long distance between them, so we might infer that the pink to red relation is more essential to the system than the red to dark red relation, since the system would only spend valuable resources to maintain such a relation if it was integral to system function. Without the spatial information, we might have incorrectly placed the same importance on the pink-to-red and the red-to-dark red relations. This example highlights one of many ways in which we can integrate spatial and structural information.

As with the previous dependency types, failure to account for a spatial dependency can greatly bias our models and results. Consider an outbreak of a contagious disease. If we record the habits of infected individuals such as their diet, but fail to record their locations and physical mobility through space [210, 7], then we might, for example, wrongly attribute disease spread to the broad consumption of a particular food that is prevalent in the infected region instead of through person-to-person contact. As another example, social contacts are also influenced by proximity. If we return to evaluating Marta's popularity, the observation that she has many friends may come from the fact that she lives in a densely populated area, rather than from her charisma or personality. In these examples, failing to account for spatial dependencies can result in attributing certain structural properties of the system to the wrong cause.

**2.4. External Sources of Dependencies.** Before we shift our focus to concrete ways of encoding system dependencies using mathematical frameworks (section 3), it is useful and interesting to consider how external forces can influence the observed system dependencies. Ideally, we as investigators would have the ability to measure all dependencies within the system under study, and then we could use this knowledge to make an informed decision as to the appropriate framework with which to model our system. However, often the processes of scientific inquiry do not proceed so effortlessly: no analysis is ever devoid of the influence of external factors, or biases. Our goal in this section is to highlight possible sources of such bias. Although we have already discussed biases arising from dependencies native to the system under study, here we emphasize that acknowledging and understanding dependencies imposed by outside sources should also play a crucial role in determining an appropriate representation and subsequent analyses.


- **Data availability.** One notable and common constraint in science is the limited data that can be acquired empirically from a given system. In other words, researchers usually have access only to a fragment of the system. As a consequence, any dependency that is observed and ultimately encoded may be determined more by the sparsity of available data than by the system's true structure and function. For example, one may have access to only sparse snapshots of or short sequences from an evolving system [190], making the subset dependency difficult to identify and effectively encode. In particular, there might not be enough data available to correctly deduce the predicates

$P$  that a subset must satisfy in order to also form a relation (see the definition of subset dependency in section 2.1).

- **Data acquisition or processing.** Certain experimental techniques or computational procedures may produce spurious dependencies. A common example involves correlation matrices. By computing the correlations of node activity (a common approach in fMRI-based functional connectivity matrices [214, 89]) one induces a transitivity dependency, which is a type of subset dependency. Concretely, if  $A, B, C$  are nodes in a system where two nodes are related if the time series of their activities are highly correlated to each other, as determined by some data acquisition method, then whenever  $A$  and  $B$  are related, and  $B$  and  $C$  are related, it is highly likely that  $A$  and  $C$  are also related. In this case, it is possible that relations between nodes implied by the calculated correlations are found in the processed data but not in the system itself. For example, one might find that changing the type of correlation results in a change in the inferred relations.
- **Research question.** The research question at hand will influence which relations within a system are particularly interesting. Moreover, it may also influence the very definition of a relation. For example, consider a system of proteins that interact to form protein complexes. If we wish to study which proteins appear together in many complexes, then we may define a relation as  $k$  proteins that participate in the same complex. If instead we wish to study protein complexes themselves, we could define a relation as a set of  $k$  proteins that together form a single complex. In the first case, the relations are tied to a subset dependency (if three proteins appear together in a complex, then so do any two of them), but in the second case they are not. On the flip side, a given research question might neglect a relevant dependency in the system. For example, we could ask whether a common food could have caused a disease outbreak. Answering that explicit question neglects the fact that individuals near each other will likely eat similar foods. The research question is not broad enough to incorporate spatial information as part of the answer, and therefore spatial dependencies that might seem irrelevant at first sight can in fact be essential to finding the real answer. We expand upon this topic in section 3.5.

To summarize, we have defined and discussed three types of dependencies that could exist in a complex system: subset, temporal, and spatial. We emphasize that dependencies can arise from within the system itself or from external factors, but regardless of their origin, we as researchers must be aware of their existence and how they influence our models and results, especially given their early position in our analysis pipeline (see Figure 2.4). As we will continue to see in what follows, the recognition and encoding of dependencies can greatly affect the results of our analyses and the conclusions that can be drawn.

**3. Formal Representations of Complex Systems.** Over the years many representations of complex systems drawn from different mathematical and computational frameworks have taken hold across scientific disciplines. Different frameworks allow for the modeling of the unique aspects and dependencies of each system, but the multiplicity of available frameworks presents challenges for the communication, collaboration, and ultimately the progress of complexity science. Furthermore, the choice of framework also complicates the analysis pipeline that researchers must decide upon when studying a particular system.




**Fig. 2.4** *Understanding system dependencies is a first step in the complex system analysis pipeline. Types of dependencies include spatial, temporal, and subset dependencies. Acknowledging dependencies at this step allows for proper preservation of dependencies throughout the rest of the analysis pipeline. When preserving all dependencies is not possible due to factors outside the control of the researcher, acknowledging this inability frames the results in the proper context.*

Here we discuss three of the many possible mathematical frameworks that researchers commonly use to represent their system: graphs, simplicial complexes, and hypergraphs, chosen for their prevalence in the complex systems literature. A complex system is, at its core, a collection of units and their relations, and therefore we require our representations to mirror this composition of units and relations. The units of all three frameworks discussed here are called *nodes*. *Graphs* represent pairwise relations between nodes as *edges*. Despite their simplicity (or perhaps because of it), graph representations have supported several important discoveries such as the prevalence of small-worldness in real-world networks [223, 5]. Still, graphs can only, by nature, represent dyadic relations between nodes.<sup>2</sup> If instead relations within the system exist among more than two nodes, one might turn to either a *simplicial complex* or a *hypergraph*. Both of these frameworks naturally allow us to encode such polyadic relations [21]. The relations represented by a simplicial complex are called *simplices* and those represented by a hypergraph are called *hyperedges*. We will first define each framework, so that later in this paper we can explicitly discuss their respective advantages and assumptions.

**3.1. Graphs.** The first and perhaps most common framework used to model complex systems stems from graph theory. A *graph*  $G$  is a collection of nodes and edges between nodes such that an edge connects at most two nodes (see Figure 3.1, left). We denote the set of nodes as  $V$  and the set of edges as  $E \subseteq V \times V$ , so that a graph is defined uniquely by  $G = (V, E)$ ; note that each edge is an unordered set of two nodes. The nodes of a graph are the units, and edges describe how these units are related. If  $v_A$  and  $v_B$  are nodes of the graph, then we write  $\{v_A, v_B\}$ , or  $v_A - v_B$  to represent the fact that the two nodes are connected by an (undirected) edge. Studies that form a graph representation from the underlying data frequently involve finding densely connected sets of nodes or determining how an object might traverse the structure. In using the graph representation, such questions could lead

<sup>2</sup>More precisely, edges in a graph can only involve (at most) two different nodes. Whether the interpretation of each of those nodes is that of a single unit or many units (as is the case, for example, in some representations that involve the idea of a “supernode”) is not a relevant matter for graph theory, but it is relevant for the process of encoding data into a graph.



**Fig. 3.1** *Three types of frameworks composed from nodes and relations.* (Left) Graphs involve units called nodes and relations between two nodes called edges. Possible features of interest for graphs include all-to-all connected sets of nodes called cliques, as well as routes between nodes called paths. (Middle) Simplicial complexes can be used to represent systems with polyadic relations among units. Sets of related nodes are connected by simplices. A  $k$ -simplex describes  $k+1$  nodes that collectively interact, such that any subset of nodes forming a simplex must also form a simplex; this is called “downward closure.” Motifs of interest include topological cavities and maximal simplices. (Right) Hypergraphs can also be used to represent systems with polyadic relations among units. Sets of related nodes are connected by hyperedges. Hypergraphs are not restricted by downward closure. Of particular interest within a hypergraph is the absence of a substructure (or smaller relation), for example, in which two nodes do not connect dyadically but participate together in a hyperedge that connects a superset of the node pair.

to detecting *cliques* or *communities* in the graph, or identifying chains of connected nodes called *paths* (see Figure 3.1, left, and section 5.1 for more examples).

Many attribute the origin of graph theory to Leonhard Euler in the 18th century [75]. One can also trace its presence outside mathematics back to the use of sociograms and social network analysis in the 1930s [79], and to graph-like data structures in computer science in the 1950s [225]. Notably, the use of graphs to model more general complex systems has rapidly increased over the past few decades, driven largely by the discovery of the small-world effect [223] and heavy-tail degree distributions [10] in real-world datasets. Encoding a system as a graph has the great advantage of hundreds of years of mathematical theory behind the concepts, generally simple computations, and insightful visualization. However, the graph by definition assumes that relations between nodes occur exclusively at the pairwise level. Systems such as transportation networks might solely contain pairwise relations among their units, but many others, especially from biology, often have polyadic relations. Still, the graph’s ability to model systems has proven quite useful in distinct fields such as neuroscience [18, 36], computer science [76, 134], and ecology [163, 137].

**3.2. Simplicial Complexes.** The next framework that we consider addresses the need to acknowledge polyadic relations in the system. Illustrated in the middle column

of Figure 3.1, a *simplicial complex* is a set of nodes  $V$  (also called *vertices* in the field) along with a collection of subsets of nodes  $\mathcal{R}$  (often denoted by  $K$  in the field) such that for any  $r \in \mathcal{R}$  and  $r' \subset r$ , we have  $r' \in \mathcal{R}$ ; we will refer to this condition as “downward closure.” A set of  $k+1$  nodes  $r \in \mathcal{R}$  is called a  $k$ -simplex, and downward closure requires that any subset of nodes within a simplex also forms a simplex. In practice, we often imagine a  $k$ -simplex to indicate an application-relevant interaction between the  $k+1$  nodes, such that these nodes can function in unison. The simplicial complex (precisely, the *abstract simplicial complex*) would then record the individual units (nodes), the functional building blocks (simplices), and how all these building blocks are assembled into one system (the simplicial complex). Since subsets of simplices are simplices by definition, then if  $k$  nodes are related, we have that any subset of those  $k$  nodes is also related. The simplicial complex can be fully described by a binary *incidence* matrix of dimensions  $\#maximal\ simplices \times \#vertices$ , where an element containing a 1 indicates node participation in the corresponding maximal simplex; a maximal simplex is a simplex that is not contained in any larger simplex.

Although algebraic topology has been studied for well over a century, it was not until the late 1990s that applied algebraic topology as a discipline began to emerge [233, 69] (though we note that earlier uses exist [9]). Many of the earliest studies used applied topology and simplicial complexes to study data in the form of point clouds [40, 191]. Later, it became clear that the simplicial complex language was a natural framework for explicitly representing biological and physical systems. For example, simplicial complexes have been used to represent neural recordings [87, 54], classify images [205, 56, 67], and describe the mesoscale architecture of brain networks [203, 204, 169, 193, 161]. Even more recent work has focused on defining generative models to construct simplicial complexes with given topological features [52, 51] and investigating dynamics that could take place upon nodes or higher-dimensional simplices [211, 132].

**3.3. Hypergraphs.** The final framework that we consider again draws from sets of nodes and their relations, yet is even more general than the simplicial complex discussed above. The *hypergraph* is an extension of the mathematical definition of a graph, in which we have a node set  $V$  and a hyperedge set  $\mathcal{R}$  (sometimes denoted in the field as  $\mathcal{E}$ ). A hyperedge  $e \in \mathcal{R}$  can connect an arbitrary number of nodes; that is, while an edge in a graph can only connect two nodes, a hyperedge can connect three, four, five, or more nodes (Figure 3.1, right). More rigorously, a hypergraph is a pair  $(V, \mathcal{R})$  with  $V$  a node set and  $\mathcal{R}$  a set of subsets of  $V$  [217, 26]. In contrast to the simplicial complex, we can use the hypergraph to encode polyadic relations without the restriction of downward closure. Formally, a subset  $e'$  of a hyperedge  $e$ ,  $e' \subset e \in \mathcal{R}$ , does not necessarily exist as a hyperedge. Additionally, we can rewrite a hypergraph as a binary *incidence* matrix of dimensions  $\#hyperedges \times \#vertices$  in which an entry of 1 indicates the node's participation in the hyperedge.

As noted above, the crucial restriction that is relaxed when moving from a simplicial complex to a hypergraph is that of downward closure. Recall that in a simplicial complex any subset  $r' \subseteq r$  of a simplex  $r$  must also be a simplex. Hypergraphs do not obey this rule. For example, we may see a hyperedge connecting vertices  $v_1, v_2$ , and  $v_3$  but no hyperedge that connects  $v_1$  to  $v_2$  exclusively. Similarly, given two hyperedges  $\{v_1, v_2, v_3\}$  and  $\{v_2, v_3, v_4\}$ , does the existence of a hyperedge  $\{v_2, v_3\}$  imply the existence of a subrelation for either, both, or neither of the hyperedges  $\{v_1, v_2, v_3\}$  and  $\{v_2, v_3, v_4\}$ ? With a hypergraph, we cannot determine how or if a subrelation emerges due to superset relations (see [197] for a deeper discussion). This subtle difference



allows hypergraphs to represent a wide diversity of systems, including many that the simplicial complex framework would not appropriately represent. The hypergraph's increase in modeling flexibility is counterbalanced by a decrease in formal analysis methods, which we will discuss more in section 5.

The flexibility and ability to model polyadic relations made hypergraphs an appealing framework in many systems that were originally studied with graph theory. Indeed, one of the earliest practical uses of hypergraphs was to understand social networks [186]. Since then, researchers have successfully employed hypergraphs to study polyadic relations in the Enron email dataset [164], find the core of yeast protein-protein interactions [165], uncover motifs in neurodevelopment [90], track changes in evolving systems [19, 57, 58], and detect failure in biochemical networks [111]. As many uses of hypergraphs arose out of systems first modeled with graphs, many analysis methods for hypergraphs mimic those originally used for graphs (we discuss this point further in section 5.3).

**3.4. Variations and Other Frameworks.** We note that the above descriptions only scratch the surface of complex systems encoding possibilities. An ever broadening set of scientific questions drives the need for novel variations, extensions, and adaptations of each framework, resulting in a myriad of definitions and manipulable parameters. One could extend our mathematical definition of complex systems to include the following properties, as a map  $p : V \times \mathcal{R} \rightarrow \mathcal{P}$ , where  $\mathcal{P}$  is a set of properties we care about, as mentioned in section 1.1. Alternatively, one could use the frameworks discussed above as building blocks from which to create a new framework. Here we note a few of the most common modifications to each of the above frameworks, driven by the need to incorporate more information about the system at hand.

**Directed.** Many complex systems including the brain, transportation networks, and metabolic pathways exhibit directionality in their relations. That is, in these systems, if  $v_A$  and  $v_B$  are units that share a dyadic relation, there is a meaningful distinction between a relation where  $v_A$  comes first, one where  $v_B$  comes first, and one where either  $v_A$  or  $v_B$  comes first (but there must always be an order in how they are related). To distinguish these cases we write  $v_A \rightarrow v_B$ ,  $v_B \rightarrow v_A$ , or  $v_A \leftrightarrow v_B$ , respectively. If we apply this idea to the graph framework, a *directed graph* is one where each edge is now an ordered set of two nodes. Directed graphs have proven extremely useful in many contexts from scheduling and monitoring workflows [113, 6] to cardiac excitation modeling [215] to understanding percolation processes relevant to wildfires and other explosive phenomena [199, 66]. Moving to simplicial complexes, directionality is still quite natural. Indeed, simplices themselves inherit a directionality, formally known as an *orientation*, encoded by the numbering of the participating vertices. In practice, in an oriented  $k$ -simplex, each node is made to point only to nodes with a higher assigned number. Oriented simplicial complexes arise in practice from directed synapses between neurons [169] as well as directed migration flow [101]. Finally, in hypergraphs, one may represent directionality with *hyperarcs*, the term for a directed hyperedge. More formally, a hyperarc is a pair of disjoint subsets of vertices with one subset comprising the sources and the other subset comprising the sinks [83]. Directed hypergraphs have proven useful in constructing a biological pathway database [114], tackling problems in computer science such as propositional logic [83] and combinatorial optimization [120, 88], and finding specific patterns of connectivity in chemical reaction systems [151], among others.

**Weighted.** In real-world systems, not all relations are created equal; even within the same system, relations between individual units may vary in strength or magnitude. To represent these differences, the strength of a relation can be encoded using the *weighted* versions of the above frameworks. To assign weights to any of the above encodings, we can define a general weight function  $W : \mathcal{R} \rightarrow \mathbb{R}$  from the set of relations  $\mathcal{R}$  (edges, simplices, or hyperedges) to the real numbers  $\mathbb{R}$ . For a graph, this function would assign a value to each edge, which we generally interpret as the strength or frequency of the pairwise interactions between the corresponding nodes. In the context of weighted representations, the original versions containing no weights are called *binary* or *unweighted*, as they can be cast as weighted objects where the weights of all relations are either one, if they exist, or zero, if they do not exist. The brain connectome, traffic between municipalities [63], and functional similarity of genes [155] have all been modeled as weighted graphs. Additionally, many common graph metrics such as the clustering coefficient and path length (covered in more detail in the next section) extend easily to the case of weighted graphs [177], making this variant of representation particularly pervasive. Similarly, we can construct a weighted simplicial complex by assigning a weight to each simplex. However, recall that in a simplicial complex any face of a simplex must also be a simplex, and thus if we have a relation between  $k$  nodes, then any subset of these nodes must be related to at least the same extent as the superset. In other words, we require that the weighting function  $W$  on simplices adheres to the rule that for any simplex  $r$ , if  $r' \subseteq r$ , then  $W(r) \leq W(r')$ . Weighted simplicial complexes can arise from point clouds with inverse distances between points as weights or from growing processes with the time of addition used to assign simplex weight. Perhaps most often, we study weighted simplicial complexes through the lens of persistent homology, which computes the organization of topological cavities housed within the weighted simplicial complex [233, 39, 84, 150] (see a few recent uses in [193, 87, 161, 203]). Last, in hypergraphs we can naturally weight hyperedges with distinct values [83]. Importantly, weighting hyperedges allows more flexibility in choosing weights, as weighted hypergraphs do not enforce rules restricting weights on subedges, in contrast to weighted simplicial complexes. Weighted hypergraphs have proven useful in image segmentation [171] and in the process of incorporating prior knowledge into learning algorithms [209].

**Dynamic.** Complex systems such as cell signaling, traffic patterns, and transactional relations also grow, separate, or fluctuate in time [125, 178, 44, 122]. Consequently, frameworks have been adapted to represent such an evolving architecture. A *dynamic graph* or a *temporal graph* is a sequence of graphs  $G_1, \dots, G_T$  in which each  $G_i$  is a graph on the same set of nodes, and each node is mapped to its identity when moving from  $G_i$  to  $G_{i+1}$  [96]. As with other variations on graphs, multiple computational tools such as community detection have been extended to include these types of dynamics [145, 192, 140]. Moving to simplicial complexes, a dynamic simplicial complex is similarly a sequence of simplicial complexes on the same node set. Questions about the topological cavities of simplicial complexes can be answered by using *vineyards* [227] and *zig-zag* persistent homology [133] depending on the types of evolving simplicial complexes. Finally, a dynamic hypergraph is a sequence of hypergraphs  $H_1, \dots, H_T$  on the same node set where hyperedges may change from  $H_i$  to  $H_{i+1}$ . At the time of writing, we have found few examples of applied dynamic hypergraphs, although we note that their visualizations have been studied [213]. Nevertheless, we suggest that this particular variation of hypergraph could be useful, for example, in

modeling evolving gene interactions, functional relations between brain regions, and the time-varying structure of social groups.

**Multilayer.** Often the units or relations of a system have types, categories, or classifications that distinguish them. It is sometimes useful to distinguish between these types of relations in our representations, and one way to do so is to use the so-called *multilayer* variations. Generally, multilayer graphs consist of a set of graphs that may (or may not) involve the same nodes; each graph in the set comprises a *layer*. The graph in a given layer contains relations of exactly one type. Consider a human brain in which two regions might show an increase in blood flow either due to coupled neuronal activity or due to interactions involving nearby blood vessels themselves. To encode these two types of relations in a single representation, we could use a multilayer graph with two layers: one encoding the relations between neurons and the other encoding relations between blood vessels. We note that when all layers contain the same set of nodes and the only interlayer edges that exist connect nodes to themselves in other layers, the representation is called a *multiplex* graph [31, 195]. We invite the interested reader to visit [109, 29] for more rigorous definitions and [130, 35, 229] for implications for diffusion and control. Time-evolving systems can be seen as a subtype of multilayer systems, in which the layers are a set of graphs ordered in time. Previous studies have used multilayer networks to model complex spreading processes [59, 180, 181, 212], understand explosive word learning [200], and uncover the community structure of trade relations [11]. Importantly, the multilayer framework can be extended to more than simply systems with multiple types of edges. Indeed, this framework can incorporate sets of graphs or systems with many types of interactions. Multilayer simplicial complexes or hypergraphs would similarly include a set of simplicial complexes (respectively, hypergraphs) not necessarily defined on the same nodes in each layer. As of the time of this writing, we have not yet found applications of this extension. We suggest that these variations could prove useful in understanding multiple types of biological data collected on a set of nodes. As an example, one could encode common properties (mutation status, chromatin rearrangements, etc.) as layers in a multiplex network of cancer cell lines in order to better understand drug response [168]. The multilayer variation is readily applicable whenever researchers have access to and want to model two different fragments of the same system.

**Higher-Order Networks for Temporal Systems.** The term “higher order” is most commonly applied to incorporate multiple units into one relation or megaunit, but could also be used to encode temporal dependencies. Specifically, higher-order networks (often referred to as HONs in the literature) are a variation of the graph framework that aims to represent a certain kind of temporal polyadic relation. Instead of encoding system units as nodes, the higher-order network encodes frequent paths or transitions in the data as nodes, which then allows us to interpret the final representation with the standard Markovian assumptions on edge sequences. Recall our example of commuting passengers in Figure 2.2. We can build a higher-order network from the observed path data to encode the observed dynamics and temporal dependencies of this system in a particular kind of graph. In Figure 2.2, the more accurate subway map on the bottom right, reconstructed from the observed data, contains two nodes that correspond to the physical station  $D$ . The node labeled  $D_B$  represents the passengers that arrive at  $D$  from station  $B$ , while  $D_C$  corresponds to those that arrive from station  $C$ . Similarly, the physical station  $E$  splits into two nodes:  $E_{DC}$  and  $E_{DB}$ . The nodes on this map do not correspond to the stations observed in the

town's transportation system, but to the possible passenger pathways through them. Indeed, as observed before, we never observe a passenger commute that traces the path  $C - D - E - H$ : all passengers that pass through stations  $C - D - E$ , in that order, go on to station  $F$ , while all passengers that pass through stations  $B - D - E$ , in that order, go on to station  $H$ . Therefore, the representation on the bottom right of Figure 2.2, an example of a higher-order network, is a more faithful representation of the observed data and its temporal dependency. Note that if the observed passenger data changed to include a route visiting stations  $C - D - E - H$ , the structure of the higher-order network would change, even if the physical brick-and-mortar subway system, and its graph representation, did not. We discuss higher-order networks for temporal data in the next subsection and refer the interested reader to [24, 176, 70, 60, 119, 160] for further details.


**Further Variations.** We note that the variations on the three main frameworks discussed above are only the start of possible ways to extend these representations. Depending on the complex system and questions at hand, certainly one may combine the variations described above to make, for example, an edge-weighted dynamic network [107], a weighted multilayer network [131], a multiorder network that combines multiple higher-order networks [184], or another combination that provides an effective representation. One may also study systems of weighted nodes instead of weighted edges [194, 142], as well as representations where each node has some kind of internal structure [48, 72] or possible action [8]. Any one of the frameworks above could also lend itself to studying the intricacies of coupled dynamical systems such as coupled oscillators [157, 149] or interacting threshold-linear models [138]. Indeed, when including variations on the three frameworks covered in this review, we find we can encode an impressive range of complex system types and properties.

**Other Frameworks.** We recognize that many other frameworks intended for complex systems exist and that those we specifically mention in this review constitute only a small subset of the possibilities. Other possible frameworks include *graphons*, which describe limits of sequences of graphs and can be used to estimate large, noisy systems [33], *metapopulation models*, which classically describe the global behavior of many local species populations [121, 206, 94] and can be adapted to networks [48], random sequences of sets [25], and *sheaves*, which can handle added information on each node in a network and have previously been used to frame the network coding problem [85] and find consensus in sensor networks [53].

**3.5. Encoding System Dependencies.** As we discuss above, the framework used to encode our data should be carefully chosen to respect the prominent properties of the system, and specifically the dependencies found therein. In this subsection we discuss the subtleties of choosing an appropriate framework and then review the common practices that researchers use to encode subset, spatial, and temporal dependencies using the frameworks we have introduced.

Once we have chosen which dependencies to model, it is important to carefully determine when two or more units in our system are related to each other—i.e., to define the relations in our model (see Figure 3.2). Depending on the exact definition of the relations, the resulting representation may or may not exhibit the desired properties, or it may even exhibit properties not found in the actual system, but which come from externalities from the data, as discussed in section 2.4.

For example, consider recording brain activity from an individual as they progress through different tasks (reading, watching a video, resting, etc.). Different tasks



**Fig. 3.2** *Native dependencies captured by the definition of relation.* (Top) We might record the on/off activity of four brain regions in each of four tasks (left). Depending on the definition of the relation chosen (middle), we may or may not record a dependency in a representation (right). (Bottom) Given five bus stations placed along a set of roads (dashed lines), we observe three bus lines that connect the stations (left). Depending on the definition of the relation chosen (middle), we might include a subset or temporal dependency which we would want to capture in our representation of the system (right).

require the activation of distinct sets of brain regions. How do we define relations between brain regions? As depicted in Figure 3.2, we could define  $k$  nodes to be related if a task requires all  $k$  nodes to be active. Alternatively, we could define a relation between  $k$  nodes if the  $k$  nodes were found to coactivate during a task. Finally, we could call two nodes related if they have a high enough measure of pairwise similarity, perhaps assessed by correlation or mutual information. Depending on our chosen definition of node relations, our resulting representation either will or will not encode a subset dependency. In this example, only the definition of node co-firing exhibits a subset dependency, which we could capture in a simplicial complex representation. Now consider a city bus system fragment including stations, roads, and bus lines (Figure 3.2, bottom). First, we could define a relation between  $k$  nodes (stations) as the sets of stations along an entire bus route. That is,  $k$  stations are related if they together form a whole bus route. This definition would propagate no subset or temporal dependencies to the representation. Second, we could instead call  $k$  nodes related if they share at least one bus line. Consequently, we now have a subset dependency that must be captured by our choice of representation. Third, we might define two bus stations as related if they are subsequent stops along a route. This third, inherently pairwise, definition of relation could be represented with a graph. Note that none of these three definitions encodes the temporal dependency, which may or may not be present in the available data. For example, if we had access to not only stations' locations but also passenger trajectories within the system, we could encode the temporal dependencies using higher-order networks.


The above examples, and those in reference [197], illustrate the fact that one must carefully choose relations to effectively encode dependencies, or, equivalently, that whether or not a given representation exhibits a dependency is a (sometimes subtle) question of semantics. This is to say, the modeling choices concerning relations, representations, and dependencies are highly, and unavoidably, interdependent on one another. We must be aware of what dependencies exist in the system, which of them are encoded or neglected in the representation, and which come from external sources. In the scientific community, these difficult choices are usually made following the common practices that we delineate next.

**Encoding Subset Dependencies.** If a system exhibits subset dependency, it is common practice to use either simplicial complexes or hypergraphs to represent it. In the case when *any* subset of a set of related units is also related, then an appropriate framework is the simplicial complex, since this framework has the downward closure property (see section 2.1). In the terms used in section 2.1, the predicate  $P$  is true for any subset of an existing relation. If instead only *some* subsets of related units are related, then one could argue that a hypergraph is the appropriate framework to use, since it allows for great freedom in encoding relations among subsets of related units. Equivalently, a particular subset dependency gives a particular choice of the predicate  $P$ , which in turn induces a particular hypergraph. Recall that the important difference between hypergraphs and simplicial complexes is the notion of a subedge. Drawing from Remark 3.5 of [197], if a 1-simplex  $\{a, b\}$  and two 2-simplices  $\{a, b, c\}$  and  $\{a, b, d\}$  exist, then by definition  $\{a, b\}$  is a subrelation (formally called a *face*) of both  $\{a, b, c\}$  and  $\{a, b, d\}$ . However, if instead we had hyperedges  $\{a, b\}$ ,  $\{a, b, c\}$ , and  $\{a, b, d\}$  in a hypergraph, we cannot say whether  $\{a, b\}$  is a subrelation (subedge) of  $\{a, b, c\}$ ,  $\{a, b, d\}$ , both, or neither. This connection or lack thereof between relations and subrelations crucially affects the interpretation of the system representation. Choosing to encode data as a simplicial complex or a hypergraph will then allow specific mathematical tools, such as those from applied topology, to be used for analyses. We will discuss this idea in more detail in section 5.

**Encoding Temporal Dependencies.** As discussed in section 3.4, one way to encode temporal dependencies uses the idea of higher-order networks. Recalling our previous description, the higher-order network begins with a set of walks, and from the patterns found therein it creates a graph in which nodes correspond to ordered sets of units in the original system, and edges connect nodes based on temporal dependence. In this way, the higher-order network takes the temporal dependency (for example, paths from A to B always lead to C) and encodes it in a special kind of node, derived from the original units of the system. At the time of writing, higher-order networks have been defined for paths on graphs. It is still an open question how to extend the higher-order network framework to simplicial complexes or hypergraphs so that the resulting representation exhibits both temporal dependencies and arbitrary subset (or spatial) dependencies.

**Encoding Spatial Dependencies.** Possibly the most straightforward method to encode spatial dependencies constructs a weighted graph in which the edge weights in some way represent how close or far nodes are from each other. However, we highlight the fact that edge weights are a popular mechanism to encode other kinds of information as well, and once we encode one piece of information within the edge weight we cannot then use edge weights to also encode spatial dependencies. For example, if we build a graph for the transportation system of a city, we may want to encode





**Fig. 3.3** *Choosing a framework marks the second step of our analysis pipeline. Frameworks include graphs, simplicial complexes, and hypergraphs. We argue that the choice of framework should be made in order to most faithfully capture system dependencies.*

both traffic flow and road length as properties of the relations. Usually, both types of information are encoded using edge weights, so we are left with three alternatives. The first is to choose an edge weight that aggregates both types of information. The second is to use a multilayer network (see section 3.4) in which each layer has weighted edges reflecting a single type of relation [44]. The third is to create a more holistic representation that efficiently combines the spatial information, traffic flow, and road length while also including any interactions between edge types. This challenge is yet another example highlighting that data availability, system dependencies, and choice of representation are not independent of one another.

If the only challenge to the study of complex systems were the choice of representation, then our discussion would be near complete. However, real-world systems usually have at least two or more dependencies, including those we do not discuss in this paper. For example, the subway network (Figure 2.2) contains both temporal dependencies (evidenced in passengers' routes) and spatial dependencies (the routes taken are usually constrained by geographical proximity), while the coauthor system (discussed further in section 6) could be further constrained by both temporal and subset dependencies. Moving forward (see Figure 3.3), we will need to develop novel methods for systematically representing and encoding complex systems with multiple dependencies.

**4. Mathematical Relationships between Frameworks.** At this point it might seem that the choice of representation wholly restricts the perspective and possible analyses on the data. For example, if we encode the data as a directed hypergraph, we can only perform analyses using hypergraph methods. However, as each of these base frameworks records relations between nodes, perhaps we could utilize the underlying mathematical relationships between each of these frameworks to gain additional insights. In this section we will explore the formal mathematical relationships among graphs, simplicial complexes, and hypergraphs, and then we will discuss the assumptions needed or information lost as we move from one to another.


**From Hypergraph to Simplicial Complex: Forgetting Independent Relations.** First let us imagine that from our data we have constructed a hypergraph  $H$ . If we would like to create a simplicial complex  $K_H$  from  $H$ , we might first map the nodes of  $H$  to nodes of  $K_H$ , before dealing with the hyperedges. Recall that in a simplicial complex we have simplices that connect multiple nodes, but we also have the downward closure restriction that if we have a simplex  $r$ , then any  $r' \subseteq r$  must



also be a simplex. So then to form  $K_H$  we could take any hyperedge connecting  $k + 1$  nodes and form from it a  $k$ -simplex (see Figure 4.1, top left), thereby forcing the downward closure of the hyperedge relation so that the system representation can abide by simplicial complex rules. Additionally, note that if we have a hyperedge  $a$  on nodes  $\{v_0, \dots, v_k\}$  as well as a hyperedge  $b$  on a subset of these nodes, the simplicial complex will view  $b$  as redundant information, since by definition every subset of nodes in  $a$  will be connected by simplices. In this way, we say that the simplicial complex “forgets” the existence of  $b$  as a relation observed independently of all other relations (specifically, observed independently from the relation  $a$ ). We can also see this forgetting notion in the matrix representation of the structure itself: from a hyperedge incidence matrix we only need to keep the maximal hyperedge rows in order to build the corresponding simplicial complex incidence matrix. Additionally,  $K_H$  will also lose information regarding the total number of relations in which a node is involved, since many of those original hyperedge relations might be a subset of another hyperedge relation. On the other hand, this procedure allows us to access methods that are available for simplicial complexes but not for hypergraphs (discussed further in section 5). Overall, in the hypergraph each hyperedge between a set of nodes arises independently, so that having additional hyperedges (or the lack thereof) between subsets of nodes within a larger hyperedge indeed supplies more information than the one largest hyperedge. In contrast, we can define a simplicial complex by its largest simplices (formally called maximal simplices) alone.

**From Simplicial Complex to Graph: Forgetting Polyadic Relations.** Next let us assume that we are given a simplicial complex  $K$  and that from  $K$  we wish to construct a graph  $G_K$  that still represents our data. This transition is more straightforward, as we can take all of the 1-simplices of  $K$  to be edges of the graph  $G_K$ . Put another way, if two nodes participate in the same  $k$ -simplex in  $K$ , then we draw an edge between these two nodes in  $G_K$  (Figure 4.1, top right). By performing this transition from simplicial complex to graph, we are now forgetting polyadic relations between nodes. For example, in a simplicial complex we may have three nodes connected by three 1-simplices, or connected by three 1-simplices and a 2-simplex; in a graph, by contrast, we can only show these three nodes as being all-to-all connected by edges, thus eliminating our ability to distinguish between the two cases. One can also move from a hypergraph to a graph by drawing an edge between two nodes only if the two nodes are connected by a hyperedge. The resulting graph recovered from this process will be the same as the graph obtained by moving from a hypergraph to a simplicial complex to a graph following the described protocol.


**From Graph to Simplicial Complex: Assuming Polyadic Relations.** What happens if we instead move in the other direction? What are the assumptions necessary to take a graph such as the one shown in Figure 4.1, right, and construct from it a simplicial complex or a hypergraph? First, let us begin with a graph  $G$  and construct a simplicial complex. If we make the assumption that all nodes involved in a  $(k + 1)$ -clique of  $G$  are related, then we can construct a simplicial complex  $K_G$  by filling in each  $(k + 1)$ -clique with a  $k$ -simplex. This particular construction is called the *clique complex* [105] or the *flag complex* [106], and it is often denoted by  $X(G)$  (Figure 4.1, bottom middle). We reemphasize that for this construction, it is necessary to assume that all nodes within a clique are all related as a single functional unit. Importantly, this clique-to-simplex assumption may not be appropriate for all systems. One example arises from social conversations in which three people may converse only in pairs and never together as a three-person group.



**Fig. 4.1** *Transitioning between frameworks requires added assumptions or engenders forgetting information.* (Top left) The original example system as a hypergraph. (Top middle) When we send hyperedges to simplices, we create a simplicial complex, and (top right) by keeping all edges, we form a graph. Going in the other direction, we begin with the same graph (bottom right), fill in all cliques as simplices to obtain a simplicial complex (bottom middle), and send maximal simplices to hyperedges to form a hypergraph (bottom left). Note that the hypergraphs on the top left and bottom left differ from one another.

**From Simplicial Complex to Hypergraph: Assuming That Only Maximal Simplices Are Independent.** As we consider moving from simplicial complex  $K$  to hypergraph  $H_K$ , we are faced with a few options. First, since a simplex by definition implies that all subsets of nodes within a simplex are also related, then we could take every simplex and form from it hyperedges between all subsets of nodes within the simplex. In constructing the hypergraph in this way, we carry through the downward closure restriction. Alternatively, we could perform a conversion more akin to the inverse of the hypergraph-to-simplicial-complex conversion discussed above by creating a hyperedge only for each maximal simplex of  $K$  (Figure 4.1, bottom left). Assigning hyperedges only for maximal simplices can be seen as a conservative approach; that is, we can uniquely define a simplicial complex using its maximal simplices so that in forming the new hypergraph, we are assuming the fewest number of hyperedges necessary to preserve only the polyadic relations already known to be independent.

**From Hypergraph to Graph, and from Graph to Hypergraph.** Perhaps most importantly, note that from a graph we can move to a simplicial complex, then to a hypergraph, then back to a simplicial complex, and finally back to a graph following the translations discussed above. In this process, we will recover the original graph with which we began. However, the opposite is not the case. As depicted in Figure 4.1, we can begin with the hypergraph on the top left, move through the simplicial complex



**Fig. 4.2** *Mathematical relations between frameworks add an optional step to the pipeline, only to be used with caution. After an appropriate framework has been chosen for system representation, one can make use of mathematical similarities between frameworks to view their representation from the lens of a different framework. Importantly, we note that moving from hypergraphs to simplicial complexes to graphs can result in a loss of information, while the reverse direction can require one to make assumptions about the system.*

to the graph, and then move back along the bottom row from right to left, and we will in fact recover a very different hypergraph than the one from which we began. This exercise emphasizes the information lost or forgotten in moving down the framework ladder. Specifically, since each hyperedge may arise independently of all others (most notably independently of any hyperedge that is a superset), we not only lose information when moving toward a graph, but also cannot recover this information when moving back up from a graph to a hypergraph.

We note that the above protocols of moving from one framework to another do not encompass all possibilities. One could define a simplicial complex from a graph by simply keeping all edges as the 1-skeleton and having no larger simplices, or perhaps one might form a weighted graph from a hypergraph by assigning edge weights as some function of the hypergraph structure [143, 43, 92]. Though we have here discussed moving between frameworks as the third step in the pipeline (see Figure 4.2), moving from one framework to another *after* the initial encoding of data into a formal representation should be performed only with extreme care, as any translation requires adding assumptions or the forgetting of relations or independencies.

**5. Methods Suitable for Each Representation.** Now that we have exerted the effort necessary to properly represent our data as a graph, simplicial complex, or hypergraph, how do we analyze the resulting structure? In this section, we will describe methods and statistics that can be used to evaluate precisely how each of the three base frameworks offers unique perspectives on the system under study. We recognize that many such methods and statistics exist, but for clarity we will focus on a few techniques that help us identify similarities and differences among representations.

Before we begin, we provide a brief note of caution. The fact that a method of interest might currently take in only one particular framework does not justify the use of that framework in representing our data. To further illustrate the point, if we intended to understand the spread of a disease by calculating the epidemic threshold [41], we would find that most existing methods that calculate the epidemic threshold do so from a graph representation. The theory of disease spread on hypergraphs



**Fig. 5.1** Frameworks provide different perspectives on the neighborhood of a node. (Left) The colored node has four direct neighbors and participates in two triangles. (Middle) The colored node has four direct neighbors and participates in one 2-simplex. (Right) The colored node has two neighbors connected to itself exclusively, and two neighbors accessible through a larger hyperedge.

and simplicial complexes is currently a nascent area of research [100, 102], so one might not find a definition of the epidemic threshold that uses either of these polyadic frameworks in the literature and is appropriate for the system at hand. Nevertheless, the absence of this particular notion for polyadic frameworks does not imply that we are justified in using a graph framework to represent the system. Generally, a result is unlikely to offer fruitful insight into a system if the calculation was performed on a representation that itself is ill suited for the system.


**5.1. Methods for Graphs.** As the most well known of the three frameworks in data analysis, graphs have offered scientists interpretable and easily computable tools for decades. Thanks to this rich history of graph analysis, we can computationally study graphs at many different levels: the local node or node-neighborhood level, a mesoscale level to see larger patterns, and the global level to summarize the entire object. Though myriad statistics exist, for the sake of brevity we limit our discussion below and point the interested reader to [144] to learn more.

At the most basic level, the number of edges incident to a node  $v_i$  is called the node *degree* and is denoted  $k_i$  (see Figure 5.1, left). The distribution of degrees can constrain the graph's large-scale organization, for example, tracking the emergence of a giant connected component [136]. At the neighborhood level, we can investigate statistics describing the connectivity between a node's neighbors. A common example is the *clustering coefficient*  $c_i$  of a node  $v_i$ . Formally, the clustering coefficient is

$$(5.1) \quad c_i = \frac{2\mu_i}{k_i(k_i - 1)},$$

where  $\mu_i$  is the number of edges between neighbors of  $v_i$ . The numerator counts the number of triangles in which  $v_i$  participates and the denominator normalizes by the number of triangles that could possibly form around  $v_i$ . Generally, the degree and clustering coefficient are examples of a much broader class of statistics proposed for the description of local and neighborhood structure in graphs.

Complementing such descriptions, other statistics have been defined to measure the nature of paths in the graph and markers of mesoscale structure. For example, the average path length, various types of centrality [80, 22], notions of modularity [91, 115, 153], and the property of small-worldness have proven useful in the study of a wide variety of systems from the human brain [36, 18] to granular materials [158]. One particular method that, at the time of writing, we found to be unique to the graph framework is that of core-periphery structure. A graph with core-periphery structure contains a dense group of nodes connected to each other called the *core*, and a second group of nodes called the *periphery* that mostly connect to the core rather




**Fig. 5.2** *The three frameworks and their corresponding downstream analyses can offer different perspectives on a complex system. (Left) For this example system, a graph representation suggests a global core-periphery organization. (Middle) A simplicial complex representation of the same system appears to show a globally circular structure. (Right) The hypergraph representation of the same system hints at the presence of two communities.*

than to other nodes in the periphery [32, 174] (see Figure 5.2, left). For a description of other network statistics, we refer the interested reader to prior literature [144, 177]. Additionally, we note that in real-world systems, the values of many of these network statistics are correlated with one another over instances in a graph ensemble, and these patterns of shared variance can be used to distinguish between types of systems [50, 148].

**5.2. Methods for Simplicial Complexes.** Simplicial complexes have entered the data analysis scene more recently than graphs, yet we can still use a simplicial complex to investigate multiple levels of system architecture with intuitive methods and statistics. As before, we keep this section brief by focusing on only a few basic statistics and then one method that is unique to simplicial complexes.

We might first seek to extrapolate basic graph definitions to simplicial complexes. If we view a graph as the 1-skeleton of a simplicial complex, then the graph degree of node  $v_i$  corresponds to the number of 1-simplices in which  $v_i$  participates. By extending this idea, we can understand the neighborhood of a node (Figure 5.1, middle) by defining the *simplex participation* of node  $v_i$  as the vector  $P(v_i)$  in which the  $k$ th element is the number of  $(k - 1)$ -simplices in which  $v_i$  participates. One could also record the vector of simplices in which the node participates (called the upper degree in [187]), or the number of simplices not contained in any larger simplices, i.e., the maximal simplices, in which the node participates [193]. Notably, one can also define the degree of a simplex of any size, instead of only defining the degree of a node (which is, after all, a zero-dimensional simplex) [187]. Similarly, we might ask whether and how the clustering coefficient could be extended to the simplicial complex framework. Depending on the precise properties that one intends to capture, one could use a ratio of simplices from dimensions  $k$  and  $(k - 1)$  to formalize the notion of a clustering coefficient. However, in the simplicial complex framework each simplex can be considered as a fundamental building block, so it makes sense to also define a clustering coefficient for an arbitrary  $k$ -simplex as in [126]. In a complementary effort, the notion of centrality has recently been extended from the graph framework to the simplicial complex framework [74].

In addition to extending graph measures to simplicial complexes, we can also harness the theory of algebraic topology to uncover more complicated motifs within the



**Fig. 5.3** *Constructing the Dowker dual of a simplicial complex.* Given a concurrence matrix denoting which nodes connect via relations (top left), we can create a simplicial complex with each simplex defined by a relation  $(a, b, c, d)$ . Alternatively, we could transpose the matrix so that now we have four nodes  $(a, b, c, d)$  and five relations (bottom left). From this transposed concurrence matrix we can then create a simplicial complex whose simplices are defined by relations in the new concurrence matrix (bottom right). This simplicial complex is called the Dowker dual of the original simplicial complex and will have the same number of topological cavities.

system. The downward closure requirement within the simplicial complex definition gives us the ability to accurately identify which simplices are involved in higher-dimensional simplices. Consequently we can then detect where a dearth of simplices leaves topological voids in the complex (Figure 5.2, middle). Detecting topological voids is the work of *homology*, and as homology relies on well-defined mappings from larger to smaller simplices, this method is best suited for the framework of simplicial complexes.<sup>3</sup>

Simplicial complexes can also be “reversed” in a way that can be useful in understanding the structure of grouped nodes, while preserving the topological organization of the system. Consider constructing, for example, a simplicial complex in which nodes represent regions of the zebrafish brain and simplices represent coactivity during a task. We could encode the complex as a  $\#simplices \times \#nodes$  binary matrix sometimes also called a *concurrence matrix* or *incidence matrix* [86, 65]. In the top left of Figure 5.3 we show a small example concurrence matrix of five nodes (1, 2, 3, 4, and 5) connected through four relations ( $a, b, c$ , or  $d$ ). We create a simplicial complex (Figure 5.3, top right) by drawing maximal simplices between nodes that share a relation in the concurrence matrix. For the zebrafish example, the simplicial complex could contain relatively few simplices but orders of magnitude more nodes (depending on data availability of course), making calculations cumbersome. As an alternative, we could “reverse” the structure by constructing the *Dowker dual* [65]. Here, the role of nodes is swapped with the role of relations [65]. In the zebrafish example, we would form a node for each coactivity relation and then connect two nodes by simplices if they share a participating region in the zebrafish brain. In Figure 5.3 we transpose the concurrence matrix to swap the role of nodes and relations, and then show how we again create a simplicial complex now called the Dowker dual. This new complex will have the same number of nodes as the original complex had maximal simplices, so that if the number of relations was small with respect to the number of nodes in the

<sup>3</sup>Sometimes the words “structural” and “topological” are used interchangeably. In this work, we use the adjective “topological” to modify nouns relating to the theory of algebraic topology. We use “structural” to refer generally to the patterns formed by the units and relations of a system.

original complex, studying the Dowker dual will be more computationally tractable.<sup>4</sup> Importantly, studying the Dowker dual preserves specific topological structure within the system [65]: the homology groups of a simplicial complex and its Dowker dual are isomorphic. Thus, the Dowker dual can be an incredibly efficient representation, assuming that we still respect the scientific question at hand.

**5.3. Methods for Hypergraphs.** Like simplicial complexes, hypergraphs have gained popularity only recently, as many fields have begun to realize the importance of encoding polyadic relations in systems. The hypergraph framework is a natural extension of the graph framework, so unsurprisingly many (though certainly not all) computational methods for hypergraphs are extensions of computational methods for graphs. As before, we will highlight basic statistics here as well as a method unique to hypergraphs.

The framework of hypergraphs is also complemented by a set of descriptive statistics. Importantly, recall that each hyperedge arises independently since we have no rules relating hyperedges to each other, and consequently computations on hypergraphs must be interpreted differently from related computations on simplicial complexes. Starting simply, we can first extend the concept of degree to hypergraphs. In a hypergraph, the degree of a node  $d_H(v_i)$  is the number of hyperedges containing  $v_i$ , sometimes called the *hyperdegree*. Since hyperedges can connect any number of nodes, we also define the *hyperedge cardinality*, also called the *hyperedge degree*, as the number of nodes contained by the hyperedge. Importantly, note that in the definition of node degree, we do not stratify by hyperedge cardinality as the appearance of a large hyperedge gives no information about the existence of smaller hyperedges. Instead, a large hyperedge is simply another relation that contains our node of interest.

In order to understand a node's neighborhood in a hypergraph (Figure 5.1, right), next we move to a definition of the hypergraph clustering coefficient (see [112, 73, 159, 81] for others). Recall the graph clustering coefficient measures connectivity of a node's neighbors via connections that *do not* include the node of interest. If we examine, for example, node  $v_i$  and its neighbors, some neighbors will be connected via hyperedges that do or do not include  $v_i$ . Intuitively, node  $v_i$  should have high clustering if its neighbors connect via hyperedges that do not contain  $v_i$ . The *extra overlap*  $EO(v_i)$  of a node  $v_i$  helps us to quantify this idea; formally, the extra overlap of two hyperedges  $e_j, e_k$  is defined as

$$(5.2) \quad EO(e_j, e_k) = \frac{|N(D_{j,k}) \cap D_{k,j}| + |D_{j,k} \cap N(D_{k,j})|}{|D_{j,k}| + |D_{k,j}|},$$

where  $D_{j,k} = e_j \setminus e_k$  and  $N(U)$  is the set of all nodes that are neighbors of any node within the set  $U$ . Then, intuitively, the extra overlap between two hyperedges counts the number of nodes connected by outside hyperedges, and we normalize by the size of the two hyperedges under consideration. Note that if we have only hyperedges of cardinality 2, then the extra overlap over two edges involved in a triangle is 1. Finally, the hypergraph *clustering coefficient*  $C_H(v_i)$  of a node  $v_i$  is

$$C_H(v_i) = \begin{cases} \left( \binom{|M(v_i)|}{2} \right)^{-1} \sum_{e_j, e_k \in M(v_i)} EO(e_j, e_k) & \text{if } d_H(v_i) > 1, \\ 0 & \text{if } d_H(v_i) = 1, \end{cases}$$

<sup>4</sup>This construction is akin to the *line graph* construction in graph theory [95].



where  $M(v_i)$  is the collection of hyperedges that include  $v_i$  [231]. This definition for the hypergraph framework is thus similar in spirit to the definition of a clustering coefficient for a graph. Indeed, the former is equivalent to the latter when all hyperedges have cardinality 2.

We note that the hypergraph also has the ability to uniquely represent the absent substructures of a system. Much like identifying repeated structural patterns (or *motifs*) in a graph, a hypergraph allows us in principle to identify repeated patterns of *absent* hyperedges. We may have a case where, for example, pairwise hyperedges exist between four nodes that also connect via a 4-hyperedge, but no 3-hyperedges exist. An interesting research question for such a representation is to ask why we observe a lack of 3-node relations but an abundance of 2-node relations within every 4-node relation. Note that neither graphs nor simplicial complexes allow for this line of questioning due to the lack of polyadic relations or the requirement for downward closure, respectively. A detailed investigation of these absent substructures is outside the scope of this paper, but we can take a step in that direction by defining the following statistic, which we call the *fill coefficient* of a hyperedge  $h$ , as


$$(5.3) \quad f(h) = \frac{|g \in \mathcal{E} : g \subsetneq h \text{ and } |g| > 1|}{2^{|h|} - 2 - |h|},$$

where  $\mathcal{E}$  is the set of hyperedges and  $|\cdot|$  is the cardinality of a hyperedge. The fill coefficient intuitively describes the fraction of smaller hyperedges that exist within hyperedge  $h$ , taking into account the hyperedge cardinalities.

**5.4. Methods and Dependencies.** Before closing this section, we note that both in choosing analyses and in interpreting results, we need to keep in mind the dependencies within the system. For example, after creating a simplicial complex from our data, how do we interpret its clustering coefficient? What does the diameter of a system mean when we have hyperedges of different cardinalities linking nodes instead of (dyadic) edges? How do communities found from a simplicial complex [30] with subset dependencies differ from communities found within a hypergraph [108] without such dependencies? Can we intertwine different sorts of system dependencies to understand their impact on function? Examples of such intertwining methods include (i) Rentian scaling, which formalizes the interaction between structure and geography [45, 17, 156], and (ii) modularity maximization with spatial null models [77, 28]. Careful consideration of the above questions can only lead to better motivated and more interpretable and insightful results.

To summarize, we see that each base framework offers a particular perspective on the data it encodes. As we show in Figure 5.2, the choice of framework can influence how we interpret the complex system structure of the same dataset. The graph representation could suggest a core-periphery structure; the simplicial complex representation lets us see that globally the system organizes around one circle; and the hypergraph representation highlights the existence of two communities. We close this section by emphasizing the importance of framework choice for proper representation of the data and the appreciation that each analysis performed or pipeline chosen offers a different perspective on the underlying complex system (see Figure 5.4).

**6. Examples.** Putting it all together, in this section we will discuss examples of a system, its dependencies, and how we might represent the system using the frameworks described above. We will then explore possible analyses on each representation and compare results. Importantly, we will see that the subtle differences in



**Fig. 5.4** Updated analysis pipeline includes consideration of which computational methods to perform on the chosen representation, and what distinct or complementary perspectives these methods offer. The last step in our pipeline involves computationally analyzing the system representation. We note that each analysis provides its own perspective on the system representation. We recommend performing steps 1–4 with careful consideration in order to gain real insight into the system.

representations and their definitions can lead to inconsistent results and conflicting interpretations.

**6.1. Coauthorship.** Consider the system made up of scientific researchers who interact to write scientific papers (for example, [46]). What kind of dependencies govern the relations in this system? How should we encode this system formally? In the following paragraphs we analyze a fragment of this system following the workflow of Figure 5.4. We begin with a toy example (Figure 6.1) and later perform similar analyses on a real dataset (Figure 6.2).

**Dependencies.** First, we may expect to find spatial dependencies in this system, as the country of origin or university affiliation of a researcher may dictate which of their colleagues are willing or able to collaborate. Second, we may also expect temporal dependencies, as a researcher’s past collaborators may also influence any future collaborations. Third, whether or not this system exhibits subset dependencies depends upon which precise fragment we are interested in studying. If we focus solely on authors and consider two or more authors as related whenever they have worked together at some point, then it is necessarily the case that whenever a group of three authors have coauthored a paper, then any two of them have coauthored a paper, and therefore a polyadic relation always implies all smaller polyadic subrelations, including all dyadic subrelations. On the other hand, we may choose to focus on both researchers and scientific papers, in which case, we may want to think about one scientific paper as determining a single relation. In this scenario, the fact that three researchers are involved in a relation (because they have authored a paper together) does not imply that two of them have authored (another, separate) paper together. We will keep these dependencies in mind as we move through the later analysis steps.

**Externalities: Data Availability.** In a vacuum, we may expect to see all of the aforementioned dependencies in this system. However, the data available may be biased in such a way that, for example, researchers working (and papers produced) in one particular country are overrepresented. In this case, the data available may not adequately record the spatial dependencies involving, for example, researchers who travel frequently between two different countries. Moreover, if the dataset is further biased to include only researchers that work in one particular institution, then it is possible

that no spatial dependencies are recorded at all, since researchers in one institution may all work with one another with the same likelihood; that is, the location of one existing collaboration offers no new information about the likelihood of another collaboration.


**Externalities: Research Question.** Let us introduce a toy example to accompany our discussion. Consider a coauthorship dataset including four authors  $a_1, a_2, a_3$ , and  $a_4$  who have written four papers  $p_1, p_2, p_3$ , and  $p_4$  (Figure 6.1, top). The three papers were authored as follows: paper  $p_1$  was authored by  $\{a_1, a_2\}$ , paper  $p_2$  by  $\{a_2, a_4\}$ , paper  $p_3$  by  $\{a_1, a_2, a_3\}$ , and paper  $p_4$  by  $\{a_3, a_4\}$ . This toy example illustrates that whether the chosen representation reflects the dependencies inherent in the system is sometimes a subtle question of semantics. For example, if the relations in our representation are defined using the first question (“has this pair of authors worked together on at least one paper?”), then the set of relations will necessarily exhibit a subset dependency, regardless of whether or not the data available records a subset dependency found in the real system. In other words, one must be aware of which dependencies reflected in our representations come from the system, from how the data was collected or from the representation constructed. In this example it is the question at hand, the intricacies of the system under study, and the data available that together guide the choice of representation of these data.

**Representations.** If we take the information from Figure 6.1, top left, and construct the classic coauthor network in which an edge exists between two authors if they have appeared as coauthors on a paper, then we recover the graph shown in Figure 6.1, top right. In particular, note that as we construct the coauthorship graph, we ask the following question exactly once for each potential relation: “Has this *pair* of authors worked together on at least one paper?” Alternatively, we can consider polyadic relations between authors and ask, “Has this *set* of authors worked together on a paper?” This question naturally yields a simplicial complex (Figure 6.1, middle right), in which nodes form a simplex if the corresponding authors are a subset of the authors of at least one paper. Finally, we imagine the author list of the paper is nonredundant so that one paper corresponds to exactly one relation. Said another way, we respect that without each and every author, the paper could not have been completed. If we take this point of view, we will instead construct a hypergraph by repeatedly asking, “Has this set of authors exclusively (needing no other authors) written a paper together?” This approach retains the large group of three authors, but now clearly shows that, for example, authors  $a_1$  and  $a_3$  have not worked on a project as an exclusive group. Note that this information is not recoverable from either of the other representations.

Importantly, access to the full data about researchers and scientific papers would allow us to build any of the three frameworks discussed. However, if we only have information about coauthorship (which sets of authors have worked with each other) rather than full knowledge of the data, we would only be able to construct the graph version or the simplicial complex version, but not the hypergraph version.<sup>5</sup>

**Methods and Analyses.** Next we analyze the three different system representations. Of our coauthor representation (graph, simplicial complex, or hypergraph), we might first ask a simple question about the involvement of a node (author) in paper writing in order to gauge the author’s productivity. In the graph, we might use the node degree

<sup>5</sup>One could build a hypergraph version, but it would not be an appropriate representation for this scenario because it does not respect the blatant subset dependency.



**Fig. 6.1** *Example of different perspectives offered by each framework on a coauthor dataset. The data (far left) consists of a list of papers and their author list. Based on a question about what defines relations between authors, we build either a graph, a simplicial complex, or a hypergraph (right). If we start with the graph, we could also use the relations between frameworks to create a simplicial complex or a hypergraph (far right), though this process can result in inaccurate representations of the original data.*

to recover this information, which would tell us that authors  $a_2$  and  $a_3$  participated in the same number of collaborations. Moving to the simplicial complex, we see by looking at node participation in maximal simplices that again authors  $a_2$  and  $a_3$  could be described as equivalently collaborative. However, in the hypergraph representation, if we look at node degree, we see clearly that  $a_2$  has participated in more collaborative projects than any other author, a conclusion that we are only able to draw from the hypergraph representation. A similar experiment comparing authors  $a_1$  and  $a_4$  shows that in this scenario, both the simplicial complex and hypergraph encodings view these authors as having different sizes of collaborative projects, while the graph structure does not. Specifically, the graph tells us that both  $a_1$  and  $a_4$  have worked with  $a_2$  and  $a_3$ ; the simplicial complex tells us that  $a_1$  worked collectively with  $a_2$  and  $a_3$ , whereas  $a_4$  only worked individually with  $a_2$  and  $a_3$ ; and finally the hypergraph tells us that  $a_1$  had an individual project with  $a_2$  as well as a team project that also included  $a_3$ , while  $a_4$  only worked on two-person papers. These analyses illustrate how the subtle differences in the three representations and associated downstream analyses can yield insights that may be at odds with one another.

**Relationships between Frameworks.** In this toy example we have constructed each of the three representations directly from the data itself, with full knowledge of the raw data. However, we could also imagine that we are given the data already represented as one framework and then try transforming our representation to another framework. If we begin with one representation and translate to another framework, will we recover the same information as if we had constructed the structure directly from the data? Here, if we begin from a graph and move to a simplicial complex by attaching simplices to cliques (i.e., construct a *clique complex*), we recover a simplicial complex with two maximal simplices formed by  $a_1, a_2, a_3$  and  $a_2, a_3, a_4$  (Figure 6.1, far right). Moving then from simplicial complex to hypergraph we would form a hypergraph with two hyperedges between  $a_1, a_2, a_3$  and  $a_2, a_3, a_4$ ; see Figure 6.1, far bottom right. If we asked the same questions about author participation as we did above, then we


would find that both pairs  $(a_2, a_3)$  and  $(a_1, a_4)$  now seem to contribute in exactly the same way across representations. In studying complex systems we may receive only one representation of the system rather than the raw data, which can make switching to a different representation that perhaps better suits the planned analyses enticing. However, the present exercise underscores the importance of understanding the assumptions made by each framework; care must be taken when moving between frameworks, not simply in recasting the mathematical language used, but also in remaining true to the original data.

**Real Dataset Example.** We close this example by illustrating the above points in a real coauthorship dataset extracted from the DBLP computer science bibliography database [23]. This dataset consists of 3,700,681 scientific articles published between the years 2000 and 2016, as well as the list of authors of each article, for a total of 1,930,378 authors. Using this dataset, we build separately a graph, a simplicial complex, and a hypergraph directly from the data for each year contained in the dataset. In each representation, we measure the degree of each node, using the definitions in section 5. Figure 6.2(a) contains a scatterplot showing the degree of each node as measured in the different representations corresponding to year 2016. In this dataset, the degree in any representation is positively correlated to the degree in any other representation, though progressively less so as the degree of the node decreases. This result means that the different representations often agree more on which nodes have the largest degrees than on which nodes have small degree. This is important to keep in mind, especially in studies that make claims about the nodes of small degree, which often outnumber those with large degree.

To see how this correlation changes over time, for each year we calculate the Spearman rank correlation coefficient, which quantifies the similarity in node degree rankings between two representations. The Spearman rank correlation coefficient is equal to 1.0 when the rankings are equal, and  $-1.0$  when the rankings are exactly reversed. Shown in Figure 6.2(b), we measure this coefficient for each year and each pair of representations. We observe the highest correlation between degrees calculated from the simplicial complex representation (number of maximal simplices) and degrees calculated from the hypergraph representation (number of hyperedges), which is likely due to the fact that these two representations both encode the polyadic relations in the dataset. This result suggests that relatively few papers authored by a subset of the authors of another paper were written. We also observe that the node degrees calculated from the graph representations show a comparatively low correlation to the node degrees calculated from the other representations. In particular, the correlation between the graph and the hypergraph drops below 0.5 in some years, signaling a very different result when ranking nodes by graph degree or by hypergraph degree. Our observations imply that, in this dataset, we should be careful when making broad claims regarding the degree of nodes, especially those with few observed relations (i.e., small degrees), as each representation may yield different results that must be interpreted accordingly.

In summary, we have used this example to illustrate each step of the workflow from Figure 5.4, as well as to show that using different representations of the same dataset may yield measurements that are at odds with one another, even in the simple case of measuring node degree and when the representations are created directly from the data.


**6.2. Email Communications.** In our next example we again follow the workflow of Figure 5.4, but more succinctly. While in the previous example we discussed



**Fig. 6.2** *Correlation among degree measurements in different representations of the same dataset.* (a) Comparing the degree calculated from the graph or hypergraph representation (left), from the simplicial complex or hypergraph representation (middle), and from the graph or simplicial complex representation (right) from the coauthorship dataset extracted from the DBLP computer science bibliography database in the year 2016. Correlation is relatively high for nodes of large degree, but relatively low for nodes of small degree. (b) Spearman correlation coefficient calculated between node degrees from pairs of data representations in each year.

multiple types of dependencies, variations in data availability, and differing research questions, here we provide an example of a seemingly straightforward analysis on a dataset of emails.

We start by considering the following scenario. Suppose Ana works at a company and is tasked with improving communication and cohesiveness between teams in the workplace. Ana works at a big company that contains many teams in diverse areas, so she decides to prioritize her involvement by focusing on average team communication via an easily accessible medium such as email. Concretely, Ana wants to evaluate how well each team integrates with all members of the company, which translates to evaluating the average clustering coefficient of each team. For this purpose, Ana has collected all the internal email communications. She decides to operationalize her task as follows. First, if a set of at least 5 people have all received the same email at the same time, she will assume they must be working together as a team. Second, she decides to focus on emails with at most 25 participants, as emails with more than 25 participants are likely company-wide communications that do not involve a single team working together. Third, having identified a team, she will quantify the team's cohesiveness by averaging the clustering coefficient of each member in the team. Note that in this system we represent no spatial dependencies as email allows instant communication regardless of geographical location. Finally, Ana only cares about the teams and communication that have already occurred, and is not hoping to predict communication in the future, so for the presented analysis on aggregate communication she does not need to incorporate any temporal dependency that might exist within the system.



**Fig. 6.3** *Graph clustering and hypergraph clustering coefficients are loosely related. For different ranges of hyperedge cardinality, the average clustering coefficient of nodes within a hyperedge calculated with the projected graph definition is compared to the average clustering coefficient calculated from the hypergraph representation. Scatterplot points are colored by the  $\log(\text{fill coefficient})$ .*

To follow up on her plan, Ana needs to choose a framework with which to encode the data, as well as decide how to measure the clustering coefficient. If she chooses to encode the system as a graph where each employee is a node and each edge joins two nodes if they simultaneously received the same email, then she may use the clustering coefficient defined in section 5.1. Alternatively, she may choose to build a hypergraph where each node is an employee and each hyperedge denotes a single email, and use the clustering coefficient defined in section 5.3. A priori, one might expect that measuring the average clustering of a set of nodes in the graph is highly correlated to measuring the same quantity in the hypergraph. However, we will see that the subtle differences in definitions lead to varying results.

For this example, we use a dataset of email communications [23] containing 10,883 emails among 148 employees of a company, from March 1999 to October 2002. Each email has a corresponding set of participants which includes the sender and all recipients. In Figure 6.3 we see the results of Ana's analysis on this dataset, using both a graph and a hypergraph representation of these data. Each marker represents an email with between  $n$  and 25 participants, for  $n = 5, 6, 7, 8$ , i.e., what Ana considers to be a team. Each email is located according to the average clustering coefficient of the email's participants, as measured in the graph (horizontal axis) and in the hypergraph (vertical axis). In the top left panel we can see that there is very little correlation between these two quantities for teams of at least 5 people (Spearman rank correlation coefficient  $r = 0.1$  and associated p-value  $p = 0.16$ ). These results show that ranking teams of employees using these two different clustering coefficients yields very different results. Consequently, if Ana wants to prioritize teams in order



of how much she needs to intervene, in other words by ranking the teams according to average clustering coefficient, then the graph and hypergraph representations will recommend very different courses of action. Indeed, Ana would need to allocate her resources in entirely different ways depending on which representation she chose. This result does not change if Ana chooses to focus on teams of at least 6, 7, or 8 people, as shown in Figure 6.3.

Next, Ana decides to distinguish between team cohesiveness with the company and intrateam cohesiveness. That is, do those teams that communicate well with everyone in the company also have robust within-team communication? A team that has excellent internal communication would have a high fill coefficient, which measures the fraction of possible smaller hyperedges that exist between the nodes of a hyperedge (see section 5.3). In order to answer this question Ana calculates the fill coefficient of each team and adds this information as color on her scatterplots (Figure 6.3). By eye her results show no relationship between a team's cohesiveness with the company (clustering coefficient calculated from the graph or hypergraph representation) and a team's internal cohesiveness (fill coefficient).

Together, these experiments illustrate that even in the case when (a) the research question is fixed, (b) the researcher has access to the full dataset, and (c) there are little to no interactions among different types of dependencies, the choice of representation alone may still yield different insights by virtue of the different assumptions made by each one (here dyadic *versus* polyadic interactions).

**7. Applications.** We can naturally encode myriad systems in the real world with at least one of the frameworks discussed in this work. Still, often we focus on analyzing a system from a *particular* perspective and spend less time imagining how alternative analysis pipelines may be more revealing—or indeed more faithful to the system—than the currently used pipeline. Here we consider the alternative perspectives offered by the dependencies, frameworks, and challenges we have discussed in this paper.

First we consider the brain. The brain can be naturally conceived of as a system of individual parts that together form large functional units at different scales: neurons work together to communicate with each other forming co-firing patterns called *code words* [55], multiple neuronal populations become active to replay past trajectories and in doing so may help the organism plan and learn [147], and entire brain regions work in unison to form functional networks [82]. Scientists have successfully studied the brain by encoding it at any one of these scales using the representations discussed in this work [27]. For example, with graph representations researchers found the brain to exhibit small-worldness [15, 16, 141], modular architecture [198, 82], and hubs [1, 2]. Using the simplicial complex representation, at the larger scale cavities in the structural adult brain were observed [161, 193], and at a smaller scale researchers detected the geometric structure of pyramidal neuron firing patterns [87]. Finally, research employing a hypergraph representation has identified functional hub hyperedges [222], characterized types of hyperedges in developing children [90], and tracked changes in brain organization over both short [19, 57] and long time scales [58].

Looking to the future, one particularly little understood aspect of the brain is the impact of temporal dependency. How do specific relations affect the existence of any other relations in the future? For example, can a brain transition from any arbitrary state to any other state [49], or is its future activity bound by its past activity [12, 220]? Though the field has used temporal networks to investigate time-varying activity, at the time of writing we have not found the inclusion of temporal

dependencies within the representation. We suggest the application of higher-order network representations to deepen our understanding of temporal dependencies in this complex system. Additionally, at all scales the brain is spatially embedded [201], and previous work has shown that the strength of connections between brain regions often depends on the Euclidean distance between them [97, 172]. Often the analysis pipeline involves comparing any computed results on the empirical data against a spatially embedded null model [28], or comodeling the spatial relations and other relations such as by examining Rentian scaling [17, 98, 179]. While these approaches do help to determine the dependence of spatial features on other features, we suggest taking an additional step to directly encoding spatial dependencies in the formal representation of the data. For example, multilayer representations or sheaves encoding position information may be of help here.

Next we consider transportation, which is another well-studied system in network science. Transportation networks come in two different types: systems where the movement is done along fixed routes (such as roads, train tracks, power lines, or airline paths [173, 20, 185, 152, 47]), and systems where the movement is done freely through (outer) space [175]. Among these, analyses specifically of public transportation networks have incorporated multilayer networks [219] or variations thereof including internal node structure [188], and have also evaluated system-specific measures that include spatial organization [218]. Analyses involving temporal representations have included investigating congestion clusters in road networks [170] and how to alleviate them [103]. These analyses usually consider spatial and temporal dependencies by assigning weights to the representation's relations associated to distances or travel times [162, 183]. Importantly, studies are beginning to encode the temporal dependency in the representation itself, as higher-order networks have revealed these temporal dependencies in data from global shipping and web browsing [226].

The subset dependency is studied far less often than other types of dependencies in transportation systems. For example, in a public transport system, if relations are defined among  $k$  stations if there exists a route  $X$  that stops at all  $k$  stations, then certainly any subset of those  $k$  stations must also be related by route  $X$ . Alternatively, a subset dependency may or may not exist within traversed paths. For example, perhaps we observe paths of length  $k$  but we do not observe smaller subpaths. How might the identification or inclusion of subset dependencies within the transportation system improve our ability to prevent system failures or predict future activity? Additionally, we suggest further investigation of polyadic relations in these systems with simplicial complexes or hypergraphs where appropriate, as these representations may elucidate previously hidden system properties.

Finally, we consider applications in cellular systems composed of any subset of proteins, genes, regulatory units such as enhancers, epigenetic factors, and more [78, 4]. Most commonly the field studies system fragments such as genetic regulatory networks (GRNs) [61, 221, 71] and protein-protein interaction networks (PPINs) [62, 166]. Unlike the above two examples, this application differs in that only in rare situations can real-world interactions be observed. Consequently, tremendous effort focuses on network reconstruction from data, i.e., inferring the interactions from indirect measurements [146, 216, 3]. Temporal information such as fluctuations in RNA counts [196] and spatial information such as colocalization [128] can be used to reconstruct the network of interactions. Often, for example, in the system fragment of proteins and protein complexes, polyadic relations exist and have been encoded using simplicial complexes or hypergraphs [165]. Multilayer representations have also been used


for representing multiple biological layers important in disease [93] and for inferring protein function [228].

The difficulties associated with macromolecule-interaction systems create an enticing problem for developing system representations. Since the existence of interactions can rarely be observed directly, perhaps a representation with weights indicating the probability of the existence of each relation might be a useful alternative. In such a case, one might consider studying an ensemble of graphs, simplicial complexes, or hypergraphs instead of only one, and differentiating among them based on the likelihood of each one being a faithful representation of the real system. Additionally, though polyadic relations are known to play an important role in these systems [207], simplicial complex and hypergraph representations are more rarely employed (examples include [74, 189, 112]). Finally, temporal fluctuations are becoming easier to record in these systems [182], which offers the opportunity to directly study temporal dependencies.

**8. Discussion and Conclusion.** In this work we have examined each step of a data analysis pipeline suitable for studying complex systems (see Figure 8.1). We first discussed system dependencies which can manifest in different flavors including but not limited to temporal, subset, and spatial. We then defined common complex system frameworks and their underlying assumptions, as well as which dependencies they encode. We discussed the mathematical relationships between frameworks, and how information can be lost (or imputed) as we convert data from one framework to another. Finally, we offered analysis examples in order to underscore the importance of dependencies, careful choice of representation, and analysis techniques in studying complex systems.

The main message of our work is that there is no perfect way to analyze a system, and that studying two different systems may require two entirely different pipelines. That is, the modeling decisions made while studying one dataset compiled from a system will not necessarily carry over to another system or, indeed, not even to another dataset extracted from the same system. In contrast, we see that many studies apply certain pipelines for seemingly no other reason than because they are common within a certain field. Instead, we recommend that each new system and dataset be individually evaluated and investigated, and each assumption and pipeline decision be made in accordance with the concepts discussed here. More specifically, and following Figure 8.1, we suggest designing pipelines based on the system and system dependencies, any external dependencies that may be induced by the data type or data collection method, and the limits of the system fragment under study. From there, we suggest choosing a framework that best fits the data, the research question, and the system itself, even if it requires using a new framework or extension that is outside of what is customary. Finally, we recommend choosing carefully the specific methods, measurements, and analyses performed on the chosen representation, and keeping in mind that their results may be biased by the choices made in the previous stages. Different choices at each of these steps may ultimately yield results that are at odds with the results yielded by other choices. Only after respecting the system's dependencies and unique qualities through proper representation and analysis methods will we uncover novel insights into the system under study.

Though here we present only a first attempt to unify the application of complex systems analyses, we hope that the drive for more accurate representations will continue to push the field both forward *and* closer together through multiplying collaborations. We imagine that complex systems researchers in the future may each



**Fig. 8.1** *Complex system analysis pipeline discussed in this paper. To begin, we suggest considering how the research question, data availability, and system dependencies may influence downstream analyses. We have discussed subset, spatial, and temporal dependencies (red). We suggest choosing a framework (navy) that preserves and respects dependencies within the system and data. Frameworks themselves are mathematically related (light blue), but switching frameworks after the initial data encoding can result in making inaccurate assumptions or forgetting independent relations. Finally, choosing the appropriate analysis method for the system and representation (green) after all other steps have been performed carefully can offer insights into the system's behavior, structure, or function.*

have a slew of representations along with carefully chosen computations that respect the dependencies one finds within the system. By continuing this discussion, the separate areas of science that use complex systems analyses will together identify what is missing from current frameworks, create more insightful analyses, and generate novel techniques.

**9. Citation Diversity Statement.** Recent work in several fields of science has identified a bias in citation practices such that papers from women and other minorities are undercited relative to the number of such papers in the field [68, 127, 38, 42, 208, 64]. Here we sought to proactively consider choosing references that reflect the diversity of the field in thought, form of contribution, gender, and other factors. Gender bias can arise due to explicit and implicit bias against a person's known gender as a woman, or due to explicit or implicit bias against a person carrying a name commonly used by women [124, 154, 139]. To evaluate the former (bias according to known gender), we obtained predicted gender of the first and last authors of each reference using pronouns affiliated with them online or pronouns known by personal friendships; by this measure (and excluding self-citations to the first and last authors of our current paper), our references contain 41% man(first)/man(last), 14% man/woman, 9%

woman/man, 14% woman/woman, 0% nonbinary, and 21% unknown categorization. This method is limited in that pronouns may not be indicative of gender identity, and may not be consistent across time or environment. To evaluate the latter (bias according to a gendered name), we used databases that store the probability of a name being carried by a woman; by this measure (again excluding self-citations), our references contains 60% man/man names, 12% man/woman names, 11% woman/man names, 10% woman/woman names, and 7% unknown categorization [230, 68]. This method is limited in that it cannot account for intersex, nonbinary, or transgender people. We look forward to future work that could help us to better understand how to support equitable practices in science.

**Acknowledgments.** First and foremost, we wish to acknowledge the colleagues, coauthors, mentors, and mentees who have shaped our perspectives on this subject. Next, we wish to thank Jason Kim, Linden Parkes, and Shubhankar Patankar for their helpful and constructive comments on an earlier version of this manuscript.

## REFERENCES

- [1] S. ACHARD, C. DELON-MARTIN, P. E. VÉRTES, F. RENARD, M. SCHENCK, F. SCHNEIDER, C. HEINRICH, S. KREMER, AND E. T. BULLMORE, *Hubs of brain functional networks are radically reorganized in comatose patients*, Proc. Natl. Acad. Sci. USA, 109 (2012), pp. 20608–20613. (Cited on p. 471)
- [2] S. ACHARD, R. SALVADOR, B. WHITCHER, J. SUCKLING, AND E. BULLMORE, *A resilient, low-frequency, small-world human brain functional network with highly connected association cortical hubs*, J. Neurosci., 26 (2006), pp. 63–72. (Cited on p. 471)
- [3] R. ALBERT, *Network inference, analysis, and modeling in systems biology*, The Plant Cell, 19 (2007), pp. 3327–3338. (Cited on p. 472)
- [4] U. ALON, *Network motifs: Theory and experimental approaches*, Nature Rev. Genetics, 8 (2007), pp. 450–461. (Cited on p. 472)
- [5] L. A. N. AMARAL, A. SCALA, M. BARTHÉLEMY, AND H. E. STANLEY, *Classes of small-world networks*, Proc. Natl. Acad. Sci. USA, 97 (2000), pp. 11149–11152. (Cited on p. 447)
- [6] *Apache Airflow*, <https://airflow.apache.org/>, The Apache Software Foundation, 2020 (accessed 2020-05-22). (Cited on p. 450)
- [7] A. APOLLONI, C. POLETO, AND V. COLIZZA, *Age-specific contacts and travel patterns in the spatial spread of 2009 H1N1 influenza pandemic*, BMC Infectious Dis., 13 (2013), art. 176. (Cited on p. 445)
- [8] V. ARORA AND M. VENTRESCA, *Action-based modeling of complex networks*, Sci. Rep., 7 (2017), pp. 1–10. (Cited on p. 453)
- [9] R. H. ATKIN, *From cohomology in physics to q-connectivity in social science*, Internat. J. Man-Machine Stud., 4 (1972), pp. 139–167. (Cited on p. 449)
- [10] A.-L. BARABÁSI AND R. ALBERT, *Emergence of scaling in random networks*, Science, 286 (1999), pp. 509–512. (Cited on p. 448)
- [11] M. BARIGOZZI, G. FAGIOLO, AND G. MANGIONI, *Identifying the community structure of the international-trade multi-network*, Phys. A, 390 (2011), pp. 2051–2066. (Cited on p. 452)
- [12] A. BARNES, E. T. BULLMORE, AND J. SUCKLING, *Endogenous human brain dynamics recover slowly following cognitive effort*, PLoS One, 4 (2009), art. e6626. (Cited on p. 471)
- [13] M. BARTHÉLEMY, *Spatial networks*, Phys. Rep., 499 (2011), pp. 1–101. (Cited on p. 444)
- [14] M. BARTHÉLEMY, *Transitions in spatial networks*, C. R. Phys., 19 (2018), pp. 205–232. (Cited on p. 444)
- [15] D. S. BASSETT AND E. T. BULLMORE, *Small-world brain networks*, Neuroscientist, 12 (2006), pp. 512–523. (Cited on p. 471)
- [16] D. S. BASSETT AND E. T. BULLMORE, *Small-world brain networks revisited*, Neuroscientist, 23 (2017), pp. 499–516. (Cited on p. 471)
- [17] D. S. BASSETT, D. L. GREENFIELD, A. MEYER-LINDENBERG, D. R. WEINBERGER, S. W. MOORE, AND E. T. BULLMORE, *Efficient physical embedding of topologically complex information processing networks in brains and computer circuits*, PLoS Comput. Biol., 6 (2010), art. e1000748. (Cited on pp. 464, 472)

- [18] D. S. BASSETT AND O. SPORNS, *Network neuroscience*, Nature Neurosci., 20 (2017), pp. 353–364. (Cited on pp. 448, 460)
- [19] D. S. BASSETT, N. F. WYMBS, M. A. PORTER, P. J. MUCHA, AND S. T. GRAFTON, *Cross-linked structure of network evolution*, Chaos, 24 (2014), art. 013112. (Cited on pp. 450, 471)
- [20] H. BAST, D. DELLING, A. GOLDBERG, M. MÜLLER-HANNEMANN, T. PAJOR, P. SANDERS, D. WAGNER, AND R. F. WERNECK, *Route planning in transportation networks*, in Algorithm Engineering, Springer, 2016, pp. 19–80. (Cited on p. 472)
- [21] F. BATTISTON, G. CENCETTI, I. IACOPINI, V. LATORA, M. LUCAS, A. PATANIA, J.-G. YOUNG, AND G. PETRI, *Networks beyond pairwise interactions: Structure and dynamics*, Phys. Rep., 874 (2020), pp. 1–92. (Cited on p. 447)
- [22] A. BAVELAS, *Communication patterns in task-oriented groups*, J. Acoust. Soc. Amer., 22 (1950), pp. 725–730. (Cited on p. 460)
- [23] A. R. BENSON, R. ABEBE, M. T. SCHAUB, A. JADBABAIE, AND J. M. KLEINBERG, *Simplicial closure and higher-order link prediction*, Proc. Natl. Acad. Sci. USA, 115 (2018), pp. E11221–E11230. (Cited on pp. 438, 468, 470)
- [24] A. R. BENSON, D. F. GLEICH, AND J. LESKOVEC, *Higher-order organization of complex networks*, Science, 353 (2016), pp. 163–166. (Cited on pp. 438, 443, 453)
- [25] A. R. BENSON, R. KUMAR, AND A. TOMKINS, *Sequences of sets*, in Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining KDD, 2018, pp. 1148–1157. (Cited on p. 453)
- [26] C. BERGE, *Hypergraphs: Combinatorics of Finite Sets*, Math. Engrg. 45, Elsevier, 1984. (Cited on p. 449)
- [27] R. F. BETZEL AND D. S. BASSETT, *Multi-scale brain networks*, NeuroImage, 160 (2017), pp. 73–83. (Cited on p. 471)
- [28] R. F. BETZEL, J. D. MEDAGLIA, L. PAPADOPOULOS, G. L. BAUM, R. GUR, R. GUR, D. ROALF, T. D. SATTERTHWAITTE, AND D. S. BASSETT, *The modular organization of human anatomical brain networks: Accounting for the cost of wiring*, Network Neurosci., 1 (2017), pp. 42–68. (Cited on pp. 464, 472)
- [29] G. BIANCONI, *Multilayer Networks: Structure and Function*, Oxford University Press, 2018. (Cited on p. 452)
- [30] J. C. W. BILLINGS, M. HU, G. LERDA, A. N. MEDVEDEV, F. MOTTES, A. ONICAS, A. SANTORO, AND G. PETRI, *Simplex2Vec Embeddings for Community Detection in Simplicial Complexes*, preprint, <https://arxiv.org/abs/1906.09068>, 2019. (Cited on p. 464)
- [31] S. BOCCALETTI, G. BIANCONI, R. CRIADO, C. I. DEL GENIO, J. GÓMEZ-GARDENES, M. ROMANCE, I. SENDINA-NADAL, Z. WANG, AND M. ZANIN, *The structure and dynamics of multilayer networks*, Phys. Rep., 544 (2014), pp. 1–122. (Cited on p. 452)
- [32] S. P. BORGATTI AND M. G. EVERETT, *Models of core/periphery structures*, Social Networks, 21 (2000), pp. 375–395. (Cited on p. 461)
- [33] C. BORGS AND J. CHAYES, *Graphons: A nonparametric method to model, estimate, and design algorithms for massive networks*, in Proceedings of the 2017 ACM Conference on Economics and Computation, ACM, 2017, pp. 665–672. (Cited on p. 453)
- [34] R. BOTVINIK-NEZER, F. HOLZMEISTER, C. F. CAMERER, A. DREBER, J. HUBER, M. JOHANNESSON, M. KIRCHLER, R. IWANIR, J. A. MUMFORD, R. A. ADCOCK ET AL., *Variability in the analysis of a single neuroimaging dataset by many teams*, Nature, 582 (2020), pp. 84–88. (Cited on p. 437)
- [35] C. D. BRUMMITT, R. M. D’SOUZA, AND E. A. LEICHT, *Suppressing cascades of load in interdependent networks*, Proc. Natl. Acad. Sci. USA, 109 (2012), pp. E680–E689. (Cited on p. 452)
- [36] E. T. BULLMORE AND O. SPORNS, *Complex brain networks: Graph theoretical analysis of structural and functional systems*, Nature Rev. Neurosci., 10 (2009), pp. 186–198. (Cited on pp. 448, 460)
- [37] C. T. BUTTS, *Revisiting the foundations of network analysis*, Science, 325 (2009), pp. 414–416. (Cited on p. 440)
- [38] N. CAPLAR, S. TACCHELLA, AND S. BIRRER, *Quantitative evaluation of gender bias in astronomical publications from citation counts*, Nature Astron., 1 (2017), pp. 1–5. (Cited on p. 474)
- [39] G. CARLSSON, *Topology and data*, Bull. Amer. Math. Soc., 46 (2009), pp. 255–308. (Cited on p. 451)
- [40] G. CARLSSON, T. ISHKHANOV, V. DE SILVA, AND A. ZOMORODIAN, *On the local behavior of spaces of natural images*, Internat. J. Comput. Vis., 76 (2008), pp. 1–12. (Cited on p. 449)

- [41] D. CHAKRABARTI, Y. WANG, C. WANG, J. LESKOVEC, AND C. FALOUTSOS, *Epidemic thresholds in real networks*, ACM Trans. Inform. Syst. Security, 10 (2008), art. 13. (Cited on p. 459)
- [42] P. CHAKRAVARTTY, R. KUO, V. GRUBBS, AND C. MCILWAIN, *#CommunicationSoWhite*, J. Commun., 68 (2018), pp. 254–266. (Cited on p. 474)
- [43] P. CHODROW AND A. MELLOR, *Annotated hypergraphs: Models and applications*, Appl. Network Sci., 5 (2020), art. 9. (Cited on p. 459)
- [44] P. S. CHODROW, Z. AL-AWWAD, S. JIANG, AND M. C. GONZÁLEZ, *Demand and congestion in multiplex transportation networks*, PLoS One, 11 (2016), art. e0161738. (Cited on pp. 451, 456)
- [45] P. CHRISTIE AND D. STROOBANDT, *The interpretation and application of rent's rule*, IEEE Trans. Very Large Scale Integration (VLSI) Systems, 8 (2000), pp. 639–648. (Cited on p. 464)
- [46] A. CLAUSET, D. B. LARREMORE, AND R. SINATRA, *Data-driven predictions in the science of science*, Science, 355 (2017), pp. 477–480. (Cited on p. 465)
- [47] V. COLIZZA, A. BARRAT, M. BARTHÉLEMY, AND A. VESPIGNANI, *The role of the airline transportation network in the prediction and predictability of global epidemics*, Proc. Natl. Acad. Sci. USA, 103 (2006), pp. 2015–2020. (Cited on p. 472)
- [48] V. COLIZZA AND A. VESPIGNANI, *Epidemic modeling in metapopulation systems with heterogeneous coupling pattern: Theory and simulations*, J. Theoret. Biol., 251 (2008), pp. 450–467. (Cited on p. 453)
- [49] E. J. CORNBLATH, A. ASHOURVAN, J. Z. KIM, R. F. BETZEL, R. CIRIC, A. ADEBIMPE, G. L. BAUM, X. HE, K. RUPAREL, T. M. MOORE, R. C. GUR, R. E. GUR, R. T. SHINOHARA, D. R. ROALF, T. D. SATTERTHWAITE, AND D. S. BASSETT, *Temporal sequences of brain activity at rest are constrained by white matter structure and modulated by cognitive demands*, Commun. Biol., 3 (2020), art. 261. (Cited on p. 471)
- [50] L. D. F. COSTA, F. A. RODRIGUES, G. TRAVIESO, AND P. R. VILLAS BOAS, *Characterization of complex networks: A survey of measurements*, Adv. Phys., 56 (2007), pp. 167–242. (Cited on p. 461)
- [51] O. T. COURTNEY AND G. BIANCONI, *Generalized network structures: The configuration model and the canonical ensemble of simplicial complexes*, Phys. Rev. E, 93 (2016), art. 062311. (Cited on p. 449)
- [52] O. T. COURTNEY AND G. BIANCONI, *Dense power-law networks and simplicial complexes*, Phys. Rev. E, 97 (2018), art. 052303. (Cited on p. 449)
- [53] J. M. CURRY, *Sheaves, Cosheaves and Their Applications*, Ph.D. thesis, University of Pennsylvania, 2014. (Cited on p. 453)
- [54] C. CURTO, *What can topology tell us about the neural code?*, Bull. Amer. Math. Soc., 54 (2017), pp. 63–78. (Cited on pp. 440, 449)
- [55] C. CURTO, E. GROSS, J. JEFFRIES, K. MORRISON, M. OMAR, Z. ROSEN, A. SHIU, AND N. YOUNGS, *What makes a neural code convex?*, SIAM J. Appl. Alg. Geom., 1 (2017), pp. 222–238, <https://doi.org/10.1137/16M1073170>. (Cited on p. 471)
- [56] D. B. DAMIANO AND M. R. MCGUIRL, *A topological analysis of targeted in-111 uptake in SPECT images of murine tumors*, J. Math. Biol., 76 (2018), pp. 1559–1587. (Cited on p. 449)
- [57] E. N. DAVISON, K. J. SCHLESINGER, D. S. BASSETT, M.-E. LYNALL, M. B. MILLER, S. T. GRAFTON, AND J. M. CARLSON, *Brain network adaptability across task states*, PLoS Comput. Biol., 11 (2015), art. e1004029. (Cited on pp. 450, 471)
- [58] E. N. DAVISON, B. O. TURNER, K. J. SCHLESINGER, M. B. MILLER, S. T. GRAFTON, D. S. BASSETT, AND J. M. CARLSON, *Individual differences in dynamic functional brain connectivity across the human lifespan*, PLoS Comput. Biol., 12 (2016), art. e1005178. (Cited on pp. 450, 471)
- [59] M. DE DOMENICO, C. GRANELL, M. A. PORTER, AND A. ARENAS, *The physics of spreading processes in multilayer networks*, Nature Phys., 12 (2016), pp. 901–906. (Cited on p. 452)
- [60] M. DE DOMENICO, A. LANCICHINETTI, A. ARENAS, AND M. ROSVALL, *Identifying modular flows on multilayer networks reveals highly overlapping organization in interconnected systems*, Phys. Rev. X, 5 (2015), art. 011027. (Cited on pp. 443, 453)
- [61] H. DE JONG, *Modeling and simulation of genetic regulatory systems: A literature review*, J. Comput. Biol., 9 (2002), pp. 67–103. (Cited on p. 472)
- [62] J. DE LAS RIVAS AND C. FONTANILLO, *Protein–protein interactions essentials: Key concepts to building and analyzing interactome networks*, PLoS Comput. Biol., 6 (2010), art. e1000807. (Cited on p. 472)



- [63] A. DE MONTIS, M. BARTHÉLEMY, A. CHESSA, AND A. VESPIGNANI, *The structure of interurban traffic: A weighted network analysis*, Environ. Planning B Planning and Design, 34 (2007), pp. 905–924. (Cited on p. 451)
- [64] M. L. DION, J. L. SUMNER, AND S. M. MITCHELL, *Gendered citation patterns across political science and social science methodology fields*, Polit. Anal., 26 (2018), pp. 312–327. (Cited on p. 474)
- [65] C. H. DOWKER, *Homology groups of relations*, Ann. of Math. (2), 56 (1952), pp. 84–95. (Cited on pp. 462, 463)
- [66] R. M. D’SOUZA, J. GÓMEZ-GARDEÑES, J. NAGLER, AND A. ARENAS, *Explosive phenomena in complex networks*, Adv. Phys., 68 (2019), pp. 123–223. (Cited on p. 450)
- [67] O. DUNAEVA, H. EDELSBRUNNER, A. LUKYANOV, M. MACHIN, D. MALKOVA, R. KUVAEV, AND S. KASHIN, *The classification of endoscopy images with persistent homology*, Pattern Recognition Lett., 83 (2016), pp. 13–22. (Cited on p. 449)
- [68] J. D. DWORKIN, K. A. LINN, E. G. TEICH, P. ZURN, R. T. SHINOHARA, AND D. S. BASSETT, *The extent and drivers of gender imbalance in neuroscience reference lists*, Nature Neurosci., 23 (2020), pp. 918–926. (Cited on pp. 474, 475)
- [69] H. EDELSBRUNNER, D. LETSCHER, AND A. ZOMORODIAN, *Topological persistence and simplification*, in Proc. of the 41st Annual Symposium on Foundations of Computer Science, IEEE, 2000, pp. 454–463. (Cited on p. 449)
- [70] D. EDLER, L. BOHLIN, AND M. ROSVALL, *Mapping higher-order network flows in memory and multilayer networks with infomap*, Algorithms, 10 (2017), art. 112. (Cited on pp. 443, 453)
- [71] F. EMMERT-STREIB, M. DEHMER, AND B. HAIBE-KAINS, *Gene regulatory networks and their applications: Understanding biological and medical problems in terms of networks*, Frontiers Cell Develop. Biol., 2 (2014), p. 38. (Cited on p. 472)
- [72] E. ESTRADA, G. ESTRADA-RODRIGUEZ, AND H. GIMPERLEIN, *Metaplex networks: Influence of the exo-endo structure of complex systems on diffusion*, SIAM Rev., 62 (2020), pp. 617–645, <https://doi.org/10.1137/18M1236253>. (Cited on p. 453)
- [73] E. ESTRADA AND J. A. RODRÍGUEZ-VELÁZQUEZ, *Subgraph centrality and clustering in complex hyper-networks*, Phys. A, 364 (2006), pp. 581–594. (Cited on p. 463)
- [74] E. ESTRADA AND G. J. ROSS, *Centralities in simplicial complexes. Applications to protein interaction networks*, J. Theoret. Biol., 438 (2018), pp. 46–60. (Cited on pp. 461, 473)
- [75] L. EULER, *Solutio problematis ad geometriam situs pertinentis*, Commentarii Academiae Scientiarum Petropolitanae, 8 (1741), pp. 128–140. (Cited on p. 448)
- [76] S. EVEN, *Graph Algorithms*, Cambridge University Press, 2011. (Cited on p. 448)
- [77] P. EXPERT, T. S. EVANS, V. D. BLONDEL, AND R. LAMBIOTTE, *Uncovering space-independent communities in spatial networks*, Proc. Natl. Acad. Sci. USA, 108 (2011), pp. 7663–7668. (Cited on p. 464)
- [78] V. FIONDA, *Networks in Biology*, Elsevier, 2019. (Cited on p. 472)
- [79] L. FREEMAN, *The Development of Social Network Analysis: A Study in the Sociology of Science*, Empirical Press, 2004. (Cited on p. 448)
- [80] L. C. FREEMAN, *A set of measures of centrality based on betweenness*, Sociometry, 40 (1977), pp. 35–41. (Cited on p. 460)
- [81] S. R. GALLAGHER AND D. S. GOLDBERG, *Clustering coefficients in protein interaction hyper-networks*, in Proceedings of the International Conference on Bioinformatics, Computational Biology and Biomedical Informatics, 2013, pp. 552–560. (Cited on p. 463)
- [82] C. L. GALLEN AND M. D’ESPOSITO, *Brain modularity: A biomarker of intervention-related plasticity*, Trends Cognitive Sci., 23 (2019), pp. 293–304. (Cited on p. 471)
- [83] G. GALLO, G. LONGO, S. PALLOTTINO, AND S. NGUYEN, *Directed hypergraphs and applications*, Discrete Appl. Math., 42 (1993), pp. 177–201. (Cited on pp. 450, 451)
- [84] R. GHRIST, *Barcodes: The persistent topology of data*, Bull. Amer. Math. Soc., 45 (2008), pp. 61–75. (Cited on p. 451)
- [85] R. GHRIST AND Y. HIRAOKA, *Applications of sheaf cohomology and exact sequences to network coding*, in Proceedings of the 2011 Nonlinear Theory and Its Applications, NOLTA, 2011. (Cited on p. 453)
- [86] C. GIUSTI, R. GHRIST, AND D. S. BASSETT, *Two’s company, three (or more) is a simplex*, J. Comput. Neurosci., 41 (2016), pp. 1–14. (Cited on p. 462)
- [87] C. GIUSTI, E. PASTALKOVA, C. CURTO, AND V. ITSKOV, *Clique topology reveals intrinsic geometric structure in neural correlations*, Proc. Natl. Acad. Sci. USA, 112 (2015), pp. 13455–13460. (Cited on pp. 449, 451, 471)
- [88] S. GNESI, U. MONTANARI, AND A. MARTELLI, *Dynamic programming as graph searching: An algebraic approach*, J. ACM, 28 (1981), pp. 737–751. (Cited on p. 450)

- [89] D. J. GREENE, C. N. LESSOV-SCHLAGGAR, AND B. L. SCHLAGGAR, *Development of the brain's functional network architecture*, in *Neurobiology of Language*, Elsevier, 2016, pp. 399–406. (Cited on p. 446)
- [90] S. GU, M. YANG, J. D. MEDAGLIA, R. C. GUR, R. E. GUR, T. D. SATTERTHWAITE, AND D. S. BASSETT, *Functional hypergraph uncovers novel covariant structures over neurodevelopment*, *Human Brain Mapping*, 38 (2017), pp. 3823–3835. (Cited on pp. 450, 471)
- [91] R. GUIMERA, M. SALES-PARDO, AND L. A. N. AMARAL, *Modularity from fluctuations in random graphs and complex networks*, *Phys. Rev. E*, 70 (2004), art. 025101. (Cited on p. 460)
- [92] M. HABIBI AND P. KHOSRAVI, *Disruption of the protein complexes from weighted complex networks*, *IEEE/ACM Trans. Comput. Biol. Bioinform.*, 17 (2020), pp. 102–109. (Cited on p. 459)
- [93] A. HALU, M. DE DOMENICO, A. ARENAS, AND A. SHARMA, *The multiplex network of human diseases*, *NPJ Syst. Biol. Appl.*, 5 (2019), pp. 1–12. (Cited on p. 473)
- [94] I. HANSKI, *Metapopulation Ecology*, Oxford University Press, 1999. (Cited on p. 453)
- [95] F. HARARY AND R. Z. NORMAN, *Some properties of line digraphs*, *Rendiconti del Circolo Matematico di Palermo*, 9 (1960), pp. 161–168. (Cited on p. 463)
- [96] P. HOLME AND J. SARAMÄKI, *Temporal networks*, *Phys. Rep.*, 519 (2012), pp. 97–125. (Cited on p. 451)
- [97] S. HORVÁT, R. GĂMĂNUT, M. ERCSEY-RAVASZ, L. MAGROU, B. GĂMĂNUT, D. C. VAN ESSEN, A. BURKHALTER, K. KNOBLAUCH, Z. TOROCZKAI, AND H. KENNEDY, *Spatial embedding and wiring cost constrain the functional layout of the cortical network of rodents and primates*, *PLoS Biol.*, 14 (2016), art. e1002512. (Cited on p. 472)
- [98] J. J. HOW AND S. NAVLAKHA, *Evidence of Rentian scaling of functional modules in diverse biological networks*, *Neural Comput.*, 30 (2018), pp. 2210–2244. (Cited on p. 472)
- [99] S. HU, H. YANG, B. CAI, AND C. YANG, *Research on spatial economic structure for different economic sectors from a perspective of a complex network*, *Phys. A*, 392 (2013), pp. 3682–3697. (Cited on p. 444)
- [100] I. IACOPINI, G. PETRI, A. BARRAT, AND V. LATORA, *Simplicial models of social contagion*, *Nature Commun.*, 10 (2019), pp. 1–9. (Cited on p. 460)
- [101] P. S. P. IGNACIO AND I. K. DARCY, *Tracing patterns and shapes in remittance and migration networks via persistent homology*, *EPJ Data Sci.*, 8 (2019), art. 1. (Cited on p. 450)
- [102] B. JHUN, M. JO, AND B. KAHNG, *Simplicial SIS model in scale-free uniform hypergraph*, *J. Stat. Mech. Theory Exp.*, 2019 (2019), art. 123207. (Cited on p. 460)
- [103] Y. JI AND N. GEROLIMINIS, *Spatial and temporal analysis of congestion in urban transportation networks*, in *Transportation Research Board Annual Meeting*, Washington, D.C., 2011. (Cited on p. 472)
- [104] C. W. JOHNSON, *What are emergent properties and how do they affect the engineering of complex systems?*, *Reliab. Engrg. Syst. Safety*, 91 (2006), pp. 1475–1481. (Cited on p. 436)
- [105] M. KAHLE, *Topology of random clique complexes*, *Discrete Math.*, 309 (2009), pp. 1658–1671. (Cited on p. 457)
- [106] M. KAHLE, *Sharp vanishing thresholds for cohomology of random flag complexes*, *Ann. of Math. (2)*, 179 (2014), pp. 1085–1107. (Cited on p. 457)
- [107] A. N. KHAMBHATI, A. E. SIZEMORE, R. F. BETZEL, AND D. S. BASSETT, *Modeling and interpreting mesoscale network dynamics*, *NeuroImage*, 180 (2018), pp. 337–349. (Cited on p. 453)
- [108] C. KIM, A. S. BANDEIRA, AND M. X. GOEMANS, *Community detection in hypergraphs, spiked tensor models, and sum-of-squares*, in *2017 International Conference on Sampling Theory and Applications (SampTA)*, IEEE, 2017, pp. 124–128. (Cited on p. 464)
- [109] M. KIVELÄ, A. ARENAS, M. BARTHÉLEMY, J. P. GLEESON, Y. MORENO, AND M. A. PORTER, *Multilayer networks*, *J. Complex Networks*, 2 (2014), pp. 203–271. (Cited on p. 452)
- [110] S. KIVELSON AND S. A. KIVELSON, *Defining emergence in physics*, *Nature Partner J. Quant. Mat.*, 1 (2016), art. 16024. (Cited on p. 436)
- [111] S. KLAMT AND E. D. GILLES, *Minimal cut sets in biochemical reaction networks*, *Bioinform.*, 20 (2004), pp. 226–234. (Cited on p. 450)
- [112] S. KLAMT, U.-U. HAUS, AND F. THEIS, *Hypergraphs and cellular networks*, *PLoS Comput. Biol.*, 5 (2009), art. e1000385. (Cited on pp. 463, 473)
- [113] M. KOTLIAR, A. V. KARTASHOV, AND A. BARSKI, *CWL-Airflow: A lightweight pipeline manager supporting common workflow language*, *GigaSci.*, 8 (2019), art. giz084. (Cited on p. 450)

- [114] L. KRISHNAMURTHY, J. NADEAU, G. OZSOYOGLU, M. OZSOYOGLU, G. SCHAEFFER, M. TASAN, AND W. XU, *Pathways database system: An integrated system for biological pathways*, Bioinform., 19 (2003), pp. 930–937. (Cited on p. 450)
- [115] F. KRZAKALA, C. MOORE, E. MOSSEL, J. NEEMAN, A. SLY, L. ZDEBOROVÁ, AND P. ZHANG, *Spectral redemption in clustering sparse networks*, Proc. Natl. Acad. Sci. USA, 110 (2013), pp. 20935–20940. (Cited on p. 460)
- [116] J. LADYMAN AND K. WIESNER, *What Is a Complex System?*, Yale University Press, 2020, <https://yalebooks.yale.edu/book/9780300251104/what-complex-system>. (Cited on p. 437)
- [117] E. C. LAI, *Notch signaling: Control of cell communication and cell fate*, Development, 131 (2004), pp. 965–973. (Cited on p. 444)
- [118] R. LAMBIOTTE, M. ROSVALL, AND I. SCHOLTES, *From networks to optimal higher-order models of complex systems*, Nature Phys., 15 (2019), pp. 313–320. (Cited on p. 443)
- [119] R. LAMBIOTTE, V. SALNIKOV, AND M. ROSVALL, *Effect of memory on the dynamics of random walks on networks*, J. Complex Networks, 3 (2014), pp. 177–188. (Cited on pp. 443, 453)
- [120] G. LEVI AND F. SIROVICH, *Generalized AND/OR graphs*, Artificial Intell., 7 (1976), pp. 243–259. (Cited on p. 450)
- [121] R. LEVINS, *Some demographic and genetic consequences of environmental heterogeneity for biological control*, Amer. Entomologist, 15 (1969), pp. 237–240. (Cited on p. 453)
- [122] J. LIANG, L. LI, AND D. ZENG, *Evolutionary dynamics of cryptocurrency transaction networks: An empirical study*, PLoS One, 13 (2018), art. e0202202. (Cited on p. 451)
- [123] A. LIMA, R. STANOJEVIC, D. PAPAGIANNAKI, P. RODRIGUEZ, AND M. C. GONZÁLEZ, *Understanding individual routing behaviour*, J. Roy. Soc. Interface, 13 (2016), art. 20160021. (Cited on p. 444)
- [124] L. MACNELL, A. DRISCOLL, AND A. N. HUNT, *What's in a name: Exposing gender bias in student ratings of teaching*, Innovative Higher Educ., 40 (2015), pp. 291–303. (Cited on p. 474)
- [125] P. MAHESHWARI, H. DU, J. SHEEN, S. M. ASSMANN, AND R. ALBERT, *Model-driven discovery of calcium-related protein-phosphatase inhibition in plant guard cell signaling*, PLoS Comput. Biol., 15 (2019), art. e1007429. (Cited on p. 451)
- [126] S. MALETIĆ, M. RAJKOVIĆ, AND D. VASILJEVIĆ, *Simplicial complexes of networks and their statistical properties*, in International Conference on Computational Science, Springer, 2008, pp. 568–575. (Cited on p. 461)
- [127] D. MALINIAK, R. POWERS, AND B. F. WALTER, *The gender citation gap in international relations*, Internat. Organization, 67 (2013), pp. 889–922. (Cited on p. 474)
- [128] F. K. MARDAKHEH, H. Z. SAILEM, S. KÜMPER, C. J. TAPE, R. R. MCCULLY, A. PAUL, S. ANJOMANI-VIRMOUNI, C. JØRGENSEN, G. POULOGIANNIS, C. J. MARSHALL, AND C. BAKAL, *Proteomics profiling of interactome dynamics by colocalisation analysis (COLA)*, Molecular BioSyst., 13 (2017), pp. 92–105. (Cited on p. 472)
- [129] K. MCRAE, G. S. CREE, M. S. SEIDENBERG, AND C. McNORGAN, *Semantic feature production norms for a large set of living and nonliving things*, Behav. Res. Methods, 37 (2005), pp. 547–559. (Cited on p. 440)
- [130] G. MENICHETTI, L. DALL'ASTA, AND G. BIANCONI, *Control of multilayer networks*, Sci. Rep., 6 (2016), art. 20706. (Cited on p. 452)
- [131] G. MENICHETTI, D. REMONDINI, P. PANZARASA, R. J. MONDRAGÓN, AND G. BIANCONI, *Weighted multiplex networks*, PLoS One, 9 (2014), art. e97857. (Cited on p. 453)
- [132] A. P. MILLÁN, J. J. TORRES, AND G. BIANCONI, *Explosive higher-order Kuramoto dynamics on simplicial complexes*, Phys. Rev. Lett., 124 (2020), art. 218301. (Cited on p. 449)
- [133] N. MILOSAVLJEVIĆ, D. MOROZOV, AND P. SKRABA, *Zigzag persistent homology in matrix multiplication time*, in Proceedings of the Twenty-Seventh Annual Symposium on Computational Geometry, ACM, 2011, pp. 216–225. (Cited on p. 451)
- [134] M. MITCHELL, *Complex systems: Network thinking*, Artificial Intell., 170 (2006), pp. 1194–1212. (Cited on p. 448)
- [135] M. MITCHELL, *Complexity: A Guided Tour*, Oxford University Press, 2009. (Cited on p. 437)
- [136] M. MOLLOY AND B. REED, *A critical point for random graphs with a given degree sequence*, Random Structures Algorithms, 6 (1995), pp. 161–180. (Cited on p. 460)
- [137] J. M. MONTOYA, S. L. PIMM, AND R. V. SOLÉ, *Ecological networks and their fragility*, Nature, 442 (2006), pp. 259–264. (Cited on p. 448)
- [138] K. MORRISON AND C. CURTO, *Predicting neural network dynamics via graphical analysis*, in Algebraic and Combinatorial Computational Biology, Elsevier, 2019, pp. 241–277. (Cited on p. 453)

- [139] C. A. MOSS-RACUSIN, J. F. DOVIDIO, V. L. BRESROLL, M. J. GRAHAM, AND J. HANDELSMAN, *Science faculty's subtle gender biases favor male students*, Proc. Natl. Acad. Sci. USA, 109 (2012), pp. 16474–16479. (Cited on p. 474)
- [140] P. J. MUCHA, T. RICHARDSON, K. MACON, M. A. PORTER, AND J.-P. ONNELA, *Community structure in time-dependent, multiscale, and multiplex networks*, Science, 328 (2010), pp. 876–878. (Cited on p. 451)
- [141] S. F. MULDOON, E. W. BRIDGEFORD, AND D. S. BASSETT, *Small-world propensity and weighted brain networks*, Sci. Rep., 6 (2016), art. 22057. (Cited on p. 471)
- [142] A. C. MURPHY, S. GU, A. N. KHAMBHATI, N. F. WYMBS, S. T. GRAFTON, T. D. SATTERTHWAITE, AND D. S. BASSETT, *Explicitly Linking Regional Activation and Function Connectivity: Community Structure of Weighted Networks with Continuous Annotation*, preprint, <https://arxiv.org/abs/1611.07962>, 2016. (Cited on p. 453)
- [143] N. NEUBAUER AND K. OBERMAYER, *Towards community detection in k-partite k-uniform hypergraphs*, in Proceedings of the NIPS 2009 Workshop on Analyzing Networks and Learning with Graphs, 2009, pp. 1–9. (Cited on p. 459)
- [144] M. NEWMAN, *Networks*, Oxford University Press, 2018. (Cited on pp. 437, 460, 461)
- [145] V. NICOSIA, J. TANG, C. MASCOLO, M. MUSOLESI, G. RUSSO, AND V. LATORA, *Graph metrics for temporal networks*, in Temporal Networks, Springer, 2013, pp. 15–40. (Cited on p. 451)
- [146] C. J. OATES AND S. MUKHERJEE, *Network inference and biological dynamics*, Ann. Appl. Stat., 6 (2012), pp. 1209–1235. (Cited on p. 472)
- [147] H. F. ÓLAFSDÓTTIR, D. BUSH, AND C. BARRY, *The role of hippocampal replay in memory and planning*, Current Biol., 28 (2018), pp. R37–R50. (Cited on p. 471)
- [148] J.-P. ONNELA, D. J. FENN, S. REID, M. A. PORTER, P. J. MUCHA, M. D. FRICKER, AND N. S. JONES, *Taxonomies of networks from community structure*, Phys. Rev. E, 86 (2012), art. 036104. (Cited on p. 461)
- [149] E. OTT, J. H. PLATIG, T. M. ANTONSEN, AND M. GIRVAN, *Echo phenomena in large systems of coupled oscillators*, Chaos, 18 (2008), art. 037115. (Cited on p. 453)
- [150] N. OTTER, M. A. PORTER, U. TILLMANN, P. GRINDROD, AND H. A. HARRINGTON, *A roadmap for the computation of persistent homology*, EPJ Data Sci., 6 (2017), art. 17. (Cited on p. 451)
- [151] C. ÖZTURAN, *On finding hypercycles in chemical reaction networks*, Appl. Math. Lett., 21 (2008), pp. 881–884. (Cited on p. 450)
- [152] G. A. PAGANI AND M. AIELLO, *The power grid as a complex network: A survey*, Phys. A, 392 (2013), pp. 2688–2700. (Cited on p. 472)
- [153] G. PALLA, I. DERÉNYI, I. FARKAS, AND T. VICSEK, *Uncovering the overlapping community structure of complex networks in nature and society*, Nature, 435 (2005), pp. 814–818. (Cited on p. 460)
- [154] M. A. PALUDI AND L. A. STRAYER, *What's in an author's name? Differential evaluations of performance as a function of author's name*, Sex Roles, 12 (1985), pp. 353–361. (Cited on p. 474)
- [155] J. PAN, R. M. MEYERS, B. C. MICHEL, N. MASHTALIR, A. E. SIZEMORE, J. N. WELLS, S. H. CASSEL, F. VAZQUEZ, B. A. WEIR, W. C. HAHN, J. A. MARSH, A. TSHERNIAK, AND C. KADOCH, *Interrogation of mammalian protein complex structure, function, and membership using genome-scale fitness screens*, Cell Syst., 6 (2018), pp. 555–568. (Cited on p. 451)
- [156] L. PAPADOPOULOS, P. BLINDER, H. RONELLENFITSCH, F. KLIMM, E. KATIFORI, D. KLEINFELD, AND D. S. BASSETT, *Comparing two classes of biological distribution systems using network analysis*, PLoS Comput. Biol., 14 (2018), art. e1006428. (Cited on p. 464)
- [157] L. PAPADOPOULOS, J. Z. KIM, J. KURTHS, AND D. S. BASSETT, *Development of structural correlations and synchronization from adaptive rewiring in networks of Kuramoto oscillators*, Chaos, 27 (2017), art. 073115. (Cited on p. 453)
- [158] L. PAPADOPOULOS, M. A. PORTER, K. E. DANIELS, AND D. S. BASSETT, *Network analysis of particles and grains*, J. Complex Networks, 6 (2018), pp. 485–565. (Cited on pp. 444, 460)
- [159] J. PEÑA AND Y. ROCHAT, *Bipartite graphs as models of population structures in evolutionary multiplayer games*, PloS One, 7 (2012), art. e44514. (Cited on p. 463)
- [160] V. PERRI AND I. SCHOLTES, *HOTVis: Higher-Order Visualization of Causal Structures in Dynamics Graphs*, preprint, <https://arxiv.org/abs/1908.05976>, 2019. (Cited on pp. 443, 453)
- [161] G. PETRI, P. EXPERT, F. TURKHEIMER, R. CARHART-HARRIS, D. NUTT, P. J. HELLYER, AND F. VACCARINO, *Homological scaffolds of brain functional networks*, J. Roy. Soc. Interface, 11 (2014), art. 20140873. (Cited on pp. 449, 451, 471)

- [162] S. PORTA, P. CRUCITTI, AND V. LATORA, *The network analysis of urban streets: A primal approach*, Environ. Planning B Planning and Design, 33 (2006), pp. 705–725. (Cited on p. 472)
- [163] S. R. PROULX, D. E. PROMISLOW, AND P. C. PHILLIPS, *Network thinking in ecology and evolution*, Trends in Ecol. Evol., 20 (2005), pp. 345–353. (Cited on p. 448)
- [164] E. PURVINE, S. AKSOY, C. JOSLYN, K. NOWAK, B. PRAGGASTIS, AND M. ROBINSON, *A topological approach to representational data models*, in International Conference on Human Interface and the Management of Information, Springer, 2018, pp. 90–109. (Cited on p. 450)
- [165] E. RAMADAN, A. TARAFDAR, AND A. POTHEN, *A hypergraph model for the yeast protein complex network*, in IEEE 18th International Parallel and Distributed Processing Symposium, 2004, p. 189. (Cited on pp. 450, 472)
- [166] K. RAMAN, *Construction and analysis of protein–protein interaction networks*, Automated Exp., 2 (2010), art. 2. (Cited on p. 472)
- [167] D. RAMEL, X. WANG, C. LAFLAMME, D. J. MONTELL, AND G. EMERY, *Rab11 regulates cell-cell communication during collective cell movements*, Nature Cell Biol., 15 (2013), pp. 317–324. (Cited on p. 444)
- [168] M. G. REES, B. SEASHORE-LUDLOW, AND P. A. CLEMONS, *Computational analyses connect small-molecule sensitivity to cellular features using large panels of cancer cell lines*, in Systems Chemical Biology, Springer, 2019, pp. 233–254. (Cited on p. 452)
- [169] M. W. REIMANN, M. NOLTE, M. SCOLAMIERO, K. TURNER, R. PERIN, G. CHINDEMI, P. DLOTKO, R. LEVI, K. HESS, AND H. MARKRAM, *Cliques of neurons bound into cavities provide a missing link between structure and function*, Frontiers Comput. Neurosci., 11 (2017), p. 48. (Cited on pp. 449, 450)
- [170] F. REMPE, G. HUBER, AND K. BOGENBERGER, *Spatio-temporal congestion patterns in urban traffic networks*, Transp. Res. Procedia, 15 (2016), pp. 513–524. (Cited on p. 472)
- [171] S. RITAL, H. CHERIFI, AND S. MIGUET, *Weighted adaptive neighborhood hypergraph partitioning for image segmentation*, in International Conference on Pattern Recognition and Image Analysis, Springer, 2005, pp. 522–531. (Cited on p. 451)
- [172] M. RIVERA-ALBA, S. N. VITALADEVUNI, Y. MISHCHENKO, Z. LU, S.-Y. TAKEMURA, L. SCHEFFER, I. A. MEINERTZHAGEN, D. B. CHKLOVSKII, AND G. G. DE POLAVIEJA, *Wiring economy and volume exclusion determine neuronal placement in the Drosophila brain*, Current Biol., 21 (2011), pp. 2000–2005. (Cited on p. 472)
- [173] J.-P. RODRIGUE, *The Geography of Transport Systems*, Taylor & Francis, 2016. (Cited on p. 472)
- [174] M. P. ROMBACH, M. A. PORTER, J. H. FOWLER, AND P. J. MUCHA, *Core-periphery structure in networks*, SIAM J. Appl. Math., 74 (2014), pp. 167–190, <https://doi.org/10.1137/120881683>. (Cited on p. 461)
- [175] S. ROSS AND M. LO, *The Lunar L1 gateway—portal to the stars and beyond*, in AIAA Space 2001 Conference and Exposition, 2001, p. 4768. (Cited on p. 472)
- [176] M. ROSVALL, A. V. ESQUIVEL, A. LANCICHINETTI, J. D. WEST, AND R. LAMBIOTTE, *Memory in network flows and its effects on spreading dynamics and community detection*, Nature Commun., 5 (2014), art. 4630. (Cited on pp. 443, 453)
- [177] M. RUBINOV AND O. SPORNS, *Complex network measures of brain connectivity: Uses and interpretations*, NeuroImage, 52 (2010), pp. 1059–1069. (Cited on pp. 451, 461)
- [178] A. SAADATPOUR AND R. ALBERT, *Discrete dynamic modeling of signal transduction networks*, Methods Mol. Biol., 880 (2012), pp. 255–272. (Cited on p. 451)
- [179] A. J. SADOVSKY AND J. N. MACLEAN, *Mouse visual neocortex supports multiple stereotyped patterns of microcircuit activity*, J. Neurosci., 34 (2014), pp. 7769–7777. (Cited on p. 472)
- [180] F. D. SAHNEH AND C. SCOGLIO, *Competitive epidemic spreading over arbitrary multilayer networks*, Phys. Rev. E, 89 (2014), art. 062817. (Cited on p. 452)
- [181] M. SALEHI, R. SHARMA, M. MARZOLLA, M. MAGNANI, P. SIYARI, AND D. MONTESI, *Spreading processes in multilayer networks*, IEEE Trans. Network Sci. Engng., 2 (2015), pp. 65–83. (Cited on p. 452)
- [182] A. F. SAVULESCU, R. BRACKIN, E. BOUILHOL, B. DARTIGUES, J. H. WARRELL, M. R. PIMENTEL, S. DALLONGEVILLE, J. SCHMORANZER, J.-C. OLIVO-MARIN, E. R. GOMES ET AL., *DypFISH: Dynamic Patterned FISH to Interrogate RNA and Protein Spatial and Temporal Subcellular Distribution*, preprint, <https://doi.org/10.2139/ssrn.3323373>, 2019. (Cited on p. 473)
- [183] J. SCHEURER, C. CURTIS, AND S. PORTA, *Spatial Network Analysis of Public Transport Systems: Developing a Strategic Planning Tool to Assess the Congruence of Movement and Urban Structure in Australian Cities*, GAMUT, Australasian Centre for the Governance and Management of Urban Transport, 2008. (Cited on p. 472)

- [184] I. SCHOLTES, *When is a network a network? Multi-order graphical model selection in pathways and temporal networks*, in Proceedings of the 23rd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining KDD, 2017, pp. 1037–1046. (Cited on p. 453)
- [185] K. A. SEATON AND L. M. HACKETT, *Stations, trains and small-world networks*, Phys. A, 339 (2004), pp. 635–644. (Cited on p. 472)
- [186] S. B. SEIDMAN, *Structures induced by collections of subsets: A hypergraph approach*, Math. Soc. Sci., 1 (1981), pp. 381–396. (Cited on p. 450)
- [187] D. H. SERRANO, J. HERNÁNDEZ-SERRANO, AND D. S. GÓMEZ, *Simplicial degree in complex networks. Applications of topological data analysis to network science*, Chaos Solitons Fractals, 137 (2020), art. 109839. (Cited on p. 461)
- [188] T. SHANMUKHAPPA, I. W. HO, K. T. CHI, X. WU, AND H. DONG, *Multi-layer public transport network analysis*, in 2018 IEEE International Symposium on Circuits and Systems (ISCAS), IEEE, 2018, pp. 1–5. (Cited on p. 472)
- [189] D. SHNIER, M. A. VOINEAGU, AND I. VOINEAGU, *Persistent homology analysis of brain transcriptome data in autism*, J. Roy. Soc. Interface, 16 (2019), art. 20190531. (Cited on p. 473)
- [190] R. SINATRA, D. CONDORELLI, AND V. LATORA, *Networks of motifs from sequences of symbols*, Phys. Rev. Lett., 105 (2010), art. 178702. (Cited on p. 445)
- [191] G. SINGH, F. MEMOLI, T. ISHKANOV, G. SAPIRO, G. CARLSSON, AND D. L. RINGACH, *Topological analysis of population activity in visual cortex*, J. Vision, 8 (2008), pp. 1–18. (Cited on p. 449)
- [192] A. E. SIZEMORE AND D. S. BASSETT, *Dynamic graph metrics: Tutorial, toolbox, and tale*, NeuroImage, 180 (2018), pp. 417–427. (Cited on p. 451)
- [193] A. E. SIZEMORE, C. GIUSTI, A. KAHN, J. M. VETTEL, R. F. BETZEL, AND D. S. BASSETT, *Cliques and cavities in the human connectome*, J. Comput. Neurosci., 44 (2018), pp. 115–145. (Cited on pp. 449, 451, 461, 471)
- [194] A. E. SIZEMORE, E. A. KARUZA, C. GIUSTI, AND D. S. BASSETT, *Knowledge gaps in the early growth of semantic feature networks*, Nature Human Behav., 2 (2018), pp. 682–692. (Cited on p. 453)
- [195] L. SOLÁ, M. ROMANCE, R. CRIADO, J. FLORES, A. GARCÍA DEL AMO, AND S. BOCCALETTI, *Eigenvector centrality of nodes in multiplex networks*, Chaos, 23 (2013), art. 033131. (Cited on p. 452)
- [196] D. SPIES AND C. CIAUDO, *Dynamics in transcriptomics: Advancements in RNA-seq time course and downstream analysis*, Comput. Structural Biotechnol. J., 13 (2015), pp. 469–477. (Cited on p. 472)
- [197] D. I. SPIVAK, *Higher-Dimensional Models of Networks*, preprint, <https://arxiv.org/abs/0909.4314>, 2009. (Cited on pp. 449, 455)
- [198] O. SPORNS AND R. F. BETZEL, *Modular brain networks*, Ann. Rev. Psychol., 67 (2016), pp. 613–640. (Cited on p. 471)
- [199] S. SQUIRES, K. SYTWU, D. ALCALA, T. M. ANTONSEN, E. OTT, AND M. GIRVAN, *Weakly explosive percolation in directed networks*, Phys. Rev. E, 87 (2013), art. 052127. (Cited on p. 450)
- [200] M. STELLA, N. M. BECKAGE, M. BREDE, AND M. DE DOMENICO, *Multiplex model of mental lexicon reveals explosive learning in humans*, Sci. Rep., 8 (2018), art. 2259. (Cited on p. 452)
- [201] J. STISO AND D. S. BASSETT, *Spatial embedding imposes constraints on neuronal network architectures*, Trends Cognitive Sci., 22 (2018), pp. 1127–1142. (Cited on p. 472)
- [202] J. STISO, A. N. KHAMBHATI, T. MENARA, A. E. KAHN, J. M. STEIN, S. R. DAS, R. GORNIK, J. TRACY, B. LITT, K. A. DAVIS ET AL., *White matter network architecture guides direct electrical stimulation through optimal state transitions*, Cell Rep., 28 (2019), pp. 2554–2566. (Cited on p. 444)
- [203] B. STOLZ, *Computational Topology in Neuroscience*, Master’s thesis, University of Oxford, 2014. (Cited on pp. 449, 451)
- [204] B. J. STOLZ, T. EMERSON, S. NAHKURI, M. A. PORTER, AND H. A. HARRINGTON, *Topological Data Analysis of Task-Based fMRI Data from Experiments on Schizophrenia*, preprint, <https://arxiv.org/abs/1809.08504>, 2018. (Cited on p. 449)
- [205] G. TAUZIN, U. LUPO, L. TUNSTALL, J. B. PÉREZ, M. CAORSI, A. MEDINA-MARDONES, A. DAS-SATTI, AND K. HESS, *giotto-tda: A Topological Data Analysis Toolkit for Machine Learning and Data Exploration*, preprint, <https://arxiv.org/abs/2004.02551>, 2020. (Cited on p. 449)

- [206] C. M. TAYLOR AND R. J. HALL, *Metapopulation models for seasonally migratory animals*, Biol. Lett., 8 (2011), pp. 477–480. (Cited on p. 453)
- [207] M. B. TAYLOR AND I. M. EHRENREICH, *Higher-order genetic interactions and their contribution to complex traits*, Trends Genetics, 31 (2015), pp. 34–40. (Cited on p. 473)
- [208] Y. THIEM, K. F. SEALEY, A. E. FERRER, A. M. TROTT, AND R. KENNISON, *Just Ideas? The Status and Future of Publication Ethics in Philosophy: A White Paper*, Technical report, 2018. (Cited on p. 474)
- [209] Z. TIAN, T. HWANG, AND R. KUANG, *A hypergraph-based learning algorithm for classifying gene expression and arrayCGH data with prior knowledge*, Bioinform., 25 (2009), pp. 2831–2838. (Cited on p. 451)
- [210] M. TIZZONI, P. BAJARDI, A. DECUYPER, G. KON KAM KING, C. M. SCHNEIDER, V. BLONDEL, Z. SMOREDA, M. C. GONZÁLEZ, AND V. COLIZZA, *On the use of human mobility proxies for modeling epidemics*, PLoS Comput. Biol., 10 (2014), art. e1003716. (Cited on p. 445)
- [211] J. J. TORRES AND G. BIANCONI, *Simplicial complexes: Higher-order spectral dimension and dynamics*, J. Phys. Complexity, 1 (2020), art. 015002. (Cited on p. 449)
- [212] E. VALDANO, L. FERRERI, C. POLETTI, AND V. COLIZZA, *Analytical computation of the epidemic threshold on temporal networks*, Phys. Rev. X, 5 (2015), art. 021005. (Cited on p. 452)
- [213] P. VALDIVIA, P. BUONO, AND J.-D. FEKETE, *Hypenet: Visualizing dynamic hypergraphs*, in EuroVis 2017-19th EG/VGC Conference on Visualization, 2017, pp. 1–3. (Cited on p. 451)
- [214] M. P. VAN DEN HEUVEL AND H. E. H. POL, *Exploring the brain network: A review on resting-state fMRI functional connectivity*, European Neuropsychopharmacology, 20 (2010), pp. 519–534. (Cited on p. 446)
- [215] N. VANDERSICKEL, E. VAN NIEUWENHUYSE, N. VAN CLEEMPUT, J. GOEDGEBEUR, M. EL HAD-DAD, J. DE NEVE, A. DEMOLDER, T. STRISCIUGLIO, M. DUYSCHAEVER, AND A. PANFILOV, *Directed networks as a novel way to describe and analyze cardiac excitation: Directed graph mapping*, Frontiers Physiol., 10 (2019), p. 1138. (Cited on p. 450)
- [216] G. VINCI, G. DASARATHY, AND G. I. ALLEN, *Graph Quilting: Graphical Model Selection from Partially Observed Covariances*, preprint, <https://arxiv.org/abs/1912.05573>, 2019. (Cited on p. 472)
- [217] V. I. VOLOSHIN, *Introduction to Graph and Hypergraph Theory*, Nova Science, Hauppauge, NY, 2009. (Cited on p. 449)
- [218] C. VON FERBER, T. HOLOVATCH, Y. HOLOVATCH, AND V. PALCHYKOV, *Network harness: Metropolis public transport*, Phys. A, 380 (2007), pp. 585–591. (Cited on p. 472)
- [219] C. VON FERBER, T. HOLOVATCH, Y. HOLOVATCH, AND V. PALCHYKOV, *Public transport networks: Empirical analysis and modeling*, European Phys. J. B, 68 (2009), pp. 261–275. (Cited on p. 472)
- [220] F. VON WEGNER, E. TAGLIAZUCCHI, AND H. LAUFS, *Information-theoretical analysis of resting state EEG microstate sequences—non-Markovianity, non-stationarity and periodicities*, NeuroImage, 158 (2017), pp. 99–111. (Cited on p. 471)
- [221] A. J. WALHOUT, *Gene-centered regulatory network mapping*, in *Caenorhabditis elegans: Molecular Genetics and Development*, Methods Cell Biol. 106, Elsevier, 2011, pp. 271–288. (Cited on p. 472)
- [222] Z. WANG, J. LIU, N. ZHONG, Y. QIN, H. ZHOU, J. YANG, AND K. LI, *A naïve hypergraph model of brain networks*, in International Conference on Brain Informatics, Springer, 2012, pp. 119–129. (Cited on p. 471)
- [223] D. J. WATTS AND S. H. STROGATZ, *Collective dynamics of “small-world” networks*, Nature, 393 (1998), pp. 440–442. (Cited on pp. 447, 448)
- [224] J. WEBER AND M.-P. KWAN, *Bringing time back in: A study on the influence of travel time variations and facility opening hours on individual accessibility*, The Professional Geographer, 54 (2002), pp. 226–240. (Cited on p. 444)
- [225] R. J. WILSON, *History of graph theory*, in Handbook of Graph Theory, Chapman and Hall/CRC, 2013, pp. 31–51. (Cited on p. 448)
- [226] J. XU, T. L. WICKRAMARATHNE, AND N. V. CHAWLA, *Representing higher-order dependencies in networks*, Sci. Adv., 2 (2016), art. e1600028. (Cited on p. 472)
- [227] J. YOO, E. Y. KIM, Y. M. AHN, AND J. C. YE, *Topological persistence vineyard for dynamic functional brain connectivity during resting and gaming stages*, J. Neurosci. Methods, 267 (2016), pp. 1–13. (Cited on p. 451)
- [228] B. ZHAO, S. HU, X. LI, F. ZHANG, Q. TIAN, AND W. NI, *An efficient method for protein function annotation based on multilayer protein networks*, Human Genomics, 10 (2016), p. 33. (Cited on p. 473)



- [229] Y. D. ZHONG, V. SRIVASTAVA, AND N. E. LEONARD, *On the linear threshold model for diffusion of innovations in multiplex social networks*, in IEEE 56th Annual Conference on Decision and Control (CDC), 2017, pp. 2593–2598. (Cited on p. 452)
- [230] D. ZHOU, E. J. CORNBLATH, J. STISO, E. G. TEICH, J. D. DWORKIN, A. S. BLEVINS, AND D. S. BASSETT, *Gender Diversity Statement and Code Notebook v1.0*, February 2020, <https://doi.org/10.5281/zenodo.3672110>. (Cited on p. 475)
- [231] W. ZHOU AND L. NAKHLEH, *Properties of metabolic graphs: Biological organization or representation artifacts?*, BMC Bioinform., 12 (2011), p. 132. (Cited on p. 464)
- [232] M. ZHU AND M. ZHANG, *Network analysis of conversation data for engineering professional skills assessment*, ETS Res. Rep. Ser., 2017 (2017), pp. 1–13. (Cited on p. 440)
- [233] A. ZOMORODIAN AND G. CARLSSON, *Computing persistent homology*, Discrete Comput. Geom., 33 (2005), pp. 249–274. (Cited on pp. 449, 451)