

FACILITY 10: eMarine Information Infrastructure (eMII)

IMOS NETCDF CONVENTIONS

Conventions and Reference Tables

Version 1.4 August, 2015

info@emii.org.au

NCRIS
National Research
Infrastructure for Australia
An Australian Government Initiative

IMOS is a national collaborative research infrastructure, supported by Australian Government. It is led by University of Tasmania in partnership with the Australian marine & climate science community



Table of contents

PREFACE TO VERSION 1.4	5
1 - OVERVIEW	7
1.1 - ABOUT IMOS	7
1.2 - ABOUT EMII	7
1.3 - ABOUT THIS DOCUMENT	8
2 - IMOS DATA FORMAT	9
2.1 - NETWORK COMMON DATA FORM (NETCDF)	9
2.2 - CF CONVENTIONS	9
2.3 - IMOS CONVENTIONS	9
3 - NETCDF FILE STRUCTURE	11
3.1 - FEATURE TYPE TEMPLATES	11
3.1.1 - Definition	11
3.1.2 - Examples of CDL templates per feature type	
3.1.2.1 - Time series	
3.1.2.1 - Time series profile	
3.1.2.2 - Trajectory	13
3.2 - GLOBAL ATTRIBUTES	13
3.2.1 - Definition	13
3.2.2 - Core global attributes	14
3.2.3 - Optional global attributes	18
3.2.4 - Date and Time formats	25
3.2.5 - Processing level	25
3.2.6 - Global Attributes added by the data provider	26
3.3 - DIMENSIONS	27
3.4 - VARIABLES	27
3.4.1 - Spatio-temporal variables	27
3.4.1.1 - Time	28

3.4.1.2 - Horizontal coordinates	30
3.4.1.3 - Vertical coordinates	31
3.4.2 - Data variables	33
3.4.3 - Variable attributes added by data provider	37
3.4.4 - Ancillary variables	37
3.4.4.1 - Quality control (QC)	38
3.4.4.1.1 - Quality Control sets used by the IMOS project	38
3.4.4.1.2 - Definition of quality control variables and attributes	38
3.4.4.2 - Uncertainty, accuracy, precision and resolution	39
3.4.4.2.1 - Implementation in IMOS	40
3.4.4.2.2 - Example	40
4 - IMOS FILE NAMING CONVENTION	41
5 - REFERENCE TABLES	42
5.1 - IMOS PARAMETER DICTIONARY	42
5.2 - QUALITY CONTROL FLAGS	43
5.2.1 - Set 1 - IMOS standard flags	43
5.2.2 - Set 2 - ARGO quality control procedure	44
5.2.2.1 - ARGO measurement flag scale	44
5.2.2.2 - ARGO profile quality flags	46
5.2.3 - Set 3 - BOM quality control procedure (SST and Air-Sea fluxes)	
5.2.4 - Set 4 - WOCE quality control procedure (Multidisciplinary Underway N	etwork - CO ₂
measurements)	_
5.3 - CELL METHODS	
S - REFERENCES	50
APPENDIX 1: EXAMPLE NETCDF FILE	52
APPENDIX 2: IMOS TOOLBOX OPTIONAL GLOBAL ATTRIBUTES	56
APPENDIX 3: IMOS FILE NAMING CONVENTION	60

Index of Tables

Table 1 List of core mandatory global attributes for IMOS netCDF files	14
Table 2 List of optional global attributes for IMOS netCDF files	19
Table 3 An example list of Dimensions for an IMOS netCDF file	27
Table 4 List of attributes defining the TIME variable for IMOS netCDF files	28
Table 5 List of attributes that define the LATITUDE and LONGITUDE variables for IMOS netCDF files	30
Table 6 List of attributes that define any depth or height variable for IMOS netCDF files	32
Table 7 List of data variables attributes for IMOS netCDF files	34
Table 8 List of attributes used to define a Quality Control variable	38
Index of Reference Tables	
Reference Table A : List of QC flags sets used in the IMOS project	43
Reference Table B : IMOS standard flags	43
Reference Table C : ARGO measurement flag scale	44
Reference Table D : ARGO profile quality flags	46
Reference Table E : BOM Quality Control procedure flags (SST and Air Sea Fluxes)	47
Reference Table F: WOCE quality control procedure flags (CO ₂ measurements)	48
Poterance Table G : List of different cell methods, derived from the CE convention	40

PREFACE to version 1.4

Due to changes in version 2.4 of the IMOS toolbox responsible for the ANMN (Australian National Moorings Network) time series and profile data processing, we have made a number of changes to this document. They are summarised below:

- -Document has been renamed from IMOS NetCDF user's manual to IMOS NetCDF Conventions.
- -Prefaces to former versions of the IMOS NetCDF Conventions are not included any more. Only the changes from the previous version to the current one are detailed.
- -Overall the document has been reviewed and corrected with fixes or updates. There has also been an attempt to reduce information to a minimum trying to cut repetitions and redundancies. The use of hyperlinks to reference information within this document or outside has also been widely spread.
- -Chapter 3 -NetCDF File structure has been extended with a sub-chapter on feature type templates with examples of templates for each relevant feature types.
- -Global attributes are divided into two categories: the core (mandatory) ones, and the optional ones.
- -Compulsory global attribute distribution_statement has been renamed disclaimer and its content updated while a new compulsory global attribute license has been added.
- -The global attributes "featureType", "instrument_serial_number", "site", "platform", "keywords", "quality_control_log", "lineage" and "project_acknowledgement" are now optional ones.
- -Contents of global attributes "file_version" and "file_version_quality_control" have been updated.
- -New optional global attribute "keywords_vocabulary" to define the vocabulary used in "keywords".
- -Optional global attribute "project_acknowledgement" has been removed.
- -IMOS recommended "units" attribute for time variable is "days since 1950-01-01 00:00:00 UTC" and not local time.
- -Variable attributes "valid_min" and "valid_max" must be of the same type as the variable they're associated with.
- -Variable attribute "_FillValue" cannot be used for a coordinate variable and is only required if there could be missing values in the data (not mandatory anymore).
- -Variable attributes "quality_control_set" and "quality_control_indicator" are not relevant to be used with a non ancillary QC variable anymore.

- -Variable attribute "uncertainty" is not mandatory any more for vertical coordinate variables.
- -A new variable attribute "coordinates" is mandatory for any measurement variable other than coordinate or ancillary data.
- -Variable attribute "reference_datum" is not relevant for non coordinate data.
- -Variable attributes "valid_min" and "valid_max" are not relevant for QC ancillary variables.
- -Variable attributes "quality_control_global_conventions" and "quality_control_global" have been added for QC ancillary variable.
- -QC ancillary variable attribute "quality_control_set" has been removed. Attribute "quality_control_conventions" is already enough and more explicit.
- -The CDL file example in Appendix 1 has been updated.
- -Optional global attributes for the IMOS toolbox "instrument_beam_angle", "cruise", "station", "time_deployment_start_origin" and "time_deployment_end_origin" have been introduced.
- -The Reference Table IMOS parameter dictionary, is not included in this document anymore. Instead a link to an up to date document is provided.
- -The Reference Table BOM Quality Control procedure flags, has been updated.

1 - OVERVIEW

1.1 - About IMOS

IMOS is a distributed set of equipment and data-information services which collectively contribute to meeting the needs of marine climate research in Australia. The observing system provides data in the open oceans around Australia out to a few thousand kilometres as well as the coastal oceans. The IMOS Office coordinates the deployment of a wide range of equipment and assembles the data through 11 facilities distributed around the country. The data are made available to researchers through the electronic Marine information Infrastructure (eMII) located at the University of Tasmania. The IMOS infrastructure also contributes to Australia's role in international programs of ocean observing.

IMOS is a national collaborative research infrastructure, supported by Australian Government. It is led by University of Tasmania in partnership with the Australian marine & climate science community.

1.2 - About eMII

The eMarine Information Infrastructure (eMII) will provide a single integrative framework for data and information management that will allow discovery and access of the data by scientists, managers and the public.

eMII activity can be summarised as follows:

- eMII will host, manage and archive data produced by the other IMOS facilities.
- eMII will provide the standards, protocols and systems to integrate the data and related information into a number of conformal frameworks, and will provide the tools to access and utilise the data.
- For some kinds of data, eMII will provide data products as web services and web features for processing, integration and visualisation of data.
- Where possible, eMII will integrate data from sources outside IMOS into IMOS data products and export IMOS data to international programs.

1.3 - About this document

The main purpose of this document is to specify the format of the files that are used to distribute IMOS data, and to document the standards used therein. This includes naming conventions, or taxonomy, as well as metadata content.

The IMOS NetCDF Conventions document was originally based on the one prescribed by the OceanSITES User's Manual, version 1.1. As both documents have evolved since, there are now significant differences between them but we will try to reduce this gap in the future. The <u>OceanSITES</u> program is the global network of open-ocean sustained time series reference stations that have been implemented by an international partnership of researchers.

The IMOS NetCDF Conventions document also draws on documents that have been produced for the IMOS project (see <u>References</u>).

2 - IMOS DATA FORMAT

2.1 - Network Common Data Form (NetCDF)

NetCDF is one of many file formats available for storing marine data. It is a binary file format that is self-describing and portable among other <u>features</u>. The netCDF software libraries and documentation are available online from <u>Unidata</u>. Many netCDF manipulation and display software utilities are also available online.

The IMOS NetCDF Conventions have been written to be used when writing data files in netCDF classic format (version 3.6). Unidata released a netCDF-4 format in 2008. This format is more flexible than the classic format and offers additional features such as compression, groups, compound types and variable length arrays. NetCDF library versions 4.0 and above are now widely adopted and backward compatible with the netCDF classic format so whenever relevant and possible, eMII encourages data providers to produce netCDF-4 files. Common Data Language (CDL) is a human readable text notation that is used to describe the netCDF objects. The netCDF utility ncdump can be used to convert netCDF binary file to CDL text. The netCDF utility ncgen creates a netCDF binary file from a well-formed CDL text file.

A CDL example which describes IMOS temperature data collected from a mooring is shown in APPENDIX 1: example netcdf file.

2.2 - CF conventions

IMOS follows the netCDF Climate and Forecast (CF) Metadata Conventions v1.6 (Eaton et al 2011). CF conventions require conforming datasets to contain sufficient metadata that they are self-describing, in the sense that each variable in the file has an associated description of what it represents, including physical units if appropriate, and that each value can be located in space and time. The CF conventions supply a standard vocabulary and some metadata conventions. Sometimes it was desirable to incorporate attributes or concepts from other conventions to the IMOS NetCDF Conventions. We have made clear notations in this document where the IMOS NetCDF Conventions extends the CF ones.

2.3 - IMOS conventions

IMOS NetCDF Conventions require that:

- Units are compliant with CF/COARDS/Udunits.
- The time parameter is encoded as recommended by COARDS and CF.
- Parameters are given standard names from the CF table when possible.
- Where time is specified as an attribute, the <u>ISO8601</u> standard is used.
- File names are created following the IMOS File Naming Convention document.

See also Unidata netCDF best practices.

3 - NETCDF FILE STRUCTURE

3.1 - Feature type templates

3.1.1 -Definition

Most of the observation data collected by IMOS are discrete sampling geometry datasets, that is to say data sets "characterized by a dimensionality that is lower than that of the space-time region that is sampled; discrete sampling geometries are typically "paths" through space-time" (see <u>CF1.6 new chapter</u> 9). We can identify distinct types of discrete sampling geometry like point, time series, profile or trajectory, so that for each of these feature type we can adopt a consistent representation or template in a netCDF file structure.

The US National Oceanographic Data Center (NODC) has designed <u>netCDF templates</u> for a wide variety of feature types. For each of them there is usually an orthogonal and an incomplete template available. IMOS recommends using the orthogonal template in which variables of a dataset must contain identical coordinate values along an axis. When the variables of a dataset contain different coordinate values along an axis then they should be separated into distinct files.

3.1.2 -Examples of CDL templates per feature type

The examples below illustrate the structure of a file for each feature type, using a single data variable as an example. A file can have multiple data variables as long as they share a single set of coordinates. For clarity, most attributes and the data values have been omitted.

3.1.2.1 - Time series

```
netcdf IMOS_timeseries_ single_dataset {

dimensions:

TIME = 22345;  // Number of time steps in the time series

variables:

double TIME(TIME);  // Coordinate variable T

double LATITUDE;  // Scalar coordinate variable Y

double LONGITUDE;  // Scalar coordinate variable X

float NOMINAL_DEPTH;  // Scalar coordinate variable Z
```

```
float TEMP(TIME);
                                     // geophysical measurement variable
               TEMP:coordinates = "TIME LATITUDE LONGITUDE NOMINAL_DEPTH";
               TEMP:ancillary_variables = "TEMP_quality_control";
                                             // geophysical measurement ancillary variable
       byte TEMP_quality_control(TIME);
               TEMP_quality_control: variable_attribute = "variable attribute value";
// global attributes:
               :featureType = "timeSeries";
}
        3.1.2.2 - Profile
netcdf IMOS profile single dataset {
dimensions:
       DEPTH = 102;
                                     // Number of vertical cells in the profile
variables:
       float DEPTH(DEPTH);
                                     // Coordinate variable Z
       double TIME;
                                     // Scalar coordinate variable T
       double LATITUDE;
                                     // Scalar coordinate variable Y
       double LONGITUDE;
                                     // Scalar coordinate variable X
       float TEMP(DEPTH);
                                     // geophysical measurement variable
               TEMP:coordinates = "TIME LATITUDE LONGITUDE DEPTH";
               TEMP:ancillary_variables = "TEMP_quality_control";
       byte TEMP_quality_control(DEPTH); // geophysical measurement ancillary variable
// global attributes:
               :featureType = "profile";
}
        3.1.2.1 - Time series profile
netcdf IMOS time series profile single dataset {
dimensions:
       TIME = 250;
                                     // Number of time steps in the time series
       DEPTH = 40;
                                     // Number of vertical cells in the profile
variables:
       double TIME(TIME);
                                     // Coordinate variable T
       float DEPTH(DEPTH);
                                     // Coordinate variable Z
                                     // Scalar coordinate variable Y
       double LATITUDE;
       double LONGITUDE;
                                     // Scalar coordinate variable X
       float CSPD(TIME, DEPTH);
                                     // geophysical measurement variable
```

```
CSPD:coordinates = "TIME LATITUDE LONGITUDE DEPTH" :
               CSPD:ancillary_variables = " CSPD_quality_control";
       byte CSPD_quality_control(TIME, DEPTH); // geophysical measurement ancillary variable
// global attributes:
               :featureType = "timeSeriesProfile";
}
       3.1.2.2 - Trajectory
netcdf IMOS_trajectory_ single_dataset {
dimensions:
       TIME = 22345;
                                             // Number of time steps in the trajectory
variables:
                                             // Coordinate variable T
       double TIME(TIME);
       double LATITUDE(TIME);
                                             // Auxiliary coordinate variable Y
       double LONGITUDE(TIME);
                                             // Auxiliary coordinate variable X
       float DEPTH(TIME);
                                             // Auxiliary coordinate variable Z
       float TEMP(TIME);
                                             // geophysical measurement variable
               TEMP:coordinates = "TIME LATITUDE LONGITUDE NOMINAL DEPTH";
               TEMP:ancillary_variables = "TEMP_quality_control";
       byte TEMP_quality_control(TIME);
                                             // geophysical measurement ancillary variable
// global attributes:
               :featureType = "trajectory";
}
```

3.2 - Global Attributes

3.2.1 -Definition

The global attribute section of a netCDF file contains metadata that describes the overall contents of the file and allows for data discovery. All fields should be human-readable and can be of either 'character' or 'numeric' type. IMOS recommends that all listed attributes be used and contain meaningful information unless there are technical reasons rendering this impossible (for example, information not available for historical data). Files must at least contain the attributes listed as "mandatory". Please contact eMII if this is proving difficult.

Global attributes can be thought of as conveying five kinds of information:

What: What are the data in the dataset

Where: The spatial coverage of the data

When: The temporal coverage of the data

Who: Who produced the data

How: How were the data produced and made available

3.2.2 -Core global attributes

The following table lists all the core global attributes are **mandatory** from the point of view of either the CF or IMOS conventions.

The "Type" values are **S** for string, **N** for numeric (byte, short, long, integer, float or double), **D** for the type of the data variable and **Q** for the type of the corresponding quality control data variable.

Definition

Table 1 List of core mandatory global attributes for IMOS netCDF files

Type Example

Name	Турс	Example	Definition
What			
project	S	project = "Integrated Marine Observing System (IMOS)"	The scientific project that produced the data. For data produced under the IMOS project, the field must be filled as shown in the example.
Conventions	S	Conventions = "CF- 1.6,IMOS-1.4"	Name of the format convention used by the dataset. Possibility to include two different conventions if necessary. For data produced under the IMOS project, the field must be filled as shown in the example.



Name

	standard_name_vocab	S	standard_name_vocabular	Table number used for CF
	ulary		y = "NetCDF Climate and	standard names.
			Forecast (CF) Metadata	
			Convention Standard	
			Name Table Version 29"	
	title	S	title = "Radar data from	Short description of the dataset
			Tannum Sands station,	
			Queensland"	
	institution	S	institution = "ACORN"	Name of the institute or facility
				where the original data was
				produced
	data anasta d		data anasta d = #0000 44	The data are which the file was
Non-CF	date_created	S	date_created = "2008-11- 23T08:35:00Z"	The date on which the file was
attribute			23100.35.002	created. See chapter Error! Reference source not found.
				on time format below.
				on time format below.
Non OF	abstract	S	abstract = "NSW-IMOS	A paragraph describing the
Non-CF attribute			Port Hacking 100m	dataset: type of data
attilibato			Mooring Water quality	contained in the dataset, how
			meters (WQM's) at one or	the data was created, the
			more depths collect	creator of the dataset, the
			bursting data. Data from	project for which the data was
			the bursts have been	created, the geospatial
			cleaned and averaged to	coverage of the data, the
			create data products. This	temporal coverage of the data.
			file is one such product."	In some instances the abstract
				may be autogenerated from
				other netCDF fields. Please
				discuss this with eMII staff if
				you think autogeneration will
				be appropriate for your data.
				as appropriate for your data.
Non-CF	naming_authority	S	naming_authority =	This will always be "IMOS"
attribute			"IMOS"	
Non-CF	Where			
attribute				

	geospatial_lat_min /	N	geospatial_lat_min = 59.8	The southernmost /
	geospatial_lat_max			northernmost latitude covered
			geospatial_lat_max = 59.8	by the data set, a value
				between -90 and 90 decimal
				degrees North unless
				otherwise specified in
				geospatial_lat_units.
	geospatial_lon_min /	N	geospatial_lon_min =-41.2	The westernmost /
	geospatial_lon_max	IN	geospatiai_tori_ffilif =-41.2	easternmost longitude, a value
	geospatiai_ioii_iiiax		geospatial_lon_max=-41.2	between -180 and 180
				decimal degrees East if not
				specified.
				specified.
	geospatial_vertical_min	N	geospatial_vertical_min =	Minimum / maximum depth for
	1		10.0	measurements in metres if not
	geospatial_vertical_ma			specified.
	Х		geospatial_vertical_max =	
			2000	
	geospatial_vertical_pos	S	geospatial_vertical_positiv	Direction towards which depth
	itive		e = "down"	is positive. Possible values are
				either "up" or "down".
	NA/IL a se			
Non-CF attribute	When			
	time_coverage_start /	S	time_coverage_start =	Start / final date of the data in
	time_coverage_end		"2008-11-23T08:35:00Z"	UTC. See chapter Error!
			time_coverage_end =	Reference source not found.
			"2009-01-06T15:47:00Z"	on time format.
			2009-01-00113.47.002	
Non-CF attribute	Who			
attributo	data_centre	S	data_centre = "eMarine	Data centre in charge of the
	_		Information Infrastructure	data management or party
			(eMII)"	who distributed the resource
			,	
	data_centre_email	S	data_centre_email =	Data Centre contact e-mail
			"info@emii.org.au"	address

author	S	author = "Doe, John"	Name of the person responsible for the creation of the dataset. Convention is last name and then first name separated by a comma.
principal_investigator	S	principal_investigator = "Doe, John"	Name of the principal investigator in charge of the platform. Convention is last name and then first name separated by a comma.
How			
citation	S	citation = Integrated Marine Observing System. 2008, "Australian Acoustic Tagging and Monitoring System (AATAMS) data", http://imos.org.au/emii_aat ams.html, accessed 20 Dec 2008.	The citation to be used in publications using the dataset should follow the format: "IMOS. [year-of-data-download], [Title], [Data access URL], accessed [date-of-access]".

Non-CF attribute

acknowledgement	S	acknowledgement = "Any	Information about how to
ag		users (including re-	acknowledge the source of the
		packagers) of IMOS data	material. For data produced
		are required to clearly	under the IMOS project, the
			field must be filled as shown in
		acknowledge the source of	
		the material in this format:	the example. If relevant, also
		"Data was sourced from	credit other organisations
		the Integrated Marine	involved in collection of this
		Observing System (IMOS)	particular data stream.
		- IMOS is supported by the	
		Australian Government	
		through the National	
		Collaborative Research	
		Infrastructure Strategy and	
		the Super Science	
		Initiative.""	
disclaimer	S	disclaimer = "Data,	Statement limiting the liability
		products and services	of the data provider. For data
		from IMOS are provided	produced under the IMOS
		"as is" without any	project, the field must be filled
		warranty as to fitness for a	as shown in the example.
		particular purpose."	·
license	S	license =	Describe the restrictions to
		http://creativecommons.or	data access and distribution.
		g/licenses/by/4.0/	For data produced under the
		-	IMOS project, the field must
			be filled as shown in the
			example.

3.2.3 -Optional global attributes

Table 2 below lists some of the **optional** global attributes than can be used by any facility to describe an IMOS netCDF dataset.

For an example of facility-oriented optional global attributes, see APPENDIX 1: example netcdf file.

The "Type" values are **S** for string, **N** for numeric (byte, short, long, integer, float or double), **D** for the type of the data variable and **Q** for the type of the corresponding quality control data variable.

Table 2 List of optional global attributes for IMOS netCDF files

	Name	Type	Example	Definition			
	What						
	featureType	S	featureType = "timeSeries"	Specifies the type of discrete			
				sampling geometry to which			
				the data in the file belongs,			
				and implies that all data			
				variables in the file contain			
				collections of features of that			
				type. Possible CF featureType			
				values are "point",			
				"timeSeries", "profile",			
				"trajectory", "timeSeriesProfile"			
				or "trajectoryProfile".			
Non-CF	date_modified	S	date_modified = "2008-12-	The date on which the file was			
attribute			23T20:35:00Z"	modified. See chapter 3.2.4 -			
				on time format. If this attribute			
				is used for the first time or			
				modified, a new entry needs to			
				be added to the "history"			
				attribute.			
	history	S	history - "2044-02	Provides an audit trail for			
	history	3	history = "2014-03- 27T23:46:36Z -				
				modifications to the original			
				data. It should contain a			
			dimension and	separate line for each			
			time_coverage_start/end	modification, with each line			
			global attributes have	beginning with a timestamp			
			been applied the following	and including user name,			
			offset : -10 hours."	modification name and			
				modification arguments.			

	comment	Ø	comment = "Geospatial vertical min information has been computed using the Gibbs-SeaWater toolbox (TEOS-10) v3.02 from latitude and relative pressure measurements"	Miscellaneous information about the data or methods used to produce it. Any free-format text is appropriate Method of production of the
	Source	0	Observation"	original data
Non-CF attribute	instrument	Ø	instrument = "WETLABS WQM"	Make and model of the instruments from which the data has been collected.
Non-CF attribute	instrument_serial_num ber	Ø	instrument_serial_number = "5124"	Serial number of the instrument which has produced the dataset.
	references	Ø	references = "http://www.imos.org.au"	Published or web-based references that describe the data or the methods used to produce the data. Include a reference to IMOS and a project-specific reference if appropriate. Multiple references should be separated with a semicolon ";".
Non-CF attribute	site_code	Ø	site_code = "NRSMAI"	Unique site code within IMOS project. A site refers to a nominal location around which (within a certain radius) repeated measurements are performed to produce a timeseries dataset.
Non-CF attribute	site	S	site = "Maria Island National Reference Station, TAS"	Site description.

Non-CF attribute	platform_code	S	platform_code = "NRSMAI-SubSurface"	Unique platform code within IMOS project. The platform codes are listed in Reference Table 3 of the File Naming Convention document. A platform refers to the actual structure to which the instrument or sensor is attached.
Non-CF attribute	platform	S	platform = "Subsurface mooring at Maria Island National Reference Station, TAS site"	Platform description. They are listed in Reference Table 3 of the File Naming Convention document.
Non-CF attribute	cdm_data_type	S	cdm_data_type = "Station"	The "cdm_data_type" attribute gives the <u>Unidata CDM</u> (Common Data Model) data type used by THREDDS. E.g. "Point", "Trajectory", "Station", "Radial", "Grid", "Swath".
Non-CF attribute	keywords	S	keywords = "Oceans > Ocean Circulation > Ocean Currents , Oceans > Ocean Waves > Significant Wave Height ,"	A comma separated list of keywords coming from the keywords_vocabulary.
Non-CF attribute	keywords_vocabulary	S	keywords_vocabulary = "NASA/GCMD Earth Science Keywords"	Identifies the controlled keyword vocabulary used to specify the values within the attribute "keywords".

Non-CF attribute	metadata	S	metadata = " http://"	URL to the metadata record corresponding to the netCDF file. eMII is considering adding this information to the data files as part of eMII data processing. Facilities would not be required to complete these fields when submitting
Non-CF attribute	sensorML	S	sensorML = " http://"	Link to the sensorML record corresponding to the netCDF
				file. eMII is considering adding this information to the data files as part of eMII data processing. Facilities would not be required to complete these fields when submitting data.
	institution_address	Ø	institution_address = "Oceanography laboratory, School of Mathematics and Statistics, University of New South Wales, Sydney NSW 2052"	Address of the institute or facility where the original data was produced.
	institution_postal_addr ess	S	institution_postal_address = "University of New South Wales, Sydney NSW 2052"	Postal address of the institute or facility where the original data was produced.
Non-CF attribute	file version	Ø	file_version = "Level 0 - Raw data"	Information about the file version of the file. Three levels are possible at the moment: - Level 0 - Raw data - Level 1 - Quality Controlled data - Level 2 - Derived product

Non-CF	file_version_quality_co	S	file_version_quality_contro	Description of the level of
attribute	ntrol	O	I = "Data in this file has not	Quality Control applied to the
	TILLOI		been quality controlled"	data. See section Error!
			been quality controlled	
				found.for more information
				and examples.
Non-CF	quality_control_log	S	quality_control_log =	QC procedures applied with
attribute			"imosImpossibleDateQC(d	their specific parameters and
			ateMin=01/01/2007,	results.
			dateMax=15/07/2014) did	
			not fail on any TIME	
			sample.\nimosImpossibleL	
			ocationSetQC(distanceKm	
			PlusMinusThreshold=2.5)	
			did not fail on any	
			LATITUDE	
			sample.\nimosImpossibleL	
			ocationSetQC(distanceKm	
			PlusMinusThreshold=2.5)	
			did not fail on any	
			LONGITUDE sample"	
			LONGITODE sample	
Non-CF	Where			
attribute				
	geospatial_lat_units	S	geospatial_lat_units =	Units used for
			"degrees_north"	geospatial_lat_min/max
				attributes.
	geospatial_lon_units	S	geospatial_lon_units =	Units used for
			"degrees_east"	geospatial_lon_min/max
				attributes.
	and a second in the second in		and a section of the	Heite word for
	geospatial_vertical_unit	S	geospatial_vertical_units =	Units used for
	S		"metres"	geospatial_vertical_min/max
				attributes.
Non OF	When			
Non-CF attribute	**IICII			
attributo				

local_time_zone	N	local_time_zone = 10	Local time zone at the location
			of the dataset. See section
			3.2.4 - on time format. If local
			time does not fall into one
			zone for the full dataset, do
			·
			not use this attribute.
Who			
author_email	S	author_email =	NetCDF file author contact e-
		"info@emii.org.au"	mail address
principal_investigator_	S	principal_investigator_ema	Principal Investigator e-mail
email		il =	address
		"john.doe@utas.edu.au"	
institution_references	S	institution_references =	References that describe the
		"http://imos.org.au/emii.ht	data provider institution, the
		ml"	place to find all information on
			the dataset (web-based, i.e.
			give URLs). Multiple
			references should be
			separated with a semicolon ";".
			·
How			
lineage	S	lineage = "Data were	Information about how the
		processed according to	data has been produced and
		standard ANMN-NRS	processed, modified.
		procedures before	
		conversion to netCDF.	
		See link for details :	
		http://help.aodn.org.au/hel	
		p/sites/help.aodn.org.au/fil	
		es/ANMN%20CTD%20Pro	
		cessing%20Procedures.pd	
		f"	

Non-CF attribute

3.2.4 -Date and Time formats

All time values in IMOS netCDF files will be recorded as Coordinated Universal Time (UTC, for most purposes equivalent to Greenwich Mean Time).

Whenever time information is given in the global attributes, it will be formatted as a string according to the ISO 8601 standard (International Organization for Standardization, 2009): "YYYY-MM-DDThh:mm:ssZ" (i.e. year – month – day "T" hour : minute : second "Z") The "Z" indicates the time zone is (zero offset from) UTC. If higher resolution than seconds is needed, any number of decimal digits (".s") for the seconds is acceptable: "YYYY-MM-DDThh:mm:ss.sZ". Examples of the time format are shown below.

2005-10-24T08:00:00Z

2008-01-01T22:50:02.03Z

The representation of time as a numerical variable is described under the TIME variable chapter 3.4.1.1 -.

The global attribute 'local_time_zone' gives the time zone at the location where the measurements were collected. This allows the UTC times in the file to be converted into local time, which is important in considering many biological processes and phenomena that depend on the diurnal cycle.

The local time zone will be recorded as an offset in hours from UTC. For example Australian Eastern Standard Time is represented as 10, meaning 10 hours ahead of UTC.

Offsets from local to UTC time for Australian time zones can be found online.

The global attribute 'local_time_zone' should be used only when all data points in a dataset are from the same time zone. If time zone changes during the dataset (e.g. moving point measurements on a ship of opportunity) then do not use this global attribute. Instead, advanced users may choose to create a user-defined variable called 'local_time_zone'. If local time zone is not defined in the dataset, it will be calculated by data users from the latitude, longitude and UTC time variables.

3.2.5 -Processing level

Two attributes <file_version> and <file_version_quality_control> respectively describe the title and definition of level of processing and Quality Control (QC) found in the dataset.

Three possibilities are available for these two attributes:

Global attribute <file_version></file_version>	Global attribute <file_version_quality_control></file_version_quality_control>
Level 0 - Raw data	Raw data is defined as unprocessed data and data products that have
	not undergone quality control. The data may be in engineering or
	physical units, time and location details can be in relative units and
	values can be pre-calibration measurements.
Level 1 – Quality Controlled	Quality controlled data have been through quality assurance procedures
data	such as automated routines and sensor calibration or visual inspection
	and flag of obvious errors. The data are in physical units using standard
	SI metric units with calibration and other pre-processing routines
	applied, all time and location values are in absolute coordinates to
	comply with standards and datum. Data includes flags for each
	measurement to indicate the estimated quality of the measurement.
	Metadata exists for the data or for the higher level dataset that the data
	belongs to. This is the standard IMOS data level and is what should be
	made available to eMII and to the IMOS community.
Level 2 – Derived Products	Derived products require scientific and technical interpretation. Normally
	these will be defined by the community that collects or utilises the data.

3.2.6 -Global Attributes added by the data provider

The global attributes listed in the table in section 3.2.2 - are most important to define a dataset as clearly as possible. However, this list will not in all cases be exhaustive and eMII requests that other meaningful global attributes be used where necessary.

It is possible to add global attributes to meet specific facility needs. New attributes will need to be self defined, including a description and an example of how it is used. User-defined global attributes should be added to the existing list (appropriate appendix section) in the next version of the IMOS NetCDF Conventions document.

An example of a 'facility defined' global attribute and supporting information is below:

This example can be used by the ACORN facility to illustrate the kind of data and the type of radar used to produce the data. The prefix "ssr" added to each attribute means "sea surface radar".

ssr_Data_Type = "Range_Time_Series"

ssr_Radar = "Helzel/WERA"

3.3 - Dimensions

NetCDF file dimensions provide information on the size of the data variables. An unlimited dimension will make extension (new data added to an existing file) and aggregation (distinct files piled together into a single one) possible later if needed along this dimension. A dimension of size 1 can also be replaced by a scalar variable. The example in Table 3 allows for measurements at an unlimited number of time steps, at five different static depths.

Requirements are described further in the section 3.4.1 -.

Table 3 An example list of Dimensions for an IMOS netCDF file

Name	Example	Comment
TIME	TIME = unlimited	Number of time steps
DEPTH	DEPTH = 5	Number of depth levels

3.4 - Variables

NetCDF variables include data measured by instruments, parameters derived from the primary measurements and coordinate variables, which may be nominal values such as values for depth for instruments that do not directly record depth. Variables are also used to store quality flags associated to a measurement, and other metadata that is not applicable to all the data in a file. Ways to represent each type of variable in an IMOS netCDF file are described in the sub-sections below. Defined variable names are listed in chapter 5.1 -. Each variable has a specific set of attributes, some of which are mandatory.

In the tables below for variable attributes, the "Type" values are S for string, N for numeric (byte, short, long, integer, float or double), **D** for the type of the data variable and **Q** for the type of the quality control data variable. Mandatory attributes are marked in bold.

3.4.1 -Spatio-temporal variables

The spatio-temporal variables locate the data in time and space. For this purpose, they have an "axis" attribute to indicate that they represent either latitude (axis = "X"), longitude ("Y"), depth/height ("Z") or time ("T"). Any measured parameter can be located in space and time by listing the relevant spatiotemporal variables in its coordinates attribute. The use of a common set of spatial and temporal units and measures is the basic requirement to be able to integrate the various data collected by the IMOS project.

These variables can be coordinate variables¹ (representing an independent dimension of the data in the file), auxiliary coordinate variables² (dependent on one or more dimensions in the file) or scalar coordinate variables³ depending on the <u>CF feature type</u> template chosen. For more details on ways to associate data variables with their spatio-temporal coordinates, see <u>chapters 5</u> and <u>9</u> of the CF conventions document.

3.4.1.1 - Time

In a netCDF file, time is represented numerically as an interval (e.g. number of days or hours) from a reference time. For IMOS data, eMII recommends using a decimal number of days since the ARGO reference time of 1st of January 1950 at 00:00:00 UTC. In these conditions, using single precision would only achieve a 30s resolution so we recommend that any time measurement is stored in double precision using the type Double.

The following table presents the attributes used to describe the time variable.

Table 4 List of attributes defining the TIME variable for IMOS netCDF files

Attributes Type		Example	Comment
standard_name	S	standard_name="time"	A CF standard name that references a description of a variable's content in the standard name table
long_name	S	long_name = "time"	A descriptive name that indicates a variable's content.

³ A scalar variable that contains coordinate data. Functionally equivalent to either a size one coordinate variable or a size one auxiliary coordinate variable.



¹ It is a one-dimensional variable with the same name as its dimension [e.g., TIME(TIME)], and it is defined as a numeric data type with values that are ordered monotonically. Missing values are not allowed in coordinate variables.

² Any netCDF variable that contains coordinate data, but is not a coordinate variable (see above). Unlike coordinate variables, there is no relationship between the name of an auxiliary coordinate variable and the name(s) of its dimension(s).

	units	S	units = "days since 1950-01-01 00:00:00 UTC"	This is eMII's recommended unit and reference time for IMOS netCDF files. Please contact eMII if you require help with this conversion.
	axis	S	axis = "T"	Identifies time axes
	valid_min	D	valid_min = 0	Smallest valid value of a variable
	valid_max	D	valid_max = 90000.0	Largest valid value of a variable
	_FillValue	D	_FillValue = 999999.0	A value used to represent missing or undefined data ⁴ . Cannot be used for coordinate variables. Required if there could be missing values in the data.
	calendar	S	calendar = "gregorian"	Calendar used for encoding time axes. See Eaton et. al. 2009 for clarification.
	comment	S	comment = ""	Miscellaneous information about the data or methods used to produce it.
Non-CF attribute	uncertainty	N	uncertainty = 0.00001	Overall measurement uncertainty. Choose appropriate value. See section 3.4.4.2
Non-CF attribute	local_time_zone See APPENDIX 1: exam	N	local_time_zone = 10	Local time zone. See chapter 3.2.4 If local time does not fall into one zone for the full dataset, do not use this attribute.

See APPENDIX 1: example netcdf file.

 4 We ask that NaN "not a number" value shouldn't be used. Instead use a decimal value e.g. _FillValue of 999999.0.



-

3.4.1.2 - Horizontal coordinates

Horizontal coordinates (Latitude and Longitude) in an IMOS netCDF file will be specified in decimal degrees relative to the WGS84 coordinate reference system, with locations south of the equator having negative Latitude and locations west of zero degrees of Longitude having negative Longitude.

Using single precision would only achieve at worst an 11m resolution while modern GPS can provide <1m resolution. We recommend that any measurement of geographic coordinates is stored in double precision using the type Double.

The table below presents the attributes used to describe the variables LATITUDE and LONGITUDE.

Table 5 List of attributes that define the LATITUDE and LONGITUDE variables for IMOS netCDF files

Attributes	Туре	Example	Comment
standard_name	S	standard_name = "latitude" or standard_name = "longitude"	A CF standard name that references a description of a variable's content in the standard name table
long_name	S	long_name = "latitude" or long_name = "longitude"	A descriptive name that indicates a variable's content. This name is the IMOS long name given in chapter 5.1
units	S	units = "degrees_north" (LATITUDE) or units = "degrees_east" (LONGITUDE)	Latitude unit: degrees north; southern latitudes are negative Longitude unit: degrees east; western longitudes are negative
axis	S	axis = "Y" (LATITUDE) or axis = "X" (LONGITUDE)	Identifies type of spatial axis

valid_min valid_max	D	<pre>valid_min = -90 (LATITUDE) valid_min = -180 (LONGITUDE) valid_max = 90</pre>	Smallest valid value of a variable Largest valid value of a variable
	U	(LATITUDE) valid_min = 180 (LONGITUDE)	
_FillValue	D	_FillValue = 999999.0	A value used to represent missing or undefined data ⁵ . Cannot be used for coordinate variables. Required if there could be missing values in the data
comment	S	comment = ""	Miscellaneous information about the data or methods used to produce it.
uncertainty	N	uncertainty = 0.001	Overall measurement uncertainty. Choose appropriate value. See section 3.4.4.2
reference_datum	S	reference_datum = "WGS84 coordinate reference system"	Text description of the geographic reference datum for the variable

See APPENDIX 1: example netcdf file.

3.4.1.3 - Vertical coordinates

For any vertical coordinate, variable attributes must define a reference point or datum (attribute "reference_datum"), the direction of increasing values (attribute "positive", up or down) and the unit of measure (attribute "units"). Four datums are recognised:

-Mean Sea Level (MSL),

Non-CF attribute

Non-CF attribute

-sea	surface	

-sea bottom,

-sensor.

The time and location of the instrument will need to be included to allow for tide corrections. When necessary, vertical measurements should be converted into one of the acceptable datums.

For example: depth may be recorded as metres below MSL, positive down.

Depth and height should be measured in metres or other SI units. Pressure measurements should be recorded in a separate parameter. It is not permissible to label a pressure measurement as "depth" or "height".

The following table presents the attributes used to describe any depth or height variable.

Table 6 List of attributes that define any depth or height variable for IMOS netCDF files

Attributes Type		Example	Comment
standard_name	S	standard_name = "depth" or "height"	A CF standard name that references a description of a variable's content in the standard name table
long_name	S	long_name = "depth" or "height"	A descriptive name that indicates a variable's content. This name is the IMOS long name given in chapter 5.1 -
units	S	units = " m "	Usually "m" for metres.
axis	S	axis = "Z"	Identifies vertical axis
positive	S	positive = "down" (depth) or "up" (height)	Direction of increasing vertical coordinate value.
valid_min	D	valid_min = 0	Smallest valid value of the variable

⁵ We ask that NaN "not a number" value shouldn't be used. Instead use a decimal value e.g. _FillValue of 999999.0.



	valid_max	D	valid_max = 12000	Largest valid value of the variable
	_FillValue	D	_FillValue = -99999.0	A value used to represent missing or undefined data ⁶ . Cannot be used if DEPTH/HEIGHT is a dimension. Required if there could be missing values in the
	comment	S	comment = "depthPP:	data. Miscellaneous information
	comment	5	Depth computed using the SeaWater toolbox from latitude and relative pressure measurements"	about the data or methods used to produce it.
Non-CF attribute	uncertainty	N	uncertainty = 0.05	Overall measurement uncertainty. Choose appropriate value. See section 3.4.4.2
Non-CF attribute	reference_datum	S	reference_datum = "Mean Sea Level (MSL)"	Text description of the reference datum for the variable

See APPENDIX 1: example netcdf file.

3.4.2 -Data variables

IMOS recommended variable names are listed in chapter 5.1 -. For example, TEMP represents the sea water temperature and PSAL represents the sea water salinity. Variable names should begin with a letter and be composed of letters, digits and underscores.

In some cases, two instruments may measure the same variable (e.g. wind speed measured by two anemometers mounted on the same vessel). In these cases, the second instance of a variable should be identified with the suffix '_2' (e.g. "WSPD" and "WSPD_2"). Several variable attributes can be used to

⁶ We ask that NaN "not a number" value shouldn't be used. Instead use a decimal value e.g. _FillValue of 999999.0.



_


specify the differences, including comments, descriptive attributes (sensor_depth, sensor_height) and long names. Two anemometers might be distinguished in their long names as "wind_speed_starboard" and "wind_speed_port".

The definition of a variable in a netCDF file has three components: type, name and dimensions.

 $\overline{\text{CF says}}$: "If any or all of the dimensions of a variable have the interpretations of "date or time" (T), "height or depth" (Z), "latitude" (Y), or "longitude" (X) then it is recommended, but do not required, that those dimensions appear in the relative order T , then Z , then Y , then X in the CDL definition corresponding to the file. All other dimensions should, whenever possible, be placed to the left of the spatiotemporal dimensions".

Example for the sea water temperature output by a 3D model over a time period:

Float TEMP(TIME, DEPTH, LATITUDE, LONGITUDE)



The following table presents the attributes used to describe a data variable.

Table 7 List of data variables attributes for IMOS netCDF files

Attributes	Туре	Example	Comment
standard_name	S	standard_name = "sea_surface_temperature"	A CF standard name that references a description of a variable's content in the CF standard name table.
units	S	units = "Celsius"	Unit of measure
_FillValue	D	_FillValue = 999999	A value used to represent missing or undefined data ⁷ . Required if there could be missing values in the data.

⁷ We ask that NaN "not a number" value shouldn't be used. Instead use a decimal value e.g. _FillValue of 999999.0.



long_name	S	long_name =	A descriptive name that
		"sea_surface_temperature"	indicates a variable's
			content. This name is the
			IMOS long name given in
			chapter 5.1 Please
			contact eMII regarding any
			parameters that don't
			appear in the table
coordinates	S	coordinates = "TIME	A blank-separated list of
		LATITUDE LONGITUDE	the names of the relevant
		DEPTH" ;	variables that include
			spatio-temporal coordinate
			information.
	_		B () ()
valid_min	D	valid_min = -2.0	Range of values for valid
valid_max		valid_max = 40	data
add_offset	N	add_offset = 25	If present for a variable,
			this number is to be added
			to the data after it is read
			by an application. If both
			scale_factor and
			add_offset attributes are
			present, the data are first
			scaled before the offset is
			added.
scale_factor	N	scale_factor = 0.01	If present for a variable, the
			data are to be multiplied by
			this factor after the data
			are read by an application.
applied_offset	N	applied_offset = -10.1325	If present for a variable, this
,		., –	offset has been added to
			the original data to correct
			it.
original_units	S	original_units = "mg/l"	Original units of a variable's
Original_utilits		original_uriits = riig/i	content in the original
			instrument file. Dissolved
			manument nie. Dissoived

Non-CF attribute

Non-CF attribute

Non-CF attribute	original_name	S	original_name = "oxsolMg/L"	oxygen concentration for example can be expressed in many units but umol I ⁻¹ is IMOS preferred units for dissemination. Original name of a variable in the original instrument file.
Non-CF attribute	sensor_serial_number	S	sensor_serial_number = "DO142"	Serial number of the sensor which collected the data of this variable.
	comment	S		Miscellaneous information about the this variable or methods used to produce it
	history	S		As for global attribute history, but specific to this variable.
	references	S		References that describe the data or methods used to produce it. Multiple references should be separated with a semicolon.
	ancillary_variables	S	ancillary_variables = "TEMP_quality_control TEMP_uncertainty"	Blank-separated list of variables that contain closely associated data, e.g. the measurement uncertainties of instrument data. See section 3.4.4
Non-CF attribute	sensor_depth	N	sensor_depth = 0	Nominal sensor depth(s) in metres positive down.
Non-CF attribute	sensor_height	N	sensor_height = 2	Nominal sensor height(s) in metres positive up.

Non-CF attribute	observation_type	S	observation_type = "measured"	Type of observation. If for example, the variable is measured or calculated.
Non-CF attribute	uncertainty	N	uncertainty = 0.001	Overall measurement uncertainty, if constant. See section 3.4.4.2
Non-CF attribute	accuracy	N	accuracy = 0.01	Nominal sensor accuracy. See section 3.4.4.2
Non-CF attribute	precision	N	precision = 0.01	Nominal sensor precision. See section 3.4.4.2
Non-CF attribute	resolution	N	resolution = 0.01	Nominal resolution of this data parameter. See section 3.4.4.2
	cell_methods	S	cell_methods = "point"	Records the method used to derive data that represents cell values. See section 5.3 -

See APPENDIX 1: example netcdf file.

3.4.3 -Variable attributes added by data provider

Additional variable attributes can be defined by the data provider (in consultation with eMII). Such attributes will be incorporated into the next version of this document.

3.4.4 - Ancillary variables

When one variable provides metadata about the individual values of another variable it may be desirable to express this association by providing a link between the variables. For example, instrument data may have associated measures of uncertainty or quality control flags. The attribute "ancillary_variable" is used to express these types of relationships.

The use of ancillary variables in the context of data Quality Control and uncertainty are described in sections 3.4.4.1 - and 3.4.4.2 -.

3.4.4.1 -Quality control (QC)

Quality control involves some sort of assessment of the data to identify data points or even data sets which have errors that limit their use. The basic approach used by IMOS is to keep all of the data but to flag data or data sets that do not meet the quality assessment standards of data collectors / principal investigators. This section describes how to represent this data quality information in an IMOS netCDF file.

3.4.4.1.1 - Quality Control sets used by the IMOS project

The attribute "quality_control_conventions" will enable users to define which set of quality control (QC) flags was applied to the dataset. Please see chapter 5.2 -. Additional QC sets may be added in future versions of this document.

3.4.4.1.2 - Definition of quality control variables and attributes

Quality flags for the data in a variable <PARAM> should be described by an ancillary variable named "<PARAM>_quality_control".

The following table lists all the attributes used to define a Quality Control variable. It also includes an example using the quality control set 1 (IMOS standard flags).

Table 8 List of attributes used to define a Quality Control variable

Attributes	Туре	Example	Comment
long_name	S	long_name = "quality flag for	Non-
		sea_surface_temperature"	standardised
			name of
			variable
standard_name	S	standard_name =	Standardised
		"sea_surface_temperature status_flag"	name
			(status_flag
			suffix) of QC
			variable using
			the CF
			convention

quality_control_conventions	S	quality_control_conventions ="IMOS	Name of the
quanty_control_conventions		' '= =	
		standard flags"	Quality
			Control
			convention
			used. See
			Reference
			table A.
FillValue	D	_FillValue = 99b	Value used to
			represent
			missing QC
			flags
flag_values	D	flag_values = 0b, 1b, 2b, 3b, 4b, 5b, 6b,	List of flag
		7b, 8b, 9b	values used.
flag_meanings	S	flag_meanings = "No_QC_performed	The meaning
		Good_data Probably_good_data Bad_data_that_are_potentially_correctable	of each flag
		Bad_data Value_changed Not_used	(in the same
		Not_used Not_used Missing_value"	order as
			flag_values).
quality_control_global_conventions	S	quality_control_global_conventions = "Argo	Convention
		reference table 2a (see	used to
		http://www.cmar.csiro.au/argo/dmqc/	describe the
		user_doc/QC_flags.html), applied to data	global quality
		in position only (between global attributes	of a variable.
		time_deployment_start and	
		time_deployment_end)"	
quality_control_global	S	quality_control_global = "A"	Global quality
			control value.
			See 5.2.2.2 -
See ADDENDIY 1: evample netedf fi	L		

See APPENDIX 1: example netcdf file.

3.4.4.2 - Uncertainty, accuracy, precision and resolution

The term uncertainty is here defined as "the parameter, associated with the result of a measurement that characterises the dispersion of the values that could reasonably be attributed to the measurand" (Underwood, 2008).

The document "IMOS Data Streams and their Uncertainties" (Underwood, 2008) contains a calculation or estimation of the uncertainty for each data stream that is provided by IMOS..

3.4.4.2.1 - Implementation in IMOS

If the overall measurement uncertainty for a variable <PARAM> is reasonably well-known, it must be provided in the attributes. If it is constant is should be provided in the attribute <PARAM>:uncertainty. If not constant it should be provided in a variable of its own, called <PARAM>_uncertainty. The standard name for this variable is formatted as: "<parameter_standard_name> standard_error" (e.g. TEMP_uncertainty:standard_name = "sea_surface_temperature standard_error")

If it is impossible to estimate the overall measurement uncertainty, the attribute <PARAM>:accuracy can be set to the nominal sensor accuracy. Accuracy characterises how close the measurement of a quantity is to the value of that quantity (systematic errors reduce accuracy).

The attributes <PARAM>:precision and <PARAM>:resolution contain the sensor precision and resolution if defined. Precision characterises the level of agreement between repeated measurements of a quantity under unchanged conditions (random errors reduce precision). Resolution is a limit on the precision of a measurement imposed by the amount of information recorded (e.g. number of decimal places, or number of measurements in a time interval).

3.4.4.2.2 - Example

This example is extracted from the "<u>IMOS Data Streams and their Uncertainties</u>" document (Underwood, 2008).

A temperature measurement may be given as "20.12 degrees Celsius with a 95% confidence of 0.01 degree Celsius". To rephrase this, there are 5 chances in one hundred that the real temperature (the measurand) was outside the range 20.12 C + 0.01 C.

In a netCDF file, the uncertainty on this temperature measurement will appear as:

TEMP:uncertainty = 0.01

4 - IMOS FILE NAMING CONVENTION

NetCDF files will be named according to the IMOS NetCDF <u>File Naming Convention</u> document. See <u>APPENDIX 3: IMOS File Naming Convention</u>.

5 - REFERENCE TABLES

5.1 - IMOS parameter dictionary

The IMOS parameter dictionary seeks to list recommended netCDF variable names, long_name, standard_name and units attributes to be used.

The most up to date list of parameter names, standard names (or long names for non-CF parameters) and units can be found on the <u>IMOS Toolbox GitHub repository</u>. This list is not exhaustive and will continue to expand and evolve. Ultimately, it will constitute an IMOS data parameter dictionary. The standard names used in the IMOS parameter dictionary are taken from the <u>CF standard names</u>.

Non-CF long names and variable names are derived from the following sources:

- a list of parameter names available on the WOCE website using GF3 codes (WOCE, 2009).
- a parameter dictionary available on the <u>OceanSites data format reference manual</u> (OceanSites, 2008).

Non-CF parameters (with no CF standard name) should be described using only the attribute long_name.

All units defined for the parameters must comply with <u>Udunits</u> (Unidata Program Centre of the University Corporation for Atmospheric Research, 2008) as implemented by the CF standard.

5.2 - Quality control flags

Quality control (QC) flags are added to a file by various procedures to indicate the quality of individual data values.

The attribute "quality_control_set" enables the user to define which Quality Control flags set was used in the dataset. Please see section 3.4.4.1 - for definitions of Quality Control sets.

If your facility is using a different set of quality control codes please supply eMII with the details. If appropriate, we will incorporate your codes into the IMOS convention and create a QC set that meets your needs.

Reference Table A: List of QC flags sets used in the IMOS project

Set Number	Description
1	IMOS standard flags (GTSPP data quality codes)
2	ARGO quality control procedure
3	BOM (SST and Air-Sea flux) quality control procedure
4	WOCE quality control procedure (Multidisciplinary Underway Network – CO ₂ measurements)

5.2.1 -Set 1 - IMOS standard flags

Reference Table B: IMOS standard flags

Flag Value	Meaning	Description
0	No QC performed	The level at which all data enter the working archive. They have not yet been quality controlled
1	Good data	Top quality data in which no malfunctions have been identified and all real features have been verified during the quality control process

2	Probably good	Good data in which some features (probably real) are
	data	present but these are unconfirmed. Code 2 date are also
		data in which minor malfunctions may be present but these
		errors are small and/or can be successfully corrected
		without seriously affecting the overall quality of the data.
	D 1 1 1 1 1	
3	Bad data that are	Suspect data in which unusual, and probably erroneous
	potentially	features are observed
	correctable	
4	Bad data	Obviously erroneous values are observed
5	Value changed ⁸	Altered by a QC Centre, with original values (before the
3	value changed	
		change) preserved in the history record of the profile
6	Not used	Flag 6 is reserved for future use
7	Not used	Flag 7 is reserved for future use
8	Not used	Flag 8 is reserved for future use
	Minainanahaa	In display that the sale result is uniquing.
9	Missing value	Indicates that the element is missing

5.2.2 -Set 2 - ARGO quality control procedure

5.2.2.1 - ARGO measurement flag scale

Reference Table C : ARGO measurement flag scale

Flag Value		Meaning	9	Real-time comment	Delayed-mode comment
0	No perfo	QC rmed	was	No QC was performed	No QC was performed

⁸ Where data values must be changed (e.g. smoothing of data sets) we strongly prefer that the original data be retained and an additional variable be added to accommodate the interpolated/corrected data values.



_

1	Good data	All ARGO real-time QC	The adjusted value is
'	Cood data	tests passed	statistically consistent and a
		10313 943304	statistical error estimate is
			supplied
2	Probably good	Probably good data	Probably good data
	data		
3	Bad data that are	Argo QC tests (15, 16 or	An adjustment has been
	potentially	17, see Carval et al 2008)	applied, but the value may still
	correctable	failed and all other real-	be bad
		time QC tests passed.	
		These data are not to be	
		used without scientific	
		correction. A flag 3 may be	
		assigned by an operator	
		during additional visual	
		QC for bad data that may	
		be corrected in delayed	
		mode	
4	Bad data	Data have failed one or	Bad data. Not adjustable
		more of the real-time QC	
		tests, excluding Test 16	
		(see Carval et al 2008). A	
		flag 4 may be assigned by	
		an operator during	
		additional visual QC for	
		bad data that are not	
		correctable	
5	Value changed 9	Value changed	Value changed
6	Not used	Not used	Not used
7	Not used	Not used	Not used
8	Interpolated value	Interpolated value	Interpolated value

-

⁹ Where data values must be changed we strongly prefer that the original data be retained and an additional variable be added to accommodate the interpolated/corrected data values.

9	Missing value	Missing value	Missing value

5.2.2.2 - ARGO profile quality flags

Argo profile quality flags (A to F) are defined as the percentage of levels (N) with good data, where:

- QC flag values of 1, 2, 5 or 8 are counted as GOOD data
- QC flag values of 9 (missing) are NOT USED in the computation
- All other QC flag values are counted as BAD data

The computation should be taken from <PARAM>_ADJUSTED_QC if available and from <PARAM>_QC otherwise (Carval et al 2008).

This could also be applied to any type of data, not only profile data.

Reference Table D : ARGO profile quality flags

Flag	Meaning
""(blank)	No QC performed
A	N = 100%; All profile levels contain good data
В	75% <= N < 100%
С	50% <= N < 75%
D	25% <= N < 50%
E	0% <= N < 25%
F	N = 0%; No profile levels have good data

Example:

A TEMP profile has 60 levels (3 levels contain missing values)

- 45 levels are flagged as 1
- 5 levels are flagged as 2
- 7 levels are flagged as 4

• 3 levels are flagged as 9 (missing)

Percentage of good levels = ((45+5)/57)*100 = 87.7%

TEMP_quality_control:quality_control_global = "B"

5.2.3 -Set 3 - BOM quality control procedure (SST and Air-Sea fluxes)

The following table summarises the different flags used by the Bureau of Meteorology to qualify the quality for different datasets, particularly SST and Air-Sea fluxes (Verein 2008).

Reference Table E: BOM Quality Control procedure flags (SST and Air Sea Fluxes)

Flag	Purpose
В	Value out of bounds
С	Time not sequential
D	Failed T, Tw and Td tests
E	Failed True wind recomputation test
F	Platform velocity unrealistic
G *	Value exceeds threshold
H **	Discontinuity
J	Erroneous value
L	Value located over land
M	Instrument malfunction
Q	Pre-flagged as suspect
S	Spike in data (visual)
Т	Time duplicate
U*	Suspect data (statistical)
V *	Step in data (statistical)
X *	Spike in data (statistical)
Z	Value passed all test

Note: * - applied for SST, ** - applied for time

5.2.4 -Set 4 - WOCE quality control procedure (Multidisciplinary Underway Network – CO₂ measurements)

Reference Table F: WOCE quality control procedure flags (CO₂ measurements)

Flag	Meaning
2	good
3	questionable
4	bad

If data is flagged as questionable (flag number 3), the variable SUBFLAG is used to add more information.

Table FF: SUBFLAG variable for questionable measurements

Flag	Meaning
1	Outside of standard range
2	questionable/interpolated SST (Sea Surface Temperature)
3	questionable EQU temperature
4	Anomalous (EQU T-SST) (+- 1 C)
5	questionable sea-surface salinity
6	questionable pressure
7	low EQU gas flow
8	questionable air value
10	other, water flow

References: "Pierrot,D. et al. 2009, Recommendations for Autonomous Underway pCO2 Measuring Systems and Data Reduction Routines, Deep-Sea Research II, doi:10.1016/j.dsr2.2008.12.005"

5.3 - Cell methods

<u>CF Cell methods</u> are applied in generating the parameter value for a cell, particularly for gridded data sets.

In the Units column, u indicates the units of the physical quantity before the method is applied.

Reference Table G: List of different cell methods, derived from the CF convention

Cell method	Units	Description
point	u	The data values are representative of points in space or time
		(instantaneous). This is the default method for a quantity that
		is intensive with respect to the specified dimension.
sum	u	The data values are representative of a sum or accumulation
		over the cell. This is the default method for a quantity that is
		extensive with respect to the specified dimension
maximum	u	Maximum
median	u	Median
mid_range	u	Average of the maximum and minimum
minimum	u	Minimum
mean	u	Mean (average value)
mode	u	Mode (most common value)
standard_deviation	u	Standard deviation
variance	u ²	Variance

6 - REFERENCES

Bainbridge, S. 2008. Data Standards Framework for the IMOS instrument Data. AODCJF Internal Report.

Carval, T., Keeley, B., Takatsuki, Y, Yoshida, T., Lock, S., Schmid, C., Goldsmith, R., Wong, A., McCreadie, R., Thresher, A and Tran, A. 2008. *Argo Data Management User's Manual Version 2.1*. IFREMER.

Convention for the standardisation of NetCDF Files. 1995. Sponsored by the "Cooperative Ocean/Atmosphere Research Data Service, a NOAA/university cooperative for the sharing and distribution of global atmospheric and oceanographic research data sets. http://ferret.wrc.noaa.gov/noaa_coop/coop_cdf_profile.html. Accessed December 2008.

Eaton, B., Gregory, J., Drach, B., Taylor, K, Hnakin, S., Caron, J., Signell, R., Bentley, P. Rappa, G., Höck H., Pamment A. and Juckes M. 2009. *NetCDF Climate and Forecast (CF) Metadata Conventions* v1.6 http://cf-pcmdi.llnl.gov/. Accessed December 2011.

International Organization for Standardization. 2009. *Numeric representation of Dates and Time*. http://www.iso.org/iso/support/faqs/faqs_widely_used_standards/widely_used_standards_other/date_and_time_format.htm. Accessed 27 Jan 2009

Mancini, S., Tattersall, K., and Proctor, R. 2008. *IMOS NetCDF File Naming Convention v1.3* http://imos.org.au/facility_manuals.html. Accessed 31 January 2009.

OceanSITES. 2007. Taking the Pulse of the Global Ocean http://www.oceansites.org. Accessed 27 January 2009.

OceanSites 2008. *OceanSites Parameters Table*. http://www.ifremer.fr/co/etc/oceansites/oceansites-user-manual-parameters.pdf . Accessed 27 January 2009.

Olsen, L.M, G. Major, K. Shein, J. Scialdone, R. Vogel, S. Leicester, H. Weir, S. Ritz, T. Stevens, M. Meaux,c. Salomon, R. Bilodeau, M. Holland, T. Northcutt, R.A. Restrepo, 2007. NASA/Global Change Master Directory (GCMD) Earth Science Keywords version 6.0.0.0.0.

http://gcmd.nasa.gov/Resources/valids/archives/keyword_list.html . Accessed 18 Mar 2009.

Reed, G. 2008. *Marine Community Profile of ISO 19115 Version 1.4*. Australian Ocean Data Centre Joint Facility

Rew, R., Davis, G., Emmersson, S. and Davies, H. 2008. *UniData NetCDF User's Guide* http://www.unidata.ucar.edu/. Accessed 20 Dec 2008.

SeaDataNet 2009. SeaDataNet measurand qualifier flags: list key L201. http://seadatanet.maris2.nl/v_bodc_vocab/welcome.aspx. Accessed 27 Jan 2009.

Time and Date AS. 2009. *Time Zone in Hobart* http://www.timeanddate.com/worldclock/timezone.html?n=396. Accessed 27 Jan 2009.

Underwood, M. 2008. *IMOS Data streams and their Uncertainties v 3.1* http://imos.org.au/facility_manuals.html. Accessed 15 December 2008.

Unidata Program Centre of the University Corporation for Atmospheric Research. 2008. *Writing NetCDF Files: Best Practices* http://www.unidata.ucar.edu/software/netcdf/docs/BestPractices.html. Accessed 15 December 2008.

Unidata Program Centre of the University Corporation for Atmospheric Research. 2008. *UDUNITS* Software Package. http://www.unidata.ucar.edu/software/udunits/. Accessed 15 December 2008...

Verein, R. 2008. Quality Control procedure for automated processing of IMOS ship and mooring observations (Facilities 2c, 2d and 3). CAWCR. Australian Bureau of Meterology.

Wikipedia contributors. 2008. *Wikipedia, The Free Encyclopedia : ISO 8601* http://en.wikipedia.org/wiki/ISO 8601. Accessed Jan 20 2009.

World Ocean Circulation Experiment 2009. WOCE Parameter Lists: Basic Parameters & Full List of Parameters with extended-GF3 codes.

http://woce.nodc.noaa.gov/woce v3/wocedata 1/sss/documents/liste param.htm . Accessed 27 January 2009.

APPENDIX 1: EXAMPLE NETCDF FILE

This is an example IMOS formatted netCDF file for ANMN timeseries temperature and pressure logger data.

```
netcdf
                       IMOS_ANMN-NSW_TZ_20110616T230000Z_PH100_FV01_PH100-1106-Aqualogger-520PT-104_END-
20110902T130000Z_C-20150225T011055Z {
dimensions:
    TIME = 22345;
variables:
    double TIME(TIME);
        TIME:standard_name = "time";
        TIME:long_name = "time";
        TIME:units = "days since 1950-01-01 00:00:00 UTC";
        TIME:calendar = "gregorian";
        TIME:axis = "T";
        TIME:valid_min = 0.;
        TIME:valid_max = 90000.;
    double LATITUDE;
        LATITUDE:standard_name = "latitude";
        LATITUDE:long_name = "latitude";
        LATITUDE:units = "degrees_north";
        LATITUDE:axis = "Y";
        LATITUDE:reference_datum = " WGS84 coordinate reference system";
        LATITUDE:valid_min = -90.;
        LATITUDE:valid max = 90. :
    double LONGITUDE;
        LONGITUDE:standard_name = "longitude";
        LONGITUDE:long_name = "longitude";
        LONGITUDE:units = "degrees_east";
        LONGITUDE:axis = "X";
        LONGITUDE:reference_datum = "WGS84 coordinate reference system";
        LONGITUDE:valid_min = -180.;
        LONGITUDE:valid_max = 180.;
    float NOMINAL_DEPTH;
        NOMINAL_DEPTH:standard_name = "depth";
        NOMINAL_DEPTH:long_name = "nominal depth";
        NOMINAL DEPTH:units = "metres";
        NOMINAL_DEPTH:axis = "Z";
        NOMINAL_DEPTH:positive = "down";
        NOMINAL_DEPTH:reference_datum = "sea surface";
        NOMINAL_DEPTH:valid_min = -5.f;
        NOMINAL_DEPTH:valid_max = 12000.f;
    float TEMP(TIME);
        TEMP:coordinates = "TIME LATITUDE LONGITUDE NOMINAL_DEPTH";
        TEMP:standard_name = "sea_water_temperature" ;
        TEMP:long_name = "sea_water_temperature";
```

```
TEMP:units = "Celsius";
         TEMP:valid_min = -2.5f;
         TEMP:valid_max = 40.f;
         TEMP:_FillValue = 999999.f;
         TEMP:ancillary_variables = "TEMP_quality_control";
    byte TEMP_quality_control(TIME);
         TEMP_quality_control:long_name = "quality flag for sea_water_temperature";
         TEMP_quality_control:standard_name = "sea_water_temperature status_flag";
         TEMP_quality_control:_FillValue = 99b;
         TEMP_quality_control:quality_control_conventions = "IMOS standard flags";
        TEMP_quality_control:flag_values = 0b, 1b, 2b, 3b, 4b, 5b, 6b, 7b, 8b, 9b;
         TEMP_quality_control:flag_meanings
                                                           "No_QC_performed
                                                                                    Good_data
                                                                                                      Probably_good_data
Bad_data_that_are_potentially_correctable Bad_data Value_changed Not_used Not_used Not_used Missing_value";
         TEMP_quality_control:quality_control_global_conventions
                                                                                                                     (see
http://www.cmar.csiro.au/argo/dmqc/user_doc/QC_flags.html), applied on data in position only (between global attributes
time_deployment_start and time_deployment_end)";
         TEMP_quality_control:quality_control_global = "A";
    float PRES(TIME);
         PRES:coordinates = "TIME LATITUDE LONGITUDE NOMINAL_DEPTH";
         PRES:standard_name = "sea_water_pressure";
         PRES:long_name = "sea_water_pressure";
         PRES:units = "dbar";
         PRES:valid_min = -5.f;
         PRES:valid_max = 12000.f;
         PRES:_FillValue = 999999.f;
         PRES:ancillary_variables = "PRES_quality_control";
    byte PRES_quality_control(TIME);
         PRES_quality_control:long_name = "quality flag for sea_water_pressure";
         PRES_quality_control:standard_name = "sea_water_pressure status_flag";
         PRES_quality_control:_FillValue = 99b;
         PRES_quality_control:quality_control_conventions = "IMOS standard flags";
         PRES_quality_control:flag_values = 0b, 1b, 2b, 3b, 4b, 5b, 6b, 7b, 8b, 9b;
         PRES_quality_control:flag_meanings
                                                           "No_QC_performed
                                                                                                      Probably_good_data
                                                                                    Good_data
Bad_data_that_are_potentially_correctable Bad_data Value_changed Not_used Not_used Not_used Missing_value";
         PRES_quality_control:quality_control_global_conventions
                                                                          "Argo
                                                                                     reference
                                                                                                   table
                                                                                                             2a
                                                                                                                     (see
http://www.cmar.csiro.au/argo/dmqc/user_doc/QC_flags.html), applied on data in position only (between global attributes
time_deployment_start and time_deployment_end)";
         PRES_quality_control:quality_control_global = "A";
    float DEPTH(TIME);
         DEPTH:coordinates = "TIME LATITUDE LONGITUDE NOMINAL_DEPTH";
         DEPTH:standard_name = "depth";
         DEPTH:long_name = "actual depth";
         DEPTH:units = "metres";
         DEPTH:reference datum = "sea surface";
         DEPTH:valid_min = -5.f;
         DEPTH:valid_max = 12000.f;
         DEPTH:_FillValue = 999999.f;
         DEPTH:comment = "depthPP: Depth computed using the Gibbs-SeaWater toolbox (TEOS-10) v3.02 from latitude and
absolute pressure measurements to which a nominal value for atmospheric pressure (10.1325 dbar) has been substracted.";
         DEPTH:ancillary_variables = "DEPTH_quality_control";
```

```
byte DEPTH_quality_control(TIME);
         DEPTH_quality_control:long_name = "quality flag for depth";
         DEPTH_quality_control:standard_name = "depth status_flag";
         DEPTH_quality_control:_FillValue = 99b;
         DEPTH_quality_control:quality_control_conventions = "IMOS standard flags";
         DEPTH_quality_control:flag_values = 0b, 1b, 2b, 3b, 4b, 5b, 6b, 7b, 8b, 9b;
         DEPTH_quality_control:flag_meanings
                                                             "No_QC_performed
                                                                                      Good_data
                                                                                                        Probably_good_data
Bad_data_that_are_potentially_correctable Bad_data Value_changed Not_used Not_used Mot_used Missing_value";
         DEPTH_quality_control:quality_control_global_conventions
                                                                            "Argo
                                                                                       reference
                                                                                                     table
                                                                                                               2a
                                                                                                                       (see
                                                                      =
http://www.cmar.csiro.au/argo/dmqc/user_doc/QC_flags.html), applied on data in position only (between global attributes
time_deployment_start and time_deployment_end)";
         DEPTH_quality_control:quality_control_global = "A";
// global attributes:
         :toolbox_input_file
"/home/ggalibert/Documents/IMOS_toolbox/data_files_examples/NSW/DATA/MOORINGS/RAW/PH100/019_PH100_20Jun2011/A
QUAtec/csv/PH100_520PT_20Jun2011_564.csv";
         :toolbox_version = "2.4 - GLNXA64";
         :file_version = "Level 1 - Quality Controlled Data";
         :file_version_quality_control = "Quality controlled data have passed quality assurance procedures such as automated
routines and sensor calibration or visual inspection and removal of obvious errors. The data are in physical units using standard SI
metric units with calibration and other pre-processing routines applied, all time and location values are in absolute coordinates to
comply with standards and datum. Metadata exists for the data or for the higher level dataset that the data belongs to. This is the
standard IMOS data level and is what should be made available to eMII and to the IMOS community.";
         :project = "Integrated Marine Observing System (IMOS)";
         :Conventions = "CF-1.6,IMOS-1.3";
         :standard_name_vocabulary = "NetCDF Climate and Forecast (CF) Metadata Convention Standard Name Table 27";
         :institution = "ANMN-NSW";
         :date_created = "2015-02-25T01:10:55Z";
         :abstract = "NSW-IMOS Port Hacking 100m Mooring";
         :comment = "Geospatial vertical min/max information has been computed using the Gibbs-SeaWater toolbox (TEOS-10)
v3.02 from latitude and absolute pressure measurements to which a nominal value for atmospheric pressure (10.1325 dbar) has
been substracted.":
         :source = "Thermistor String";
         :instrument = "Aquatec Aqualogger 520PT";
         :keywords = "Aqualogger 520PT, TIME, LATITUDE, LONGITUDE, NOMINAL DEPTH, TEMP, PRES, DEPTH";
                                            "IMOS
         :keywords_vocabulary
                                                        parameter
                                                                        names.
                                                                                      See
                                                                                                https://github.com/aodn/imos-
toolbox/blob/master/IMOS/imosParameters.txt"
         :references = "http://www.imos.org.au";
         :site_code = "PH100";
         :platform_code = "PH100";
         :deployment_code = "PH100-1106";
         :featureType = "timeSeries";
         :naming_authority = "IMOS";
         :instrument_serial_number = "023-564";
         :instrument_sample_interval = 300.;
         :history = "2015-02-25T01:11:21Z - depthPP: Depth computed using the Gibbs-SeaWater toolbox (TEOS-10) v3.02 from
latitude and absolute pressure measurements to which a nominal value for atmospheric pressure (10.1325 dbar) has been
```

substracted.";

:quality_control_log = "imosImpossibleDateQC(dateMin=01/01/2007, dateMax=10/02/2015) did not fail on any TIME sample.\nimosImpossibleLocationSetQC(distanceKmPlusMinusThreshold=2.5) did **LATITUDE** not fail on anv sample.\nimosImpossibleLocationSetQC(distanceKmPlusMinusThreshold=2.5) did LONGITUDE not fail on anv sample.\nimosInOutWaterQC(in=20/06/11 12:55:00, out=31/08/11 13:30:00) flagged 1601 TEMP samples with Bad_data.\nimosInOutWaterQC(in=20/06/11 12:55:00, out=31/08/11 13:30:00) flagged 1601 PRES samples with Bad_data.\nimosInOutWaterQC(in=20/06/11 12:55:00, out=31/08/11 13:30:00) flagged 1601 DEPTH samples with flag Bad_data.\nimosGlobalRangeQC(min=-2.5, max=40) did not fail on any TEMP sample.\nimosGlobalRangeQC(min=-5, max=12000) did not fail on any PRES sample.\nimosGlobalRangeQC(min=-5, max=12000) did not fail on any DEPTH sample.\nimosImpossibleDepthQC(zNominalMargin=15, maxAngle=70 => min=99.7923, max=143.1251) did not fail on any PRES sample.\nimosImpossibleDepthQC(zNominalMargin=15, maxAngle=70 => min=89, max=132) did not fail on any DEPTH sample.";

```
:geospatial_lat_min = -34.1203333333;
:geospatial_lat_max = -34.1203333333 ;
:geospatial_lon_min = 151.22415;
:geospatial_lon_max = 151.22415;
:instrument_nominal_height = 6.;
:instrument_nominal_depth = 104.;
:site_nominal_depth = 110.;
:geospatial_vertical_min = 105.41f;
:geospatial_vertical_max = 105.41f;
:geospatial_vertical_positive = "down";
:time_deployment_start = "2011-06-20T12:55:00Z";
:time_deployment_start_origin = "TimeFirstInPos";
:time_deployment_end = "2011-08-31T13:30:00Z";
:time_deployment_end_origin = "TimeLastInPos";
:time_coverage_start = "2011-06-16T23:00:00Z";
:time_coverage_end = "2011-09-02T13:00:00Z";
:data_centre = "eMarine Information Infrastructure (eMII)";
:data_centre_email = "info@emii.org.au";
:author_email = "t.austin@unsw.edu.au";
:author = "Austin, Tim";
:principal_investigator = "Roughan, Moninya";
:principal_investigator_email = "mroughan@unsw.edu.au";
:institution_references = "http://www.imos.org.au/emii.html";
:citation = "The citation in a list of references is: \"IMOS [year-of-data-download], [Title], [data-access-url], accessed [date-
```

of-access]\"";
:acknowledgement = "Any users of IMOS data (including re-packagers) are required to clearly acknowledge the source of

:acknowledgement = "Any users of IMOS data (including re-packagers) are required to clearly acknowledge the source of the material in this format: \"Data was sourced from the Integrated Marine Observing System (IMOS) - IMOS is supported by the Australian Government through the National Collaborative Research Infrastructure Strategy and the Super Science Initiative\".";

:use_limitation = "Data, products and services from IMOS are provided \"as is\" without any warranty as to fitness for a particular purpose.";

```
:license = "http://creativecommons.org/licenses/by/4.0/"
```

}

Version 1.4 – July 2015

APPENDIX 2: IMOS TOOLBOX OPTIONAL GLOBAL **ATTRIBUTES**

The IMOS-Toolbox has been developed by the Australian National Mooring Network, supported by IMOS and the eMarine Information Infrastructure. It is written in MATLAB and Java with a graphical user interface and aims at converting oceanographic data files into pre-processed and quality controlled netCDF files. This IMOS toolbox is freely available in a standalone executable with its source code. More documentation and downloads can be found on the imos-toolbox GitHub page. When correctly configured, this toolbox automatically documents these optional global attributes:

Non-CF attribute

Name	Туре	Example	Definition
What			
toolbox_input_file	S	toolbox_input_file =	Full local path and filename of
		"E:\Documents and	the original data file processed
		Settings\ggalibert\My	by the toolbox.
		Documents\IMOS_toolbox	
		\data_files_examples\NS	
		W\DATA\MOORINGS\SY	
		D100\RAW\021_SYD100_	
		15Dec2010\WQM\ASCII\	
		WQM0141_031.DAT"	
toolbox_version	S	toolbox_version = "2.1b"	Version of the toolbox used to
			process data.

deployment_code	S	deployment_code =	Deployment unique code
dopieyment_sede		"NRSMAI-0807"	within IMOS project, usually
	İ	TATACIVII AI OOOT	composed of a site_code and
	İ		a date information in format
	İ		
	Ì		YYMM or YYMMDD. Its
	Ì		content can be adapted to
	Ì		what suits best any particular
	İ		needs of a facility. A
	Ì		deployment refers to a specific
	Ì		time period over which a
	Ì		specific platform (e.g.
	ſ		mooring) is continuously
	İ		collecting measurements at a
	ſ		specific location.
	İ		
instrument_sample_int	N	instrument_sample_interv	Sampling interval in seconds
erval	İ	al = 1	performed by the instrument
	İ		on this data set.
instrument_beam_angl	N	instrument_beam_angle =	Angle between a transducer
е	İ	25	beam's main axis and the
	İ		vertical axis of the ADCP.
instrument_burst_interv	N	instrument_burst_interval	Interval in seconds between
al	İ	= 900	two bursts of data collection
	İ		performed by the instrument
	Ì		on this data set. Note that not
	İ		all instruments are sampling
	Ì		data in bursts.
instrument_burst_durat	N	instrument_burst_duration	Duration in seconds of a burst.
ion	1	= 120	Note that not all instruments
1.5	ſ	0	are sampling data in bursts.
cruise	S	cruise = "125456"	Reference to the cruise during
cruise	١	Gruise - 120400	
	ſ		which the dataset was
		4.11	collected.
station	S	station = "1"	Reference to the station where
	ſ		the dataset (cast) was
			collected.
Where			

Non-CF attribute

instrument_nominal_dept	N	instrument_nominal_depth	Instrument nominal depth
h		= 90	below sea surface in metres.
instrument_nominal_heig	N	instrument nominal_height	Instrument nominal depth
ht		= 0	above sea floor in metres.
site_nominal_depth	Ν	site_nominal_depth = 90	Site nominal depth below sea
			surface in metres.
site_depth_at_deploymen	N	site_depth_at_deployment	Measured depth on site at
t		= 84	deployment in metres.
When			
			0
time_deployment_start	S	time_deployment_start =	Start date in UTC when the
		"2008-11-23T10:16:00Z"	instrument is deployed in its
			nominal position. See section
			3.2.4 - on time format.
time_deployment_start	S	time_deployment_start_ori	Origin of
_origin		gin = "TimeFirstInPos"	time_deployment_start. Can
			be:
			TimeFirstGoodData
			T: E: 4 B
			TimeFirstInPos
			TimeFirstWet
			1111101 112111101
			TimeSwitchOn
time_deployment_end	S	time_deployment_end =	Final date in UTC when the
		"2009-01-06T09:43:00Z"	instrument is retrieved from its
			nominal position. See section
			3.2.4 - on time format.
			J.Z.+ - UII IIIIIG IUIIIIal.

Non-CF attribute

time_deployment_end_	S	time_deployment_end_ori	Origin of
origin		gin = "TimeLastInPos"	time_deployment_end. Can be
			:
			TimeLastGoodData
			TimeLastInPos
			TimeOnDeck
			TimeSwitchOff

APPENDIX 3: IMOS FILE NAMING CONVENTION