

# Structures and All That

September 24, 2019

“Here at Brymar College  
We can get you prepared for the 31st century  
With advanced programming and quad rendering  
And Java plus plus plus scripting language  
We offer advanced job placement assistance”  
from Upgrade by Deltron 3030

## Data Descriptions Matter

We have taken a weird approach by fixating on data structured in the form of “or” first.

## Data Descriptions Matter

We have taken a weird approach by fixating on data structured in the form of “or” first.

- We would say that a traffic light's state is red **or** yellow **or** green. I will sometimes refer to data in this form as defining a *sum type*, but for now I will stick to saying itemization.

## Data Descriptions Matter

We have taken a weird approach by fixating on data structured in the form of “or” first.

- We would say that a traffic light's state is red **or** yellow **or** green. I will sometimes refer to data in this form as defining a *sum type*, but for now I will stick to saying itemization.
- But tons of data is written in a compound manner. A person has a head **and** a face **and** a body ... I will sometimes refer to data in this form as being a *product type*, but will usually stick to saying *struct*. When I talk about classes, I will be talking about more than compound data.

## Data Descriptions Matter

We have taken a weird approach by fixating on data structured in the form of “or” first.

- We would say that a traffic light’s state is red **or** yellow **or** green. I will sometimes refer to data in this form as defining a *sum type*, but for now I will stick to saying itemization.
- But tons of data is written in a compound manner. A person has a head **and** a face **and** a body ... I will sometimes refer to data in this form as being a *product type*, but will usually stick to saying *struct*. When I talk about classes, I will be talking about more than compound data.
- Whereas with “or” we would check which kind of data we would have and then use a computation specific to that data, with products we can directly project out data.

## Data Descriptions Matter

We have taken a weird approach by fixating on data structured in the form of “or” first.

- We would say that a traffic light's state is red **or** yellow **or** green. I will sometimes refer to data in this form as defining a *sum type*, but for now I will stick to saying itemization.
- But tons of data is written in a compound manner. A person has a head **and** a face **and** a body ... I will sometimes refer to data in this form as being a *product type*, but will usually stick to saying *struct*. When I talk about classes, I will be talking about more than compound data.
- Whereas with “or” we would check which kind of data we would have and then use a computation specific to that data, with products we can directly project out data.
- Let's say that in Java that you have some person class with a first and last name represented as strings.

## Data Descriptions Matter

We have taken a weird approach by fixating on data structured in the form of “or” first.

- We would say that a traffic light's state is red **or** yellow **or** green. I will sometimes refer to data in this form as defining a *sum type*, but for now I will stick to saying itemization.
- But tons of data is written in a compound manner. A person has a head **and** a face **and** a body ... I will sometimes refer to data in this form as being a *product type*, but will usually stick to saying *struct*. When I talk about classes, I will be talking about more than compound data.
- Whereas with “or” we would check which kind of data we would have and then use a computation specific to that data, with products we can directly project out data.
- Let's say that in Java that you have some person class with a first and last name represented as strings.
- It is easy to define a method that returns the person's full name by concatenating the first and last name.



## Who Needs Structs Anyway?

So, why do we need compound data?

## Who Needs Structs Anyway?

So, why do we need compound data?

- The obvious answer is that we have programs that have some kind of compound state.

## Who Needs Structs Anyway?

So, why do we need compound data?

- The obvious answer is that we have programs that have some kind of compound state.
- Consider the simple program where we wanted to move a dot left and right.

## Who Needs Structs Anyway?

So, why do we need compound data?

- The obvious answer is that we have programs that have some kind of compound state.
- Consider the simple program where we wanted to move a dot left and right.
- We were able to represent the state of the world as a single position number.

## Who Needs Structs Anyway?

So, why do we need compound data?

- The obvious answer is that we have programs that have some kind of compound state.
- Consider the simple program where we wanted to move a dot left and right.
- We were able to represent the state of the world as a single position number.
- Let's add another dimension of movement where we can now move the dot up and down.

## Who Needs Structs Anyway?

So, why do we need compound data?

- The obvious answer is that we have programs that have some kind of compound state.
- Consider the simple program where we wanted to move a dot left and right.
- We were able to represent the state of the world as a single position number.
- Let's add another dimension of movement where we can now move the dot up and down.
- Can we represent the state of the world as a single number?

## Who Needs Structs Anyway?

So, why do we need compound data?

- The obvious answer is that we have programs that have some kind of compound state.
- Consider the simple program where we wanted to move a dot left and right.
- We were able to represent the state of the world as a single position number.
- Let's add another dimension of movement where we can now move the dot up and down.
- Can we represent the state of the world as a single number?
- If you said no, I get it! But that happens to be incorrect.

## Who Needs Structs Anyway?

So, why do we need compound data?

- The obvious answer is that we have programs that have some kind of compound state.
- Consider the simple program where we wanted to move a dot left and right.
- We were able to represent the state of the world as a single position number.
- Let's add another dimension of movement where we can now move the dot up and down.
- Can we represent the state of the world as a single number?
- If you said no, I get it! But that happens to be incorrect.
- We can represent a grid with one number in the same sense that we can simulate a 10x10 2D array with a 100 element array.



# Structs Make Things Easier

Personally, I like doing things the easy way.



# Unstructured Compound Data?

We can actually represent compound data without needing to provide names for the individual pieces of data.

## Unstructured Compound Data?

We can actually represent compound data without needing to provide names for the individual pieces of data.

- Let's consider some individual examples in Python.

# Unstructured Compound Data?

We can actually represent compound data without needing to provide names for the individual pieces of data.

- Let's consider some individual examples in Python.
- We can represent a Person with a first name, last name, and age with the following kind of tuple:

## Unstructured Compound Data?

We can actually represent compound data without needing to provide names for the individual pieces of data.

- Let's consider some individual examples in Python.
- We can represent a Person with a first name, last name, and age with the following kind of tuple:
- ("Peter", "Campora", 26)

## Unstructured Compound Data?

We can actually represent compound data without needing to provide names for the individual pieces of data.

- Let's consider some individual examples in Python.
- We can represent a Person with a first name, last name, and age with the following kind of tuple:
- ("Peter", "Campora", 26)
- We could then define functions to act like field accesses.

## Unstructured Compound Data?

We can actually represent compound data without needing to provide names for the individual pieces of data.

- Let's consider some individual examples in Python.
- We can represent a Person with a first name, last name, and age with the following kind of tuple:
- ("Peter", "Campora", 26)
- We could then define functions to act like field accesses.

```
def first_name(tup):  
    return tup[0]
```

-

# Data (Un)Structures

We can actually define other data structures in terms of things like lists.



# Data (Un)Structures

We can actually define other data structures in terms of things like lists.

- Let's consider defining a binary tree in terms of a python list.

# Data (Un)Structures

We can actually define other data structures in terms of things like lists.

- Let's consider defining a binary tree in terms of a python list.
- We can define a null node with []

# Data (Un)Structures

We can actually define other data structures in terms of things like lists.

- Let's consider defining a binary tree in terms of a python list.
- We can define a null node with []
- A tree with a single root element can be [ [] 1 [] ]

# Data (Un)Structures

We can actually define other data structures in terms of things like lists.

- Let's consider defining a binary tree in terms of a python list.
- We can define a null node with `[]`
- A tree with a single root element can be `[[] 1 []]`
- Here's a nice balanced tree `[[[] 1 []] 2 [[] 3 []]]`

# Data (Un)Structures

We can actually define other data structures in terms of things like lists.

- Let's consider defining a binary tree in terms of a python list.
- We can define a null node with `[]`
- A tree with a single root element can be `[[] 1 []]`
- Here's a nice balanced tree `[[], 1, [], 2, [], 3, []]`
- This representation gets a bit ugly fast, huh?

# Data (Un)Structures

We can actually define other data structures in terms of things like lists.

- Let's consider defining a binary tree in terms of a python list.
- We can define a null node with `[]`
- A tree with a single root element can be `[[] 1 []]`
- Here's a nice balanced tree `[[[] 1 []] 2 [[] 3 []]]`
- This representation gets a bit ugly fast, huh?
- So Python gives classes (or named tuples) as a way to more easily define such structured data.

## Unstructured Data in Racket

Similarly, we can define data using pairs and lists in Racket.

## Unstructured Data in Racket

Similarly, we can define data using pairs and lists in Racket.

- We can write a pair (1,2) as (1 . 2).



## Unstructured Data in Racket

Similarly, we can define data using pairs and lists in Racket.

- We can write a pair (1, 2) as (1 . 2).
- We can write a linked list 1-2-3-4-empty as '(1 2 3 4)

## Unstructured Data in Racket

Similarly, we can define data using pairs and lists in Racket.

- We can write a pair (1,2) as (1 . 2).
- We can write a linked list 1- $\hookrightarrow$ 2- $\hookrightarrow$ 3- $\hookrightarrow$ 4- $\hookrightarrow$ empty as '(1 2 3 4)
- To get the first element in the linked list, you can write:  
`(first '(1 2 3 4))`  $\hookrightarrow$  1

## Unstructured Data in Racket

Similarly, we can define data using pairs and lists in Racket.

- We can write a pair  $(1, 2)$  as  $(1 \ . \ 2)$ .
- We can write a linked list  $1 \rightarrow 2 \rightarrow 3 \rightarrow 4 \rightarrow \text{empty}$  as  $'(1 \ 2 \ 3 \ 4)$
- To get the first element in the linked list, you can write:  
 $(\text{first } '(1 \ 2 \ 3 \ 4)) \hookrightarrow 1$
- To get the rest of the linked list you can write  
 $(\text{rest } '(1 \ 2 \ 3 \ 4)) \hookrightarrow '(2 \ 3 \ 4)$

## Unstructured Data in Racket

Similarly, we can define data using pairs and lists in Racket.

- We can write a pair (1,2) as (1 . 2).
- We can write a linked list 1-2-3-4-empty as '(1 2 3 4)
- To get the first element in the linked list, you can write:  
`(first '(1 2 3 4))`  $\hookrightarrow$  1
- To get the rest of the linked list you can write  
`(rest '(1 2 3 4))`  $\hookrightarrow$  '(2 3 4)
- The empty list is represented with '() and you can check for the empty list with `(empty? '())`  $\hookrightarrow$  \#t

## Unstructured Data in Racket

Similarly, we can define data using pairs and lists in Racket.

- We can write a pair (1, 2) as (1 . 2).
- We can write a linked list 1- $\hookrightarrow$ 2- $\hookrightarrow$ 3- $\hookrightarrow$ 4- $\hookrightarrow$ empty as '(1 2 3 4)
- To get the first element in the linked list, you can write:  
(first '(1 2 3 4))  $\hookrightarrow$  1
- To get the rest of the linked list you can write  
(rest '(1 2 3 4))  $\hookrightarrow$  '(2 3 4)
- The empty list is represented with '() and you can check for the empty list with (empty? '())  $\hookrightarrow$  \#t
- We will return to discussing lists in more detail later, since they are *extremely* important.

## Unstructured Data in Racket

Similarly, we can define data using pairs and lists in Racket.

- We can write a pair (1, 2) as (1 . 2).
- We can write a linked list 1- $\hookrightarrow$ 2- $\hookrightarrow$ 3- $\hookrightarrow$ 4- $\hookrightarrow$ empty as '(1 2 3 4)
- To get the first element in the linked list, you can write:  
`(first '(1 2 3 4))  $\hookrightarrow$  1`
- To get the rest of the linked list you can write  
`(rest '(1 2 3 4))  $\hookrightarrow$  '(2 3 4)`
- The empty list is represented with '() and you can check for the empty list with `(empty? '())  $\hookrightarrow$  \#t`
- We will return to discussing lists in more detail later, since they are *extremely* important.
- But for now, remember that we wanted to avoid the inconveniences given by using other existing data types to represent some piece of compound data!

# The Talk

We said that we didn't want to represent all of our compound data with existing structures like lists or tuples, so let's *finally* talk about structs.

# The Talk

We said that we didn't want to represent all of our compound data with existing structures like lists or tuples, so let's *finally* talk about structs.

- Let's reconsider our 2 dimensional movement program.



# The Talk

We said that we didn't want to represent all of our compound data with existing structures like lists and tuples, so let's *finally* talk about structs.

- Let's reconsider our 2 dimensional movement program.
- We need a natural representation for cartesian coordinates for the state of our world.

# The Talk

We said that we didn't want to represent all of our compound data with existing structures like lists or tuples, so let's *finally* talk about structs.

- Let's reconsider our 2 dimensional movement program.
- We need a natural representation for cartesian coordinates for the state of our world.
- We could obviously have the state of our world be a pair '(x . y)' or a list '(x y)

## The Talk

We said that we didn't want to represent all of our compound data with existing structures like lists or tuples, so let's *finally* talk about structs.

- Let's reconsider our 2 dimensional movement program.
- We need a natural representation for cartesian coordinates for the state of our world.
- We could obviously have the state of our world be a pair '(x . y)' or a list '(x y)
- But it would be better if we had piece of compound data with two fields, one field named x to represent the x coordinate and similarly a y...

# The Talk

We said that we didn't want to represent all of our compound data with existing structures like lists or tuples, so let's *finally* talk about structs.

- Let's reconsider our 2 dimensional movement program.
- We need a natural representation for cartesian coordinates for the state of our world.
- We could obviously have the state of our world be a pair '(x . y)' or a list '(x y)'
- But it would be better if we had piece of compound data with two fields, one field named x to represent the x coordinate and similarly a y...
- To define the struct: (`struct` point [x y])

# The Talk

We said that we didn't want to represent all of our compound data with existing structures like lists or tuples, so let's *finally* talk about structs.

- Let's reconsider our 2 dimensional movement program.
- We need a natural representation for cartesian coordinates for the state of our world.
- We could obviously have the state of our world be a pair '(x . y)' or a list '(x y)
- But it would be better if we had piece of compound data with two fields, one field named x to represent the x coordinate and similarly a y...
- To define the struct: (struct point [x y])
- To make a new point: (define one-two (point 1 2))

# The Talk

We said that we didn't want to represent all of our compound data with existing structures like lists or tuples, so let's *finally* talk about structs.

- Let's reconsider our 2 dimensional movement program.
- We need a natural representation for cartesian coordinates for the state of our world.
- We could obviously have the state of our world be a pair '(x . y)' or a list '(x y)'
- But it would be better if we had piece of compound data with two fields, one field named x to represent the x coordinate and similarly a y...
- To define the struct: (struct point [x y])
- To make a new point: (define one-two (point 1 2))
- To get the x-coordinate: (point-x one-two)

## Writing Simple Programs With Structs

Before we consider writing more complex applications involving structs, let's consider writing a simple function.

## Writing Simple Programs With Structs

Before we consider writing more complex applications involving structs, let's consider writing a simple function.

- Let's consider computing the distance to the origin where we take in one parameter that is a point, instead of taking two parameters for an x-coordinate and y-coordinate.



## Writing Simple Programs With Structs

Before we consider writing more complex applications involving structs, let's consider writing a simple function.

- Let's consider computing the distance to the origin where we take in one parameter that is a point, instead of taking two parameters for an x-coordinate and y-coordinate.
- As will happen many times in this course, we will introduce the concept by examples before we cover how our design recipes change to address this new feature

## Writing Simple Programs With Structs

Before we consider writing more complex applications involving structs, let's consider writing a simple function.

- Let's consider computing the distance to the origin where we take in one parameter that is a point, instead of taking two parameters for an x-coordinate and y-coordinate.
- As will happen many times in this course, we will introduce the concept by examples before we cover how our design recipes change to address this new feature

```
;;Point -> Number
```

```
;;Compute a point's distance from the origin
```

```
(define (distance-point posn) 0)
```

-

## Writing Simple Programs With Structs

Before we consider writing more complex applications involving structs, let's consider writing a simple function.

- Let's consider computing the distance to the origin where we take in one parameter that is a point, instead of taking two parameters for an x-coordinate and y-coordinate.
- As will happen many times in this course, we will introduce the concept by examples before we cover how our design recipes change to address this new feature

```
;;Point -> Number
```

```
;;Compute a point's distance from the origin
```

```
(define (distance-point posn) 0)
```

- 
- Let's add functional examples as tests:

## Writing Simple Programs With Structs

Before we consider writing more complex applications involving structs, let's consider writing a simple function.

- Let's consider computing the distance to the origin where we take in one parameter that is a point, instead of taking two parameters for an x-coordinate and y-coordinate.
- As will happen many times in this course, we will introduce the concept by examples before we cover how our design recipes change to address this new feature

```
;;Point -> Number  
;;Compute a point's distance from the origin  
(define (distance-point posn) 0)
```

- 
- Let's add functional examples as tests:  
(check-expect (distance-to-0 (point 0 5)) 5)  
(check-expect (distance-to-0 (point 7 0)) 7)



## Structs and Skeletons

We now can take inventory (step 4) and add a skeleton for our function. In this case we should know that we have to project out the x-coordinate and the y-coordinate in our distance function.

## Structs and Skeletons

We now can take inventory (step 4) and add a skeleton for our function. In this case we should know that we have to project out the x-coordinate and the y-coordinate in our distance function.

```
(define (distance-to-0 ap)
  (... (posn-x ap) ...
        (... (posn-y ap) ...)))
```



## Structs and Skeletons

We now can take inventory (step 4) and add a skeleton for our function. In this case we should know that we have to project out the x-coordinate and the y-coordinate in our distance function.

```
(define (distance-to-0 ap)
  (... (posn-x ap) ...
        (... (posn-y ap) ...)))
```

- 
- To code, we essentially have the same logic as when we had a previous version of this function that took in two parameters. Now, we just use the projected out x-coordinate and y-coordinate from our point.

## Structs and Skeletons

We now can take inventory (step 4) and add a skeleton for our function. In this case we should know that we have to project out the x-coordinate and the y-coordinate in our distance function.

```
(define (distance-to-0 ap)
  (... (posn-x ap) ...
        ... (posn-y ap) ...))
```

- 
- To code, we essentially have the same logic as when we had a previous version of this function that took in two parameters. Now, we just use the projected out x-coordinate and y-coordinate from our point.

```
(define (distance-to-0 ap)
  (sqrt
   (+ (sqr (posn-x ap))
      (sqr (posn-y ap))))))
```





## Structs in General

Testing that function is simple, so let's just move on to talking about structs in general.

## Structs in General

Testing that function is simple, so let's just move on to talking about structs in general.

- You can define a struct in general with:  
(**struct** s-name [field-name-1 ...field-name-n])

## Structs in General

Testing that function is simple, so let's just move on to talking about structs in general.

- You can define a struct in general with:  
`(struct s-name [field-name-1 ...field-name-n])`
- After creating a struct, 3 kinds of functions are automatically made for you.

## Structs in General

Testing that function is simple, so let's just move on to talking about structs in general.

- You can define a struct in general with:  
`(struct s-name [field-name-1 ...field-name-n])`
- After creating a struct, 3 kinds of functions are automatically made for you.
  1. One constructor, a function that creates structure instances. It takes as many values as there are fields; as mentioned, structure is short for structure instance. The phrase structure type is a generic name for the collection of all possible instances;

## Structs in General

Testing that function is simple, so let's just move on to talking about structs in general.

- You can define a struct in general with:  
`(struct s-name [field-name-1 ...field-name-n])`
- After creating a struct, 3 kinds of functions are automatically made for you.
  1. One constructor, a function that creates structure instances. It takes as many values as there are fields; as mentioned, structure is short for structure instance. The phrase structure type is a generic name for the collection of all possible instances;
  2. One selector per field, which extracts the value of the field from a structure instance; and

## Structs in General

Testing that function is simple, so let's just move on to talking about structs in general.

- You can define a struct in general with:  
`(struct s-name [field-name-1 ...field-name-n])`
- After creating a struct, 3 kinds of functions are automatically made for you.
  1. One constructor, a function that creates structure instances. It takes as many values as there are fields; as mentioned, structure is short for structure instance. The phrase structure type is a generic name for the collection of all possible instances;
  2. One selector per field, which extracts the value of the field from a structure instance; and
  3. One structure predicate, which, like ordinary predicates, distinguishes instances from all other kinds of values.

## Basic Struct Options

Let's illustrate each of these three kinds of functions, with our point struct.

## Basic Struct Options

Let's illustrate each of these three kinds of functions, with our point struct.

1. The constructor is: `(point x-val y-val)` where `x-val` and `y-val` will be values passed to the `x-field` and `y-field` in our point struct. The general form is `(struct-name field-name-1-arg ... field-name-n-arg)`



## Basic Struct Options

Let's illustrate each of these three kinds of functions, with our point struct.

1. The constructor is: `(point x-val y-val)` where `x-val` and `y-val` will be values passed to the `x-field` and `y-field` in our point struct. The general form is `(struct-name field-name-1-arg ... field-name-n-arg)`
2. The selectors per field are `(point-x point-val)` and `(point-y point-val)`. The general form of a selector for a specific field is `(struct-name-field-name val)`

## Basic Struct Options

Let's illustrate each of these three kinds of functions, with our point struct.

1. The constructor is: `(point x-val y-val)` where `x-val` and `y-val` will be values passed to the `x-field` and `y-field` in our point struct. The general form is `(struct-name field-name-1-arg ... field-name-n-arg)`
2. The selectors per field are `(point-x point-val)` and `(point-y point-val)`. The general form of a selector for a specific field is `(struct-name-field-name val)`
3. A predicate for checking types is automatically created, for example: `(point? point-val)` and in general a predicate `struct?` is created.

# Examples of Structs

Here are some basic examples of structs:

## Examples of Structs

Here are some basic examples of structs:

- (`struct` movie [title producer year])

**Sample Problem** Develop a structure type definition for a program that deals with bouncing balls,. The balls location is a single number, namely the distance of pixels from the top. Its constant speed is the number of pixels it moves per clock tick. Its velocity is the speed plus the direction in which it moves.

## Examples of Structs

Here are some basic examples of structs:

- (`struct` movie [title producer year])
- (`struct` person [name hair eyes phone])

**Sample Problem** Develop a structure type definition for a program that deals with bouncing balls,. The balls location is a single number, namely the distance of pixels from the top. Its constant speed is the number of pixels it moves per clock tick. Its velocity is the speed plus the direction in which it moves.

## Examples of Structs

Here are some basic examples of structs:

- (`struct` movie [title producer year])
- (`struct` person [name hair eyes phone])
- You guys should be able to think of many more examples.

**Sample Problem** Develop a structure type definition for a program that deals with bouncing balls,. The balls location is a single number, namely the distance of pixels from the top. Its constant speed is the number of pixels it moves per clock tick. Its velocity is the speed plus the direction in which it moves.

## Designing Our Ball Struct

Since we are talking about a ball that bounces up and down, our structure definition is pretty simple. We need a single number for the y position and single number for the velocity in the y-axis.

## Designing Our Ball Struct

Since we are talking about a ball that bounces up and down, our structure definition is pretty simple. We need a single number for the y position and single number for the velocity in the y-axis.

- `(struct ball [location vec])`



## Designing Our Ball Struct

Since we are talking about a ball that bounces up and down, our structure definition is pretty simple. We need a single number for the y position and single number for the velocity in the y-axis.

- `(struct ball [location vec])`
- This is simple because our ball is moving in a single direction. But if we had a Brick Breaker esque game then we would have a bouncing ball that travels along a 2D plane, then our definition is much more complicated.

## Designing Our Ball Struct

Since we are talking about a ball that bounces up and down, our structure definition is pretty simple. We need a single number for the y position and single number for the velocity in the y-axis.

- `(struct ball [location vec])`
- This is simple because our ball is moving in a single direction. But if we had a Brick Breaker esque game then we would have a bouncing ball that travels along a 2D plane, then our definition is much more complicated.
- Let's first consider defining a 2D vector struct as follows:  
`(struct vector [delta-x delta-y])`

## Designing Our Ball Struct

Since we are talking about a ball that bounces up and down, our structure definition is pretty simple. We need a single number for the y position and single number for the velocity in the y-axis.

- (`struct` ball [location vec])
- This is simple because our ball is moving in a single direction. But if we had a Brick Breaker esque game then we would have a bouncing ball that travels along a 2D plane, then our definition is much more complicated.
- Let's first consider defining a 2D vector struct as follows:  
(`struct` vector [delta-x delta-y])
- Now, we can represent a ball as a point (which only has positive components) and a vector (which can have negative components): (`struct` 2D-ball position vec)

## Other Representations

Our 2D Ball struct has nested occurrences of other structs. This is a natural thing, and even recursive descriptions of data are natural, i.e. linked lists and binary trees. But we can also consider using a *flat representation* for our 2D Ball, which doesn't nest structs.

## Other Representations

Our 2D Ball struct has nested occurrences of other structs. This is a natural thing, and even recursive descriptions of data are natural, i.e. linked lists and binary trees. But we can also consider using a *flat representation* for our 2D Ball, which doesn't nest structs.

- (`struct` 2D-ball [x y delta-x delta-y])

## Other Representations

Our 2D Ball struct has nested occurrences of other structs. This is a natural thing, and even recursive descriptions of data are natural, i.e. linked lists and binary trees. But we can also consider using a *flat representation* for our 2D Ball, which doesn't nest structs.

- `(struct 2D-ball [x y delta-x delta-y]`
- Although valid, I think it's better to keep representations natural and just nest things, barring performance concerns.

## Other Representations

Our 2D Ball struct has nested occurrences of other structs. This is a natural thing, and even recursive descriptions of data are natural, i.e. linked lists and binary trees. But we can also consider using a *flat representation* for our 2D Ball, which doesn't nest structs.

- (`struct` 2D-ball [x y delta-x delta-y]
- Although valid, I think it's better to keep representations natural and just nest things, barring performance concerns.
- Let's talk about defining data definitions for structs. We must specify the form of the struct and the types of its field and provide an interpretation of what each of the fields represents. Here's how we do this for our point struct:

## Other Representations

Our 2D Ball struct has nested occurrences of other structs. This is a natural thing, and even recursive descriptions of data are natural, i.e. linked lists and binary trees. But we can also consider using a *flat representation* for our 2D Ball, which doesn't nest structs.

- (`struct` 2D-ball [x y delta-x delta-y])
- Although valid, I think it's better to keep representations natural and just nest things, barring performance concerns.
- Let's talk about defining data definitions for structs. We must specify the form of the struct and the types of its field and provide an interpretation of what each of the fields represents. Here's how we do this for our point struct:

```
(define-struct point [x y])
; A Point is a structure:
;   (point Number Number)
; interpretation a point x pixels from left, y from top
```





## Structs and Program Design

Now we need to consider designing programs using structs.

**Sample Problem** Your team is designing an interactive game program that moves a red dot across a image canvas and allows players to use the mouse to reset the dot. Here is how far you got together:

## Structs and Program Design

Now we need to consider designing programs using structs.

**Sample Problem** Your team is designing an interactive game program that moves a red dot across a image canvas and allows players to use the mouse to reset the dot. Here is how far you got together:

```
(define MTS (empty-scene 100 100))  
(define DOT (circle 3 "solid" "red"))
```

*; A Point represents the state of the world.*

*; Point -> Point*

```
(define (main p0)  
  (big-bang p0  
    [on-tick x+]  
    [on-mouse reset-dot]  
    [to-draw scene+dot]))
```

## Designing scene+dot

Let us first assume that you're tasked with designing scene+dot.

## Designing scene+dot

Let us first assume that you're tasked with designing scene+dot.

- Of course, we already have our data interpretation so we start with step 2 and provide our signature, statement of purpose, and function header.

## Designing scene+dot

Let us first assume that you're tasked with designing scene+dot.

- Of course, we already have our data interpretation so we start with step 2 and provide our signature, statement of purpose, and function header.

```
; Point -> Image
```

```
; adds a red spot to MTS at p
```

```
(define (scene+dot p) MTS)
```

-

## Designing scene+dot

Let us first assume that you're tasked with designing scene+dot.

- Of course, we already have our data interpretation so we start with step 2 and provide our signature, statement of purpose, and function header.

```
; Point -> Image  
; adds a red spot to MTS at p  
(define (scene+dot p) MTS)
```

- 
- Finishing step 3 and creating the following functional examples (as tests) is straightforward:

## Designing scene+dot

Let us first assume that you're tasked with designing scene+dot.

- Of course, we already have our data interpretation so we start with step 2 and provide our signature, statement of purpose, and function header.

```
; Point -> Image
; adds a red spot to MTS at p
(define (scene+dot p) MTS)
```

- Finishing step 3 and creating the following functional examples (as tests) is straightforward:

```
(check-expect (scene+dot (make-posn 10 20))
               (place-image DOT 10 20 MTS))
(check-expect (scene+dot (make-posn 88 73))
               (place-image DOT 88 73 MTS))
```

## Designing scene+dot (cont.)

We can now move on to carrying out step 4 and taking inventory:



## Designing scene+dot (cont.)

We can now move on to carrying out step 4 and taking inventory:

```
(define (scene+dot p)  
  (... (point-x p) ... (point-y p) ...))
```



## Designing scene+dot (cont.)

We can now move on to carrying out step 4 and taking inventory:

```
(define (scene+dot p)  
  (... (point-x p) ... (point-y p) ...))
```

- 
- Finishing step 5 is easy, we simply need to place the projected x and y coordinates as arguments to place-image

## Designing scene+dot (cont.)

We can now move on to carrying out step 4 and taking inventory:

```
(define (scene+dot p)
  (... (point-x p) ... (point-y p) ...))
```

- 
- Finishing step 5 is easy, we simply need to place the projected x and y coordinates as arguments to place-image

```
(define (scene+dot p)
  (place-image DOT (point-x p) (point-y p) MTS))
```

-

## Designing scene+dot (cont.)

We can now move on to carrying out step 4 and taking inventory:

```
(define (scene+dot p)
  (... (point-x p) ... (point-y p) ...))
```

- 
- Finishing step 5 is easy, we simply need to place the projected x and y coordinates as arguments to place-image

```
(define (scene+dot p)
  (place-image DOT (point-x p) (point-y p) MTS))
```

- 
- Testing this is uninteresting, so let's consider if we were asked to define the x+ function, which takes in a Point and returns a new Point with an x-coordinate that is 3 units further to the right of the old point.

## Designing x+

Designing our `x+` function is a bit harder than `scene+dot`, because we are producing structures as output.

## Designing x+

Designing our x+ function is a bit harder than scene+dot, because we are producing structures as output.

- When carrying out step 2, recall that x+ handles clock ticks:

```
;;Point -> Point
```

```
;;Updates the position of our dot at each clock tick
```

```
(define (x+ p) p)
```

## Designing x+

Designing our x+ function is a bit harder than scene+dot, because we are producing structures as output.

- When carrying out step 2, recall that x+ handles clock ticks:

```
;;Point -> Point
```

```
;;Updates the position of our dot at each clock tick
```

```
(define (x+ p) p)
```

- Coming up with functional examples as tests is straightforward:

```
(check-expect (x+ (point 0 0)) (point 3 0))
```

```
(check-expect (x+ (point 10 10)) (point 13 10))
```

```
(check-expect (x+ (point 0 10)) (point 3 10))
```

## Designing x+

Designing our x+ function is a bit harder than scene+dot, because we are producing structures as output.

- When carrying out step 2, recall that x+ handles clock ticks:

```
;;Point -> Point
;;Updates the position of our dot at each clock tick
(define (x+ p) p)
```

- Coming up with functional examples as tests is straightforward:

```
(check-expect (x+ (point 0 0)) (point 3 0))
(check-expect (x+ (point 10 10)) (point 13 10))
(check-expect (x+ (point 0 10)) (point 3 10))
```

- To take inventory we project out the x and y fields from our point, as usual:

```
(define (x+ p) (... (point-x p) ... (point-y p) ...))
```



## Designing $x+$ (cont.)

To finish coding, we need to first add 3 to the x-coordinate and then pack the result back into a new point structure.

## Designing x+ (cont.)

To finish coding, we need to first add 3 to the x-coordinate and then pack the result back into a new point structure.

```
(define (x+ p)  
  (point (+ (point-x p) 3) (point-y p)))
```



## Designing x+ (cont.)

To finish coding, we need to first add 3 to the x-coordinate and then pack the result back into a new point structure.

```
(define (x+ p)
  (point (+ (point-x p) 3) (point-y p)))
```

- 
- This is a perfect example of the *essence* of functional programming. We are creating a *new* point whose x-coordinate is based on the old one, instead of modifying the original point to store a new x-coordinate.

## Designing x+ (cont.)

To finish coding, we need to first add 3 to the x-coordinate and then pack the result back into a new point structure.

```
(define (x+ p)
  (point (+ (point-x p) 3) (point-y p)))
```

- 
- This is a perfect example of the *essence* of functional programming. We are creating a *new* point whose x-coordinate is based on the old one, instead of modifying the original point to store a new x-coordinate.
- But there is something inelegant about this, right?

## Designing x+ (cont.)

To finish coding, we need to first add 3 to the x-coordinate and then pack the result back into a new point structure.

```
(define (x+ p)
  (point (+ (point-x p) 3) (point-y p)))
```

- 
- This is a perfect example of the *essence* of functional programming. We are creating a *new* point whose x-coordinate is based on the old one, instead of modifying the original point to store a new x-coordinate.
- But there is something inelegant about this, right?
- If we had more fields than y, we simply are projecting out the old field as an argument when creating the new struct value.

## Designing x+ (cont.)

To finish coding, we need to first add 3 to the x-coordinate and then pack the result back into a new point structure.

```
(define (x+ p)
  (point (+ (point-x p) 3) (point-y p)))
```

- 
- This is a perfect example of the *essence* of functional programming. We are creating a *new* point whose x-coordinate is based on the old one, instead of modifying the original point to store a new x-coordinate.
- But there is something inelegant about this, right?
- If we had more fields than y, we simply are projecting out the old field as an argument when creating the new struct value.
- This adds a lot of boilerplate code...

## Struct Boilerplate

We might want to define a function, `point-set-x` which takes in a point and a value and produces a new point where the x-coordinate is the given value and the y-coordinate is taken from the old point.

## Struct Boilerplate

We might want to define a function, `point-set-x` which takes in a point and a value and produces a new point where the x-coordinate is the given value and the y-coordinate is taken from the old point.

- Here is the code:

```
(define (point-set-x p x)
  (point x (point-y p)))
```



## Struct Boilerplate

We might want to define a function, `point-set-x` which takes in a point and a value and produces a new point where the x-coordinate is the given value and the y-coordinate is taken from the old point.

- Here is the code:

```
(define (point-set-x p x)
  (point x (point-y p)))
```

- We can now redefine `x+` with it:

```
(define (x+ p)
  (point-set-x p (+ (point-x p) 3)))
```

## Struct Boilerplate

We might want to define a function, `point-set-x` which takes in a point and a value and produces a new point where the x-coordinate is the given value and the y-coordinate is taken from the old point.

- Here is the code:

```
(define (point-set-x p x)
  (point x (point-y p)))
```

- We can now redefine `x+` with it:

```
(define (x+ p)
  (point-set-x p (+ (point-x p) 3)))
```

- `point-set-x` is known as a *functional setter*, similar to a more traditional setter in languages like Java.

## Struct Boilerplate

We might want to define a function, `point-set-x` which takes in a point and a value and produces a new point where the x-coordinate is the given value and the y-coordinate is taken from the old point.

- Here is the code:

```
(define (point-set-x p x)
  (point x (point-y p)))
```

- We can now redefine `x+` with it:

```
(define (x+ p)
  (point-set-x p (+ (point-x p) 3)))
```

- `point-set-x` is known as a *functional setter*, similar to a more traditional setter in languages like Java.
- However, defining an update operation on a complicated structure can get very complicated, and we can get around this using *lenses* (we may discuss this later in the course).