

Willy Wonka's Candy Factory API Documentation

Overview

Overview

This document outlines the necessary API endpoints for integrating with Willy Wonka's Candy Factory's custom Order Management System (OMS). The endpoints will facilitate querying customer information, retrieving order details, updating order statuses, and canceling orders.

Authentication

All requests to the Willy Wonka's Candy Factory API must include an API key in the header for authentication.

Header:

Authorization: Bearer YOUR_API_KEY

Willy Wonka's Candy Factory API Documentation

Endpoints

Endpoints

1. Get Customer Information

Retrieve customer information based on a specific field such as email, name, customer ID, or address.

Endpoint:

GET /api/customers

Parameters:

- email (optional, string): Email address of the customer.
- name (optional, string): Full name of the customer.
- customerId (optional, string): Unique identifier of the customer.
- address (optional, string): Address of the customer.

Response:

```
{  
  "customerId": "12345",  
  "name": "John Doe",  
  "email": "john.doe@example.com",  
  "phone": "+1234567890",  
  "address": {  
    "street": "123 Main St",
```

Willy Wonka's Candy Factory API Documentation

```
{
  "city": "Anytown",
  "state": "CA",
  "zip": "12345"
},
"orderHistory": [
  {
    "orderId": "abc123",
    "orderDate": "2023-06-15",
    "status": "Shipped",
    "total": 100.00
  }
]
}
```

2. Get Order Details

Retrieve details of a specific order, including fulfillment information such as tracking number.

Endpoint:

GET /api/orders/{orderId}

Path Parameters:

- orderId (required, string): The unique identifier of the order to retrieve.

Response:

Willy Wonka's Candy Factory API Documentation

```
{  
  "orderId": "def456",  
  "customerId": "12345",  
  "orderDate": "2023-07-15",  
  "status": "Shipped",  
  "items": [  
    {  
      "itemId": "item123",  
      "quantity": 2,  
      "price": 50.00  
    },  
    {  
      "itemId": "item456",  
      "quantity": 1,  
      "price": 50.00  
    }  
  ],  
  "shippingAddress": {  
    "street": "123 Main St",  
    "city": "Anytown",  
    "state": "CA",  
    "zip": "12345"  
  },  
  "fulfillment": {
```

Willy Wonka's Candy Factory API Documentation

```
"carrier": "UPS",  
"trackingNumber": "1Z999AA10123456789",  
"estimatedDeliveryDate": "2023-07-20"  
},  
"total": 150.00  
}
```

3. Update Order Status

Update the status of an existing order.

Endpoint:

PUT /api/orders/{orderId}/status

Path Parameters:

- orderId (required, string): The unique identifier of the order to update.

Request Body:

```
{  
  "status": "Shipped"  
}
```

Response:

```
{  
  "orderId": "def456",
```

Willy Wonka's Candy Factory API Documentation

```
"status": "Shipped",  
"updateDate": "2023-07-16"  
}
```

4. Cancel Order

Cancel an existing order.

Endpoint:

DELETE /api/orders/{orderId}

Path Parameters:

- orderId (required, string): The unique identifier of the order to cancel.

Response:

```
{  
  "orderId": "def456",  
  "status": "Canceled",  
  "updateDate": "2023-07-16"  
}
```

Willy Wonka's Candy Factory API Documentation

Error Handling

Error Handling

All endpoints should return appropriate HTTP status codes and error messages for various error conditions such as invalid parameters, unauthorized access, or resource not found.

Example Error Response:

```
{  
  "error": "Invalid API key",  
  "message": "The provided API key is invalid."  
}
```