

← Back To Course Home

Grokking the Coding Interview: Patterns for Coding Questions

15% completed

🔍 Search Course

Quadruple Sum to Target (medium)

Dutch National Flag Problem (medium)

Problem Challenge 1

Solution Review: Problem Challenge 1

Problem Challenge 2

# Solution Review: Problem Challenge 1

We'll cover the following

- Quadruple Sum to Target (medium)
- Solution
  - Code
  - Time complexity
  - Space complexity

## Quadruple Sum to Target (medium) #

Given an array of unsorted numbers and a target number, find all **unique quadruplets** in it, whose **sum is equal to the target number**.

Example 1:

```
Input: [4, 1, 2, -1, 1, -3], target=1
Output: [-3, -1, 1, 4], [-3, 1, 1, 2]
Explanation: Both the quadruplets add up to the target.
```

Example 2:

```
Input: [2, 0, -1, 1, -2, 2], target=2
Output: [-2, 0, 2, 2], [-1, 0, 1, 2]
Explanation: Both the quadruplets add up to the target.
```

## Solution #

This problem follows the **Two Pointers** pattern and shares similarities with [Triplet Sum to Zero](#).

We can follow a similar approach to iterate through the array, taking one number at a time. At every step during the iteration, we will search for the quadruplets similar to [Triplet Sum to Zero](#) whose sum is equal to the given target.

## Code #

Here is what our algorithm will look like:

JavaPython3C++JS

```
1 import java.util.*;
2
3 class QuadrupleSumToTarget {
4
5     public static List<List<Integer>> searchQuadruplets(int[] arr, int target) {
6         Arrays.sort(arr);
7         List<List<Integer>> quadruplets = new ArrayList<>();
8         for (int i = 0; i < arr.length - 3; i++) {
9             if (i > 0 && arr[i] == arr[i - 1]) // skip same element to avoid duplicate quadruplets
10                 continue;
11             for (int j = i + 1; j < arr.length - 2; j++) {
12                 if (j > i + 1 && arr[j] == arr[j - 1]) // skip same element to avoid duplicate quadruplets
13                     continue;
14                 searchPairs(arr, target, i, j, quadruplets);
15             }
16         }
17         return quadruplets;
18     }
19
20     private static void searchPairs(int[] arr, int targetSum, int first, int second, List<List<Integer>> quadruplets) {
21         int left = second + 1;
22         int right = arr.length - 1;
23         while (left < right) {
24             int sum = arr[first] + arr[second] + arr[left] + arr[right];
25             if (sum == targetSum) { // found the quadruplet
26                 quadruplets.add(Arrays.asList(arr[first], arr[second], arr[left], arr[right]));
27                 left++;
28                 right--;
```

RunSaveReset

## Time complexity #

Sorting the array will take  $O(N * \log N)$ . Overall `searchQuadruplets()` will take  $O(N * \log N + N^3)$ , which is asymptotically equivalent to  $O(N^3)$ .

## Space complexity #

The space complexity of the above algorithm will be  $O(N)$  which is required for sorting.

Want to work at Google, Facebook, or Amazon? Get hired faster with anonymous mock interviews conducted by senior engineers from those companies. Detailed feedback helps you prep. [See how](#)