

←

Back To Course Home

Grokking the Coding Interview: Patterns for Coding Questions

19% completed

Q

Search Course

Pattern: Fast & Slow pointers

●

 Introduction

○

 LinkedList Cycle (easy)

●

 Start of LinkedList Cycle (medium)

●

 Happy Number (medium)

●

 Middle of the LinkedList (easy)

○

 Problem Challenge 1

○

 Solution Review: Problem Challenge 1

○

 Problem Challenge 2

○

 Solution Review: Problem

Middle of the LinkedList (easy)

We'll cover the following

●

 Problem Statement

●

 Try it yourself

●

 Solution

●

 Code

●

 Time complexity

●

 Space complexity

Problem Statement#

Given the head of a **Singly LinkedList**, write a method to return the **middle node** of the LinkedList.

If the total number of nodes in the LinkedList is even, return the second middle node.

Example 1:

```
Input: 1 -> 2 -> 3 -> 4 -> 5 -> null
Output: 3
```

Example 2:

```
Input: 1 -> 2 -> 3 -> 4 -> 5 -> 6 -> null
Output: 4
```

Example 3:

```
Input: 1 -> 2 -> 3 -> 4 -> 5 -> 6 -> 7 -> null
Output: 4
```

Try it yourself#

Try solving this question here:

JavaPython3JS C++

```
5
6  ListNode(int value) {
7      this.value = value;
8  }
9  }
10
11 class MiddleOfLinkedList {
12
13     public static ListNode findMiddle(ListNode head) {
14         // TODO: Write your code here
15         return head;
16     }
17
18     public static void main(String[] args) {
19         ListNode head = new ListNode(1);
20         head.next = new ListNode(2);
21         head.next.next = new ListNode(3);
22         head.next.next.next = new ListNode(4);
23         head.next.next.next.next = new ListNode(5);
24         System.out.println("Middle Node: " + MiddleOfLinkedList.findMiddle(head).value);
25
26         head.next.next.next.next.next = new ListNode(6);
27         System.out.println("Middle Node: " + MiddleOfLinkedList.findMiddle(head).value);
28
29         head.next.next.next.next.next.next = new ListNode(7);
30         System.out.println("Middle Node: " + MiddleOfLinkedList.findMiddle(head).value);
31     }
32 }
```

Run

Save

Reset

Solution#

One brute force strategy could be to first count the number of nodes in the LinkedList and then find the middle node in the second iteration. Can we do this in one iteration?

We can use the **Fast & Slow pointers** method such that the fast pointer is always twice the nodes ahead of the slow pointer. This way, when the fast pointer reaches the end of the LinkedList, the slow pointer will be pointing at the middle node.

Code#

Here is what our algorithm will look like:

JavaPython3C++JS

```
1
2 class ListNode {
3     int value = 0;
4     ListNode next;
5
6     ListNode(int value) {
7         this.value = value;
8     }
9 }
10
11 class MiddleOfLinkedList {
12
13     public static ListNode findMiddle(ListNode head) {
14         ListNode slow = head;
15         ListNode fast = head;
16         while (fast != null && fast.next != null) {
17             slow = slow.next;
18             fast = fast.next.next;
19         }
20
21         return slow;
22     }
23
24     public static void main(String[] args) {
25         ListNode head = new ListNode(1);
26         head.next = new ListNode(2);
27         head.next.next = new ListNode(3);
28         head.next.next.next = new ListNode(4);
```

Run

Save

Reset

Time complexity#

The above algorithm will have a time complexity of $O(N)$ where 'N' is the number of nodes in the LinkedList.

Space complexity#

The algorithm runs in constant space $O(1)$.

Want to work at Google, Facebook, or Amazon? Get hired faster with anonymous mock interviews conducted by senior engineers from those companies. Detailed feedback helps you prep. [See how](#)