

Kiosk System - Technical Customization & Administration

Various settings can only be changed directly in the code. Any plain-text editor can be used for this purpose. As a precaution, make a backup copy of App.py and app_streamdeck.py before making changes.

1) Server Port, Credentials & Protection (Python Server)

File: app.py

- Change the port: Variable 'port = 53100'. It must match on all clients.
- Password protection for the control interfaces:
password_protection = True
USERNAME = "admin"
PASSWORD = "password123" -> change this value here.
- API protection (optional): Set API_protection = True if the API should also be protected.
- Default content & schedule: Define DEFAULT_PROGRAM and SCHEDULE_PROGRAM, as well as SCHEDULE_TIME (e.g. '02:00').

2) Customize the StreamDeck Driver

File: app_streamdeck.py

- API_BASE_URL: Enter the same port as configured in app.py.
 - STREAMDECK_INPUT_LOCK: True = buttons are locked at startup.
- Note: Port changes must always be made consistently in both the server and StreamDeck code.

3) Presentation and Control Web Pages

File: presentation.html

- slideshowTimer: Interval between image changes in milliseconds (3000 = 3 seconds).
- IP_BADGE_MINUTES: Duration of the IP address display in minutes.
- Default startup: showVideo('videos/video1.mp4') or showSlideshow('bild1/').

File: admin.html

- The Admin Panel displays the status and heartbeat and allows the StreamDeck to be enabled or locked.

File: remote.html

- Buttons are loaded dynamically from button_config.json and can be customized through the Admin Panel.

4) Button Assignment

File: button_config.json

- Structure: enabled, label, type (slideshow/video/playlist), src (path).

- Editing: Open the Admin Panel, adjust the button configuration, and save the changes.
- Changes are distributed to all connected clients (reload_clients).

5) Security

- The default username and password must be changed before the system is put into operation.
- Enable API protection when external systems are involved.
- Use the StreamDeck input lock to prevent unintended input.

These settings make it possible to secure the system flexibly - from open operation within an isolated network to password-protected and input-locked operation in sensitive environments.