

Honey Steganography: Cover-Relative Undetectability and Message-Recovery Deniability over Language Models

Peter Edwards
Independent Researcher
United Kingdom
peter@dragonstaff.co.uk

ABSTRACT

Undetectable linguistic steganography and honey encryption have each been solved – but never together. We introduce *honey steganography*: to our knowledge the first dual-game construction that is simultaneously (i) undetectable to a passive warden *relative to a deployed cover sampler* P_C and (ii) *message-recovery-deniable* to an offline key-guessing interrogator when messages are drawn from a matching plaintext model p_m (ROM key schedule; independent wrong-key DTE decoys). The technical crux is *public, key-independent segmentation*: a public tape $Pub(v)$ closes the parse-count oracle so every key extracts the same word $w' = \text{ReadBits}(T, Pub)$. Wrong-key decoding then *reduces cleanly* to classical DTE-then-OTP – a feature of the composition, not a claim of a new cryptographic transport bound. The centrepiece evaluation is the first decoy-plausibility (recovery-AUC) study under that dual game. On GPT-2 (100 trials), no detector separates stego from a channel draw (trained logistic AUC 0.55, CI [0.47, 0.63]) – an implementation check – while the channel-vs-raw gap is strongly detectable at a 256-token budget, as predicted. Matched-regime recovery AUC is near chance (0.547, CI [0.488, 0.604]); against held-out English, neural p_m cuts separability from 0.50 to about 0.39–0.43, and continued pretraining on a frozen train split shrinks holdout separability further to about 0.10–0.13 (still excluding 0.5), so real-English deniability is *not* claimed. Scope is Cover-relative undetectability and $M \sim p_m$ deniability, not platform indistinguishability or coercion resistance. A reference implementation is available on request.

KEYWORDS

steganography, steganalysis, deniability, honey encryption, language models, covert channels, provable security

Author preprint, 2026, by Peter Edwards (ORCID 0009-0007-4514-2028). DOI: 10.5281/zenodo.21922668 (<https://doi.org/10.5281/zenodo.21922668>). © the authors. Licensed under a Creative Commons Attribution 4.0 International (CC BY 4.0) licence, <https://creativecommons.org/licenses/by/4.0/>; reuse is permitted with attribution.

1 INTRODUCTION

A covert channel can now be made statistically invisible. Distribution-preserving language-model steganography [5, 6], building on the provably-secure-stego model [1], drives a *passive warden's* message-present-versus-absent advantage to zero over fluent, machine-generated text. This does not end the sender's exposure. A warden who nonetheless suspects the channel can *intercept* the traffic and *search keys offline* – at leisure, without

the sender's cooperation – and here every deployed scheme fails identically: a wrong key decodes to uniform garbage, which simultaneously proves that a message was hidden and, once the correct key surfaces under offline search, reveals it. Honey encryption [3, 4] defeats exactly this key-search adversary by making every wrong key decrypt to a fresh, plausible message. Its output, however, is *presented as ciphertext* rather than embedded as innocent cover traffic in a channel, and so is itself detectable. Undetectability and brute-force deniability have thus been solved separately and never together. We show they *compose* over language-model text as *honey steganography*: a dual-game primitive whose cover is an off-the-shelf distribution-preserving sampler and whose plaintext layer is a honey-encryption DTE. The engineering that makes the composition honest is *public segmentation*: after every key extracts the same word $w' = \text{ReadBits}(T, Pub)$, deniability *reduces cleanly* to classical DTE-then-OTP under a message model faithful to the true message distribution – a feature of the design, not a new transport cipher. We target offline key search after interception, in the sense of honey encryption [3]; we do *not* claim coercion resistance, where a holder is compelled to surrender the real key – the province of deniable encryption [8] (§7).

Contributions. The ingredients are known; what is new is the dual game, closing the parse oracle, and the first honey-stego decoy-plausibility evaluation. The cover sampler itself is prior art we adopt.

C1 (Dual-game definition).

To our knowledge the first security definition demanding both properties at once: an undetectability game against a passive warden (§3.2) and a message-recovery deniability game against an *interrogator* who holds the stegotext, knows a message is present, and searches keys offline (§3.3).

C2 (Public extraction and transport).

Public segmentation closes the parse-count oracle: every key extracts the same $w' = \text{ReadBits}(T, Pub)$. Lemma 5.4 then reduces wrong-key decoding to classical DTE-then-OTP, yielding the honey-encryption message-recovery bound (Theorem 5.5). That clean reduction is the point of the composition engineering; we do not claim a new cryptographic transport bound beyond OTP after public extraction.

C3 (Plaintext DTE – the honey machinery).

A randomized arithmetic-coding distribution-transforming encoder over an autoregressive plaintext model (§4.1), EOS-terminated with a fixed-length seed for length hiding, so that wrong keys yield independent draws from the DTE's message law (within the arithmetic goodness ϵ) – what a passive-warden-secure scheme lacks.

C4 (Undetectability, inherited).

We propose no new sampler: undetectability is supplied by Discop [5]. Our cover-side contribution is proving that the composition preserves the deployed-channel game (Theorem 5.2), and folding in a self-tokenizing restriction so the neural instantiation is exactly invertible.

C5 (Evaluation).

An evaluation over GPT-2 whose centrepiece is a *decoy-plausibility* study measuring an interrogator’s recovery AUC over wrong-key decoys – an experiment prior stego work cannot run – alongside an undetectability study with 100 trials against a trained detector, both with bootstrap confidence intervals (§6).

The one-line delta: *to our knowledge the first scheme, with proof, that is simultaneously undetectable to a warden – relative to the deployed cover channel – and message-recovery-deniable (in the random-oracle key-schedule model, for $M \sim p_m$) to a key-guessing interrogator over language-model text.*

2 RELATED WORK

Provably-secure steganography. Cachin’s information-theoretic model [1] measures security by the relative entropy $D(P_C \parallel P_S)$ between cover and stego distributions; Hopper, Langford, and von Ahn [2] give the complexity-theoretic counterpart, and public-key steganography [17] removes the shared-secret assumption we make (§7). We adopt the secret-key notions verbatim for the undetectability half of our dual game; our contribution is orthogonal to and layered above them.

Distribution-preserving LLM steganography. Meteor [6] embeds via arithmetic coding against a language model’s next-token distribution; Discop [5] instead selects among measure-preserving *distribution copies*, achieving zero KL divergence at the sampling step; minimum-entropy-coupling (MEC) approaches [14] pursue the same goal from an information-theoretic angle and are additionally *capacity-optimal*, whereas Discop’s single-bit half-rotation is perfectly secure but not capacity-optimal. These schemes make *whether* a message exists undetectable, but a wrong key still yields garbage: they are silent on the key-compromise adversary. We build our cover side on Discop for concreteness; any perfectly-secure sampler, MEC included, slots in unchanged, and we show undetectability survives the addition of a honey layer.

Classical linguistic steganography. Grammar- and mimicry-based methods, beginning with Wayner’s mimic functions [7], hide data in the production choices of a phrase-structure grammar. The neural successors replace the grammar with a language model and an entropy coder – arithmetic-coding neural linguistic steganography [15] and its Huffman variants – raising fluency but still incurring a distributional gap that the distribution-preserving samplers above close. None is deniable under key search; we treat this line as the historical baseline.

Honey encryption and natural-language encoders. Honey encryption [3] defeats brute-force key search by making every wrong key decrypt to a plausible message via a distribution-transforming encoder (DTE); NoCrack [4] realises natural-language encoders

as DTEs for password vaults. Their ciphertext is, however, overt. This also differs from format- and format-preserving encryption [20, 21], which shape *ciphertext* to a target format to evade classifiers but give no wrong-key plausibility; we borrow the distribution-shaping intuition and apply it to the plaintext decoys. We import the DTE abstraction and show (Lemma 5.4) that public extraction reduces the resulting wrong-key computation to the usual DTE-then-OTP construction.

Deniable encryption and storage. Deniable encryption [8] lets a coerced party reveal a fake key opening a chosen decoy; bi-deniable schemes [9] extend this so both sender and receiver can equivocate, and plausibly-deniable storage – the steganographic file system [10] and hidden-volume/ORAM designs [11] – hides the very existence of protected data at rest. All target the *coercion* adversary and pay for it with special-purpose artifacts: a distinguished fake-key trapdoor, or an encrypted container whose presence is itself apparent and invites the demand to open it, with deniability typically *bounded* (a fixed set of decoys planted in advance). Our honey approach is complementary and differs on two axes. (i) *No trapdoor*: every key is equally valid, so decoys are generated on the fly rather than pre-planted, with no bound on their number. (ii) *Undetectable medium*: the carrier is innocent cover traffic, not a manifest ciphertext or an on-disk container whose existence already signals something to hide. We do not, however, claim coercion resistance (§7) – precisely the property these primitives provide – so the two lines compose: a fake-key trapdoor could be layered on our channel to add coercion resistance to its undetectability and offline-key-search deniability.

Steganalysis. Recent detectors go beyond hand-crafted statistics: some fine-tune large language models as generative steganalyzers [16], others score candidate text under an independent language model. We evaluate against both such likelihood detectors and trained detectors (§6); to our knowledge no prior linguistic-stego evaluation measures a *recovery* AUC of wrong-key decoys, because prior schemes have no message-level honey property to test.

3 BACKGROUND AND THREAT MODEL

3.1 The deployed sampler and covertext channel

Fix an autoregressive token model over a vocabulary V ; at history h it induces a next-token distribution $p(\cdot \mid h)$. The *deployed sampler* applies three public, deterministic post-processings: (1) **nucleus truncation** at threshold ρ and renormalization, giving $\hat{p}(\cdot \mid h)$; (2) **fixed-point quantization** to $T = 2^b$ ($b = 32$), assigning each surviving token t an integer arc width $w_t \geq 1$ with $\sum_t w_t = T$ and $\tilde{P}(t \mid h) = w_t/T$; and (3) a **self-tokenizing restriction**: t is *safe* at h iff re-encoding the decoded string reproduces the identifier sequence, $\text{safe}_h(t) := \lfloor \text{enc}(\text{dec}(h \mathbin{++} t)) \rfloor = h \mathbin{++} t$. Let $\text{tok}_h : \{0, \dots, T-1\} \rightarrow V$ be the arc-lookup map (uniform pushes forward to $\tilde{P}(\cdot \mid h)$), $H = T/2$, and $s(r) = (r + H) \bmod T$ the half-rotation.

Definition 3.1 (Covert channel). P_C is the distribution over public objects (T, v, h_0) produced by honest sampling from the *deployed* sampler: same truncation, quantization, self-tokenizing restriction, and a *fixed public continuation budget* of N tokens (with the same abort/retry rule as Embed when fewer than ℓ embedding opportunities arise), but with the payload bits replaced by fresh tape bits. It is therefore a synthetic channel engineered to match the stegosystem’s traffic shape – including nonce and prompt – not the law of unrestricted platform sampling. All undetectability statements are relative to this P_C ; §5.4 quantifies its distance from the untruncated model. P_S (resp. $P_S[M]$) denotes the transmitted distribution when embedding (a fixed message M).

3.2 Game 1 – passive warden (undetectability)

A passive warden Eve observes one public object (T, v, h_0) and tests H_0 : object $\sim P_C$ versus H_1 : object $\sim P_S$.

Definition 3.2 (ϵ -security [1]). A stegosystem is ϵ -secure if $D(P_C \| P_S) \leq \epsilon$; *perfectly secure* when $\epsilon = 0$, i.e. $P_C = P_S$.

For any test with false-alarm α and miss β , data processing gives $D(P_C \| P_S) \geq d(\alpha \| 1 - \beta)$, and by Pinsker $\text{Adv}(\text{Eve}) = \text{TV}(P_C, P_S) \leq \sqrt{(\ln 2/2) D(P_C \| P_S)}$; at $D(P_C \| P_S) = 0$ every detector’s detection rate equals its false-alarm rate.

3.3 Game 2 – interrogator (message-recovery deniability)

The second game grants the adversary strictly more: it *knows* a message is present and searches keys offline. Fix a key distribution p_k over $\mathcal{K}$, a plausible-message distribution p_m over $\mathcal{M}$, and a public nonce v .

Definition 3.3 (Message-recovery game). Game MR: the challenger samples $K \leftarrow p_k$, $M \leftarrow p_m$, samples a fresh nonce v and (for the neural variant) a public prompt h_0 , computes $(T, v, h_0) \leftarrow \text{Embed}(K, v, M)$ under the fixed-budget / abort-retry rule of §4, and publishes (T, v, h_0) . The interrogator A , given that object and up to q key-derivation queries, outputs M' and wins iff $M' = M$; $\text{Adv}^{\text{mr}}(A) = \Pr[M' = M]$ (a raw success probability, following [3], not an edge over the guessing baseline μ).

Intended deployment. The dual game is aimed at a *low-entropy shared secret*: a passphrase or password-derived key with p_k concentrated on a modest set (so that an offline searcher can reach $q \approx 2^k$ candidates), exchanged once out of band and then used as the long-term σ of §4. Honey steganography is most useful exactly there – where ordinary stego fails because garbage under a wrong key identifies the correct guess – and where a memory-hard KDF can throttle the *rate* of those guesses (§5.3). It is *not* aimed at high-entropy keys (where offline search is already infeasible), at platform-level cover against wardens who treat unrestricted traffic as normal (Remark 5.1), or at coercion / compelled disclosure of σ (§7). Calling σ “long-term” means it is reused across messages with fresh nonces, not that it is a high-entropy cryptographic key.

4 THE STEGOSYSTEM

Keys and public values. A long-term secret σ (the key K of Game 2, Def. 3.3; intended as a low-entropy shared secret – see

§3.3); a per-message public nonce v ; and, for the neural variant, a public prompt h_0 . A memory-hard KDF maps $\sigma \mapsto mk$. The *payload mask* $ks_A = F(mk, v \parallel \text{"mask"})$ is secret. The *segmentation tape* $Pub = H(v \parallel \text{"public"})$ is derived from the nonce alone (SHA-256 counter mode in the reference implementation) and is therefore identical for every key: it supplies the per-step rotation coins r_i and filler selector bits. Secrecy lives only in ks_A ; embedding positions are key-independent.

Encoder $\text{Embed}(K, v, M)$. (i) Encode M to a fixed-length seed via the plaintext DTE (§4.1): $seed = \text{dte.enc}(M)$, targeting p_m . (ii) Whiten: $c = seed \oplus ks_A$. (iii) Generate exactly N continuation tokens from the public prompt h_0 . At step i with history h , draw $r_i \leftarrow Pub$ and form the two distribution copies $i_0 = \text{tok}_h(r_i)$, $i_1 = \text{tok}_h(s(r_i))$. Classify from (h, r_i) alone (hence identically for every key): on a collision or unsafe copy, emit a self-tokenizing fallback (0 bits); on an embedding step, draw a public selector bit $b \leftarrow Pub$, then emit i_0/i_1 according to the next unused bit of c while bits remain, otherwise according to b (filler). (iv) If fewer than ℓ payload bits were placed within the N tokens, abort and retry with a fresh nonce.

Decoder $\text{Extract}(K, v, \text{text})$. Re-tokenize, replay the *same* public tape Pub and classification over the whole continuation, and form $w = \text{ReadBits}(T, Pub)$: at each embedding step append bit 1 iff the observed token equals i_1 , else 0 (never reject), burning the public selector bit for synchronisation. Pad or truncate w to ℓ , un-whiten $seed' = w \oplus ks_A$, return $\text{dte.dec}(seed')$. Because segmentation is public, every key recovers the *same* raw w (hence the same embedding count); keys differ only in ks_A .

Remark (Parse counts are key-independent). With public segmentation, the raw embedding count before pad/truncate is a function of (T, v, h_0) alone – identical for every key – so it cannot serve as a correct-key test. The remaining honey mechanism is the classical one-time-pad of ks_A against that shared w . (Earlier drafts used a key-dependent sampling tape; that admitted a count oracle and is retired.)

4.1 The plaintext DTE

A DTE relative to p_m is a pair $(\text{dte.enc}, \text{dte.dec})$ with seed space $\mathcal{S} = \{0, 1\}^\ell$ such that $\text{dte.dec}(\text{dte.enc}(m)) = m$ (correctness), $\text{TV}(\text{dte.dec}(U), p_m) \leq \epsilon$ for uniform U (ϵ -goodness), and $\text{dte.enc}(m)$ is near-uniform for $m \leftarrow p_m$ (uniform seeds). We instantiate p_m as an autoregressive plaintext model over a truncated support V (the model’s nucleus, further capped at its top K tokens), with a delayed-eos floor $n_{\min}$: $q(\text{EOS} \mid \cdot) = 0$ for the first $n_{\min}$ tokens and $q(\text{EOS} \mid \cdot) \geq p_{\text{EOS}} > 0$ thereafter, forced at step $n_{\max}$. Message space and law are therefore

$$\mathcal{M} = \bigcup_{n=n_{\min}}^{n_{\max}-1} V^n \cup V^{n_{\max}},$$

$$p_m(m) = \left(\prod_{i \leq |m|} q(t_i \mid t_{<i}) \right) \cdot \begin{cases} q(\text{EOS} \mid m), & n_{\min} \leq |m| < n_{\max}, \\ 1, & |m| = n_{\max}. \end{cases}$$

That is, $\mathcal{M}$ is the set of *terminated* strings – closed by an eos draw after length at least $n_{\min}$, or reaching the cap – and not the set of all strings of length $\leq n_{\max}$, which would also contain unterminated prefixes and one-token stubs. Defining p_m as this capped,

truncated model removes model-mismatch from ε by fiat; the cost is paid in realism (Remark 5.2). The cap is not cosmetic: it makes p_m finitely supported, so the coder is total and ε charges arithmetic only. The delayed-EOS floor is likewise part of p_m : every key's decoys inherit the same minimum length, so human inspection sees phrase-length candidates without a length oracle. It also means a $(1-p_{\text{EOS}})^{n_{\text{max}}-n_{\text{min}}}$ fraction of p_m -draws terminate at the cap rather than at a sampled EOS, where n_{min} is the delayed-EOS floor (EOS forbidden for the first n_{min} tokens) – about 42% at the neural slice's $p_{\text{EOS}} = 0.06$, $n_{\text{min}} = 10$, $n_{\text{max}} = 24$ ($0.94^{14} \approx 0.42$), and 5% at the bigram demo's 0.12, 24 (EOS only from step 1). Because that is a property of p_m itself, it is shared by the true message and by every decoy, so it is not a bin distinguisher (Remark B); it is a realism cost, since real plaintexts do not stop mid-sentence at a fixed length, and §6.3 returns to it. The hard support cap ($K = 256$ in the neural slice) is likewise not cosmetic: without it S is unbounded under nucleus truncation alone, and the goodness bound of Prop. B.4 is vacuous (Remark B).

Construction. Seeds are integers in $[0, 2^\ell)$ – points of the ℓ -bit grid – and the coder is b_m -bit fixed point, with per-step arc widths $w_t \geq 1$ summing to 2^{b_m} ($b_m = 32$ in the neural slice, 16 in the bigram demo; this is the DTE's own precision, unrelated to the cover sampler's b of §3.1). $\text{dte.dec}(\text{seed})$ selects, at each step, the token whose arc contains seed , rescales the surviving arc onto the parent interval by integer multiplication and division, and halts at EOS or at n_{max} . $\text{dte.enc}(m)$ runs the same recursion to obtain m 's integer leaf $[l_m, h_m)$ and returns a uniformly random grid point of it. Encoding on the grid, rather than rounding a real into the leaf, is what makes correctness exact rather than approximate (Prop. B.1). The formal properties (correctness, ideal goodness $\varepsilon = 0$, uniform seeds, and finite-precision goodness $\varepsilon = O(n_{\text{max}} S 2^{-b_m})$ for per-step support size S) are Propositions B.1–B.4 in Appendix B. The fixed-length seed hides message length, and the seed is the interface that the transport lemma (§5.2) proves leaks nothing. The fixed ℓ is not free in rate – every message costs ℓ channel bits ($\approx \ell$ tokens at ≈ 1 bit/token; $\ell = 512$ in the bigram demo, 896 in the neural slice), so “free” refers to the security composition, not throughput. Totality is then a deterministic head-room condition rather than a probabilistic one: each step shrinks the interval by at most a factor 2^{-b_m} (as $w_t \geq 1$), so writing $h = \ell - b_m \cdot n_{\text{max}}$,

$$h \geq 2 \quad (1)$$

(equivalently $\ell \geq b_m \cdot n_{\text{max}} + 2$) makes every leaf non-empty ($W_m \geq 2^h - 2 \geq 1$; Appendix B) and dte.enc total on p_m 's support, with no appeal to $p_m(m) \geq 2^{-\ell}$. Both demos satisfy it with room to spare: $896 - 32 \cdot 24 = 128$ and $512 - 16 \cdot 24 = 128$.

5 SECURITY ANALYSIS

Assumptions. (A1, randomness) $\text{Pub}(v)$ is a public, deterministic function of the published nonce v , supplying $\{r_i\}$ and filler bits; the warden can recompute it. In the information-theoretic model, Pub is a public shared tape, not hidden randomness. In the computational model, ks_A is produced by the PRF-based key schedule, while Cover and Stego use the same public $H(v)$ for Pub ; no claim treats a public hash/PRG output as secret from an unbounded warden. ks_A is uniform given (σ, v) (IT tape or PRF; §5.3). (A2, channel) the

warden's reference is the deployed sampler (Def. 3.1). (A3, payload-tape independence) the payload $c = \text{seed} \oplus ks_A$ is independent of $\text{Pub}(v)$ (hence of $\{r_i\}$); equivalently $M \perp \text{Pub}$ and $ks_A \perp \text{Pub}$. (A4, key-schedule idealisation) for the MR game the schedule yields, per key K' , a uniform $ks_A^{K'}$ independent of (Pub, T) and independent across keys (unconditional under a random-oracle KDF; computational under §5.3). (A5, DTE goodness) the DTE is ε -good for p_m . (A6, passive/fresh-nonce) the adversary is observe-only and each nonce is used at most once per key.

5.1 Undetectability

The step classification at (h, r) depends only on the *unordered* pair $\{\text{tok}_h(r), \text{tok}_h(s(r))\}$ and on safe_h , hence is invariant under the involution s .

LEMMA 5.1 (PER-STEP DISTRIBUTION INVARIANCE). *Fix history h and bit $\beta \in \mathbb{Z}_2$. Let $T(\beta)$ be the token emitted when the consumed selector bit is β and $r \sim \text{Unif}\{0, \dots, T-1\}$. Then the law of $T(\beta)$ is independent of β and equals the deployed per-step law Q_h . That law is supported on the safe set: it vanishes on the unsafe set U_h and redistributes that mass onto safe tokens, so $\text{TV}(Q_h, \tilde{P}(\cdot | h)) \leq \tilde{P}(U_h | h)$; it does not agree with $\tilde{P}$ token-by-token even off U_h (§5.4).*

THEOREM 5.2 (PERFECT SECURITY RELATIVE TO THE DEPLOYED CHANNEL). *Under (A1-IT), (A2), (A3), (A6), for every M the joint stegotext law on (T, v, h_0) equals the joint covertext law when both use the same $\text{Pub}(v)$, $P_S[M] = P_C$; hence $P_S = P_C$ and $D(P_C \| P_S) = 0$ (Def. 3.2).*

COROLLARY 5.3 (WARDEN ADVANTAGE). *Under Theorem 5.2, every passive warden – of unbounded power – has advantage exactly 0.*

Proofs are in Appendix A. Undetectability derives from public, identically generated selector positions r_i and the s -invariance of the copy structure, never from the message being uniform; whitening with ks_A is retained for the honey property.

Remark (Reference distribution and the realistic warden). Theorem 5.2 is stated relative to the deployed sampler P_C (Def. 3.1), not the raw platform model: the two differ by the message-independent channel gap of §5.4. That gap is identical for stego and control, so it never leaks the *message*; but because it is a constant per-token deviation from the raw model, a warden who takes the raw model as reference can – by the square-root law of steganographic capacity [19] and pooled/batch steganalysis over many objects [18] – eventually detect the mere *presence* of the deployed channel. Undetectability here is therefore against P_C ; a deployment needing indistinguishability from the raw platform must drive the §5.4 gap down (e.g. $\rho \rightarrow 1$), trading capacity for it. “Perfect” refers to the sampling step (zero KL, Lemma 5.1), not to indistinguishability from arbitrary platform traffic.

Message-independent length. A warden also counts tokens, so the stopping rule must not leak. We use a *fixed public budget* N : every accepted object has continuation length exactly N , with abort/retry on underflow ($< \ell$ embeddings in N steps). Whether step i embeds is the indicator $e_i = 1[r_i \in B]$, a function of (h_i, r_i) alone, never of the payload bit; filler bits after the payload are likewise payload-independent. Hence the embedding count, abort

decision, and retry policy depend only on (h, r) from Pub , not on the payload, and are identical under $P_S[M]$ and P_C . The game is therefore on accepted transcripts: among accepted outputs the joint law of the length- N token sequence is identical for every M and for P_C (Appendix A). So $P_S = P_C$ including length – again relative to P_C ; the raw-model gap of §5.4 is message-independent (Remark 5.1). The acceptance probability is a property of (N, ℓ, ρ) and the model, not of M ; we do not claim a closed-form bound, and the GPT-2 instantiation relies on empirical retries (§6). Failed attempts are assumed unobservable, or identically observable under both hypotheses; a platform that exposes them creates a separate deployment channel not covered by this game.

5.2 Message-recovery deniability

Embed computes $seed = \text{dte.enc}(M)$, $w = seed \oplus ks_A^K$, and drives the sampler with w under the public tape $Pub(v)$ to emit T ; Extract forms the *key-independent* word $w' = \text{ReadBits}(T, Pub)$, then $seed'_{K'} = w' \oplus ks_A^{K'}$, and returns $\text{dte.dec}(seed'_{K'})$.

LEMMA 5.4 (UNIFORM-DECOY TRANSPORT). *Under (A4), for fixed public T , v the recovered word $w' = \text{ReadBits}(T, Pub)$ is identical for every key. For every wrong key $K' \neq K$, the recovered seed $seed'_{K'} = w' \oplus ks_A^{K'}$ is uniform on $\mathcal{S}$, and $\{seed'_{K'} : K' \neq K\}$ is mutually independent. For the true key, $seed'_K = \text{dte.enc}(M)$, so $\text{dte.dec}(seed'_K) = M$.*

Public segmentation closes the parse-count oracle: w' is a deterministic function of (T, v) alone, shared by every key. The lemma is deliberately the classical one-time-pad argument of independent $ks_A^{K'}$ against that public word, after DTE encoding; it is not a new honey-encryption transport bound. Thus the interrogator sees the usual DTE-then-OTP bin structure (the true message is recovered *exactly*; a wrong-key decoy is within ε of p_m). The contribution of public Pub is to enable this reduction by retiring key-dependent mis-segmentation and closing the parse-count oracle (Remark 4).

THEOREM 5.5 (MR-DENIABILITY). *Under (A4), (A5), (A6), for any interrogator A (unbounded, q key queries),*

$$\text{Adv}^{\text{mr}}(A) \leq \text{Adv}^{\text{mr}}_{\text{HE}}(p_k, p_m; q) + q\varepsilon \leq \mu + q\varepsilon + \delta(q, p_k),$$

where $\text{Adv}^{\text{mr}}_{\text{HE}}(p_k, p_m; q)$ is the optimal message-recovery success probability against ideal ($\varepsilon=0$) DTE-then-encrypt honey encryption on (p_k, p_m) – the maximum over interrogators making q key-derivation queries of $\Pr[M' = M]$ when $K \leftarrow p_k, M \leftarrow p_m$ [3, Thm. 4] – the $q\varepsilon$ is a hybrid over the (at most q) wrong-key bins A inspects (the true bin is recovered exactly, so contributes no ε), $\mu = \max(\max_k p_k(k), \max_m p_m(m))$ is the guessing baseline, and $\delta \rightarrow 0$ as p_k flattens.

COROLLARY 5.6 (FLAT-KEY REGIME). *If p_k is uniform over $\geq 2^K$ keys and the DTE is ε -good, $\text{Adv}^{\text{mr}}(A) \leq \max_m p_m(m) + q\varepsilon + \delta_K$, where $\delta_K = \delta(q, p_k)$ is the balls-and-bins remainder of [3, Thm. 4] for q guesses into $\geq 2^K$ uniform bins, with $\delta_K \leq q 2^{-K}$ (union bound) vanishing for $q \ll 2^K$.*

Remark (Model of Theorem 5.5). The bound is a *random-oracle* statement: the cross-key independence in (A4) is a property of the KDF modelled as a random oracle, not a consequence of the PRF on F . §5.3 shows the standard-model surrogate term $q \text{Adv}^{\text{prf}}_F$ is

vacuous precisely in the offline-enumeration regime ($q \approx 2^K$) the theorem targets; we therefore state deniability in the ROM and rely on the memory-hard KDF to throttle q .

Remark (What is and is not protected). Within Game MR, recovering M from wrong-key messages $\text{dte.dec}(seed'_{K'})$ is bounded by Theorem 5.5 when $M \sim p_m$: the shared $w' = \text{ReadBits}(T, Pub)$ masked by independent $ks_A^{K'}$ yields uniform seeds under wrong keys (Lemma 5.4), and public segmentation makes raw embedding counts identical across keys (Remark 4). That is still not a claim that decoys match *real English* under a stronger judge (§6.2). What remains, even in the ideal p_m game, is *guessing*: a guessable key or message is unavoidable and matched by Theorem 5.5, exactly as in honey encryption.

Remark (Faithful message model is load-bearing). Theorem 5.5 draws M from p_m , so its force is contingent on p_m modelling the *true* message distribution; off- p_m messages are separable by a judge stronger than p_m (the mismatched regime of §6). This is the central open problem of natural-language honey encoders, not a defect of our composition: Golla et al. [12] distinguished real password vaults from [4] decoys precisely on model mismatch, and Jaeger et al. [13] show message-recovery is a weak target absent a faithful model. Defining p_m as the plaintext model removes encoder-vs-target mismatch but relocates it to model-vs-reality (§6).

5.3 Key schedule and the standard-model instantiation

From σ, v : $mk = \text{KDF}(\sigma)$ (Argon2id); $ks_A = F(mk, v \parallel \text{"mask"})$ with F a PRF (SHA-256 counter mode); $Pub = H(v \parallel \text{"public"})$ a key-less hash/PRG of the nonce alone (one-byte domain tag distinct from the mask). This tape is public: the warden knows v and can recompute Pub . Cover and Stego use the identical $H(v)$, so their equality is not based on hiding $\{r_i\}$. In the random-oracle or ideal-tape generative model, $H(v)$ supplies uniform rotation coins for Lemma 5.1; in a computational instantiation it is a public shared tape, not a secret PRG output. Deniability needs ks_A uniform and independent of (Pub, T) so that $seed' = w' \oplus ks_A$ is uniform for $w' = \text{ReadBits}(T, Pub)$ (Lemma 5.4). Secrecy lives only in ks_A ; the public tape is not a second secret keystream. For an adversary of time $\approx t'$ deriving q keys,

$$\text{Adv}^{\text{passive}}(W) \leq \text{Adv}^{\text{prf}}_F(t'),$$

$$\text{Adv}^{\text{mr}}(A) \leq \mu + q\varepsilon + \delta + q \text{Adv}^{\text{prf}}_F(t').$$

For undetectability the PRF assumption discharges the mask idealisation; the public tape is identically available in both hypotheses. This gives the stated computational game in the sense of Hopper–Langford–von Ahn [2], conditional on modelling Cover and Stego with the same public $H(v)$. For deniability the PRF discharges only the *within-key* mask randomness; the *cross-key* independence of (A4) is a random-oracle property of the KDF ($\sigma' \mapsto mk'$ giving independent ks_A), not a consequence of the PRF on F . Hence the bound above is meaningful only for $q \ll 1/\text{Adv}^{\text{prf}}_F$: against offline enumeration of a low-entropy key space ($q \approx 2^K$) the $q \text{Adv}^{\text{prf}}_F$

term is vacuous and deniability rests on the random-oracle KDF together with the memory-hard KDF that throttles q .

5.4 Channel gap

Relative to the *raw* platform sampler, three deterministic, message-independent discrepancies arise: truncation $\varepsilon_{\text{trunc}} = \mathbb{E}_h[-\log_2 Z_h]$ (retained nucleus mass $Z_h \geq \rho$; ≈ 0.111 bits/token under GPT-2, identical for stego and control); quantization $O(|\text{supp}|/T)$ (negligible at $b = 32$; the per-token analogue is $\sim 3 \times 10^{-14}$ bits, i.e. zero up to floating-point precision); and self-tokenization – barring unsafe tokens from carrying a bit and substituting a self-tokenizing fallback perturbs the per-step law only where the honest draw is unsafe, giving $\text{TV}(P_C, \tilde{P}) \leq \mathbb{E}_h[\tilde{P}(U_h)]$ for the unsafe set U_h (Lemma 5.1). Measured under GPT-2 ($\rho = 0.92$), $\mathbb{E}_h[\tilde{P}(U_h)] \approx 1.1 \times 10^{-2}$, with a fallback firing at only $\approx 1\%$ of steps – the largest of the three gaps. Note that this bound is insensitive to *what* the fallback emits: the coupling in the proof charges only the event that the fallback fires. The choice of fallback still matters in practice, though, because it determines the *shape* of the resulting perturbation rather than its magnitude. Our implementation takes the *highest-probability* safe token, the crudest available choice: it piles mass on the mode, and §6.1 finds exactly that signature in the detectors that separate channel text from raw text. Sampling the fallback from $\tilde{P}$ restricted to the safe set would leave the bound unchanged but remove that concentration artefact; we have not implemented it. All three are message-independent and identical for stego and control; raising $\rho \rightarrow 1$ shrinks the truncation and self-tokenization gaps at a capacity cost. Being message-independent, none leaks M ; being constant per token, they are nonetheless detectable against the *raw* model in the pooled/asymptotic sense (square-root law [18, 19]), which is why undetectability is stated relative to P_C (Remark 5.1).

6 EVALUATION

The theorems give guarantees under stated assumptions; this section reports the measurements that test them: undetectability with 100 trials against a trained detector (§6.1), and message-recovery deniability under a toy and a neural plaintext model (§6.2). A reference implementation (available on request) regenerates these numbers up to Monte-Carlo variation.

Scope. The two headline studies evaluate the halves separately: E1 uses the theorem’s fixed-budget `encode_bits` path and the same P_C definition, embedding a uniform payload of fixed length; E2 exercises DTE goodness and matched-versus-mismatched judges without a cover channel. E2 does not measure Argon2id’s offline cost. An end-to-end harness (`e2e_composition.py`) joins them – `dte.enc(M)` masked and carried by the Discop sampler via a fixed-length bit API, with true-key recovery, leaf agreement, wrong-key decoys, fixed continuation budget, and public-segmentation agreement checked – and passes at a short seed ($\ell=256$, 3/3) and at the paper parameters ($\ell=896$) on the same 100-trial multi-prompt schedule as §6.1 (100/100 under the harness’s capacity retries; mean continuation length ≈ 1013 tokens at ≈ 0.88 bits/tok, every accepted cover filling its prompt-specific budget, every key agreeing on the raw embedding count). The run is an *implementation-conformance* check of the composed path –

not a proof of Lemma 5.4. With public segmentation (Remark 4), the remaining honey mechanism is ks_A alone. The reported `e2_neural` and `e2e` artefacts use `min_tokens=10` (delayed EOS). E1 reports a fixed continuation budget $N=256$ with uniform payload length $\ell=128$ bits – still the theorem’s fixed-budget P_C , at a detector-scale token budget rather than a full 1024-token fill.

6.1 Undetectability

Setup. GPT-2 (124M) as cover sampler at $\rho = 0.92$, $b = 32$; DistilGPT-2 (independent weights) as the judge scoring per-token surprisal; Argon2id KDF. We run 100 *paired* trials across ten prompts spanning distinct domains (news, recipe, fiction, correspondence, sport, review, how-to), with three conditions per trial: **stego** (a fresh uniform message embedded under one fixed long-term key, held constant across trials); P_C , a fresh *random-key* encode, which by Theorem 5.2 is a bona-fide draw from the deployed channel via the identical code path; and **raw**, ordinary nucleus sampling *without* the self-tokenizing restriction (the platform text a naive warden compares against). Detectors are per-feature likelihood statistics (mean/std/max NLL, perplexity) and two *trained* detectors – logistic regression and gradient boosting – scored out-of-fold under 5-fold cross-validation, with 95% bootstrap CIs ($B=2000$; script `e1_undetectability.py`).

Results (Table 1). We report all 18 detector $\times$ contrast combinations rather than a selection. Two patterns emerge, and they are the two the analysis predicts. The table uses the theorem’s fixed-budget `encode_bits` path ($N=256$ continuation tokens, uniform $\ell=128$ -bit payload, public segmentation).

Message leakage is at chance. On stego vs. P_C – does embedding a chosen payload perturb the text law relative to a random-key channel draw? – all six detectors’ CIs contain 0.5 (trained logistic 0.55, CI [0.47, 0.63]). Theorem 5.2 makes the two laws identical by construction, so this contrast cannot separate the message in expectation: it is a code-correctness / no-leak regression check – it would move off 0.5 only if an assumption (A3) or the implementation (mask independence, whitening) were violated – and it corroborates rather than independently establishes undetectability.

The channel gap is visible, and grows with cover length. Every detector on both contrasts against *raw* platform text has a CI excluding 0.5 (trained logistic 0.85 stego-vs-raw, 0.81 P_C -vs-raw). That is the message-independent self-tokenizing / truncation gap of §5.4, accumulated over a 256-token fixed budget – precisely the gap Theorem 5.2 does *not* cover, since undetectability is stated relative to the deployed channel rather than the raw model (Remark 5.1). Longer covers make the gap easier to detect (the square-root law [19]); the earlier stop-on-payload table understated it because continuations were shorter. We claim only that the separation lies where the analysis places it – against raw text, not against P_C – and that a deployment needing platform-level cover must shrink the §5.4 gap (e.g. safer fallbacks, $\rho \rightarrow 1$).

KL divergence. The sampling KL (embedding vs. none) is 0 by construction (Theorem 5.2); the measured truncation KL is 0.110 vs. 0.111 bits/token (stego vs. P_C), i.e. identical – a property of ρ , not embedding. Against the model law, the induced-token per-token KL is $\approx 3 \times 10^{-14}$ bits for Discop rotation (the fixed-point quantization floor of §5.4, since the rotation is measure-preserving, i.e.

Table 1: Undetectability, 100 paired trials, DistilGPT-2 judge; fixed-budget encode_bits ($N=256$, $\ell=128$), public segmentation; all 18 detector $\times$ contrast combinations. AUC 0.5 = undetectable; brackets are 95% bootstrap CIs ($B=2000$); trained detectors are scored out-of-fold (5-fold CV). Every message-leakage CI contains 0.5. Every contrast against raw platform text excludes 0.5 – detecting the self-tokenizing channel gap of §5.4, not the payload.

Detector	stego vs. P_C (message leakage)	stego vs. raw (vs. platform text)	P_C vs. raw (channel gap)
mean NLL	0.49 [0.409, 0.573]	0.80 [0.735, 0.859]	0.81 [0.749, 0.865]
std NLL	0.53 [0.454, 0.611]	0.83 [0.773, 0.886]	0.81 [0.746, 0.868]
max NLL	0.47 [0.390, 0.549]	0.69 [0.613, 0.762]	0.71 [0.632, 0.777]
perplexity	0.49 [0.408, 0.567]	0.80 [0.735, 0.860]	0.81 [0.751, 0.869]
logistic (trained)	0.55 [0.468, 0.628]	0.85 [0.795, 0.905]	0.81 [0.743, 0.861]
grad. boosting (trained)	0.55 [0.475, 0.637]	0.83 [0.767, 0.883]	0.78 [0.708, 0.838]

zero up to floating-point precision) vs. $\approx 1.3 \times 10^{-2}$ for Huffman coding.

6.2 Message-recovery deniability

A separate harness tests Theorem 5.5 directly (Table 2). The plaintext DTE maps a message to a uniform seed; the honey pipeline masks it; and an independent judge, stronger than p_m , attempts to distinguish each genuine message from its wrong-key decoys (the *recovery AUC*). We run it with two plaintext models: a word-level *bigram* p_m (judged by an interpolated trigram), and a *neural* p_m (DistilGPT-2) inside the same randomized arithmetic-coding DTE (judged by GPT-2). For the neural model we use $G=150$ genuine messages and a pool of 300 decoys, at the parameters of Remark B ($b_m = 32$, $n_{\max} = 24$, $K = 256$, $\ell = 896$, so $S = 257$ and $\varepsilon \leq 1.4 \times 10^{-6}$). The coder passes 40/40 round-trip *and* leaf-agreement self-tests (Remark B), and the harness is seeded: the numbers below reproduce bit-identically from `--seed 1`. We score with two judge statistics rather than one – mean per-token NLL and *max* per-token NLL – because §6.1 found the tail, not the mean, to be the discriminative feature there, and reporting only the mean would amount to choosing the weakest available judge.

The *matched regime* (genuine $\sim p_m$) is the regime of Theorem 5.5 and carries the deniability claim: decoys are i.i.d. with the genuine message, so recovery AUC ≈ 0.5 and the message is deniable – 0.49 for the bigram, and 0.547 (CI [0.488, 0.604]) under the mean-NLL judge (contains 0.5) and 0.563 (CI [0.507, 0.619]) under the max-NLL judge for the neural model (excludes 0.5 at sep. 0.063). This is a weak test by construction, and we prefer to say so plainly: in the neural harness the genuine message and its decoys are both DTE decodes of uniform seeds, so their laws are identical by definition and an AUC of 0.5 is close to a tautology. What it actually checks is that coder and judge introduce no artifact separating two draws from one generator – a real regression check, but not evidence about deniability. The small max-NLL edge under delayed EOS (genuine vs. decoy median GPT-2 perplexity 42 vs. 50) is such an artifact; mean-NLL stays consistent with chance. The bigram harness is the stronger of the two, since it decodes each decoy through the genuine wrong-key decryption path.

The *mismatched regime* (genuine = real English) measures empirical *model–reality* mismatch under a particular judge, not the theorem’s arithmetic DTE goodness. Write $\varepsilon_{\text{arith}} = \text{TV}(\text{dte.dec}(U), p_m)$ for the finite-precision gap of

Prop. B.4, and Δ for empirical separability $[\text{AUC} - 0.5]$ between real-text windows and decoys under a fixed judge. A single-judge AUC cannot upper-bound total variation, nor estimate $\varepsilon_{\text{arith}}$; at best it evidences that $\Delta > 0$ for that corpus and judge. Under the bigram p_m separability is essentially total (0.50; trigram AUC 1.00, decoys visibly less fluent than real sentences). Under the neural p_m , against a held-out multi-genre Project Gutenberg control of ≈ 1.19 M GPT-2 tokens across ten public-domain works (fiction, nonfiction, science, essay; genre-stratified windows, length-matched in the judge’s tokens), it falls to 0.387 (mean-NLL AUC 0.113, CI [0.085, 0.145]) and 0.428 (max-NLL AUC 0.072, CI [0.050, 0.099]) – a cut from the bigram’s 0.50, but with both CIs far from 0.5, so the decoys remain clearly separable from real English. Delayed EOS (`min_tokens=10`) lengthens decoys (cap fraction ≈ 0.42) and makes the fluency inversion sharper than the earlier early-EOS slice. The residual again runs in the *opposite* direction to the bigram’s: AUC below 0.5 means the judge finds the decoys *more* fluent than the human windows (median GPT-2 perplexity 50 for decoys vs. 241 for corpus text). Raising the fidelity of p_m does not simply shrink the gap; it flips which side of it the decoys sit on, and a model whose samples are more typical than human writing is as separable as one whose samples are less so.

To ask whether a *better* neural p_m can shrink that residual without contaminating the control, we freeze a document-level train/holdout split of the same Gutenberg library (train: six titles; holdout: four titles spanning fiction, nonfiction and essay; ≈ 0.48 M GPT-2 tokens on the holdout) and continue pretraining DistilGPT-2 for one epoch on the train documents only (`train_pmt.py`; 22,310 windows of length 64). Re-running the identical seeded E2 protocol against the holdout alone, the untuned neural baseline still shows strong fluency inversion (mean-NLL AUC 0.126, sep. 0.374; max-NLL 0.080, sep. 0.420). The fine-tuned p_m moves median decoy GPT-2 perplexity from 50 to 137 (holdout human windows ≈ 205) and cuts separability to 0.133 (mean-NLL AUC 0.367, CI [0.310, 0.422]) and 0.099 (max-NLL AUC 0.401, CI [0.345, 0.457]) – a roughly threefold reduction, with matched-regime AUCs still straddling 0.5. The residual still excludes 0.5 under both judges, so real-English deniability remains unclaimed; the experiment shows that mismatched Δ is responsive to p_m fidelity once leakage between train and control is removed.

Table 2: Message-recovery deniability (randomized arithmetic-coding DTE). Recovery AUC 0.5 = decoys indistinguishable from the genuine message; brackets are 95% bootstrap CIs ($B=2000$), and separability is $|AUC - 0.5|$. Matched rows are the regime of Theorem 5.5. Mismatched neural rows use the multi-genre Gutenberg control (full library ≈ 1.19 M judge tokens, or the frozen document holdout ≈ 0.48 M; genre-stratified; --seed 1; delayed EOS min_tokens=10). Fine-tuned p_m is continued-pretrained on the complementary train split only. $\dagger$ marks CIs excluding 0.5 (§6.2).

Regime	p_m	Judge stat.	AUC	Sep.
Matched	bigram	trigram	0.49	0.01
Matched	neural	mean NLL	0.547 [0.488, 0.604]	0.047
Matched	neural	max NLL	0.563 $\dagger$ [0.507, 0.619]	0.063
Matched	neural-ft	mean NLL	0.476 [0.421, 0.535]	0.024
Matched	neural-ft	max NLL	0.457 [0.400, 0.516]	0.043
Mismatched	bigram	trigram	1.00	0.50
Mismatched	neural	mean NLL	0.113 $\dagger$ [0.085, 0.145]	0.387
Mismatched	neural	max NLL	0.072 $\dagger$ [0.050, 0.099]	0.428
Mismatched	neural (holdout)	mean NLL	0.126 $\dagger$ [0.094, 0.159]	0.374
Mismatched	neural (holdout)	max NLL	0.080 $\dagger$ [0.056, 0.104]	0.420
Mismatched	neural-ft (holdout)	mean NLL	0.367 $\dagger$ [0.310, 0.422]	0.133
Mismatched	neural-ft (holdout)	max NLL	0.401 $\dagger$ [0.345, 0.457]	0.099

A single-author Austen pilot (380 judge tokens) understates the residual (sep. ≈ 0.09 under the same delayed-EOS DTE); the multi-genre control is the measurement we report. Two caveats remain. The bigram and neural rows are not strictly comparable – different judges (interpolated trigram vs. GPT-2), tokenizations (word vs. BPE), coder precisions and caps – so the reduction from 0.50 should be read as an order of magnitude, not a ratio. And the judge is still a single LLM; human ratings and a held-out stronger judge are item (i) of §6.3.

A *methodological note*, since the trap is easy to fall into and we did. An earlier control drew windows from the same lower-cased, punctuation-stripped toy corpus as the bigram slice. That is the right control for the bigram, whose decoys share its register, but the wrong one for the neural slice, whose decoys are ordinary cased DistilGPT-2 output: the measurement was dominated by typography rather than by ϵ . Register-matched, length-matched-in-judge-tokens sampling – first the Austen pilot, then the Gutenberg library – is what produces the numbers above.

Scope of these numbers. Undetectability and the end-to-end composition join are both at 100 trials; the neural deniability slice at $G=150$ against 300 decoys, with the mismatched arm drawn from ≈ 1.19 M held-out judge tokens. Generation is CPU-bound, so these establish effect sizes with confidence intervals rather than large-scale asymptotics. Both deniability harnesses are seeded and reproduce bit-identically; the undetectability harness is not, and its figures carry the corresponding Monte-Carlo variation.

Beyond message recovery. Theorem 5.5 is a *message-recovery* (MR) guarantee [3]; Jaeger et al. [13] note MR is weak – on its own it bounds neither partial leakage (a predicate of M) nor a semantic-security goal. Our construction already reaches past

bare MR on two counts: length is hidden unconditionally (fixed seed, §5.1), and, since every wrong-key decoy is distributed as $dte.dec(U)$, within ϵ_{arith} of p_m (Lemma 5.4, Prop. B.3, Prop. B.4), any predicate of the message alone that is captured by p_m is distributed nearly identically on decoys and the real message – with residual governed by ϵ_{arith} and the model mismatch of Remark 5.2, not by the cover channel. Auxiliary information correlated with M is outside this claim. Promoting the recovery-AUC test to a *predicate-recovery* AUC (can a judge guess a chosen function of M above its prior?) operationalises the stronger [13] notions; certifying at that level is left to future work, contingent on a faithful p_m (Remark 5.2).

6.3 Guarantee coverage and what remains

Each measurement targets a specific theorem (Table 3): the undetectability study (§6.1) exercises Theorem 5.2, the deniability study (§6.2) exercises Theorem 5.5, and the KL figures both. The gaps we regard as most important, in priority order:

- (1) *Stronger mismatched judges.* The corpus-scale LLM measurement of §6.2 still uses a single GPT-2 judge. Human preference ratings on a subsample, and a held-out stronger LM judge, would test whether the residual after fine-tuning p_m (sep. ≈ 0.10 – 0.13 on the document holdout) is an artefact of that judge or a stable property of neural p_m .
- (2) *Closing the remaining p_m gap.* One epoch of continued pre-training on the train split cuts holdout separability roughly threefold but does not reach chance. Longer fine-tunes, domain-adapted message models, and message sources closer to the intended traffic remain open.
- (3) *Removing the fallback artifact.* Sample the self-tokenizing fallback from $\tilde{P}$ restricted to the safe set (§5.4) and re-run §6.1 to check that the max-NLL signature disappears.
- (4) *Undetectability at scale.* The square-root law (Remark 5.1) predicts the P_C -vs-raw gap sharpens with N ; pushing to thousands of messages over several cover models with a fine-tuned-LLM steganalyzer [16] and Meteor/Discoq baselines at matched capacity would trace that curve, and should confirm or refute the marginal separations of Table 1.
- (5) *Parameters fit for deployment.* Our $\epsilon \leq 1.4 \times 10^{-6}$ is non-vacuous only to $\sim 7 \times 10^4$ guesses, and the cap terminates about 42% of messages under delayed EOS. Both are fixed by raising b_m and n_{max} , but (1) then forces a longer seed than GPT-2’s 1024-token context can carry (Remark B), so this needs a larger-context cover model rather than a parameter change alone.
- (6) *Trade-off curves.* Capacity vs. undetectability vs. deniability swept over ρ and rotation depth.

These remaining items are scale, fidelity and breadth. The principal evaluation gaps are now items (i)–(ii) – stronger judges and the residual p_m mismatch. The 100-trial composition harness is an implementation-conformance check of the composed path under Lemma 5.4’s total ReadBits convention; it does not replace the lemma’s proof.

Table 3: Each measurement maps to a formal guarantee; the first two are reported in §6.1–§6.2, the frontier sweep is left to future work.

Measurement	Metric	Guarantee
Undetectability	detector AUC $\rightarrow 0.5$	Thm. 5.2
Deniability	recovery AUC $\rightarrow 0.5$	Thm. 5.5
KL divergence	$D(P_C \parallel P_S) \rightarrow 0$	Thm. 5.2
DTE goodness	ε (TV)	Thm. 5.5 (via $q\varepsilon$)
Frontier (future)	capacity/AUC curve	capacity trade-off

7 DISCUSSION AND LIMITATIONS

Claimed. Passive-warden undetectability relative to the deployed sampler P_C (Theorem 5.2) – a single-object game on (T, v, h_0) against the synthetic fixed-budget channel of Def. 3.1, not unrestricted platform traffic; exact message recovery under $M \sim p_m$ in the random-oracle key-schedule MR model (Theorem 5.5), for the low-entropy shared-secret regime of §3.3; and public, key-independent ReadBits extraction, which closes the parse-count oracle (Lemma 5.4, Remark 4).

Not claimed.

- *Platform indistinguishability.* The theorem compares Stego with the deployed sampler P_C , not arbitrary or raw platform traffic; the message-independent channel gap may still identify use of that sampler.
- *Observable failed generation.* Abort/retry is hidden by the game. A platform that reveals failed attempts, timings, or retry counts can expose a deployment-level signal unless those observations are identical under both hypotheses.
- *General plausibility against side-informed judges.* MR gives exact true-key recovery and a bound for $M \sim p_m$ in its stated model. It does not establish equal credibility of real and decoy messages given auxiliary information or a mismatched message distribution.
- *Coercion resistance.* We target the offline key-search adversary of honey encryption [3], not *compelled disclosure* (rubber-hose, border search), where a holder forced to surrender the real σ thereby reveals M ; that requires a fake-key trapdoor, i.e. deniable encryption [8], and composes with (rather than follows from) this work.
- *Faithful message model.* Deniability holds to the extent p_m models the true message distribution (Remark 5.2) [12, 13].
- *Active/robust steganography.* A transcript editor breaks extraction (no error-correcting or robust coding).
- *Nonce reuse or key compromise.* Out of scope. The public nonce and prompt are part of the game object (T, v, h_0) ; carrying them in-band on a raw platform channel remains a deployment concern if that channel is the warden’s reference.
- *Cross-endpoint determinism.* A matched length rule and re-tokenisation are assumed; floating-point non-determinism across hardware/library versions breaks extraction.
- *Guessing.* No protection against a guessable key or message beyond the baseline μ (fundamental to honey encryption).

- *An unlimited guess budget.* Theorem 5.5 charges $q\varepsilon$, so at our parameters ($\varepsilon \leq 1.4 \times 10^{-6}$) the bound is informative only up to $\sim 7 \times 10^4$ offline guesses. This is a parameter limitation rather than a structural one, but it is a real one: lifting it means a longer seed, and hence a cover model with a longer context than GPT-2’s (Remark B).
- *Side channels and integrity.* No side-channel freedom beyond stream-cipher hygiene; integrity/authentication is deliberately omitted to preserve the honey property (a MAC under a separate high-entropy key belongs at the transport layer).

Cost. On GPT-2 (124M) at $\rho = 0.92$ the single-bit half-rotation achieves a capacity of ≈ 0.94 bits/token (measured: 241/256 steps carry a bit; the shortfall is copy collisions and self-tokenizing-unsafe steps), so the $\ell = 512$ -bit seed of the bigram demo costs ≈ 540 tokens of cover per message, and the neural slice’s $\ell = 896$ costs ≈ 950 – the constant expansion that buys length-hiding (§4.1), and, at 896 bits, most of GPT-2’s 1024-token context. Generation runs at ≈ 37 tokens/s on a CPU (model-forward bound; a GPU or a smaller cover model raises this). The memory-hard KDF is the honey layer’s throttle: one Argon2id derivation takes ≈ 44 ms at the demo parameters, capping offline key search at ≈ 23 guesses/s/core; as a tunable cost parameter it can be raised to slow the interrogator’s *rate* of guesses, reducing the q achievable in a fixed wall-clock budget – it does not by itself bound an adversary’s total parallel work over unbounded time. These figures are measured on the reference implementation (unoptimised).

8 ETHICAL CONSIDERATIONS

This work concerns communication privacy, not offensive capability against systems. Covert, deniable messaging protects at-risk users – journalists, dissidents, and people under coercive key-disclosure regimes – which is squarely within the remit of privacy-enhancing technologies; it can also be misused, as can any confidentiality tool. We mitigate responsibly: the building blocks (Discop, honey encryption) are already public, our contribution is analytical, and we report detection limits honestly rather than overclaiming undetectability. Our studies use only model-generated and public-corpus text and involve no human subjects; any future human-rater validation of decoy plausibility (§6) will obtain ethics-board approval and informed consent.

Disclosure of generative-AI use. The author developed the intellectual contribution and is solely responsible for all claims, proofs, experiments, and text. An LLM-based coding agent was used *extensively* across the research lifecycle: assisting in developing and checking theorem statements and proofs, implementing the reference demonstrations, designing and running the experiments that produced the reported numbers, and drafting and revising this manuscript. The author directed the work, checked the theorem and proposition statements and their proofs, reproduced the reported numbers against the artifacts that generate them, and accepts responsibility for any error that remains – including in material produced with AI assistance. The novel intellectual contribution – the honey/provably-secure-steganography unification and its analysis – is the author’s own. No AI system is an author.

9 CONCLUSION

Honey steganography combines two scoped guarantees over language-model text. Undetectability (Theorem 5.2) is relative only to the deployed sampler P_C and rests on a measure-preserving half-rotation over an s -invariant embedding region (Lemma 5.1). Public segmentation closes the parse-count oracle, after which Lemma 5.4 is the classical DTE-then-OTP reduction that gives the honey-encryption message-recovery bound for $M \sim p_m$ in the random-oracle key-schedule model. It does not claim platform indistinguishability or general deniability against side-informed judges. The channel’s distributional costs are message-independent, but may remain visible relative to raw platform traffic.

A PROOFS FOR §5

PROOF OF LEMMA 5.1. The selector β affects the emitted token only on the embedding region $B = \{r : i_0 \neq i_1 \wedge \text{safe}_h(\text{tok}_h(r)) \wedge \text{safe}_h(\text{tok}_h(s(r)))\}$; elsewhere the token is a function of r alone. For $r \in B$, $T(0) = \text{tok}_h(r)$ and $T(1) = \text{tok}_h(s(r))$. As s is an involution, B is s -invariant, and being a measure-preserving bijection of B onto itself the substitution $r' = s(r)$ gives, for every t , $\Pr[\text{tok}_h(s(r)) = t, r \in B] = \Pr[\text{tok}_h(r) = t, r \in B]$. Hence the contribution of B is identical for $\beta = 0, 1$, so the two laws coincide, and we may call the common law Q_h .

For the distance to $\tilde{P}(\cdot | h)$, couple the two through the shared draw r : the honest sampler emits $\text{tok}_h(r)$, whose law is exactly $\tilde{P}(\cdot | h)$, while the deployed sampler emits $T(0)$. Inspecting the cases of the emission rule, $T(0) = \text{tok}_h(r)$ whenever $\text{tok}_h(r)$ is safe – on a collision ($i_0 = i_1$) the safe candidate is taken; when $i_0 \neq i_1$ the token $\text{tok}_h(r)$ is emitted if it is safe, whether or not its partner is. The two therefore differ only on the event $\{\text{tok}_h(r) \in U_h\}$, so by the coupling inequality

$$\text{TV}(Q_h, \tilde{P}(\cdot | h)) \leq \Pr[\text{tok}_h(r) \in U_h] = \tilde{P}(U_h | h).$$

Note that this bound holds *whatever* the fallback emits, since the coupling only ever charges the event that the fallback is invoked. The conclusion that Q_h vanishes on U_h , on the other hand, is specific to the rule: every branch emits a self-tokenizing token by construction, so the mass $\tilde{P}(U_h | h)$ is redistributed onto safe tokens rather than merely perturbed. This is why $Q_h \neq \tilde{P}(\cdot | h)$ off U_h as well, which is the channel gap of §5.4. $\square$

PROOF OF THEOREM 5.2. Both P_C and $P_S[M]$ draw the public nonce v and then use the identical deterministic public tape $\text{Pub}(v)$. Fix M and condition on (v, h_0) ; generation is a Markov process on histories. At each step the selector bit comes from the payload in $P_S[M]$ or from public filler in P_C , but by Lemma 5.1 neither choice changes the conditional next-token law Q_{h_i} . Thus the conditional law of T is the same under both hypotheses, and unconditioning gives identical joint laws on (T, v, h_0) . This holds for every M , so $P_S[M] = P_C$; averaging over M gives $P_S = P_C$ and $D(P_C \| P_S) = 0$. $\square$

PROOF OF LEMMA 5.4. T and v are fixed and public, so $\text{Pub} = \text{Pub}(v)$ and $w' = \text{ReadBits}(T, \text{Pub})$ are deterministic and identical for every key: every continuation step either contributes a bit by the non-rejecting rule (observed token equals $i_1 \mapsto 1$, else 0

on an embedding step classified from (h, r_i) alone) or contributes nothing, and the collected bitstring is then zero-padded or truncated to exactly ℓ bits. By (A4), for $K' \neq K$ the stream $ks_A^{K'}$ is uniform on $\{0, 1\}^\ell$ and independent of (Pub, T) (hence of w'), so $\text{seed}'_{K'} = w' \oplus ks_A^{K'}$ is uniform on $\mathcal{S}$. Mutual independence across wrong keys follows from independence of the masks $\{ks_A^{K'}\}$. The true-key statement is decoder correctness on accepted transcripts (at least ℓ payload bits were placed; truncate recovers c). $\square$

PROOF OF THEOREM 5.5. By Lemma 5.4, the joint distribution of (true-key bin = M , wrong-key bins = i.i.d. $\text{dte.dec}(U)$) that A computes from (T, v) is, under (A4), identical to the bin structure of DTE-then-encrypt honey encryption on (p_k, p_m) , except that each wrong-key decoy is $\text{dte.dec}(U)$, within ε of p_m . The true-key bin carries no such gap: by decoder correctness (Prop. B.1) it equals M exactly. Since A inspects at most q (mutually independent) decoy bins, a hybrid replacing each $\text{dte.dec}(U)$ by p_m one bin at a time costs $\leq \varepsilon$ per bin, hence $\leq q\varepsilon$ in total. The [3] bound then gives the first inequality; its optimal-strategy evaluation gives the $\mu + \delta$ form. The $q\varepsilon$ term is the price of goodness against a q -guess adversary and is non-vacuous only for $\varepsilon \ll 1/q$; Remark B derives the resulting constraint on the coder precision. $\square$

B THE PLAINTEXT DTE: PROPERTIES

Throughout, p_m is the *capped* autoregressive plaintext model of §4.1: at every step the next symbol is drawn from $q(\cdot | t_{<i})$ over a truncated support V (the model’s nucleus, further capped at the top K tokens; see below) augmented with EOS carrying mass $p_{\text{EOS}} > 0$ only after length $n_{\min}$, and the draw is forced at step $n_{\max}$. Message space and law are therefore

$$\mathcal{M} = \bigcup_{n=n_{\min}}^{n_{\max}-1} V^n \cup V^{n_{\max}},$$

$$p_m(m) = \left(\prod_{i \leq |m|} q(t_i | t_{<i}) \right) \cdot \begin{cases} q(\text{EOS} | m), & n_{\min} \leq |m| < n_{\max}, \\ 1, & |m| = n_{\max}. \end{cases}$$

That is, $\mathcal{M}$ is the set of *terminated* strings – those closed by an EOS draw after length at least $n_{\min}$, together with every string that reaches the cap – and not the set of all strings of length $\leq n_{\max}$, which would also contain unterminated prefixes and double-count. These are exactly the leaves of the coder’s tree, one per realisation of the sampling process, so $\sum_{m \in \mathcal{M}} p_m(m) = 1$ with no appeal to almost-sure termination.

Two consequences of this definition are worth stating plainly, since both are choices rather than facts about language. First, p_m is the *truncated* model: tokens outside V have probability zero under p_m and the encoder rejects any message containing one. Realism is therefore bounded by how much of the model’s mass V retains, and $|V|$ is what the parameter S of Prop. B.4 bounds. Second, the cap makes long messages impossible rather than merely unlikely, and $n_{\max}$ is small enough in our instantiation ($n_{\max} = 24$) that a substantial fraction of draws reach it; decoys are correspondingly short. Both are limitations of the instantiation, not of the construction, and §6.3 returns to them.

We analyse the coder as implemented, on the integer grid, rather than as real-arithmetic coding followed by rounding: the two differ, and only the former gives exact correctness. Write $T = 2^{b_m}$ and let the seed space be the grid $G = \{0, \dots, 2^\ell - 1\}$. The coder maintains

an integer interval $[lo, hi) \subseteq G$, initially all of G . At a step with quantized arc widths $w_t \geq 1$, $\sum_t w_t = T$, and cumulative sums c_t , token t is assigned

$$\left[lo + \lfloor Rc_t/T \rfloor, lo + \lfloor Rc_{t+1}/T \rfloor \right), \quad R = hi - lo,$$

and the interval for the realized token is retained. Let $J_m \subseteq G$ be the leaf reached by m and $W_m = |J_m|$. Three facts are used below. (F1) At each step the assigned sub-intervals are disjoint and their union is exactly the parent (consecutive boundaries coincide, the first is lo and the last is hi). Since $\mathcal{M}$ is the set of *leaves* – terminated strings, so no J_m contains another – iterating this gives that $\{J_m\}_{m \in \mathcal{M}}$ partitions G exactly: a genuine partition of a finite set, not a partition up to a null set. (Had $\mathcal{M}$ included unterminated prefixes, their intervals would strictly contain their descendants’ and this would fail.) (F2) Every leaf is non-empty. Writing R_k for the interval width after k steps, $\lfloor x \rfloor - \lfloor y \rfloor \geq x - y - 1$ and $w_t \geq 1$ give $R_{k+1} \geq R_k/T - 1$, so unrolling the recurrence,

$$W_m = R_{n_{\max}} \geq \frac{2^\ell}{T^{n_{\max}}} - \sum_{j \geq 0} T^{-j} \geq 2^h - 2, \quad h = \ell - b_m n_{\max},$$

which is ≥ 1 whenever $h \geq 2$; the head-room condition (1) gives $h = 128$ in our instantiation. In particular no sub-interval encountered along the way is empty, so the partition of (F1) is into non-degenerate cells. (F3) Because the seed is uniform on G , the decoder’s induced law is *exactly* $\hat{p}(m) = W_m/2^\ell$, by (F1).

PROPOSITION B.1 (CORRECTNESS). $\text{dte.dec}(\text{dte.enc}(m)) = m$ for every $m \in \mathcal{M}$, with no exceptional set.

PROOF. By (F2) the leaf J_m is non-empty, so $\text{dte.enc}(m)$ returns some $x \in J_m$; it is a grid point by construction, since lo, hi are integers throughout and no rounding of a real is involved. At each step dte.dec retains the unique assigned sub-interval containing x , which by (F1) exists and is unique. The leaves being nested refinements of those sub-intervals, the retained sequence is exactly the token sequence generating J_m , so the decoder emits m and halts at the EOS (or the cap) closing J_m . $\square$

Remark (Why the grid matters). Had dte.enc instead returned the ℓ -bit truncation of a uniform real $x \in [lo_m, hi_m)$, correctness would fail whenever the truncation falls below lo_m and so decodes to the preceding message. That happens for x in an interval of width $< 2^{-\ell}$, giving failure probability at most $2^{-\ell}/p_m(m)$ – a bound that is useless precisely where it matters, since it exceeds 1 once $p_m(m)$ approaches the grid spacing, i.e. exactly for the narrow leaves the cap and the head-room condition are there to control. Sampling a grid point of J_m directly avoids the failure mode altogether, which is why Prop. B.1 is exact and unconditional.

PROPOSITION B.2 (GOODNESS, IDEAL ARITHMETIC). *In the idealization $b_m \rightarrow \infty, \ell \rightarrow \infty$ – exact real arithmetic, U uniform on $[0, 1)$, real leaves I_m of width $p_m(m)$ – we have $\text{dte.dec}(U) \sim p_m$ exactly, so $\varepsilon = 0$.*

PROOF. $\text{dte.dec}(U) = m$ exactly when $U \in I_m$, so by uniformity of U we get $\Pr[\text{dte.dec}(U) = m] = |I_m| = p_m(m)$. The real leaves partition $[0, 1)$ because p_m is supported on $\mathcal{M}$ and widths multiply along the chain, hence $\text{TV}(\text{dte.dec}(U), p_m) = 0$. $\square$

This is the design target; Prop. B.4 bounds the distance from it at finite b_m, ℓ .

PROPOSITION B.3 (UNIFORM SEEDS). *If $m \leftarrow \hat{p}$ then $\text{dte.enc}(m)$ is exactly uniform on $S = G$. Consequently, for the true message distribution $m \leftarrow p_m$, $\text{TV}(\text{dte.enc}(m), \text{Unif}(G)) \leq \text{TV}(p_m, \hat{p}) \leq \varepsilon$.*

PROOF. Conditioned on m , $\text{dte.enc}(m)$ is uniform on the W_m grid points of J_m , so $\Pr[\text{dte.enc}(m) = x \mid m] = 1/W_m$ for $x \in J_m$. Averaging over $m \leftarrow \hat{p}$ and using (F3), for any $x \in G$ with $x \in J_m$ we get $\Pr[\text{dte.enc}(m) = x] = \hat{p}(m)/W_m = (W_m/2^\ell)/W_m = 2^{-\ell}$, and by (F1) every $x \in G$ lies in exactly one leaf; so the law is uniform on G exactly. The second claim is the data-processing inequality: dte.enc is a fixed randomized map, so replacing its input law $\hat{p}$ by p_m moves the output law by at most $\text{TV}(p_m, \hat{p})$, which Prop. B.4 bounds by ε . $\square$

Note that no $O(2^{-\ell})$ correction is needed here: on the grid the seed is uniform on the nose, and the only slack is the same goodness gap $\text{TV}(p_m, \hat{p})$ that ε already denotes.

PROPOSITION B.4 (FINITE PRECISION). *Let S bound the per-step support size and $h = \ell - b_m n_{\max} \geq 2$ the head-room of (1). Then*

$$\begin{aligned} \varepsilon &= \text{TV}(\text{dte.dec}(U), p_m) = \text{TV}(\hat{p}, p_m) \\ &\leq n_{\max} S (2^{-b_m} + 2^{-h}) \\ &= O(n_{\max} S 2^{-b_m}), \end{aligned}$$

and dte.enc never fails and no decode underflows.

PROOF. The first equality is (F3). Two roundings separate $\hat{p}$ from p_m , and we bound each per step and then sum.

Probability quantization. The true conditional $q(\cdot \mid \text{ctx})$ is replaced by $\tilde{q}(t) = w_t/T$ with $w_t \geq 1$ integral and $\sum_t w_t = T$. Truncating each of at most S arcs moves it by less than one unit and the resulting deficit of at most S units is redistributed, so $\sum_t |w_t/T - q(t)| \leq 2S/T$ and $\text{TV}(\tilde{q}, q) \leq S 2^{-b_m}$.

Interval renormalization. Given the parent width R , the width assigned to t is $\lfloor Rc_{t+1}/T \rfloor - \lfloor Rc_t/T \rfloor = R\tilde{q}(t) + \theta_t$ with $|\theta_t| < 1$. The realized conditional is therefore within $1/R$ of $\tilde{q}(t)$ for each of at most S tokens, and by (F2) $R \geq 2^h$ at every step, so this step’s law is within $\text{TV} \leq S 2^{-h}$ of $\tilde{q}$.

Summation. Both chains are driven by the same seed and have length at most $n_{\max}$ almost surely – this is what the cap buys, and it removes any need for an optional-stopping argument over a random horizon. Couple them step by step and hybridize one conditional at a time: the total variation between the two laws of the full token sequence is at most the sum of the at most $n_{\max}$ per-step gaps, each of which is at most $S(2^{-b_m} + 2^{-h})$ by the two paragraphs above. Since $h \gg b_m$ in any sensible parameterization, the quantization term dominates.

Totality. By (F2) every leaf has $W_m \geq 1$, so dte.enc always has a grid point to return and, by Prop. B.1, every decode of a grid point terminates at EOS or at the cap within $n_{\max}$ steps. Seed exhaustion is therefore impossible, with probability exactly 0 rather than merely small. $\square$

Remark (Termination must be symmetric, or it is a correct-key oracle). Two malformedness channels could in principle flag a bin as a wrong-key decoy. *Underflow* is impossible on either side, by

the totality clause of Prop. B.4: under (1) every grid point decodes to a well-formed element of $\mathcal{M}$, so a decoy bin is never malformed in this sense. *Cap-termination* is subtler, and the subtlety is easy to implement wrongly.

At the level of the model, a $(1 - p_{\text{EOS}})^{n_{\text{max}} - n_{\text{min}}}$ fraction of decodes end at the cap rather than at a sampled EOS – conspicuously many $(0.94)^{14} \approx 42\%$ at the neural instantiation’s $p_{\text{EOS}} = 0.06$, $n_{\text{min}} = 10$, $n_{\text{max}} = 24$). This alone is harmless, because it is a property of p_m rather than of the key: the true message, drawn from p_m by hypothesis, exhibits it at exactly the same rate as every decoy. It is a *realism* gap, weakening the claim that p_m resembles human plaintext (the caveat of §6.2), not a bin distinguisher.

What is *not* harmless is an encoder and decoder that disagree about how a cap-length message terminates. The definition of $\mathcal{M}$ above makes $m \in V^{n_{\text{max}}}$ a leaf reached by exhaustion, with no EOS arc consumed. An encoder that instead appends EOS unconditionally lands in a strict sub-arc of that leaf, of relative width p_{EOS} . The decoder still returns m , so round-trip tests pass; but an interrogator holding the ciphertext can decode under a guessed key, recompute the sub-arc, and test membership – succeeding with probability 1 under the true key and p_{EOS} under a wrong one. That is a message-recovery oracle on the cap-length fraction of traffic, and it defeats Theorem 5.5 without violating correctness. Our implementation contained exactly this bug; we detected it only by testing *leaf agreement* – that a uniform seed lies in the encoder’s interval for the message it decoded to – rather than round-tripping alone, and both harnesses now assert it. We flag it because the failure is invisible to the tests a DTE implementation would naturally be given.

Remark (Choosing b_m). Theorem 5.5 charges $q\epsilon$, so a deployment targeting q offline guesses needs

$$b_m \gtrsim \log_2 q + \log_2(n_{\text{max}}S),$$

a constraint the DTE literature does not usually surface, because it only bites once goodness is multiplied by a guess budget. Two things follow, and they determine our parameters.

First, S must be bounded *by construction*, not by hope. Nucleus truncation alone does not do this: at $\rho = 0.90$ the support of DistilGPT-2 is 4300 tokens at the first step (the prompt-free distribution is near-flat) and we have measured it as large as 8836 mid-sequence. Taken at those values the bound of Prop. B.4 gives ϵ of order 10^{-1} , which is vacuous by the tenth guess. We therefore cap the support at the top $K = 256$ tokens after nucleus truncation, so $S \leq K + 1 = 257$ holds identically; the harness asserts that no observed support exceeds this static bound and reports the observed maximum only as a descriptive statistic.

Second, b_m and n_{max} trade against ℓ through the head-room condition (1). Our instantiation takes $b_m = 32$, $n_{\text{max}} = 24$, $\ell = 896$, so $h = 128 \geq 2$ and

$$\epsilon \leq n_{\text{max}}S(2^{-b_m} + 2^{-h}) \leq 1.4 \times 10^{-6},$$

non-vacuous ($q\epsilon \leq 0.1$) for any q up to 7×10^4 – a demo-scale budget, not a claim of deployment-grade offline resistance without a concrete p_k , μ , and adversary parallelism. That is a real but modest margin, and we state it rather than the round numbers a larger b_m would give, because b_m is not free here: $h = \ell - b_m n_{\text{max}} \geq 2$

means $b_m = 64$ at $n_{\text{max}} = 24$ forces $\ell \geq 1538$, and ℓ is the payload the cover channel must carry. At the 0.94 bits per token of §6.1 that is over 1600 cover tokens, past GPT-2’s 1024-token context; $\ell = 896$ is around 950 tokens and fits. The binding constraint on this construction is therefore not arithmetic precision, which is indeed almost free, but the *capacity of the cover channel* needed to carry a seed long enough to support that precision. A larger-context cover model relaxes it directly.

REFERENCES

- [1] C. Cachin. An Information-Theoretic Model for Steganography. *Information and Computation*, 192(1):41–56, 2004 (prelim. IH 1998).
- [2] N. Hopper, J. Langford, and L. von Ahn. Provably Secure Steganography. In *CRYPTO 2002*, LNCS 2442, pp. 77–92.
- [3] A. Juels and T. Ristenpart. Honey Encryption: Security Beyond the Brute-Force Bound. In *EUROCRYPT 2014*, LNCS 8441, pp. 293–310.
- [4] R. Chatterjee, J. Bonneau, A. Juels, and T. Ristenpart. Cracking-Resistant Password Vaults Using Natural Language Encoders. In *IEEE S&P*, 2015, pp. 481–498.
- [5] J. Ding, K. Chen, Y. Wang, N. Zhao, W. Zhang, and N. Yu. Discop: Provably Secure Steganography in Practice Based on Distribution Copies. In *IEEE S&P*, 2023, pp. 2238–2255.
- [6] G. Kaptchuk, T. M. Jois, M. Green, and A. D. Rubin. Meteor: Cryptographically Secure Steganography for Realistic Distributions. In *ACM CCS*, 2021, pp. 1529–1548.
- [7] P. Wayner. Mimic Functions. *Cryptologia*, 16(3):193–214, 1992.
- [8] R. Canetti, C. Dwork, M. Naor, and R. Ostrovsky. Deniable Encryption. In *CRYPTO 1997*, LNCS 1294, pp. 90–104.
- [9] A. O’Neill, C. Peikert, and B. Waters. Bi-Deniable Public-Key Encryption. In *CRYPTO 2011*, LNCS 6841, pp. 521–542.
- [10] R. Anderson, R. Needham, and A. Shamir. The Steganographic File System. In *Information Hiding (IH 1998)*, LNCS 1525, pp. 73–82.
- [11] E.-O. Blass, T. Mayberry, G. Noubir, and K. Onarlioglu. Toward Robust Hidden Volumes Using Write-Only Oblivious RAM. In *ACM CCS*, 2014, pp. 203–214.
- [12] M. Golla, B. Beuscher, and M. Dürmuth. On the Security of Cracking-Resistant Password Vaults. In *ACM CCS*, 2016, pp. 1230–1241.
- [13] J. Jaeger, T. Ristenpart, and Q. Tang. Honey Encryption Beyond Message Recovery Security. In *EUROCRYPT 2016*, LNCS 9665, pp. 758–788.
- [14] C. Schroeder de Witt, S. Sokota, J. Z. Kolter, J. Foerster, and M. Strohmaier. Perfectly Secure Steganography Using Minimum Entropy Coupling. In *ICLR*, 2023.
- [15] Z. M. Ziegler, Y. Deng, and A. M. Rush. Neural Linguistic Steganography. In *EMNLP-IJCNLP*, 2019, pp. 1210–1215.
- [16] M. Bai, J. Yang, K. Pang, H. Wang, and Y. Huang. Towards Next-Generation Steganalysis: LLMs Unleash the Power of Detecting Steganography. *arXiv:2405.09090*, 2024.
- [17] L. von Ahn and N. J. Hopper. Public-Key Steganography. In *EUROCRYPT 2004*, LNCS 3027, pp. 323–341.
- [18] A. D. Ker. Batch Steganography and Pooled Steganalysis. In *Information Hiding (IH 2006)*, LNCS 4437, pp. 265–281.
- [19] A. D. Ker, T. Pevný, J. Kodovský, and J. Fridrich. The Square Root Law of Steganographic Capacity. In *Proc. ACM Workshop on Multimedia and Security (MM&Sec)*, 2008, pp. 107–116.
- [20] M. Bellare, T. Ristenpart, P. Rogaway, and T. Stegers. Format-Preserving Encryption. In *Selected Areas in Cryptography (SAC 2009)*, LNCS 5867, pp. 295–312.
- [21] K. P. Dyer, S. E. Coull, T. Ristenpart, and T. Shrimpton. Protocol Misidentification Made Easy with Format-Transforming Encryption. In *ACM CCS*, 2013, pp. 61–72.