1 Shape Optimization of a Photo Gun

1.1 Geometry

- initial geometry in Figure 1
- corresponding electric field for $p = 3$, $n_{\text{sub}} = 16$, $V_{\text{el}} = -300$ kV and $V_{\text{ar}} = 1$ kV



Figure 1: Initial geometry and magnitude of electric field.

1.2 Optimization

- optimized geometry in Figure 2
- corresponding electric field for $p = 3$, $n_{\text{sub}} = 16$, $V_{\text{el}} = -300$ kV and $V_{\text{ar}} = 1$ kV
- cost function employs $I = \{14, \ldots, 19\}$
- **results**:

	$(V_{\text{el}} - 625)$ in cm^3	$\frac{1}{\lvert I\rvert}\sum_{i\in I}\max_{\mathbf{x}\in\Omega_i}\lVert\mathbf{E}(\mathbf{x})\rVert_2$ in $\frac{\text{MV}}{\text{m}}$	$\max_{\mathbf{x}\in\Omega}\lVert\mathbf{E}(\mathbf{x})\rVert_2$ in $\frac{\text{MV}}{\text{m}}$
initial	2.458	7.858	9.272
optimized	-55.532	6.625	7.318



Figure 2: Optimized geometry and electric field.

1.3 Tracking

- **general settings**: $Q = 100$ fC
- **spatial distribution**: generated from measurement, see Figure **??** for comparison with laser measurement
- **temporal distribution**: Gaussian with $\sigma = 5$ ps (model from thesis requires additional data about cathode in use and measurement for comparison, measurement alone could work analogous to spatial case)



Figure 3: Spatial distribution generated from measurement (2^{10} particles) and laser measurement.



Figure 4: Spatial distribution from Gaussian ($\sigma = 400$ μm) and temporal distribution (2^{10} particles).

- **convergence of time integrator**: relative error of normalized transverse emmitance ϵ w. r. t. finest time step is shown in Figure **??**
- computed with $n_x = n_y = 8$ and $n_z = 256$
- $H = 2^{-12}$ ns used later on



Figure 5: Normalized transverse emmitance and relative error in l_∞-norm.

- **convergence of field map**: look at convergence with number of grid points in transverse (n_x, n_y) and longitudinal (n_z) direction individually
- Figure **??** looks at convergence of n_x, n_y for $n_z = 64$
- Figure **??** looks at convergence of n_z for $n_x = n_y = 8$
- $n_x = n_y = 8$ and $n_z = 256$ used for convergence studies
- $n_x = n_y = 16$ and $n_z = 256$ used for actual simulation (actual distribution is larger by more then a factor 2, see Figure **??**)



Figure 6: Normalized transverse emmitance and relative error in l_∞-norm for $n_z = 64$ and $n_x = n_y$ variable.



Figure 7: Normalized transverse emmitance and relative error in l_∞-norm for n_z variable and $n_x = n_y = 8$.

- **convergence of space charge**: look at convergence with number of grid cells in radial (n_r) and longitudinal (n_l) direction and number of particles (n_I) separately
- Figure **??** looks at convergence of n_r, n_l for $n_I = 2^{10}$
- $n_r = n_l = 64$ used later on
- Figure **??** looks at convergence of n_I for $n_r = n_l = 64$
- $n_I = 2^{11}$ used later on



Figure 8: Normalized transverse emmitance and relative error in l_∞-norm for $n_I = 2^{10}$ and n_l, n_r variable.



Figure 9: Normalized transverse emmitance and relative error in l_∞-norm for n_I variable and $n_l = n_r = 64$.

References

[1] Markus Wagner. “Production and investigation of pulsed electron beams at the S-DALINAC”. PhD thesis. Technische Universität Darmstadt, 2013.