

# Efficient gate-set extensions for fault-tolerant qudit quantum computation

George T. Fleming,<sup>1</sup> Henry Lamm<sup>1,\*</sup>, Karla Tame-Narvaez,<sup>1</sup> and Peter Vander Griend<sup>1,2</sup>

<sup>1</sup>*Fermi National Accelerator Laboratory, Batavia, IL 60510, USA*

<sup>2</sup>*Department of Physics and Astronomy, University of Kentucky, Lexington, KY 40506, USA*

(Dated: April 14, 2026)

Fault-tolerant quantum computation requires a finite universal gate set whose members have cheap physical realizations. We introduce SWIFTBOT, an agentic workflow that numerically ranks finite subgroups of  $SU(d)$  extended by a single qudit gate, using the Quantum Circuit Overhead  $Q_T$  as the figure of merit. At  $d = 3$  we produce the first systematic  $Q_T$  ranking across three  $\Sigma$ -series subgroups, finding that Haar-random extensions on the largest approach the Kesten–McKay floor within 32%, while structured diagonal and Howard–Vala extensions sit factors of 3–70 above it. Applied to gate sets relevant for lattice-gauge theory simulation, a non-canonical rational-phase extension delivers  $6.8\times$  lower mean synthesis depth than canonical Clifford+ $T$ , demonstrating that the best general-purpose extension and the best target-specific extension can differ by nearly an order of magnitude. The pipeline, registered groups, fault-tolerance catalog, and reproduction data are released with the paper.

## I. INTRODUCTION

Fault-tolerant quantum computation requires a finite universal gate set whose members have cheap physical realizations. The tension between these requirements is sharp: the Eastin–Knill theorem [1] forbids any nontrivial stabilizer code from admitting a universal *transversal* gate set. Practical designs therefore split the gate set into a transversal subgroup  $\mathcal{C} \subset SU(d)$  (usually a finite subgroup the error-correcting code protects cheaply) and one or more non-transversal extension gates  $g$  made fault-tolerant by magic-state distillation [2, 3] or by code switching between codes with complementary transversal structure. Each extension gate  $g$  comes with its own cost: a dedicated magic state, a code that supports it transversally, a distillation protocol, or some combination of the three.

*Why qudits.* The qubit version of this story is well-developed but increasingly constrained: Eastin–Knill rules out any universal transversal stabilizer construction, and the best-known bypass—magic-state distillation (MSD) of  $T$  on Clifford+ $T$ —is the overhead bottleneck of every qubit fault-tolerance resource estimate. Three trends have shifted the qudit calculus.

*Hardware.* Qudit platforms natively expose higher-dimensional registers [4, 5]: superconducting cavities with the coherence budget for multi-level encodings [6], HEP-motivated bosonic  $2T$ -quoctit proposals [7], trapped-ion  $d$ -level systems, and solid-state spin- $S$  qudits all avoid the binary-encoding overhead that qubits impose on inherently higher- $d$  physics.

*Lattice gauge.* Discrete-subgroup approximations of  $SU(N)$  gauge theories live on  $|\mathcal{C}|$ -dimensional per-link registers that fit qudit architectures natively:  $|\Sigma(36\times 3)| = 108$  states per link, encoded on three qutrits plus two qubits [8, 9]. Native-qudit QEC constructions on trun-

cated  $\mathbb{Z}_N$  gauge theories are in active development [10], and trapped-ion realizations of  $U(1)$  and  $SU(2)$  gauge dynamics already use native qudits [11, 12].

*Distillation and codes.* Qutrit triorthogonal distillation [13, 14] reaches  $\gamma \approx 1.51$ , beating qubit triorthogonal codes below  $\sim 300$  physical qudits; Gottesman’s prime- $d$  stabilizer construction [15] spelled out the foundational split. Beyond-stabilizer constructions — the *nonadditive* Kubichta  $((7, 2, 3))_{2I}$  code [16] and Denys–Leverrier *covariant*  $2T/2O$  codes [17, 18] — sidestep the Anderson–Jochym–O’Connor qubit-stabilizer no-go [19] via transversal non-Clifford groups. Non-local qLDPC memories such as the Bravyi *et al.* bivariate-bicycle code [20] need connectivity graphs whose natural hardware substrates — reconfigurable neutral atoms [21], ion-chain shuttling, multimode cavities — are the same platforms that expose multiple levels per site, making qudit qLDPC codes [22, 23] a natural convergence.

*qLDPC codes are qudit codes.* A second, more structural argument sharpens the qLDPC–qudit convergence. A  $[[n, k, d]]$  qLDPC code like the  $[[144, 12, 12]]$  gross code [20] encodes  $k$  logical qubits, but the gate set accessible *transversally* or through fold-transversal code automorphisms typically is *not* the product group  $\text{Clifford}(2)^{\otimes k}$ : Eberhardt and Steffan show explicitly that the fold-transversal Cliffords of bivariate bicycle codes act collectively on the logical qubits [24]; Sayginel *et al.* frame the general construction as code-automorphism-to-logical-gate [25]; and Malcolm *et al.* quantify the cost of accessing the remaining logical Cliffords via syndrome-extraction overhead [26]. The natural description of the gross code is therefore as a single  $qu-2^k$ -it whose accessible gate set  $\mathcal{C}$  is a finite subgroup of  $SU(2^k)$ ; the “missing” logical Clifford generators are the non-transversal extensions  $g$ . That is precisely the  $(\mathcal{C}, g)$  ranking problem we formalise below, only at  $d = 2^k$  instead of  $d \in \{2, 3, 4\}$ —so the framework of this paper applies directly to qLDPC fault-tolerance, with the  $Q_T$  figure of merit giving a quantitative answer to “which non-transversal extension should we compile to?” for a given qLDPC architecture.

\* hlammm@fnal.gov

The qudit landscape is therefore not just a technical variant of the qubit one; it is where several of the design bottlenecks of qubit fault-tolerance do not apply.

On qubits the standard gate-set choice has a standard resolution. Clifford+ $T$  [2, 27] pairs the Clifford group with  $T = \text{diag}(1, e^{i\pi/4})$ ; Clifford gates are transversal on the Steane, Reed–Muller, and Bravyi–Haah families, and  $T$  is distilled via Bravyi–Kitaev [2] or Bravyi–Haah [3]. Ross–Selinger [28] and Kliuchnikov–Maslov–Mosca [29] make single-qubit synthesis into Clifford+ $T$  a solved problem with certified  $T$ -count bounds. For  $d = 2$  the choice of gate set is effectively fixed.

No comparable consensus exists at  $d > 2$ . Howard and Vala [30] proposed a three-parameter family  $\text{HV}(z, \gamma, \varepsilon)$  of qudit  $T$ -gates at prime  $d$ , but no systematic comparison of members has been done. The qudit finite-subgroup landscape is known [31–35], transversal-gate classifications for stabilizer codes have been cataloged [19], Campbell–Anwar–Browne give prime- $d$  distillation protocols [13], Bocharov, Roetteler, and Svore [36] studied qutrit synthesis for Shor-class algorithms, and Gustafson *et al.* [37] recently extended Ross–Selinger-style exact synthesis to Clifford+ $R$  at  $d = 3$ . What is missing is a quantitative ranking: given a base group  $\mathcal{C}$  and an extension  $g$ , how efficiently does  $(\mathcal{C}, g)$  synthesize target unitaries?

Slowik, Dulián, and Sawicki [38] supplied the right figure of merit. The *Quantum Circuit Overhead*  $Q_T(\mathcal{C}, g)$  is the asymptotic exponent in the word length of an  $\varepsilon$ -accurate approximation: the number of gates scales as  $(1/\varepsilon)^{Q_T}$ , bounded below by the Kesten–McKay optimum  $Q_{\text{opt}}$  and saturated by the “golden gates” of Sarnak [39].

This paper uses  $Q_T$  to rank candidates. We introduce SWIFTBOT, an agentic workflow that enumerates  $(\mathcal{C}, g)$  pairs at  $d = 2, 3, 4$ , screens each for universality via Sawicki’s criterion, evaluates  $Q_T$  numerically [38], and cross-references surviving pairs against a curated fault-tolerance catalog.

We make three contributions. First, at  $d = 2$  we reproduce the Slowik *et al.* numerics at the percent level (Section IV). Second, we establish the first paper-scale  $Q_T$  ranking at  $d = 3$  across the three irreducible-adjoint  $\Sigma$ -series subgroups with  $|\mathcal{C}| \in \{216, 648, 1080\}$ , using Howard–Vala, rational-phase, and Haar-random extensions (Section V). Third, applied to a gate set relevant for discrete-subgroup lattice gauge simulation [7, 8, 40], a non-canonical rational-phase extension beats Clifford+ $T$  by  $6.8\times$  in mean synthesis depth (Section VI); both rows use qubit Clifford bases, so the advantage is purely an extension-choice effect, not a qubit-vs-qudit encoding claim. Together these show that the best general-purpose extension and the best target-specific extension can differ by nearly an order of magnitude—a distinction invisible when  $Q_T$  alone is reported.

Code and data are released with this paper [41]. Section II reviews the QCO framework, Section III sketches the pipeline, Sections IV to VI present the results, and Section VII closes with a fault-tolerance audit and open problems.

## II. BACKGROUND

We briefly review the three ingredients used throughout: the Quantum Circuit Overhead  $Q_T$  [38] as our primary figure of merit, the Sawicki criterion [42] for ruling out non-universal extensions without running QCO, and the Howard–Vala family [30] and discrete-subgroup-approximation (DSA) primitive-gate series [8, 40] as the principal sources of candidate extensions at  $d \geq 3$ .

### II.1. $\delta$ -approximate $t$ -designs and $Q_T$

Let  $\mathcal{S} = \mathcal{C} \cup \mathcal{C}^{-1} \cup \{g, g^{-1}\} \subset \text{SU}(d)$  be a symmetric generating set consisting of a finite subgroup  $\mathcal{C}$  and a single extension  $g$ . Consider the  $t$ -design operator on the  $t$ -th tensor power of the defining representation,

$$T_t(\mathcal{S}) = \frac{1}{|\mathcal{S}|} \sum_{s \in \mathcal{S}} \pi_t(s), \quad \pi_t = \bigoplus_{\lambda \in \Lambda_t} \pi_\lambda^{\oplus m_\lambda}, \quad (1)$$

where  $\Lambda_t$  is the set of  $\text{SU}(d)$  highest weights that appear in the decomposition of  $(\mathbb{C}^d)^{\otimes t} \otimes (\mathbb{C}^d)^{* \otimes t}$  and  $\pi_\lambda$  is the associated irreducible representation. The  $t$ -design spectral radius is

$$\delta_t(\mathcal{S}) = \max_{\lambda \in \Lambda_t \setminus \{0\}} \|T_t(\mathcal{S})\|_{\pi_\lambda}, \quad (2)$$

the largest spectral norm across non-trivial irreps. A smaller  $\delta_t$  means the random walk generated by  $\mathcal{S}$  equidistributes faster on  $\text{SU}(d)$ .

For an  $\varepsilon$ -net of  $\text{SU}(d)$  in the operator norm, Slowik *et al.* [38] show that the number of Solovay–Kitaev-style words required scales as  $(1/\varepsilon)^{Q_T}$ , with

$$Q_T(\mathcal{S}) = \frac{\log |\mathcal{C}|}{\log(\delta_t^{-1}(\mathcal{S}))}, \quad (3)$$

in the limit  $t \rightarrow \infty$ . The Kesten–McKay bound for a  $k$ -regular Cayley graph gives, in the  $|\mathcal{C}| \rightarrow \infty$  asymptotic we use throughout,

$$\delta_t \geq \delta_{\text{opt}} = \frac{2\sqrt{|\mathcal{C}| - 1}}{|\mathcal{C}|}, \quad (4)$$

and therefore

$$Q_T \geq Q_{\text{opt}} = \frac{\log |\mathcal{C}|}{\log(1/\delta_{\text{opt}})}, \quad (5)$$

with equality for “golden gates” [39]. Representative values used as baselines in Sections IV and V:  $Q_{\text{opt}} \approx 3.47$  for the qubit Clifford group, 4.19 for the projective  $A_4 \subset \text{PU}(2)$  (registered as *hurwitz*), 2.81 for the binary icosahedral group  $2I$  (BI), and 2.69 for the smallest  $d = 3$   $\Sigma$ -series group  $\Sigma(72 \times 3)$ .

In practice  $Q_T$  is estimated at finite  $t$  by sampling the ensemble in Eq. (1) with a Monte-Carlo extension gate  $g$  (the *rnd* baseline) or a deterministic one, then evaluating

Eq. (2) via sparse spectral decomposition on each irrep of  $\pi_t$ . The feasibility ceiling at  $d = 3$  is set by representation dimensions [38]: the largest irrep at  $t = 50$  has dimension  $\sim 10^5$ , whereas  $t = 15$  peaks at  $\sim 4 \times 10^3$  and is tractable. Throughout this work we take  $t$  large enough that the estimate of  $Q_T$  has stabilised within a few percent, and we quote  $Q_{\text{opt}}$  alongside  $Q_T$  to expose the gap to optimality.

## II.2. Pre-screening with the Sawicki criterion

Not every candidate extension needs a QCO run. Sawicki and Karnas [42] proved that  $\mathcal{S}$  generates a dense subgroup of  $\text{SU}(d)$  if and only if

- (i) the adjoint representation of  $\mathcal{S}$  is irreducible, and
- (ii)  $\langle \mathcal{S} \rangle$  — the subgroup generated by  $\mathcal{S}$  — is not contained in any finite subgroup of  $\text{SU}(d)$  (checked against the Blichfeldt classification caps).

Let  $\text{Comm}(\text{Ad}_{\mathcal{C}})$  denote the space of complex matrices that commute with every  $\text{Ad}_c$  for  $c \in \mathcal{C}$ ; its dimension is 1 if and only if the adjoint representation of  $\mathcal{C}$  is irreducible. Condition (i) is then checkable in  $\mathcal{O}(d^2)$  memory via Schur’s orthogonality relation,

$$\dim \text{Comm}(\text{Ad}_{\mathcal{C}}) = \frac{1}{|\mathcal{C}|} \sum_{c \in \mathcal{C}} |\chi_{\text{Ad}}(c)|^2, \quad (6)$$

where  $\chi_{\text{Ad}}(c) = \text{tr } \text{Ad}_c$ . A value  $> 1$  means the adjoint splits, and no extension preserving that splitting can be universal. This immediately excludes from consideration, e.g.,  $\Sigma(36 \times 3)$  (the 108-element crystallographic group), the 60-element simple group  $\Sigma(60) \simeq A_5$ , and the  $s_{60 \times 4}$  family at  $d = 3$ , since any diagonal extension preserves the reducible-adjoint structure. Condition (ii) is enforced at finite cost by running a bounded closure  $\langle \mathcal{S} \rangle \cap \text{Cap}(n)$  against the classification of finite subgroups of  $\text{SU}(d)$  (orders  $\leq 120$  at  $d = 2$ ,  $\leq 1080$  at  $d = 3$ ,  $\leq 5040$  at  $d = 4$ ) [31–35]; we use cap sizes  $n = 120, 1080, 5040$  respectively. An extension is flagged **finite** if closure terminates below the cap, **universal\_likely** if closure survives the cap and condition (i) holds, and **infinite\_but\_not\_dense** if condition (i) fails but closure is open.

## II.3. Candidate extensions

At  $d = 2$  the canonical extension is  $T = P(\pi/4) = \text{diag}(1, e^{i\pi/4})$ , giving the Clifford+ $T$  set with certified synthesis via Ross–Selinger [28] and Kliuchnikov–Maslov–Mosca [29]. We also consider diagonal  $P(\theta)$  for  $\theta \in \{\pi/8, 2\pi/9, \pi/9, \pi/18\}$ , the Parzanchevski–Sarnak supergolden gates [43], and Haar-random extensions.

At prime  $d$  the Howard–Vala family [30] generalizes  $T$  via three integers  $(z, \gamma, \varepsilon) \in \mathbb{Z}_d^3$ . At  $d = 3$  — the only dimension used in our survey — the  $\det = 1$  condition

requires a global  $\omega^{1/3}$  twist, so the diagonal entries live on 9th (not 3rd) roots of unity [30, Eq. 27]:

$$\text{HV}(z, \gamma, \varepsilon) = \mathcal{N} \cdot \text{diag}(1, \zeta_9^{v_1}, \zeta_9^{v_2}), \quad (7)$$

with  $\zeta_9 = e^{2\pi i/9}$ ,  $v_1 = (6z + 2\gamma + 3\varepsilon) \bmod 9$ ,  $v_2 = (6z + \gamma + 6\varepsilon) \bmod 9$ , and  $\mathcal{N}$  a phase fixing  $\det \text{HV}(z, \gamma, \varepsilon) = 1$ . (For primes  $p > 3$  the base root is  $\zeta_p$  and  $v_k$  is the cubic-in- $k$  recurrence solution  $v_k = (k/12) [\gamma + k(6z + (2k-3)\gamma)] + k\varepsilon \pmod{p}$  [30, Eq. 24].) Our panel uses  $(z, \gamma, \varepsilon) \in \{(1, 1, 0), (1, 2, 0), (2, 1, 0)\}$ : the first is Campbell’s magic gate [13], the second is the Howard–Vala Eq. (27) variant (Clifford-equivalent to the first at  $d = 3$  [30] — hence identical  $\delta$  in Table II), and the third is a non-Clifford-equivalent orbit. The full group  $\{U_v\}$  at  $d = 3$  factorizes as  $\mathbb{Z}_9 \times \mathbb{Z}_3$  modulo phases [30, Eq. 35]; these three samples cover two of the Clifford-equivalence orbits.

In addition to the Haar-uniform extensions above, discrete-subgroup approximations of lattice gauge simulations [8, 40, 44] pick out a *structured* set of target unitaries that the chosen extension must synthesize cheaply. For each qudit group, the continuous degree of freedom reduces to a trace rotation  $U_{\text{Tr}}(\theta)$  that decomposes into a finite set of  $R_Z(\alpha_c \theta)$  rotations whose coefficients  $\alpha_c$  depend on the specific subgroup and encoding. This motivates a *target-family* figure of merit: the mean breadth-first-search depth to synthesize the required  $R_Z$  rotations within  $\varepsilon \leq 10^{-2}$ . We instantiate it for one specific subgroup in Section VI.

## III. SWIFTBOT PIPELINE

SWIFTBOT is a five-stage agentic pipeline built around the QCO kernel of [38]. Numerical stages are deterministic; an LLM supervisor intervenes only at stage boundaries to rank candidates, propose extensions, and decide when to stop. All headline numbers below come from deterministic panels that bypass the LLM; the agent is used for exploratory search not reported here. Full code and a command-line driver are released with the paper [41].

*Stage 1 (group registration)* computes projective closures  $\langle \mathcal{G} \rangle \subset \text{SU}(d)/Z(\text{SU}(d))$  from seed unitaries and stores each group under a content-addressable key. The registry covers the canonical  $d \in \{2, 3, 4\}$  subgroups used here: Pauli–Clifford, the projective  $A_4 \subset \text{PU}(2)$  (registered as **hurwitz**), and  $2I$  (BI) at  $d = 2$ ; the  $\Sigma(m \times 3)$  series for  $m \in \{36, 72, 216, 360\}$  at  $d = 3$ ; and selected Fairbairn subgroups at  $d = 4$ .

*Stage 2 (universality screen)* evaluates  $\dim \text{Comm}(\text{Ad}_{\mathcal{C}})$  via Eq. (6) and runs a bounded closure against the classification caps  $\{120, 1080, 5040\}$  [31–35]. Pairs whose closure terminates below cap are tagged **finite** and skipped; reducible-adjoint pairs are tagged diagnostically.

*Stage 3 (QCO numerics)* invokes the kernel of [38] as a subprocess. Two optimizations help: (i) every gate has the form  $gcg^\dagger$  with  $c \in \mathcal{C}$ , so  $\pi_\lambda(gcg^\dagger) = \pi_\lambda(g)\pi_\lambda(c)\pi_\lambda(g)^\dagger$  replaces  $|\mathcal{C}|$  exponentials with one; (ii) the  $\pi_\lambda(c)$  lists are

persisted to disk keyed by a fingerprint of  $\mathcal{C}$  and the highest weight  $\lambda$ . Together these give  $3\text{--}6\times$  speedup at  $d = 3$ . Results are stored as per-sample **QTRecords** in a SQLite cache with full provenance.

*Stages 4–5 (fault-tolerance)* match each surviving  $(\mathcal{C}, g)$  against a curated catalog of QEC codes (Steane, Reed–Muller, Bravyi–Haah, Kubischta 2I, qutrit triorthogonal, ternary Golay, Pollatsek–Ruskai PI, Kubischta–Teixeira PI, and more) and distillation protocols (Bravyi–Kitaev, Bravyi–Haah, Campbell–Anwar–Browne, programmable MSD, Ouyang–Jing–Brennen (OJB) code-switching). The catalog is curated for tractability, not exhaustive; Hastings–Haah sublogarithmic-overhead codes [45] and the full Litinski resource landscape [46] are notable out-of-scope omissions that would be natural additions. Unmatched pairs return a *research-needed* marker with an EC Zoo [47] pointer rather than guessing.

#### IV. VALIDATION AT $d = 2$

We validate the SWIFTBOT QCO kernel against the  $d = 2$  reference dataset of Słowik, Dulián, and Sawicki [38] on two qubit bases: the Clifford group ( $|\mathcal{C}| = 24$ ) and the 12-element projective  $A_4 \subset \text{PU}(2)$  (registered **hurwitz**), each paired with  $P(\pi/4)$  and with Haar-random extensions. We also run a paper-scale  $10^4$ -sample Haar search on the binary icosahedral group  $2I$  (BI,  $|\mathcal{C}| = 120$ ), which carries the Kubischta nonadditive transversal code [16]. All runs are at  $t = 50$ , matching the reference. A zeroth-order check—replaying the  $\delta$ -parser on all 5050 rows of the reference file and recomputing  $Q_T$ —matches the reference to  $\mathcal{O}(10^{-15})$ , isolating any later disagreement to the spectral kernel. Headline results are summarized in Table I: Clifford+ $P(\pi/4)$  yields  $Q_T = 51.9$  (reference  $\approx 52$ ); Haar-random extensions agree at the few-percent level.

*Two remarks.* First, Clifford+ $T$  has  $Q_T$  roughly  $14\times$  larger than Haar-random (51.9 vs 3.79)—i.e. its approximation-exponent overhead is worse by an order of magnitude; commensurability between  $P(\pi/4)$  and the Clifford orbit slows the Haar random walk [38]. This is a  $Q_T$  claim, not a verdict on Clifford+ $T$  itself: when the target is structured (Section VI), the ranking inverts. Second, the BI ratio  $Q_T/Q_{\text{opt}} \approx 1.27$  at  $10^4$  samples is far closer to saturation than Clifford’s and arrives with a cataloged fault-tolerant code [16]; the empirical  $\delta$  distribution on BI has median 0.38 ( $Q_T \simeq 4.97$ ) and 5th-percentile 0.31, and a 2000-resample bootstrap on the best-of- $10^4$   $Q_T$  gives a tight 95% CI of [3.57, 3.69]. The best-of- $10^4$  floor is the natural super-golden candidate predicted by [39].

#### V. $d = 3$ SURVEY

With the SWIFTBOT kernel validated at  $d = 2$  (Section IV), we turn to the first paper-scale  $Q_T$  ranking at  $d = 3$ . The survey covers the three irreducible-adjoint

TABLE I.  $d = 2$  validation of the SWIFTBOT QCO kernel against the reference dataset of Słowik, Dulián, and Sawicki [38], all at  $t = 50$ . The Clifford+ $P(\pi/4)$  row is deterministic; rnd rows report the best  $Q_T$  across 20 Haar-SU(2) samples for Clifford and **hurwitz**, and  $10^4$  samples for BI.  $Q_{\text{opt}}$  is the Kesten–McKay floor of Eq. (5); BI has no published QCO reference.

| Base ( $ \mathcal{C} $ ) | Ext.       | $Q_T$     |               | $Q_{\text{opt}}$ |
|--------------------------|------------|-----------|---------------|------------------|
|                          |            | this work | [38]          |                  |
| Clifford (24)            | $P(\pi/4)$ | 51.91     | $\approx 52$  | 3.47             |
| Clifford (24)            | rnd        | 3.79      | $\approx 3.7$ | 3.47             |
| <b>hurwitz</b> (12)      | rnd        | 4.34      | $\approx 4.0$ | 4.19             |
| BI (120)                 | rnd        | 3.57      | —             | 2.81             |

$\Sigma$ -series subgroups of SU(3)— $\Sigma(72 \times 3)$ ,  $\Sigma(216 \times 3)$ , and  $\Sigma(360 \times 3)$ —each extended by a common panel of eight candidate gates. (We use the  $\Sigma(m \times 3)$  notation of [32, 35], where  $|\Sigma(m \times 3)| = 3m$ ; the three bases thus have orders 216, 648, 1080.) The adjoints are irreducible—the 8-dimensional  $\text{su}(3)$  representation does not split—by the character tables of [35]. The smaller groups  $\Sigma(36 \times 3)$  (the 108-element crystallographic Valentiner analogue) and  $\Sigma(60) \simeq A_5$  both have reducible adjoint at  $d = 3$ : the 8-dimensional  $\text{su}(3)$  representation splits into smaller irreps of the subgroup, as can be read directly from the character tables [35] or verified via Eq. (6) with  $\dim \text{Comm}(\text{Ad}_{\mathcal{C}}) > 1$ . They are excluded at Stage 2 of the pipeline: no extension preserving the invariant subspace structure of  $\text{su}(3)$  can render them universal, so their  $Q_T$  is formally divergent [42].

##### V.1. Panel specification

The panel fixes eight extensions per base group, with identical parameters across the three groups. Three are Howard–Vala variants HV(1, 1, 0), HV(1, 2, 0), HV(2, 1, 0) (see Eq. (7)). Three are diagonal phase gates  $P(\theta)$  at angles  $\theta \in \{2\pi/9, \pi/9, 2\pi/5\}$ , chosen to span both the cyclotomic-9th-root sector relevant to Section VI and the coarser  $2\pi/5$  angle that generates no low-order closure against any of the three base groups. The remaining two slots per group are independent Haar-random batches of size 10, drawn freshly per subprocess from the invariant measure on SU(3); these serve as the *rnd* baseline of [38]. All eight extensions survive the Stage 2 universality screen of Section II.2: each  $\Sigma$ -series base has one-dimensional adjoint commutant by Eq. (6), and the bounded closures stay open past the  $|\mathcal{C}| \leq 1080$  cap of [31–35].

The panel is evaluated in two passes. An initial Tier-1 screen at  $t = 5$ —the largest design order at which the full  $3 \times 8$  panel completes in  $\sim 17$  min on a single 32-core workstation—fixes the ranking and feeds Sections V.3 and V.4 below. For the headline values of Table II and Fig. 1 we re-run the panel at  $t = 10$  (Tier-2); all structured-extension  $\delta$  agree bit-for-bit with  $t = 5$



except HV(2, 1, 0) on the two smaller groups, which lifts off its finite- $t$  floor at  $t = 10$  (see item (i) below). Fixed extensions use `sample_size = 1` (the gate is deterministic); Haar-random batches use `sample_size = 10`. Each (group, extension) pair is dispatched as an independent `qco` subprocess with `OMP_NUM_THREADS=1` and `--workers 8` to keep the per-irrep spectral evaluation of Eq. (2) single-threaded while exploiting thread-level parallelism across the  $|\mathcal{C}|$  matrix actions described in Section III. All numerical values reported below are reproduced bit-identically from the SQLite caches released with the paper [41].

## V.2. Survey ranking

Table II lists every (group, extension) pair at  $t = 10$ , ranked within each group by  $\delta$ . The  $Q_T / \log |\mathcal{C}|$  column divides out the base-group scale and exposes the spectral-gap content of the extension.

Fig. 1 elaborates three findings against Table II.

*Finding 1 (structured-extension degeneracy).* Five of six structured extensions give  $\delta$  identical to four decimals across all three base groups, bit-for-bit the same as at  $t = 5$ . HV(2, 1, 0) is the only exception: it lifts from the  $t = 5$  floor  $\delta = 0.5000$  on the smaller groups to  $\delta \approx 0.58$  at  $t = 10$ , while  $\Sigma(360 \times 3)$  stays at 0.5698. The degeneracy is structural, not a finite- $t$  artifact.

*Finding 2 (linear  $Q_T$  growth with  $\log |\mathcal{C}|$ ).* Because  $\delta$  is essentially constant,  $Q_T$  grows linearly with  $\log |\mathcal{C}|$  for the degenerate extensions: a larger base group needs proportionally more depth to densely cover SU(3), so the normalized  $Q_T / \log |\mathcal{C}|$  (rightmost column) collapses the three groups onto the same value.

*Finding 3 (Haar-random gains with  $|\mathcal{C}|$ ).* Best-sample Haar  $\delta$  drops from 0.26 to 0.18 from  $\Sigma(72 \times 3)$  to  $\Sigma(360 \times 3)$ ; a random draw couples to every Lie-algebra direction including the subdominant channels that grow with  $|\mathcal{C}|$ . Statistically significant Haar distributions are deferred to Sections V.3 and V.4.

## V.3. Apples-to-apples Haar panel

To separate the base-group effect from random-extension variance, we generated a single batch of ten Haar-random single-qutrit extensions (`seed=42`) and evaluated the panel identically on all three groups. Table III lists the best-sample  $\delta$  per matrix.

Across the  $N = 100$  Haar panel (same `seed = 42`; the first ten matrices coincide with Table III), the three panel means land at  $\mu_{216} = 0.3214$ ,  $\mu_{648} = 0.2623$ ,  $\mu_{1080} = 0.2118$  with standard deviations 0.073, 0.074, and 0.090 respectively (Fig. 2). Mean  $\delta$  decreases strictly monotonically with  $|\mathcal{C}|$  at  $\sim 5.7$  standard errors of the mean, strengthening Finding 3. At  $N = 10$  this ordering inverts between  $\Sigma(216 \times 3)$  and  $\Sigma(360 \times 3)$  because a single outlier (`apple05`,  $\delta = 0.4377$  on  $\Sigma(360 \times 3)$  vs. 0.24 on the smaller groups) inflates the  $\Sigma(360 \times 3)$  mean by roughly

one panel standard deviation — Monte-Carlo noise visible in the small panel, resolved in the large one.

## V.4. Random-diagonal ternary scan

The Tier-1 and Tier-2 panels show a striking feature: five of six structured diagonal and Howard–Vala extensions give  $\delta$  values identical to four decimals across  $\Sigma(72 \times 3)$  and  $\Sigma(216 \times 3)$ . A natural question is whether this four-decimal degeneracy is specific to the cyclotomic content of the panel’s three phases  $P(2\pi/9)$ ,  $P(\pi/9)$ ,  $P(2\pi/5)$ , or whether it applies to the full maximal torus of SU(3). We answer by scanning  $N = 50$  random SU(3) diagonal extensions  $\text{diag}(e^{i\theta_1}, e^{i\theta_2}, e^{i\theta_3})$  (`seed = 42`,  $\theta_1, \theta_2$  uniform on  $[0, 2\pi)$ ,  $\theta_3 = -\theta_1 - \theta_2 \bmod 2\pi$ ) on all three base groups at  $t = 5$ , a  $3 \times 50 = 150$ -evaluation panel completed in  $\sim 14$  minutes of wall time on a 32-core node.

The result is stronger than the structured-panel observation: for every one of the 50 random diagonals, the  $\delta$  value on  $\Sigma(72 \times 3)$  and  $\Sigma(216 \times 3)$  agrees *bit-for-bit*, while  $\Sigma(360 \times 3)$  is generically distinct. Per-group summary statistics (best / mean / max) across the 50 samples are

$$\begin{aligned} \Sigma(72 \times 3), \Sigma(216 \times 3) &: 0.4516 / 0.6769 / 0.9921, (8) \\ \Sigma(360 \times 3) &: 0.2539 / 0.5106 / 0.9662. (9) \end{aligned}$$

Fig. 3 plots the full distribution on the SU(3) maximal-torus simplex; the  $\Sigma$ -series base groups have a permutation subgroup (the qutrit Clifford contains SU(3) Weyl elements), so each random-diagonal point is  $S_3$ -symmetrized to six positions with the same  $\delta$ , exposing the full torus symmetry.

The Finding-1 degeneracy is therefore *not* a property of the cyclotomic angles we chose to probe but a structural property of the nested-subgroup relation  $\Sigma(72 \times 3) \subset \Sigma(216 \times 3)$ : at  $t = 5$ , the dominant  $t$ -design irreps of SU(3) restrict to representations that both groups act on identically, so any diagonal extension couples through the same spectral channel on both.  $\Sigma(360 \times 3)$  does not sit in this chain, hence its breakout. A  $t = 10$  rerun would test whether a subdominant irrep of  $\Sigma(216 \times 3)$  that is absent in  $\Sigma(72 \times 3)$  becomes spectrally visible and lifts the degeneracy.

## V.5. Best achievable $Q_T$

Combining the two panels, the best (group, extension) pair is `apple04` on  $\Sigma(360 \times 3)$  at  $t = 5$  with  $\delta = 0.1197$  and  $Q_T = 3.291$ —within 32% of  $Q_{\text{opt}} = 2.495$ . Note that this rnd winner, like every Haar-random extension, is not exactly synthesized and therefore inherits the distillation caveat of Section VII.1: the  $Q_T$  figure ranks reachability, not fault-tolerant cost. At  $t = 10$  the best *fixed* extension is HV(2, 1, 0) on  $\Sigma(72 \times 3)$ , with  $Q_T = 10.28$ , a factor 3.8 above  $Q_{\text{opt}} = 2.692$ . The shape of the ranking is the same at both  $t$ : Haar-random extensions dominate every structured extension, HV(2, 1, 0) leads the structured field, and

TABLE II.  $d = 3$  survey at  $t = 10$ . Each fixed extension is deterministic ( $\delta$  from a single evaluation); the rnd row per group reports the best of two independent Haar draws, each itself a single-sample evaluation at this design order. Kesten–McKay floor  $Q_{\text{opt}}$ : 2.692, 2.544, 2.495 for  $\Sigma(72, 216, 360 \times 3)$ . Rows are ranked within each group by  $\delta$ ; all structured extensions match their  $t = 5$  values to four decimals except HV(2, 1, 0) on the two smaller groups, where the  $t = 5$  floor at  $\delta = 0.5000$  lifts at  $t = 10$ .

| Group                  | Extension       | kind        | $\delta$ | $Q_T$   | $Q_T / \log  \mathcal{C} $ |
|------------------------|-----------------|-------------|----------|---------|----------------------------|
| $\Sigma(72 \times 3)$  | rnd (best of 2) | rnd         | 0.2605   | 3.996   | 0.744                      |
|                        | HV(2, 1, 0)     | howard_vala | 0.5927   | 10.277  | 1.911                      |
|                        | $P(2\pi/5)$     | angle       | 0.6545   | 12.681  | 2.360                      |
|                        | HV(1, 1, 0)     | howard_vala | 0.6764   | 13.750  | 2.559                      |
|                        | HV(1, 2, 0)     | howard_vala | 0.6764   | 13.750  | 2.559                      |
|                        | $P(2\pi/9)$     | angle       | 0.8830   | 43.208  | 8.041                      |
|                        | $P(\pi/9)$      | angle       | 0.9698   | 175.561 | 32.671                     |
| $\Sigma(216 \times 3)$ | rnd (best of 2) | rnd         | 0.2107   | 4.157   | 0.643                      |
|                        | HV(2, 1, 0)     | howard_vala | 0.5833   | 12.011  | 1.856                      |
|                        | $P(2\pi/5)$     | angle       | 0.6545   | 15.273  | 2.360                      |
|                        | HV(1, 1, 0)     | howard_vala | 0.6764   | 16.561  | 2.559                      |
|                        | HV(1, 2, 0)     | howard_vala | 0.6764   | 16.561  | 2.559                      |
|                        | $P(2\pi/9)$     | angle       | 0.8830   | 52.039  | 8.041                      |
|                        | $P(\pi/9)$      | angle       | 0.9698   | 211.443 | 32.671                     |
| $\Sigma(360 \times 3)$ | rnd (best of 2) | rnd         | 0.1784   | 4.052   | 0.579                      |
|                        | HV(2, 1, 0)     | howard_vala | 0.5698   | 12.419  | 1.775                      |
|                        | $P(2\pi/5)$     | angle       | 0.6545   | 16.478  | 2.360                      |
|                        | HV(1, 1, 0)     | howard_vala | 0.6764   | 17.867  | 2.559                      |
|                        | HV(1, 2, 0)     | howard_vala | 0.6764   | 17.867  | 2.559                      |
|                        | $P(2\pi/9)$     | angle       | 0.8830   | 56.145  | 8.041                      |
|                        | $P(\pi/9)$      | angle       | 0.9698   | 228.127 | 32.671                     |

TABLE III. Apples-to-apples Haar panel at  $t = 5$ : ten pre-generated single-qutrit extensions (**seed=42**) evaluated identically against each of the three base groups. The smallest  $\delta$  in each row is bolded. Mean  $\delta$  over the ten matrices appears in the last row; lower is better.

| matrix  | $\delta$              |                        |                        |
|---------|-----------------------|------------------------|------------------------|
|         | $\Sigma(72 \times 3)$ | $\Sigma(216 \times 3)$ | $\Sigma(360 \times 3)$ |
| apple00 | <b>0.2974</b>         | <b>0.2974</b>          | 0.3462                 |
| apple01 | 0.4636                | 0.4636                 | <b>0.2029</b>          |
| apple02 | 0.2221                | <b>0.1727</b>          | 0.2285                 |
| apple03 | 0.2493                | <b>0.2292</b>          | 0.2299                 |
| apple04 | 0.3430                | 0.2104                 | <b>0.1197</b>          |
| apple05 | 0.2446                | <b>0.2412</b>          | 0.4377                 |
| apple06 | 0.2842                | <b>0.1701</b>          | 0.1965                 |
| apple07 | 0.3169                | 0.2312                 | <b>0.2271</b>          |
| apple08 | 0.3996                | <b>0.2377</b>          | 0.3795                 |
| apple09 | 0.2526                | 0.2526                 | <b>0.1823</b>          |
| mean    | 0.3073                | <b>0.2506</b>          | 0.2550                 |

the three diagonal-phase angles  $P(2\pi/9)$ ,  $P(\pi/9)$ ,  $P(2\pi/5)$  all give worse  $Q_T$  than even the worst Howard–Vala variant. The narrow-angle  $P(\pi/9)$  in particular produces  $\delta$  within 3% of unity, inflating  $Q_T$  by two orders of magnitude relative to the Haar baseline—a direct analogue of the  $14 \times$  Clifford+ $T$  penalty at  $d = 2$  (Section IV).

The Tier-1 ( $t = 5$ ) and Tier-2 ( $t = 10$ ) panels agree to four decimals for all structured extensions except the HV(2, 1, 0) floor lift noted above; the  $d = 2$  Clifford+ $T$

$Q_T(t)$  curve of [38] reaches the same stabilization pattern by  $t \gtrsim 30$ , so our  $t = 5/t = 10$  cross-check is the  $d = 3$  analogue. The four-decimal cross-group  $\delta$ -degeneracy is therefore not a finite- $t$  artifact; it is a structural feature of rational-angle diagonal and Howard–Vala extensions on the  $\Sigma$ -series. Rnd batches at  $t = 10$  are single-sample draws (the qco optimized kernel aggregates to one row per subprocess regardless of the `sample_size` argument); statistically significant Haar statistics come from the apples-100 panel in Section V.3 and from the  $10^4$ -sample BI pilot at  $d = 2$  (Section IV).

## VI. THE DSA PRIMITIVE-GATE TARGET FAMILY

The  $d = 3$  survey of Section V ranks extensions by the Haar-uniform figure of merit  $Q_T$ . Many applications do not need a uniform net. Discrete-subgroup approximations of lattice gauge simulations [8, 40, 44] require instead a small structured family of unitaries: a few continuous-angle  $R_Z$  rotations with group-theoretic coefficients, plus a finite set of cyclotomic phases from the discrete Fourier transform  $U_F$ . On such a workload the relevant figure of merit is the mean synthesis cost over that finite family, not a  $t$ -design spectral gap. The two figures of merit disagree in general. We note that  $\Sigma(36 \times 3)$  itself appears here as a *target family* of  $SU(2)$  rotations derived from its trace spectrum under a qubit encoding [9]; it is not used as a base group, its reducible adjoint at  $d = 3$  having




FIG. 1.  $Q_T$  across the three  $\Sigma$ -series base groups at  $d = 3$ ,  $t = 10$ , for every extension in the panel of Table II. The dashed line is the Kesten–McKay floor  $Q_{\text{opt}}$  of Eq. (5); rational-angle diagonal and Howard–Vala extensions run nearly parallel to it at a factor  $\sim 3$ –70 offset (Finding 2), while Haar-random extensions (stars) approach  $Q_{\text{opt}}$  as  $|\mathcal{C}|$  grows (Finding 3). The HV(1, 1, 0) and HV(1, 2, 0) markers coincide at every  $|\mathcal{C}|$  because the two gates are Clifford-equivalent at  $d = 3$  (Eq. (7)).

excluded it from the QCO survey (Section V).

*A concrete target family.* We work out the case of the  $\Sigma(36 \times 3)$  encoding as a representative example; different subgroups in the series produce different coefficient sets. The trace gate  $U_{\text{Tr}}(\theta) = \text{diag}_{g \in \mathcal{C}}(e^{i\theta \text{Re Tr}(g)})$  appears in the magnetic plaquette of any DSA lattice gauge simulation [8]. For  $\Sigma(36 \times 3)$ , Gustafson *et al.* [9] reduce it to a three-qubit trace register: the 14 conjugacy classes collapse to 7 distinct  $\text{Re Tr}(g) \in \{3, \pm 1, \pm \frac{1}{2}, -\frac{3}{2}, 0\}$ , and a Boolean map  $(p, q, r, s, t) \mapsto (v_0, v_1, v_2)$  separates them. On the  $(v_0, v_1, v_2)$  register the trace Hamiltonian factorizes as

$$H_{\text{Tr}} = \frac{1}{16} [3(III + IIZ + IZI) + 5 IZZ + 1 ZII + 9(ZIZ + ZZI) + 15 ZZZ] \quad (10)$$

so  $U_{\text{Tr}}(\theta)$  decomposes (up to Clifford conjugation) into  $R_Z$  rotations at angles proportional to  $\alpha_c \theta$  for  $\alpha_c \in \{1, 3, 5, 9, 15\}$  — the five distinct non-zero coefficients in the decomposition. These coefficients are specific to  $\Sigma(36 \times 3)$ ; other subgroups in the series produce different trace spectra and different  $\alpha_c$ . The discrete half comes from  $U_F$ : up to global phase, the Howard–Vala qutrit gate HV(1, 2, 0) [30] injects 9th-root phases, requiring  $R_Z(2\pi k/9)$  for  $k = 1, \dots, 8$ . The synthesis target for the  $\Sigma(36 \times 3)$  qubit pipeline is therefore

$$\mathcal{T}_{36} = \{R_Z(2\pi k/9)\}_{k=1}^8 \cup \{R_Z(\alpha_c \theta)\}_{\alpha_c \in \{1, 3, 5, 9, 15\}, \theta \in (0, \pi)}. \quad (11)$$

*Mean-depth figure of merit.* Given a qubit base group  $\mathcal{C}$  and single-gate extension  $g$ , SWIFTBOT enumerates the word tree of  $\mathcal{C} \cup \{g, g^{-1}\}$  by breadth-first search with

projective-phase deduplication, capped at  $2 \times 10^5$  unique words. For each  $U \in \mathcal{T}_{36}$  we record the shortest BFS word whose projective distance  $d(U, W) = \sqrt{2 - |\text{Tr}(U^\dagger W)|}$  falls below  $\varepsilon = 10^{-2}$ , or the depth of closest approach if no such word exists. The  $\varepsilon = 10^{-2}$  floor matches the per-link accuracy typical of near-term Trotter budgets [8]; the BFS-exhaust cap prevents runaway search at this tolerance, and tightening  $\varepsilon$  can only increase the  $6.8\times$  advantage (see §Caveats below). Discrete targets may be hit *exactly* at finite depth, in which case the corresponding distance is zero and the  $T$ -count is read directly from the word. Continuous targets are sampled at ten uniform  $\theta \in (0, \pi)$  per  $\alpha_c$ , for fifty continuous evaluations per extension. We report mean distance across Eq. (11) as the single headline number; ties are broken on the discrete-exact count.

*Result.* Table IV ranks the candidates at BFS depth 15,  $\varepsilon = 10^{-2}$ ,  $N_\theta = 10$  per continuous coefficient. The Clifford+ $P(2\pi/9)$  extension attains mean projective distance 0.0122 on  $\mathcal{T}_{36}$  with 27 of 58 targets hit below  $\varepsilon$ , while the canonical Clifford+ $T$  extension attains mean distance 0.0833 with only 5 hits—a factor  $6.8\times$  separation in mean distance. The equivalence class of  $P(2\pi k/18)$  with  $\text{gcd}(k, 18) = 1$  (which includes  $P(\pi/9)$  and  $P(\pi/18)$ ) all saturate the discrete 9th-root targets, a direct consequence of  $\langle \text{Clifford}, P(2\pi/9) \rangle$  closing at a finite group of  $\sim 3 \times 10^4$  elements; the algebraic ring  $\mathbb{Z}[\omega_{18}, \frac{1}{2}]$  supplies every 9th-root phase via a short word. Within this equivalence class, Clifford+ $P(\pi/18)$  marginally edges Clifford+ $P(2\pi/9)$  at depth 15 (mean 0.0104 vs. 0.0122; 34




FIG. 2. Apples-to-apples Haar panel at  $N = 100$  matrices on the three  $d = 3$   $\Sigma$ -series base groups. Matrix id  $k \in \{0, \dots, 99\}$  labels **apple** $k$ , the  $k$ -th Haar-SU(3) draw from **seed** = 42; ids 0–9 coincide with the ten-matrix subset of Table III. Top: overlaid  $\delta$  histograms. Bottom: per-matrix  $\delta$  for each group. The monotone reduction  $\mu_{216} > \mu_{648} > \mu_{1080}$  predicted by Finding 3 is resolved at  $\sim 5.7\sigma/\sqrt{N}$ ; the single **apple05** outlier visible as the  $\Sigma(360 \times 3)$  peak near  $\delta \simeq 0.44$  is the one that inverted the ten-matrix ordering in Table III.




FIG. 3.  $\delta$  on the SU(3) maximal torus at  $t = 5$ . Each panel shows the 50 random-diagonal extensions of Section V.4,  $S_3$ -symmetrized to six copies each (300 points per panel). The left panel, labeled  $\Sigma(72 \times 3)$  &  $\Sigma(216 \times 3)$ , reports the  $\delta$  values that are bit-for-bit identical on the two smaller  $\Sigma$ -series groups; the right panel reports  $\Sigma(360 \times 3)$ . Red stars mark the three structured rational-angle extensions  $P(2\pi/9)$ ,  $P(\pi/9)$ ,  $P(2\pi/5)$  from Table II, colored by their own  $\delta$  on each group; they sit on the  $\theta_1 = 0$  edge because each has the form  $\text{diag}(1, e^{i\theta}, e^{-i\theta})$ .

vs. 27 hits), reflecting the strictly larger 18th-root coverage:  $P(\pi/18)$  generates  $\omega_{36}$ , which contains both the 9th- and 18th-root phases of  $U_F$ . Crucially, the super-golden extensions  $T_{24}$  and  $T_{12}$ —which optimize  $Q_T$  for Clifford and for the 12-element projective  $A_4$  base **hurwitz** respectively [39]—perform *worse* on  $\mathcal{T}_{36}$  than the rational-angle

TABLE IV. DSA  $\Sigma(36 \times 3)$  target-family coverage at BFS depth 15,  $\varepsilon = 10^{-2}$ , 10 continuous  $\theta$ -samples per  $\alpha_c$ . “hits” counts the 58 targets (the 8 discrete 9th-root phases in Eq. (11) plus 50 continuous  $R_Z(\alpha_c \theta)$  samples) reached below  $\varepsilon$ . “mean/max” are projective distances across all 58; lower is better.  $\langle T \rangle$  is the mean  $T$ -count along hit words. “method” is **rs** for Ross–Selinger [28] exact synthesis and **bfs** for the SWIFTBOT BFS estimate; all rows are **bfs** except the canonical  $P(\pi/4)$ , no RS-style normal form having yet been established for the rational-angle cyclotomic rings  $\mathbb{Z}[\omega_{18}, \frac{1}{2}]$  or  $\mathbb{Z}[i, \sqrt{2}]$ .

| Base + ext.                  | hits (/58) | mean dist. | max dist. | $\langle T \rangle$ | method     |
|------------------------------|------------|------------|-----------|---------------------|------------|
| Clifford+ $P(\pi/18)$        | 34         | 0.0104     | 0.0420    | 2.79                | <b>bfs</b> |
| <b>hurwitz</b> + $P(\pi/18)$ | 35         | 0.0112     | 0.0420    | 5.37                | <b>bfs</b> |
| Clifford+ $P(\pi/9)$         | 27         | 0.0120     | 0.0401    | 2.04                | <b>bfs</b> |
| Clifford+ $P(2\pi/9)$        | 27         | 0.0122     | 0.0401    | 2.11                | <b>bfs</b> |
| Clifford+ $P(\pi/8)$         | 7          | 0.0221     | 0.0387    | 0.29                | <b>bfs</b> |
| Clifford+ $T_{24}$           | 6          | 0.0228     | 0.0465    | 0.83                | <b>bfs</b> |
| Clifford+ $T_{12}$           | 8          | 0.0233     | 0.0474    | 1.88                | <b>bfs</b> |
| <b>hurwitz</b> + $T_{12}$    | 0          | 0.0313     | 0.0573    | —                   | <b>bfs</b> |
| Clifford+ $P(\pi/4)$         | 5          | 0.0833     | 0.1554    | 0.00                | <b>rs</b>  |

rows: their algebra  $\mathbb{Z}[i, \sqrt{2}]$  does not contain  $\omega_9$ , so they cannot reach the 9th-root targets exactly at any depth; on the  $|\mathcal{C}| = 12$  **hurwitz** base the  $T_{12}$  extension hits zero targets at depth 15. The **hurwitz**+ $P(\pi/18)$  row is competitive (35 hits, mean 0.0112) and does so with a strictly *smaller* base group: in the target-family regime the overhead advantage tracks the cyclotomic content of the extension, not the size of the base.

*Interpretation.* Clifford+ $P(2\pi/9)$  is worse on  $Q_T$  than Clifford+ $T$  yet  $6.8\times$  better on mean depth over  $\mathcal{T}_{36}$ . The reason is structural:  $Q_T$  is the coefficient of a Haar-uniform covering rate, while  $\mathcal{T}_{36}$  is a measure-zero algebraic slice of SU(2) whose  $\omega_9$  cyclotomic content matches  $\langle \text{Clifford}, P(2\pi/9) \rangle$ . The super-golden extensions saturate  $Q_{\text{opt}}$  but equidistribute in the wrong direction for this target. A lattice-gauge simulator compiling Eq. (11) should therefore rank extensions by target-family mean depth, not by  $Q_T$ , and the two rankings can disagree by nearly an order of magnitude.

*Caveats.* The Clifford+ $T$  row’s  $T$ -count is certified by Ross–Selinger exact synthesis [28, 29]; the companion Clifford-cyclotomic framework of Forest *et al.* [48] extends this to  $\mathbb{Z}[\zeta_{2^n}]$  but not to the rational-prime-denominator rings relevant here. No analogous normal form exists for  $\mathbb{Z}[\omega_{18}, \frac{1}{2}]$ , so the rational-angle rows carry depth-15 BFS upper bounds. The  $6.8\times$  advantage is therefore a *lower bound*: a certified synthesis theorem over  $\mathbb{Z}[\omega_{18}, \frac{1}{2}]$  would only shorten the BFS-side words, while the canonical Ross–Selinger side is already tight. Anderson–Jochym–O’Connor [19] excludes any qubit *stabilizer* code with transversal  $|k\pi/9\rangle$ . Two routes sidestep this. Programmable MSD [49–51] is indirect synthesis: it prepares  $|\psi(\theta)\rangle$  from already-distilled  $|T\rangle$  on a Clifford+ $T$  stabilizer substrate, so the AJOC no-go never applied to it. Non-stabilizer code-switching to a Kubischta–Teixeira PI code [52, 53] is a genuine bypass but requires a PI






FIG. 4. DSA  $\Sigma(36 \times 3)$  target-family coverage from Table IV: hits/58 versus mean projective distance on  $\mathcal{T}_{36}$  at BFS depth 15,  $\varepsilon = 10^{-2}$ . Canonical Clifford+ $T$  (red, **rs\_exact** certified) sits bottom-right with the largest mean distance and only 5 hits. Rational-angle  $P(k\pi/18)$  extensions (blue, **bfs\_estimate**) cluster top-left with many hits at an order of magnitude smaller distance; super-golden  $T_{12}/T_{24}$  rows fall in between despite saturating  $Q_{\text{opt}}$  (Section IV). The visual separation matches the  $6.8\times$  headline.

code of sufficient distance hosting  $|\omega_9\rangle$ , which has not been constructed. The  $6.8\times$  advantage is cleanest when  $P(2\pi/9)$  is a native primitive—e.g., in a qutrit register or on a hypothetical nonadditive code that distills  $|\omega_9\rangle$  directly.

## VII. DISCUSSION

Two findings drive the discussion below. First, at  $d = 3$  and  $t = 5$ , Haar-random extensions on the largest irreducible-adjoint  $\Sigma$ -series base reach  $Q_T/Q_{\text{opt}} \approx 1.32$ —essentially the same “golden-gate direction” observed at  $d = 2$ , where Haar extensions sit 4% above  $Q_{\text{opt}}$  on the 12-element **hurwitz** base (Section IV). No structured extension in our panel (Howard–Vala or rational diagonal) gets closer than a factor  $\sim 2.9$  of  $Q_{\text{opt}}$ . Second, and in apparent tension with the first, the non-canonical Clifford+ $P(2\pi/9)$  extension beats the canonical Clifford+ $T$  by  $6.8\times$  on the DSA primitive-gate target family (Section VI) despite being  $\sim 8\times$  worse on  $Q_T$ . The two findings together are the paper’s central design lesson: the “best general-purpose extension” and the “best target-specific extension” optimize different objectives, and paper-scale qudit fault-

tolerance design must report both.

### VII.1. Fault-tolerance status of the winning extensions

A  $Q_T$  ranking is necessary but not sufficient for fault-tolerant implementation. Table V audits every extension evaluated against the curated SWIFTBOT catalogs of transversal codes, distillation protocols, and certified synthesis rings. Only canonical Clifford+ $T$  at  $d = 2$  admits an end-to-end certified stack and serves as our validation anchor. Three rows inherit a transversal-code half only: **hurwitz**-based super-golden extensions via Parzanchevski–Sarnak [43], BI+**rnd** via the Kubischta 2I code [16], and the  $d = 3$   $\Sigma + \text{HV}(z, \gamma, \varepsilon)$  rows via the qutrit triorthogonal  $[[9m - k, k, 2]]_3$  family [13]. All other rows lack either a distillation circuit or a certified synthesis ring.

Three regimes deserve comment. First, the cyclotomic ring  $\mathbb{Z}[\omega_{18}, \frac{1}{2}]$ —hosting the  $d = 2$  target-family winners  $P(2\pi/9)$ ,  $P(\pi/9)$ ,  $P(\pi/18)$ —has no Ross–Selinger-style normal form, and Anderson–Jochym–O’Connor [19] excludes any qubit *stabilizer* code with a transversal  $[k\pi/9]$  state. Two non-stabilizer routes handle the exclusion. First, programmable MSD [49–51] is indirect synthesis: the  $|\psi(\theta)\rangle$  state is synthesized from distilled  $|T\rangle$  on a Clifford+ $T$  substrate, so the AJOC no-go does not apply; the overhead is the synthesis cost times the  $|T\rangle$  distillation cost. Second, measurement-free code-switching between a Clifford stabilizer code and a Kubischta–Teixeira permutation-invariant code [52, 53] is a true non-stabilizer bypass, but requires a PI code of sufficient distance hosting the target rotation; no such code has been constructed for  $|\omega_9\rangle$ , so this remains an open direction. At  $d = 3$  the same rotations are qutrit-native and Campbell–Anwar–Browne [13] distills  $|\omega_9\rangle$  directly.

Second, the super-golden gates of Parzanchevski–Sarnak [43] live in  $\mathbb{Z}[i, \sqrt{2}]$  and are not Clifford-orbit rotations of stabilizer states, so triorthogonal distillation does not apply. Whether a golden-gate-compatible distillation circuit can be built—possibly on the Kubischta 2I code, whose transversal group is precisely the super-golden base—is open.

Third, Haar-random extensions are by definition not exactly synthesized, and so cannot be distilled in the usual sense [2, 3]. This applies uniformly to every **rnd** row; the best current claim is transversal-group support at the base-code level.

For the  $\Sigma$ -series at  $d = 3$ , data and distillation codes are structurally separable. The Howard–Vala magic state is distilled by the qutrit triorthogonal family [13, 14], but no explicit data code hosts a  $\Sigma$ -series group transversally. Denys–Leverrier covariant codes at  $d = 2$  [17, 18] support  $2T$  and  $2O$  group actions natively through continuous-group covariance, distinct from Eastin–Knill transversality on a stabilizer code; extending either to a qutrit  $\Sigma(m \times 3)$  base—an open case inside the twisted unitary  $t$ -group program [52]—would complete the stack. (Clifford+ $R$  syn-

thesis [37] separately closes the compilation-certification gap for these  $d = 3$  gate sets; we return to this below.)

Higher-dimensional qudit MSD is advancing rapidly. Krishna–Tillich [54] opened the low-overhead program; Wills, Hsieh, and Yamasaki [55] achieved the first constant-overhead MSD construction via asymptotically good quantum codes; Golowich–Guruswami [56] and Nguyen [57] gave asymptotically good qubit codes with transversal non-Clifford and CCZ gates. Most directly applicable to our framework, Cervia *et al.* [58] construct triorthogonal codes on  $\mathbb{F}_{2^{2m}}$  at qudit dimensions as small as  $q = 64$  that beat the Tsfasman–Vlăduț–Zink bound and give constant-space-overhead  $|CCZ\rangle$  distillation, together with an explicit qudit-to-qubit conversion circuit that makes the construction a drop-in upgrade for any Clifford+CCZ evaluation. None of these high- $d$  codes have cataloged transversal pairings with our base-group registry, but the infrastructure now exists to pair them.

A complementary recent development is *magic-state cultivation* [59]: rather than distilling high-fidelity  $|T\rangle$  states from many noisy copies, one grows a protected  $|T\rangle$  inside a surface-code patch using roughly the same gate budget as a logical CNOT, reducing qubit-round cost by an order of magnitude at realistic noise [60], with an experimental demonstration on a superconducting processor [61]. Cultivation is currently qubit-native and surface-code-specific; the open question for the qudit program is whether a native- $d$  analogue exists on codes with transversal non-Clifford structure (Kubischta 2I, Denys–Leverrier 2T/2O, or the twisted  $t$ -group codes of [52]). Two arguments have historically favored  $d = 2$ : the maturity of Ross–Selinger Clifford+ $T$  synthesis and the qubit-specificity of magic-state cultivation. The first is closing at  $d = 3$  with Clifford+ $R$  synthesis [37]; a qudit cultivation analogue would close the second.

On the synthesis side of the qudit story, single-qutrit exact-synthesis methods over Clifford+ $T$  and related Clifford+cyclotomic rings are by now well developed [37, 62–64], so the qutrit compilation story is closing to parity with the qubit one.

## VII.2. Limitations

Three limitations frame the numerical claims. First, the  $d = 3$  Haar statistics come from either single-sample  $t = 10$  draws (Tier-2 panel) or the 100-matrix apples-to-apples panel at  $t = 5$  (Section V.3); a joint  $t = 10$ ,  $\sim 100$ -sample Haar run is held up by a qco-kernel limitation that aggregates each subprocess to a single output row regardless of sample size. Second, no  $d = 4$  survey is attempted: largest-irrep dimensions scale as  $t^6$  at  $d = 4$  and squared matrix-storage as  $t^{12}$ , so only the smallest  $SU(4)$  subgroups ( $|C| \lesssim 300$ ) fit in a single-node 125 GB budget at  $t = 10$ . A pilot on those is tractable overnight; the large- $|C|$   $SU(4)$  subgroups (e.g. S7F) would need a cluster slot. Third, the target-family  $T$ -counts in Table IV are depth-15 BFS upper bounds except for the

Ross–Selinger-certified Clifford+ $P(\pi/4)$  row. The  $6.8\times$  advantage is a *lower bound*: a certified normal form over  $\mathbb{Z}[\omega_{18}, \frac{1}{2}]$  [48] would only tighten the BFS side, not the canonical side, which is already exact.

## VII.3. Open questions

Two quantitative questions are directly posed by our  $t = 5$  data and should be sharp enough to settle at  $t \geq 10$ : (a) does the four-decimal  $\delta$ -degeneracy across  $\Sigma(216, 648, 1080 \times 3)$  observed for structured diagonal and Howard–Vala extensions in Table II persist, break, or re-rank at larger  $t$ ? and (b) does the  $\Sigma(360 \times 3)$  apples-panel mean cross strictly below the  $\Sigma(216 \times 3)$  mean once the  $\sim 100$ -matrix apples panel removes the 10-matrix outlier sensitivity? Question (b) has been *settled in the affirmative* at  $t = 5$  in Section V.3 ( $5.7\sigma/\sqrt{N}$  separation at  $N = 100$ ); the  $t \geq 10$  rerun will establish whether the same ordering holds at converged design order. Three qualitative questions are left open: (c) a super-golden construction at  $d = 3$  saturating  $Q_{\text{opt}} \approx 2.69$  on  $\Sigma(72 \times 3)$ , 2.54 on  $\Sigma(216 \times 3)$ , or 2.50 on  $\Sigma(360 \times 3)$ ; (d) an explicit data code  $C_{\text{data}}$  that hosts one of our  $\Sigma$ -series base groups transversally, analogous to the Denys–Leverrier constructions for  $2T$  and  $2O$  at  $d = 2$  [17, 18] or to the Kubischta–Teixeira twisted unitary  $t$ -group framework [52]; and (e) a Ross–Selinger-style normal form for the cyclotomic ring  $\mathbb{Z}[\omega_{18}, \frac{1}{2}]$  that would certify the Table IV  $T$ -counts.

## VII.4. Software release

SWIFTBOT is released with this paper [41] under the MIT license. The release contains: the five-stage pipeline (Section III); the pre-seeded group registry for  $d \in \{2, 3, 4\}$ ; the SWIFTBOT optimizations of the QCO kernel of [38], including the conjugation cache and on-disk  $\pi_\lambda(C)$  cache described in Section III; the Stage-4 QEC-code catalog and Stage-5 distillation-protocol catalog with their cross-references to transversal groups; the BFS target-family coverage module used in Section VI; the `q-panel` CLI entry point and the two panel specifications `d3_survey` and `d3_rnd_apples` that reproduce Tables II and III bit-identically; the SQLite cache containing all 54 per-sample rows quoted in Section V; and the  $\text{\LaTeX}$  source of this paper. A minimal README walks new users through reproducing Tables I to III on a laptop in under an hour. Pull requests adding new base groups, extensions, codes, or distillation protocols are welcome; the catalog cross-validation tests ensure that every registered transversal-group string resolves to a registered base group.

TABLE V. Magic-state distillation (MSD) status for every extension evaluated in this paper. “Algebra” is the cyclotomic or quaternionic ring hosting the non-Clifford factor of the extension. “Status/closest cousin” combines synthesis and distillation coverage: COMPLETE means transversal code, published MSD protocol, and certified normal-form synthesis are all available; PARTIAL means a transversal code is available but no matching MSD circuit (or the code–extension pairing is not yet established); NONE means no cataloged MSD, either because no protocol exists for the algebra or because the extension is not exactly synthesizable. Rows are grouped by qudit dimension and by the panel section in which the extension appears.

| Extension                                                                          | Algebra                        | Status / closest cousin                                                                                                                                                                                                           | Reference   |
|------------------------------------------------------------------------------------|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| <i>d = 2 canonical (Section IV)</i>                                                |                                |                                                                                                                                                                                                                                   |             |
| Clifford+ $P(\pi/4)$ (canonical $\mathbb{Z}[\omega_8, 1/\sqrt{2}]$ )               |                                | COMPLETE: BK 15-to-1; Bravyi–Haah triorthogonal                                                                                                                                                                                   | [2, 3]      |
| Clifford+ $P(\pi/8)$                                                               | $\mathbb{Z}[\omega_{16}, 1/2]$ | NONE: no published protocol for $\omega_{16}$ ; cousin BK 15-to-1 [2] does not distill this state                                                                                                                                 |             |
| <i>d = 2 DSA target family (Section VI)</i>                                        |                                |                                                                                                                                                                                                                                   |             |
| Clifford+ $P(2\pi/9)$ , $P(\pi/9)$ , $\mathbb{Z}[\omega_{18}, 1/2]$<br>$P(\pi/18)$ |                                | PARTIAL (INDIRECT): no direct stabilizer-code distillation (Anderson–Jochym–O’Connor [19]); programmable-MSD distills $ \psi(\theta)\rangle$ on a Clifford+ $T$ substrate; PI code-switching [53] is a non-stabilizer alternative | [49–51, 53] |
| Clifford+ $P(2\pi/5)$                                                              | $\mathbb{Z}[\omega_{10}]$      | PARTIAL (INDIRECT): stabilizer-code distillation excluded [19]; programmable-MSD and PI code-switching both apply to arbitrary $\theta$                                                                                           | [49–51, 53] |
| Clifford+ $T_{24}$ , hurwitz+ $T_{12}$ (super-golden)<br>$\mathbb{Z}[i, \sqrt{2}]$ |                                | PARTIAL: Parzanchevski–Sarnak supplies transversal base; [43] magic state is not a Clifford-orbit stabilizer rotation, so triorthogonal MSD does not apply                                                                        |             |
| <i>Haar-random rows, any d</i>                                                     |                                |                                                                                                                                                                                                                                   |             |
| Clifford+rnd, hurwitz+rnd ( $d = 2$ )                                              | generic SU(2) (no ring)        | NONE: not exactly synthesizable, so MSD is not defined                                                                                                                                                                            | —           |
| BI+rnd ( $d = 2$ )                                                                 | generic SU(2) (no ring)        | PARTIAL: Kubischta ((7, 2, 3)) supplies transversal $2I$ base; [16] no MSD for a Haar magic state                                                                                                                                 |             |
| $\Sigma$ -series+rnd ( $d = 3$ )                                                   | generic SU(3) (no ring)        | NONE: not exactly synthesizable; no cataloged qutrit transversal classification for $\Sigma$ -series                                                                                                                              | —           |
| <i>d = 3 structured (Section V)</i>                                                |                                |                                                                                                                                                                                                                                   |             |
| $\Sigma + \text{HV}(1, 1, 0)$ , $\mathbb{Z}[\omega_9]$                             |                                | PARTIAL: qutrit triorthogonal $[[9m-k, k, 2]]_3$ distills Howard–Vala magic state; $\Sigma$ -series transversal pairing unestablished                                                                                             | [13]        |
| $\Sigma + \text{HV}(1, 2, 0)$                                                      |                                | PARTIAL: cousin Campbell–Anwar–Browne qutrit triorthogonal; no protocol certified for this orbit                                                                                                                                  | [13]        |
| $\Sigma + \text{HV}(2, 1, 0)$                                                      | $\mathbb{Z}[\omega_9]$         | PARTIAL: qutrit-native $\omega_9$ phase; Campbell–Anwar–Browne applies modulo transversal pairing                                                                                                                                 | [13]        |
| $\Sigma + P(2\pi/9)$ ( $d = 3$ )                                                   | $\mathbb{Z}[\omega_9]$         | NONE: $\omega_{18}$ outside Campbell–Anwar–Browne; no cousin at $d = 3$                                                                                                                                                           | —           |
| $\Sigma + P(\pi/9)$ ( $d = 3$ )                                                    | $\mathbb{Z}[\omega_{18}]$      | NONE: $\omega_{10}$ not in any qutrit stabilizer setting; no cousin                                                                                                                                                               | —           |
| $\Sigma + P(2\pi/5)$ ( $d = 3$ )                                                   | $\mathbb{Z}[\omega_{10}]$      |                                                                                                                                                                                                                                   |             |

## VIII. CONCLUSIONS

SWIFTBOT—an agentic workflow that ranks  $(\mathcal{C}, g)$  pairs by  $Q_T$  and cross-references each against a curated fault-tolerance catalog—produces the first systematic  $d = 3$   $Q_T$  ranking in our registry and identifies  $\Sigma(360 \times 3)$  with a Haar-random extension as the best general-purpose qudit base ( $Q_T/Q_{\text{opt}} \approx 1.32$  in the apples-100 panel at  $t = 5$ , and consistent single-sample draws at  $t = 10$ ). A paper-scale  $10^4$ -sample Haar pilot on the binary icosahedral base at  $d = 2$  gives  $Q_T/Q_{\text{opt}} \approx 1.27$ , the natural super-golden candidate. Applied to a lattice-gauge simulation target family, the non-canonical Clifford+ $P(2\pi/9)$  beats canonical Clifford+ $T$  by  $6.8\times$  on mean depth despite being worse on  $Q_T$ , establishing that the two rankings locate different gates. Only canonical Clifford+ $T$  admits an end-to-end certified fault-tolerant stack; every other winner is covered partially, with sharp open algebraic-compilation or code-pairing problems standing between

it and full fault-tolerance. Three concrete next steps carry most of the remaining design risk. (i) A  $d = 4$  pilot on the Fairbairn subgroups [32] would test whether the  $Q_T/Q_{\text{opt}} \rightarrow 1$  trend continues past  $d = 3$  or the  $d = 3$  “golden direction” is an accident. (ii) An explicit  $\Sigma$ -series  $\leftrightarrow$  data-code transversal pairing [18, 52, 53] would upgrade the  $d = 3$  winners from PARTIAL to COMPLETE in Table V. (iii) A Ross–Selinger normal form for  $\mathbb{Z}[\omega_{18}, \frac{1}{2}]$  would replace the BFS upper bound in Table IV and likely sharpen the  $6.8\times$  headline. For a hardware vendor choosing between qubit and qudit architectures *today*, the practical takeaway is narrower: if the workload is lattice-gauge-simulation-shaped, a rational-phase qubit Clifford extension already buys nearly an order of magnitude over the canonical Clifford+ $T$  stack with no new hardware.

## Acknowledgements

We thank A. Sawicki, P. Dulián, and O. Słowik for the QCO reference dataset and numerical kernel that SWIFTBOT builds on. This material is based upon work

supported by the U.S. Department of Energy, Office of Science, Office of High Energy Physics, under Award No. DE-SCL0000090 “HEP AmSC IDA Pilot: Knowledge Extraction”. This manuscript has been authored by Fermi Forward Discovery Group, LLC under Contract No. 89243024CSC000002 with the U.S. Department of Energy, Office of Science, Office of High Energy Physics.

- 
- [1] B. Eastin and E. Knill, Restrictions on Transversal Encoded Quantum Gate Sets, *Phys. Rev. Lett.* **102**, 110502 (2009), [arXiv:0811.4262 \[quant-ph\]](#).
  - [2] S. Bravyi and A. Kitaev, Universal quantum computation with ideal Clifford gates and noisy ancillas, *Phys. Rev. A* **71**, 022316 (2005), [arXiv:quant-ph/0403025](#).
  - [3] S. Bravyi and J. Haah, Magic-state distillation with low overhead, *Phys. Rev. A* **86**, 052329 (2012), [arXiv:1209.2426](#).
  - [4] Y. Wang, Z. Hu, B. C. Sanders, and S. Kais, Qudits and High-Dimensional Quantum Computing, *Front. Phys.* **8**, 589504 (2020).
  - [5] E. O. Kiktenko, A. S. Nikolaeva, and A. K. Fedorov, Colloquium: Quantum Computing with Qudits, *Rev. Mod. Phys.* **97**, 021003 (2025), [arXiv:2212.12934 \[quant-ph\]](#).
  - [6] T. Kim, T. Roy, X. You, A. C. Y. Li, H. Lamm, O. Pronitchev, *et al.*, Ultracoherent superconducting cavity-based multiqudit platform with error-resilient control (2025), [arXiv:2506.03286 \[quant-ph\]](#).
  - [7] D. M. Kürkgüoğlu, H. Lamm, O. Ogunkoya, and L. Pierattelli, The 2T-quocit: a two-mode bosonic qudit for high energy physics, *arXiv preprint* (2025), [arXiv:2509.21941 \[quant-ph\]](#).
  - [8] H. Lamm, S. Lawrence, and Y. Yamauchi (NuQS), General methods for digital quantum simulation of gauge theories, *Phys. Rev. D* **100**, 034518 (2019), [arXiv:1903.08807 \[hep-lat\]](#).
  - [9] E. J. Gustafson, Y. Ji, H. Lamm, E. M. Muraire, S. Osorio Perez, and S. Zhu, Primitive Quantum Gates for an SU(3) Discrete Subgroup:  $\Sigma(36 \times 3)$ , *Phys. Rev. D* **110**, 034515 (2024), [arXiv:2405.05973 \[hep-lat\]](#).
  - [10] L. Spagnoli, A. Roggero, and N. Wiebe, Qudit stabiliser codes for  $\mathbb{Z}_N$  lattice gauge theories with matter (2026), [arXiv:2602.20661 \[quant-ph\]](#).
  - [11] M. Meth, J. F. Haase, J. Zhang, C. Edmunds, L. Postler, A. Steiner, A. J. Jena, L. Dellantonio, R. Blatt, P. Zoller, T. Monz, P. Schindler, C. Muschik, and M. Ringbauer, Simulating 2D lattice gauge theories on a qudit quantum computer, *Nature Phys.* **21**, 570 (2025), [arXiv:2310.12110 \[quant-ph\]](#).
  - [12] P. P. Popov, M. Meth, M. Lewenstein, P. Hauke, M. Ringbauer, E. Zohar, and V. Kasper, Variational quantum simulation of U(1) lattice gauge theories with qudit systems (2023), [arXiv:2307.15173 \[quant-ph\]](#).
  - [13] E. T. Campbell, H. Anwar, and D. E. Browne, Magic-state distillation in all prime dimensions using quantum Reed-Muller codes, *Phys. Rev. X* **2**, 041021 (2012), [arXiv:1205.3104](#).
  - [14] S. Prakash and T. Saha, Low-overhead qutrit magic state distillation, *Quantum* **9**, 1768 (2025), [arXiv:2403.06228 \[quant-ph\]](#).
  - [15] D. Gottesman, Fault-tolerant quantum computation with higher-dimensional systems, *Chaos, Solitons & Fractals* **10**, 1749 (1999), [arXiv:quant-ph/9802007](#).
  - [16] E. Kubischta and I. Teixeira, Family of Quantum Codes with Exotic Transversal Gates, *Phys. Rev. Lett.* **131**, 240601 (2023), [arXiv:2305.07023 \[quant-ph\]](#).
  - [17] A. Denys and A. Leverrier, The 2T-qutrit, a two-mode bosonic qutrit, *Quantum* **7**, 1032 (2023), [arXiv:2210.16188 \[quant-ph\]](#).
  - [18] A. Denys and A. Leverrier, Quantum error-correcting codes with a covariant encoding, *Phys. Rev. Lett.* **133**, 240603 (2024), [arXiv:2306.11621 \[quant-ph\]](#).
  - [19] J. T. Anderson and T. Jochym-O’Connor, Classification of transversal gates in qubit stabilizer codes, *Quant. Inf. Comp.* **16**, 0771 (2016), [arXiv:1409.8320 \[quant-ph\]](#).
  - [20] S. Bravyi, A. W. Cross, J. M. Gambetta, D. Maslov, P. Rall, and T. J. Yoder, High-threshold and low-overhead fault-tolerant quantum memory, *Nature* **627**, 778 (2024), [arXiv:2308.07915 \[quant-ph\]](#).
  - [21] L. Pecorari, S. Jandura, G. K. Brennen, and G. Pupillo, High-rate quantum LDPC codes for long-range-connected neutral atom registers, *Nature Commun.* **16**, 1111 (2025), [arXiv:2404.13010 \[quant-ph\]](#).
  - [22] D. J. Spencer, A. Tanggara, T. Haug, D. Khu, and K. Bharti, Qudit low-density parity-check codes, *Quantum* **10**, 2023 (2026), [arXiv:2510.06495 \[quant-ph\]](#).
  - [23] B. Vasić, V. Savin, M. Pacenti, S. Borah, and N. Raveendran, Quantum Low-Density Parity-Check Codes (2025), [arXiv:2510.14090 \[quant-ph\]](#).
  - [24] J. N. Eberhardt and V. Steffan, Logical Operators and Fold-Transversal Gates of Bivariate Bicycle Codes (2024), [arXiv:2407.03973 \[quant-ph\]](#).
  - [25] H. Sayginel, S. Koutsoumpas, M. Webster, A. Rajput, and D. E. Browne, Fault-Tolerant Logical Clifford Gates from Code Automorphisms (2024), [arXiv:2409.18175 \[quant-ph\]](#).
  - [26] A. J. Malcolm, A. N. Glaudell, P. Fuentes, D. Chandra, A. Schotte, C. DeLisle, R. Haenel, A. Ebrahimi, J. Roffe, A. O. Quintavalle, S. J. Beale, N. R. Lee-Hone, and S. Simmons, Computing Efficiently in QLDPC Codes (2025), [arXiv:2502.07150 \[quant-ph\]](#).
  - [27] A. Y. Kitaev, Quantum computations: algorithms and error correction, *Russ. Math. Surv.* **52**, 1191 (1997).
  - [28] N. J. Ross and P. Selinger, Optimal ancilla-free Clifford+T approximation of  $z$ -rotations, *Quant. Inf. Comp.* **16**, 901 (2016), [arXiv:1403.2975 \[quant-ph\]](#).
  - [29] V. Kliuchnikov, D. Maslov, and M. Mosca, Fast and efficient exact synthesis of single qubit unitaries generated by Clifford and  $T$  gates, *Quant. Inf. Comp.* **13**, 607 (2013), [arXiv:1206.5236 \[quant-ph\]](#).
  - [30] M. Howard and J. Vala, Qudit versions of the qubit  $\pi/8$  gate, *Phys. Rev. A* **86**, 022316 (2012), [arXiv:1206.1598](#)



- [quant-ph].
- [31] H. F. Blichfeldt, *Finite Collineation Groups* (University of Chicago Press, 1917).
  - [32] W. M. Fairbairn, T. Fulton, and W. H. Klink, Finite and Disconnected Subgroups of  $SU(3)$  and their Application to the Elementary-Particle Spectrum, *J. Math. Phys.* **5**, 1038 (1964).
  - [33] H. Flyvbjerg, Character table for the 1080 element point group like subgroup of  $SU(3)$ , *J. Math. Phys.* **26**, 2985 (1985).
  - [34] A. Hanany and Y.-H. He, A Monograph on the Classification of the Discrete Subgroups of  $SU(4)$ , *JHEP* **02**, 027, [arXiv:hep-th/9905212](#).
  - [35] W. Grimus and P. O. Ludl, Principal series of finite subgroups of  $SU(3)$ , *J. Phys. A* **43**, 445209 (2010), [arXiv:1006.0098 \[math-ph\]](#).
  - [36] A. Bocharov, M. Roetteler, and K. M. Svore, Factoring with qutrits: Shor’s algorithm on ternary and metaplectic quantum architectures, *Phys. Rev. A* **96**, 012306 (2017), [arXiv:1605.02756 \[quant-ph\]](#).
  - [37] E. J. Gustafson, H. Lamm, D. Liu, E. M. Muraïri, and S. Zhu, Synthesis of Single Qutrit Circuits from Clifford+ $R$  (2025), [arXiv:2503.20203 \[quant-ph\]](#).
  - [38] O. Słowik, P. Dulián, and A. Sawicki, Quantum Circuit Overhead: the cost of approximating unitaries with finite gate sets, *arXiv preprint* (2025), [arXiv:2505.00683 \[quant-ph\]](#).
  - [39] P. Sarnak, [Letter to Aaronson and Pollington on the Solovay–Kitaev theorem and golden gates](#) (2015).
  - [40] E. J. Gustafson, H. Lamm, F. Lovelace, and D. Musk, Primitive Quantum Gates for an  $SU(2)$  Discrete Subgroup: Binary Tetrahedral, *Phys. Rev. D* **106**, 114501 (2022), [arXiv:2208.12309 \[hep-lat\]](#).
  - [41] G. T. Fleming, H. Lamm, K. Tame-Narvaez, and P. Vander Griend, SWIFTbot: a pipeline for efficient qudit gate-set discovery, <https://github.com/petergerrit/quai> (2026).
  - [42] A. Sawicki and K. Karnas, Universality of Single-Qudit Gates, *Ann. Henri Poincaré* **18**, 3515 (2017), [arXiv:1610.00547 \[quant-ph\]](#).
  - [43] O. Parzanchevski and P. Sarnak, Super-golden-gates for  $PU(2)$ , *Adv. Math.* **327**, 869 (2018), [arXiv:1704.02106 \[math.NT\]](#).
  - [44] M. S. Alam, S. Hadfield, H. Lamm, and A. C. Y. Li (SQMS), Primitive quantum gates for dihedral gauge theories, *Phys. Rev. D* **105**, 114501 (2022), [arXiv:2108.13305 \[hep-lat\]](#).
  - [45] M. B. Hastings and J. Haah, Distillation with sublogarithmic overhead (2018), [arXiv:1709.03543 \[quant-ph\]](#).
  - [46] D. Litinski, Magic state distillation: Not as costly as you think, *Quantum* **3**, 205 (2019), [arXiv:1905.06903 \[quant-ph\]](#).
  - [47] V. V. Albert and P. Faist, The Error Correction Zoo, <https://errorcorrectionzoo.org> (2024).
  - [48] S. Forest, D. Gosset, V. Kliuchnikov, and D. McKinnon, Exact synthesis of single-qubit unitaries over Clifford-cyclotomic gate sets, *J. Math. Phys.* **56**, 082201 (2015), [arXiv:1501.04944 \[quant-ph\]](#).
  - [49] G. Duclos-Cianci and D. Poulin, Reducing the quantum-computing overhead with complex gate distillation, *Phys. Rev. A* **91**, 042315 (2015), [arXiv:1403.5280 \[quant-ph\]](#).
  - [50] E. T. Campbell and J. O’Gorman, An efficient magic state approach to small angle rotations, *Quantum Sci. Technol.* **1**, 015007 (2016), [arXiv:1603.04230 \[quant-ph\]](#).
  - [51] E. T. Campbell and M. Howard, Magic state parity-checker with pre-distilled components, *Quantum* **2**, 56 (2018), [arXiv:1709.02214 \[quant-ph\]](#).
  - [52] E. Kubicsha and I. Teixeira, Quantum Codes from Twisted Unitary  $t$ -groups, *Phys. Rev. Lett.* **133**, 030602 (2024), [arXiv:2402.01638 \[quant-ph\]](#).
  - [53] Y. Ouyang, Y. Jing, and G. K. Brennen, Measurement-free code-switching for low overhead quantum computation using permutation invariant codes, *arXiv preprint* (2024), [arXiv:2411.13142 \[quant-ph\]](#).
  - [54] A. Krishna and J.-P. Tillich, Towards low overhead magic state distillation, *Phys. Rev. Lett.* **123**, 070507 (2019), [arXiv:1811.08461 \[quant-ph\]](#).
  - [55] A. Wills, M.-H. Hsieh, and H. Yamasaki, Constant-overhead magic state distillation, *Nature Physics* **10.1038/s41567-025-03026-0** (2025).
  - [56] L. Golowich and V. Guruswami, Asymptotically Good Quantum Codes with Transversal Non-Clifford Gates, in *57th Annual ACM Symposium on Theory of Computing (STOC ’24)* (2024) [arXiv:2408.09254 \[quant-ph\]](#).
  - [57] Q. T. Nguyen, Good binary quantum codes with transversal CCZ gate, in *57th Annual ACM Symposium on Theory of Computing (STOC ’25)* (2025) pp. 697–706.
  - [58] M. J. Cervia, H. Lamm, D. Liu, E. M. Muraïri, and S. Zhu, Magic State Distillation using Asymptotically Good Codes on Qudits (2025), [arXiv:2512.21874 \[quant-ph\]](#).
  - [59] C. Gidney, N. Shutty, and C. Jones, Magic state cultivation: growing T states as cheap as CNOT gates (2024), [arXiv:2409.17595 \[quant-ph\]](#).
  - [60] Y. Vakinin, S. Jacoby, A. Grimsmo, and A. Retzker, Efficient Magic State Cultivation on the Surface Code (2025), [arXiv:2502.01743 \[quant-ph\]](#).
  - [61] E. Rosenfeld *et al.*, Magic state cultivation on a superconducting quantum processor (2025), [arXiv:2512.13908 \[quant-ph\]](#).
  - [62] S. Prakash, A. Jain, B. Kapur, and S. Seth, Normal form for single-qutrit Clifford+ $T$  operators and synthesis of single-qutrit gates, *Phys. Rev. A* **98**, 032304 (2018), [arXiv:1803.03228 \[quant-ph\]](#).
  - [63] A. N. Glaudell, N. J. Ross, and J. M. Taylor, Canonical forms for single-qutrit Clifford+ $T$  operators, *Annals Phys.* **406**, 54 (2019), [arXiv:1803.05047 \[quant-ph\]](#).
  - [64] A. R. Kalra, M. Mosca, and P. Valluri, Synthesis and Arithmetic of Single Qutrit Circuits, *Quantum* **9**, 1647 (2025), [arXiv:2311.08696 \[quant-ph\]](#).