

专题2-OK6410开发板烧录

U-Boot 1.1.6 (Sep 19 2014 - 09:58:46) for SMDK6410

```
** u-boot 1.1.6          **
** Updated for OK6410 TE6410 Board **
** Version (2012-09-23)    **
** OEM: Forlinx Embedded   **
** Web: http://www.witech.com.cn **
*****
```

CPU: S3C6410 @532MHz

Fclk = 532MHz, Hclk = 133MHz, Pclk = 66MHz, Serial = CLKUART (SYNC Mode)

Board: SMDK6410

DRAM: 256 MB

Flash: 0 kB

NandFlash Information:

Nandflash:ChipType= SLC ChipName=MT29F16G08ABACAWP

No No Calc pagesize, blocksize, erasesize, use ids table

NandFlash:name=NAND 2GiB 1,8V 8-bit,id=38, pagesize=4096 ,chipsize=1024 MB,erasesize=524288 oobsize=128

NandFlash Size is 1024 MB

SD/MMC: SD 2.0 SDHC / Manufacturer: 0x27,OEM: "PH/SD32G",REV: 3.0,S/N: 26617475,DATE: 2016/8

SDHC size: 29664 MiB

Freq = 50MHz

In: serial

Out: lcd

Err: lcd

Hit any key to stop autoboot: 0

NAND erase: device 0 whole chip

Erasing at 0x3ff80000 -- 100% complete.

OK

reading u-boot.bin

212992 bytes read

NAND write: device 0 offset 0x0, size 0x200000

1032192 bytes written: OK

reading zImage

4119008 bytes read

NAND write: device 0 offset 0x500000, size 0x500000

Writing data at 0x9ff000 -- 100% complete.

5242880 bytes written: OK

reading rootfs.yaffs2

133545984 bytes read

NAND write: device 0 offset 0x1e00000, size 0x7f5c000

Writing data at 0x997f000 -- 100% complete.

133545984 bytes written: OK