

Table of Contents

1. Syntax for outer joins (Left, Right, Full).....	1
2. Queries using the altgeld_mart tables.....	3
2.1. Customers and orders.....	3
2.2. Products and orders.....	5

These are the tables we are using. Note that we have employees with no projects and a department with no employees and employees with no department.

z_em_dept	
D_ID	D_Name
100	Manufacturing
150	Accounting
200	Marketing
250	Research

z_em_emp		
E_ID	E_Name	D_ID
1	Jones	150
2	Martin	150
3	Gates	250
4	Anders	100
5	Bossy	NULL
6	Perkins	NULL

z_em_empproj	
P_ID	E_ID
ORDB-10	3
ORDB-10	5
Q4-SALES	2
Q4-SALES	4
ORDB-10	2
Q4-SALES	5

1. Syntax for outer joins (Left, Right, Full)

Outer joins can use the syntax Left Join or Right Join. A left outer join written as

```
From tblA LEFT JOIN tblB
```

will include all rows from table tblA and any matching rows from tblB. The table to the left of the phrase Left Join will have all of its rows returned.

A right outer join written as

```
From tblA RIGHT JOIN tblB
```

will include all rows from table tblB and any matching rows from tblA. The table to the right of the phrase Right Join will have all of its rows returned.

The outer joins are not symmetric.

The word OUTER is optional; you can use Left Outer Join or Left Join.

You will still need to identify the joining columns and code the join phrase.

Demo 01: All departments; employees of those departments if they exist.

```
select d_id, d_name, e_id, e_name
from z_em_dept
LEFT JOIN z_em_emp using(d_id)
order by e_id;
```

D_ID	D_NAME	E_ID	E_NAME
150	Accounting	1	Jones
150	Accounting	2	Martin
250	Research	3	Gates
100	Manufacturing	4	Anders
200	Marketing		

Demo 02: All employees; assigned departments if they exist. Outer joins are not commutative

```
select d_id, d_name, e_id, e_name
from z_em_emp
LEFT JOIN z_em_dept using(d_id)
order by e_id;
```

D_ID	D_NAME	E_ID	E_NAME
150	Accounting	1	Jones
150	Accounting	2	Martin
250	Research	3	Gates
100	Manufacturing	4	Anders
		5	Bossy
		6	Perkins

Demo 03: All employees; assigned departments if they exist.

```
select d_id, d_name, e_id, e_name
from z_em_dept
RIGHT JOIN z_em_emp using(d_id)
order by e_id;
```

D_ID	D_NAME	E_ID	E_NAME
150	Accounting	1	Jones
150	Accounting	2	Martin
250	Research	3	Gates
100	Manufacturing	4	Anders
		5	Bossy
		6	Perkins

Oracle supports the Full Outer joins which includes all rows from each table and matches where it can.

Demo 04: all employees and all departments matching employees to their departments.

```
select d_id, d_name, e_id, e_name
from z_em_dept
FULL OUTER JOIN z_em_emp using(d_id)
order by e_id;
```

D_ID	D_NAME	E_ID	E_NAME
150	Accounting	1	Jones
150	Accounting	2	Martin
250	Research	3	Gates
100	Manufacturing	4	Anders
		5	Bossy
		6	Perkins
200	Marketing		

Demo 05: Three table outer join. This is all of the departments and their employees if there are any in the department and the projects if the employees have a project.

```
select d_id, d_name, e_id, e_name, p_id
from z_em_dept
LEFT JOIN z_em_emp using(d_id)
LEFT JOIN z_em_empproj using(e_id)
order by e_id;
```

D_ID	D_NAME	E_ID	E_NAME	P_ID
150	Accounting	1	Jones	
150	Accounting	2	Martin	ORDB-10

150 Accounting	2 Martin	Q4-SALES
250 Research	3 Gates	ORDB-10
100 Manufacturing	4 Anders	Q4-SALES
200 Marketing		

Demo 06: Three table outer join. This is all of the employees and their departments if they have one and their projects if they have one

```
select e_id, e_name, d_id, d_name, p_id
from z_em_emp
LEFT JOIN z_em_dept using(d_id)
LEFT JOIN z_em_empproj using(e_id)
order by e_id;
```

E_ID	E_NAME	D_ID	D_NAME	P_ID
1	Jones	150	Accounting	
2	Martin	150	Accounting	Q4-SALES
2	Martin	150	Accounting	ORDB-10
3	Gates	250	Research	ORDB-10
4	Anders	100	Manufacturing	Q4-SALES
5	Bossy			ORDB-10
5	Bossy			Q4-SALES
6	Perkins			

Demo 07: Suppose we want to see all employees and their departments if they have one and the names of their projects if they have one. The following query does not do that. We start with an outer join but then use an inner join which eliminates employees with no projects.

```
select z_em_emp.e_id, e_name, z_em_dept.d_id, d_name, p_id
from z_em_emp
LEFT JOIN z_em_dept on z_em_dept.d_id = z_em_emp.d_id
join      z_em_empproj on z_em_emp.e_id = z_em_empproj.e_id
order by z_em_emp.e_id;
```

E_ID	E_NAME	D_ID	D_NAME	P_ID
2	Martin	150	Accounting	Q4-SALES
2	Martin	150	Accounting	ORDB-10
3	Gates	250	Research	ORDB-10
4	Anders	100	Manufacturing	Q4-SALES
5	Bossy			ORDB-10
5	Bossy			Q4-SALES

2. Queries using the altgeld_mart tables

2.1. Customers and orders

Demo 08: Customers with orders. This uses an inner join. The cust_id filter is simply to reduce the volume of output.

```
select customer_id
, customer_name_last
, order_id
from cust_customers
join oe_orderHeaders using(customer_id)
where customer_id between 404900 and 409030
order by customer_id, order_id;
```

CUSTOMER_ID	CUSTOMER_NAME_LAST	ORDER_ID
404900	Williams	520
404950	Morris	110
404950	Morris	408
404950	Morris	411
404950	Morris	535
404950	Morris	540
404950	Morris	4510
405000	Day	116
408770	Clay	405
409030	Mazur	128
409030	Mazur	130
409030	Mazur	324

Demo 09: Customers with and without orders. This uses an outer join; Customers Left Join Order Headers. That means we get customers with orders and if the customer has several orders, that customer gets multiple lines in the result set.

We also get rows for the customers in this cust_id range who have no orders and the column for their order id value is null- these customers each get one row.

```
select customer_id
, customer_name_last
, order_id
from cust_customers
LEFT JOIN oe_orderHeaders using(customer_id)
where customer_id between 404900 and 409030
order by customer_id, order_id
;
```

CUSTOMER_ID	CUSTOMER_NAME_LAST	ORDER_ID
404900	Williams	520
404950	Morris	110
404950	Morris	408
404950	Morris	411
404950	Morris	535
404950	Morris	540
404950	Morris	4510
405000	Day	116
408770	Clay	405
408777	Morise	
409010	Morris	
409020	Max	
409030	Mazur	128
409030	Mazur	130
409030	Mazur	324

Demo 10: Now consider this join. I change the join to a right join. The result set is the same as the inner join used previously. Why?

```
select customer_id
, customer_name_last
, order_id
from cust_customers
RIGHT JOIN oe_orderHeaders using(customer_id)
where customer_id between 404900 and 409030
order by customer_id, order_id
;
```

CUSTOMER_ID	CUSTOMER_NAME_LAST	ORDER_ID
404900	Williams	520
404950	Morris	110
404950	Morris	408
404950	Morris	411
404950	Morris	535
404950	Morris	540
404950	Morris	4510
405000	Day	116
408770	Clay	405
409030	Mazur	128
409030	Mazur	130
409030	Mazur	324

12 rows selected.

In our database we have a foreign key in the order headers table that refers back to the customer table and (by default) to the customer_id in the customer table.

```
create table oe_orderHeaders (
    order_id          integer not null
,   order_date       date      not null
,   cust_id          integer not null
. . .
,   constraint ord_cust_fk foreign key (customer_id) references cust_customers
. . . )
```

I also set the customer_id in the order headers table as Not null. This means that every row in the order headers table must have a value for the customer_id (it is Not null) and that customer_id in the order header must match a customer_id in the customers tables (foreign key reference) .

The outer join in this query is asking for all orders whether or not they match a customer. But our database is set up so that every order header row is matched with a customer. So it does not make sense to ask to see order headers rows that do not match a customer. In this case you should use an inner join. Using an outer join when it is logically impossible to return unmatched rows is inefficient. Someone reading your query would assume you have made a mistake someplace but they would not know what the mistake is- is the database badly designed and allows the entry of orders that do not belong to a customer (who pays for those orders?), or did you get the join order incorrect?

2.2. Products and orders

These are limited to products in the MUS category to reduce the volume of output

Demo 11: First an inner join- these show products which have been ordered- each product id must match a product id on an order detail row

```
select pr.prod_id, pr.prod_desc, pr.catg_id, od.order_id
from prd_products pr
join oe_orderDetails od on pr.prod_id = od.prod_id
where pr.catg_id in ('MUS')
order by pr.prod_id;
```

PROD_ID	PROD_DESC	CATG_ID	ORDER_ID
2014	Bix Beiderbecke - Tiger Rag	MUS	413
2014	Bix Beiderbecke - Tiger Rag	MUS	552
2014	Bix Beiderbecke - Tiger Rag	MUS	525
2014	Bix Beiderbecke - Tiger Rag	MUS	2218
2014	Bix Beiderbecke - Tiger Rag	MUS	715
2014	Bix Beiderbecke - Tiger Rag	MUS	3518
2412	David Newman - Davey Blue	MUS	525

2412	David Newman - Davey Blue	MUS	2225
2746	Charles Mingus - Blues & Politics	MUS	2218
2746	Charles Mingus - Blues & Politics	MUS	525
2747	Charles Mingus - Blues & Roots	MUS	520
2947	Ornette Coleman - Sound Grammar	MUS	525
2947	Ornette Coleman - Sound Grammar	MUS	2225
2984	John Coltrane - Lush Life	MUS	715
2984	John Coltrane - Lush Life	MUS	552
2984	John Coltrane - Lush Life	MUS	413
2984	John Coltrane - Lush Life	MUS	3518

17 rows selected.

Demo 12: How many products do we have in the MUS category?

We have 11 products; looking at the previous result set, 6 of these products were sold (Several were sold on more than one order.)

```
select pr.prod_id, pr.prod_desc, pr.catg_id
from prd_products pr
where catg_id in ('MUS')
order by pr.prod_id;
```

PROD_ID	PROD_DESC	CATG_ID
2014	Bix Beiderbecke - Tiger Rag	MUS
2234	Charles Mingus - Pithecanthropus Erectus	MUS
2337	John Coltrane - Blue Train	MUS
2412	David Newman - Davey Blue	MUS
2487	Stanley Turrentine - Don't Mess With Mr. T	MUS
2746	Charles Mingus - Blues & Politics	MUS
2747	Charles Mingus - Blues & Roots	MUS
2933	David Newman - I Remember Brother Ray	MUS
2947	Ornette Coleman - Sound Grammar	MUS
2984	John Coltrane - Lush Life	MUS
2987	Stanley Turrentine - Ballads	MUS

11 rows selected.

Demo 13: We can use an outer join to get both ordered and un-ordered products. I have highlighted the rows where the order id is null; those are the products that were never sold.

```
select pr.prod_id, prod_desc, catg_id, order_id
from prd_products pr
LEFT JOIN oe_orderDetails od on pr.prod_id = od.prod_id
where catg_id in ('MUS')
order by pr.prod_id;
```

PROD_ID	PROD_DESC	CATG_ID	ORDER_ID
2014	Bix Beiderbecke - Tiger Rag	MUS	413
2014	Bix Beiderbecke - Tiger Rag	MUS	552
2014	Bix Beiderbecke - Tiger Rag	MUS	525
2014	Bix Beiderbecke - Tiger Rag	MUS	2218
2014	Bix Beiderbecke - Tiger Rag	MUS	715
2014	Bix Beiderbecke - Tiger Rag	MUS	3518
2234	Charles Mingus - Pithecanthropus Erectus	MUS	
2337	John Coltrane - Blue Train	MUS	
2412	David Newman - Davey Blue	MUS	525
2412	David Newman - Davey Blue	MUS	2225
2487	Stanley Turrentine - Don't Mess With Mr. T	MUS	
2746	Charles Mingus - Blues & Politics	MUS	2218
2746	Charles Mingus - Blues & Politics	MUS	525
2747	Charles Mingus - Blues & Roots	MUS	520

2933 David Newman - I Remember Brother Ray	MUS	
2947 Ornette Coleman - Sound Grammar	MUS	525
2947 Ornette Coleman - Sound Grammar	MUS	2225
2984 John Coltrane - Lush Life	MUS	715
2984 John Coltrane - Lush Life	MUS	552
2984 John Coltrane - Lush Life	MUS	413
2984 John Coltrane - Lush Life	MUS	3518
2987 Stanley Turrentine - Ballads	MUS	
22 rows selected.		

Demo 14: This query gives us rows for the same products- why are we missing values in the first column which shows the product id? Every product has a product Id!

```
select od.prod_id, prod_desc, catg_id, order_id
from prd_products pr
LEFT JOIN oe_orderDetails od on pr.prod_id = od.prod_id
where catg_id in ('MUS')
order by od.prod_id;
```

PROD_ID	PROD_DESC	CATG_ID	ORDER_ID

2014	Bix Beiderbecke - Tiger Rag	MUS	3518
2014	Bix Beiderbecke - Tiger Rag	MUS	413
2014	Bix Beiderbecke - Tiger Rag	MUS	715
2014	Bix Beiderbecke - Tiger Rag	MUS	2218
2014	Bix Beiderbecke - Tiger Rag	MUS	525
2014	Bix Beiderbecke - Tiger Rag	MUS	552
2412	David Newman - Davey Blue	MUS	525
2412	David Newman - Davey Blue	MUS	2225
2746	Charles Mingus - Blues & Politics	MUS	525
2746	Charles Mingus - Blues & Politics	MUS	2218
2747	Charles Mingus - Blues & Roots	MUS	520
2947	Ornette Coleman - Sound Grammar	MUS	525
2947	Ornette Coleman - Sound Grammar	MUS	2225
2984	John Coltrane - Lush Life	MUS	3518
2984	John Coltrane - Lush Life	MUS	413
2984	John Coltrane - Lush Life	MUS	552
2984	John Coltrane - Lush Life	MUS	715
	Stanley Turrentine - Ballads	MUS	
	Charles Mingus - Pithecanthropus Erectus	MUS	
	John Coltrane - Blue Train	MUS	
	David Newman - I Remember Brother Ray	MUS	
	Stanley Turrentine - Don't Mess With Mr. T	MUS	
22 rows selected.			

What I did is switch the column alias for the first column and for the sort key to use the order details table. If I am looking for the product id in the order details table, the products which are not ordered do not have a value for that column and display as nulls.